

1 Product Introduction

The device can independently monitor and identify UAV Remote ID broadcast signals (Remote ID, abbreviated as RID), and extract and display multidimensional information in real time, including UAV serial number (SN), model, position, speed, altitude, takeoff point, and pilot location.

It can be widely used in important scenarios such as airports, high-speed railways, power parks, transportation hubs, major event security, and full-area low-altitude control, enabling detection, identification, and supervision of UAVs and pilots. The device can serve as new infrastructure to meet urban airspace management needs and support the development of the low-altitude economy.



Figure 1 UAV Remote Identification Information Monitoring Device

2 Key Features

- Target Parsing and Positioning

Supports reception of Remote ID messages and parsing of UAV ID, location, and pilot location information

- Multi-Target Detection

Detects ≥ 12 UAV targets and tracks simultaneously.

- Networked Multi-System Detection

Supports networking with spectrum, radar, and other devices, and fuses detection data.

- Multiple Transmission Methods

Supports data transmission via wired network, 4G/5G, and other methods.

- Multi-Standard Mode:

Supports UAVs compliant with the mandatory technical requirements of Safety Requirements for Civil Unmanned Aircraft Systems (GB42590-2023). Supports ASTM F3411-22a (U.S.) and ASD-STAN PrEN 4709-002 (EU) standards.

- Extended ADS-B

Supports reception and parsing of ADS-B messages, providing surrounding airspace situational awareness monitoring and collision conflict warning.

Basic Specifications	
Operating Mode	Remote ID (standard), ADS-B (extended)
Monitoring Radius	1-2 km (omnidirectional)
Refresh Rate	2-3 s/time
Multi-Target Monitoring	Number of UAVs and pilots ≥ 12 (simultaneously)
Device Dimensions	L×W×H: 321 mm × 231 mm × 126 mm (without antennas)
Device Weight	4.2 kg
Protection Rating	IP65
Operating Temperature	-40°C to +70°C

