

Redis的安装

- 1、redis官网下载最新安装包到家目录（已经下载，无需大家下载）
- 2、解压压缩包，然后会在家目录下面生成一个对应文件夹redis-6.0.8。

```
1 | tar zxvf redis-6.0.8.tar.gz
```

- 3、进入到解压后的目录redis-6.0.8，然后执行make

```
1 | cd redis-6.0.8
2 | make
3 | sudo make install
```

- 4、进入utils目录

```
1 | cd utils
```

接着进入到install_server.sh文件，注释掉下面的内容（大于在77行，有8行，shell的注释是以#进行的注释）

```
77 # _pid_1_exe="$(readlink -f /proc/1/exe)"
78 # if [ "${_pid_1_exe##*/}" = systemd ]
79 # then
80 #     echo "This systems seems to use systemd."
81 #     echo "Please take a look at the provided example service unit files in this directory, and adapt and install them. Sorry!"
82 #     exit 1
83 # fi
84 # unset _pid_1_exe
85
```

注释之后，保存退出并且执行下面命令

```
1 | sudo ./install_server.sh
```

```
wangdao@wangdao:utils$ sudo ./install_server.sh
Welcome to the redis service installer
This script will help you easily set up a running redis server

Please select the redis port for this instance: [6379]
Selecting default: 6379
Please select the redis config file name [/etc/redis/6379.conf]
Selected default - /etc/redis/6379.conf
Please select the redis log file name [/var/log/redis_6379.log]
Selected default - /var/log/redis_6379.log
Please select the data directory for this instance [/var/lib/redis/6379]
Selected default - /var/lib/redis/6379
Please select the redis executable path [/usr/local/bin/redis-server]
Selected config:
Port                : 6379
Config file         : /etc/redis/6379.conf
Log file            : /var/log/redis_6379.log
Data dir            : /var/lib/redis/6379
Executable          : /usr/local/bin/redis-server
Cli Executable      : /usr/local/bin/redis-cli
Is this ok? Then press ENTER to go on or Ctrl-C to abort.
Copied /tmp/6379.conf => /etc/init.d/redis_6379
Installing service...
Success!
Starting Redis server...
Installation successful!
wangdao@wangdao:utils$
```

5、检查redis-cli安装成功后的命令行

```
1  redis-cli
2  #显示结果如下
3  127.0.0.1:6379>
4  ping
5  #返回一个PONG
```