BT Practical 16: Create Your Own Wallet using MetaMask for Crypto Transactions

Type: No code. Practical work in MetaMask; submit screenshots plus a short write-up. *(If you already did Practical 15, reuse that wallet and start from Part B.)*

Part A: Create the wallet

1. Install MetaMask from **https://metamask.io** (Add to Chrome → Add extension → pin the fox icon).
2. Open MetaMask → **Create a new wallet** → set a password.
3. **Secure my wallet** → write down the **12-word Secret Recovery Phrase** on paper → confirm the words.
   - The phrase generates your **private key**. The private key gives the **public key**, and that gives your **address** (`0x...`).
   - Anyone with the phrase owns the wallet. Never share it.

[Screenshot] *Screenshot 1: Wallet created (Account 1, 0 ETH).*

Part B: Explore the wallet

4. Click the account name to **copy the public address**. This is what you give people so they can pay you.
5. Click ⋮ (three dots) → **Account details**. Note the address and QR code.

[Screenshot] *Screenshot 2: Account details with QR code.*

6. (Viva knowledge only) **Show private key** exists in this menu. **Do not reveal it in screenshots.**
7. Account dropdown → **Add account** → create **Account 2**. One seed phrase can hold many accounts (HD wallet).

[Screenshot] *Screenshot 3: Two accounts listed.*

Part C: Get test cryptocurrency

8. Network dropdown → enable **Show test networks** → select **Sepolia**.
9. Copy Account 1's address and get free SepoliaETH from a faucet, for example

https://cloud.google.com/application/web3/faucet/ethereum/sepolia **[Screenshot]** *Screenshot 4: Balance in Account 1.*

Part D: Do crypto transactions

10. **Send:** Account 1 → **Send** → paste Account 2's address → amount `0.002` → **Next** → check the fee → **Confirm**.

[Screenshot] *Screenshot 5: Confirmation screen.*

11. **Receive:** Switch to Account 2 and check that 0.002 SepoliaETH arrived.

[Screenshot] *Screenshot 6: Account 2 balance.*

12. **Send back:** Account 2 → Send `0.001` to Account 1.
13. **Activity tab:** Click a transaction → **View on block explorer**.

Note the **Transaction Hash**, **From**, **To**, **Value**, **Transaction Fee**, **Block** and **Status: Success**. **[Screenshot]** *Screenshot 7: Etherscan transaction page.*

Part E (optional extras)

14. **Import a token:** Tokens tab → *Import tokens* → paste a test-token contract address.
15. **Connect to a dApp:** Open https://remix.ethereum.org → Deploy tab → Environment "Injected Provider – MetaMask"

→ MetaMask asks to **Connect**. This is how the wallet talks to websites.

16. **Lock and restore:** □ → *Lock*. Then unlock with the password. (Restoring on another browser uses the seed phrase.)

Observation table

Tx	From	To	Amount	Fee (ETH)	Tx hash (first 10 chars)	Status
1	Account 1	Account 2	0.002	____	____	Success
2	Account 2	Account 1	0.001	____	____	Success

Conclusion (write this)

A non-custodial, hot wallet was created using MetaMask. The wallet stores the private key locally and signs transactions with it. Test Ether was received from a faucet and sent between two accounts, and each transaction was verified on the Sepolia block explorer using its transaction hash.