

#	Source		Pattern	
1	<pre>LeafQueue leafQueue = ...; -synchronized (leafQueue) { 57 LOC }</pre>	<pre>LeafQueue leafQueue = ...; +try { + leafQueue.getReadLock().lock(); 57 LOC +} finally { + leafQueue.getReadLock().unlock(); +}</pre>	<pre>synchronized (obj) { ... }</pre>	<pre>try { lock.lock(); ... } finally { lock.unlock(); }</pre>
2	<pre>-Lock readlock = - classLoaderContainerMapLock.readLock(); -try { - readlock.lock(); - result = classLoaderContainerMap.get(tccl); -} finally { - readlock.unlock(); -} -if (result == null) { - Lock writelock = - classLoaderContainerMapLock.writeLock(); - try { - writelock.lock(); - result = classLoaderContainerMap.get(tccl); - if (result == null) { - result = new ServerContainerImpl(); - classLoaderContainerMap.put(tccl,result); - } - } finally { - writelock.unlock(); - } -}</pre>	<pre>+synchronized (classLoaderContainerMapLock) { result = classLoaderContainerMap.get(tccl); if (result == null) { - result = new ServerContainerImpl(); - classLoaderContainerMap.put(tccl,result); } }</pre>	<pre>try { readLock.lock(); read operations } finally { readLock.unlock(); try { writeLock.lock(); write operations } finally { writeLock.unlock(); }</pre>	<pre>synchronized { all operations }</pre>
3	<pre>private static final Object lock = new Object(); private Map<...> count = new HashMap<>(); -synchronized (count) { - Pair<Job, String> key = - new ImmutablePair<>(jobID, name); - if (count.containsKey(key)) { - count.put(key, count.get(key) + 1); - } else { - count.put(key, 1); - } -}</pre>	<pre>private static final Object lock = new Object(); private Map<...> count = new HashMap<>(); +synchronized(lock) + if (!jobCounts.containsKey(jobID)) { + jobCounts.put(jobID, new HashMap<>()); + } + Map<String, Integer> count = + jobCounts.get(jobID); + if (count.containsKey(name)) { + count.put(name, count.get(name) + 1); + } else { + count.put(name, 1); + } +}</pre>	<pre>synchronized (obj1) { ... }</pre>	<pre>synchronized (obj2) { ... }</pre>
4	<pre>-public synchronized void reset() { map.clear(); members = EMPTY_MEMBERS; }</pre>	<pre>+private final Object membersLock = new + Object(); +public void reset() { + synchronized (membersLock) { + map.clear(); + members = EMPTY_MEMBERS; + } +}</pre>	<pre>synchronized void foo() { ... }</pre>	<pre>void foo() { synchronized (obj) { ... } }</pre>
5	<pre>-public boolean isAccessed() { - return this.accessed; -}</pre>	<pre>+public synchronized boolean isAccessed() { - return this.accessed; +}</pre>	<pre>void foo() { ... }</pre>	<pre>synchronized void foo() { ... }</pre>
6	<pre>-synchronized (this.channelLookup) { - try{ - lookupResponse = AkkaUtils. <JobManagerMessages.ConnectionInformation>ask(c hannelLookup, new JobManagerMessages.LookupConnectionInformation(connectionInfo, jobID, sourceChannelID), timeout).response(); - }catch(IOException ioe) { - throw ioe; - } -}</pre>	<pre>lookupResponse = AkkaUtils. <JobManagerMessages.ConnectionInformation>ask(c hannelLookup, new JobManagerMessages.LookupConnectionInformation(connectionInfo, jobID, sourceChannelID), timeout).response();</pre>	<pre>synchronized (obj) { ... }</pre>	<pre>...</pre>