                        Definitions of Managed Objects
                          for the DS1 Interface Type

Status of this Memo

   This memo defines objects for managing DS1 Interface objects for use
   with the SNMP protocol. This memo is a product of the Transmission
   MIB Working Group of the Internet Engineering Task Force (IETF).
   This RFC specifies an IAB standards track protocol for the Internet
   community, and requests discussion and suggestions for improvements.
   Please refer to the current edition of the "IAB Official Protocol
   Standards" for the standardization state and status of this protocol.
   Distribution of this memo is unlimited.

Table of Contents

1. Abstract

   This memo defines an experimental portion of the Management
   Information Base (MIB) for use with network management protocols in
   TCP/IP-based internets. In particular, this memo defines MIB objects

for representing DS1 physical interfaces. Implementors should
consult in addition to this memo the companion document that
describes that DS3 managed objects.

2. The Network Management Framework

The Internet-standard Network Management Framework consists of three
components. They are:

RFC 1155 which defines the SMI, the mechanisms used for describing
and naming objects for the purpose of management. RFC 1212
defines a more concise description mechanism, which is wholly
consistent with the SMI.

RFC 1156 which defines MIB-I, the core set of managed objects for
the Internet suite of protocols. RFC 1213, defines MIB-II, an
evolution of MIB-I based on implementation experience and new
operational requirements.

RFC 1157 which defines the SNMP, the protocol used for network
access to managed objects.

The Framework permits new objects to be defined for the purpose of
experimentation and evaluation.

3. Objects

Managed objects are accessed via a virtual information store, termed
the Management Information Base or MIB. Objects in the MIB are
defined using the subset of Abstract Syntax Notation One (ASN.1) [7]
defined in the SMI. In particular, each object has a name, a syntax,
and an encoding. The name is an object identifier, an
administratively assigned name, which specifies an object type. The
object type together with an object instance serves to uniquely
identify a specific instantiation of the object. For human
convenience, we often use a textual string, termed the OBJECT
DESCRIPTOR, to also refer to the object type.

The syntax of an object type defines the abstract data structure
corresponding to that object type. The ASN.1 language is used for
this purpose. However, the SMI [3] purposely restricts the ASN.1
constructs which may be used. These restrictions are explicitly made
for simplicity.

The encoding of an object type is simply how that object type is
represented using the object type's syntax. Implicitly tied to the
notion of an object type's syntax and encoding is how the object type
is represented when being transmitted on the network.

The SMI specifies the use of the basic encoding rules of ASN.1 [8], subject to the additional requirements imposed by the SNMP.

3.1. Format of Definitions

Section 5 contains contains the specification of all object types contained in this MIB module. The object types are defined using the conventions defined in the SMI, as amended by the extensions specified in [13].

4. Overview

These objects are used when the particular media being used to realize an interface is a DS1 physical interface. At present, this applies to these values of the ifType variable in the Internet-standard MIB:

                ds1 (18)
                e1 (19)

The definitions contained herein are based on the AT&T T-1 specifications and Extended Superframe (ESF) format [9, 10], the latter of which conforms to proposed ANSI specifications [14, 15]. The various T1 and E1 line disciplines are similar enough that separate MIBs are unwarranted, although there are some differences. For example, Loss of Frame is defined more rigorously in the ESF specification than in the D4 specification, but it is defined in both.

4.1. Binding between Interfaces and CSUs

It should be noted that it is possible to multiplex multiple bit streams onto a single DS1 physical interface (CSU), realizing multiple interfaces from the perspective of the Internet-standard MIB. It is also possible to concatenate physical interfaces to provide a single logical interface. As such, it is important to be able to distinguish between the indices used to identify the CSUs attached to a node and the indices used to identify an interface (in the MIB sense) attached to a node.

Each agent which resides on a host which uses DS1 physical interfaces is required to assign a small, positive integer uniquely to each CSU. This is known as the "CSUIndex", and is used to distinguish between different CSUs attached to a node. The CSUIndex is also used as the "key" when accessing tabular information about DS1 physical interfaces.

The potentially many-to-one binding between CSU indices and the

   ifIndex value assigned to each MIB interface are defined in the
   ds1ConfigTable table defined in the next section.

4.2. Objectives of this MIB Module

   There are numerous things that could be included in a MIB for DS1
   Interfaces: the management of multiplexors, CSUs, DSUs, and the like.
   The intent of this document is to facilitate the common management of
   CSUs, both in-chassis and external via proxy. As such, a design
   decision was made up front to very closely align the MIB with the set
   of objects that can generally be read from CSUs that are currently
   deployed, which is to say ESF CSUs conforming to AT&T specifications.
   However, by simple generalization of these objects, the MIB is also
   made applicable to D4 and G.704 devices.

   To meet a requirement not easily satisfied in other places, there is
   one additional group present, the Fractional DS1 group. This is
   intended to facilitate the use of fractional DS1 devices (i.e.,
   devices which utilize a subset of the 8 bit channels available in the
   frame) over the managed CSUs.

4.3. DS1 Terminology

   The terminology used in this document to describe error conditions on
   a T1 or E1 circuit monitored by a CSU are from references [10], [11],
   [14], and [15].

           Out of Frame event
                 An Out of Frame event is declared when the receiver
                 detects two or more framing-bit errors within a 3
                 millisecond period, or two or more errors out of five or
                 less consecutive framing-bits. At this time, the framer
                 enters the Out of Frame State, and starts searching for a
                 correct framing pattern. The Out of Frame state ends
                 when reframe occurs.

           Loss of Signal
                 This event is declared upon observing 175 +/- 75
                 contiguous pulse positions with no pulses of either
                 positive or negative polarity (also called keep alive).

           Code Violation Error Event
                 A Code Violation Error Event is the occurrence of a
                 received Cyclic Redundancy Check code that is not
                 identical to the corresponding locally-calculated code.

           Bipolar Violation
                 A Bipolar Violation, for B8ZS-coded signals, is the

occurrence of a received bipolar violation that is not
part of a zero-substitution code. It also includes other
error patterns such as: eight or more consecutive zeros
and incorrect parity.

Errored Seconds
     An Errored Second is a second with one or more Code
     Violation Error Events OR one or more Out of Frame
     events. In D4 and G.704 section 2.1.3.2 (eg, G.704 which
     does not implement the CRC), the presence of Bipolar
     Violations also triggers an Errored Second.

Severely Errored Seconds
     A Severely Errored Second is a second with 320 or more
     Code Violation Error Events OR one or more Out of Frame
     events.

Severely Errored Framing Second
     An Severely Errored Framing Second is a second with one
     or more Out of Frame events.

Unavailable Signal State
     This state is declared at the onset of 10 consecutive
     Severely Errored Seconds. It is cleared at the onset of
     10 consecutive seconds with no Severely Errored Second.

Unavailable Seconds
     Unavailable Seconds are calculated by counting the number
     of seconds that the CSU is in the Unavailable Signal
     State, including the initial 10 seconds to enter the
     state but not including the 10 seconds to exit the state.

     Note that any second that may be counted as an
     Unavailable Second may not be counted as an Errored
     Second, a Severely Errored Second. Since the 10 Severely
     Errored Seconds that comprise the transition from the
     available to Unavailable Signal State may also be counted
     as Errored Seconds, and Severely Errored Seconds previous
     to entering the state, these three counters are adjusted
     so that any second counted during this transition is then
     subtracted. The 10 seconds in the transition from
     unavailable to available may be counted as Errored
     Seconds.

     A special case exists when the 10 or more second period
     crosses the 900 second statistics window boundary, as the
     foregoing description implies that the Severely Errored
     Second and Unavailable Second counters must be adjusted

            when the Unavailable Signal State is entered. Clearly,
            successive GETs of the affected ds1IntervalSES and
            ds1IntervalUAS objects will return differing values if
            the first GET occurs during the first few seconds of the
            window. This is viewed as an unavoidable side-effect of
            selecting the presently deployed AT&T objects as a basis
            for this memo.

      Yellow Alarm
            A Yellow Alarm is declared because of an incoming Yellow
            Signal from the far-end. In effect, the circuit is
            declared to be a one way link.

      Red Alarm
            A Red Alarm is declared because of an incoming Loss of
            Signal, Loss of Framing, Alarm Indication Signal. After
            a Red Alarm is declared, the device sends a Yellow Signal
            to the far-end. The far-end, when receives the Yellow
            Signal, declares a Yellow Alarm.

      Circuit Identifier
            This is a character string specified by the circuit
            vendor, and is useful when communicating with the vendor
            during the troubleshooting process.

5. Definitions

      RFC1232-MIB DEFINITIONS ::= BEGIN

      IMPORTS
            experimental, Counter
                  FROM RFC1155-SMI
            DisplayString
                  FROM RFC1158-MIB
            OBJECT-TYPE
                  FROM RFC-1212;

      -- This MIB module uses the extended OBJECT-TYPE macro as
      -- defined in [13].

      -- this is the MIB module for ds1 objects

      ds1 OBJECT IDENTIFIER ::= { experimental 2 }

      -- the DS1 Configuration group

```
        -- Although the objects in this group are read-only, at the
        -- agent's discretion they may be made read-write so that the
        -- management station, when appropriately authorized, may
        -- change the behavior of the CSU, e.g., to place the device
        -- into a loopback state or emit a QRSS BER test.

        -- Implementation of this group is mandatory for all systems
        -- that attach to a ds1.

        ds1ConfigTable OBJECT-TYPE
            SYNTAX  SEQUENCE OF DS1ConfigEntry
            ACCESS  not-accessible
            STATUS  mandatory
            DESCRIPTION
                    "The DS1 Configuration table."
            ::= { ds1 1 }

        ds1ConfigEntry OBJECT-TYPE
            SYNTAX  DS1ConfigEntry
            ACCESS  not-accessible
            STATUS  mandatory
            DESCRIPTION
                    "An entry in the DS1 Configuration table."
            INDEX   { ds1CSUIndex }
            ::= { ds1ConfigTable 1 }

        DS1ConfigEntry ::=
            SEQUENCE {
                ds1CSUIndex
                    INTEGER,
                ds1Index
                    INTEGER,
                ds1TimeElapsed
                    INTEGER (1..900),
                ds1ValidIntervals
                    INTEGER (0..96),
                ds1LineType
                    INTEGER,
                ds1ZeroCoding
                    INTEGER,
                ds1Loopback
                    INTEGER,
                ds1SendCode
                    INTEGER,
                ds1YellowAlarm
                    INTEGER,
                ds1RedAlarm
                    INTEGER,
```

```
            ds1CircuitIdentifier
                DisplayString (SIZE (0..255))
        }

        ds1CSUIndex OBJECT-TYPE
            SYNTAX  INTEGER
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The index value which uniquely identifies the CSU
                    to which this entry is applicable."
            ::= { ds1ConfigEntry 1 }

        ds1Index OBJECT-TYPE
            SYNTAX  INTEGER
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "An index value that uniquely identifies an
                    interface to a ds1.  The interface identified by a
                    particular value of this index is the same
                    interface as identified by the same value an
                    ifIndex object instance."
            ::= { ds1ConfigEntry 2 }

        ds1TimeElapsed OBJECT-TYPE
            SYNTAX  INTEGER (1..900)
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The number of seconds that have elapsed since the
                    beginning of the current error-measurement period.
                    Any fraction is rounded up."
            ::= { ds1ConfigEntry 3 }

        ds1ValidIntervals OBJECT-TYPE
            SYNTAX  INTEGER (0..96)
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The number of previous intervals for which valid
                    data was collected.  The value will be 96 unless
                    the CSU device was brought online within the last
                    24 hours, in which case the value will be the
                    number of complete 15 minute intervals the CSU has
                    been online."
            ::= { ds1ConfigEntry 4 }
```

```
        ds1LineType OBJECT-TYPE
            SYNTAX  INTEGER {
                    other(1),
                    ds1ESF(2),
                    ds1D4(3),
                    ds1ANSI-ESF(4),
                    ds1G704(5),
                    ds1G704-CRC(6)
                }
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "This variable indicates the variety of DS1 Line
                    implementing this circuit.  The type of circuit
                    affects the number of bits per second that the
                    circuit can reasonably carry, as well as the
                    interpretation of the usage and error statistics.

                    The values, in sequence, describe:
                    TITLE:        SPECIFICATION:
                    ds1ESF        AT&T Extended SuperFrame DS1 [10]
                    ds1D4         AT&T D4 format DS1 [16], [17]
                    ds1ANSI-ESF   ANSI Extended SuperFrame format [14]
                    ds1G704       CCITT Recommendation G.704 [12]
                                     (section 2.1.3.2)
                    ds1G704-CRC   CCITT Recommendation G.704 [12]
                                     (section 2.1.3.1)
                    "
            ::= { ds1ConfigEntry 5 }

        ds1ZeroCoding OBJECT-TYPE
            SYNTAX  INTEGER {
                    ds1JammedBit(1),
                    ds1B8ZS(2),
                    ds1InvertedHDLC(3),
                    ds1HDB3(4),
                    ds1ZBTSI(5)
                }
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "This variable describes the variety of Zero Code
                    Suppression used on the link, which in turn
                    affects a number of its characteristics.

                    ds1JammedBit refers the Jammed bit Zero Encoding,
                    in which the AT&T specification of at least one
                    pulse every 8 bit periods is literally implemented
```

by forcing a pulse in bit 8 of each channel.
Thus, only seven bits per channel, or 1.344 Mbps,
is available for data.

ds1B8ZS refers to the use of a specified pattern
of normal bits and bipolar violations which are
used to replace a sequence of eight zero bits (see
[14]). In this context, all eight bits in a
channel are technically available for data, but
care must be taken with D4 encoded data to avoid
having HDLC Flag streams imitate spurious Yellow
Alarm conditions. Typically, one bit per frame is
ignored to force flag streams to rotate, thereby
avoiding this error type. CCITT Recommendation
G.703 [11] may be referred to for further
definition of these.

ds1InvertedHDLC refers to the practice, common on
HDLC encoded DS1 data links, of inverting the data
between the serial interface chip and the CSU.
Since HDLC guarantees one zero every 6 bits in the
worst case, while the standards call for (in
effect) at least one pulse every eight, inverted
HDLC enjoys 4/24 one's density on the line, which
may improve the effective clock stability of a DS1
line. As with B8ZS, all eight bits in a channel
are technically available for data, but care must
be taken with D4 encoded data to avoid having HDLC
Flag streams imitate spurious Yellow Alarm
conditions. Typically, one bit per frame is
ignored to force flag streams to rotate, thereby
avoiding this error type.

ANSI Clear Channels may use ds1ZBTSI, or Zero Byte
Time Slot Interchange (see [14]).

G.704 links, with or without CRC, use ds1HDB3 (see
[11]). "
    ::= { ds1ConfigEntry 6 }

ds1Loopback OBJECT-TYPE
    SYNTAX INTEGER {
            ds1NoLoop(1),
            ds1LocalLoopbackLocalSide(2),
            ds1LocalLoopbackRemoteSide(3),
            ds1RemoteLoopbackLocalSide(4),
            ds1RemoteLoopbackRemoteSide(5)
            }

```
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "This variable represents the loopback state of
                    the CSU.  Devices supporting read/write access
                    should return badValue in response to a requested
                    loopback state that the CSU does not support.  The
                    values mean:

                    ds1NoLoop

                       Not in the loopback state.  A device that is
                       not capable of performing a loopback on either
                       interface shall always return this as it's
                       value.

                    ds1LocalLoopbackLocalSide

                       Signal received from the local side of the
                       device is looped back at the local connector
                       (eg, without involving the CSU).

                    ds1LocalLoopbackRemoteSide

                       Signal received from the local side of the
                       device is looped back at the remote connector
                       (eg, through the CSU).

                    ds1RemoteLoopbackLocalSide

                       Signal received from the remote side of the
                       device is looped back at the local connector
                       (eg, through the CSU).

                    ds1RemoteLoopbackRemoteSide

                       Signal received from the remote side of the
                       device is looped back at the remote connector
                       (eg, without involving the CSU)."
            ::= { ds1ConfigEntry 7 }

        ds1SendCode OBJECT-TYPE
            SYNTAX  INTEGER {
                     ds1OtherTest(1),
                     ds1SendNoCode(2),
                     ds1SendSetCode(3),
                     ds1SendResetCode(4),
                     ds1SendQRSS(5)
```

```
                }
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
           "This variable indicates what type of code is
           being sent across the DS1 circuit by the CSU.  The
           values mean:

           ds1SendNoCode    sending looped or normal data
           ds1SendSetCode    sending a loopback request
           ds1SendResetCode sending a loopback termination request
           ds1SendQRSS       sending the BERT pattern described in
                             ANSI T1.403-1989 section 5.6
           ds1OtherTest      sending a different BERT/BLERT pattern,
                             such as all zeroes, all ones, etc."
        ::= { ds1ConfigEntry 8 }

    ds1YellowAlarm OBJECT-TYPE
        SYNTAX  INTEGER {
                   ds1NoYellowAlarm (1),
                   ds1YellowAlarm (2)
                }
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
                "This variable indicates if a Yellow Alarm
                condition exists.

                Note that G.704 interfaces do not support Yellow
                Alarms.  Accordingly, such agents should return
                the value ds1NoYellowAlarm."
        ::= { ds1ConfigEntry 9 }

    ds1RedAlarm OBJECT-TYPE
        SYNTAX  INTEGER {
                   ds1NoRedAlarm (1),
                   ds1RedAlarm (2)
                }
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
                "This variable indicates if a Red Alarm condition
                exists.

                Note that G.704 interfaces do not support Red
                Alarms.  Accordingly, such agents should return
                the value ds1NoRedAlarm."
        ::= { ds1ConfigEntry 10 }
```

```
        ds1CircuitIdentifier OBJECT-TYPE
            SYNTAX  DisplayString (SIZE (0..255))
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "This variable contains the transmission vendor's
                    circuit identifier, for the purpose of
                    facilitating troubleshooting."
            ::= { ds1ConfigEntry 11 }


        -- the DS1 Interval group

        -- Implementation of this group is mandatory for all systems
        -- that attach to a ds1.

        -- It is recognized that some currently deployed CSUs do not
        -- record the entire set of statistics specified in this
        -- group.  Accordingly, some agents queried for these objects
        -- may treat these objects as having an ACCESS clause value
        -- of not-accessible.

        -- The DS1 Interval Table contains various statistics
        -- collected by each CSU over the previous 24 hours of
        -- operation.  The past 24 hours are broken into 96 completed
        -- 15 minute intervals.

        ds1IntervalTable OBJECT-TYPE
            SYNTAX  SEQUENCE OF DS1IntervalEntry
            ACCESS  not-accessible
            STATUS  mandatory
            DESCRIPTION
                    "The DS1 Interval table."
            ::= { ds1 2 }

        ds1IntervalEntry OBJECT-TYPE
            SYNTAX  DS1IntervalEntry
            ACCESS  not-accessible
            STATUS  mandatory
            DESCRIPTION
                    "An entry in the DS1 Interval table."
            INDEX   { ds1IntervalIndex, ds1IntervalNumber }
            ::= { ds1IntervalTable 1 }

        DS1IntervalEntry ::=
            SEQUENCE {
                ds1IntervalIndex
                    INTEGER,
```

```
                ds1IntervalNumber
                    INTEGER (1..96),
                ds1IntervalESs
                    Counter,
                ds1IntervalSESs
                    Counter,
                ds1IntervalSEFSs
                    Counter,
                ds1IntervalUASs
                    Counter,
                ds1IntervalCSSs
                    Counter,
                ds1IntervalBPVs
                    Counter,
                ds1IntervalCVs
                    Counter
            }

        ds1IntervalIndex OBJECT-TYPE
            SYNTAX  INTEGER
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The index value which uniquely identifies the CSU
                    to which this entry is applicable.  The interface
                    identified by a particular value of this index is
                    the same interface as identified by the same value
                    an ds1CSUIndex object instance."
            ::= { ds1IntervalEntry 1 }

        ds1IntervalNumber OBJECT-TYPE
            SYNTAX  INTEGER (1..96)
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "A number between 1 and 96, where 1 is the most
                    recently completed 15 minute interval and 96 is
                    the least recently completed 15 minute interval
                    (assuming that all 96 intervals are valid)."
            ::= { ds1IntervalEntry 2 }

        ds1IntervalESs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of Errored
                    Seconds, as defined by ANSI Draft Standard
```

```
                    T1M1.3/90 - 027R2[15], encountered by a DS1 CSU
                    during one of the previous 96 fifteen minute
                    intervals."
                ::= { ds1IntervalEntry 3 }

        ds1IntervalSESs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of
                    Severely Errored Seconds, as defined by ANSI Draft
                    Standard T1M1.3/90 - 027R2[15], encountered by a
                    DS1 CSU during one of the previous 96 fifteen
                    minute intervals."
                ::= { ds1IntervalEntry 4 }

        ds1IntervalSEFSs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of
                    Severely Errored Framing Seconds, as defined by
                    ANSI Draft Standard T1M1.3/90 - 027R2[15],
                    encountered by a DS1 CSU during one of the
                    previous 96 fifteen minute intervals."
                ::= { ds1IntervalEntry 5 }

        ds1IntervalUASs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of
                    Unavailable Seconds, as defined by ANSI Draft
                    Standard T1M1.3/90 - 027R2[15], encountered by a
                    DS1 CSU during one of the previous 96 fifteen
                    minute intervals."
                ::= { ds1IntervalEntry 6 }

        ds1IntervalCSSs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of
                    Controlled Slip Seconds, as defined by ANSI Draft
```

```
                   Standard T1M1.3/90 - 027R2[15], encountered by a
                   DS1 CSU during one of the previous 96 fifteen
                   minute intervals."
            ::= { ds1IntervalEntry 7 }

        ds1IntervalBPVs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                   "The counter associated with the number of Bipolar
                   Violations, as defined by ANSI Draft Standard
                   T1M1.3/90 - 027R2[15], encountered by a DS1 CSU
                   during one of the previous 96 fifteen minute
                   intervals."
            ::= { ds1IntervalEntry 8 }

        ds1IntervalCVs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                   "The counter associated with the number of Code
                   Violation Error Events, as defined by ANSI Draft
                   Standard T1M1.3/90 - 027R2[15], encountered by a
                   DS1 CSU during one of the previous 96 fifteen
                   minute intervals.

                   Note that D4 and G.704 (section 2.1.3.2)
                   interfaces do not support Code Violation Error
                   Events.  Accordingly, such agents may treat this
                   object as having an ACCESS clause value of not-
                   accessible."
             ::= { ds1IntervalEntry 9 }


        -- the DS1 Current group

        -- Implementation of this group is mandatory for all systems
        -- that attach to a ds1.

        -- It is recognized that some currently deployed CSUs do not
        -- record the entire set of statistics specified in this
        -- group.  Accordingly, some agents queried for these objects
        -- may treat these objects as having an ACCESS clause value
        -- of not-accessible.

        -- The DS1 current table contains various statistics being
```

```
        -- collected for the current 15 minute interval.

        ds1CurrentTable OBJECT-TYPE
            SYNTAX   SEQUENCE OF DS1CurrentEntry
            ACCESS   not-accessible
            STATUS   mandatory
            DESCRIPTION
                    "The DS1 Current table."
            ::= { ds1 3 }

        ds1CurrentEntry OBJECT-TYPE
            SYNTAX   DS1CurrentEntry
            ACCESS   not-accessible
            STATUS   mandatory
            DESCRIPTION
                    "An entry in the DS1 Current table."
            INDEX   { ds1CurrentIndex }
            ::= { ds1CurrentTable 1 }

        DS1CurrentEntry ::=
            SEQUENCE {
                ds1CurrentIndex
                    INTEGER,
                ds1CurrentESs
                    Counter,
                ds1CurrentSESs
                    Counter,
                ds1CurrentSEFSs
                    Counter,
                ds1CurrentUASs
                    Counter,
                ds1CurrentCSSs
                    Counter,
                ds1CurrentBPVs
                    Counter,
                ds1CurrentCVs
                    Counter
            }

        ds1CurrentIndex OBJECT-TYPE
            SYNTAX   INTEGER
            ACCESS   read-only
            STATUS   mandatory
            DESCRIPTION
                    "The index value which uniquely identifies the CSU
                    to which this entry is applicable.  The interface
                    identified by a particular value of this index is
                    the same interface as identified by the same value
```

```
                 an ds1CSUIndex object instance."
            ::= { ds1CurrentEntry 1 }

        ds1CurrentESs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of Errored
                    Seconds, as defined by ANSI Draft Standard
                    T1M1.3/90 - 027R2[15], encountered by a DS1 CSU in
                    the current 15 minute interval."
            ::= { ds1CurrentEntry 2 }

        ds1CurrentSESs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of
                    Severely Errored Seconds, as defined by ANSI Draft
                    Standard T1M1.3/90 - 027R2[15], encountered by a
                    DS1 CSU in the current 15 minute interval."
            ::= { ds1CurrentEntry 3 }

        ds1CurrentSEFSs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of
                    Severely Errored Framing Seconds, as defined by
                    ANSI Draft Standard T1M1.3/90 - 027R2[15],
                    encountered by a DS1 CSU in the current 15 minute
                    interval."
            ::= { ds1CurrentEntry 4 }

        ds1CurrentUASs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of
                    Unavailable Seconds, as defined by ANSI Draft
                    Standard T1M1.3/90 - 027R2[15], encountered by a
                    DS1 CSU in the current 15 minute interval."
            ::= { ds1CurrentEntry 5 }
```

```
        ds1CurrentCSSs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of
                    Controlled Slip Seconds, as defined by ANSI Draft
                    Standard T1M1.3/90 - 027R2[15], encountered by a
                    DS1 CSU in the current 15 minute interval."
            ::= { ds1CurrentEntry 6 }

        ds1CurrentBPVs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of Bipolar
                    Violations, as defined by ANSI Draft Standard
                    T1M1.3/90 - 027R2[15], encountered by a DS1 CSU in
                    the current 15 minute interval."
            ::= { ds1CurrentEntry 7 }

        ds1CurrentCVs OBJECT-TYPE
            SYNTAX  Counter
            ACCESS  read-only
            STATUS  mandatory
            DESCRIPTION
                    "The counter associated with the number of Code
                    Violation Error Events, as defined by ANSI Draft
                    Standard T1M1.3/90 - 027R2[15], encountered by a
                    DS1 CSU in the current 15 minute interval.

                    Note that D4 and G.704 (section 2.1.3.2)
                    interfaces do not support Code Violation Error
                    Events.  Accordingly, such agents may treat this
                    object as having an ACCESS clause value of not-
                    accessible."
            ::= { ds1CurrentEntry 8 }


    -- the DS1 Total group

    -- Implementation of this group is mandatory for all systems
    -- that attach to a ds1.

    -- It is recognized that some currently deployed CSUs do not
    -- record the entire set of statistics specified in this
    -- group.  Accordingly, some agents queried for these objects
```

```
        -- may treat these objects as having an ACCESS clause value
        -- of not-accessible.

        -- The DS1 Total Table contains the cumulative sum of the
        -- various statistics for the 24 hour interval preceding the
        -- first valid interval in the ds1CurrentTable.

        ds1TotalTable OBJECT-TYPE
            SYNTAX  SEQUENCE OF DS1TotalEntry
            ACCESS  not-accessible
            STATUS  mandatory
            DESCRIPTION
                    "The DS1 Total table.  24 hour interval."
            ::= { ds1 4 }

        ds1TotalEntry OBJECT-TYPE
            SYNTAX  DS1TotalEntry
            ACCESS  not-accessible
            STATUS  mandatory
            DESCRIPTION
                    "An entry in the DS1 Total table."
            INDEX   { ds1TotalIndex }
            ::= { ds1TotalTable 1 }

        DS1TotalEntry ::=
            SEQUENCE {
                ds1TotalIndex
                    INTEGER,
                ds1TotalESs
                    Counter,
                ds1TotalSESs
                    Counter,
                ds1TotalSEFSs
                    Counter,
                ds1TotalUASs
                    Counter,
                ds1TotalCSSs
                    Counter,
                ds1TotalBPVs
                    Counter,
                ds1TotalCVs
                    Counter
            }

        ds1TotalIndex OBJECT-TYPE
            SYNTAX  INTEGER
            ACCESS  read-only
            STATUS  mandatory
```

```
     DESCRIPTION
             "The index value which uniquely identifies the CSU
             to which this entry is applicable.  The interface
             identified by a particular value of this index is
             the same interface as identified by the same value
             an ds1CSUIndex object instance."
     ::= { ds1TotalEntry 1 }

ds1TotalESs OBJECT-TYPE
     SYNTAX  Counter
     ACCESS  read-only
     STATUS  mandatory
     DESCRIPTION
             "The counter associated with the number of Errored
             Seconds, as defined by ANSI Draft Standard
             T1M1.3/90 - 027R2[15], encountered by a DS1 CSU in
             the previous 24 hour interval"
     ::= { ds1TotalEntry 2 }

ds1TotalSESs OBJECT-TYPE
     SYNTAX  Counter
     ACCESS  read-only
     STATUS  mandatory
     DESCRIPTION
             "The counter associated with the number of
             Severely Errored Seconds, as defined by ANSI Draft
             Standard T1M1.3/90 - 027R2[15], encountered by a
             DS1 CSU in the previous 24 hour interval."
     ::= { ds1TotalEntry 3 }

ds1TotalSEFSs OBJECT-TYPE
     SYNTAX  Counter
     ACCESS  read-only
     STATUS  mandatory
     DESCRIPTION
             "The counter associated with the number of
             Severely Errored Framing Seconds, as defined by
             ANSI Draft Standard T1M1.3/90 - 027R2[15],
             encountered by a DS1 CSU in the previous 24 hour
             interval."
     ::= { ds1TotalEntry 4 }

ds1TotalUASs OBJECT-TYPE
     SYNTAX  Counter
     ACCESS  read-only
     STATUS  mandatory
     DESCRIPTION
             "The counter associated with the number of
```

```
                 Unavailable Seconds, as defined by ANSI Draft
                 Standard T1M1.3/90 - 027R2[15], encountered by a
                 DS1 CSU in the previous 24 hour interval."
         ::= { ds1TotalEntry 5 }

     ds1TotalCSSs OBJECT-TYPE
         SYNTAX  Counter
         ACCESS  read-only
         STATUS  mandatory
         DESCRIPTION
                 "The counter associated with the number of
                 Controlled Slip Seconds, as defined by ANSI Draft
                 Standard T1M1.3/90 - 027R2[15], encountered by a
                 DS1 CSU in the previous 24 hour interval."
         ::= { ds1TotalEntry 6 }

     ds1TotalBPVs OBJECT-TYPE
         SYNTAX  Counter
         ACCESS  read-only
         STATUS  mandatory
         DESCRIPTION
                 "The counter associated with the number of Bipolar
                 Violations, as defined by ANSI Draft Standard
                 T1M1.3/90 - 027R2[15], encountered by a DS1 CSU in
                 the previous 24 hour interval."
         ::= { ds1TotalEntry 7 }

     ds1TotalCVs OBJECT-TYPE
         SYNTAX  Counter
         ACCESS  read-only
         STATUS  mandatory
         DESCRIPTION
                 "The counter associated with the number of Code
                 Violation Error Events, as defined by ANSI Draft
                 Standard T1M1.3/90 - 027R2[15], encountered by a
                 DS1 CSU in the previous 24 hour interval.

                 Note that D4 and G.704 (section 2.1.3.2)
                 interfaces do not support Code Violation Error
                 Events.  Accordingly, such agents may treat this
                 object as having an ACCESS clause value of not-
                 accessible."
         ::= { ds1TotalEntry 8 }


     -- the DS1 Fractional group

     -- Implementation of this group is mandatory for those
```

```
            -- systems utilizing a fractional DS1 capability


            -- The DS1 fractional table contains identifies which DS1
            -- channels associated with a CSU are being used to support a
            -- logical interface, i.e., an entry in the interfaces table
            -- from the Internet-standard MIB.  For Clear Channel
            -- implementations, exactly one ifTable entry corresponds to
            -- the CSU being managed.  In this very typical case, the
            -- variable ds1Index indicates the value of ifIndex which
            -- corresponds to the interface being supported by a
            -- particular CSU.

            -- However, for fractional DS1 implementations, the
            -- correspondent value of ds1Index is 0, and for each DS1
            -- channel supporting a logical interface, there is an entry
            -- in the DS1 fractional table which names a value for
            -- ifIndex.
            --
            --      For ds1ESF, ds1D4, and ds1ANSI-ESF, there are 24 legal
            --      channels, numbered 1 through 24.
            --
            --      For G.704, there are 32 legal channels, numbered 1
            --      through 32.  ds1G704 can carry user data in channels 2
            --      through 32, channel 1 being an overhead channel.
            --      ds1G704-CRC can carry user data in channels 2 through
            --      16 and 18 through 32, channels 1 and 17 being overhead
            --      channels.

            ds1FracTable OBJECT-TYPE
                SYNTAX   SEQUENCE OF DS1FracEntry
                ACCESS   not-accessible
                STATUS   mandatory
                DESCRIPTION
                        "The DS1 Fractional table."
                ::= { ds1 5 }

            ds1FracEntry OBJECT-TYPE
                SYNTAX   DS1FracEntry
                ACCESS   not-accessible
                STATUS   mandatory
                DESCRIPTION
                        "An entry in the DS1 Fractional table."
                INDEX    { ds1FracIndex, ds1FracNumber }
                ::= { ds1FracTable 1 }

            DS1FracEntry ::=
                SEQUENCE {
```

```
            ds1FracIndex
                INTEGER,
            ds1FracNumber
                INTEGER (1..32),
            ds1FracIfIndex
                INTEGER
        }

    ds1FracIndex OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
                "The index value which uniquely identifies the CSU
                to which this entry is applicable.  The interface
                identified by a particular value of this index is
                the same interface as identified by the same value
                an ds1CSUIndex object instance."
        ::= { ds1FracEntry 1 }

    ds1FracNumber OBJECT-TYPE
        SYNTAX  INTEGER (1..32)
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
                "The channel number for this entry."
        ::= { ds1FracEntry 2 }

    ds1FracIfIndex OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
                "An index value that uniquely identifies an
                interface to a ds1.  The interface identified by a
                particular value of this index is the same
                interface as identified by the same value an
                ifIndex object instance."
        ::= { ds1FracEntry 3 }

        END
```

6. Acknowledgements

   This document was produced by the SNMP and the Transmission MIB
   Working Groups:

                L. Michael Sabo, NCSC
                Jon Saperia, DEC
                John Seligson
                Fei Shu, NEC
                Sam Sjogren, TGV
                Mark Sleeper, Sparta
                Lance Sprung
                Mike St.Johns
                Bob Stewart, Xyplex
                Emil Sturniold
                Kaj Tesink, Bellcore
                Dean Throop, Data General
                Bill Townsend, Xylogics
                Maurice Turcotte
                Kannan Varadhou
                Sudhanshu Verma, HP
                Warren Vik, Interactive Systems
                David Waitzman, BBN
                Steve Waldbusser, CMU
                Dan Wintringhan
                David Wood
                Jeff Young, Cray Research

7. References

   [1] Cerf, V., "IAB Recommendations for the Development of Internet
       Network Management Standards", RFC 1052, NRI, April 1988.

   [2] Cerf, V., "Report of the Second Ad Hoc Network Management Review
       Group", RFC 1109, NRI, August 1989.

   [3] Rose M., and K. McCloghrie, "Structure and Identification of
       Management Information for TCP/IP-based internets", RFC 1155,
       Performance Systems International, Hughes LAN Systems, May 1990.

   [4] McCloghrie K., and M. Rose, "Management Information Base for
       Network Management of TCP/IP-based internets", RFC 1156, Hughes
       LAN Systems, Performance Systems International, May 1990.

   [5] Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple
       Network Management Protocol", RFC 1157, SNMP Research,
       Performance Systems International, Performance Systems
       International, MIT Laboratory for Computer Science, May 1990.

   [6] McCloghrie K., and M. Rose, Editors, "Management Information Base
       for Network Management of TCP/IP-based internets", RFC 1213,
       Performance Systems International, March 1991.

   [7] Information processing systems - Open Systems Interconnection -
       Specification of Abstract Syntax Notation One (ASN.1),
       International Organization for Standardization, International
       Standard 8824, December 1987.

   [8] Information processing systems - Open Systems Interconnection -
       Specification of Basic Encoding Rules for Abstract Notation One
       (ASN.1), International Organization for Standardization,
       International Standard 8825, December 1987.

   [9] AT&T Information Systems, AT&T ESF DS1 Channel Service Unit
       User's Manual, 999-100-305, February 1988.

  [10] AT&T Technical Reference, Requirements for Interfacing Digital
       Terminal Equipment to Services Employing the Extended Superframe
       Format, Publication 54016, May 1988.

  [11] CCITT Specifications Volume III, Recommendation G.703,
       Physical/Electrical Characteristics of Hierarchical Digital
       Interfaces, July 1988.

  [12] CCITT Specifications Volume III, Recommendation G.704,
       Synchronous frame structures used at primary and secondary
       hierarchical levels, July 1988.

  [13] Rose, M., and K. McCloghrie, Editors, "Concise MIB Definitions",
       RFC 1212, Performance Systems International, Hughes LAN Systems,
       March 1991.

  [14] ANSI T1.403-1989 American National Standard for
       Telecommunications -- Carrier-to-Customer Installation -- DS1
       Metallic Interface.

  [15] ANSI T1M1.3/90 - 027R2 Draft Proposed Standard -- Description of
       Installation and Maintenance Parameters for Digital Circuits,
       Facilities, and Networks.

  [16] Bell System Techical Reference, Publication 62411, High Capacity
       Digital Service Channel Interface Specification, September 1983.

  [17] Bell System Technical Reference, Publication 43801, "Digital
       Channel Bank Requirements and Objectives", November 1982.

8. Security Considerations

   Security issues are not discussed in this memo.

9. Authors' Addresses

Fred Baker
Advanced Computer Communications, Inc.
720 Santa Barbara Street
Santa Barbara, California 93101

Phone: (805) 963 9431

EMail: fbaker@acc.com

Christopher P. Kolb
Performance Systems International, Inc.
Reston International Center
11800 Sunrise Valley Drive
Suite 1100
Reston, VA 22091

Phone: (703) 620-6651

EMail: kolb@psi.com