

Party MIB
for version 2 of the
Simple Network Management Protocol (SNMPv2)

Status of this Memo

This RFC specifies an IAB standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "IAB Official Protocol Standards" for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Table of Contents

| | |
|---|----|
| 1 Introduction | 2 |
| 1.1 A Note on Terminology | 2 |
| 2 Definitions | 3 |
| 3.1 Textual Conventions | 4 |
| 3.2 Administrative Assignments | 7 |
| 3.2.1 Initial Party and Context Identifiers | 8 |
| 3.3 Object Assignments | 16 |
| 3.4 The SNMPv2 Party Database Group | 16 |
| 3.5 The SNMPv2 Contexts Database Group | 29 |
| 3.5 The SNMPv2 Access Privileges Database Group | 36 |
| 3.6 The MIB View Database Group | 40 |
| 3.7 Conformance Information | 45 |
| 3.7.1 Compliance Statements | 45 |
| 3.7.2 Units of Conformance | 47 |
| 3 Acknowledgments | 48 |
| 4 References | 49 |
| 5 Security Considerations | 50 |
| 6 Authors' Addresses | 50 |

1. Introduction

A network management system contains: several (potentially many) nodes, each with a processing entity, termed an agent, which has access to management instrumentation; at least one management station; and, a management protocol, used to convey management information between the agents and management stations. Operations of the protocol are carried out under an administrative framework which defines both authentication and authorization policies.

Network management stations execute management applications which monitor and control network elements. Network elements are devices such as hosts, routers, terminal servers, etc., which are monitored and controlled through access to their management information.

Management information is viewed as a collection of managed objects, residing in a virtual information store, termed the Management Information Base (MIB). Collections of related objects are defined in MIB modules. These modules are written using a subset of OSI's Abstract Syntax Notation One (ASN.1) [1], termed the Structure of Management Information (SMI) [2].

The Administrative Model for SNMPv2 document [3] defines the properties associated with SNMPv2 parties, SNMPv2 contexts, and access control policies. It is the purpose of this document, the Party MIB for SNMPv2, to define managed objects which correspond to these properties.

1.1. A Note on Terminology

For the purpose of exposition, the original Internet-standard Network Management Framework, as described in RFCs 1155, 1157, and 1212, is termed the SNMP version 1 framework (SNMPv1). The current framework is termed the SNMP version 2 framework (SNMPv2).

2. Definitions

```
SNMPv2-PARTY-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, snmpModules,
        UInteger32
    FROM SNMPv2-SMI
    TEXTUAL-CONVENTION, RowStatus, TruthValue
    FROM SNMPv2-TC
    MODULE-COMPLIANCE, OBJECT-GROUP
    FROM SNMPv2-CONF;
```

```
partyMIB MODULE-IDENTITY
```

```
    LAST-UPDATED "9304010000Z"
    ORGANIZATION "IETF SNMP Security Working Group"
    CONTACT-INFO
        "          Keith McCloghrie
```

```
        Postal: Hughes LAN Systems
                1225 Charleston Road
                Mountain View, CA 94043
                US
```

```
        Tel: +1 415 966 7934
        Fax: +1 415 960 3738
```

```
        E-mail: kzm@hls.com"
```

```
DESCRIPTION
```

```
    "The MIB module describing SNMPv2 parties."
    ::= { snmpModules 3 }
```

-- textual conventions

Party ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"Denotes a SNMPv2 party identifier.

Note that agents may impose implementation limitations on the length of OIDs used to identify Parties. As such, management stations creating new parties should be aware that using an excessively long OID may result in the agent refusing to perform the set operation and instead returning the appropriate error response, e.g., noCreation."

SYNTAX OBJECT IDENTIFIER

TAddress ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"Denotes a transport service address.

For snmpUDPDomain, a TAddress is 6 octets long, the initial 4 octets containing the IP-address in network-byte order and the last 2 containing the UDP port in network-byte order. Consult [5] for further information on snmpUDPDomain."

SYNTAX OCTET STRING

Clock ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"A party's authentication clock - a non-negative integer which is incremented as specified/allowed by the party's Authentication Protocol.

For noAuth, a party's authentication clock is unused and its value is undefined.

For v2md5AuthProtocol, a party's authentication clock is a relative clock with 1-second granularity."

SYNTAX UInteger32

Context ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"Denotes a SNMPv2 context identifier.

Note that agents may impose implementation limitations on the length of OIDs used to identify Contexts. As such, management stations creating new contexts should be aware that using an excessively long OID may result in the agent refusing to perform the set operation and instead returning the appropriate error response, e.g., noCreation."

SYNTAX OBJECT IDENTIFIER

```
StorageType ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        "Describes the memory realization of a conceptual
        row.  A row which is volatile(2) is lost upon
        reboot.  A row which is nonVolatile(3) is backed
        up by stable storage.  A row which is permanent(4)
        cannot be changed nor deleted."
    SYNTAX      INTEGER {
        other(1),          -- eh?
        volatile(2),       -- e.g., in RAM
        nonVolatile(3),    -- e.g., in NVRAM
        permanent(4)      -- e.g., in ROM
    }
```

```
-- administrative assignments

partyAdmin      OBJECT IDENTIFIER ::= { partyMIB 1 }

-- definitions of security protocols

partyProtocols OBJECT IDENTIFIER ::= { partyAdmin 1 }

-- the protocol without authentication
noAuth          OBJECT IDENTIFIER ::= { partyProtocols 1 }

-- the protocol without privacy
noPriv          OBJECT IDENTIFIER ::= { partyProtocols 2 }

-- the DES Privacy Protocol [4]
desPrivProtocol
    OBJECT IDENTIFIER ::= { partyProtocols 3 }

-- the MD5 Authentication Protocol [4]
v2md5AuthProtocol
    OBJECT IDENTIFIER ::= { partyProtocols 4 }

-- definitions of temporal domains

temporalDomains
    OBJECT IDENTIFIER ::= { partyAdmin 2 }

-- this temporal domain refers to management information
-- at the current time
currentTime     OBJECT IDENTIFIER ::= { temporalDomains 1 }

-- this temporal domain refers to management information
-- upon the next re-initialization of the managed device
restartTime     OBJECT IDENTIFIER ::= { temporalDomains 2 }

-- the temporal domain { cacheTime N } refers to management
-- information that is cached and guaranteed to be at most
-- N seconds old
cacheTime       OBJECT IDENTIFIER ::= { temporalDomains 3 }
```

```
-- Definition of Initial Party and Context Identifiers

-- When devices are installed, they need to be configured
-- with an initial set of SNMPv2 parties and contexts.  The
-- configuration of SNMPv2 parties and contexts requires (among
-- other things) the assignment of several OBJECT IDENTIFIERS.
-- Any local network administration can obtain the delegated
-- authority necessary to assign its own OBJECT IDENTIFIERS.
-- However, to provide for those administrations who have not
-- obtained the necessary authority, this document allocates a
-- branch of the naming tree for use with the following
-- conventions.

initialPartyId OBJECT IDENTIFIER ::= { partyAdmin 3 }

initialContextId
    OBJECT IDENTIFIER ::= { partyAdmin 4 }

-- Note these are identified as "initial" party and context
-- identifiers since these allow secure SNMPv2 communication
-- to proceed, thereby allowing further SNMPv2 parties to be
-- configured through use of the SNMPv2 itself.

-- The following definitions identify a party identifier, and
-- specify the initial values of various object instances
-- indexed by that identifier.  In addition, the SNMPv2
-- context, access control policy, and MIB view information
-- assigned, by convention, are identified.
```



```
-- Party Identifiers for use as initial SNMPv2 parties
--      at IP address  a.b.c.d

-- Note that for all OBJECT IDENTIFIERS assigned under
-- initialPartyId, the four sub-identifiers immediately
-- following initialPartyId represent the four octets of
-- an IP address.  Initial party identifiers for other address
-- families are assigned under a different OBJECT IDENTIFIER,
-- as defined elsewhere.

-- Devices which support SNMPv2 as entities acting in an
-- agent role, and accessed via the snmpUDPDomain transport
-- domain, are required to be configured with the appropriate
-- set of the following as implicit assignments as and when
-- they are configured with an IP address.  The appropriate
-- set is all those applicable to the authentication and
-- privacy protocols supported by the device.
```

```
--      a noAuth/noPriv party which executes at the agent
-- partyIdentity      = { initialPartyId a b c d 1 }
-- partyIndex         = 1
-- partyTDomain       = snmpUDPDomain
-- partyTAddress       = a.b.c.d, 161
-- partyLocal         = true (in agent's database)
-- partyAuthProtocol   = noAuth
-- partyAuthClock      = 0
-- partyAuthPrivate    = ''H      (the empty string)
-- partyAuthPublic     = ''H      (the empty string)
-- partyAuthLifetime   = 0
-- partyPrivProtocol   = noPriv
-- partyPrivPrivate    = ''H      (the empty string)
-- partyPrivPublic     = ''H      (the empty string)

--      a noAuth/noPriv party which executes at a manager
-- partyIdentity      = { initialPartyId a b c d 2 }
-- partyIndex         = 2
-- partyTDomain       = snmpUDPDomain
-- partyTAddress       = assigned by local administration
-- partyLocal         = false (in agent's database)
-- partyAuthProtocol   = noAuth
-- partyAuthClock      = 0
-- partyAuthPrivate    = ''H      (the empty string)
-- partyAuthPublic     = ''H      (the empty string)
-- partyAuthLifetime   = 0
-- partyPrivProtocol   = noPriv
-- partyPrivPrivate    = ''H      (the empty string)
-- partyPrivPublic     = ''H      (the empty string)
```

```
--      a md5Auth/noPriv party which executes at the agent
-- partyIdentity          = { initialPartyId a b c d 3 }
-- partyIndex             = 3
-- partyTDomain           = snmpUDPDomain
-- partyTAddress          = a.b.c.d, 161
-- partyLocal             = true (in agent's database)
-- partyAuthProtocol      = v2md5AuthProtocol
-- partyAuthClock         = 0
-- partyAuthPrivate       = assigned by local administration
-- partyAuthPublic        = ''H      (the empty string)
-- partyAuthLifetime      = 300
-- partyPrivProtocol      = noPriv
-- partyPrivPrivate       = ''H      (the empty string)
-- partyPrivPublic        = ''H      (the empty string)

--      a md5Auth/noPriv party which executes at a manager
-- partyIdentity          = { initialPartyId a b c d 4 }
-- partyIndex             = 4
-- partyTDomain           = snmpUDPDomain
-- partyTAddress          = assigned by local administration
-- partyLocal             = false (in agent's database)
-- partyAuthProtocol      = v2md5AuthProtocol
-- partyAuthClock         = 0
-- partyAuthPrivate       = assigned by local administration
-- partyAuthPublic        = ''H      (the empty string)
-- partyAuthLifetime      = 300
-- partyPrivProtocol      = noPriv
-- partyPrivPrivate       = ''H      (the empty string)
-- partyPrivPublic        = ''H      (the empty string)
```

```
--      a md5Auth/desPriv party which executes at the agent
-- partyIdentity      = { initialPartyId a b c d 5 }
-- partyIndex         = 5
-- partyTDomain       = snmpUDPDomain
-- partyTAddress       = a.b.c.d, 161
-- partyLocal         = true (in agent's database)
-- partyAuthProtocol  = v2md5AuthProtocol
-- partyAuthClock     = 0
-- partyAuthPrivate   = assigned by local administration
-- partyAuthPublic    = ''H      (the empty string)
-- partyAuthLifetime  = 300
-- partyPrivProtocol  = desPrivProtocol
-- partyPrivPrivate   = assigned by local administration
-- partyPrivPublic    = ''H      (the empty string)

--      a md5Auth/desPriv party which executes at a manager
-- partyIdentity      = { initialPartyId a b c d 6 }
-- partyIndex         = 6
-- partyTDomain       = snmpUDPDomain
-- partyTAddress       = assigned by local administration
-- partyLocal         = false (in agent's database)
-- partyAuthProtocol  = v2md5AuthProtocol
-- partyAuthClock     = 0
-- partyAuthPrivate   = assigned by local administration
-- partyAuthPublic    = ''H      (the empty string)
-- partyAuthLifetime  = 300
-- partyPrivProtocol  = desPrivProtocol
-- partyPrivPrivate   = assigned by local administration
-- partyPrivPublic    = ''H      (the empty string)
```

```
-- the initial SNMPv2 contexts assigned, by convention, are:

-- contextIdentity          = { initialContextId a b c d 1 }
-- contextIndex             = 1
-- contextLocal             = true (in agent's database)
-- contextViewIndex         = 1
-- contextLocalEntity       = ''H      (the empty string)
-- contextLocalTime         = currentTime
-- contextProxyDstParty     = { 0 0 }
-- contextProxySrcParty     = { 0 0 }
-- contextProxyContext      = { 0 0 }

-- contextIdentity          = { initialContextId a b c d 2 }
-- contextIndex             = 2
-- contextLocal             = true (in agent's database)
-- contextViewIndex         = 2
-- contextLocalEntity       = ''H      (the empty string)
-- contextLocalTime         = currentTime
-- contextProxyDstParty     = { 0 0 }
-- contextProxySrcParty     = { 0 0 }
-- contextProxyContext      = { 0 0 }
```

```
-- The initial access control policy assigned, by
-- convention, is:

-- aclTarget          = 1
-- aclSubject         = 2
-- aclResources       = 1
-- aclPrivileges      = 35 (Get, Get-Next & Get-Bulk)

-- aclTarget          = 2
-- aclSubject         = 1
-- aclResources       = 1
-- aclPrivileges      = 132 (Response & SNMPv2-Trap)

-- aclTarget          = 3
-- aclSubject         = 4
-- aclResources       = 2
-- aclPrivileges      = 43 (Get, Get-Next, Set & Get-Bulk)

-- aclTarget          = 4
-- aclSubject         = 3
-- aclResources       = 2
-- aclPrivileges      = 4 (Response)

-- aclTarget          = 5
-- aclSubject         = 6
-- aclResources       = 2
-- aclPrivileges      = 43 (Get, Get-Next, Set & Get-Bulk)

-- aclTarget          = 6
-- aclSubject         = 5
-- aclResources       = 2
-- aclPrivileges      = 4 (Response)

-- Note that the initial context and access control
-- information assigned above, by default, to the
-- md5Auth/desPriv parties are identical to those assigned to
-- the md5Auth/noPriv parties. However, each administration
-- may choose to have different authorization policies,
-- depending on whether privacy is used.
```

```
-- The initial MIB views assigned, by convention, are:

-- viewIndex          = 1
-- viewSubtree        = system
-- viewMask            = ''H
-- viewType            = included

-- viewIndex          = 1
-- viewSubtree        = snmpStats
-- viewMask            = ''H
-- viewType            = included

-- viewIndex          = 1
-- viewSubtree        = snmpParties
-- viewMask            = ''H
-- viewType            = included

-- viewIndex          = 2
-- viewSubtree        = internet
-- viewMask            = ''H
-- viewType            = included

-- Note that full access to the partyTable, contextTable,
-- aclTable, and viewTable gives a manager the ability to
-- configure any parties with any/all capabilities (the
-- equivalent of "root" access).  A lesser manager can be
-- given access only to the partyTable so that it can
-- maintain its own parties, but not increase/decrease
-- their capabilities.  Such a lesser manager can also
-- create new parties but they are of no use to it.
```

-- object assignments

partyMIBObjects

OBJECT IDENTIFIER ::= { partyMIB 2 }

-- the SNMPv2 party database group

snmpParties OBJECT IDENTIFIER ::= { partyMIBObjects 1 }

partyTable OBJECT-TYPE

SYNTAX SEQUENCE OF PartyEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The SNMPv2 Party database."

::= { snmpParties 1 }

partyEntry OBJECT-TYPE

SYNTAX PartyEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Locally held information about a particular
SNMPv2 party."

INDEX { IMPLIED partyIdentity }

::= { partyTable 1 }

PartyEntry ::=

```
SEQUENCE {
    partyIdentity      Party,
    partyIndex         INTEGER,
    partyTDomain       OBJECT IDENTIFIER,
    partyTAddress      TAddress,
    partyMaxMessageSize INTEGER,
    partyLocal         TruthValue,
    partyAuthProtocol  OBJECT IDENTIFIER,
    partyAuthClock     Clock,
    partyAuthPrivate   OCTET STRING,
    partyAuthPublic    OCTET STRING,
    partyAuthLifetime  INTEGER,
    partyPrivProtocol  OBJECT IDENTIFIER,
    partyPrivPrivate   OCTET STRING,
    partyPrivPublic    OCTET STRING,
    partyCloneFrom     Party,
    partyStorageType   StorageType,
    partyStatus        RowStatus
}
```

partyIdentity OBJECT-TYPE

```
SYNTAX      Party
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"A party identifier uniquely identifying a particular SNMPv2 party."

::= { partyEntry 1 }

partyIndex OBJECT-TYPE

```
SYNTAX      INTEGER (1..65535)
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"A unique value for each SNMPv2 party. The value for each SNMPv2 party must remain constant at least from one re-initialization of the entity's network management system to the next re-initialization."

::= { partyEntry 2 }

```
partyTDomain OBJECT-TYPE
    SYNTAX      OBJECT IDENTIFIER
    MAX-ACCESS   read-create
    STATUS      current
    DESCRIPTION
        "Indicates the kind of transport service by which
         the party receives network management traffic."
    DEFVAL      { snmpUDPDomain }
    ::= { partyEntry 3 }

partyTAddress OBJECT-TYPE
    SYNTAX      TAddress
    MAX-ACCESS   read-create
    STATUS      current
    DESCRIPTION
        "The transport service address by which the party
         receives network management traffic, formatted
         according to the corresponding value of
         partyTDomain. For snmpUDPDomain, partyTAddress is
         formatted as a 4-octet IP Address concatenated
         with a 2-octet UDP port number."
    DEFVAL      { '000000000000'H }
    ::= { partyEntry 4 }

partyMaxMessageSize OBJECT-TYPE
    SYNTAX      INTEGER (484..65507)
    MAX-ACCESS   read-create
    STATUS      current
    DESCRIPTION
        "The maximum length in octets of a SNMPv2 message
         which this party will accept. For parties which
         execute at an agent, the agent initializes this
         object to the maximum length supported by the
         agent, and does not let the object be set to any
         larger value. For parties which do not execute at
         the agent, the agent must allow the manager to set
         this object to any legal value, even if it is
         larger than the agent can generate."
    DEFVAL      { 484 }
    ::= { partyEntry 5 }
```

partyLocal OBJECT-TYPE

SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"An indication of whether this party executes at this SNMPv2 entity. If this object has a value of true(1), then the SNMPv2 entity will listen for SNMPv2 messages on the partyTAddress associated with this party. If this object has the value false(2), then the SNMPv2 entity will not listen for SNMPv2 messages on the partyTAddress associated with this party."

DEFVAL { false }
::= { partyEntry 6 }

partyAuthProtocol OBJECT-TYPE

SYNTAX OBJECT IDENTIFIER
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The authentication protocol by which all messages generated by the party are authenticated as to origin and integrity. The value noAuth signifies that messages generated by the party are not authenticated.

Once an instance of this object is created, its value can not be changed."

DEFVAL { v2md5AuthProtocol }
::= { partyEntry 7 }

```
partyAuthClock OBJECT-TYPE
    SYNTAX      Clock
    MAX-ACCESS   read-create
    STATUS      current
    DESCRIPTION
        "The authentication clock which represents the
        local notion of the current time specific to the
        party.  This value must not be decremented unless
        the party's private authentication key is changed
        simultaneously."
    DEFVAL      { 0 }
    ::= { partyEntry 8 }
```

```
partyAuthPrivate OBJECT-TYPE
    SYNTAX      OCTET STRING
                -- for v2md5AuthProtocol: (SIZE (16))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "An encoding of the party's private authentication
        key which may be needed to support the
        authentication protocol.  Although the value of
        this variable may be altered by a management
        operation (e.g., a SNMPv2 Set-Request), its value
        can never be retrieved by a management operation:
        when read, the value of this variable is the zero
        length OCTET STRING.

        The private authentication key is NOT directly
        represented by the value of this variable, but
        rather it is represented according to an encoding.
        This encoding is the bitwise exclusive-OR of the
        old key with the new key, i.e., of the old private
        authentication key (prior to the alteration) with
        the new private authentication key (after the
        alteration).  Thus, when processing a received
        protocol Set operation, the new private
        authentication key is obtained from the value of
        this variable as the result of a bitwise
        exclusive-OR of the variable's value and the old
        private authentication key.  In calculating the
        exclusive-OR, if the old key is shorter than the
        new key, zero-valued padding is appended to the
        old key.  If no value for the old key exists, a
        zero-length OCTET STRING is used in the
        calculation."
    DEFVAL      { 'H }      -- the empty string
    ::= { partyEntry 9 }
```

```
partyAuthPublic OBJECT-TYPE
    SYNTAX      OCTET STRING
                -- for v2md5AuthProtocol: (SIZE (0..16))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "A publically-readable value for the party.

        Depending on the party's authentication protocol,
        this value may be needed to support the party's
        authentication protocol.  Alternatively, it may be
        used by a manager during the procedure for
        altering secret information about a party.  (For
        example, by altering the value of an instance of
        this object in the same SNMPv2 Set-Request used to
        update an instance of partyAuthPrivate, a
        subsequent Get-Request can determine if the Set-
        Request was successful in the event that no
        response to the Set-Request is received, see [4].)

        The length of the value is dependent on the
        party's authentication protocol.  If not used by
        the authentication protocol, it is recommended
        that agents support values of any length up to and
        including the length of the corresponding
        partyAuthPrivate object."
    DEFVAL      { ''H }      -- the empty string
    ::= { partyEntry 10 }
```

partyAuthLifetime OBJECT-TYPE

SYNTAX INTEGER (0..2147483647)

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The lifetime (in units of seconds) which represents an administrative upper bound on acceptable delivery delay for protocol messages generated by the party.

Once an instance of this object is created, its value can not be changed."

DEFVAL { 300 }

::= { partyEntry 11 }

partyPrivProtocol OBJECT-TYPE

SYNTAX OBJECT IDENTIFIER

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The privacy protocol by which all protocol messages received by the party are protected from disclosure. The value noPriv signifies that messages received by the party are not protected.

Once an instance of this object is created, its value can not be changed."

DEFVAL { noPriv }

::= { partyEntry 12 }

```
partyPrivPrivate OBJECT-TYPE
    SYNTAX      OCTET STRING
                -- for desPrivProtocol: (SIZE (16))
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "An encoding of the party's private encryption key
        which may be needed to support the privacy
        protocol.  Although the value of this variable may
        be altered by a management operation (e.g., a
        SNMPv2 Set-Request), its value can never be
        retrieved by a management operation: when read,
        the value of this variable is the zero length
        OCTET STRING.

        The private encryption key is NOT directly
        represented by the value of this variable, but
        rather it is represented according to an encoding.
        This encoding is the bitwise exclusive-OR of the
        old key with the new key, i.e., of the old private
        encryption key (prior to the alteration) with the
        new private encryption key (after the alteration).
        Thus, when processing a received protocol Set
        operation, the new private encryption key is
        obtained from the value of this variable as the
        result of a bitwise exclusive-OR of the variable's
        value and the old private encryption key.  In
        calculating the exclusive-OR, if the old key is
        shorter than the new key, zero-valued padding is
        appended to the old key.  If no value for the old
        key exists, a zero-length OCTET STRING is used in
        the calculation."
    DEFVAL      { ''H }      -- the empty string
    ::= { partyEntry 13 }
```



```
partyPrivPublic OBJECT-TYPE
    SYNTAX      OCTET STRING
                -- for desPrivProtocol: (SIZE (0..16))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "A publically-readable value for the party.

        Depending on the party's privacy protocol, this
        value may be needed to support the party's privacy
        protocol.  Alternatively, it may be used by a
        manager as a part of its procedure for altering
        secret information about a party.  (For example,
        by altering the value of an instance of this
        object in the same SNMPv2 Set-Request used to
        update an instance of partyPrivPrivate, a
        subsequent Get-Request can determine if the Set-
        Request was successful in the event that no
        response to the Set-Request is received, see [4].)

        The length of the value is dependent on the
        party's privacy protocol.  If not used by the
        privacy protocol, it is recommended that agents
        support values of any length up to and including
        the length of the corresponding partyPrivPrivate
        object."
    DEFVAL      { ''H }      -- the empty string
    ::= { partyEntry 14 }
```

partyCloneFrom OBJECT-TYPE

SYNTAX Party

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The identity of a party to clone authentication and privacy parameters from. When read, the value { 0 0 } is returned.

This value must be written exactly once, when the associated instance of partyStatus either does not exist or has the value 'notReady'. When written, the value identifies a party, the cloning party, whose status column has the value 'active'. The cloning party is used in two ways.

One, if instances of the following objects do not exist for the party being created, then they are created with values identical to those of the corresponding objects for the cloning party:

partyAuthProtocol
partyAuthPublic
partyAuthLifetime
partyPrivProtocol
partyPrivPublic

Two, instances of the following objects are updated using the corresponding values of the cloning party:

partyAuthPrivate
partyPrivPrivate

(e.g., the value of the cloning party's instance of the partyAuthPrivate object is XOR'd with the value of the partyAuthPrivate instances of the party being created.)"

::= { partyEntry 15 }

```
partyStorageType OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The storage type for this conceptual row in the
        partyTable."
    DEFVAL      { nonVolatile }
    ::= { partyEntry 16 }
```

```
partyStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The status of this conceptual row in the
        partyTable."
```

A party is not qualified for activation until instances of all columns of its partyEntry row have an appropriate value. In particular:

A value must be written to the Party's partyCloneFrom object.

If the Party's partyAuthProtocol object has the value md5AuthProtocol, then the corresponding instance of partyAuthPrivate must contain a secret of the appropriate length. Further, at least one management protocol set operation updating the value of the party's partyAuthPrivate object must be successfully processed, before the partyAuthPrivate column is considered appropriately configured.

If the Party's partyPrivProtocol object has the value desPrivProtocol, then the corresponding instance of partyPrivPrivate must contain a secret of the appropriate length. Further, at least one management protocol set operation updating the value of the party's partyPrivPrivate object must be successfully processed, before the partyPrivPrivate column is considered appropriately configured.

Until instances of all corresponding columns are appropriately configured, the value of the corresponding instance of the partyStatus column is 'notReady'."

```
::= { partyEntry 17 }
```

-- the SNMPv2 contexts database group

snmpContexts OBJECT IDENTIFIER ::= { partyMIBObjects 2 }

contextTable OBJECT-TYPE

SYNTAX SEQUENCE OF ContextEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The SNMPv2 Context database."

::= { snmpContexts 1 }

contextEntry OBJECT-TYPE

SYNTAX ContextEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Locally held information about a particular
SNMPv2 context."

INDEX { IMPLIED contextIdentity }

::= { contextTable 1 }

ContextEntry ::=

SEQUENCE {

| | |
|----------------------|--------------------|
| contextIdentity | Context, |
| contextIndex | INTEGER, |
| contextLocal | TruthValue, |
| contextViewIndex | INTEGER, |
| contextLocalEntity | OCTET STRING, |
| contextLocalTime | OBJECT IDENTIFIER, |
| contextProxyDstParty | Party, |
| contextProxySrcParty | Party, |
| contextProxyContext | OBJECT IDENTIFIER, |
| contextStorageType | StorageType, |
| contextStatus | RowStatus |

}

```
contextIdentity OBJECT-TYPE
    SYNTAX      Context
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A context identifier uniquely identifying a
        particular SNMPv2 context."
    ::= { contextEntry 1 }

contextIndex OBJECT-TYPE
    SYNTAX      INTEGER (1..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A unique value for each SNMPv2 context.  The
        value for each SNMPv2 context must remain constant
        at least from one re-initialization of the
        entity's network management system to the next
        re-initialization."
    ::= { contextEntry 2 }

contextLocal OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "An indication of whether this context is realized
        by this SNMPv2 entity."
    DEFVAL      { true }
    ::= { contextEntry 3 }
```

contextViewIndex OBJECT-TYPE

SYNTAX INTEGER (0..65535)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"If the value of an instance of this object is zero, then this corresponding conceptual row in the contextTable refers to a SNMPv2 context which identifies a proxy relationship; the values of the corresponding instances of the contextProxyDstParty, contextProxySrcParty, and contextProxyContext objects provide further information on the proxy relationship.

Otherwise, if the value of an instance of this object is greater than zero, then this corresponding conceptual row in the contextTable refers to a SNMPv2 context which identifies a MIB view of a locally accessible entity; the value of the instance identifies the particular MIB view which has the same value of viewIndex; and the value of the corresponding instances of the contextLocalEntity and contextLocalTime objects provide further information on the local entity and its temporal domain."

::= { contextEntry 4 }

```
contextLocalEntity OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "If the value of the corresponding instance of the
        contextViewIndex is greater than zero, then the
        value of an instance of this object identifies the
        local entity whose management information is in
        the SNMPv2 context's MIB view.  The empty string
        indicates that the MIB view contains the SNMPv2
        entity's own local management information;
        otherwise, a non-empty string indicates that the
        MIB view contains management information of some
        other local entity, e.g., 'Repeater1'."
    DEFVAL      { ''H }      -- the empty string
    ::= { contextEntry 5 }

contextLocalTime OBJECT-TYPE
    SYNTAX      OBJECT IDENTIFIER
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "If the value of the corresponding instance of the
        contextViewIndex is greater than zero, then the
        value of an instance of this object identifies the
        temporal context of the management information in
        the MIB view."
    DEFVAL      { currentTime }
    ::= { contextEntry 6 }
```


contextProxyDstParty OBJECT-TYPE

SYNTAX Party

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"If the value of the corresponding instance of the contextViewIndex is equal to zero, then the value of an instance of this object identifies a SNMPv2 party which is the proxy destination of a proxy relationship.

If the value of the corresponding instance of the contextViewIndex is greater than zero, then the value of an instance of this object is { 0 0 }."

::= { contextEntry 7 }

contextProxySrcParty OBJECT-TYPE

SYNTAX Party

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"If the value of the corresponding instance of the contextViewIndex is equal to zero, then the value of an instance of this object identifies a SNMPv2 party which is the proxy source of a proxy relationship.

Interpretation of an instance of this object depends upon the value of the transport domain associated with the SNMPv2 party used as the proxy destination in this proxy relationship.

If the value of the corresponding instance of the contextViewIndex is greater than zero, then the value of an instance of this object is { 0 0 }."

::= { contextEntry 8 }

```
contextProxyContext OBJECT-TYPE
    SYNTAX          OBJECT IDENTIFIER
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "If the value of the corresponding instance of the
        contextViewIndex is equal to zero, then the value
        of an instance of this object identifies the
        context of a proxy relationship.

        Interpretation of an instance of this object
        depends upon the value of the transport domain
        associated with the SNMPv2 party used as the proxy
        destination in this proxy relationship.

        If the value of the corresponding instance of the
        contextViewIndex is greater than zero, then the
        value of an instance of this object is { 0 0 }."
    ::= { contextEntry 9 }

contextStorageType OBJECT-TYPE
    SYNTAX          StorageType
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "The storage type for this conceptual row in the
        contextTable."
    DEFVAL          { nonVolatile }
    ::= { contextEntry 10 }
```

contextStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The status of this conceptual row in the
contextTable.

A context is not qualified for activation until
instances of all corresponding columns have the
appropriate value. In particular, if the
context's contextViewIndex is greater than zero,
then the viewStatus column of the associated
conceptual row(s) in the viewTable must have the
value 'active'. Until instances of all
corresponding columns are appropriately
configured, the value of the corresponding
instance of the contextStatus column is
'notReady'."

::= { contextEntry 11 }

```
-- the SNMPv2 access privileges database group

snmpAccess      OBJECT IDENTIFIER ::= { partyMIBObjects 3 }

aclTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF AclEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "The access privileges database."
    ::= { snmpAccess 1 }

aclEntry OBJECT-TYPE
    SYNTAX      AclEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "The access privileges for a particular subject
        SNMPv2 party when asking a particular target
        SNMPv2 party to access a particular SNMPv2
        context."
    INDEX       { aclTarget, aclSubject, aclResources }
    ::= { aclTable 1 }

AclEntry ::=
    SEQUENCE {
        aclTarget      INTEGER,
        aclSubject      INTEGER,
        aclResources    INTEGER,
        aclPrivileges   INTEGER,
        aclStorageType  StorageType,
        aclStatus       RowStatus
    }
```

aclTarget OBJECT-TYPE

SYNTAX INTEGER (1..65535)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The value of an instance of this object identifies a SNMPv2 party which is the target of an access control policy, and has the same value as the instance of the partyIndex object for that party."

::= { aclEntry 1 }

aclSubject OBJECT-TYPE

SYNTAX INTEGER (1..65535)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The value of an instance of this object identifies a SNMPv2 party which is the subject of an access control policy, and has the same value as the instance of the partyIndex object for that SNMPv2 party."

::= { aclEntry 2 }

aclResources OBJECT-TYPE

SYNTAX INTEGER (1..65535)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The value of an instance of this object identifies a SNMPv2 context in an access control policy, and has the same value as the instance of the contextIndex object for that SNMPv2 context."

::= { aclEntry 3 }

aclPrivileges OBJECT-TYPE

SYNTAX INTEGER (0..255)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The access privileges which govern what management operations a particular target party may perform with respect to a particular SNMPv2 context when requested by a particular subject party. These privileges are specified as a sum of values, where each value specifies a SNMPv2 PDU type by which the subject party may request a permitted operation. The value for a particular PDU type is computed as 2 raised to the value of the ASN.1 context-specific tag for the appropriate SNMPv2 PDU type. The values (for the tags defined in [5]) are defined in [3] as:

| | | |
|-------------|---|-----|
| Get | : | 1 |
| GetNext | : | 2 |
| Response | : | 4 |
| Set | : | 8 |
| unused | : | 16 |
| GetBulk | : | 32 |
| Inform | : | 64 |
| SNMPv2-Trap | : | 128 |

The null set is represented by the value zero."

DEFVAL { 35 } -- Get, Get-Next & Get-Bulk

::= { aclEntry 4 }

aclStorageType OBJECT-TYPE

SYNTAX StorageType

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The storage type for this conceptual row in the aclTable."

DEFVAL { nonVolatile }

::= { aclEntry 5 }

```
aclStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The status of this conceptual row in the
         aclTable."
    ::= { aclEntry 6 }
```

-- the MIB view database group

snmpViews OBJECT IDENTIFIER ::= { partyMIBObjects 4 }

viewTable OBJECT-TYPE

SYNTAX SEQUENCE OF ViewEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Locally held information about the MIB views known to this SNMPv2 entity.

Each SNMPv2 context which is locally accessible has a single MIB view which is defined by two collections of view subtrees: the included view subtrees, and the excluded view subtrees. Every such subtree, both included and excluded, is defined in this table.

To determine if a particular object instance is in a particular MIB view, compare the object instance's OBJECT IDENTIFIER with each of the MIB view's entries in this table. If none match, then the object instance is not in the MIB view. If one or more match, then the object instance is included in, or excluded from, the MIB view according to the value of viewType in the entry whose value of viewSubtree has the most sub-identifiers. If multiple entries match and have the same number of sub-identifiers, then the lexicographically greatest instance of viewType determines the inclusion or exclusion.

An object instance's OBJECT IDENTIFIER X matches an entry in this table when the number of sub-identifiers in X is at least as many as in the value of viewSubtree for the entry, and each sub-identifier in the value of viewSubtree matches its corresponding sub-identifier in X. Two sub-identifiers match either if the corresponding bit of viewMask is zero (the 'wild card' value), or if they are equal.

Due to this 'wild card' capability, we introduce

the term, a 'family' of view subtrees, to refer to the set of subtrees defined by a particular combination of values of viewSubtree and viewMask. In the case where no 'wild card' is defined in viewMask, the family of view subtrees reduces to a single view subtree."

::= { snmpViews 1 }

viewEntry OBJECT-TYPE

SYNTAX ViewEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Information on a particular family of view subtrees included in or excluded from a particular SNMPv2 context's MIB view.

Implementations must not restrict the number of families of view subtrees for a given MIB view, except as dictated by resource constraints on the overall number of entries in the viewTable."

INDEX { viewIndex, IMPLIED viewSubtree }

::= { viewTable 1 }

ViewEntry ::=

SEQUENCE {

| | |
|-----------------|--------------------|
| viewIndex | INTEGER, |
| viewSubtree | OBJECT IDENTIFIER, |
| viewMask | OCTET STRING, |
| viewType | INTEGER, |
| viewStorageType | StorageType, |
| viewStatus | RowStatus |

}

viewIndex OBJECT-TYPE

SYNTAX INTEGER (1..65535)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A unique value for each MIB view. The value for each MIB view must remain constant at least from one re-initialization of the entity's network management system to the next re-initialization."

::= { viewEntry 1 }

viewSubtree OBJECT-TYPE

SYNTAX OBJECT IDENTIFIER

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A MIB subtree."

::= { viewEntry 2 }

viewMask OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (0..16))

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The bit mask which, in combination with the corresponding instance of viewSubtree, defines a family of view subtrees.

Each bit of this bit mask corresponds to a sub-identifier of viewSubtree, with the most significant bit of the i-th octet of this octet string value (extended if necessary, see below) corresponding to the (8*i - 7)-th sub-identifier, and the least significant bit of the i-th octet of this octet string corresponding to the (8*i)-th sub-identifier, where i is in the range 1 through 16.

Each bit of this bit mask specifies whether or not the corresponding sub-identifiers must match when determining if an OBJECT IDENTIFIER is in this family of view subtrees; a '1' indicates that an exact match must occur; a '0' indicates 'wild card', i.e., any sub-identifier value matches.

Thus, the OBJECT IDENTIFIER X of an object instance is contained in a family of view subtrees if the following criteria are met:

for each sub-identifier of the value of viewSubtree, either:

the i-th bit of viewMask is 0, or

the i-th sub-identifier of X is equal to the i-th sub-identifier of the value of viewSubtree.

If the value of this bit mask is M bits long and there are more than M sub-identifiers in the corresponding instance of viewSubtree, then the bit mask is extended with 1's to be the required length.

Note that when the value of this object is the zero-length string, this extension rule results in a mask of all-1's being used (i.e., no 'wild card'), and the family of view subtrees is the one view subtree uniquely identified by the corresponding instance of viewSubtree."

```
DEFVAL      { ''H }  
::= { viewEntry 3 }
```

```
viewType OBJECT-TYPE
    SYNTAX      INTEGER {
                    included(1),
                    excluded(2)
                }
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The status of a particular family of view
        subtrees within the particular SNMPv2 context's
        MIB view. The value 'included(1)' indicates that
        the corresponding instances of viewSubtree and
        viewMask define a family of view subtrees included
        in the MIB view. The value 'excluded(2)'
        indicates that the corresponding instances of
        viewSubtree and viewMask define a family of view
        subtrees excluded from the MIB view."
    DEFVAL       { included }
    ::= { viewEntry 4 }

viewStorageType OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The storage type for this conceptual row in the
        viewTable."
    DEFVAL       { nonVolatile }
    ::= { viewEntry 5 }

viewStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The status of this conceptual row in the
        viewTable."
    ::= { viewEntry 6 }
```

```
-- conformance information

partyMIBConformance
    OBJECT IDENTIFIER ::= { partyMIB 3 }

partyMIBCompliances
    OBJECT IDENTIFIER ::= { partyMIBConformance 1 }
partyMIBGroups
    OBJECT IDENTIFIER ::= { partyMIBConformance 2 }

-- compliance statements

unSecurableCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for SNMPv2 entities
        which implement the Party MIB, but do not support
        any authentication or privacy protocols (i.e.,
        only the noAuth and noPriv protocols are
        supported)."
```

```
    MODULE -- this module
        MANDATORY-GROUPS { partyMIBGroup }
    ::= { partyMIBCompliances 1 }
```

```
partyNoPrivacyCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for SNMPv2 entities
        which implement the Party MIB, and support an
        authentication protocol, but do not support any
        privacy protocols (i.e., only the noAuth,
        v2md5AuthProtocol, and noPriv protocols are
        supported)."
```

```
    MODULE -- this module
        MANDATORY-GROUPS { partyMIBGroup }
    ::= { partyMIBCompliances 2 }
```

partyPrivacyCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for SNMPv2 entities which implement the Party MIB, support an authentication protocol, and support a privacy protocol ONLY for the purpose of accessing security parameters.

For all aclTable entries authorizing a subject and/or target SNMPv2 party whose privacy protocol is desPrivProtocol, to be used in accessing a SNMPv2 context, the MIB view for that SNMPv2 context shall include only those objects subordinate to partyMIBObjects, or a subset thereof, e.g.,

```
viewSubtree = { partyMIBObjects }
viewMask     = 'H
viewType     = { included }
```

Any attempt to configure an entry in the partyTable, the contextTable, the aclTable or the viewTable such that a party using the desPrivProtocol would be authorized for use in accessing objects outside of the partyMIBObjects subtree shall result in the appropriate error response (e.g., wrongValue or inconsistentValue)."

MODULE -- this module

MANDATORY-GROUPS { partyMIBGroup }

::= { partyMIBCompliances 3 }

```
fullPrivacyCompliance MODULE-COMPLIANCE
    STATUS    current
    DESCRIPTION
        "The compliance statement for SNMPv2 entities
        which implement the Party MIB, support an
        authentication protocol, and support a privacy
        protocol without restrictions on its use."
    MODULE    -- this module
        MANDATORY-GROUPS { partyMIBGroup }
    ::= { partyMIBCompliances 4 }

-- units of conformance

partyMIBGroup OBJECT-GROUP
    OBJECTS { partyIndex, partyTDomain, partyTAddress,
        partyMaxMessageSize, partyLocal,
        partyAuthProtocol, partyAuthClock,
        partyAuthPrivate, partyAuthPublic,
        partyAuthLifetime, partyPrivProtocol,
        partyPrivPrivate, partyPrivPublic,
        partyStorageType, partyStatus,
        partyCloneFrom,
        contextIndex, contextLocal,
        contextViewIndex, contextLocalEntity,
        contextLocalTime, contextStorageType,
        contextStatus, aclTarget, aclSubject,
        aclPrivileges, aclStorageType, aclStatus,
        viewMask, viewType, viewStorageType, viewStatus }
    STATUS    current
    DESCRIPTION
        "The collection of objects allowing the
        description and configuration of SNMPv2 parties.

        Note that objects which support proxy
        relationships are not included in this conformance
        group."
    ::= { partyMIBGroups 1 }

END
```

3. Acknowledgments

This document is based, almost entirely, on [RFC 1353](#).

4. References

- [1] Information processing systems - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1), International Organization for Standardization. International Standard 8824, (December, 1987).
- [2] Case, J., McCloghrie, K., Rose, M., and Waldbusser, S., "Structure of Management Information for version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1442](#), SNMP Research, Inc., Hughes LAN Systems, Dover Beach Consulting, Inc., Carnegie Mellon University, April 1993.
- [3] Galvin, J., and McCloghrie, K., "Administrative Model for version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1445](#), Trusted Information Systems, Hughes LAN Systems, April 1993.
- [4] Galvin, J., and McCloghrie, K., "Security Protocols for version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1446](#), Trusted Information Systems, Hughes LAN Systems, April 1993.
- [5] Case, J., McCloghrie, K., Rose, M., and Waldbusser, S., "Protocol Operations for version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1448](#), SNMP Research, Inc., Hughes LAN Systems, Dover Beach Consulting, Inc., Carnegie Mellon University, April 1993.
- [5] Case, J., McCloghrie, K., Rose, M., and Waldbusser, S., "Transport Mappings for version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1449](#), SNMP Research, Inc., Hughes LAN Systems, Dover Beach Consulting, Inc., Carnegie Mellon University, April 1993.

5. Security Considerations

Security issues are not discussed in this memo.

6. Authors' Addresses

Keith McCloghrie
Hughes LAN Systems
1225 Charleston Road
Mountain View, CA 94043
US

Phone: +1 415 966 7934
Email: kzm@hls.com

James M. Galvin
Trusted Information Systems, Inc.
3060 Washington Road, Route 97
Glenwood, MD 21738

Phone: +1 301 854-6889
EMail: galvin@tis.com