

Internet Engineering Task Force (IETF)
Request for Comments: 6648
BCP: 178
Category: Best Current Practice
ISSN: 2070-1721

P. Saint-Andre
Cisco Systems, Inc.
D. Crocker
Brandenburg InternetWorking
M. Nottingham
Rackspace
June 2012

Deprecating the "X-" Prefix and Similar Constructs in Application Protocols

Abstract

Historically, designers and implementers of application protocols have often distinguished between standardized and unstandardized parameters by prefixing the names of unstandardized parameters with the string "X-" or similar constructs. In practice, that convention causes more problems than it solves. Therefore, this document deprecates the convention for newly defined parameters with textual (as opposed to numerical) names in application protocols.

Status of This Memo

This memo documents an Internet Best Current Practice.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on BCPs is available in [Section 2 of RFC 5741](#).

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6648>.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. Recommendations for Implementers of Application Protocols	4
3. Recommendations for Creators of New Parameters	4
4. Recommendations for Protocol Designers	4
5. Security Considerations	5
6. IANA Considerations	5
7. Acknowledgements	5
Appendix A. Background	6
Appendix B. Analysis	7
References	10
Normative References	10
Informative References	10

1. Introduction

Many application protocols use parameters with textual (as opposed to numerical) names to identify data (media types, header fields in Internet mail messages and HTTP requests, vCard parameters and properties, etc.). Historically, designers and implementers of application protocols have often distinguished between standardized and unstandardized parameters by prefixing the names of unstandardized parameters with the string "X-" or similar constructs (e.g., "x."), where the "X" is commonly understood to stand for "eXperimental" or "eXtension".

Under this convention, the name of a parameter not only identified the data, but also embedded the status of the parameter into the name itself: a parameter defined in a specification produced by a recognized standards development organization (or registered according to processes defined in such a specification) did not start

with "X-" or similar constructs, whereas a parameter defined outside such a specification or process started with "X-" or similar constructs.

As explained more fully under [Appendix A](#), this convention was encouraged for many years in application protocols such as file transfer, email, and the World Wide Web. In particular, it was codified for email by [\[RFC822\]](#) (via the distinction between "Extension-fields" and "user-defined-fields"), but then removed by [\[RFC2822\]](#) based on implementation and deployment experience. A similar progression occurred for SIP technologies with regard to the "P-" header, as explained in [\[RFC5727\]](#). The reasoning behind those changes is explored under [Appendix B](#).

In short, although in theory the "X-" convention was a good way to avoid collisions (and attendant interoperability problems) between standardized parameters and unstandardized parameters, in practice the benefits have been outweighed by the costs associated with the leakage of unstandardized parameters into the standards space.

This document generalizes from the experience of the email and SIP communities by doing the following:

1. Deprecates the "X-" convention for newly defined parameters in application protocols, including new parameters for established protocols. This change applies even where the "X-" convention was only implicit, and not explicitly provided, such as was done for email in [\[RFC822\]](#).
2. Makes specific recommendations about how to proceed in a world without the distinction between standardized and unstandardized parameters (although only for parameters with textual names, not parameters that are expressed as numbers, which are out of the scope of this document).
3. Does not recommend against the practice of private, local, preliminary, experimental, or implementation-specific parameters, only against the use of "X-" and similar constructs in the names of such parameters.
4. Makes no recommendation as to whether existing "X-" parameters ought to remain in use or be migrated to a format without the "X-"; this is a matter for the creators or maintainers of those parameters.

5. Does not override existing specifications that legislate the use of "X-" for particular application protocols (e.g., the "x-name" token in [\[RFC5545\]](#)); this is a matter for the designers of those protocols.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

2. Recommendations for Implementers of Application Protocols

Implementations of application protocols MUST NOT make any assumptions about the status of a parameter, nor take automatic action regarding a parameter, based solely on the presence or absence of "X-" or a similar construct in the parameter's name.

3. Recommendations for Creators of New Parameters

Creators of new parameters to be used in the context of application protocols:

1. SHOULD assume that all parameters they create might become standardized, public, commonly deployed, or usable across multiple implementations.
2. SHOULD employ meaningful parameter names that they have reason to believe are currently unused.
3. SHOULD NOT prefix their parameter names with "X-" or similar constructs.

Note: If the relevant parameter name space has conventions about associating parameter names with those who create them, a parameter name could incorporate the organization's name or primary domain name (see [Appendix B](#) for examples).

4. Recommendations for Protocol Designers

Designers of new application protocols that allow extensions using parameters:

1. SHOULD establish registries with potentially unlimited value-spaces, defining both permanent and provisional registries if appropriate.
2. SHOULD define simple, clear registration procedures.

3. SHOULD mandate registration of all non-private parameters, independent of the form of the parameter names.
4. SHOULD NOT prohibit parameters with an "X-" prefix or similar constructs from being registered.
5. MUST NOT stipulate that a parameter with an "X-" prefix or similar constructs needs to be understood as unstandardized.
6. MUST NOT stipulate that a parameter without an "X-" prefix or similar constructs needs to be understood as standardized.

5. Security Considerations

Interoperability and migration issues with security-critical parameters can result in unnecessary vulnerabilities (see [Appendix B](#) for further discussion).

As a corollary to the recommendation provided under [Section 2](#), implementations MUST NOT assume that standardized parameters are "secure" whereas unstandardized parameters are "insecure", based solely on the names of such parameters.

6. IANA Considerations

This document does not modify registration procedures currently in force for various application protocols. However, such procedures might be updated in the future to incorporate the best practices defined in this document.

7. Acknowledgements

Thanks to Claudio Allocchio, Adam Barth, Nathaniel Borenstein, Eric Burger, Stuart Cheshire, Al Constanzo, Dave Cridland, Ralph Droms, Martin Duerst, Frank Ellermann, J.D. Falk, Ned Freed, Tony Finch, Randall Gellens, Tony Hansen, Ted Hardie, Joe Hildebrand, Alfred Hoenes, Paul Hoffman, Eric Johnson, Scott Kelly, Scott Kitterman, John Klensin, Graham Klyne, Murray Kucherawy, Eliot Lear, John Levine, Bill McQuillan, Alexey Melnikov, Subramanian Moonesamy, Keith Moore, Ben Niven-Jenkins, Zoltan Ordogh, Tim Petch, Dirk Pranke, Randy Presuhn, Julian Reschke, Dan Romascanu, Doug Royer, Andrew Sullivan, Henry Thompson, Martin Thomson, Matthew Wild, Nicolas Williams, Tim Williams, Mykyta Yevstifeyev, and Kurt Zeilenga for their feedback.

Appendix A. Background

The beginnings of the "X-" convention can be found in a suggestion made by Brian Harvey in 1975 with regard to FTP parameters [RFC691]:

Thus, FTP servers which care about the distinction between Telnet print and non-print could implement SRVR N and SRVR T. Ideally the SRVR parameters should be registered with Jon Postel to avoid conflicts, although it is not a disaster if two sites use the same parameter for different things. I suggest that parameters be allowed to be more than one letter, and that an initial letter X be used for really local idiosyncracies [sic].

This "X" prefix was subsequently used in [RFC737], [RFC743], and [RFC775]. This usage was noted in [RFC1123]:

FTP allows "experimental" commands, whose names begin with "X". If these commands are subsequently adopted as standards, there may still be existing implementations using the "X" form.... All FTP implementations SHOULD recognize both forms of these commands, by simply equating them with extra entries in the command lookup table.

The "X-" convention has been used for email header fields since at least the publication of [RFC822] in 1982, which distinguished between "Extension-fields" and "user-defined-fields" as follows:

The prefatory string "X-" will never be used in the names of Extension-fields. This provides user-defined fields with a protected set of names.

That rule was restated by [RFC1154] as follows:

Keywords beginning with "X-" are permanently reserved to implementation-specific use. No standard registered encoding keyword will ever begin with "X-".

This convention continued with various specifications for media types ([RFC2045], [RFC2046], [RFC2047]), HTTP headers ([RFC2068], [RFC2616]), vCard parameters and properties ([RFC2426]), Uniform Resource Names ([RFC3406]), Lightweight Directory Access Protocol (LDAP) field names ([RFC4512]), and other application technologies.

However, use of the "X-" prefix in email headers was effectively deprecated between the publication of [RFC822] in 1982 and the publication of [RFC2822] in 2001 by removing the distinction between the "extension-field" construct and the "user-defined-field"

construct (a similar change happened with regard to Session Initiation Protocol "P-" headers when [RFC3427] was obsoleted by [RFC5727]).

Despite the fact that parameters containing the "X-" string have been effectively deprecated in email headers, they continue to be used in a wide variety of application protocols. The two primary situations motivating such use are:

1. Experiments that are intended to possibly be standardized in the future, if they are successful.
2. Extensions that are intended to never be standardized because they are intended only for implementation-specific use or for local use on private networks.

Use of this naming convention is not mandated by the Internet Standards Process [BCP9] or IANA registration rules [BCP26]. Rather, it is an individual choice by each specification that references the convention or each administrative process that chooses to use it. In particular, some Standards Track RFCs have interpreted the convention in a normative way (e.g., [RFC822] and [RFC5451]).

Appendix B. Analysis

The primary problem with the "X-" convention is that unstandardized parameters have a tendency to leak into the protected space of standardized parameters, thus introducing the need for migration from the "X-" name to a standardized name. Migration, in turn, introduces interoperability issues (and sometimes security issues) because older implementations will support only the "X-" name and newer implementations might support only the standardized name. To preserve interoperability, newer implementations simply support the "X-" name forever, which means that the unstandardized name has become a de facto standard (thus obviating the need for segregation of the name space into standardized and unstandardized areas in the first place).

We have already seen this phenomenon at work with regard to FTP in the quote from [RFC1123] in Appendix A. The HTTP community had the same experience with the "x-gzip" and "x-compress" media types, as noted in [RFC2068]:

For compatibility with previous implementations of HTTP, applications should consider "x-gzip" and "x-compress" to be equivalent to "gzip" and "compress" respectively.

A similar example can be found in [RFC5064], which defined the "Archived-At" message header field but also found it necessary to define and register the "X-Archived-At" field:

For backwards compatibility, this document also describes the X-Archived-At header field, a precursor of the Archived-At header field. The X-Archived-At header field MAY also be parsed, but SHOULD NOT be generated.

One of the original reasons for segregation of name spaces into standardized and unstandardized areas was the perceived difficulty of registering names. However, the solution to that problem has been simpler registration rules, such as those provided by [RFC3864] and [RFC4288]. As explained in [RFC4288]:

[W]ith the simplified registration procedures described above for vendor and personal trees, it should rarely, if ever, be necessary to use unregistered experimental types. Therefore, use of both "x-" and "x." forms is discouraged.

For some name spaces, another helpful practice has been the establishment of separate registries for permanent names and provisional names, as in [RFC4395].

Furthermore, often standardization of a unstandardized parameter leads to subtly different behavior (e.g., the standardized version might have different security properties as a result of security review provided during the standardization process). If implementers treat the old, unstandardized parameter and the new, standardized parameter as equivalent, interoperability and security problems can ensue. Analysis of unstandardized parameters to detect and correct flaws is, in general, a good thing and is not intended to be discouraged by the lack of distinction in element names. If an originally unstandardized parameter or protocol element is standardized and the new form has differences that affect interoperability or security properties, it would be inappropriate for implementations to treat the old form as identical to the new form.

For similar considerations with regard to the "P-" convention in the Session Initiation Protocol, see [RFC5727].

In some situations, segregating the parameter name space used in a given application protocol can be justified:

1. When it is extremely unlikely that some parameters will ever be standardized. In this case, implementation-specific and private-use parameters could at least incorporate the organization's name (e.g., "ExampleInc-foo" or, consistent with [RFC4288], "VND.ExampleInc.foo") or primary domain name (e.g., "com.example.foo" or a Uniform Resource Identifier [RFC3986] such as "http://example.com/foo"). In rare cases, truly experimental parameters could be given meaningless names such as nonsense words, the output of a hash function, or Universally Unique Identifiers (UUIDs) [RFC4122].
2. When parameter names might have significant meaning. This case too is rare, since implementers can almost always find a synonym for an existing term (e.g., "urgency" instead of "priority") or simply invent a more creative name (e.g., "get-it-there-fast"). The existence of multiple similarly named parameters can be confusing, but this is true regardless if there is an attempt to segregate standardized and unstandardized parameters (e.g., "X-Priority" can be confused with "Urgency").
3. When parameter names need to be very short (e.g., as in [RFC5646] for language tags). In this case, it can be more efficient to assign numbers instead of human-readable names (e.g., as in [RFC2939] for DHCP options) and to leave a certain numeric range for implementation-specific extensions or private use (e.g., as with the codec numbers used with the Session Description Protocol [RFC4566]).

There are three primary objections to deprecating the "X-" convention as a best practice for application protocols:

1. Implementers might mistake one parameter for another parameter that has a similar name; a rigid distinction such as an "X-" prefix can make this clear. However, in practice, implementers are forced to blur the distinction (e.g., by treating "X-foo" as a de facto standard), so it inevitably becomes meaningless.
2. Collisions are undesirable, and it would be bad for both a standardized parameter "foo" and a unstandardized parameter "foo" to exist simultaneously. However, names are almost always cheap, so an experimental, implementation-specific, or private-use name of "foo" does not prevent a standards development organization from issuing a similarly creative name such as "bar".

3. [BCP82] is entitled "Assigning Experimental and Testing Numbers Considered Useful" and therefore implies that the "X-" prefix is also useful for experimental parameters. However, BCP 82 addresses the need for protocol numbers when the pool of such numbers is strictly limited (e.g., DHCP options) or when a number is absolutely required even for purely experimental purposes (e.g., the Protocol field of the IP header). In almost all application protocols that make use of protocol parameters (including email headers, media types, HTTP headers, vCard parameters and properties, URNs, and LDAP field names), the name space is not limited or constrained in any way, so there is no need to assign a block of names for private use or experimental purposes (see also [BCP26]).

Therefore, it appears that segregating the parameter space into a standardized area and a unstandardized area has few, if any, benefits and has at least one significant cost in terms of interoperability.

References

Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

Informative References

- [BCP9] Bradner, S., "The Internet Standards Process -- Revision 3", BCP 9, RFC 2026, October 1996.
- [BCP26] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 5226, May 2008.
- [BCP82] Narten, T., "Assigning Experimental and Testing Numbers Considered Useful", BCP 82, RFC 3692, January 2004.
- [RFC691] Harvey, B., "One more try on the FTP", RFC 691, June 1975.
- [RFC737] Harrenstien, K., "FTP extension: XSEN", RFC 737, October 1977.
- [RFC743] Harrenstien, K., "FTP extension: XRSQ/XRCP", RFC 743, December 1977.
- [RFC775] Mankins, D., Franklin, D., and A. Owen, "Directory oriented FTP commands", RFC 775, December 1980.

- [RFC822] Crocker, D., "Standard for the format of ARPA Internet text messages", STD 11, [RFC 822](#), August 1982.
- [RFC1123] Braden, R., "Requirements for Internet Hosts - Application and Support", STD 3, [RFC 1123](#), October 1989.
- [RFC1154] Robinson, D. and R. Ullmann, "Encoding header field for internet messages", [RFC 1154](#), April 1990.
- [RFC2045] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", [RFC 2045](#), November 1996.
- [RFC2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", [RFC 2046](#), November 1996.
- [RFC2047] Moore, K., "MIME (Multipurpose Internet Mail Extensions) Part Three: Message Header Extensions for Non-ASCII Text", [RFC 2047](#), November 1996.
- [RFC2068] Fielding, R., Gettys, J., Mogul, J., Nielsen, H., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2068](#), January 1997.
- [RFC2426] Dawson, F. and T. Howes, "vCard MIME Directory Profile", [RFC 2426](#), September 1998.
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.
- [RFC2822] Resnick, P., "Internet Message Format", [RFC 2822](#), April 2001.
- [RFC2939] Droms, R., "Procedures and IANA Guidelines for Definition of New DHCP Options and Message Types", [BCP 43](#), [RFC 2939](#), September 2000.
- [RFC3406] Daigle, L., van Gulik, D., Iannella, R., and P. Faltstrom, "Uniform Resource Names (URN) Namespace Definition Mechanisms", [BCP 66](#), [RFC 3406](#), October 2002.
- [RFC3427] Mankin, A., Bradner, S., Mahy, R., Willis, D., Ott, J., and B. Rosen, "Change Process for the Session Initiation Protocol (SIP)", [RFC 3427](#), December 2002.

- [RFC3864] Klyne, G., Nottingham, M., and J. Mogul, "Registration Procedures for Message Header Fields", [BCP 90](#), [RFC 3864](#), September 2004.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC4122] Leach, P., Mealling, M., and R. Salz, "A Universally Unique IDentifier (UUID) URN Namespace", [RFC 4122](#), July 2005.
- [RFC4288] Freed, N. and J. Klensin, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 4288](#), December 2005.
- [RFC4395] Hansen, T., Hardie, T., and L. Masinter, "Guidelines and Registration Procedures for New URI Schemes", [BCP 35](#), [RFC 4395](#), February 2006.
- [RFC4512] Zeilenga, K., "Lightweight Directory Access Protocol (LDAP): Directory Information Models", [RFC 4512](#), June 2006.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.
- [RFC5064] Duerst, M., "The Archived-At Message Header Field", [RFC 5064](#), December 2007.
- [RFC5451] Kucherawy, M., "Message Header Field for Indicating Message Authentication Status", [RFC 5451](#), April 2009.
- [RFC5545] Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", [RFC 5545](#), September 2009.
- [RFC5646] Phillips, A. and M. Davis, "Tags for Identifying Languages", [BCP 47](#), [RFC 5646](#), September 2009.
- [RFC5727] Peterson, J., Jennings, C., and R. Sparks, "Change Process for the Session Initiation Protocol (SIP) and the Real-time Applications and Infrastructure Area", [BCP 67](#), [RFC 5727](#), March 2010.

Authors' Addresses

Peter Saint-Andre
Cisco Systems, Inc.
1899 Wynkoop Street, Suite 600
Denver, CO 80202
USA

Phone: +1-303-308-3282
EMail: psaintan@cisco.com

Dave Crocker
Brandenburg InternetWorking
675 Spruce Dr.
Sunnyvale, CA
USA

Phone: +1.408.246.8253
EMail: dcrocker@bbiw.net
URI: <http://bbiw.net>

Mark Nottingham
Rackspace

EMail: mnot@mnot.net
URI: <http://www.mnot.net>