

Network Working Group
Request for Comments: 3485
Category: Standards Track

M. Garcia-Martin
Ericsson
C. Bormann
J. Ott
TZI/Uni Bremen
R. Price
Siemens/Roke Manor
A. B. Roach
dynamicsoft
February 2003

The Session Initiation Protocol (SIP) and Session Description Protocol
(SDP) Static Dictionary for Signaling Compression (SigComp)

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

Abstract

The Session Initiation Protocol (SIP) is a text-based protocol for initiating and managing communication sessions. The protocol can be compressed by using Signaling Compression (SigComp). Similarly, the Session Description Protocol (SDP) is a text-based protocol intended for describing multimedia sessions for the purposes of session announcement, session invitation, and other forms of multimedia session initiation. This memo defines the SIP/SDP-specific static dictionary that SigComp may use in order to achieve higher efficiency. The dictionary is compression algorithm independent.

Table of Contents

1. Introduction.....	2
2. Design considerations.....	3
3. Binary representation of the SIP/SDP dictionary.....	5
4. Security Considerations.....	13
5. IANA Considerations.....	13
6. Acknowledgements.....	14
7. References.....	14
7.1 Normative References.....	14
7.2 Informative References.....	14
Appendix A. SIP input strings to the SIP/SDP static dictionary.....	17
Appendix B. SDP input strings to the SIP/SDP static dictionary.....	26
Authors' Addresses.....	29
Full Copyright Statement.....	30

1. Introduction

SIP [3] and SDP [24] are text-based protocols that use the UTF-8 charset (RFC 2279 [5]). SIP and SDP were designed for rich bandwidth links. However, when SIP/SDP is run over narrow bandwidth links, such as radio interfaces or low speed serial links, the session setup time increases substantially, compared to an operation over a rich bandwidth link.

The session setup time can decrease dramatically if the SIP/SDP signaling is compressed. The signaling compression mechanisms specified in SigComp [1] provide a multiple compression/decompression algorithm framework to compress and decompress text-based protocols such as SIP and SDP.

When compression is used in SIP/SDP, the compression achieves its maximum rate once a few message exchanges have taken place. This is due to the fact that the first message the compressor sends to the decompressor is only partially compressed, as there is not a previous stored state to compress against. As the goal is to reduce the session setup time as much as possible, it seems sensible to investigate a mechanism to boost the compression rate from the first message.

In this memo we introduce the static dictionary for SIP and SDP. The dictionary is to be used in conjunction with SIP, SDP and SigComp. The static SIP/SDP dictionary constitutes a SigComp state that can be referenced in the first SIP message that the compressor sends out.

2. Design considerations

The static SIP/SDP dictionary is a collection of well-known strings that appear in most of the SIP and SDP messages. The dictionary is not a comprehensive list of reserved words, but it includes many of the strings that appear in SIP and SDP signaling.

The static dictionary is unique and MUST be available in all SigComp implementations for SIP/SDP. The dictionary is not intended to evolve as SIP or SDP evolve. It is defined once, and stays as is forever. This solves the problems of updating, upgrading and finding out the dictionary that is supported at the remote end when several versions of the same dictionary coexist.

[Appendix A](#) contains the collection of strings that SIP contributed to the static dictionary. The appendix includes references to the documents that define those strings.

[Appendix B](#) contains the collection of strings that SDP contributed to the static dictionary. Again, the appendix includes references to the documents that define those strings.

While these appendices are of an informative nature, [Section 3](#) gives the normative binary form of the SIP/SDP dictionary. This is the dictionary that is included in the SigComp implementation. This dictionary has been formed from the collection of individual dictionaries given in appendices A and B.

The two input collections are collections of UTF-8 encoded character strings. In order to facilitate the readability, the appendices describe them in one table for each collection. In these tables, each row represents an entry. Each entry contains the string that actually occurs in the dictionary, its priority (see below), its offset from the first octet and its length (both in hexadecimal), and one or more references that elucidate why this string is expected to occur in SIP/SDP messages. Note: Length in this document always refers to octets.

The columns in the tables are described as follows:

String: represents the UTF-8 string that is inserted into the dictionary. Note that the quotes (") are not part of the string itself. Note also that the notation [CRLF] represents a Carriage Return character (ASCII code 0x0D) followed by a Line Feed character (ASCII code 0x0A).

Pr: indicates the priority of this string within the dictionary. Some compression algorithms, such as DEFLATE, offer an increased efficiency when the most commonly used strings are located at the bottom of the dictionary. To facilitate generating a dictionary that has the most frequently occurring strings further down at the bottom, we have decided to allocate a priority to each string in the dictionary. Priorities range from 1 until 5. A low number in the priority column (e.g., 1) indicates that we believe in a high probability of finding the string in SIP or SDP messages. A high number in the priority column (e.g., 5) indicates lower probability of finding the string in a SIP or SDP message. This is typically the case for less frequent error codes or optional infrequent tags.

Off: indicates the hexadecimal offset of the entry with respect to the first octet in the dictionary. Note that several strings in the collections can share space in the dictionary if they exhibit suitable common substrings.

Len: the length of the string (in octets, in hexadecimal).

References: contains one or more references to the specification and the section within the specification where the string is defined.

Note that the strings stored in the dictionary are case sensitive. (Again, the strings do not comprise the quotes ("), they are just shown here to increase the readability.) Where the string is a header field, we also included the colon ":" and the amount of white space expected to occur. Note that this means that not all messages that conform to the SIP Augmented BNF, which allows other combinations (e.g., a white space or horizontal tabulator before the colon (":") sign), will benefit as much from the dictionary -- the best increase in compression performance is to be expected for messages that use the recommended formatting guidelines for SIP.

Some strings appear followed by an equal sign and some others do not. This depends on whether the string is part of a parameter name or a parameter value.

In a SIP message, all the SIP headers terminate with a CRLF pair of characters. As these characters are appended to the end of each SIP header line, right after the header values, and because the header values are typically not part of the static SIP dictionary, we cannot include the terminating CRLF as part of the SIP static dictionary. Instead, the approach we have taken is to include in each header field entry the CRLF from the previous line that prefixes every header field. We have represented CRLF by the notation [CRLF]. Therefore, in generating the actual binary dictionary, an entry in the dictionary represented as: "[CRLF]From: " has been interpreted as

an entry whose value is CR, LF, the word From, a colon and a whitespace.

Note that most SIP header field names are included with the full string from CRLF to the colon-blank pair. However, in certain situations, when the likelihood of occurrence is not considered high (as indicated by a priority value of 3 to 5), and when there are common substrings shared by a number of headers, we have added one entry with the common substring and several entries with the non-common substrings remaining. An example is the "Proxy-Authenticate" and "Proxy-Authorization" headers. There are three entries in the dictionary: the common substring "[CRLF]Proxy-", and the non-common substrings "Authenticate: " and "Authorization: ". This allows the re-use of the non-common substrings by other entries and may save a number of bytes in the binary form of the dictionary. Note that this splitting mechanism does not apply with strings that are likely to occur very often (those whose priority is set to 1 or 2).

SIP responses start with a status code (e.g., "302") and a reason phrase (e.g., "Moved Temporarily"). The status code is a normative part, whereas the reason phrase is not normative, it is just a suggested text. For instance, both "302 Moved Temporarily" and "302 Redirect" are valid beginnings of SIP responses.

In the SIP dictionary we have included two entries per response code, one including only the status code and a space (e.g., "302 ") and another one including both the status code and the suggested reason phrase (e.g., "302 Moved Temporarily"). The former can be used when the SIP response changed the suggested reason phrase to another one. The latter can be used when the suggested reason phrase is part of the response. In this way, we accommodate both alternatives. (Note that in the actual dictionary, both strings occupy the same space in the string subset, but have two separate entries in the table subset.)

3. Binary representation of the SIP/SDP dictionary

This section contains the result of combining the SIP and the SDP dictionaries described in appendices A and B in order to create a single dictionary that is loaded into SigComp as a state.

The binary SigComp dictionary is comprised of two parts, the concatenation of which serves as the state value of the state item: A string subset, which contains all strings in the contributing collections as a substring (roughly ordered such that strings with low priority numbers occur at the end), and a table subset, which contains pairs of length and offset values for all the strings in the contributing collections. In each of these pairs, the length is

stored as a one-byte value, and the offset is stored as a two-byte value that has had 1024 added to the offset (this allows direct referencing from the stored value if the dictionary state has been loaded at address 1024).

The intention is that all compression algorithms will be able to use the (or part of the) string subset, and some compression methods, notably those that are related to the LZ78 family, will also use the table in order to form an initial set of tokens for that compression method. The text below therefore gives examples for referencing both the table subset and the string subset of the dictionary state item.

As defined in [section 3.3.3](#) in the Signaling Compression specification [1], a SigComp state is characterized by a certain set of information. For the static SIP/SDP dictionary, the information in the following Table 1 fully characterizes the state item.

Note that the string subset of the dictionary can be accessed using:

```
STATE-ACCESS (%ps, 6, 0, 0x0D8C, %sa, 0),
```

and the table subset can be accessed using:

```
STATE-ACCESS (%ps, 6, 0x0D8C, 0x0558, %sa, 0),
```

where %ps points to UDVM memory containing

```
0xfbe507dfe5e6
```

and %sa is the desired destination address in UDVM memory (with UDVM byte copying rules applied).

If only a subset of the dictionary up to a specific priority is desired (e.g., to save UDVM space), the values for the third and forth operand in these STATE-ACCESS instructions can be changed to:

Priorities	String	String	Table	Table
desired	offset	length	offset	length
=====	=====	=====	=====	=====
1 only	0x0CB2	0x00DA	0x0D8C	0x003F
1..2	0x0920	0x046C	0x0D8C	0x0147
1..3	0x07B8	0x05D4	0x0D8C	0x01A7
1..4	0x0085	0x0D07	0x0D8C	0x044A
1..5	0x0000	0x0D8C	0x0D8C	0x0558

The state item consists of the following elements:

Name:	Value:
state_identifier	0xfbe507dfe5e6aa5af2abb914ceaa05f99ce61ba5
state_length	0x12E4
state_address	0 (not relevant for the dictionary)
state_instruction	0 (not relevant for the dictionary)
minimum_access_length	6
state_value	Representation of the table below.

0000	0d0a	5265	6a65	6374	2d43	6f6e	7461	6374	..Reject-Contact
0010	3a20	0d0a	4572	726f	722d	496e	666f	3a20	: ..Error-Info:
0020	0d0a	5469	6d65	7374	616d	703a	200d	0a43	..Timestamp: ..C
0030	616c	6c2d	496e	666f	3a20	0d0a	5265	706c	all-Info: ..Repl
0040	792d	546f	3a20	0d0a	5761	726e	696e	673a	y-To: ..Warning:
0050	200d	0a53	7562	6a65	6374	3a20	3b68	616e	..Subject: ;han
0060	646c	696e	673d	696d	6167	653b	7075	7270	dling=image;purp
0070	6f73	653d	3b63	6175	7365	3d3b	7465	7874	ose=;cause=;text
0080	3d63	6172	6433	3030	204d	756c	7469	706c	=card300 Multipl
0090	6520	4368	6f69	6365	736d	696d	6573	7361	e Choicesmimessa
00A0	6765	2f73	6970	6672	6167	3430	3720	5072	ge/sipfrag407 Pr
00B0	6f78	7920	4175	7468	656e	7469	6361	7469	oxy Authenticati
00C0	6f6e	2052	6571	7569	7265	6469	6765	7374	on Requiredigest
00D0	2d69	6e74	6567	7269	7479	3438	3420	4164	-integrity484 Ad
00E0	6472	6573	7320	496e	636f	6d70	6c65	7465	dress Incomplete
00F0	6c65	7068	6f6e	652d	6576	656e	7473	3439	lephone-events49
0100	3420	5365	6375	7269	7479	2041	6772	6565	4 Security Agree
0110	6d65	6e74	2052	6571	7569	7265	6465	6163	ment Requiredeac
0120	7469	7661	7465	6434	3831	2043	616c	6c2f	tivated481 Call/
0130	5472	616e	7361	6374	696f	6e20	446f	6573	Transaction Does
0140	204e	6f74	2045	7869	7374	616c	653d	3530	Not Existale=50
0150	3020	5365	7276	6572	2049	6e74	6572	6e61	0 Server Interna
0160	6c20	4572	726f	726f	6275	7374	2d73	6f72	l Errorobust-sor
0170	7469	6e67	3d34	3136	2055	6e73	7570	706f	ting=416 Unsuppo
0180	7274	6564	2055	5249	2053	6368	656d	6572	rted URI Schemer
0190	6765	6e63	7934	3135	2055	6e73	7570	706f	gency415 Unsuppo
01A0	7274	6564	204d	6564	6961	2054	7970	656e	rted Media Typen
01B0	6469	6e67	3438	3820	4e6f	7420	4163	6365	ding488 Not Acce
01C0	7074	6162	6c65	2048	6572	656a	6563	7465	ptable Herejecte
01D0	6434	3233	2049	6e74	6572	7661	6c20	546f	d423 Interval To
01E0	6f20	4272	6965	6672	6f6d	2d74	6167	512e	o Brieffrom-tagQ.
01F0	3835	3035	2056	6572	7369	6f6e	204e	6f74	8505 Version Not
0200	2053	7570	706f	7274	6564	3430	3320	466f	Supported403 Fo
0210	7262	6964	6465	6e6f	6e2d	7572	6765	6e74	rbiddenon-urgent
0220	3432	3920	5072	6f76	6964	6520	5265	6665	429 Provide Refe
0230	7272	6f72	2049	6465	6e74	6974	7934	3230	rror Identity420
0240	2042	6164	2045	7874	656e	7369	6f6e	6f72	Bad Extensionor

0250	6573	6f75	7263	650d	0a61	3d6b	6579	2d6d	esource..a=key-m
0260	676d	743a	6d69	6b65	794f	5054	494f	4e53	gmt:mikeyOPTIONS
0270	204c	616e	6775	6167	653a	2035	3034	2053	Language: 504 S
0280	6572	7665	7220	5469	6d65	2d6f	7574	6f2d	erver Time-ouo-
0290	7461	670d	0a41	7574	6865	6e74	6963	6174	tag..Authenticat
02A0	696f	6e2d	496e	666f	3a20	4465	6320	3338	ion-Info: Dec 38
02B0	3020	416c	7465	726e	6174	6976	6520	5365	0 Alternative Se
02C0	7276	6963	6535	3033	2053	6572	7669	6365	rvice503 Service
02D0	2055	6e61	7661	696c	6162	6c65	3432	3120	Unavailable421
02E0	4578	7465	6e73	696f	6e20	5265	7175	6972	Extension Requir
02F0	6564	3430	3520	4d65	7468	6f64	204e	6f74	ed405 Method Not
0300	2041	6c6c	6f77	6564	3438	3720	5265	7175	Allowed487 Requ
0310	6573	7420	5465	726d	696e	6174	6564	6175	est Terminatedau
0320	7468	2d69	6e74	6572	6c65	6176	696e	673d	th-interleaving=
0330	0d0a	6d3d	6170	706c	6963	6174	696f	6e20	..m=application
0340	4175	6720	3531	3320	4d65	7373	6167	6520	Aug 513 Message
0350	546f	6f20	4c61	7267	6536	3837	2044	6961	Too Large687 Dia
0360	6c6f	6720	5465	726d	696e	6174	6564	3330	log Terminated30
0370	3220	4d6f	7665	6420	5465	6d70	6f72	6172	2 Moved Temporar
0380	696c	7933	3031	204d	6f76	6564	2050	6572	ily301 Moved Per
0390	6d61	6e65	6e74	6c79	6d75	6c74	6970	6172	manentlymultipar
03A0	742f	7369	676e	6564	0d0a	5265	7472	792d	t/signed..Retry-
03B0	4166	7465	723a	2047	4d54	6875	2c20	3430	After: GMThu, 40
03C0	3220	5061	796d	656e	7420	5265	7175	6972	2 Payment Requir
03D0	6564	0d0a	613d	6f72	6965	6e74	3a6c	616e	ed..a=orient:lan
03E0	6473	6361	7065	3430	3020	4261	6420	5265	dscape400 Bad Re
03F0	7175	6573	7472	7565	3439	3120	5265	7175	questtrue491 Requ
0400	6573	7420	5065	6e64	696e	6735	3031	204e	est Pending501 N
0410	6f74	2049	6d70	6c65	6d65	6e74	6564	3430	ot Implemented40
0420	3620	4e6f	7420	4163	6365	7074	6162	6c65	6 Not Acceptable
0430	3630	3620	4e6f	7420	4163	6365	7074	6162	606 Not Acceptab
0440	6c65	0d0a	613d	7479	7065	3a62	726f	6164	le..a=type:broad
0450	6361	7374	6f6e	6534	3933	2055	6e64	6563	castone493 Undec
0460	6970	6865	7261	626c	650d	0a4d	494d	452d	ipherable..MIME-
0470	5665	7273	696f	6e3a	204d	6179	2034	3832	Version: May 482
0480	204c	6f6f	7020	4465	7465	6374	6564	0d0a	Loop Detected..
0490	4f72	6761	6e69	7a61	7469	6f6e	3a20	4a75	Organization: Ju
04A0	6e20	6d6f	6465	2d63	6861	6e67	652d	6e65	n mode-change-ne
04B0	6967	6862	6f72	3d63	7269	7469	6361	6c65	ighbor=criticale
04C0	7274	6370	2d66	6234	3839	2042	6164	2045	rtcp-fb489 Bad E
04D0	7665	6e74	6c73	0d0a	556e	7375	7070	6f72	ventls..Unsuppor
04E0	7465	643a	204a	616e	2035	3032	2042	6164	ted: Jan 502 Bad
04F0	2047	6174	6577	6179	6d6f	6465	2d63	6861	Gatewaymode-cha
0500	6e67	652d	7065	7269	6f64	3d0d	0a61	3d6f	nge-period=..a=o
0510	7269	656e	743a	7365	6173	6361	7065	0d0a	rient:seascape..
0520	613d	7479	7065	3a6d	6f64	6572	6174	6564	a=type:moderated
0530	3430	3420	4e6f	7420	466f	756e	6433	3035	404 Not Found305
0540	2055	7365	2050	726f	7879	0d0a	613d	7479	Use Proxy..a=ty


```

0550 7065 3a72 6563 766f 6e6c 790d 0a61 3d74 pe:recvonly..a=t
0560 7970 653a 6d65 6574 696e 670d 0a6b 3d70 ype:meeting..k=p
0570 726f 6d70 743a 0d0a 5265 6665 7272 6564 rompt:..Referred
0580 2d42 793a 200d 0a49 6e2d 5265 706c 792d -By: ..In-Reply-
0590 546f 3a20 5452 5545 6e63 6f64 696e 673a To: TRUEncoding:
05A0 2031 3832 2051 7565 7565 6441 7574 6865 182 QueuedAuthe
05B0 6e74 6963 6174 653a 200d 0a55 7365 722d nticate: ..User-
05C0 4167 656e 743a 200d 0a61 3d66 7261 6d65 Agent: ..a=frame
05D0 7261 7465 3a0d 0a41 6c65 7274 2d49 6e66 rate:..Alert-Inf
05E0 6f3a 2043 414e 4345 4c20 0d0a 613d 6d61 o: CANCEL ..a=ma
05F0 7870 7469 6d65 3a3b 7265 7472 792d 6166 xptime;;retry-af
0600 7465 723d 7561 6368 616e 6e65 6c73 3d34 ter=uachannels=4
0610 3130 2047 6f6e 650d 0a52 6566 6572 2d54 10 Gone..Refer-T
0620 6f3a 200d 0a50 7269 6f72 6974 793a 200d o: ..Priority: .
0630 0a6d 3d63 6f6e 7472 6f6c 200d 0a61 3d71 .m=control ..a=q
0640 7561 6c69 7479 3a0d 0a61 3d73 6470 6c61 uality:..a=sdpla
0650 6e67 3a0d 0a61 3d63 6861 7273 6574 3a0d ng:..a=charset:.
0660 0a52 6570 6c61 6365 733a 2052 4546 4552 .Replaces: REFER
0670 2069 7073 6563 2d69 6b65 3b74 7261 6e73 ipsec-ike;trans
0680 706f 7274 3d0d 0a61 3d6b 6579 7764 733a port=..a=keywds:
0690 0d0a 6b3d 6261 7365 3634 3a3b 7265 6672 ..k=base64;;refr
06A0 6573 6865 723d 0d0a 613d 7074 696d 653a esher=..a=ptime:
06B0 0d0a 6b3d 636c 6561 723a 3b72 6563 6569 ..k=clear;;recei
06C0 7665 643d 3b64 7572 6174 696f 6e3d 0d0a ved=;duration=..
06D0 4163 6365 7074 3a20 0d0a 613d 6772 6f75 Accept: ..a=grou
06E0 703a 4641 4c53 453a 2049 4e46 4f20 0d0a p:FALSE: INFO ..
06F0 4163 6365 7074 2d0d 0a61 3d6c 616e 673a Accept-..a=lang:
0700 0d0a 6d3d 6461 7461 206d 6f64 652d 7365 ..m=data mode-se
0710 743d 0d0a 613d 746f 6f6c 3a54 4c53 756e t=..a=tool:TLSun
0720 2c20 0d0a 4461 7465 3a20 0d0a 613d 6361 , ..Date: ..a=ca
0730 743a 0d0a 6b3d 7572 693a 0d0a 5072 6f78 t:..k=uri:..Prox
0740 792d 3b72 6561 736f 6e3d 3b6d 6574 686f y-;reason=;metho
0750 643d 0d0a 613d 6d69 643a 3b6d 6164 6472 d=..a=mid;;maddr
0760 3d6f 7061 7175 653d 0d0a 4d69 6e2d 3b61 =opaque=..Min-;a
0770 6c67 3d4d 6f6e 2c20 5475 652c 2057 6564 lg=Mon, Tue, Wed
0780 2c20 4672 692c 2053 6174 2c20 3b74 746c , Fri, Sat, ;ttl
0790 3d61 7574 733d 0d0a 723d 0d0a 7a3d 0d0a =auts=..r=..z=..
07A0 653d 3b69 643d 0d0a 693d 6372 633d 0d0a e;;id=..i=crc=..
07B0 753d 3b71 3d75 6173 3431 3420 5265 7175 u;;q=uas414 Requ
07C0 6573 742d 5552 4920 546f 6f20 4c6f 6e67 est-URI Too Long
07D0 6976 6575 7072 6976 6163 7975 6470 7265 iveuprivacyudpre
07E0 6665 7236 3030 2042 7573 7920 4576 6572 fer600 Busy Ever
07F0 7977 6865 7265 7175 6972 6564 3438 3020 ywhererequired480
0800 5465 6d70 6f72 6172 696c 7920 556e 6176 Temporarily Unav
0810 6169 6c61 626c 650d 0a61 3d74 7970 653a ailable..a=type:
0820 482e 3333 3230 3220 4163 6365 7074 6564 H.33202 Accepted
0830 0d0a 5365 7373 696f 6e2d 4578 7069 7265 ..Session-Expire
0840 733a 200d 0a53 7562 7363 7269 7074 696f s: ..Subscriptio

```

```

0850 6e2d 5374 6174 653a 204e 6f76 200d 0a53 n-State: Nov ..S
0860 6572 7669 6365 2d52 6f75 7465 3a20 5365 ervice-Route: Se
0870 7020 0d0a 416c 6c6f 772d 4576 656e 7473 p ..Allow-Events
0880 3a20 4665 6220 0d0a 613d 696e 6163 7469 : Feb ..a=inacti
0890 7665 5254 502f 5341 5650 2052 5450 2f41 veRTP/SAVP RTP/A
08A0 5650 4620 416e 6f6e 796d 6f75 7369 7073 VPF Anonymousips
08B0 3a0d 0a61 3d74 7970 653a 7465 7374 656c :..a=type:testel
08C0 3a4d 4553 5341 4745 200d 0a61 3d72 6563 :MESSAGE ..a=rec
08D0 766f 6e6c 790d 0a61 3d73 656e 646f 6e6c vonly..a=sendonl
08E0 790d 0a63 3d49 4e20 4950 3420 0d0a 5265 y..c=IN IP4 ..Re
08F0 6173 6f6e 3a20 0d0a 416c 6c6f 773a 200d ason: ..Allow: .
0900 0a45 7665 6e74 3a20 0d0a 5061 7468 3a20 .Event: ..Path:
0910 3b75 7365 723d 0d0a 623d 4153 2043 5420 ;user=..b=AS CT
0920 0d0a 5757 572d 4175 7468 656e 7469 6361 ..WWW-Authentica
0930 7465 3a20 4469 6765 7374 200d 0a61 3d73 te: Digest ..a=s
0940 656e 6472 6563 7669 6465 6f63 7465 742d endrecvideoctet-
0950 616c 6967 6e3d 6170 706c 6963 6174 696f align=applicatio
0960 6e2f 7364 7061 7468 6561 6465 7273 7061 n/sdpatheaderspa
0970 7574 683d 0d0a 613d 6f72 6965 6e74 3a70 uth=..a=orient:p
0980 6f72 7472 6169 7469 6d65 6f75 7474 722d ortraitimeouttr-
0990 696e 7469 636f 6e63 3d34 3833 2054 6f6f inticonc=483 Too
09A0 204d 616e 7920 486f 7073 6c69 6e66 6f70 Many Hopslinfop
09B0 7469 6f6e 616c 676f 7269 7468 6d3d 3630 tionalgorithm=60
09C0 3420 446f 6573 204e 6f74 2045 7869 7374 4 Does Not Exist
09D0 2041 6e79 7768 6572 6573 706f 6e73 653d Anywheresponse=
09E0 0d0a 0d0a 5265 7175 6573 742d 4469 7370 ....Request-Disp
09F0 6f73 6974 696f 6e3a 204d 4435 3830 2050 osition: MD580 P
0A00 7265 636f 6e64 6974 696f 6e20 4661 696c recondition Fail
0A10 7572 6570 6c61 6365 7334 3232 2053 6573 ureplaces422 Ses
0A20 7369 6f6e 2049 6e74 6572 7661 6c20 546f sion Interval To
0A30 6f20 536d 616c 6c6f 6361 6c31 3831 2043 o Smallocal181 C
0A40 616c 6c20 4973 2042 6569 6e67 2046 6f72 all Is Being For
0A50 7761 7264 6564 6f6d 6169 6e3d 6661 696c wardedomain=fail
0A60 7572 656e 6465 7265 616c 6d3d 5355 4253 urenderealm=SUBS
0A70 4352 4942 4520 7072 6563 6f6e 6469 7469 CRIBE preconditi
0A80 6f6e 6f72 6d61 6c69 7073 6563 2d6d 616e onormalipsec-man
0A90 6461 746f 7279 3431 3320 5265 7175 6573 datory413 Reques
0AA0 7420 456e 7469 7479 2054 6f6f 204c 6172 t Entity Too Lar
0AB0 6765 3265 3138 3320 5365 7373 696f 6e20 ge2e183 Session
0AC0 5072 6f67 7265 7373 6374 7034 3836 2042 Progressctp486 B
0AD0 7573 7920 4865 7265 6d6f 7465 726d 696e usy Heremotermin
0AE0 6174 6564 414b 4176 312d 4d44 352d 7365 atedAKAv1-MD5-se
0AF0 7373 696f 6e6f 6e65 0d0a 4175 7468 6f72 ssionone..Author
0B00 697a 6174 696f 6e3a 2036 3033 2044 6563 ization: 603 Dec
0B10 6c69 6e65 7874 6e6f 6e63 653d 3438 3520 linextnonce=485
0B20 416d 6269 6775 6f75 7365 726e 616d 653d Ambiguoususername=
0B30 6175 6469 6f0d 0a43 6f6e 7465 6e74 2d54 audio..Content-T
0B40 7970 653a 204d 6172 200d 0a52 6563 6f72 ype: Mar ..Recor

```

0B50	642d	526f	7574	653a	204a	756c	2034	3031	d-Route: Jul 401
0B60	2055	6e61	7574	686f	7269	7a65	640d	0a52	Unauthorized..R
0B70	6571	7569	7265	3a20	0d0a	743d	3020	302e	equire: ..t=0 0.
0B80	302e	302e	300d	0a53	6572	7665	723a	2052	0.0.0..Server: R
0B90	4547	4953	5445	5220	0d0a	633d	494e	2049	EGISTER ..c=IN I
0BA0	5036	2031	3830	2052	696e	6769	6e67	3130	P6 180 Ringing10
0BB0	3020	5472	7969	6e67	763d	300d	0a6f	3d55	0 Tryingv=0..o=U
0BC0	5044	4154	4520	4e4f	5449	4659	200d	0a53	PDATE NOTIFY ..S
0BD0	7570	706f	7274	6564	3a20	756e	6b6e	6f77	upported: unknow
0BE0	6e41	4d52	5450	2f41	5650	200d	0a50	7269	nAMRTP/AVP ..Pri
0BF0	7661	6379	3a20	0d0a	5365	6375	7269	7479	vacy: ..Security
0C00	2d0d	0a45	7870	6972	6573	3a20	0d0a	613d	-..Expires: ..a=
0C10	7274	706d	6170	3a0d	0a6d	3d76	6964	656f	rtpmap:..m=video
0C20	200d	0a6d	3d61	7564	696f	200d	0a73	3d20	..m=audio ..s=
0C30	6661	6c73	650d	0a61	3d63	6f6e	663a	3b65	false..a=conf:;e
0C40	7870	6972	6573	3d0d	0a52	6f75	7465	3a20	xpires=..Route:
0C50	0d0a	613d	666d	7470	3a0d	0a61	3d63	7572	..a=fmtp:..a=cur
0C60	723a	436c	6965	6e74	3a20	5665	7269	6679	r:Client: Verify
0C70	3a20	0d0a	613d	6465	733a	0d0a	5241	636b	: ..a=des:..Rack
0C80	3a20	0d0a	5253	6571	3a20	4259	4520	636e	: ..RSeq: BYE cn
0C90	6f6e	6365	3d31	3030	7265	6c75	7269	3d71	once=100reluri=q
0CA0	6f70	3d54	4350	5544	5071	6f73	786d	6c3b	op=TCPUDPqosxml;
0CB0	6c72	0d0a	5669	613a	2053	4950	2f32	2e30	lr..Via: SIP/2.0
0CC0	2f54	4350	2034	3038	2052	6571	7565	7374	/TCP 408 Request
0CD0	2054	696d	656f	7574	696d	6572	7073	6970	Timeouttimerpsip
0CE0	3a0d	0a43	6f6e	7465	6e74	2d4c	656e	6774	:..Content-Lengt
0CF0	683a	204f	6374	200d	0a56	6961	3a20	5349	h: Oct ..Via: SI
0D00	502f	322e	302f	5544	5020	3b63	6f6d	703d	P/2.0/UDP ;comp=
0D10	7369	6763	6f6d	7072	6f62	6174	696f	6e61	sigcomprobationa
0D20	636b	3b62	7261	6e63	683d	7a39	6847	3462	ck;branch=z9hG4b
0D30	4b0d	0a4d	6178	2d46	6f72	7761	7264	733a	K..Max-Forwards:
0D40	2041	7072	2053	4354	5052	4143	4b20	494e	Apr SCTPRACK IN
0D50	5649	5445	200d	0a43	616c	6c2d	4944	3a20	VITE ..Call-ID:
0D60	0d0a	436f	6e74	6163	743a	2032	3030	204f	..Contact: 200 O
0D70	4b0d	0a46	726f	6d3a	200d	0a43	5365	713a	K..From: ..CSeq:
0D80	200d	0a54	6f3a	203b	7461	673d	0410	dd10	..To: ;tag=....
0D90	1131	0d11	0a07	10b9	0c10	fe12	10e1	0611	.1.....
0DA0	4e07	114e	0311	4a04	114a	0710	b208	1179	N..N..J..J....y
0DB0	0611	810f	1122	0b11	5506	116b	0b11	6013"..U..k..`.
0DC0	10b2	0811	7105	1187	1310	f709	0e8d	080dq.....
0DD0	ae0c	10b9	0710	8e03	0d96	0310	8a04	108a
0DE0	090d	d70a	0f12	080f	8f09	0f8f	080d	6c06l.
0DF0	0e66	090e	6c0a	0e6c	060f	c607	0fc6	0511	.f..l..l.....
0E00	4806	1148	060f	bf07	0fbf	070e	5506	0f16	H..H.....U...
0E10	040e	f403	0eb1	0310	a609	1050	0310	a30aP....
0E20	0db4	050e	3606	0ed6	030d	f911	0ef8	040c6.....
0E30	d908	0eea	0409	5303	0a4b	040e	e410	0f35S..K.....5
0E40	090e	e408	0d3f	030f	e10b	1001	0310	ac06?.....

0E50	1095	0c0e	760b	0feb	0a0f	ae05	102b	0410v.....+..
0E60	2b08	107a	100f	4907	0fb8	0910	3e0b	100c	+..z..I.....>...
0E70	070f	780b	0f6d	0910	4708	1082	0b0f	f608	..x..m..G.....
0E80	1062	080f	8708	106a	040f	780d	0fcd	080d	.b.....j..x.....
0E90	ae10	0f5d	0b0f	9814	0d20	1b0d	2004	0de0	...]
0EA0	140e	b40b	0fa3	0b07	340f	0d56	040e	f4034..V....
0EB0	10af	070d	3409	0f27	0410	9b04	109f	09104..'.....
0EC0	5908	1072	0910	350a	1021	0a10	1708	0fe3	Y..r..5..!.....
0ED0	0310	a905	0cac	040c	bd07	0cc1	080c	c109
0EE0	0cf6	100c	720c	0c86	040d	640c	0cd5	090cr.....d.....
0EF0	ff1b	0bfc	110c	5d13	0c30	090c	a40c	0c24] ..0.....\$
0F00	0c0d	3b03	0d1a	030d	1d16	0c43	090c	9209	..i.....C....
0F10	0c9b	0d0e	cb04	0d16	060d	1005	04f2	0b0c
0F20	e105	0bde	0a0c	ec13	0be3	070b	d408	0d08
0F30	0c0c	c909	0c3a	040a	e50c	0a23	080b	3a0e:.....#...:
0F40	09ab	0f0e	fa09	0f6f	0c0a	170f	0976	0c0ao.....v..
0F50	5f17	0de2	0f07	a80a	0f85	0f08	d60e	09b9	_.....
0F60	0b0a	7a03	0bdb	0308	c104	0ec7	0308	d302	..z.....
0F70	048d	080b	4a05	0b8c	070b	6106	0548	0407J.....a..H..
0F80	f405	1030	0407	1e08	071e	050b	9110	04ca	...0.....
0F90	090a	7109	0e87	0504	9805	0b6e	0b04	9b0f	..q.....n....
0FA0	049b	0704	9b03	04a3	0704	a310	0798	0907
0FB0	9805	0b73	050b	7805	0b7d	0507	b905	0b82	...s..x..}.....
0FC0	050b	8705	0b1d	0508	e405	0c81	050f	4405D.
0FD0	1140	0508	7805	089d	050f	5805	073f	050c	..@..x.....X..?..
0FE0	6d05	10f2	050c	5805	06a9	0407	b609	058c	m.....X.....
0FF0	0606	1a06	0e81	0a06	160a	0ac4	070b	5a0aZ.
1000	0aba	030b	1b04	1145	060c	8c07	05ad	0a0eE.....
1010	da08	0b42	0d09	f70b	051c	0911	1608	05c9	...B.....
1020	070d	8606	0bcf	0a06	4d04	0ba2	0606	8d08M.....
1030	05e6	080e	110b	0a9b	030a	0403	0bb5	0510
1040	d704	0994	050a	e203	0bb2	060d	6704	0d11g...
1050	0808	b71b	0e3b	0a09	a114	0485	1507	8315i.....
1060	076e	0d09	3d17	06ae	0f07	e614	07be	0d06	..n..=.....
1070	0a0d	0930	1606	f212	081e	2104	aa13	10c5	...0.....!.....
1080	080a	0f1c	0e96	180b	b81a	0595	1a05	7511u.
1090	063d	1606	dc1e	0e19	1605	d11d	0620	2305	..=..... #.
10A0	2711	087d	110d	9916	04da	0d0f	1c16	0708	'...}.....
10B0	1705	b40d	08c7	1307	f812	0857	1f04	fe19W....
10C0	054e	1308	0b0f	08e9	1706	c513	067b	1905	..N.....{..
10D0	f115	0744	180d	fb0b	0f09	1b0d	be12	0830	...D.....0
10E0	1507	5904	0ba6	040b	ae04	0b9e	040b	9604	..Y.....
10F0	0b9a	0a0a	b00b	0a90	080b	320b	096b	080b2..k..
1100	2a0b	0a85	090b	120a	0aa6	0d09	ea13	0d74	*.....t
1110	1407	d213	090b	1208	4210	095b	1209	1e0dB..[....
1120	0cb1	0e0c	1711	094a	0c0a	530c	0a47	090aJ..S..G..
1130	f70e	09c7	0c0a	3b07	0669	0806	6906	09e3i..i.i...
1140	080b	520a	0ad8	1206	570d	0657	0709	e304	..R.....W..W....

```

1150 0ae9 1007 3009 0b00 0c0a 2f05 0ae9 050a ....0...../.....
1160 6b06 0a6b 0a0a ce09 0aee 030b db07 0f7e k..k.....~
1170 0a09 970a 0671 0e09 d517 0693 070e 5c07 .....q.....\.
1180 0fda 0a0f 350d 0dec 0a09 970a 0671 080b ....5.....q..
1190 220f 0985 060b 680c 0d4a 090b 0913 08f8 ".....h..J.....
11A0 1508 a204 0baa 0f05 660d 0723 090a 060b .....f..#....
11B0 0d4a 0f04 ee06 04f8 0409 2b04 0853 0708 .J.....+..S..
11C0 c003 111f 0411 1e07 0d8c 0307 3404 10db .....4...
11D0 0307 3603 0da9 0d04 200b 0451 0c04 3a04 ..6..... ..Q...:
11E0 0bb8 040c 2404 0595 0404 7c04 0575 0404 ....$......|.u..
11F0 8504 096b 0406 3d06 047b 0406 dc04 0783 ...k..=..{.....
1200 040e 1912 0400 1008 8e10 0869 0e04 120d .....i....
1210 042d 0310 b904 05d1 0407 6e04 0620 0704 .-.....n.. ..
1220 7404 0bfc 0a04 5c04 0527 0409 3d04 087d t.....\..'..=..}
1230 040f ae04 0d99 0406 ae04 04da 0904 0908 .....
1240 1122 040f 1c04 07e6 040e cb05 08bd 0407 .".....
1250 0804 0fa3 0406 5704 05b4 040f 5d04 08c7 .....W.....]...
1260 080b f404 07f8 0407 3004 07be 0408 5705 .....0.....W.
1270 0d46 0404 fe04 060a 0405 4e04 0e3b 0408 .F.....N...;...
1280 0b04 0930 0408 e905 05ee 0406 c504 06f2 ...0.....
1290 0406 7b04 09a1 0405 f104 081e 0407 4404 ..{.....D.
12A0 0bdd 040d fb04 04aa 040b e307 0eee 040f .....
12B0 0904 0eb4 040d be04 10c5 0408 3005 0f30 .....0..0
12C0 0407 5904 0a0f 060e 6104 0481 040d ab04 ..Y.....a.....
12D0 0d93 0411 6b04 0e96 0504 6609 046b 0b04 ....k.....f..k..
12E0 4604 0ce1 F...

```

Table 1: binary representation of the static SIP/SDP dictionary for SigComp

4. Security Considerations

The security considerations of [1] apply. This memo does not introduce any known additional security risk.

5. IANA Considerations

None.

6. Acknowledgements

The authors would like to thank Lars-Erik Jonsson, Zhigang C. Liu and Jonathan Rosenberg for their valuable comments.

7. References

7.1 Normative References

- [1] Price, R., Bormann, C., Christoffersson, J., Hannu, H., Liu, Z. and J. Rosenberg, "Signaling Compression (SigComp)", [RFC 3320](#), January 2003.
- [2] Bradner, S., "Key words for use in RFCs to indicate requirement levels", [BCP 14](#), [RFC 2119](#), March 1997.

7.2 Informative References

- [3] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M. and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [4] Garcia-Martin, M., "3rd-Generation Partnership Project (3GPP) Release 5 requirements on the Session Initiation Protocol (SIP)", Work in Progress.
- [5] Yergeau, F., "UTF-8, a transformation format of ISO 10646", [RFC 2279](#), January 1998.
- [6] Franks, J., Hallam-Baker, P., Hostetler, J., Lawrence, S., Leach, P., Luotonen, A. and L. Stewart, "HTTP Authentication: Basic and Digest Access Authentication", [RFC 2617](#), June 1999.
- [7] Vaha-Sipila, A., "URLs for telephone calls", [RFC 2806](#), April 2000.
- [8] Donovan, S., "The SIP INFO Method", [RFC 2976](#), October 2000.
- [9] Roach, A. B., "Session Initiation Protocol (SIP)-Specific Event Notification", [RFC 3265](#), June 2002.
- [10] Rosenberg, J. and H. Schulzrinne, "Reliability of Provisional Responses in Session Initiation Protocol (SIP)", [RFC 3262](#), June 2002.
- [11] Rosenberg, J., "The Session Initiation Protocol UPDATE Method", [RFC 3311](#), October 2002.
- [12] Camarillo, G., Ed., Marshall, W., Ed. and J. Rosenberg, "Integration of Resource Management and Session Initiation Protocol (SIP)", [RFC 3312](#), October 2002.
- [13] Sparks, R., "[The SIP Refer Method](#)", Work in Progress.

- [14] Mahy, R., Biggs, B. and R. Dean, "The Session Initiation Protocol (SIP) "Replaces" Header", Work in Progress.
- [15] Sparks, R., "Internet Media Type message/sipfrag", [RFC 3420](#), November 2002.
- [16] Willis, D. and B. Hoeneisen, "Session Initiation Protocol (SIP) Extension Header Field for Registering Non-Adjacent Contacts", [RFC 3327](#), December 2002.
- [17] Schulzrinne, H., Oran, D. and G. Camarillo, "The Reason Header Field for the Session Initiation Protocol (SIP)", [RFC 3326](#), December 2002.
- [18] Donovan, S., and J. Rosenberg, "Session Timers in the Session Initiation Protocol (SIP)", Work in Progress.
- [19] Niemi, A., Arkko, J. and V. Torvinen , "Hypertext Transfer Protocol (HTTP) Digest Authentication Using Authentication and Key Agreement (AKA)", [RFC 3310](#), September 2002.
- [20] Arkko, J., Torvinen, V., Camarillo, G., Niemi A. and T. Haukka, "Security Mechanism Agreement for the Session Initiation Protocol (SIP)", [RFC 3329](#), January 2003.
- [21] Campbell, B., Rosenberg, J., Schulzrinne, H., Huitema, C. and D. Gurle, "Session Initiation Protocol (SIP) Extension for Instant Messaging", [RFC 3428](#), December 2002.
- [22] Schulzrinne, H. and J. Rosenberg, "Session Initiation Protocol (SIP) Caller Preferences and Callee Capabilities", Work in Progress.
- [23] Camarillo, G., "Compressing the Session Initiation Protocol (SIP)", [RFC 3486](#), February 2003.
- [24] Handley, M., Jacobson, V. and C. Perkins, "SDP: Session Description Protocol", Work in Progress.
- [25] Sjoberg, J., Westerlund, M., Lankaniemi, A. and Q. Xie, "Real-Time Transport Protocol payload format and file storage format for the Adaptive Multi-Rate (AMR) and Adaptive Multi-Rate Wideband (AMR-WB) audio codecs", [RFC 3267](#), June 2002.
- [26] Camarillo, G., Eriksson, G., Holler, J. and H. Schulzrinne, "Grouping of Media Lines in the Session Description Protocol (SDP)", [RFC 3388](#), December 2002.

- [27] Schulzrinne, H. and S. Petrack, "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals", [RFC 2833](#), May 2000.
- [28] Arkko, J., Carrara, E., Lindholm, F., Naslund, M. and K. Norrman, "Key Management Extensions for SDP and RTSP", Work in Progress.
- [29] Arkko, J., Carrara, E., Lindholm, F., Naslund, M. and K. Norrman, "MIKEY: Multimedia Internet KEYing", Work in Progress.
- [30] Baugher, M., Blom, R., Carrara, E., McGrew, D., Naslund, M., Norrman, K. and D. Oran, "The Secure Real Time Transport Protocol", Work in Progress.
- [31] Ott, J., Wenger, S., Fukunaga, S., Sato, N., Burmeister, C., and Rey, J., "Extended RTP Profile for RTCP-based feedback (RTP/AVPF)", Work in Progress.
- [32] Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol (SDP)", [RFC 3264](#), June 2002.
- [33] Peterson, J., "A Privacy Mechanism for the Session Initiation Protocol (SIP)", [RFC 3323](#), November 2002.
- [34] Sparks, R., "[The Referred-By mechanism](#)", Work in Progress.
- [35] Willis, D. and B. Hoeneisen, "Session Initiation Protocol Extension Header Field for Service Route Discovery During Registration", Work in Progress.

Appendix A. SIP input strings to the SIP/SDP static dictionary

For reference, this section lists the SIP input strings that were used in generating the dictionary, as well as a priority value, the offset of the string in the generated dictionary, the length of the string, and one or more references into the referenced documents that motivate the presence of this string. Note that the notation "[CRLF]" stands for a sequence of two bytes with the values 0x0d and 0x0a, respectively.

The priority value is used for determining the position of the string in the dictionary. Lower priority values (higher priorities) cause the string to occur at a later position in the dictionary, making it more efficient to reference the string in certain compression algorithms. Hence, lower priority values were assigned to strings more likely to occur.

String	Pr	Off	Len	References
=====	==	====	====	=====
"sip:"	1	0CDD	0004	[3] 19.1.1
"sips:"	3	08AC	0005	[3] 19.1.1
"tel:"	3	08BD	0004	[7] 2.2
"SIP/2.0"	1	0CB9	0007	[3] 25.1
"SIP/2.0/UDP "	1	0CFE	000C	[3] 25.1
"SIP/2.0/TCP "	2	0CB9	000C	[3] 25.1
"INVITE"	1	0D4E	0006	[3] 25.1
"INVITE "	1	0D4E	0007	[3] 25.1
"ACK"	1	0D4A	0003	[3] 25.1
"ACK "	1	0D4A	0004	[3] 25.1
"OPTIONS"	4	0269	0007	[3] 25.1
"OPTIONS "	4	0269	0008	[3] 25.1
"BYE"	2	0C8A	0003	[3] 25.1
"BYE "	2	0C8A	0004	[3] 25.1
"CANCEL"	4	05E3	0006	[3] 25.1
"CANCEL "	4	05E3	0007	[3] 25.1
"REGISTER"	2	0B8F	0008	[3] 25.1
"REGISTER "	2	0B8F	0009	[3] 25.1
"INFO"	4	06E9	0004	[8] 2
"INFO "	4	06E9	0005	[8] 2
"SUBSCRIBE"	2	0A6C	0009	[9] 8.1.1
"SUBSCRIBE "	2	0A6C	000A	[9] 8.1.1
"NOTIFY"	2	0BC6	0006	[9] 8.1.2
"NOTIFY "	2	0BC6	0007	[9] 8.1.2
"PRACK"	2	0D48	0005	[10] 6
"PRACK "	2	0D48	0006	[10] 6
"UPDATE"	2	0BBF	0006	[11] 7, 10
"UPDATE "	2	0BBF	0007	[11] 7, 10
"REFER"	4	066B	0005	[13] 2.1, 7

"REFER "	4 066B 0006 [13] 2.1, 7
"MESSAGE"	3 08C1 0007 [21] 9
"MESSAGE "	3 08C1 0008 [21] 9
"[CRLF]Accept: "	4 06CE 000A [3] 20.1
"[CRLF]Accept-"	4 06EE 0009 [22] 5, [3] 20.2, 20.3
"Contact: "	5 0009 0009 [22] 5
"Encoding: "	4 0597 000A [3] 20.2, [3] 20.12
"Language: "	4 0271 000A [3] 20.3, [3] 20.13
"[CRLF]Alert-Info: "	4 05D5 000E [3] 20.4
"[CRLF]Allow: "	3 08F6 0009 [3] 20.5
"[CRLF]Allow-Events: "	3 0872 0010 [9] 8.2.1
"[CRLF]Authentication-Info: "	4 0293 0017 [3] 20.6
"[CRLF]Authorization: "	2 0AF8 0011 [3] 20.7
"[CRLF]Call-ID: "	1 0D55 000B [3] 20.8
"[CRLF]Call-Info: "	5 002D 000D [3] 20.9
"[CRLF]Contact: "	1 0D60 000B [3] 20.10
"[CRLF]Content-"	4 0B35 000A [3] 20.11, 20.12, 20.13, [3] 20.14, 20.15
"Disposition: "	4 09EC 000D [3] 20.11
"Encoding: "	4 0597 000A [3] 20.2, [3] 20.12
"Language: "	4 0271 000A [3] 20.3, [3] 20.13
"[CRLF]Content-Length: "	1 0CE1 0012 [3] 20.14
"[CRLF]Content-Type: "	2 0B35 0010 [3] 20.15
"[CRLF]CSeq: "	1 0D79 0008 [3] 20.16
"[CRLF]Date: "	4 0722 0008 [3] 20.17
"[CRLF]Error-Info: "	5 0012 000E [3] 20.18
"[CRLF]Event: "	3 08FF 0009 [9] 8.2.1
"[CRLF]Expires: "	2 0C01 000B [3] 20.19
"[CRLF]From: "	1 0D71 0008 [3] 20.20
"[CRLF]In-Reply-To: "	4 0585 000F [3] 20.21
"[CRLF]Max-Forwards: "	1 0D31 0010 [3] 20.22
"[CRLF]Min-"	4 0768 0006 [3] 20.23, [18] 5
"Expires: "	4 083A 0009 [3] 20.23
"SE: "	4 06E5 0004 [18] 5
"[CRLF]MIME-Version: "	5 0469 0010 [3] 20.24
"[CRLF]Organization: "	5 048E 0010 [3] 20.25
"[CRLF]Path: "	3 0908 0008 [16] 3
"[CRLF]Priority: "	4 0623 000C [3] 20.26
"[CRLF]Privacy: "	2 0BEB 000B [33] 4.2
"[CRLF]Proxy-"	4 073A 0008 [3] 20.27, 20.28, 20.29

"Authenticate: "	4	05AB	000E	[3]	20.27
"Authorization: "	4	0AFA	000F	[3]	20.28
"Require: "	4	0B6F	0009	[3]	20.29
"[CRLF]RAck: "	2	0C7A	0008	[10]	7.2
"[CRLF]Reason: "	3	08EC	000A	[17]	2
"[CRLF]Record-Route: "	2	0B49	0010	[3]	20.30
"[CRLF]Refer-To: "	4	0617	000C	[13]	2.1, 7
"[CRLF]Referred-By: "	4	0576	000F	[34]	9
"[CRLF]Reject-Contact: "	5	0000	0012	[22]	5
"[CRLF]Replaces: "	4	065F	000C	[14]	3.1
"[CRLF]Reply-To: "	5	003A	000C	[3]	20.31
"[CRLF]Request-Disposition: "	4	09E2	0017	[22]	5
"[CRLF]Require: "	2	0B6D	000B	[3]	20.32
"[CRLF]Retry-After: "	4	03A8	000F	[3]	20.33
"[CRLF]Route: "	2	0C47	0009	[3]	20.34
"[CRLF]RSeq: "	2	0C82	0008	[10]	7.1
"[CRLF]Security-"	2	0BF6	000B	[20]	3.3
"Client: "	2	0C62	0008	[20]	3.3
"Server: "	2	0B87	0008	[20]	3.3
"Verify: "	2	0C6A	0008	[20]	3.3
"[CRLF]Server: "	4	0B85	000A	[3]	20.35
"[CRLF]Service-Route: "	3	085D	0011	[35]	
"[CRLF]Session-Expires: "	3	0830	0013	[18]	4
"[CRLF]Subject: "	5	0051	000B	[3]	20.36
"[CRLF]Subscription-State: "	3	0843	0016	[9]	8.2.3
"[CRLF]Supported: "	2	0BCD	000D	[3]	20.37
"[CRLF]Timestamp: "	5	0020	000D	[3]	20.38
"[CRLF]To: "	1	0D81	0006	[3]	20.39
"[CRLF]Unsupported: "	4	04D6	000F	[3]	20.40
"[CRLF]User-Agent: "	4	05B9	000E	[3]	20.41
"[CRLF]Via: "	1	0CB2	0007	[3]	20.42
"[CRLF]Via: SIP/2.0/UDP "	1	0CF7	0013	[3]	20.42
"[CRLF]Via: SIP/2.0/TCP "	1	0CB2	0013	[3]	20.42
"[CRLF]Warning: "	5	0046	000B	[3]	20.43
"[CRLF]WWW-Authenticate: "	2	0920	0014	[3]	20.44
"[CRLF]WWW-Authenticate: Digest "	2	0920	001B	[3]	20.44
"[CRLF][CRLF]"	2	09E0	0004	[3]	7
";transport="	4	067A	000B	[3]	25.1
"udp"	4	07DB	0003	[3]	25.1,
				[24]	A, [3] 25.1, [24] A
"tcp"	4	04C1	0003	[3]	25.1
"sctp"	4	0AC7	0004	[3]	25.1
"tls"	4	04D3	0003	[3]	25.1,
				[20]	3.3
" ;user="	3	0910	0006	[3]	25.1
"phone"	3	00F2	0005	[3]	25.1
"ip"	4	008D	0002	[3]	25.1
" ;method="	4	074A	0008	[3]	25.1

" ;ttl="	4	078C	0005	[3]	25.1
" ;lr"	2	0CAF	0003	[3]	25.1
"Digest "	2	0934	0007	[6]	3.2.1, 3.2.2
"username="	2	0B27	0009	[6]	3.2.2
"uri="	2	0C9B	0004	[6]	3.2.2
"qop="	2	0C9F	0004	[6]	3.2.1, 3.2.2
"cnonce="	2	0C8E	0007	[6]	3.2.2
"nc="	2	0996	0003	[6]	3.2.2
"response="	2	09D7	0009	[6]	3.2.2
"nextnonce="	2	0B12	000A	[6]	3.2.3
"rspauth="	2	096C	0008	[6]	3.2.3
"realm="	2	0A66	0006	[6]	3.2.1
"domain="	2	0A55	0007	[6]	3.2.1
"nonce="	2	0B16	0006	[6]	3.2.1
"opaque="	4	0761	0007	[6]	3.2.1
"stale="	4	0148	0006	[6]	3.2.1
"true"	4	03F4	0004	[6]	3.2.1
"false"	4	0C30	0005	[6]	3.2.1
"algorithm="	2	09B4	000A	[6]	3.2.1, [19] 3.1
"MD5"	2	09F9	0003	[6]	3.2.1, [19] 3.1
"MD5-sess"	2	0AEA	0008	[6]	3.2.1, [19] 3.1
"auth"	4	031E	0004	[6]	3.2.1
"auth-int"	4	031E	0008	[6]	3.2.1
"AKAv"	2	0AE4	0004	[19]	3.1, 6
"AKAv1-MD5"	2	0AE4	0009	[19]	3.1, 6
"auts="	4	0791	0005	[19]	3.4
"digest-integrity"	4	00CA	0010	[20]	3.3
"ipsec-ike"	4	0671	0009	[20]	3.3
"ipsec-man"	4	0A87	0009	[20]	3.3
"smime"	4	0098	0005	[20]	3.3
" ;alg="	4	076E	0005	[20]	3.3
" ;purpose="	5	006B	0009	[3]	20.9
"icon"	5	0993	0004	[3]	20.9, 20.11
"info"	5	09AB	0004	[3]	20.9
"card"	5	0081	0004	[3]	20.9
" ;expires="	2	0C3E	0009	[3]	25.1, [9] 8.4
"render"	5	0A61	0006	[3]	20.11
"session"	5	0AEE	0007	[3]	20.11, [33] 4.2
"alert"	5	04BD	0005	[3]	20.11
" ;handling="	5	005C	000A	[3]	20.11
"optional"	2	09AE	0008	[3]	20.11,

	[12]	4,	[3]	20.11,	[12]	4
"required"	5	07F4	0008	[3]	20.11	
"text"	5	007C	0004	[3]	25.1	
"image"	5	0066	0005	[3]	25.1	
"audio"	5	0B30	0005	[3]	25.1	
"video"	5	0946	0005	[3]	25.1	
"application"	2	0334	000B	[3]	25.1	
"application/sdp"	2	0956	000F	[3]	25.1	
"message/sip"	4	009B	000B	[3]	27.5	
"message/sipfrag"	4	009B	000F	[15]	2	
"message"	4	009B	0007	[3]	27.5,	
				[15]	2	
"sip"	4	00A3	0003	[3]	27.5	
"sipfrag"	4	00A3	0007	[15]	2	
"multipart/signed"	4	0398	0010	[3]	23.3	
"multipart"	4	0398	0009	[3]	25.1, 7.4.1	
"sdp"	2	064B	0003			
"xml"	2	0CAC	0003			
"Mon, "	4	0773	0005	[3]	25.1	
"Tue, "	4	0778	0005	[3]	25.1	
"Wed, "	4	077D	0005	[3]	25.1	
"Thu, "	4	03B9	0005	[3]	25.1	
"Fri, "	4	0782	0005	[3]	25.1	
"Sat, "	4	0787	0005	[3]	25.1	
"Sun, "	4	071D	0005	[3]	25.1	
" Jan "	4	04E4	0005	[3]	25.1	
" Feb "	4	0881	0005	[3]	25.1	
" Mar "	4	0B44	0005	[3]	25.1	
" Apr "	4	0D40	0005	[3]	25.1	
" May "	4	0478	0005	[3]	25.1	
" Jun "	4	049D	0005	[3]	25.1	
" Jul "	4	0B58	0005	[3]	25.1	
" Aug "	4	033F	0005	[3]	25.1	
" Sep "	4	086D	0005	[3]	25.1	
" Oct "	4	0CF2	0005	[3]	25.1	
" Nov "	4	0858	0005	[3]	25.1	
" Dec "	4	02A9	0005	[3]	25.1	
" GMT"	4	03B6	0004	[3]	25.1	
";tag="	1	0D87	0005	[3]	25.1	
"emergency"	4	018C	0009	[3]	20.26	
"urgent"	4	021A	0006	[3]	20.26	
"normal"	4	0A81	0006	[3]	20.26	
"non-urgent"	4	0216	000A	[3]	20.26	
";duration="	4	06C4	000A	[3]	20.33	
";maddr="	4	075A	0007	[3]	20.42	
";received="	4	06BA	000A	[3]	20.42	
";branch="	5	0D22	0008	[3]	20.42	
";branch=z9hG4bK"	1	0D22	000F	[3]	8.1.1.7	

"SIP"	5	0CB9	0003	[3]	25.1, [17]	2
"UDP"	2	0CA6	0003	[3]	20.42	
"TCP"	2	0CA3	0003	[3]	20.42	
"TLS"	4	071B	0003	[3]	20.42	
"SCTP"	4	0D45	0004	[3]	20.42	
"active"	4	088C	0006	[9]	8.4	
"pending"	4	01AD	0007	[9]	8.4	
"terminated"	4	0ADA	000A	[9]	8.4	
" ;reason= "	4	0742	0008	[9]	8.4	
" ;retry-after= "	4	05F7	000D	[9]	8.4	
"deactivated"	4	011C	000B	[9]	8.4	
"probation"	4	0D16	0009	[9]	8.4	
"rejected"	4	01C9	0008	[9]	8.4	
"timeout"	4	0986	0007	[9]	8.4	
"giveup"	4	07CF	0006	[9]	8.4	
"noresource"	4	024D	000A	[9]	8.4	
" ;id= "	4	07A2	0004	[9]	8.4	
"100rel"	2	0C95	0006	[10]	8.1	
"precondition"	2	0A76	000C	[12]	8	
"refer"	3	07DE	0005	[13]	3.1, 7	
"to-tag"	4	028D	0006	[14]	3.2	
"from-tag"	4	01E6	0008	[14]	3.2	
"replaces"	4	0A11	0008	[14]	3.4	
"Q.850"	5	01EE	0005	[17]	2	
" ;cause= "	5	0074	0007	[17]	2	
" ;text= "	5	007B	0006	[17]	2	
"path"	3	0964	0004	[16]	3	
" ;refresher= "	4	069B	000B	[18]	4	
"uas"	4	0604	0003	[18]	4	
"uas"	4	07B5	0003	[18]	4	
"timer"	4	0CD7	0005	[18]	7.1	
"pref"	5	07DD	0004	[22]	4.1	
"TRUE"	4	0594	0004	[22]	6.2	
"FALSE"	4	06E2	0005	[22]	6.2	
" ;q= "	4	07B2	0003	[3]	25.1, [22]	6.2, [20] 3.3
" ;comp=sigcomp"	1	0D0A	000D	[23]	6	
"privacy"	3	07D4	0007	[33]	4.2	
"header"	4	0967	0006	[33]	4.2	
"user"	4	0911	0004	[33]	4.2	
"none"	2	0AF4	0004	[33]	4.2, [12]	4
"critical"	4	04B7	0008	[33]	4.2	
"100 "	5	0BAE	0004	[3]	21.1.1	
"100 Trying"	2	0BAE	000A	[3]	21.1.1	
"180 "	5	0BA3	0004	[3]	21.1.2	
"180 Ringing"	2	0BA3	000B	[3]	21.1.2	

"181 "	5	0A3B	0004	[3]	21.1.3
"181 Call Is Being Forwarded"	4	0A3B	001B	[3]	21.1.3
"182 "	5	05A1	0004	[3]	21.1.4
"182 Queued"	4	05A1	000A	[3]	21.1.4
"183 "	5	0AB4	0004	[3]	21.1.5
"183 Session Progress"	2	0AB4	0014	[3]	21.1.5
"200 "	5	0D6B	0004	[3]	21.2.1
"200 OK"	1	0D6B	0006	[3]	21.2.1
"202 "	5	0824	0004	[9]	8.3.1
"202 Accepted"	3	0824	000C	[9]	8.3.1
"300 "	5	0085	0004	[3]	21.3.1
"300 Multiple Choices"	4	0085	0014	[3]	21.3.1
"301 "	5	0383	0004	[3]	21.3.2
"301 Moved Permanently"	4	0383	0015	[3]	21.3.2
"302 "	5	036E	0004	[3]	21.3.3
"302 Moved Temporarily"	4	036E	0015	[3]	21.3.3
"305 "	5	053D	0004	[3]	21.3.4
"305 Use Proxy"	4	053D	000D	[3]	21.3.4
"380 "	5	02AE	0004	[3]	21.3.5
"380 Alternative Service"	4	02AE	0017	[3]	21.3.5
"400 "	5	03E6	0004	[3]	21.4.1
"400 Bad Request"	4	03E6	000F	[3]	21.4.1
"401 "	5	0B5D	0004	[3]	21.4.2
"401 Unauthorized"	2	0B5D	0010	[3]	21.4.2
"402 "	5	03BE	0004	[3]	21.4.3
"402 Payment Required"	4	03BE	0014	[3]	21.4.3
"403 "	5	020A	0004	[3]	21.4.4
"403 Forbidden"	4	020A	000D	[3]	21.4.4
"404 "	5	0530	0004	[3]	21.4.5
"404 Not Found"	4	0530	000D	[3]	21.4.5
"405 "	5	02F2	0004	[3]	21.4.6
"405 Method Not Allowed"	4	02F2	0016	[3]	21.4.6
"406 "	5	041E	0004	[3]	21.4.7
"406 Not Acceptable"	4	041E	0012	[3]	21.4.7
"407 "	5	00AA	0004	[3]	21.4.8
"407 Proxy Authentication Required"	4	00AA	0021	[3]	21.4.8
"408 "	5	0CC5	0004	[3]	21.4.9
"408 Request Timeout"	4	0CC5	0013	[3]	21.4.9
"410 "	5	060F	0004	[3]	21.4.10
"410 Gone"	4	060F	0008	[3]	21.4.10
"413 "	5	0A96	0004	[3]	21.4.11
"413 Request Entity Too Large"	4	0A96	001C	[3]	21.4.11
"414 "	5	07B8	0004	[3]	21.4.12
"414 Request-URI Too Long"	4	07B8	0018	[3]	21.4.12
"415 "	5	0195	0004	[3]	21.4.13
"415 Unsupported Media Type"	4	0195	001A	[3]	21.4.13
"416 "	5	0175	0004	[3]	21.4.14
"416 Unsupported URI Scheme"	4	0175	001A	[3]	21.4.14

"420 "	5	023D	0004	[3]	21.4.15
"420 Bad Extension"	4	023D	0011	[3]	21.4.15
"421 "	5	02DC	0004	[3]	21.4.16
"421 Extension Required"	4	02DC	0016	[3]	21.4.16
"422 "	5	0A19	0004	[18]	6, 12.1
"422 Session Interval Too Small"	4	0A19	001E	[18]	6, 12.2
"423 "	5	01D1	0004	[3]	21.4.17
"423 Interval Too Brief"	4	01D1	0016	[3]	21.4.17
"429 "	5	0220	0004	[34]	9
"429 Provide Referrer Identity"	4	0220	001D	[34]	9
"480 "	5	07FC	0004	[3]	21.4.18
"480 Temporarily Unavailable"	3	07FC	001B	[3]	21.4.18
"481 "	5	0127	0004	[3]	21.4.19
"481 Call/Transaction Does Not Exist"	4	0127	0023	[3]	21.4.19
"482 "	5	047D	0004	[3]	21.4.20
"482 Loop Detected"	4	047D	0011	[3]	21.4.20
"483 "	5	0999	0004	[3]	21.4.21
"483 Too Many Hops"	4	0999	0011	[3]	21.4.21
"484 "	5	00DA	0004	[3]	21.4.22
"484 Address Incomplete"	4	00DA	0016	[3]	21.4.22
"485 "	5	0B1C	0004	[3]	21.4.23
"485 Ambiguous"	4	0B1C	000D	[3]	21.4.23
"486 "	5	0ACB	0004	[3]	21.4.24
"486 Busy Here"	3	0ACB	000D	[3]	21.4.24
"487 "	5	0308	0004	[3]	21.4.25
"487 Request Terminated"	4	0308	0016	[3]	21.4.25
"488 "	5	01B4	0004	[3]	21.4.26
"488 Not Acceptable Here"	4	01B4	0017	[3]	21.4.26
"489 "	5	04C7	0004	[9]	8.3.2
"489 Bad Event"	4	04C7	000D	[9]	8.3.2
"491 "	5	03F8	0004	[3]	21.4.27
"491 Request Pending"	4	03F8	0013	[3]	21.4.27
"493 "	5	0457	0004	[3]	21.4.28
"493 Undecipherable"	4	0457	0012	[3]	21.4.28
"494 "	5	00FE	0004	[20]	3.3.1
"494 Security Agreement Required"	4	00FE	001F	[20]	3.3.1
"500 "	5	014E	0004	[3]	21.5.1
"500 Server Internal Error"	4	014E	0019	[3]	21.5.1
"501 "	5	040B	0004	[3]	21.5.2
"501 Not Implemented"	4	040B	0013	[3]	21.5.2
"502 "	5	04E9	0004	[3]	21.5.3
"502 Bad Gateway"	4	04E9	000F	[3]	21.5.3
"503 "	5	02C5	0004	[3]	21.5.4
"503 Service Unavailable"	4	02C5	0017	[3]	21.5.4
"504 "	5	027B	0004	[3]	21.5.5
"504 Server Time-out"	4	027B	0013	[3]	21.5.5
"505 "	5	01F1	0004	[3]	21.5.6
"505 Version Not Supported"	4	01F1	0019	[3]	21.5.6

"513 "	5 0344 0004 [3] 21.5.7
"513 Message Too Large"	4 0344 0015 [3] 21.5.7
"580 "	5 09FB 0004 [12] 8
"580 Precondition Failure"	4 09FB 0018 [12] 8
"600 "	5 07E3 0004 [3] 21.6.1
"600 Busy Everywhere"	3 07E3 0013 [3] 21.6.1
"603 "	5 0B09 0004 [3] 21.6.2
"603 Decline"	4 0B09 000B [3] 21.6.2
"604 "	5 09BE 0004 [3] 21.6.3
"604 Does Not Exist Anywhere"	4 09BE 001B [3] 21.6.3
"606 "	5 0430 0004 [3] 21.6.4
"606 Not Acceptable"	4 0430 0012 [3] 21.6.4
"687 "	5 0359 0004 [14] 3.5
"687 Dialog Terminated"	4 0359 0015 [14] 3.5
"Anonymous"	3 08A4 0009 [3] 8.1.1.3

Table A.1: SIP input strings for the SIP/SDP dictionary

Appendix B. SDP input strings to the SIP/SDP static dictionary

For reference, this section lists the SDP input strings that were used in generating the dictionary, as well as a priority value, the offset of the string in the generated dictionary, the length of the string, and one or more references into the referenced documents that motivate the presence of this string. Note that the notation "[CRLF]" stands for a sequence of two bytes with the values 0x0d and 0x0a, respectively.

The priority value is used for determining the position of the string in the dictionary. Lower priority values (higher priorities) cause the string to occur at a later position in the dictionary, making it more efficient to reference the string in certain compression algorithms. Hence, lower priority values were assigned to strings more likely to occur.

String	Pr	Off	Len	References
=====	==	====	====	=====
"v=0[CRLF]o="	2	0BB8	0007	[24] 6
"[CRLF]s="	2	0C2B	0004	[24] 6
"[CRLF]s= "	2	0C2B	0005	[32] 5
"[CRLF]i="	4	07A6	0004	[24] 6
"[CRLF]u="	4	07AE	0004	[24] 6
"[CRLF]e="	4	079E	0004	[24] 6
"[CRLF]c=IN IP4 "	3	08E1	000B	[24] 6
"[CRLF]c=IN IP6 "	2	0B98	000B	[24] 6
"[CRLF]c="	5	08E1	0004	[24] 6
"[CRLF]b="	3	0916	0004	[24] 6
"[CRLF]t="	2	0B78	0004	[24] 6
"[CRLF]t=0 0"	2	0B78	0007	[32] 5
"[CRLF]r="	4	0796	0004	[24] 6
"[CRLF]z="	4	079A	0004	[24] 6
"[CRLF]k=clear:"	4	06B0	000A	[24] 6
"[CRLF]k=base64:"	4	0690	000B	[24] 6
"[CRLF]k=uri:"	4	0732	0008	[24] 6
"[CRLF]k=prompt:"	4	056B	000B	[24] 6
"[CRLF]k="	5	056B	0004	[24] 6
"[CRLF]a=cat:"	4	072A	0008	[24] 6
"[CRLF]a=keywds:"	4	0685	000B	[24] 6
"[CRLF]a=tool:"	4	0712	0009	[24] 6
"[CRLF]a=ptime:"	4	06A6	000A	[24] 6
"[CRLF]a=maxptime:"	4	05EA	000D	[24] 6
"[CRLF]a=rtpmap:"	2	0C0C	000B	[24] 6, [32] 5
"[CRLF]a=recvonly"	3	08C9	000C	[24] 6
"[CRLF]a=sendrecv"	3	093B	000C	[24] 6
"[CRLF]a=sendonly"	3	08D5	000C	[24] 6
"[CRLF]a=inactive"	3	0886	000C	[24] 6

"[CRLF]a=orient:portrait"	4	0974	0013	[24]	6
"[CRLF]a=orient:landscape"	4	03D2	0014	[24]	6
"[CRLF]a=orient:seascape"	4	050B	0013	[24]	6
"[CRLF]a=type:broadcast"	4	0442	0012	[24]	6
"[CRLF]a=type:meeting"	4	055B	0010	[24]	6
"[CRLF]a=type:moderated"	4	051E	0012	[24]	6
"[CRLF]a=type:test"	4	08B1	000D	[24]	6
"[CRLF]a=type:H.332"	4	0817	000E	[24]	6
"[CRLF]a=type:recvonly"	4	054A	0011	[24]	6
"[CRLF]a=charset:"	4	0653	000C	[24]	6
"[CRLF]a=sdplang:"	4	0647	000C	[24]	6
"[CRLF]a=lang:"	4	06F7	0009	[24]	6
"[CRLF]a=framerate:"	4	05C7	000E	[24]	6
"[CRLF]a=quality:"	4	063B	000C	[24]	6
"[CRLF]a=fmtp:"	2	0C50	0009	[24]	6
"[CRLF]a=curr:"	2	0C59	0009	[12]	4
"[CRLF]a=des:"	2	0C72	0008	[12]	4
"[CRLF]a=conf:"	2	0C35	0009	[12]	4
"[CRLF]a=mid:"	4	0752	0008	[26]	3
"[CRLF]a=group:"	4	06D8	000A	[26]	3
"[CRLF]a=key-mgmt:mikey"	4	0257	0012	[28]	2.1, [29] 6
"[CRLF]a=key-mgmt:"	4	0257	000D	[28]	2.1
"[CRLF]a="	5	0257	0004	[24]	6
"[CRLF]m=audio "	2	0C21	000A	[24]	6
"[CRLF]m=video "	2	0C17	000A	[24]	6
"[CRLF]m=application "	4	0330	0010	[24]	6
"[CRLF]m=data "	4	0700	0009	[24]	6
"[CRLF]m=control "	4	062F	000C	[24]	6
"[CRLF]m="	5	0330	0004	[24]	6
"AS "	3	091A	0003	[24]	6
"CT "	3	091D	0003	[24]	6
"RTP/AVP "	2	0BE3	0008	[24]	A
"RTP/SAVP "	3	0892	0009	[30]	12
"RTP/AVPF "	3	089B	0009	[31]	4.1
"udp"	4	07DB	0003	[3]	25.1, [24] A, [3] 25.1, [24] A
"0.0.0.0"	4	0B7E	0007	[24]	A
"qos"	2	0CA9	0003	[12]	4
"mandatory"	2	0A8D	0009	[12]	4
"optional"	2	09AE	0008	[3]	20.11, [12] 4, [3] 20.11, [12] 4
"none"	2	0AF4	0004	[33]	4.2, [12] 4
"failure"	4	0A5C	0007	[12]	4
"unknown"	4	0BDA	0007	[12]	4
"e2e"	2	0AB1	0003	[12]	4
"local"	2	0A36	0005	[12]	4

"remote"	2	0AD6	0006	[12]	4
"send"	2	08D9	0004	[12]	4
"recv"	2	0553	0004	[12]	4
"sendrecv"	2	093F	0008	[12]	4
"AMR"	2	0BE1	0003	[25]	8
"octet-align="	4	094A	000C	[25]	8
"mode-set="	4	0709	0009	[25]	8
"mode-change-period="	4	04F8	0013	[25]	8
"mode-change-neighbor="	4	04A2	0015	[25]	8
"crc="	4	07AA	0004	[25]	8
"robust-sorting="	4	0166	000F	[25]	8
"interleaving="	4	0323	000D	[25]	8
"channels="	4	0606	0009	[25]	8
"octet-align"	4	094A	000B	[25]	8
"telephone-event"	4	00EE	000F	[27]	3.3, 6.1
"events"	4	00F8	0006	[27]	6.1
"rate"	4	052B	0004	[27]	6.1, 6.2
"tone"	4	0453	0004	[27]	6.2
"rtcp-fb"	4	04C0	0007	[31]	4
"ack"	4	0D1F	0003	[31]	4
"nack"	4	0D1E	0004	[31]	4
"ttr-int"	4	098C	0007	[31]	4
"app"	4	0334	0003	[31]	4
"rpsi"	4	0CDB	0004	[31]	4
"pli"	4	0336	0003	[31]	4
"sli"	4	09A9	0003	[31]	4

Table B.1: SDP input strings for the SIP/SDP dictionary

Authors' Addresses

Miguel A. Garcia-Martin
Ericsson
Hirsalantie 11
FIN-02420, Jorvas, Finland

Phone: +358 9299 3553
EMail: miguel.a.garcia@ericsson.com

Carsten Bormann
Universitaet Bremen TZI
Postfach 330440
D-28334 Bremen, Germany

Phone: +49 421 218 7024
EMail: cabo@tzi.org

Joerg Ott
Universitaet Bremen TZI
Postfach 330440
D-28334 Bremen, Germany

Phone: +49.421.201-7028
EMail: jo@tzi.org

Richard Price
Roke Manor Research Ltd
Romsey, Hants, SO51 0ZN, United Kingdom

Phone: +44 1794 833681
EMail: richard.price@roke.co.uk

Adam Roach
dynamicsoft
5100 Tennyson Parkway, Suite 1200
Plano, TX 75024, USA

EMail: adam@dynamicsoft.com

Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.