

## BGP/MPLS Layer 3 VPN Multicast Management Information Base

### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects to configure and/or monitor Multicast communication over IP Virtual Private Networks (VPNs) supported by the Multiprotocol Label Switching/Border Gateway Protocol (MPLS/BGP) on a Provider Edge (PE) router.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in [Section 2 of RFC 7841](#).

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc8503>.

### Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
1.1. Terminology . . . . .	2
2. The Internet-Standard Management Framework . . . . .	3
3. BGP-MPLS-LAYER3-VPN-MULTICAST-MIB . . . . .	3
3.1. Summary of the MIB Module . . . . .	4
3.2. MIB Module Definitions . . . . .	5
4. Security Considerations . . . . .	51
5. IANA Considerations . . . . .	53
6. References . . . . .	54
6.1. Normative References . . . . .	54
6.2. Informative References . . . . .	56
Acknowledgements . . . . .	57
Author's Address . . . . .	57

## 1. Introduction

[RFC6513], [RFC6514], and [RFC6625] specify procedures for supporting multicast in Multiprotocol Label Switching/Border Gateway Protocol (MPLS/BGP) Layer 3 (IP) Virtual Private Networks (VPNs). Throughout this document, we will use the term "MVPN" (for "multicast VPN") [RFC6513] to refer to a BGP/MPLS IP VPN that supports multicast.

Provider Edge (PE) routers that attach to a particular MVPN exchange customer multicast (C-multicast) routing information with neighboring PEs. In [RFC6513], two basic methods for exchanging C-multicast routing information are defined: (1) Protocol Independent Multicast (PIM) [RFC7761] and (2) BGP.

In the rest of this document, we will use the term "PIM-MVPN" to refer to the case where PIM is used for exchanging C-multicast routing information and "BGP-MVPN" to refer to the case where BGP is used for exchanging C-multicast routing information.

This document describes managed objects to configure and/or monitor MVPNs. Most of the managed objects are common to both PIM-MVPN and BGP-MVPN, and some managed objects are BGP-MVPN specific.

## 1.1. Terminology

This document adopts the definitions, abbreviations, and mechanisms described in [RFC4364], [RFC6513], and [RFC6514]. Familiarity with multicast, MPLS, Layer 3 (L3) VPN, and MVPN concepts and/or mechanisms is assumed. Some terms specifically related to this document are explained below.

An MVPN can be realized by using various kinds of transport mechanisms for forwarding a packet to all or a subset of PEs across service provider networks. Such transport mechanisms are referred to as provider tunnels (P-tunnels).

A Provider Multicast Service Interface (PMSI) [RFC6513] is a conceptual interface instantiated by a P-tunnel. A PE uses a PMSI to send customer multicast traffic to all or some PEs in the same VPN.

There are two kinds of PMSIs: Inclusive PMSI (I-PMSI) and Selective PMSI (S-PMSI) [RFC6513]. An I-PMSI enables a PE attached to a particular MVPN to transmit a message to all PEs in the same MVPN. An S-PMSI enables a PE to transmit a message to a selected set of PEs in the same MVPN.

As described in [RFC4382], each PE maintains one default forwarding table and zero or more Virtual Routing and Forwarding (VRF) tables. Throughout this document, we will use the term "MVRF" (for "multicast VRF") to refer to a VRF that contains multicast routing information.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

## 2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

## 3. BGP-MPLS-LAYER3-VPN-MULTICAST-MIB

This document defines BGP-MPLS-LAYER3-VPN-MULTICAST-MIB, a MIB module for monitoring and/or configuring MVPNs on PEs. This MIB module will be used in conjunction with MPLS-L3VPN-STD-MIB [RFC4382] and IPMCAST-MIB [RFC5132].

### 3.1. Summary of the MIB Module

BGP-MPLS-LAYER3-VPN-MULTICAST-MIB provides the following functionalities.

- o Monitoring attributes of MVPNs on a PE
- o Configuring timers and thresholds related to an MVPN on a PE
- o Notifying creation, deletion, and modification of MVRFs on a PE
- o Monitoring PMSI attributes
- o Monitoring statistics of advertisements exchanged by a PE
- o Monitoring routing information for multicast destinations
- o Monitoring next hops for each multicast destination

To provide these functionalities, BGP-MPLS-LAYER3-VPN-MULTICAST-MIB defines the following tables.

- o mvpnGenericTable

This table contains generic information about MVPNs on a PE. Each entry in this table represents an instance of an MVPN on a PE and contains generic information related to the MVPN. For each entry in this table, there MUST be a corresponding VRF in MPLS-L3VPN-STD-MIB [RFC4382].

- o mvpnBgpTable

This table contains information specific to BGP-MVPNs. Each BGP-MVPN on a PE will have an entry in this table.

- o mvpnPmsiTable

This table contains managed objects representing attribute information that is common to I-PMSIs and S-PMSIs on a PE.

- o mvpnSpmsiTable

This table contains managed objects representing attribute information specific to S-PMSIs. An S-PMSI represented in this table will have a corresponding entry in mvpnPmsiTable.

- o mvpnAdvtStatsTable

This table contains statistics pertaining to I-PMSI and S-PMSI advertisements sent/received.

- o mvpnMrouteTable

This table contains multicast routing information in MVRFs on a PE.

- o mvpnMrouteNextHopTable

This table contains information on the next hops for routing IP multicast datagrams in MVPNs on a PE.

### 3.2. MIB Module Definitions

This MIB module makes reference to the following documents:  
[RFC2003], [RFC2784], [RFC2863], [RFC3032], [RFC4001], and [RFC8502].

BGP-MPLS-LAYER3-VPN-MULTICAST-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,  
Counter32, Counter64, Gauge32, Unsigned32, TimeTicks,  
mib-2  
FROM SNMPv2-SMI -- RFC 2578

MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP  
FROM SNMPv2-CONF -- RFC 2580

RowPointer, TimeStamp, DateAndTime  
FROM SNMPv2-TC -- RFC 2579

InterfaceIndex, InterfaceIndexOrZero  
FROM IF-MIB -- RFC 2863

InetAddress, InetAddressType, InetAddressPrefixLength  
FROM INET-ADDRESS-MIB -- RFC 4001

mplsL3VpnVrfName, MplsL3VpnRouteDistinguisher  
FROM MPLS-L3VPN-STD-MIB -- RFC 4382

IANAipRouteProtocol, IANAipMRouteProtocol  
FROM IANA-RTPROTO-MIB  
-- <http://www.iana.org/assignments/ianaiprouteprotocol-mib>

L2L3VpnMcastProviderTunnelType

FROM L2L3-VPN-MULTICAST-TC-MIB;

-- RFC 8502

mvpnMIB MODULE-IDENTITY

LAST-UPDATED "201812140000Z" -- 14 December 2018

ORGANIZATION "IETF BESS Working Group"

CONTACT-INFO

"Hiroshi Tsunoda  
Tohoku Institute of Technology  
35-1, Yagiyama Kasumi-cho  
Taihaku-ku, Sendai, 982-8577  
Japan  
Email: tsuno@m.ieice.org"

DESCRIPTION

"This MIB module contains managed object definitions to configure and/or monitor Multicast communication over IP Virtual Private Networks (VPNs) supported by the Multiprotocol Label Switching/Border Gateway Protocol (MPLS/BGP) on a Provider Edge (PE) router.

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

"

-- Revision History

REVISION "201812140000Z" -- 14 December 2018

DESCRIPTION

"Initial version, published as [RFC 8503](#)."

::= { mib-2 243 }

-- Top-level components of this MIB module.

mvpnNotifications OBJECT IDENTIFIER ::= { mvpnMIB 0 }

-- Scalars, Tables

mvpnObjects OBJECT IDENTIFIER ::= { mvpnMIB 1 }

-- Conformance Information

mvpnConformance OBJECT IDENTIFIER ::= { mvpnMIB 2 }

```
-- MVPN Objects
mvpnScalars      OBJECT IDENTIFIER ::= { mvpnObjects 1 }

-- Scalar Objects

mvpnMvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The total number of Multicast Virtual Routing and
        Forwarding (MVRF) tables that are present on
        this Provider Edge (PE) router.  This includes MVRFs
        for IPv4, IPv6, and Multipoint LDP (mLDP) C-multicast.
        "
    ::= { mvpnScalars 1 }

mvpnV4Mvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of MVRFs for IPv4 C-multicast on this PE.
        "
    ::= { mvpnScalars 2 }

mvpnV6Mvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of MVRFs for IPv6 C-multicast on this PE.
        "
    ::= { mvpnScalars 3 }

mvpnMldpMvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of MVRFs on this PE that use BGP for
        exchanging mLDP C-multicast routing information.
        "
    ::= { mvpnScalars 4 }
```

```
mvpnPimV4Mvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of MVRFs on this PE that use Provider
        Independent Multicast (PIM) for exchanging IPv4
        C-multicast routing information.
        "
    ::= { mvpnScalars 5 }

mvpnPimV6Mvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of MVRFs on this PE that use PIM for
        exchanging IPv6 C-multicast routing information.
        "
    ::= { mvpnScalars 6 }

mvpnBgpV4Mvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of MVRFs on this PE that use BGP for
        exchanging IPv4 C-multicast routing information.
        "
    ::= { mvpnScalars 7 }

mvpnBgpV6Mvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of MVRFs on this PE that use BGP for
        exchanging IPv6 C-multicast routing information.
        "
    ::= { mvpnScalars 8 }

mvpnSPTunnelLimit OBJECT-TYPE
    SYNTAX          Unsigned32 (1..4294967295)
    MAX-ACCESS      read-write
    STATUS          current
    DESCRIPTION
        "The maximum number of selective provider tunnels that
        are allowed for a particular MVPN on this PE."
```



```
"
REFERENCE
  "RFC 6513, Section 13"
 ::= { mvpnScalars 9 }

mvpnBgpCmcastRouteWithdrawalTimer OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "milliseconds"
    MAX-ACCESS   read-write
    STATUS      current
    DESCRIPTION
        "A configurable timer to control the delay
         of C-multicast route withdrawal advertisements."
    "
    REFERENCE
        "RFC 6514, Section 16.1.1"
    ::= { mvpnScalars 10 }

mvpnBgpSrcSharedTreeJoinTimer OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "milliseconds"
    MAX-ACCESS   read-write
    STATUS      current
    DESCRIPTION
        "A configurable timer to control the delay
         of Source/Shared Tree Join C-multicast route
         advertisements."
    "
    REFERENCE
        "RFC 6514, Section 16.1.2"
    ::= { mvpnScalars 11 }

-- Generic MVRP Information Table

mvpnGenericTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MvpnGenericEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "A conceptual table containing generic information about
         MVPNs on this PE."
    "
    ::= { mvpnObjects 2 }

mvpnGenericEntry OBJECT-TYPE
    SYNTAX      MvpnGenericEntry
    MAX-ACCESS   not-accessible
    STATUS      current
```

## DESCRIPTION

"A conceptual row that represents an MVPN on this PE.  
 The MVPN represented by this entry will have one or more  
 corresponding P-Multicast Service Interfaces (PMSIs)  
 and a corresponding VRF in MPLS-L3VPN-STD-MIB ([RFC 4382](#)).  
 "

```
INDEX {
    mplsL3VpnVrfName
}
::= { mvpnGenericTable 1 }
```

```
MvpnGenericEntry ::= SEQUENCE {
    mvpnGenMvrfLastAction      INTEGER,
    mvpnGenMvrfLastActionTime  DateAndTime,
    mvpnGenMvrfCreationTime    DateAndTime,
    mvpnGenCmcastRouteProtocol INTEGER,
    mvpnGenIpmsiInfo           RowPointer,
    mvpnGenInterAsPmsiInfo     RowPointer,
    mvpnGenUmhSelection         INTEGER,
    mvpnGenCustomerSiteType    INTEGER
}
```

mvpnGenMvrfLastAction OBJECT-TYPE

```
SYNTAX      INTEGER {
                                createdMvrf      (1),
                                deletedMvrf      (2),
                                modifiedMvrfIpmsiConfig (3),
                                modifiedMvrfSpmsiConfig (4)
                            }
```

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"This object describes the last action pertaining  
 to the MVPN represented by this entry.

The enumerated action types and the corresponding  
 descriptions are as follows:

createdMvrf:

MVRF was created for this MVPN on the PE.

deletedMvrf:

MVRF for this MVPN was deleted from the PE.  
 A conceptual row in this table will never have  
 mvpnGenMvrfLastAction equal to deletedMvrf,  
 because in that case, the row itself will not exist  
 in the table.

This value for mvpnGenMvrfLastAction is defined solely for use in the mvpnMvrfActionChange notification.

modifiedMvrfIpmsiConfig:

An I-PMSI for this MVPN was configured, deleted, or changed.

modifiedMvrfSpmsiConfig:

An S-PMSI for this MVPN was configured, deleted, or changed.

"

::= { mvpnGenericEntry 2 }

mvpnGenMvrfLastActionTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp when the last action, given in the corresponding mvpnGenMvrfLastAction object, was carried out.

"

::= { mvpnGenericEntry 3 }

mvpnGenMvrfCreationTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp when the MVRF was created for the MVPN represented by this entry.

"

::= { mvpnGenericEntry 4 }

mvpnGenCmcastRouteProtocol OBJECT-TYPE

SYNTAX INTEGER {  
pim (1),  
bgp (2)  
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The protocol used to signal C-multicast routing information across the provider core for the MVPN represented by this entry.

The enumerated protocols and the corresponding descriptions are as follows:

```

        pim : PIM (PIM-MVPN)
        bgp : BGP (BGP-MVPN)
    "
REFERENCE
    "RFC 6513, Section 5"
 ::= { mvpnGenericEntry 5 }

mvpnGenIpmsiInfo OBJECT-TYPE
    SYNTAX      RowPointer
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "A pointer to a conceptual row representing
        the corresponding I-PMSI in mvpnPmsiTable.
        If there is no I-PMSI for the MVPN
        represented by this entry, the
        value of this object will be zeroDotZero."
    "
 ::= { mvpnGenericEntry 6 }

mvpnGenInterAsPmsiInfo OBJECT-TYPE
    SYNTAX      RowPointer
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "A pointer to a conceptual row representing
        the corresponding segmented Inter-AS I-PMSI in mvpnPmsiTable.
        If there is no segmented Inter-AS I-PMSI for the MVPN,
        the value of this object will be zeroDotZero."
    "
 ::= { mvpnGenericEntry 7 }

mvpnGenUmhSelection OBJECT-TYPE
    SYNTAX      INTEGER {
                                highestPeAddress  (1),
                                cRootGroupHashing (2),
                                ucastUmhRoute     (3)
                            }
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The Upstream Multicast Hop (UMH) selection method for the
        MVPN represented by this entry."

```

The enumerated methods and the corresponding descriptions are as follows:

```

highestPeAddress : PE with the highest address
                  (see RFC 6513, Section 5.1.3)
cRootGroupHashing : hashing based on (c-root, c-group)
ucastUmhRoute     : per-unicast route towards c-root

```

"

#### REFERENCE

"RFC 6513, Section 5.1"

::= { mvpnGenericEntry 8 }

#### mvpnGenCustomerSiteType OBJECT-TYPE

```

SYNTAX          INTEGER {
                                senderReceiver (1),
                                receiverOnly   (2),
                                senderOnly     (3)
                            }

```

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"The type of the customer site, connected to the MVPN represented by this entry.

The enumerated types and the corresponding descriptions are as follows:

```

senderReceiver : Site is both sender and receiver
receiverOnly   : Site is receiver only
senderOnly     : Site is sender only

```

"

#### REFERENCE

"RFC 6513, Section 2.3"

::= { mvpnGenericEntry 9 }

#### -- Generic BGP-MVPN Table

#### mvpnBgpTable OBJECT-TYPE

```

SYNTAX          SEQUENCE OF MvpnBgpEntry

```

MAX-ACCESS not-accessible

STATUS current

#### DESCRIPTION

"A conceptual table that supplements mvpnGenericTable with BGP-MVPN-specific information for BGP-MVPNs on this PE.

"

::= { mvpnObjects 3 }

```

mvpnBgpEntry OBJECT-TYPE
    SYNTAX          MvpnBgpEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "A conceptual row corresponding to a BGP-MVPN on this PE.
        "
    INDEX {
        mplsL3VpnVrfName
    }
 ::= { mvpnBgpTable 1 }

MvpnBgpEntry ::= SEQUENCE {
    mvpnBgpMode                INTEGER,
    mvpnBgpVrfRouteImportExtendedCommunity MplsL3VpnRouteDistinguisher,
    mvpnBgpSrcASExtendedCommunity Unsigned32,
    mvpnBgpMsgRateLimit        Unsigned32,
    mvpnBgpMaxSpmsiAdRoutes     Unsigned32,
    mvpnBgpMaxSpmsiAdRouteFreq  Unsigned32,
    mvpnBgpMaxSrcActiveAdRoutes Unsigned32,
    mvpnBgpMaxSrcActiveAdRouteFreq Unsigned32
}

mvpnBgpMode OBJECT-TYPE
    SYNTAX          INTEGER {
                        other      (0),
                        rptSpt     (1),
                        sptOnly    (2)
                    }
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The inter-site C-tree mode used by the BGP-MVPN
        represented by this entry.

        other      : none of the following
        rptSpt     : inter-site shared tree mode
                     (Rendezvous Point Tree (RPT) and
                     source-specific shortest-path tree (SPT))
        sptOnly    : inter-site source-only tree mode
        "
    REFERENCE
        "RFC 6513, Section 9.3.1"
    ::= { mvpnBgpEntry 1 }

mvpnBgpVrfRouteImportExtendedCommunity OBJECT-TYPE
    SYNTAX          MplsL3VpnRouteDistinguisher
    MAX-ACCESS      read-only

```

```
STATUS          current
DESCRIPTION
    "The VRF Route Import Extended Community added by this PE
    to unicast VPN routes that it advertises for the BGP-MVPN
    corresponding to this entry.
    "
REFERENCE
    "RFC 6514, Section 7
    "
 ::= { mvpnBgpEntry 2 }

mvpnBgpSrcASExtendedCommunity OBJECT-TYPE
    SYNTAX          Unsigned32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The Source AS Extended Community added by this PE
        to the unicast VPN routes that it advertises for
        the BGP-MVPN represented by this entry.
        "
    REFERENCE
        "RFC 6514, Section 6
        "
    ::= { mvpnBgpEntry 3 }

mvpnBgpMsgRateLimit OBJECT-TYPE
    SYNTAX          Unsigned32 (0..4294967295)
    UNITS           "messages per second"
    MAX-ACCESS      read-write
    STATUS          current
    DESCRIPTION
        "The configurable upper bound for the rate of the BGP
        C-multicast routing information message exchange between
        this PE and other PEs in the BGP-MVPN corresponding to
        this entry.
        "
    REFERENCE
        "RFC 6514, Section 17"
    ::= { mvpnBgpEntry 4 }

mvpnBgpMaxSpmsiAdRoutes OBJECT-TYPE
    SYNTAX          Unsigned32 (0..4294967295)
    MAX-ACCESS      read-write
    STATUS          current
    DESCRIPTION
        "The configurable upper bound for the number of S-PMSI
        auto-discovery (A-D) routes for the BGP-MVPN
        corresponding to this entry."
```

```
"
REFERENCE
  "RFC 6514, Section 17"
 ::= { mvpnBgpEntry 5 }

mvpnBgpMaxSpmsiAdRouteFreq OBJECT-TYPE
    SYNTAX      Unsigned32 (0..4294967295)
    UNITS        "routes per second"
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "The configurable upper bound for the frequency of
         S-PMSI A-D route generation for the BGP-MVPN
         corresponding to this entry."
    "
REFERENCE
  "RFC 6514, Section 17"
 ::= { mvpnBgpEntry 6 }

mvpnBgpMaxSrcActiveAdRoutes OBJECT-TYPE
    SYNTAX      Unsigned32 (0..4294967295)
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "The configurable upper bound for the number of
         Source Active A-D routes for the BGP-MVPN corresponding
         to this entry."
    "
REFERENCE
  "RFC 6514, Section 17"
 ::= { mvpnBgpEntry 7 }

mvpnBgpMaxSrcActiveAdRouteFreq OBJECT-TYPE
    SYNTAX      Unsigned32 (0..4294967295)
    UNITS        "routes per second"
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "The configurable upper bound for the frequency of Source
         Active A-D route generation for the BGP-MVPN corresponding
         to this entry."
    "
REFERENCE
  "RFC 6514, Section 17"
 ::= { mvpnBgpEntry 8 }
```



-- Table of PMSI Information

```

mvpnPmsiTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MvpnPmsiEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A conceptual table containing information related
        to PMSIs on this PE.
        "
    ::= { mvpnObjects 4 }

mvpnPmsiEntry OBJECT-TYPE
    SYNTAX      MvpnPmsiEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A conceptual row corresponding to a
        PMSI on this PE.
        "
    INDEX        {
        mvpnPmsiTunnelIfIndex
    }
    ::= { mvpnPmsiTable 1 }

MvpnPmsiEntry ::= SEQUENCE {
    mvpnPmsiTunnelIfIndex      InterfaceIndex,
    mvpnPmsiRD                 MplsL3VpnRouteDistinguisher,
    mvpnPmsiTunnelType         L2L3VpnMcastProviderTunnelType,
    mvpnPmsiTunnelAttribute    RowPointer,
    mvpnPmsiTunnelPimGroupAddrType InetAddressType,
    mvpnPmsiTunnelPimGroupAddr  InetAddress,
    mvpnPmsiEncapsulationType   INTEGER
}

mvpnPmsiTunnelIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A unique value for this conceptual row. Its value
        will be the same as that of the ifIndex object instance
        for the corresponding PMSI in ifTable.
        "
    REFERENCE
        "RFC 2863, Section 3.1.5
        "
    ::= { mvpnPmsiEntry 1 }

```

## mvpnPmsiRD OBJECT-TYPE

SYNTAX MplsL3VpnRouteDistinguisher  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The Route Distinguisher for this I-PMSI."  
 ::= { mvpnPmsiEntry 3 }

## mvpnPmsiTunnelType OBJECT-TYPE

SYNTAX L2L3VpnMcastProviderTunnelType  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The type of tunnel used to  
instantiate the PMSI corresponding to this entry."  
REFERENCE  
"RFC 6513, Section 2.6"  
 ::= { mvpnPmsiEntry 4 }

## mvpnPmsiTunnelAttribute OBJECT-TYPE

SYNTAX RowPointer  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"A pointer to a conceptual row representing  
the P-tunnel used by the PMSI in  
l2L3VpnMcastPmsiTunnelAttributeTable."  
 ::= { mvpnPmsiEntry 5 }

## mvpnPmsiTunnelPimGroupAddrType OBJECT-TYPE

SYNTAX InetAddressType  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The InetAddressType of the mvpnPmsiTunnelPimGroupAddr object  
that follows. When the PMSI corresponding to this entry  
does not use the PIM provider tunnel, i.e., the value of  
mvpnPmsiTunnelType is not one of pimSsm(3), pimAsm(4), or  
pimBidir(5), this object should be unknown(0)."  
 ::= { mvpnPmsiEntry 6 }

mvpnPmsiTunnelPimGroupAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The tunnel address that is used by the PMSI corresponding to this entry. When the PMSI corresponding to this entry does not use the PIM provider tunnel, i.e., the value of mvpnPmsiTunnelType is not one of pimSsm(3), pimAsm(4), or pimBidir(5), this object should be a zero-length octet string.

"

::= { mvpnPmsiEntry 7 }

mvpnPmsiEncapsulationType OBJECT-TYPE

SYNTAX INTEGER {  
                                 greIp (1),  
                                 ipIp (2),  
                                 mpls (3)  
                             }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The encapsulation type used for sending packets through the PMSI corresponding to this entry.

The enumerated encapsulation types and the corresponding descriptions are as follows:

greIp : Generic Routing Encapsulation (GRE)  
       (RFC 2784)

ipIp : IP-in-IP encapsulation (RFC 2003)

mpls : MPLS encapsulation (RFC 3032)

"

REFERENCE

"RFC 2003

RFC 2784

RFC 3032

RFC 6513, Section 12.1

"

::= { mvpnPmsiEntry 8 }

-- Table of S-PMSI-Specific Information

mvpnSpmsiTable OBJECT-TYPE

SYNTAX SEQUENCE OF MvpnSpmsiEntry

MAX-ACCESS not-accessible

```

STATUS          current
DESCRIPTION
    "A conceptual table containing information related
    to S-PMSIs on this PE.
    This table stores only S-PMSI-specific attribute
    information.  Generic PMSI attribute information of
    S-PMSIs is stored in mvpnPmsiTable.
    "
 ::= { mvpnObjects 5 }

mvpnSpmsiEntry OBJECT-TYPE
    SYNTAX      MvpnSpmsiEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "A conceptual row corresponding to an S-PMSI on this PE.
        Implementers need to be aware that if the total number of
        octets in mplsL3VpnVrfName, mvpnSpmsiCmcastGroupAddr, and
        mvpnSpmsiCmcastSourceAddr exceeds 113, the OIDs of column
        instances in this row will have more than 128 sub-identifiers
        and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3.
        "
    INDEX
        {
            mplsL3VpnVrfName,
            mvpnSpmsiCmcastGroupAddrType,
            mvpnSpmsiCmcastGroupAddr,
            mvpnSpmsiCmcastGroupPrefixLen,
            mvpnSpmsiCmcastSourceAddrType,
            mvpnSpmsiCmcastSourceAddr,
            mvpnSpmsiCmcastSourcePrefixLen
        }
    ::= { mvpnSpmsiTable 1 }

MvpnSpmsiEntry ::= SEQUENCE {
    mvpnSpmsiCmcastGroupAddrType  InetAddressType,
    mvpnSpmsiCmcastGroupAddr      InetAddress,
    mvpnSpmsiCmcastGroupPrefixLen InetAddressPrefixLength,
    mvpnSpmsiCmcastSourceAddrType  InetAddressType,
    mvpnSpmsiCmcastSourceAddr      InetAddress,
    mvpnSpmsiCmcastSourcePrefixLen InetAddressPrefixLength,
    mvpnSpmsiPmsiPointer           RowPointer
}

mvpnSpmsiCmcastGroupAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS   not-accessible
    STATUS      current

```

## DESCRIPTION

"The InetAddressType of the mvpnSpmsiCmcastGroupAddr object that follows.

"

::= { mvpnSpmsiEntry 1 }

## mvpnSpmsiCmcastGroupAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The group address of the C-flow assigned to the S-PMSI corresponding to this entry.

"

## REFERENCE

"[RFC 6513, Section 3.1](#)"

::= { mvpnSpmsiEntry 2 }

## mvpnSpmsiCmcastGroupPrefixLen OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The prefix length of the corresponding mvpnSpmsiCmcastGroupAddr object.

"

::= { mvpnSpmsiEntry 3 }

## mvpnSpmsiCmcastSourceAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The InetAddressType of the mvpnSpmsiCmcastSourceAddr object that follows.

"

::= { mvpnSpmsiEntry 4 }

## mvpnSpmsiCmcastSourceAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The source address of the C-flow assigned to the S-PMSI corresponding to this entry.

"

::= { mvpnSpmsiEntry 5 }

```
mvpnSpmsiCmcastSourcePrefixLen OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "The prefix length of the corresponding
         mvpnSpmsiCmcastSourceAddr object.
        "
    ::= { mvpnSpmsiEntry 6 }

mvpnSpmsiPmsiPointer OBJECT-TYPE
    SYNTAX      RowPointer
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A pointer to a conceptual row representing
         generic information of this S-PMSI in mvpnPmsiTable.
        "
    ::= { mvpnSpmsiEntry 7 }

-- Table of Statistics Pertaining to
-- Advertisements Sent/Received

mvpnAdvtStatsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MvpnAdvtStatsEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A conceptual table containing statistics pertaining to
         I-PMSI and S-PMSI advertisements sent/received by this PE.
        "
    ::= { mvpnObjects 6 }

mvpnAdvtStatsEntry OBJECT-TYPE
    SYNTAX      MvpnAdvtStatsEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A conceptual row corresponding to statistics
         pertaining to advertisements sent/received
         for a particular MVPN on this PE.

        Implementers need to be aware that if the total number of
        octets in mplsL3VpnVrfName and mvpnAdvtPeerAddr exceeds 115,
        then OIDs of column instances in this row will have more than
        128 sub-identifiers and cannot be accessed using SNMPv1,
        SNMPv2c, or SNMPv3.
        "
```

```

INDEX {
    mplsL3VpnVrfName,
    mvpnAdvtType,
    mvpnAdvtPeerAddrType,
    mvpnAdvtPeerAddr
}

 ::= { mvpnAdvtStatsTable 1 }

MvpnAdvtStatsEntry ::= SEQUENCE {
    mvpnAdvtType                INTEGER,
    mvpnAdvtPeerAddrType        InetAddressType,
    mvpnAdvtPeerAddr            InetAddress,
    mvpnAdvtSent                Counter32,
    mvpnAdvtReceived            Counter32,
    mvpnAdvtReceivedError       Counter32,
    mvpnAdvtReceivedMalformedTunnelType Counter32,
    mvpnAdvtReceivedMalformedTunnelId Counter32,
    mvpnAdvtLastSentTime        DateAndTime,
    mvpnAdvtLastReceivedTime    DateAndTime,
    mvpnAdvtCounterDiscontinuityTime TimeStamp
}

mvpnAdvtType OBJECT-TYPE
    SYNTAX      INTEGER {
                                intraAsIpmsi (0),
                                interAsIpmsi (1),
                                sPmsi        (2)
                            }
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "The PMSI type.

        The enumerated PMSI types and corresponding
        descriptions are as follows:

            intraAsIpmsi : Intra-AS Inclusive PMSI
            interAsIpmsi : Inter-AS Inclusive PMSI
            sPmsi        : Selective PMSI

        "
    REFERENCE
        "RFC 6513, Sec. 3.2.1"
    ::= { mvpnAdvtStatsEntry 1 }

mvpnAdvtPeerAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS   not-accessible
    STATUS       current

```

## DESCRIPTION

"The InetAddressType of the mvpnAdvtPeerAddr object that follows.

"

::= { mvpnAdvtStatsEntry 2 }

## mvpnAdvtPeerAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The address of a peer PE that exchanges advertisement with this PE.

"

::= { mvpnAdvtStatsEntry 3 }

## mvpnAdvtSent OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of advertisements successfully sent to the peer PE specified by the corresponding mvpnAdvtPeerAddr.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnAdvtCounterDiscontinuityTime object.

"

::= { mvpnAdvtStatsEntry 4 }

## mvpnAdvtReceived OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of advertisements received from the peer PE specified by the corresponding mvpnAdvtPeerAddr object. This includes advertisements that were discarded.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnAdvtCounterDiscontinuityTime object.

"

::= { mvpnAdvtStatsEntry 5 }



## mvpnAdvtReceivedError OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The total number of advertisements received from a peer PE, specified by the corresponding mvpnAdvtPeerAddr object, that were rejected due to an error(s) in the advertisement. The value of this object includes the error cases counted in the corresponding mvpnAdvtReceivedMalformedTunnelType and mvpnAdvtReceivedMalformedTunnelId objects.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnAdvtCounterDiscontinuityTime object.

"

::= { mvpnAdvtStatsEntry 6 }

## mvpnAdvtReceivedMalformedTunnelType OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The total number of advertisements received from the peer PE, specified by the corresponding mvpnAdvtPeerAddr object, that were rejected due to a malformed Tunnel Type in the PMSI Tunnel attribute.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnAdvtCounterDiscontinuityTime object.

"

## REFERENCE

"[RFC 6514, Section 5](#)"

::= { mvpnAdvtStatsEntry 7 }

## mvpnAdvtReceivedMalformedTunnelId OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The total number of advertisements received from the peer PE, specified by the corresponding mvpnAdvtPeerAddr object, that were rejected due to a malformed Tunnel Identifier in the PMSI Tunnel attribute. Discontinuities in the value

of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnAdvtCounterDiscontinuityTime object.

"

REFERENCE

"RFC 6514, Section 5"

::= { mvpnAdvtStatsEntry 8 }

mvpnAdvtLastSentTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp when the last advertisement was successfully sent by this PE. If no advertisement has been sent since the last re-initialization of this PE, this object will have a zero-length string.

"

::= { mvpnAdvtStatsEntry 9 }

mvpnAdvtLastReceivedTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp when the last advertisement was successfully received from the peer PE specified by the corresponding mvpnAdvtPeerAddr object and processed by this PE. If no advertisement has been received since the last re-initialization of this PE, this object will have a zero-length string.

"

::= { mvpnAdvtStatsEntry 10 }

mvpnAdvtCounterDiscontinuityTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime on the most recent occasion at which any one or more of this application's counters, viz., counters with the OID prefix 'mvpnAdvtSent', 'mvpnAdvtReceived', 'mvpnAdvtReceivedError', 'mvpnAdvtReceivedMalformedTunnelType', or 'mvpnAdvtReceivedMalformedTunnelId', suffered a

```

        discontinuity.
        If no such discontinuities have occurred since the
        last re-initialization of the local management
        subsystem, this object will have a zero value.
    "
    ::= { mvpnAdvtStatsEntry 11 }

-- Table of Multicast Routes in an MVPN

mvpnMrouteTable OBJECT-TYPE
    SYNTAX          SEQUENCE OF MvpnMrouteEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "A conceptual table containing multicast routing information
        corresponding to the MVRFs present on the PE.
    "
    ::= { mvpnObjects 7 }

mvpnMrouteEntry OBJECT-TYPE
    SYNTAX          MvpnMrouteEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "A conceptual row corresponding to a route for IP datagrams
        from a particular source and addressed to a particular
        IP multicast group address.

        Implementers need to be aware that if the total number of
        octets in mplsL3VpnVrfName, mvpnMrouteCmcastGroupAddr, and
        mvpnMrouteCmcastSourceAddrs exceeds 113, the OIDs of column
        instances in this row will have more than 128 sub-identifiers
        and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3.
    "
    INDEX {
        mplsL3VpnVrfName,
        mvpnMrouteCmcastGroupAddrType,
        mvpnMrouteCmcastGroupAddr,
        mvpnMrouteCmcastGroupPrefixLength,
        mvpnMrouteCmcastSourceAddrType,
        mvpnMrouteCmcastSourceAddrs,
        mvpnMrouteCmcastSourcePrefixLength
    }
    ::= { mvpnMrouteTable 1 }

```

```

MvpnMrouteEntry ::= SEQUENCE {
    mvpnMrouteCmcastGroupAddrType      InetAddressType,
    mvpnMrouteCmcastGroupAddr          InetAddress,
    mvpnMrouteCmcastGroupPrefixLength  InetAddressPrefixLength,
    mvpnMrouteCmcastSourceAddrType     InetAddressType,
    mvpnMrouteCmcastSourceAddr         InetAddress,
    mvpnMrouteCmcastSourcePrefixLength  InetAddressPrefixLength,
    mvpnMrouteUpstreamNeighborAddrType  InetAddressType,
    mvpnMrouteUpstreamNeighborAddr     InetAddress,
    mvpnMrouteInIfIndex                InterfaceIndexOrZero,
    mvpnMrouteExpiryTime               TimeTicks,
    mvpnMrouteProtocol                 IANAipMRouteProtocol,
    mvpnMrouteRtProtocol               IANAipRouteProtocol,
    mvpnMrouteRtAddrType               InetAddressType,
    mvpnMrouteRtAddr                   InetAddress,
    mvpnMrouteRtPrefixLength            InetAddressPrefixLength,
    mvpnMrouteRtType                   INTEGER,
    mvpnMrouteOctets                   Counter64,
    mvpnMroutePkts                     Counter64,
    mvpnMrouteTtlDroppedOctets          Counter64,
    mvpnMrouteTtlDroppedPackets         Counter64,
    mvpnMrouteDroppedInOctets           Counter64,
    mvpnMrouteDroppedInPackets          Counter64,
    mvpnMroutePmsiPointer               RowPointer,
    mvpnMrouteNumberOfLocalReplication  Unsigned32,
    mvpnMrouteNumberOfRemoteReplication Unsigned32,
    mvpnMrouteCounterDiscontinuityTime  TimeStamp
}

mvpnMrouteCmcastGroupAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The InetAddressType of the mvpnMrouteCmcastGroupAddr object
        that follows.
        "
    ::= { mvpnMrouteEntry 1 }

mvpnMrouteCmcastGroupAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The IP multicast group address that, along with
        the corresponding mvpnMrouteCmcastGroupPrefixLength object,
        identifies destinations for which this entry contains
        multicast routing information.

```

This address object is only significant up to mvpnMrouteCmcastGroupPrefixLength bits. The remaining address bits MUST be set to zero.

For addresses of type 'ipv4z' or 'ipv6z', the appended zone index is significant even though it lies beyond the prefix length. The use of these address types indicates that this forwarding state applies only within the given zone. Zone index zero is not valid in this table.

```
"
 ::= { mvpnMrouteEntry 2 }
```

mvpnMrouteCmcastGroupPrefixLength OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The length in bits of the mask that, along with the corresponding mvpnMrouteCmcastGroupAddr object, identifies destinations for which this entry contains multicast routing information.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z', this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z', this object must be in the range 8..128.

```
"
 ::= { mvpnMrouteEntry 3 }
```

mvpnMrouteCmcastSourceAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The InetAddressType of the mvpnMrouteCmcastSourceAddrs object that follows.

A value of unknown(0) indicates a non-source-specific entry, corresponding to all sources in the group. Otherwise, the value MUST be the same as the value of mvpnMrouteCmcastGroupAddrType.

```
"
 ::= { mvpnMrouteEntry 4 }
```

mvpnMrouteCmcastSourceAddrs OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The network address that, along with the corresponding mvpnMrouteCmcastSourcePrefixLength object, identifies the sources for which this entry contains multicast routing information.

This address object is only significant up to mvpnMrouteCmcastSourcePrefixLength bits.  
The remaining address bits MUST be set to zero.

For addresses of type 'ipv4z' or 'ipv6z', the appended zone index is significant even though it lies beyond the prefix length. The use of these address types indicates that this source address applies only within the given zone. Zone index zero is not valid in this table.

"

::= { mvpnMrouteEntry 5 }

## mvpnMrouteCmcastSourcePrefixLength OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The length in bits of the mask that, along with the corresponding mvpnMrouteCmcastSourceAddr object, identifies the sources for which this entry contains multicast routing information.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z', this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z', this object must be in the range 8..128.

If the corresponding InetAddressType is 'unknown', this object must be zero.

"

::= { mvpnMrouteEntry 6 }

## mvpnMrouteUpstreamNeighborAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The InetAddressType of the mvpnMrouteUpstreamNeighborAddr object that follows.

A value of unknown(0) indicates that the upstream neighbor is unknown, for example, in Bidirectional PIM (BIDIR-PIM).

```
"
REFERENCE
  "RFC 5015"
 ::= { mvpnMrouteEntry 7 }

mvpnMrouteUpstreamNeighborAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The address of the upstream neighbor (for example,
         the Reverse Path Forwarding (RPF) neighbor) from
         which IP datagrams from these sources represented
         by this entry to this multicast address are received.
        "
    ::= { mvpnMrouteEntry 8 }

mvpnMrouteInIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of ifIndex for the interface on which IP
         datagrams sent by these sources represented by this entry to
         this multicast address are received.

        A value of zero indicates that datagrams are not
        subject to an incoming interface check but may be accepted
        on multiple interfaces (for example, in BIDIR-PIM).
        "
    REFERENCE
        "RFC 5015"
    ::= { mvpnMrouteEntry 9 }

mvpnMrouteExpiryTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The minimum amount of time remaining before this entry will
         be aged out. The value zero indicates that the entry is not
         subject to aging. If the corresponding mvpnMrouteNextHopState
         object is pruned(1), this object represents the remaining
         time for the prune to expire after which the state will
         return to forwarding(2).
         If the corresponding mvpnMrouteNextHopState object is
         forwarding(2), this object indicates the time after which
         this entry will be removed from the table."
```

```
"
 ::= { mvpnMrouteEntry 10 }

mvpnMrouteProtocol OBJECT-TYPE
    SYNTAX      IANAipMRouteProtocol
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The multicast routing protocol via which this multicast
          forwarding entry was learned.
        "
    ::= { mvpnMrouteEntry 11 }

mvpnMrouteRtProtocol OBJECT-TYPE
    SYNTAX      IANAipRouteProtocol
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The routing protocol via which the route used to find the
          upstream or parent interface for this multicast forwarding
          entry was learned.
        "
    ::= { mvpnMrouteEntry 12 }

mvpnMrouteRtAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The InetAddressType of the mvpnMrouteRtAddr object
          that follows.
        "
    ::= { mvpnMrouteEntry 13 }

mvpnMrouteRtAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The address portion of the route used to find the upstream
          or parent interface for this multicast forwarding entry.

        This address object is only significant up to
        mvpnMrouteRtPrefixLength bits.  The remaining address bits
        MUST be set to zero.

        For addresses of type 'ipv4z' or 'ipv6z', the appended zone
        index is significant even though it lies beyond the prefix
```



length. The use of these address types indicates that this forwarding state applies only within the given zone. Zone index zero is not valid in this table.

"

::= { mvpnMrouteEntry 14 }

mvpnMrouteRtPrefixLength OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The length in bits of the mask associated with the route used to find the upstream or parent interface for this multicast forwarding entry.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z', this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z', this object must be in the range 8..128.

"

::= { mvpnMrouteEntry 15 }

mvpnMrouteRtType OBJECT-TYPE

SYNTAX INTEGER {  
                         unicast (1),  
                         multicast (2)  
                     }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The reason for placing the route in the (logical) multicast Routing Information Base (RIB).

The enumerated reasons and the corresponding descriptions are as follows:

unicast:

The route would normally be placed only in the unicast RIB, but it was placed in the multicast RIB by local configuration, such as when running PIM over RIP.

multicast:

The route was explicitly added to the multicast RIB by the routing protocol, such as the Distance Vector Multicast Routing Protocol (DVMRP) or Multiprotocol BGP.

"

::= { mvpnMrouteEntry 16 }

## mvpnMrouteOctets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of octets contained in IP datagrams that were received from sources represented by this entry and addressed to this multicast group address and that were forwarded by this router.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

::= { mvpnMrouteEntry 17 }

## mvpnMroutePkts OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of packets routed using this multicast route entry.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

::= { mvpnMrouteEntry 18 }

## mvpnMrouteTtlDroppedOctets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of octets contained in IP datagrams that this router has received from sources represented by this entry and addressed to this multicast group address, which were dropped due to Time To Live (TTL) issues. TTL issues occur when the TTL (IPv4) or Hop Limit (IPv6) of the incoming packet was decremented to zero or to a value less than ipMcastInterfaceTtl of the corresponding interface.

The ipMcastInterfaceTtl object is defined in IPMCAST-MIB (RFC 5132) and represents the datagram TTL

threshold for the interface. Any IP multicast datagrams with a TTL (IPv4) or Hop Limit (IPv6) less than this threshold will not be forwarded out of the interface. The default value of zero means all multicast packets are forwarded out of the interface. A value of 256 means that no multicast packets are forwarded out of the interface.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

REFERENCE

"RFC 5132, Section 6

"

::= { mvpnMrouteEntry 19 }

mvpnMrouteTtlDroppedPackets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets that this router has received from the sources represented by this entry and addressed to this multicast group address, which were dropped due to Time To Live (TTL) issues. TTL issues occur when the TTL (IPv4) or Hop Limit (IPv6) of the incoming packet was decremented to zero or to a value less than ipMcastInterfaceTtl of the corresponding interface.

The ipMcastInterfaceTtl object is defined in IPMCAST-MIB (RFC 5132) and represents the datagram TTL threshold for the interface. Any IP multicast datagrams with a TTL (IPv4) or Hop Limit (IPv6) less than this threshold will not be forwarded out of the interface. The default value of zero means all multicast packets are forwarded out of the interface. A value of 256 means that no multicast packets are forwarded out of the interface.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

REFERENCE

"RFC 5132, Section 6

"

::= { mvpnMrouteEntry 20 }

## mvpnMrouteDroppedInOctets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of octets contained in IP datagrams that this router has received from sources represented by this entry and addressed to this multicast group address, which were dropped due to an error(s). The value of this object includes the octets counted in the corresponding mvpnMrouteTtlDroppedOctets object.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

::= { mvpnMrouteEntry 21 }

## mvpnMrouteDroppedInPackets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of packets that this router has received from sources represented by this entry and addressed to this multicast group address, which were dropped due to an error(s). The value of this object includes the number of octets counted in the corresponding mvpnMrouteTtlDroppedPackets object.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

::= { mvpnMrouteEntry 22 }

## mvpnMroutePmsiPointer OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"A pointer to a conceptual row representing the corresponding I-PMSI in mvpnPmsiTable or S-PMSI in mvpnSpmsiTable that this C-multicast route is using.

"

::= { mvpnMrouteEntry 23 }

```
mvpnMrouteNumberOfLocalReplication OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "Number of replications for local receivers.
        For example, if an ingress PE needs to send traffic out of
        N PE-CE interfaces, then mvpnMrouteNumberOfLocalReplication
        is N.
        "
    ::= { mvpnMrouteEntry 24 }

mvpnMrouteNumberOfRemoteReplication OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "Number of local replications for remote PEs. For example,
        if the number of remote PEs that need to receive traffic is N,
        then mvpnMrouteNumberOfRemoteReplication is N in case of
        Ingress Replication, but it may be less than N in case of
        RSVP-TE or mLDP Point-to-Multipoint (P2MP) tunnels, depending
        on the actual number of replications the PE needs to do.
        "
    ::= { mvpnMrouteEntry 25 }

mvpnMrouteCounterDiscontinuityTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The value of sysUpTime on the most recent occasion
        at which any one or more of this application's
        counters, viz., counters with the OID prefix
        'mvpnMrouteOctets', 'mvpnMroutePkts',
        'mvpnMrouteTtlDroppedOctets',
        'mvpnMrouteTtlDroppedPackets',
        'mvpnMrouteDroppedInOctets', or 'mvpnMrouteDroppedInPackets',
        suffered a discontinuity.
        If no such discontinuities have occurred since the
        last re-initialization of the local management
        subsystem, this object will have a zero value.
        "
    ::= { mvpnMrouteEntry 26 }
```

-- Table of Next Hops for Multicast Routes in an MVPN

mvpnMrouteNextHopTable OBJECT-TYPE

SYNTAX SEQUENCE OF MvpnMrouteNextHopEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A conceptual table containing information on the next hops for routing IP multicast datagrams. Each entry is one of a list of next hops for a set of sources sending to a multicast group address.

"

::= { mvpnObjects 8 }

mvpnMrouteNextHopEntry OBJECT-TYPE

SYNTAX MvpnMrouteNextHopEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A conceptual row corresponding to a next hop to which IP multicast datagrams from a set of sources to an IP multicast group address are routed.

Implementers need to be aware that if the total number of octets in mplsL3VpnVrfName, mvpnMrouteNextHopGroupAddr, mvpnMrouteNextHopSourceAddrs, and mvpnMrouteNextHopAddr exceeds 111, the OIDs of column instances in this row will have more than 128 sub-identifiers and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3.

"

```
INDEX      {
            mplsL3VpnVrfName,
            mvpnMrouteNextHopGroupAddrType,
            mvpnMrouteNextHopGroupAddr,
            mvpnMrouteNextHopGroupPrefixLength,
            mvpnMrouteNextHopSourceAddrType,
            mvpnMrouteNextHopSourceAddrs,
            mvpnMrouteNextHopSourcePrefixLength,
            mvpnMrouteNextHopIfIndex,
            mvpnMrouteNextHopAddrType,
            mvpnMrouteNextHopAddr
          }
```

::= { mvpnMrouteNextHopTable 1 }

MvpnMrouteNextHopEntry ::= SEQUENCE {

mvpnMrouteNextHopGroupAddrType

InetAddressType,

mvpnMrouteNextHopGroupAddr

InetAddress,

mvpnMrouteNextHopGroupPrefixLength	InetAddressPrefixLength,
mvpnMrouteNextHopSourceAddrType	InetAddressType,
mvpnMrouteNextHopSourceAddrs	InetAddress,
mvpnMrouteNextHopSourcePrefixLength	InetAddressPrefixLength,
mvpnMrouteNextHopIfIndex	InterfaceIndex,
mvpnMrouteNextHopAddrType	InetAddressType,
mvpnMrouteNextHopAddr	InetAddress,
mvpnMrouteNextHopState	INTEGER,
mvpnMrouteNextHopExpiryTime	TimeTicks,
mvpnMrouteNextHopClosestMemberHops	Unsigned32,
mvpnMrouteNextHopProtocol	IANAipMRouteProtocol,
mvpnMrouteNextHopOctets	Counter64,
mvpnMrouteNextHopPkts	Counter64,
mvpnMrouteNextHopCounterDiscontinuityTime	TimeStamp

}

mvpnMrouteNextHopGroupAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The InetAddressType of the mvpnMrouteNextHopGroupAddr object that follows.

"

::= { mvpnMrouteNextHopEntry 1 }

mvpnMrouteNextHopGroupAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IP multicast group address that, along with the corresponding mvpnMrouteNextHopGroupPrefixLength object, identifies destinations for which this entry contains multicast forwarding information.

This address object is only significant up to mvpnMrouteNextHopGroupPrefixLength bits. The remaining address bits MUST be set to zero.

For addresses of type 'ipv4z' or 'ipv6z', the appended zone index is significant even though it lies beyond the prefix length. The use of these address types indicates that this forwarding state applies only within the given zone. Zone index zero is not valid in this table.

"

::= { mvpnMrouteNextHopEntry 2 }

```
mvpnMrouteNextHopGroupPrefixLength OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The length in bits of the mask that, along with
        the corresponding mvpnMrouteGroupAddr object,
        identifies destinations for which this entry contains
        multicast routing information.

        If the corresponding InetAddressType is 'ipv4' or 'ipv4z',
        this object must be in the range 4..32.
        If the corresponding InetAddressType is 'ipv6' or 'ipv6z',
        this object must be in the range 8..128.
        "
    ::= { mvpnMrouteNextHopEntry 3 }
```

```
mvpnMrouteNextHopSourceAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The InetAddressType of the mvpnMrouteNextHopSourceAddrs
        object that follows.

        A value of unknown(0) indicates a non-source-specific entry,
        corresponding to all sources in the group. Otherwise, the
        value MUST be the same as the value of
        mvpnMrouteNextHopGroupAddrType.
        "
    ::= { mvpnMrouteNextHopEntry 4 }
```

```
mvpnMrouteNextHopSourceAddrs OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The network address that, along with the
        corresponding mvpnMrouteNextHopSourcePrefixLength object,
        identifies the sources for which this entry specifies
        a next hop.

        This address object is only significant up to
        mvpnMrouteNextHopSourcePrefixLength bits. The remaining
        address bits MUST be set to zero.

        For addresses of type 'ipv4z' or 'ipv6z', the appended zone
        index is significant even though it lies beyond the prefix
```



length. The use of these address types indicates that this source address applies only within the given zone. Zone index zero is not valid in this table.

"

::= { mvpnMrouteNextHopEntry 5 }

mvpnMrouteNextHopSourcePrefixLength OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The length in bits of the mask that, along with the corresponding mvpnMrouteNextHopSourceAddr object, identifies the sources for which this entry specifies a next hop.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z', this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z', this object must be in the range 8..128.

If the corresponding InetAddressType is 'unknown', this object must be zero.

"

::= { mvpnMrouteNextHopEntry 6 }

mvpnMrouteNextHopIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The ifIndex value of the outgoing interface for this next hop.

"

::= { mvpnMrouteNextHopEntry 7 }

mvpnMrouteNextHopAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The InetAddressType of the mvpnMrouteNextHopAddr object that follows.

"

::= { mvpnMrouteNextHopEntry 8 }

mvpnMrouteNextHopAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

```
STATUS      current
DESCRIPTION
    "The address of the next hop specific to this entry.  For
    most interfaces, this is identical to
    mvpnMrouteNextHopGroupAddr.  Non-Broadcast Multi-Access
    (NBMA) interfaces, however, may have multiple next-hop
    addresses out of a single outgoing interface.
    "
 ::= { mvpnMrouteNextHopEntry 9 }

mvpnMrouteNextHopState OBJECT-TYPE
    SYNTAX      INTEGER {
                                pruned(1),
                                forwarding(2)
                        }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "An indication of whether the outgoing interface and next
        hop represented by this entry is currently being used to
        forward IP datagrams.

        The enumerated states and the corresponding
        descriptions are as follows:

            pruned      : this entry is not currently being used.
            forwarding  : this entry is currently being used.
        "
 ::= { mvpnMrouteNextHopEntry 10 }

mvpnMrouteNextHopExpiryTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The minimum amount of time remaining before this entry will
        be aged out.  If mvpnMrouteNextHopState is pruned(1),
        this object represents the remaining time for the prune
        to expire after which the state will return to forwarding(2).
        If mvpnMrouteNextHopState is forwarding(2),
        this object indicates the time after which this
        entry will be removed from the table.

        The value of zero indicates that the entry is not subject to
        aging.
        "
 ::= { mvpnMrouteNextHopEntry 11 }
```

```
mvpnMrouteNextHopClosestMemberHops OBJECT-TYPE
    SYNTAX      Unsigned32 (0..256)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The minimum number of hops between this router and any
        member of this IP multicast group reached via this next hop
        on the corresponding outgoing interface. Any IP multicast
        datagram for the group that has a TTL (IPv4) or a Hop Count
        (IPv6) less than mvpnMrouteNextHopClosestMemberHops will
        not be forwarded through this interface.

        A value of zero means all multicast datagrams are forwarded
        out of the interface. A value of 256 means that no multicast
        datagrams are forwarded out of the interface.

        This is an optimization applied by multicast routing
        protocols that explicitly track hop counts to downstream
        listeners. Multicast protocols that are not aware of hop
        counts to downstream listeners set this object to zero.
        "
    ::= { mvpnMrouteNextHopEntry 12 }
```

```
mvpnMrouteNextHopProtocol OBJECT-TYPE
    SYNTAX      IANAipMRouteProtocol
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The routing protocol via which this next hop was learned.
        "
    ::= { mvpnMrouteNextHopEntry 13 }
```

```
mvpnMrouteNextHopOctets OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of octets of multicast packets that have been
        forwarded using this route.

        Discontinuities in the value of this counter can
        occur at re-initialization of the management system
        and at other times as indicated by the corresponding
        mvpnMrouteNextHopCounterDiscontinuityTime object.
        "
    ::= { mvpnMrouteNextHopEntry 14 }
```

## mvpnMrouteNextHopPkts OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of packets that have been forwarded using this route.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the corresponding mvpnMrouteNextHopCounterDiscontinuityTime object.

"

::= { mvpnMrouteNextHopEntry 15 }

## mvpnMrouteNextHopCounterDiscontinuityTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The value of sysUpTime on the most recent occasion at which any one or more of this application's counters, viz., counters with the OID prefix 'mvpnMrouteNextHopOctets' or 'mvpnMrouteNextHopPackets', suffered a discontinuity.

If no such discontinuities have occurred since the last re-initialization of the local management subsystem, this object will have a zero value.

"

::= { mvpnMrouteNextHopEntry 16 }

## -- MVPN Notifications

## mvpnMvrfActionTaken NOTIFICATION-TYPE

```
OBJECTS {
    mvpnGenMvrfCreationTime,
    mvpnGenMvrfLastAction,
    mvpnGenMvrfLastActionTime,
    mvpnGenMvrfCreationTime,
    mvpnGenCmcastRouteProtocol,
    mvpnGenUmhSelection,
    mvpnGenCustomerSiteType
}
```

STATUS current

## DESCRIPTION

"mvpnMvrfActionTaken notifies about a change in an MVRP on the PE. The change itself will be given by mvpnGenMvrfLastAction.

```
"
 ::= { mvpnNotifications 1 }

-- MVPN MIB Conformance Information

mvpnGroups      OBJECT IDENTIFIER ::= { mvpnConformance 1 }
mvpnCompliances OBJECT IDENTIFIER ::= { mvpnConformance 2 }

-- Compliance Statements

mvpnModuleFullCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "Compliance statement for agents that provide full support
        for BGP-MPLS-LAYER3-VPN-MULTICAST-MIB.
        "
    MODULE -- this module
    MANDATORY-GROUPS {
        mvpnScalarGroup,
        mvpnGenericGroup,
        mvpnPmsiGroup,
        mvpnAdvtStatsGroup,
        mvpnMrouteGroup,
        mvpnMrouteNextHopGroup,
        mvpnNotificationGroup
    }

    GROUP mvpnBgpScalarGroup
        DESCRIPTION
            "This group is mandatory for systems that support
            BGP-MVPN.
            "

    GROUP mvpnBgpGroup
        DESCRIPTION
            "This group is mandatory for systems that support
            BGP-MVPN.
            "

 ::= { mvpnCompliances 1 }

mvpnModuleReadOnlyCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION "Compliance requirement for implementations that
        only provide read-only support for
        BGP-MPLS-LAYER3-VPN-MULTICAST-MIB. Such devices
        can then be monitored but cannot be configured
        using this MIB module.
```

```
"
MODULE -- this module
MANDATORY-GROUPS {
    mvpnScalarGroup,
    mvpnGenericGroup,
    mvpnPmsiGroup,
    mvpnAdvtStatsGroup,
    mvpnMrouteGroup,
    mvpnMrouteNextHopGroup,
    mvpnNotificationGroup
}

GROUP mvpnBgpScalarGroup
DESCRIPTION
    "This group is mandatory for systems that support
    BGP-MVPN.
    "

GROUP mvpnBgpGroup
DESCRIPTION
    "This group is mandatory for systems that support
    BGP-MVPN.
    "

OBJECT      mvpnSPTunnelLimit
MIN-ACCESS  read-only
DESCRIPTION "Write access is not required."

OBJECT      mvpnBgpCmcastRouteWithdrawalTimer
MIN-ACCESS  read-only
DESCRIPTION "Write access is not required."

OBJECT      mvpnBgpSrcSharedTreeJoinTimer
MIN-ACCESS  read-only
DESCRIPTION "Write access is not required."

OBJECT      mvpnBgpMsgRateLimit
MIN-ACCESS  read-only
DESCRIPTION "Write access is not required."

OBJECT      mvpnBgpMaxSpmsiAdRoutes
MIN-ACCESS  read-only
DESCRIPTION "Write access is not required."

OBJECT      mvpnBgpMaxSpmsiAdRouteFreq
MIN-ACCESS  read-only
DESCRIPTION "Write access is not required."

OBJECT      mvpnBgpMaxSrcActiveAdRoutes
```

```
MIN-ACCESS    read-only
DESCRIPTION   "Write access is not required."

OBJECT        mvpnBgpMaxSrcActiveAdRouteFreq
MIN-ACCESS    read-only
DESCRIPTION   "Write access is not required."

::= { mvpnCompliances 2 }

mvpnModuleAdvtStatsCompliance MODULE-COMPLIANCE
STATUS        current
DESCRIPTION   "Compliance statement for agents that support
               the monitoring of the statistics pertaining
               to advertisements sent/received by a PE.
               "
MODULE        -- this module

MANDATORY-GROUPS {
    mvpnAdvtStatsGroup
}

::= { mvpnCompliances 3 }

-- Units of Conformance

mvpnScalarGroup    OBJECT-GROUP
OBJECTS {
    mvpnMvrfs,
    mvpnV4Mvrfs,
    mvpnV6Mvrfs,
    mvpnPimV4Mvrfs,
    mvpnPimV6Mvrfs,
    mvpnSPTunnelLimit
}
STATUS        current
DESCRIPTION   "These objects are used to monitor/manage
               global statistics and parameters.
               "
::= { mvpnGroups 1 }

mvpnBgpScalarGroup    OBJECT-GROUP
OBJECTS {
    mvpnMldpMvrfs,
    mvpnBgpV4Mvrfs,
    mvpnBgpV6Mvrfs,
    mvpnBgpCmcastRouteWithdrawalTimer,
```

```
        mvpnBgpSrcSharedTreeJoinTimer
    }
    STATUS          current
    DESCRIPTION
        "These objects are used to monitor/manage
        BGP-MVPN-specific global parameters.
        "
    ::= { mvpnGroups 2 }

mvpnGenericGroup    OBJECT-GROUP
    OBJECTS {
        mvpnGenMvrfLastAction,
        mvpnGenMvrfLastActionTime,
        mvpnGenMvrfCreationTime,
        mvpnGenCmcastRouteProtocol,
        mvpnGenIpmsiInfo,
        mvpnGenInterAsPmsiInfo,
        mvpnGenUmhSelection,
        mvpnGenCustomerSiteType
    }
    STATUS          current
    DESCRIPTION
        "These objects are used to monitor MVPNs on a PE.
        "
    ::= { mvpnGroups 3 }

mvpnBgpGroup        OBJECT-GROUP
    OBJECTS {
        mvpnBgpMode,
        mvpnBgpVrfRouteImportExtendedCommunity,
        mvpnBgpSrcASEExtendedCommunity,
        mvpnBgpMsgRateLimit,
        mvpnBgpMaxSpmsiAdRoutes,
        mvpnBgpMaxSpmsiAdRouteFreq,
        mvpnBgpMaxSrcActiveAdRoutes,
        mvpnBgpMaxSrcActiveAdRouteFreq
    }
    STATUS          current
    DESCRIPTION
        "These objects are used to monitor/manage
        MVPN-wise BGP-specific parameters.
        "
    ::= { mvpnGroups 4 }

mvpnPmsiGroup       OBJECT-GROUP
    OBJECTS {
        mvpnPmsiRD,
        mvpnPmsiTunnelType,
```



```

        mvpnPmsiTunnelAttribute,
        mvpnPmsiTunnelPimGroupAddrType,
        mvpnPmsiTunnelPimGroupAddr,
        mvpnPmsiEncapsulationType,
        mvpnSpmsiPmsiPointer
    }
STATUS      current
DESCRIPTION
    "These objects are used to monitor
     I-PMSI and S-PMSI tunnels on a PE.
    "
::= { mvpnGroups 5 }

mvpnAdvtStatsGroup      OBJECT-GROUP
OBJECTS {
    mvpnAdvtSent,
    mvpnAdvtReceived,
    mvpnAdvtReceivedError,
    mvpnAdvtReceivedMalformedTunnelType,
    mvpnAdvtReceivedMalformedTunnelId,
    mvpnAdvtLastSentTime,
    mvpnAdvtLastReceivedTime,
    mvpnAdvtCounterDiscontinuityTime
}
STATUS      current
DESCRIPTION
    "These objects are used to monitor
     the statistics pertaining to I-PMSI and S-PMSI
     advertisements sent/received by a PE.
    "
::= { mvpnGroups 6 }

mvpnMrouteGroup      OBJECT-GROUP
OBJECTS {
    mvpnMrouteUpstreamNeighborAddrType,
    mvpnMrouteUpstreamNeighborAddr,
    mvpnMrouteInIfIndex,
    mvpnMrouteExpiryTime,
    mvpnMrouteProtocol,
    mvpnMrouteRtProtocol,
    mvpnMrouteRtAddrType,
    mvpnMrouteRtAddr,
    mvpnMrouteRtPrefixLength,
    mvpnMrouteRtType,
    mvpnMrouteOctets,
    mvpnMroutePkts,
    mvpnMrouteTtlDroppedOctets,
    mvpnMrouteTtlDroppedPackets,

```

```
        mvpnMrouteDroppedInOctets,
        mvpnMrouteDroppedInPackets,
        mvpnMroutePmsiPointer,
        mvpnMrouteNumberOfLocalReplication,
        mvpnMrouteNumberOfRemoteReplication,
        mvpnMrouteCounterDiscontinuityTime
    }
    STATUS      current
    DESCRIPTION
        "These objects are used to monitor multicast routing
        information corresponding to the MVRFs on a PE.
        "
    ::= { mvpnGroups 7 }

mvpnMrouteNextHopGroup OBJECT-GROUP
    OBJECTS {
        mvpnMrouteNextHopState,
        mvpnMrouteNextHopExpiryTime,
        mvpnMrouteNextHopClosestMemberHops,
        mvpnMrouteNextHopProtocol,
        mvpnMrouteNextHopOctets,
        mvpnMrouteNextHopPkts,
        mvpnMrouteNextHopCounterDiscontinuityTime
    }
    STATUS      current
    DESCRIPTION
        "These objects are used to monitor the information on
        next hops for routing datagrams to MVPNs on a PE.
        "
    ::= { mvpnGroups 8 }

mvpnNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS {
        mvpnMvrfActionTaken
    }
    STATUS      current
    DESCRIPTION
        "Objects required for MVPN notifications."
    ::= { mvpnGroups 9 }

END
```

#### 4. Security Considerations

This MIB module contains some read-only objects that may be deemed sensitive. It also contains some read-write objects whose settings will change the device's MVPN-related behavior. Appropriate security procedures that are related to SNMP in general but are not specific to this MIB module need to be implemented by concerned operators.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection opens devices to attack. These are the tables and objects and their sensitivity/vulnerability:

- o mvpnSPTunnelLimit

The value of this object is used to control the maximum number of selective provider tunnels that a PE allows for a particular MVPN. Access to this object may be abused to impact the performance of the PE or prevent the PE from having new selective provider tunnels.

- o mvpnBgpCmcastRouteWithdrawalTimer

The value of this object is used to control the delay for the advertisement of withdrawals of C-multicast routes. Access to this object may be abused to impact the performance of a PE.

- o mvpnBgpSrcSharedTreeJoinTimer

The value of this object is used to control the delay for the advertisement of Source/Shared Tree Join C-multicast routes. Access to this object may be abused to impact the propagation of C-multicast routing information.

- o mvpnBgpMsgRateLimit

The value of this object is used to control the upper bound for the rate of BGP C-multicast routing information message exchange among PEs. Access to this object may be abused to impact the performance of the PE or disrupt the C-multicast routing information message exchange using BGP.

- o mvpnBgpMaxSpmsiAdRoutes

The value of this object is used to control the upper bound for the number of S-PMSI A-D routes. Access to this object may be abused to impact the performance of the PE or prevent the PE from receiving S-PMSI A-D routes.

- o mvpnBgpMaxSpmsiAdRouteFreq

The value of this object is used to control the upper bound for the frequency of S-PMSI A-D route generation. Access to this object may be abused to impact the performance of the PE or prevent the PE from generating new S-PMSI A-D routes.

- o mvpnBgpMaxSrcActiveAdRoutes

The value of this object is used to control the upper bound for the number of Source Active A-D routes. Access to this object may be abused to impact the performance of the PE or prevent the PE from receiving Source Active A-D routes.

- o mvpnBgpMaxSrcActiveAdRouteFreq

The value of this object is used to control the upper bound for the frequency of Source Active A-D route generation. Access to this object may be abused to impact the performance of the PE or prevent the PE from generating new Source Active A-D routes.

Some of the objects in this MIB module may be considered sensitive or vulnerable in some network environments. This includes INDEX objects with a MAX-ACCESS of not-accessible, and any indices from other modules exposed via AUGMENTS. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o The address-related objects in this MIB module may have impact on privacy and security. These objects may reveal the locations of senders and recipients.

- \* mvpnPmsiTunnelPimGroupAddr

- \* mvpnSpmsiCmcastGroupAddr

- \* mvpnSpmsiCmcastSourceAddr

- \* mvpnAdvtPeerAddr

- \* mvpnMrouteCmcastGroupAddr
- \* mvpnMrouteCmcastSourceAddrs
- \* mvpnMrouteUpstreamNeighborAddr
- \* mvpnMrouteRtAddr
- \* mvpnMrouteNextHopGroupAddr
- \* mvpnMrouteNextHopSourceAddrs
- \* mvpnMrouteNextHopAddr

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations SHOULD provide the security features described by the SNMPv3 framework (see [RFC3410]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 5. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER value recorded in the "SMI Network Management MGMT Codes Internet-standard MIB" registry:

Name	Description	OBJECT IDENTIFIER value
-----	-----	-----
mvpnMIB	BGP-MPLS-LAYER3-VPN-MULTICAST-MIB	{ mib-2 243 }

## 6. References

### 6.1. Normative References

- [RFC2003] Perkins, C., "IP Encapsulation within IP", [RFC 2003](#), DOI 10.17487/RFC2003, October 1996, <<https://www.rfc-editor.org/info/rfc2003>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), DOI 10.17487/RFC2578, April 1999, <<https://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), DOI 10.17487/RFC2579, April 1999, <<https://www.rfc-editor.org/info/rfc2579>>.
- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), DOI 10.17487/RFC2580, April 1999, <<https://www.rfc-editor.org/info/rfc2580>>.
- [RFC2784] Farinacci, D., Li, T., Hanks, S., Meyer, D., and P. Traina, "Generic Routing Encapsulation (GRE)", [RFC 2784](#), DOI 10.17487/RFC2784, March 2000, <<https://www.rfc-editor.org/info/rfc2784>>.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), DOI 10.17487/RFC2863, June 2000, <<https://www.rfc-editor.org/info/rfc2863>>.
- [RFC3032] Rosen, E., Tappan, D., Fedorkow, G., Rekhter, Y., Farinacci, D., Li, T., and A. Conta, "MPLS Label Stack Encoding", [RFC 3032](#), DOI 10.17487/RFC3032, January 2001, <<https://www.rfc-editor.org/info/rfc3032>>.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, [RFC 3414](#), DOI 10.17487/RFC3414, December 2002, <<https://www.rfc-editor.org/info/rfc3414>>.

- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", [RFC 3826](#), DOI 10.17487/RFC3826, June 2004, <<https://www.rfc-editor.org/info/rfc3826>>.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), DOI 10.17487/RFC4001, February 2005, <<https://www.rfc-editor.org/info/rfc4001>>.
- [RFC4364] Rosen, E. and Y. Rekhter, "BGP/MPLS IP Virtual Private Networks (VPNs)", [RFC 4364](#), DOI 10.17487/RFC4364, February 2006, <<https://www.rfc-editor.org/info/rfc4364>>.
- [RFC4382] Nadeau, T., Ed. and H. van der Linde, Ed., "MPLS/BGP Layer 3 Virtual Private Network (VPN) Management Information Base", [RFC 4382](#), DOI 10.17487/RFC4382, February 2006, <<https://www.rfc-editor.org/info/rfc4382>>.
- [RFC5132] McWalter, D., Thaler, D., and A. Kessler, "IP Multicast MIB", [RFC 5132](#), DOI 10.17487/RFC5132, December 2007, <<https://www.rfc-editor.org/info/rfc5132>>.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", STD 78, [RFC 5591](#), DOI 10.17487/RFC5591, June 2009, <<https://www.rfc-editor.org/info/rfc5591>>.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", [RFC 5592](#), DOI 10.17487/RFC5592, June 2009, <<https://www.rfc-editor.org/info/rfc5592>>.
- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", STD 78, [RFC 6353](#), DOI 10.17487/RFC6353, July 2011, <<https://www.rfc-editor.org/info/rfc6353>>.
- [RFC6513] Rosen, E., Ed. and R. Aggarwal, Ed., "Multicast in MPLS/BGP IP VPNs", [RFC 6513](#), DOI 10.17487/RFC6513, February 2012, <<https://www.rfc-editor.org/info/rfc6513>>.
- [RFC6514] Aggarwal, R., Rosen, E., Morin, T., and Y. Rekhter, "BGP Encodings and Procedures for Multicast in MPLS/BGP IP VPNs", [RFC 6514](#), DOI 10.17487/RFC6514, February 2012, <<https://www.rfc-editor.org/info/rfc6514>>.

- [RFC6625] Rosen, E., Ed., Rekhter, Y., Ed., Hendrickx, W., and R. Qiu, "Wildcards in Multicast VPN Auto-Discovery Routes", [RFC 6625](#), DOI 10.17487/RFC6625, May 2012, <<https://www.rfc-editor.org/info/rfc6625>>.
- [RFC7761] Fenner, B., Handley, M., Holbrook, H., Kouvelas, I., Parekh, R., Zhang, Z., and L. Zheng, "Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification (Revised)", STD 83, [RFC 7761](#), DOI 10.17487/RFC7761, March 2016, <<https://www.rfc-editor.org/info/rfc7761>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8502] Zhang, Z. and H. Tsunoda, "L2L3 VPN Multicast MIB", [RFC 8502](#), DOI 10.17487/RFC8502, December 2018, <<https://www.rfc-editor.org/info/rfc8502>>.

## 6.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), DOI 10.17487/RFC3410, December 2002, <<https://www.rfc-editor.org/info/rfc3410>>.



### Acknowledgements

An earlier draft version of this document was coauthored by Zhaohui (Jeffrey) Zhang, Saud Asif, Andy Green, Sameer Gulrajani, and Pradeep G. Jain. That document, in turn, was based on an earlier document written by Susheela Vaidya, Thomas D. Nadeau, and Harmen Van der Linde.

This document also borrows heavily from the design and descriptions of ipMcastRouteTable and ipMcastRouteNextHopTable from IPMCAST-MIB [[RFC5132](#)].

Glenn Mansfield Keeni did the MIB Doctor review and provided valuable comments.

### Author's Address

Hiroshi Tsunoda  
Tohoku Institute of Technology  
35-1, Yagiyama Kasumi-cho, Taihaku-ku  
Sendai 982-8577  
Japan

Phone: +81-22-305-3411  
Email: [tsuno@m.ieice.org](mailto:tsuno@m.ieice.org)