Internet Engineering Task Force (IETF)
Request for Comments: 6945
Category: Standards Track
ISSN: 2070-1721

R. Bush
Internet Initiative Japan
B. Wijnen
RIPE NCC
K. Patel
Cisco Systems
M. Baer
SPARTA

May 2013

Definitions of Managed Objects for the Resource Public Key Infrastructure (RPKI) to Router Protocol

Abstract

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects used for monitoring the Resource Public Key Infrastructure (RPKI) to Router Protocol.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at http://www.rfc-editor.org/info/rfc6945.

Table of Contents

1. Introduction

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines objects used for monitoring the RPKI-Router Protocol [RFC6810].

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410]. Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB.

MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579], and STD 58, RFC 2580 [RFC2580].

3. Overview

The objects defined in this document are used to monitor the RPKI-Router Protocol [RFC6810]. The MIB module defined here is broken into these tables: the RPKI-Router Cache Server (Connection) Table, the RPKI-Router Cache Server Errors Table, and the RPKI-Router Prefix Origin Table.

The RPKI-Router Cache Server Table contains information about the state and current activity of connections with the RPKI-router cache servers. It also contains counters for the number of messages received and sent, plus the number of announcements, withdrawals, and active records. The RPKI-Router Cache Server Errors Table contains counters of occurrences of errors on the connections (if any). The RPKI-Router Prefix Origin Table contains IP prefixes with their minimum and maximum prefix lengths and the Origin Autonomous System (AS). This data is the collective set of information received from all RPKI cache servers that the router is connected with. The cache servers are running the RPKI-Router Protocol.

Two notifications have been defined to inform a Network Management Station (NMS) or operators about changes in the connection state of the connections listed in the RPKI-Router Cache Server (Connection) Table.

4. Definitions

The following MIB module imports definitions from [RFC2578], [RFC2579], [RFC2580], [RFC4001], and [RFC2287]. That means we have a normative reference to each of those documents.

The MIB module also has a normative reference to the RPKI-Router Protocol [RFC6810]. Furthermore, for background and informative information, the MIB module refers to [RFC1982], [RFC4252], [RFC5246], and [RFC5925].

```
RPKI-ROUTER-MIB DEFINITIONS ::= BEGIN

IMPORTS

    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
    Integer32, Unsigned32, mib-2, Gauge32, Counter32
            FROM SNMPv2-SMI                          -- RFC 2578

    InetAddressType, InetAddress, InetPortNumber,
    InetAddressPrefixLength, InetAutonomousSystemNumber
            FROM INET-ADDRESS-MIB                    -- RFC 4001

    TEXTUAL-CONVENTION, TimeStamp
            FROM SNMPv2-TC                           -- RFC 2579

    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
            FROM SNMPv2-CONF                         -- RFC 2580

    LongUtf8String FROM SYSAPPL-MIB                  -- RFC 2287

    ;

rpkiRtrMIB  MODULE-IDENTITY
    LAST-UPDATED "201305010000Z"
    ORGANIZATION "IETF Secure Inter-Domain Routing (SIDR)
                  Working Group
                 "
    CONTACT-INFO "Working Group Email: sidr@ietf.org

                  Randy Bush
                  Internet Initiative Japan
                  5147 Crystal Springs
                  Bainbridge Island, WA  98110
                  USA
                  Email: randy@psg.com

                  Bert Wijnen
                  RIPE NCC
                  Schagen 33
                  3461 GL Linschoten
                  Netherlands
                  Email: bertietf@bwijnen.net

                  Keyur Patel
                  Cisco Systems
                  170 W. Tasman Drive
                  San Jose, CA  95134
                  USA
```

```
                     Email: keyupate@cisco.com

                     Michael Baer
                     SPARTA
                     P.O. Box 72682
                     Davis, CA  95617
                     USA
                     Email: baerm@tislabs.com
                    "

        DESCRIPTION  "This MIB module contains management objects to
                      support monitoring of the Resource Public Key
                      Infrastructure (RPKI) protocol on routers.

                      Copyright (c) 2013 IETF Trust and the persons
                      identified as authors of the code.  All rights
                      reserved.

                      Redistribution and use in source and binary
                      forms, with or without modification, is
                      permitted pursuant to, and subject to the
                      license terms contained in, the Simplified BSD
                      License set forth in Section 4.c of the IETF
                      Trust's Legal Provisions Relating to IETF
                      Documents
                      (http://trustee.ietf.org/license-info).

                      This version of this MIB module is part of
                      RFC 6945; see the RFC itself for full legal
                      notices."

        REVISION     "201305010000Z"
        DESCRIPTION  "Initial version, published as RFC 6945."
        ::= { mib-2 218 }

    rpkiRtrNotifications  OBJECT IDENTIFIER ::= { rpkiRtrMIB 0 }
    rpkiRtrObjects        OBJECT IDENTIFIER ::= { rpkiRtrMIB 1 }
    rpkiRtrConformance    OBJECT IDENTIFIER ::= { rpkiRtrMIB 2 }

    -- ============================================================
    -- Textual Conventions used in this MIB module
    -- ============================================================

    RpkiRtrConnectionType ::= TEXTUAL-CONVENTION
        STATUS      current
        DESCRIPTION "The connection type used between a router (as a
                     client) and a cache server.
```

```
                    The following types have been defined in RFC 6810:
                      ssh(1)    - Section 7.1; see also RFC 4252.
                      tls(2)    - Section 7.2; see also RFC 5246.
                      tcpMD5(3) - Section 7.3; see also RFC 2385.
                      tcpAO(4)  - Section 7.4; see also RFC 5925.
                      tcp(5)    - Section 7.
                      ipsec(6)  - Section 7; see also RFC 4301.
                      other(7)  - none of the above."

        REFERENCE   "The RPKI-Router Protocol, RFC 6810, Section 7"
        SYNTAX      INTEGER {
                              ssh(1),
                              tls(2),
                              tcpMD5(3),
                              tcpAO(4),
                              tcp(5),
                              ipsec(6),
                              other(7)
                    }

    -- ============================================================
    -- Scalar objects
    -- ============================================================
    rpkiRtrDiscontinuityTimer OBJECT-TYPE
        SYNTAX      TimeStamp
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "This timer represents the timestamp (value
                    of sysUpTime) at which time any of the
                    Counter32 objects in this MIB module
                    encountered a discontinuity.

                    For objects that use rpkiRtrDiscontinuityTimer to
                    indicate discontinuity, only values received since
                    the time indicated by rpkiRtrDiscontinuityTimer are
                    comparable to each other.  A manager should take the
                    possibility of rollover into account when
                    calculating difference values.

                    In principle, that should only happen if the
                    SNMP agent or the instrumentation for this
                    MIB module starts or restarts."
        ::= { rpkiRtrObjects 1 }

    -- ============================================================
    -- RPKI-Router Cache Server Connection Table
    -- ============================================================
```

```
   rpkiRtrCacheServerTable OBJECT-TYPE
       SYNTAX       SEQUENCE OF RpkiRtrCacheServerTableEntry
       MAX-ACCESS   not-accessible
       STATUS       current
       DESCRIPTION "This table lists the RPKI cache servers
                    known to this router/system."
       ::= { rpkiRtrObjects 2 }

   rpkiRtrCacheServerTableEntry OBJECT-TYPE
       SYNTAX       RpkiRtrCacheServerTableEntry
       MAX-ACCESS   not-accessible
       STATUS       current
       DESCRIPTION "An entry in the rpkiRtrCacheServerTable.
                    It holds management attributes associated
                    with one connection to a RPKI cache server.

                    Implementers should be aware that if the
                    rpkiRtrCacheServerRemoteAddress object exceeds 114
                    octets, the index values will exceed the 128
                    sub-identifier limit and cannot be accessed using
                    SNMPv1, SNMPv2c, or SNMPv3."

       INDEX        { rpkiRtrCacheServerRemoteAddressType,
                      rpkiRtrCacheServerRemoteAddress,
                      rpkiRtrCacheServerRemotePort
                    }
       ::= { rpkiRtrCacheServerTable 1 }

   RpkiRtrCacheServerTableEntry ::= SEQUENCE {
       rpkiRtrCacheServerRemoteAddressType    InetAddressType,
       rpkiRtrCacheServerRemoteAddress        InetAddress,
       rpkiRtrCacheServerRemotePort           InetPortNumber,
       rpkiRtrCacheServerLocalAddressType     InetAddressType,
       rpkiRtrCacheServerLocalAddress         InetAddress,
       rpkiRtrCacheServerLocalPort            InetPortNumber,
       rpkiRtrCacheServerPreference           Unsigned32,
       rpkiRtrCacheServerConnectionType       RpkiRtrConnectionType,
       rpkiRtrCacheServerConnectionStatus     INTEGER,
       rpkiRtrCacheServerDescription          LongUtf8String,
       rpkiRtrCacheServerMsgsReceived         Counter32,
       rpkiRtrCacheServerMsgsSent             Counter32,
       rpkiRtrCacheServerV4ActiveRecords      Gauge32,
       rpkiRtrCacheServerV4Announcements      Counter32,
       rpkiRtrCacheServerV4Withdrawals        Counter32,
       rpkiRtrCacheServerV6ActiveRecords      Gauge32,
       rpkiRtrCacheServerV6Announcements      Counter32,
       rpkiRtrCacheServerV6Withdrawals        Counter32,
       rpkiRtrCacheServerLatestSerial         Unsigned32,
```

```
        rpkiRtrCacheServerSessionID            Unsigned32,
        rpkiRtrCacheServerRefreshTimer         Unsigned32,
        rpkiRtrCacheServerTimeToRefresh        Integer32,
        rpkiRtrCacheServerId                   Unsigned32
    }

    rpkiRtrCacheServerRemoteAddressType OBJECT-TYPE
        SYNTAX       InetAddressType
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The network address type of the connection
                     to this RPKI cache server.

                     Note: Only IPv4, IPv6, and DNS support are required
                     for read-only compliance with RFC 6945."
        ::= { rpkiRtrCacheServerTableEntry 1 }

    rpkiRtrCacheServerRemoteAddress OBJECT-TYPE
        SYNTAX       InetAddress
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The remote network address for this connection
                     to this RPKI cache server.

                     The format of the address is defined by the
                     value of the corresponding instance of
                     rpkiRtrCacheServerRemoteAddressType.

                     This object matches the address type used within
                     the local router configuration.  If the address is
                     of type dns (fqdn), then the router will resolve it
                     at the time it connects to the cache server."
        ::= { rpkiRtrCacheServerTableEntry 2 }

    rpkiRtrCacheServerRemotePort OBJECT-TYPE
        SYNTAX       InetPortNumber (1..65535)
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The remote port number for this connection
                     to this RPKI cache server."
        ::= { rpkiRtrCacheServerTableEntry 3 }

    rpkiRtrCacheServerLocalAddressType OBJECT-TYPE
        SYNTAX       InetAddressType
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The network address type of the connection
                     to this RPKI cache server.
```

```
                    Note: Only IPv4, IPv6, and DNS support are required
                    for read-only compliance with RFC 6945."
        ::= { rpkiRtrCacheServerTableEntry 4 }

    rpkiRtrCacheServerLocalAddress OBJECT-TYPE
        SYNTAX       InetAddress
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The local network address for this connection
                    to this RPKI cache server.

                    The format of the address is defined by the
                    value of the corresponding instance of
                    rpkiRtrCacheServerLocalAddressType.

                    This object matches the address type used within
                    the local router configuration.  If the address is
                    of type dns (fqdn), then the router will resolve it
                    at the time it connects to the cache server."
        ::= { rpkiRtrCacheServerTableEntry 5 }

    rpkiRtrCacheServerLocalPort OBJECT-TYPE
        SYNTAX       InetPortNumber (1..65535)
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The local port number for this connection
                    to this RPKI cache server."
        ::= { rpkiRtrCacheServerTableEntry 6 }

    rpkiRtrCacheServerPreference OBJECT-TYPE
        SYNTAX       Unsigned32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The routers' preference for this RPKI cache server.

                    A lower value means more preferred.  If two entries
                    have the same preference, then the order is
                    arbitrary.

                    In two cases, the maximum value for an Unsigned32
                    object should be returned for this object:
                    - If no order is specified in the RPKI-Router
                      configuration.
                    - If a preference value is configured that is
                      larger than the max value for an Unsigned32
                      object."

        REFERENCE    "The RPKI-Router Protocol, RFC 6810, Section 8."
```

```
        DEFVAL       { 4294967295 }
        ::= { rpkiRtrCacheServerTableEntry 7 }

    rpkiRtrCacheServerConnectionType OBJECT-TYPE
        SYNTAX       RpkiRtrConnectionType
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The connection type or transport security suite
                     in use for this RPKI cache server."
        ::= { rpkiRtrCacheServerTableEntry 8 }

    rpkiRtrCacheServerConnectionStatus OBJECT-TYPE
        SYNTAX       INTEGER { up(1), down(2) }
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The connection status for this entry
                     (connection to this RPKI cache server)."
        ::= { rpkiRtrCacheServerTableEntry 9 }

    rpkiRtrCacheServerDescription OBJECT-TYPE
        SYNTAX       LongUtf8String
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "Free form description/information for this
                     connection to this RPKI cache server."
        ::= { rpkiRtrCacheServerTableEntry 10 }

    rpkiRtrCacheServerMsgsReceived OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "Number of messages received from this
                     RPKI cache server via this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerTableEntry 11 }

    rpkiRtrCacheServerMsgsSent OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "Number of messages sent to this
                     RPKI cache server via this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerTableEntry 12 }
```

```
   rpkiRtrCacheServerV4ActiveRecords OBJECT-TYPE
       SYNTAX       Gauge32
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "Number of active IPv4 records received from
                    this RPKI cache server via this connection."
       ::= { rpkiRtrCacheServerTableEntry 13 }

   rpkiRtrCacheServerV4Announcements OBJECT-TYPE
       SYNTAX       Counter32
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The number of IPv4 records announced by the
                    RPKI cache server via this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
       ::= { rpkiRtrCacheServerTableEntry 14 }

   rpkiRtrCacheServerV4Withdrawals OBJECT-TYPE
       SYNTAX      Counter32
       MAX-ACCESS  read-only
       STATUS      current
       DESCRIPTION "The number of IPv4 records withdrawn by the
                    RPKI cache server via this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
       ::= { rpkiRtrCacheServerTableEntry 15 }

   rpkiRtrCacheServerV6ActiveRecords OBJECT-TYPE
       SYNTAX       Gauge32
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "Number of active IPv6 records received from
                    this RPKI cache server via this connection."
       ::= { rpkiRtrCacheServerTableEntry 16 }

   rpkiRtrCacheServerV6Announcements OBJECT-TYPE
       SYNTAX       Counter32
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The number of IPv6 records announced by the
                    RPKI cache server via this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
       ::= { rpkiRtrCacheServerTableEntry 17 }
```

```
   rpkiRtrCacheServerV6Withdrawals OBJECT-TYPE
       SYNTAX       Counter32
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The number of IPv6 records withdrawn by the
                    RPKI cache server via this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
       ::= { rpkiRtrCacheServerTableEntry 18 }

   rpkiRtrCacheServerLatestSerial OBJECT-TYPE
       SYNTAX       Unsigned32
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The latest serial number of data received from
                    this RPKI server on this connection.

                    Note: this value wraps back to zero when it
                    reaches its maximum value."
       REFERENCE   "RFC 1982 and RFC 6810, Section 2"
       ::= { rpkiRtrCacheServerTableEntry 19 }

   rpkiRtrCacheServerSessionID OBJECT-TYPE
       SYNTAX      Unsigned32 (0..65535)
       MAX-ACCESS  read-only
       STATUS      current
       DESCRIPTION "The Session ID associated with the RPKI cache
                    server at the other end of this connection."
       REFERENCE   "RFC 6810, Section 2"
       ::= { rpkiRtrCacheServerTableEntry 20 }

   rpkiRtrCacheServerRefreshTimer OBJECT-TYPE
       SYNTAX       Unsigned32 (60..7200)
       UNITS       "seconds"
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The number of seconds configured for the refresh
                    timer for this connection to this RPKI cache
                    server."
       REFERENCE   "RFC 6810, Sections 6.1 and 8"
       ::= { rpkiRtrCacheServerTableEntry 21 }

   rpkiRtrCacheServerTimeToRefresh OBJECT-TYPE
       SYNTAX       Integer32
       UNITS       "seconds"
       MAX-ACCESS   read-only
       STATUS       current
```

```
        DESCRIPTION "The number of seconds remaining before a new
                     refresh is performed via a Serial Query to
                     this cache server over this connection.

                     A negative value means that the refresh time has
                     passed this many seconds and the refresh has not
                     yet been completed.  It will stop decrementing at
                     the maximum negative value.

                     Upon a completed refresh (i.e., a successful
                     and complete response to a Serial Query) the
                     value of this attribute will be reinitialized
                     with the value of the corresponding
                     rpkiRtrCacheServerRefreshTimer attribute."
        REFERENCE   "RFC 6810, Section 8"
        ::= { rpkiRtrCacheServerTableEntry 22 }

    rpkiRtrCacheServerId OBJECT-TYPE
        SYNTAX       Unsigned32 (1..4294967295)
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The unique ID for this connection.

                     An implementation must make sure this ID is unique
                     within this table.  It is this ID that can be used
                     to find entries in the rpkiRtrPrefixOriginTable
                     that were created by announcements received on
                     this connection from this cache server."
        REFERENCE   "RFC 6810, Section 4"
        ::= { rpkiRtrCacheServerTableEntry 23 }

    -- ================================================================
    -- Errors Table
    -- ================================================================

    rpkiRtrCacheServerErrorsTable OBJECT-TYPE
        SYNTAX       SEQUENCE OF RpkiRtrCacheServerErrorsTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "This table provides statistics on errors per
                     RPKI peer connection.  These can be used for
                     debugging."
        ::= { rpkiRtrObjects 3 }

    rpkiRtrCacheServerErrorsTableEntry OBJECT-TYPE
        SYNTAX       RpkiRtrCacheServerErrorsTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
```

```
        DESCRIPTION "An entry in the rpkiCacheServerErrorTable.  It
                     holds management objects associated with errors
                     codes that were received on the specified
                     connection to a specific cache server."
        REFERENCE   "RFC 6810, Section 10"
        AUGMENTS    { rpkiRtrCacheServerTableEntry }
        ::= { rpkiRtrCacheServerErrorsTable 1 }

    RpkiRtrCacheServerErrorsTableEntry ::= SEQUENCE {
        rpkiRtrCacheServerErrorsCorruptData        Counter32,
        rpkiRtrCacheServerErrorsInternalError      Counter32,
        rpkiRtrCacheServerErrorsNoData             Counter32,
        rpkiRtrCacheServerErrorsInvalidRequest     Counter32,
        rpkiRtrCacheServerErrorsUnsupportedVersion Counter32,
        rpkiRtrCacheServerErrorsUnsupportedPdu     Counter32,
        rpkiRtrCacheServerErrorsWithdrawalUnknown  Counter32,
        rpkiRtrCacheServerErrorsDuplicateAnnounce  Counter32
        }

    rpkiRtrCacheServerErrorsCorruptData OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Corrupt Data' errors received
                     from the RPKI cache server at the other end
                     of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 1 }

    rpkiRtrCacheServerErrorsInternalError OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Internal Error' errors received
                     from the RPKI cache server at the other end
                     of this connection.

                     Discontinuities are indicated by the value
                     of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 2 }

    rpkiRtrCacheServerErrorsNoData OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'No Data Available' errors received
```

```
                    from the RPKI cache server at the other end
                    of this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 3 }

    rpkiRtrCacheServerErrorsInvalidRequest OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Invalid Request' errors received
                    from the RPKI cache server at the other end
                    of this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 4 }

    rpkiRtrCacheServerErrorsUnsupportedVersion OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Unsupported Protocol Version'
                    errors received from the RPKI cache server at
                    the other end of this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 5 }

    rpkiRtrCacheServerErrorsUnsupportedPdu OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Unsupported PDU Type' errors
                    received from the RPKI cache server at the
                    other end of this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 6 }

    rpkiRtrCacheServerErrorsWithdrawalUnknown OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Withdrawal of Unknown Record'
```

```
                    errors received from the RPKI cache server at
                    the other end of this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 7 }

    rpkiRtrCacheServerErrorsDuplicateAnnounce OBJECT-TYPE
        SYNTAX       Counter32
        MAX-ACCESS   read-only
        STATUS       current
        DESCRIPTION "The number of 'Duplicate Announcement Received'
                    errors received from the RPKI cache server at
                    the other end of this connection.

                    Discontinuities are indicated by the value
                    of rpkiRtrDiscontinuityTimer."
        ::= { rpkiRtrCacheServerErrorsTableEntry 8 }

    -- ================================================================
    -- The rpkiRtrPrefixOriginTable
    -- ================================================================

    rpkiRtrPrefixOriginTable OBJECT-TYPE
        SYNTAX       SEQUENCE OF RpkiRtrPrefixOriginTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "This table lists the prefixes that were
                    announced by RPKI cache servers to this system.
                    That is the prefixes and their Origin Autonomous
                    System Number (ASN) as received by announcements
                    via the RPKI-Router Protocol."
        ::= { rpkiRtrObjects 4 }

    rpkiRtrPrefixOriginTableEntry OBJECT-TYPE
        SYNTAX       RpkiRtrPrefixOriginTableEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "An entry in the rpkiRtrPrefixOriginTable.  This
                    represents one announced prefix.  If a cache server
                    is removed from the local configuration, any table
                    rows associated with that server (indicated by
                    rpkiRtrPrefixOriginCacheServerId) are also removed
                    from this table.

                    Implementers should be aware that if the
                    rpkiRtrPrefixOriginAddress object exceeds 111
                    octets, the index values will exceed the 128
```

```
                    sub-identifier limit and cannot be accessed using
                    SNMPv1, SNMPv2c, or SNMPv3."

        INDEX       { rpkiRtrPrefixOriginAddressType,
                      rpkiRtrPrefixOriginAddress,
                      rpkiRtrPrefixOriginMinLength,
                      rpkiRtrPrefixOriginMaxLength,
                      rpkiRtrPrefixOriginASN,
                      rpkiRtrPrefixOriginCacheServerId
                    }
        ::= { rpkiRtrPrefixOriginTable 1 }

    RpkiRtrPrefixOriginTableEntry ::= SEQUENCE {
        rpkiRtrPrefixOriginAddressType    InetAddressType,
        rpkiRtrPrefixOriginAddress        InetAddress,
        rpkiRtrPrefixOriginMinLength      InetAddressPrefixLength,
        rpkiRtrPrefixOriginMaxLength      InetAddressPrefixLength,
        rpkiRtrPrefixOriginASN            InetAutonomousSystemNumber,
        rpkiRtrPrefixOriginCacheServerId  Unsigned32
    }

    rpkiRtrPrefixOriginAddressType OBJECT-TYPE
        SYNTAX       InetAddressType
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The network address type for this prefix.

                    Note: Only IPv4 and IPv6 support are required
                    for read-only compliance with RFC 6945."
        ::= { rpkiRtrPrefixOriginTableEntry 1 }

    rpkiRtrPrefixOriginAddress OBJECT-TYPE
        SYNTAX       InetAddress
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The network address for this prefix.

                    The format of the address is defined by the
                    value of the corresponding instance of
                    rpkiRtrPrefixOriginAddressType."
        ::= { rpkiRtrPrefixOriginTableEntry 2 }

    rpkiRtrPrefixOriginMinLength OBJECT-TYPE
        SYNTAX       InetAddressPrefixLength
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION "The minimum prefix length allowed for this prefix."
        ::= { rpkiRtrPrefixOriginTableEntry 3 }
```

```
   rpkiRtrPrefixOriginMaxLength OBJECT-TYPE
       SYNTAX       InetAddressPrefixLength
       MAX-ACCESS   not-accessible
       STATUS       current
       DESCRIPTION "The maximum prefix length allowed for this prefix.

                    Note, this value must be greater or equal to the
                    value of rpkiRtrPrefixOriginMinLength."
       ::= { rpkiRtrPrefixOriginTableEntry 4 }

   rpkiRtrPrefixOriginASN OBJECT-TYPE
       SYNTAX       InetAutonomousSystemNumber (0..4294967295)
       MAX-ACCESS   not-accessible
       STATUS       current
       DESCRIPTION "The ASN that is authorized to announce the
                    prefix or sub-prefixes covered by this entry."
       ::= { rpkiRtrPrefixOriginTableEntry 5 }

   rpkiRtrPrefixOriginCacheServerId OBJECT-TYPE
       SYNTAX       Unsigned32 (1..4294967295)
       MAX-ACCESS   read-only
       STATUS       current
       DESCRIPTION "The unique ID of the connection to the cache
                    server from which this announcement was received.
                    That connection is identified/found by a matching
                    value in attribute rpkiRtrCacheServerId."
       ::= { rpkiRtrPrefixOriginTableEntry 6 }

   -- ================================================================
   -- Notifications
   -- ================================================================

   rpkiRtrCacheServerConnectionStateChange NOTIFICATION-TYPE
       OBJECTS     { rpkiRtrCacheServerConnectionStatus,
                     rpkiRtrCacheServerLatestSerial,
                     rpkiRtrCacheServerSessionID
                   }
       STATUS      current
       DESCRIPTION "This notification signals a change in the status
                    of an rpkiRtrCacheServerConnection.

                    The management agent MUST throttle the generation of
                    consecutive rpkiRtrCacheServerConnectionStateChange
                    notifications such that there is at least a 5 second
                    gap between them.

                    If more than one notification has occurred locally
                    during that time, the most recent notification is
```

```
                    sent at the end of the 5 second gap and the others
                    are discarded."
        ::= { rpkiRtrNotifications 1 }

    rpkiRtrCacheServerConnectionToGoStale NOTIFICATION-TYPE
        OBJECTS     { rpkiRtrCacheServerV4ActiveRecords,
                      rpkiRtrCacheServerV6ActiveRecords,
                      rpkiRtrCacheServerLatestSerial,
                      rpkiRtrCacheServerSessionID,
                      rpkiRtrCacheServerRefreshTimer,
                      rpkiRtrCacheServerTimeToRefresh
                    }
        STATUS      current
        DESCRIPTION "This notification signals that an RPKI cache
                     server connection is about to go stale.
                     It is suggested that this notification is
                     generated when the value of the
                     rpkiRtrCacheServerTimeToRefresh attribute
                     goes below 60 seconds.

                     The SNMP agent MUST throttle the generation of
                     consecutive rpkiRtrCacheServerConnectionToGoStale
                     notifications such that there is at least a
                     5 second gap between them.
                    "
        ::= { rpkiRtrNotifications 2 }

    -- ================================================================
    -- Module Compliance information
    -- ================================================================

    rpkiRtrCompliances OBJECT IDENTIFIER ::=
                                            {rpkiRtrConformance 1}
    rpkiRtrGroups      OBJECT IDENTIFIER ::=
                                            {rpkiRtrConformance 2}

    rpkiRtrRFC6945ReadOnlyCompliance MODULE-COMPLIANCE
        STATUS       current
        DESCRIPTION
            "The compliance statement for the rpkiRtrMIB module.  There
            are only read-only objects in this MIB module, so the
            'ReadOnly' in the name of this compliance statement is there
            only for clarity and truth in advertising.

            There are a number of INDEX objects that cannot be
            represented in the form of OBJECT clauses in SMIv2, but for
            which there are compliance requirements.  Those requirements
            and similar requirements for related objects are expressed
```

```
            below, in pseudo-OBJECT clause form, in this description:

            -- OBJECT rpkiRtrCacheServerRemoteAddressType
            -- SYNTAX InetAddressType { ipv4(1), ipv6(2), dns(16) }
            -- DESCRIPTION
            --   The MIB requires support for the IPv4, IPv6, and DNS
            --   InetAddressTypes for this object.

            -- OBJECT rpkiRtrCacheServerLocalAddressType
            -- SYNTAX InetAddressType { ipv4(1), ipv6(2), dns(16) }
            -- DESCRIPTION
            --   The MIB requires support for the IPv4, IPv6, and DNS
            --   InetAddressTypes for this object.

            -- OBJECT rpkiRtrPrefixOriginAddressType
            -- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
            -- DESCRIPTION
            --   The MIB requires support for the IPv4, and IPv6
            --   InetAddressTypes for this object.
            "

        MODULE      -- This module
        MANDATORY-GROUPS { rpkiRtrCacheServerGroup,
                           rpkiRtrPrefixOriginGroup,
                           rpkiRtrNotificationsGroup
                         }

        GROUP       rpkiRtrCacheServerErrorsGroup
        DESCRIPTION "Implementation of this group is optional and
                     would be useful for debugging."

        ::= { rpkiRtrCompliances 1 }

    rpkiRtrCacheServerGroup OBJECT-GROUP
        OBJECTS     {
                      rpkiRtrDiscontinuityTimer,
                      rpkiRtrCacheServerLocalAddressType,
                      rpkiRtrCacheServerLocalAddress,
                      rpkiRtrCacheServerLocalPort,
                      rpkiRtrCacheServerPreference,
                      rpkiRtrCacheServerConnectionType,
                      rpkiRtrCacheServerConnectionStatus,
                      rpkiRtrCacheServerDescription,
                      rpkiRtrCacheServerMsgsReceived,
                      rpkiRtrCacheServerMsgsSent,
                      rpkiRtrCacheServerV4ActiveRecords,
                      rpkiRtrCacheServerV4Announcements,
                      rpkiRtrCacheServerV4Withdrawals,
```

```
                    rpkiRtrCacheServerV6ActiveRecords,
                    rpkiRtrCacheServerV6Announcements,
                    rpkiRtrCacheServerV6Withdrawals,
                    rpkiRtrCacheServerLatestSerial,
                    rpkiRtrCacheServerSessionID,
                    rpkiRtrCacheServerRefreshTimer,
                    rpkiRtrCacheServerTimeToRefresh,
                    rpkiRtrCacheServerId
                  }
      STATUS      current
      DESCRIPTION "The collection of objects to monitor the RPKI peer
                   connections."
      ::= { rpkiRtrGroups 1 }

   rpkiRtrCacheServerErrorsGroup OBJECT-GROUP
      OBJECTS     {
                    rpkiRtrCacheServerErrorsCorruptData,
                    rpkiRtrCacheServerErrorsInternalError,
                    rpkiRtrCacheServerErrorsNoData,
                    rpkiRtrCacheServerErrorsInvalidRequest,
                    rpkiRtrCacheServerErrorsUnsupportedVersion,
                    rpkiRtrCacheServerErrorsUnsupportedPdu,
                    rpkiRtrCacheServerErrorsWithdrawalUnknown,
                    rpkiRtrCacheServerErrorsDuplicateAnnounce
                  }
      STATUS      current
      DESCRIPTION "The collection of objects that may help in
                   debugging the communication between RPKI
                   clients and cache servers."
      ::= { rpkiRtrGroups 2 }

   rpkiRtrPrefixOriginGroup OBJECT-GROUP
      OBJECTS     {
                    rpkiRtrPrefixOriginCacheServerId
                  }
      STATUS      current
      DESCRIPTION "The collection of objects that represent
                   the prefix(es) and their validated Origin
                   ASes."
      ::= { rpkiRtrGroups 3 }
```

```
rpkiRtrNotificationsGroup NOTIFICATION-GROUP
    NOTIFICATIONS { rpkiRtrCacheServerConnectionStateChange,
                    rpkiRtrCacheServerConnectionToGoStale
                  }
    STATUS      current
    DESCRIPTION "The set of notifications to alert an NMS of change
                 in connections to RPKI cache servers."
    ::= { rpkiRtrGroups 4 }

END
```

5. IANA Considerations

IANA has assigned the MIB module in this document the following OBJECT IDENTIFIER within the SMI Numbers registry.

Descriptor	OBJECT IDENTIFIER value
rpkiRtrMIB	{ mib-2 218 }

6. Security Considerations

There are no management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations.

Most of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. They are vulnerable in the sense that when an intruder sees the information in this MIB module, then it might help him/her to set up an attack on the router or cache server. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations MUST provide the security features described by the SNMPv3 framework (see [RFC3410]), including full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations

MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

7. References

7.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

[RFC2287] Krupczak, C. and J. Saperia, "Definitions of System-Level Managed Objects for Applications", RFC 2287, February 1998.

[RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.

[RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.

[RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.

[RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.

[RFC6810] Bush, R. and R. Austein, "The Resource Public Key Infrastructure (RPKI) to Router Protocol", RFC 6810, January 2013.

7.2. Informative References

[RFC1982] Elz, R. and R. Bush, "Serial Number Arithmetic", RFC 1982, August 1996.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.

[RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, December 2002.

[RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, June 2004.

[RFC4252] Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Authentication Protocol", RFC 4252, January 2006.

[RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", RFC 5246, August 2008.

[RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", RFC 5591, June 2009.

[RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, June 2009.

[RFC5925] Touch, J., Mankin, A., and R. Bonica, "The TCP Authentication Option", RFC 5925, June 2010.

[RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", RFC 6353, July 2011.

Authors' Addresses

Randy Bush
Internet Initiative Japan
5147 Crystal Springs
Bainbridge Island, WA 98110
US

EMail: randy@psg.com

Bert Wijnen
RIPE NCC
Schagen 33
3461 GL Linschoten
Netherlands

EMail: bertietf@bwijnen.net

Keyur Patel
Cisco Systems
170 W. Tasman Drive
San Jose, CA 95134
USA

EMail: keyupate@cisco.com

Michael Baer
SPARTA
P.O. Box 72682
Davis, CA 95617
USA

EMail: baerm@tislabs.com