

Network Working Group  
Request for Comments: 5543  
Category: Standards Track

H. Ould-Brahim  
Nortel Networks  
D. Fedyk  
Alcatel-Lucent  
Y. Rekhter  
Juniper Networks  
May 2009

## BGP Traffic Engineering Attribute

### Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

### Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

### Abstract

This document defines a new BGP attribute, the Traffic Engineering attribute, that enables BGP to carry Traffic Engineering information.

The scope and applicability of this attribute currently excludes its use for non-VPN reachability information.

## 1. Introduction

In certain cases (e.g., Layer-1 VPNs (L1VPNs) [RFC5195]), it may be useful to augment the VPN reachability information carried in BGP with Traffic Engineering information.

This document defines a new BGP attribute, the Traffic Engineering attribute, that enables BGP [RFC4271] to carry Traffic Engineering information.

Section 4 of [RFC5195] describes one possible usage of this attribute.

The scope and applicability of this attribute currently excludes its use for non-VPN reachability information.

Procedures for modifying the Traffic Engineering attribute, when re-advertising a route that carries such an attribute, are outside the scope of this document.

## 2. Specification of Requirements

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

## 3. Traffic Engineering Attribute

The Traffic Engineering attribute is an optional, non-transitive BGP attribute.

The information carried in this attribute is identical to what is carried in the Interface Switching Capability Descriptor, as specified in [RFC4203] and [RFC5307].

The attribute contains one or more of the following:

0								1								2								3							
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
Switching Cap								Encoding								Reserved															
								Max LSP Bandwidth at priority 0																							
								Max LSP Bandwidth at priority 1																							
								Max LSP Bandwidth at priority 2																							
								Max LSP Bandwidth at priority 3																							
								Max LSP Bandwidth at priority 4																							
								Max LSP Bandwidth at priority 5																							
								Max LSP Bandwidth at priority 6																							
								Max LSP Bandwidth at priority 7																							
								Switching Capability specific information																							
								(variable)																							

The Switching Capability (Switching Cap) field contains one of the values specified in [Section 3.1.1 of \[RFC3471\]](#).

The Encoding field contains one of the values specified in [Section 3.1.1 of \[RFC3471\]](#).

The Reserved field SHOULD be set to 0 on transmit and MUST be ignored on receive.

Maximum LSP (Label Switched Path) Bandwidth is encoded as a list of eight 4-octet fields in the IEEE floating point format [\[IEEE\]](#), with priority 0 first and priority 7 last. The units are bytes (not bits!) per second.

The content of the Switching Capability specific information field depends on the value of the Switching Capability field.

When the Switching Capability field is PSC-1, PSC-2, PSC-3, or PSC-4, the Switching Capability specific information field includes Minimum LSP Bandwidth and Interface MTU.



Constructing the Traffic Engineering attribute when aggregating routes with identical Traffic Engineering attributes follows the procedure of [RFC4201].

## 5. Implication on Scalability

The use of the Traffic Engineering attribute does not increase the number of routes, but may increase the number of BGP Update messages required to distribute the routes, depending on whether or not these routes share the same BGP Traffic Engineering attribute (see below).

When the routes differ other than in the Traffic Engineering attribute (e.g., differ in the set of Route Targets and/or NEXT\_HOP), use of the Traffic Engineering attribute has no impact on the number of BGP Update messages required to carry the routes. There is also no impact when routes share all other attribute information and have an aggregated or identical Traffic Engineering attribute. When routes share all other attribute information and have different Traffic Engineering attributes, routes must be distributed in per-route BGP Update messages, rather than in a single message.

## 6. IANA Considerations

This document defines a new BGP attribute, Traffic Engineering. This attribute is optional and non-transitive.

## 7. Security Considerations

This extension to BGP does not change the underlying security issues currently inherent in BGP. BGP security considerations are discussed in RFC 4271.

## 8. Acknowledgements

The authors would like to thank John Scudder and Jeffrey Haas for their review and comments.

## 9. References

### 9.1. Normative References

- [IEEE] IEEE, "IEEE Standard for Binary Floating-Point Arithmetic", Standard 754-1985, 1985 (ISBN 1-5593-7653-8).
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

- [RFC3471] Berger, L., Ed., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description", [RFC 3471](#), January 2003.
- [RFC4201] Kompella, K., Rekhter, Y., and L. Berger, "Link Bundling in MPLS Traffic Engineering (TE)", [RFC 4201](#), October 2005.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), January 2006.

## 9.2. Informative References

- [RFC4203] Kompella, K., Ed., and Y. Rekhter, Ed., "OSPF Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 4203](#), October 2005.
- [RFC5195] Ould-Brahim, H., Fedyk, D., and Y. Rekhter, "BGP-Based Auto-Discovery for Layer-1 VPNs", [RFC 5195](#), June 2008.
- [RFC5307] Kompella, K., Ed., and Y. Rekhter, Ed., "IS-IS Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 5307](#), October 2008.

## Authors' Addresses

Hamid Ould-Brahim  
Nortel Networks  
EMail: [hbrahim@nortel.com](mailto:hbrahim@nortel.com)

Don Fedyk  
Alcatel-Lucent  
EMail: [donald.fedyk@alcatel-lucent.com](mailto:donald.fedyk@alcatel-lucent.com)  
Phone: 978-467-5645

Yakov Rekhter  
Juniper Networks, Inc.  
EMail: [yakov@juniper.net](mailto:yakov@juniper.net)