

Internet Engineering Task Force (IETF)  
Request for Comments: 6933  
Obsoletes: [4133](#)  
Category: Standards Track  
ISSN: 2070-1721

A. Bierman  
YumaWorks, Inc.  
D. Romascanu  
Avaya  
J. Quittek  
NEC Europe Ltd.  
M. Chandramouli  
Cisco Systems, Inc.  
May 2013

## Entity MIB (Version 4)

### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing multiple logical and physical entities managed by a single Simple Network Management Protocol (SNMP) agent. This document specifies version 4 of the Entity MIB. This memo obsoletes version 3 of the Entity MIB module published as [RFC 4133](#).

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in [Section 2 of RFC 5741](#).

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6933>.

### Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. The SNMP Management Framework .....	3
2. Overview .....	3
2.1. Terms .....	5
2.2. Relationship to Community Strings .....	6
2.3. Relationship to SNMP Contexts .....	6
2.4. Relationship to Proxy Mechanisms .....	6
2.5. Relationship to a Chassis MIB .....	7
2.6. Relationship to the Interfaces MIB .....	7
2.7. Relationship to the Other MIB Modules .....	7
2.8. Relationship to Naming Scopes .....	7
2.9. Multiple Instances of the Entity MIB .....	8
2.10. Re-Configuration of Entities .....	9
2.11. Textual Convention Change .....	9
2.12. MIB Structure .....	9
2.12.1. entityPhysical Group .....	10
2.12.2. entityLogical Group .....	12
2.12.3. entityMapping Group .....	12
2.12.4. entityGeneral Group .....	13
2.12.5. entityNotifications Group .....	13
2.13. Multiple Agents .....	13
2.14. Changes Since RFC 2037 .....	14
2.14.1. Textual Conventions .....	14
2.14.2. New entPhysicalTable Objects .....	14
2.14.3. New entLogicalTable Objects .....	14
2.14.4. Bug Fixes .....	14
2.15. Changes Since RFC 2737 .....	15
2.15.1. Textual Conventions .....	15
2.15.2. New Objects .....	15
2.15.3. Bug Fixes .....	15
2.16. Changes Since RFC 4133 .....	15
2.16.1. MIB Module Addition .....	15
2.16.2. Modification to Some of the MIB Objects .....	15
2.16.3. New TC for Universally Unique Identifier .....	16
3. MIB Definitions .....	16
3.1. ENTITY-MIB .....	16
3.2. IANA-ENTITY-MIB .....	50
3.3. UUID-TC-MIB .....	53
4. Usage Examples .....	55
4.1. Router/Bridge .....	55
4.2. Repeaters .....	62
4.3. EMAN Example .....	69
5. Security Considerations .....	70

6. IANA Considerations .....	72
7. Acknowledgements .....	73
8. References .....	73
8.1. Normative References .....	73
8.2. Informative References .....	74

## 1. The SNMP Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [RFC2578], STD 58, [RFC 2579](#) [RFC2579] and STD 58, [RFC 2580](#) [RFC2580].

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [RFC2119].

## 2. Overview

There is a need for a standardized way of representing a single agent, which supports multiple instances of one MIB module. This is presently true for at least 3 standard MIB modules and is likely to become true for more and more MIB modules as time passes. For example:

- multiple instances of a bridge supported within a single device that has a single agent;
- multiple repeaters supported by a single agent; and
- multiple OSPF backbone areas, each operating as part of its own Autonomous System and each identified by the same area-id (e.g., 0.0.0.0), supported inside a single router with one agent.

The single agent present in each of these cases implies a relationship binds these entities. Effectively, there is some "overall" physical entity that houses the sum of the things managed by that one agent, i.e., there are multiple "logical" entities within a single physical entity. Sometimes, the overall physical entity

contains multiple (smaller) physical entities, and each logical entity is associated with a particular physical entity. Sometimes, the overall physical entity is a "compound" of multiple physical entities (e.g., a stack of stackable hubs).

What is needed is a way to determine exactly which logical entities are managed by the agent (with some version of SNMP) in order to communicate with the agent about a particular logical entity. When different logical entities are associated with different physical entities within the overall physical entity, it is also useful to be able to use this information to distinguish between logical entities.

In these situations, there is no need for varbinds for multiple logical entities to be referenced in the same SNMP message (although that might be useful in the future). Rather, it is sufficient, and in some situations preferable, to have the context/community in the message identify the logical entity to which the varbinds apply.

Version 2 of this MIB addresses new requirements that have emerged since the publication of the first Entity MIB [RFC2037]. There is a need for a standardized way of providing non-volatile, administratively assigned identifiers for physical components represented with the Entity MIB. There is also a need to align the Entity MIB with the SNMPv3 administrative framework (STD 62, [RFC3411]). Implementation experience has shown that additional physical component attributes are also desirable.

Version 3 of this MIB addresses new requirements that have emerged since the publication of the second Entity MIB [RFC2737]. There is a need to identify physical entities that are central processing units (CPUs) and a need to provide a Textual Convention (TC) that identifies an entPhysicalIndex value or zero, where the value zero has application-specific semantics. Two new objects have been added to the entPhysicalTable to identify the manufacturing date and provide additional URIs for a particular physical entity.

Version 4 of this MIB addresses new requirements that have emerged since the publication of the third version of the Entity MIB [RFC4133]. There is a need to add new enumerated values for entity physical classes, a need to provide identification information for physical entities using a Universally Unique Identifier (UUID) format, and a need to have compliant implementations of the Entity MIB with a smaller subsets of MIB objects for devices with constrained resources.

The PhysicalClass TEXTUAL-CONVENTION was deprecated, and a new IANAPhysicalClass TC (maintained by IANA) was created. A new TC, UUIDorZero, was created to represent a UUID, and a new MIB object was

added to the `entPhysicalTable` to identify an entity. A new compliance statement, `entity4CRCompliance`, has been added for possible implementation of a selected subset of MIB objects by entities with constrained resources.

## 2.1. Terms

The following terms are used throughout this document:

- Naming Scope  
A "naming scope" represents the set of information that may be potentially accessed through a single SNMP operation. All instances within the naming scope share the same unique identifier space. For SNMPv1, a naming scope is identified by the value of the associated `entLogicalCommunity` instance. For SNMPv3, the term "context" is used instead of "naming scope". The complete definition of an SNMP context can be found in Section 3.3.1 of [RFC 3411](#) [[RFC3411](#)].
- Multi-Scoped Object  
A MIB object for which identical instance values identify different managed information in different naming scopes is called a "multi-scoped" MIB object.
- Single-Scoped Object  
A MIB object for which identical instance values identify the same managed information in different naming scopes is called a "single-scoped" MIB object.
- Logical Entity  
A managed system contains one or more "logical entities", each represented by at most one instantiation of each of a particular set of MIB objects. A set of management functions is associated with each logical entity. Examples of logical entities include routers, bridges, print-servers, etc.
- Physical Entity  
A "physical entity" or "physical component" represents an identifiable physical resource within a managed system. Zero or more logical entities may utilize a physical resource at any given time. Determining which physical components are represented by an agent in the `EntPhysicalTable` is an implementation-specific matter. Typically, physical resources (e.g., communications ports, backplanes, sensors, daughter-cards, power supplies, and the overall chassis), which can be managed via functions associated with one or more logical entities, are included in the MIB.

- Containment Tree

Each physical component may be modeled as 'contained' within another physical component. A "containment-tree" is the conceptual sequence of entPhysicalIndex values that uniquely specifies the exact physical location of a physical component within the managed system. It is generated by 'following and recording' each entPhysicalContainedIn instance 'up the tree towards the root' until a value of zero, indicating no further containment, is found.

## 2.2. Relationship to Community Strings

For community-based SNMP, differentiating logical entities is one (but not the only) purpose of the community string [RFC1157]. This is accommodated by representing each community string as a logical entity.

Note that different logical entities may share the same naming scope and, therefore, the same values of entLogicalCommunity. This is possible, providing they have no need for the same instance of a MIB object to represent different managed information.

## 2.3. Relationship to SNMP Contexts

Version 2 of the Entity MIB contains support for associating SNMPv3 contexts with logical entities. Two new MIB objects, defining an SnmpEngineID and ContextName pair, are used together to identify an SNMP context associated with a logical entity. This context can be used (in conjunction with the entLogicalTAddress and entLogicalTDomain MIB objects) to send SNMPv3 messages on behalf of a particular logical entity.

## 2.4. Relationship to Proxy Mechanisms

The Entity MIB is designed to allow functional component discovery. The administrative relationships between different logical entities are not visible in any Entity MIB tables. A Network Management System (NMS) cannot determine whether MIB instances in different naming scopes are realized locally or remotely (e.g., via some proxy mechanism) by examining any particular Entity MIB objects.

The management of administrative framework functions is not an explicit goal of the Entity MIB WG at this time. This new area of functionality may be revisited after some operational experience with the Entity MIB is gained.

Note that for community-based versions of SNMP, a network administrator will likely be able to associate community strings with naming scopes that have proprietary mechanisms, as a matter of configuration. There are no mechanisms for managing naming scopes defined in this MIB.

## 2.5. Relationship to a Chassis MIB

Some readers may recall that a previous IETF working group attempted to define a Chassis MIB. No consensus was reached by that working group, possibly because its scope was too broad. As such, it is not the purpose of the ENTITY-MIB module to be a "Chassis MIB replacement", nor is it within the scope of the ENTITY-MIB module to contain all the information that might be necessary to manage a "chassis". On the other hand, the entities represented by an implementation of the ENTITY-MIB module might well be contained in a chassis.

## 2.6. Relationship to the Interfaces MIB

The Entity MIB contains a mapping table identifying physical components that have 'external values' (e.g., ifIndex) associated with them within a given naming scope. This table can be used to identify the physical location of each interface in the ifTable [RFC2863]. Because ifIndex values in different contexts are not related to one another, the interface-to-physical-component associations are relative to the same logical entity within the agent.

The Entity MIB also contains entPhysicalName and entPhysicalAlias objects, which approximate the semantics of the ifName and ifAlias objects (respectively) from the Interfaces MIB [RFC2863] for all types of physical components.

## 2.7. Relationship to the Other MIB Modules

The Entity MIB contains a mapping table identifying physical components that have identifiers from other standard MIB modules associated with them. For example, this table can be used along with the physical mapping table to identify the physical location of each repeater port in the rpTrPortTable or each interface in the ifTable.

## 2.8. Relationship to Naming Scopes

There is some question as to which MIB objects may be returned within a given naming scope. MIB objects that are not multi-scoped within a managed system are likely to ignore context information in

implementation. In such a case, it is likely such objects will be returned in all naming scopes (e.g., not just the 'default' naming scope or the SNMPv3 default context).

For example, a community string used to access the management information for logical device 'bridge2' may allow access to all the non-bridge-related objects in the 'default' naming scope, as well as a second instance of the Bridge MIB [RFC4188].

The isolation of single-scoped MIB objects by the agent is an implementation-specific matter. An agent may wish to limit the objects returned in a particular naming scope to only the multi-scoped objects in that naming scope (e.g., system group and the Bridge MIB). In this case, all single-scoped management information would belong to a common naming scope (e.g., 'default'), which itself may contain some multi-scoped objects (e.g., system group).

## 2.9. Multiple Instances of the Entity MIB

It is possible that more than one agent may exist in a managed system. In such cases, multiple instances of the Entity MIB (representing the same managed objects) may be available to an NMS.

In order to reduce complexity for agent implementation, multiple instances of the Entity MIB are not required to be equivalent or even consistent. An NMS may be able to 'align' instances returned by different agents by examining the columns of each table, but vendor-specific identifiers and (especially) index values are likely to be different. Each agent may be managing different subsets of the entire chassis as well.

When all of a physically modular device is represented by a single agent, the entry (for which `entPhysicalContainedIn` has the value zero) would likely have 'chassis' as the value of its `entPhysicalClass`. Alternatively, for an agent on a module where the agent represents only the physical entities on that module (not those on other modules), the entry (for which `entPhysicalContainedIn` has the value zero) would likely have 'module' as the value of its `entPhysicalClass`.

An agent implementation of the `entLogicalTable` is not required to contain information about logical entities managed primarily by other agents. That is, the `entLogicalTAddress` and `entLogicalTDomain` objects in the `entLogicalTable` are provided to support a historical multiplexing mechanism, not to identify other SNMP agents.

Note that the Entity MIB is a single-scoped MIB, in the event an agent represents the MIB in different naming scopes.



## 2.10. Re-Configuration of Entities

Most of the MIB objects defined in this MIB have, at most, a read-only MAX-ACCESS clause. This is a conscious decision by the working group to limit this MIB's scope. The second version of the Entity MIB allows a network administrator to configure some common attributes of physical components.

## 2.11. Textual Convention Change

Version 1 of the Entity MIB contains three MIB objects defined with the (now obsolete) DisplayString TEXTUAL-CONVENTION. In version 2 of the Entity MIB, the syntax for these objects has been updated to use the (now preferred) SnmpAdminString TEXTUAL-CONVENTION.

The ENTMIB working group (which was in charge of the document at that point) realized that this change is not strictly supported by SMIV2. In their judgment, the alternative of deprecating the old objects and defining new objects would have had a more adverse impact on backward compatibility and interoperability, given the particular semantics of these objects.

## 2.12. MIB Structure

The Entity MIB contains five groups of MIB objects:

- entityPhysical group  
Describes the physical entities managed by a single agent.
- entityLogical group  
Describes the logical entities managed by a single agent.
- entityMapping group  
Describes the associations between the physical entities, logical entities, interfaces, and non-interface ports managed by a single agent.
- entityGeneral group  
Describes general system attributes shared by potentially all types of entities managed by a single agent.
- entityNotifications group  
Contains status indication notifications.

### 2.12.1. entityPhysical Group

This group contains a single table to identify physical system components, called the entPhysicalTable.

The entPhysicalTable contains one row per physical entity and must always contain at least one row for an "overall" physical entity, which should have an entPhysicalClass value of 'stack(11)', 'chassis(3)', or 'module(9)'.

Each row is indexed by an arbitrary, small integer and contains a description and type of the physical entity. It also optionally contains the index number of another entPhysicalEntry, indicating a containment relationship between the two.

Version 2 of the Entity MIB provides additional MIB objects for each physical entity. Some common read-only attributes have been added, as well as three writable string objects.

- entPhysicalAlias  
This string can be used by an NMS as a non-volatile identifier for the physical component. Maintaining a non-volatile string for every physical component represented in the entPhysicalTable can be costly and unnecessary. An agent may algorithmically generate entPhysicalAlias strings for particular entries (e.g., based on the entPhysicalClass value).
- entPhysicalAssetID  
This string is provided to store a user-specific asset identifier for removable physical components. In order to reduce the non-volatile storage needed by a particular agent, a network administrator should only assign asset identifiers to physical entities that are field-replaceable (i.e., not permanently contained within another physical entity).
- entPhysicalSerialNum  
This string is provided to store a vendor-specific serial number string for physical components. This writable object is used when an agent cannot identify the serial numbers of all installed physical entities and a network administrator wishes to configure the non-volatile serial number strings manually (via an NMS application).

Version 3 of the Entity MIB provides two additional MIB objects for each physical entity:

- entPhysicalMfgDate  
This object contains the date of manufacturing of the managed entity. If the manufacturing date is unknown or not supported the object is not instantiated. The special value '0000000000000000'H may also be returned in this case.
- entPhysicalUri  
This object provides additional identification information about the physical entity.

This object contains one or more Uniform Resource Identifiers (URIs); therefore, the syntax of this object must conform to [RFC3986], Section 3. Uniform Resource Names (URNs) [RFC3406] are resource identifiers with the specific requirements for enabling location-independent identification of a resource, as well as longevity of reference. URNs are part of the larger URI family with the specific goal of providing persistent naming of resources. URI schemes and URN namespaces are registered by IANA (see <http://www.iana.org/assignments/uri-schemes> and <http://www.iana.org/assignments/urn-namespaces>).

For example, the entPhysicalUri object may be used to encode a URI containing a Common Language Equipment Identifier (CLEI) URN for the managed physical entity. The URN namespace for CLEIs is defined in [RFC4152], and the CLEI format is defined in [T1.213] and [T1.213a]. For example, an entPhysicalUri instance may have the value of:

URN:CLEI:D4CE18B7AA

[RFC3986] and [RFC4152] identify this as a URI in the CLEI URN namespace. The specific CLEI code, D4CE18B7AA, is based on the example provided in [T1.213a].

Multiple URIs may be present and are separated by white space characters. Leading and trailing white space characters are ignored.

If no additional identification information is known about the physical entity or supported, the object is not instantiated.

Version 4 of the Entity MIB module provides an additional MIB object for each physical entity.

- entPhysicalUUID

This object provides an unique identification about the physical entity. This object contains a globally unique identifier for the physical entity with the format defined in RFC 4122 [RFC4122].

To support the existing implementations of ENTITY-MIB version 3 [RFC4133], entPhysicalUris object should be used to store the UUID value of the physical entity as well in URN format. This duplication of information enables backward compatibility. Note that entPhysicalUris allows write access while entPhysicalUUID is read-only.

### 2.12.2. entityLogical Group

This group contains a single table to identify logical entities, called the entLogicalTable.

The entLogicalTable contains one row per logical entity. Each row is indexed by an arbitrary, small integer and contains a name, description, and type of the logical entity. It also contains information to allow access to the MIB information for the logical entity. This includes SNMP versions that use a community name (with some form of implied context representation) and SNMP versions that use the SNMP ARCH [RFC3411] method of context identification.

If an agent represents multiple logical entities with this MIB, then this group must be implemented for all logical entities known to the agent.

If an agent represents a single logical entity, or multiple logical entities within a single naming scope, then implementation of this group may be omitted by the agent.

### 2.12.3. entityMapping Group

This group contains three tables to identify associations between different system components.

- entLPMappingTable

This table contains mappings between entLogicalIndex values (logical entities) and entPhysicalIndex values (the physical components supporting that entity). A logical entity can map to more than one physical component, and more than one logical entity can map to (share) the same physical component. If an agent represents a single logical entity, or multiple logical entities within a single naming scope, then implementation of this table may be omitted by the agent.

- entAliasMappingTable  
This table contains mappings between entLogicalIndex, entPhysicalIndex pairs, and 'alias' object identifier values. This allows resources managed with other MIB modules (e.g., repeater ports, bridge ports, physical and logical interfaces) to be identified in the physical entity hierarchy. Note that each alias identifier is only relevant in a particular naming scope. If an agent represents a single logical entity, or multiple logical entities within a single naming scope, then implementation of this table may be omitted by the agent.
- entPhysicalContainsTable  
This table contains simple mappings between entPhysicalContainedIn values for each container/'containee' relationship in the managed system. The indexing of this table allows an NMS to quickly discover the entPhysicalIndex values for all children of a given physical entity.

#### 2.12.4. entityGeneral Group

This group contains general information relating to the other object groups.

At this time, the entGeneral group contains a single scalar object (entLastChangeTime), which represents the value of sysUpTime when any part of the Entity MIB configuration last changed.

#### 2.12.5. entityNotifications Group

This group contains notification definitions relating to the overall status of the Entity MIB instantiation.

### 2.13. Multiple Agents

Even though a primary motivation for this MIB is to represent the multiple logical entities supported by a single agent, another motivation is to represent multiple logical entities supported by multiple agents (in the same "overall" physical entity). Indeed, it is implicit in the SNMP architecture that the number of agents is transparent to a network management station.

However, there is no agreement at this time as to the degree of cooperation that should be expected for agent implementations. Therefore, multiple agents within the same managed system are free to implement the Entity MIB independently. (For more information, refer to [Section 2.9](#), "Multiple Instances of the Entity MIB".)

## 2.14. Changes Since RFC 2037

### 2.14.1. Textual Conventions

The PhysicalClass TC text has been clarified, and a new enumeration to support 'stackable' components has been added. The SnmpEngineIdOrNone TC has been added to support SNMPv3.

### 2.14.2. New entPhysicalTable Objects

The entPhysicalHardwareRev, entPhysicalFirmwareRev, and entPhysicalSoftwareRev objects have been added for revision identification.

The entPhysicalSerialNum, entPhysicalMfgName, entPhysicalModelName, and entPhysicalIsFRU objects have been added for better vendor identification for physical components. In the event the agent cannot identify this information, the entPhysicalSerialNum object can be set by a management station.

The entPhysicalAlias and entPhysicalAssetID objects have been added for better user component identification. These objects are intended to be set by a management station and preserved by the agent across restarts.

### 2.14.3. New entLogicalTable Objects

The entLogicalContextEngineID and entLogicalContextName objects have been added to provide an SNMP context for SNMPv3 access on behalf of a logical entity.

### 2.14.4. Bug Fixes

A bug was fixed in the entLogicalCommunity object. The subrange was incorrect (1..255) and is now correct (0..255). The description clause has also been clarified. This object is now deprecated.

The entLastChangeTime object description has been changed to generalize the events that cause an update to the last change timestamp.

The syntax was changed from DisplayString to SnmpAdminString for the entPhysicalDescr, entPhysicalName, and entLogicalDescr objects.

## 2.15. Changes Since [RFC 2737](#)

### 2.15.1. Textual Conventions

The PhysicalIndexOrZero TC has been added to allow objects to reference an entPhysicalIndex value or zero. The PhysicalClass TC has been extended to support a new enumeration for central processing units.

### 2.15.2. New Objects

The entPhysicalMfgDate object has been added to the entPhysicalTable to provide the date of manufacturing of the managed entity.

The entPhysicalUris object has been added to the entPhysicalTable to provide additional identification information about the physical entity, such as a Common Language Equipment Identifier (CLEI) URN.

### 2.15.3. Bug Fixes

The syntax was changed from INTEGER to Integer32 for the entPhysicalParentRelPos, entLogicalIndex, and entAliasLogicalIndexOrZero objects, and from INTEGER to PhysicalIndexOrZero for the entPhysicalContainedIn object.

## 2.16. Changes Since [RFC 4133](#)

### 2.16.1. MIB Module Addition

Over time, there may be the need to add new enumerated values to the PhysicalClass TEXTUAL-CONVENTION. To allow for such additions without requiring re-issuing of this MIB module, a new MIB module called IANA-ENTITY-MIB that provides the IANA-maintained TEXTUAL-CONVENTION IANAPhysicalClass has been created. The PhysicalClass TC has been deprecated.

### 2.16.2. Modification to Some of the MIB Objects

A new MIB object has been added to the entPhysicalTable, entPhysicalUUID. In comparison to entPhysicalUris, the new object is read-only and restricted to a fixed size to allow only for [RFC 4122](#) [RFC4122] compliant values. The PhysicalClass TEXTUAL-CONVENTION was deprecated, and a new IANAPhysicalClass TC (maintained by IANA) has been created.

Two new MODULE-COMPLIANCE modules have been created: entity4Compliance for full compliance with version 4 of the Entity MIB, and entity4CRCompliance for devices with constrained resources like batteries that might require a limited number of objects to be supported (entPhysicalClass, entPhysicalName, and entPhysicalUUID).

### 2.16.3. New TC for Universally Unique Identifier

A new TEXTUAL-CONVENTION, UUIDorZero, was created to represent a Universally Unique Identifier (UUID) with a syntax that conforms to [RFC4122], Section 4.1. Defining it as a TC will allow for future reuse in other MIB modules that will import the TC. This Textual Convention is included in the UUID-TC-MIB module.

## 3. MIB Definitions

### 3.1. ENTITY-MIB

```
ENTITY-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, mib-2, NOTIFICATION-TYPE,
    Integer32
        FROM SNMPv2-SMI                      -- RFC 2578
    TDomain, TAddress, TEXTUAL-CONVENTION,
    AutonomousType, RowPointer, TimeStamp, TruthValue,
    DateAndTime
        FROM SNMPv2-TC                      -- RFC 2579
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
        FROM SNMPv2-CONF                    -- RFC 2580
    SnmpAdminString
        FROM SNMP-FRAMEWORK-MIB             -- RFC 3411
    UUIDorZero
        FROM UUID-TC-MIB                    -- RFC 6933
    IANAPhysicalClass
        FROM IANA-ENTITY-MIB;               -- RFC 6933
```

```
entityMIB MODULE-IDENTITY
```

```
    LAST-UPDATED "201304050000Z"             -- April 5, 2013
    ORGANIZATION "IETF Energy Management Working Group"
    CONTACT-INFO
        "WG Email: eman@ietf.org
        Mailing list subscription info:
        http://www.ietf.org/mailman/listinfo/eman
```



Andy Bierman  
YumaWorks, Inc.  
274 Redwood Shores Parkway, #133  
Redwood City, CA 94065  
USA  
Phone: +1 408-716-0466  
Email: andy@yumaworks.com

Dan Romascanu  
Avaya  
Park Atidim, Bldg. #3  
Tel Aviv, 61581  
Israel  
Phone: +972-3-6458414  
Email: dromasca@avaya.com

Juergen Quittek  
NEC Europe Ltd.  
Network Research Division  
Kurfuersten-Anlage 36  
Heidelberg 69115  
Germany  
Phone: +49 6221 4342-115  
Email: quittek@neclab.eu

Mouli Chandramouli  
Cisco Systems, Inc.  
Sarjapur Outer Ring Road  
Bangalore 560103  
India  
Phone: +91 80 4429 2409  
Email: moulchan@cisco.com"

#### DESCRIPTION

"The MIB module for representing multiple logical entities supported by a single SNMP agent.

Copyright (c) 2013 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>)."

REVISION                    "201304050000Z"                    -- April 5, 2013

## DESCRIPTION

"Entity MIB (Version 4).

This revision obsoletes [RFC 4133](#).

- Creation of a new MIB module, IANA-ENTITY-MIB, which makes the PhysicalIndex TC an IANA-maintained TEXTUAL-CONVENTION. IANAPhysicalClass is now imported from the IANA-ENTITY-MIB.

- Addition of a new MIB object to the entPhysicalTable, entPhysicalUUID. UUIDorZero is imported from the UUID-TC-MIB.

- Addition of two new MODULE-COMPLIANCE modules- entity4Compliance and entity4CRCCompliance.

This version is published as [RFC 6933](#)."

REVISION "200508100000Z"

## DESCRIPTION

"Initial Version of Entity MIB (Version 3).

This revision obsoletes [RFC 2737](#).

Additions:

- cpu(12) enumeration added to IANAPhysicalClass TC
- DISPLAY-HINT clause to PhysicalIndex TC
- PhysicalIndexOrZero TC
- entPhysicalMfgDate object
- entPhysicalUris object

Changes:

- entPhysicalContainedIn SYNTAX changed from INTEGER to PhysicalIndexOrZero

This version was published as [RFC 4133](#)."

REVISION "199912070000Z"

## DESCRIPTION

"Initial Version of Entity MIB (Version 2).

This revision obsoletes [RFC 2037](#).

This version was published as [RFC 2737](#)."

REVISION "199610310000Z"

## DESCRIPTION

"Initial version (version 1), published as [RFC 2037](#)."

::= { mib-2 47 }

entityMIBObjects OBJECT IDENTIFIER ::= { entityMIB 1 }

```
-- MIB contains four groups
entityPhysical OBJECT IDENTIFIER ::= { entityMIBObjects 1 }
entityLogical  OBJECT IDENTIFIER ::= { entityMIBObjects 2 }
entityMapping  OBJECT IDENTIFIER ::= { entityMIBObjects 3 }
entityGeneral  OBJECT IDENTIFIER ::= { entityMIBObjects 4 }

-- Textual Conventions
PhysicalIndex ::= TEXTUAL-CONVENTION
    DISPLAY-HINT      "d"
    STATUS             current
    DESCRIPTION
        "An arbitrary value that uniquely identifies the physical
        entity.  The value should be a small positive integer.
        Index values for different physical entities are not
        necessarily contiguous."
    SYNTAX Integer32 (1..2147483647)

PhysicalIndexOrZero ::= TEXTUAL-CONVENTION
    DISPLAY-HINT      "d"
    STATUS             current
    DESCRIPTION
        "This TEXTUAL-CONVENTION is an extension of the
        PhysicalIndex convention, which defines a greater than zero
        value used to identify a physical entity.  This extension
        permits the additional value of zero.  The semantics of the
        value zero are object-specific and must, therefore, be
        defined as part of the description of any object that uses
        this syntax.  Examples of the usage of this extension are
        situations where none or all physical entities need to be
        referenced."
    SYNTAX Integer32 (0..2147483647)

SnmpEngineIdOrNone ::= TEXTUAL-CONVENTION
    STATUS             current
    DESCRIPTION
        "A specially formatted SnmpEngineID string for use with the
        Entity MIB.

        If an instance of an object of SYNTAX SnmpEngineIdOrNone has
        a non-zero length, then the object encoding and semantics
        are defined by the SnmpEngineID TEXTUAL-CONVENTION (see STD
        62, RFC 3411).
```

If an instance of an object of SYNTAX SnmpEngineIdOrNone contains a zero-length string, then no appropriate SnmpEngineID is associated with the logical entity (i.e., SNMPv3 is not supported)."

SYNTAX OCTET STRING (SIZE(0..32)) -- empty string or SnmpEngineID

PhysicalClass ::= TEXTUAL-CONVENTION

STATUS deprecated

DESCRIPTION

"Starting with version 4 of the ENTITY-MIB, this TC is deprecated, and the usage of the IANAPhysicalClass TC from the IANA-ENTITY-MIB is recommended instead.

An enumerated value that provides an indication of the general hardware type of a particular physical entity. There are no restrictions as to the number of entPhysicalEntries of each entPhysicalClass, which must be instantiated by an agent.

The enumeration 'other' is applicable if the physical entity class is known but does not match any of the supported values.

The enumeration 'unknown' is applicable if the physical entity class is unknown to the agent.

The enumeration 'chassis' is applicable if the physical entity class is an overall container for networking equipment. Any class of physical entity, except a stack, may be contained within a chassis; a chassis may only be contained within a stack.

The enumeration 'backplane' is applicable if the physical entity class is some sort of device for aggregating and forwarding networking traffic, such as a shared backplane in a modular ethernet switch. Note that an agent may model a backplane as a single physical entity, which is actually implemented as multiple discrete physical components (within a chassis or stack).

The enumeration 'container' is applicable if the physical entity class is capable of containing one or more removable physical entities, possibly of different types. For example, each (empty or full) slot in a chassis will be modeled as a container. Note that all removable physical entities should be modeled within a container entity, such

as field-replaceable modules, fans, or power supplies. Note that all known containers should be modeled by the agent, including empty containers.

The enumeration 'powerSupply' is applicable if the physical entity class is a power-supplying component.

The enumeration 'fan' is applicable if the physical entity class is a fan or other heat-reduction component.

The enumeration 'sensor' is applicable if the physical entity class is some sort of sensor, such as a temperature sensor within a router chassis.

The enumeration 'module' is applicable if the physical entity class is some sort of self-contained sub-system. If the enumeration 'module' is removable, then it should be modeled within a container entity; otherwise, it should be modeled directly within another physical entity (e.g., a chassis or another module).

The enumeration 'port' is applicable if the physical entity class is some sort of networking port capable of receiving and/or transmitting networking traffic.

The enumeration 'stack' is applicable if the physical entity class is some sort of super-container (possibly virtual) intended to group together multiple chassis entities. A stack may be realized by a 'virtual' cable, a real interconnect cable, attached to multiple chassis, or may in fact be comprised of multiple interconnect cables. A stack should not be modeled within any other physical entities, but a stack may be contained within another stack. Only chassis entities should be contained within a stack.

The enumeration 'cpu' is applicable if the physical entity class is some sort of central processing unit."

```
SYNTAX      INTEGER {
    other(1),
    unknown(2),
    chassis(3),
    backplane(4),
    container(5),      -- e.g., chassis slot or daughter-card holder
    powerSupply(6),
    fan(7),
    sensor(8),
    module(9),         -- e.g., plug-in card or daughter-card
    port(10),
```

```

        stack(11),          -- e.g., stack of multiple chassis entities
        cpu(12)
    }

--          The Physical Entity Table
entPhysicalTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF EntPhysicalEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains one row per physical entity.  There is
         always at least one row for an 'overall' physical entity."
    ::= { entityPhysical 1 }

entPhysicalEntry      OBJECT-TYPE
    SYNTAX      EntPhysicalEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Information about a particular physical entity.

        Each entry provides objects (entPhysicalDescr,
        entPhysicalVendorType, and entPhysicalClass) to help an NMS
        identify and characterize the entry and objects
        (entPhysicalContainedIn and entPhysicalParentRelPos) to help
        an NMS relate the particular entry to other entries in this
        table."
    INDEX      { entPhysicalIndex }
    ::= { entPhysicalTable 1 }

EntPhysicalEntry ::= SEQUENCE {
    entPhysicalIndex      PhysicalIndex,
    entPhysicalDescr      SnmpAdminString,
    entPhysicalVendorType AutonomousType,
    entPhysicalContainedIn PhysicalIndexOrZero,
    entPhysicalClass      IANAPhysicalClass,
    entPhysicalParentRelPos Integer32,
    entPhysicalName        SnmpAdminString,
    entPhysicalHardwareRev  SnmpAdminString,
    entPhysicalFirmwareRev  SnmpAdminString,
    entPhysicalSoftwareRev  SnmpAdminString,
    entPhysicalSerialNum    SnmpAdminString,
    entPhysicalMfgName       SnmpAdminString,
    entPhysicalModelName    SnmpAdminString,
    entPhysicalAlias         SnmpAdminString,
    entPhysicalAssetID       SnmpAdminString,
    entPhysicalIsFRU         TruthValue,

```

```
    entPhysicalMfgDate      DateAndTime,
    entPhysicalUris         OCTET STRING,
    entPhysicalUUID         UUIDorZero
}

entPhysicalIndex OBJECT-TYPE
    SYNTAX      PhysicalIndex
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The index for this entry."
    ::= { entPhysicalEntry 1 }

entPhysicalDescr OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A textual description of physical entity. This object
        should contain a string that identifies the manufacturer's
        name for the physical entity and should be set to a
        distinct value for each version or model of the physical
        entity."
    ::= { entPhysicalEntry 2 }

entPhysicalVendorType OBJECT-TYPE
    SYNTAX      AutonomousType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "An indication of the vendor-specific hardware type of the
        physical entity. Note that this is different from the
        definition of MIB-II's sysObjectID.

        An agent should set this object to an enterprise-specific
        registration identifier value indicating the specific
        equipment type in detail. The associated instance of
        entPhysicalClass is used to indicate the general type of
        hardware device.

        If no vendor-specific registration identifier exists for
        this physical entity, or the value is unknown by this agent,
        then the value { 0 0 } is returned."
    ::= { entPhysicalEntry 3 }
```

## entPhysicalContainedIn OBJECT-TYPE

SYNTAX PhysicalIndexOrZero

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The value of entPhysicalIndex for the physical entity that 'contains' this physical entity. A value of zero indicates this physical entity is not contained in any other physical entity. Note that the set of 'containment' relationships define a strict hierarchy; that is, recursion is not allowed.

In the event that a physical entity is contained by more than one physical entity (e.g., double-wide modules), this object should identify the containing entity with the lowest value of entPhysicalIndex."

::= { entPhysicalEntry 4 }

## entPhysicalClass OBJECT-TYPE

SYNTAX IANAPhysicalClass

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"An indication of the general hardware type of the physical entity.

An agent should set this object to the standard enumeration value that most accurately indicates the general class of the physical entity, or the primary class if there is more than one entity.

If no appropriate standard registration identifier exists for this physical entity, then the value 'other(1)' is returned. If the value is unknown by this agent, then the value 'unknown(2)' is returned."

::= { entPhysicalEntry 5 }

## entPhysicalParentRelPos OBJECT-TYPE

SYNTAX Integer32 (-1..2147483647)

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"An indication of the relative position of this 'child' component among all its 'sibling' components. Sibling components are defined as entPhysicalEntries that share the same instance values of each of the entPhysicalContainedIn and entPhysicalClass objects.



An NMS can use this object to identify the relative ordering for all sibling components of a particular parent (identified by the `entPhysicalContainedIn` instance in each sibling entry).

If possible, this value should match any external labeling of the physical component. For example, for a container (e.g., card slot) labeled as 'slot #3', `entPhysicalParentRelPos` should have the value '3'. Note that the `entPhysicalEntry` for the module plugged in slot 3 should have an `entPhysicalParentRelPos` value of '1'.

If the physical position of this component does not match any external numbering or clearly visible ordering, then user documentation or other external reference material should be used to determine the parent-relative position. If this is not possible, then the agent should assign a consistent (but possibly arbitrary) ordering to a given set of 'sibling' components, perhaps based on internal representation of the components.

If the agent cannot determine the parent-relative position for some reason, or if the associated value of `entPhysicalContainedIn` is '0', then the value '-1' is returned. Otherwise, a non-negative integer is returned, indicating the parent-relative position of this physical entity.

Parent-relative ordering normally starts from '1' and continues to 'N', where 'N' represents the highest positioned child entity. However, if the physical entities (e.g., slots) are labeled from a starting position of zero, then the first sibling should be associated with an `entPhysicalParentRelPos` value of '0'. Note that this ordering may be sparse or dense, depending on agent implementation.

The actual values returned are not globally meaningful, as each 'parent' component may use different numbering algorithms. The ordering is only meaningful among siblings of the same parent component.

The agent should retain parent-relative position values across reboots, either through algorithmic assignment or use of non-volatile storage."

::= { entPhysicalEntry 6 }

`entPhysicalName` OBJECT-TYPE

SYNTAX            SnmpAdminString  
MAX-ACCESS       read-only  
STATUS            current  
DESCRIPTION

"The textual name of the physical entity. The value of this object should be the name of the component as assigned by the local device and should be suitable for use in commands entered at the device's 'console'. This might be a text name (e.g., 'console') or a simple component number (e.g., port or module number, such as '1'), depending on the physical component naming syntax of the device.

If there is no local name, or if this object is otherwise not applicable, then this object contains a zero-length string.

Note that the value of entPhysicalName for two physical entities will be the same in the event that the console interface does not distinguish between them, e.g., slot-1 and the card in slot-1."

::= { entPhysicalEntry 7 }

entPhysicalHardwareRev       OBJECT-TYPE

SYNTAX            SnmpAdminString  
MAX-ACCESS       read-only  
STATUS            current  
DESCRIPTION

"The vendor-specific hardware revision string for the physical entity. The preferred value is the hardware revision identifier actually printed on the component itself (if present).

Note that if revision information is stored internally in a non-printable (e.g., binary) format, then the agent must convert such information to a printable format in an implementation-specific manner.

If no specific hardware revision string is associated with the physical component, or if this information is unknown to the agent, then this object will contain a zero-length string."

::= { entPhysicalEntry 8 }

entPhysicalFirmwareRev       OBJECT-TYPE

SYNTAX            SnmpAdminString  
MAX-ACCESS       read-only  
STATUS            current

## DESCRIPTION

"The vendor-specific firmware revision string for the physical entity.

Note that if revision information is stored internally in a non-printable (e.g., binary) format, then the agent must convert such information to a printable format in an implementation-specific manner.

If no specific firmware programs are associated with the physical component, or if this information is unknown to the agent, then this object will contain a zero-length string."

::= { entPhysicalEntry 9 }

entPhysicalSoftwareRev OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The vendor-specific software revision string for the physical entity.

Note that if revision information is stored internally in a non-printable (e.g., binary) format, then the agent must convert such information to a printable format in an implementation-specific manner.

If no specific software programs are associated with the physical component, or if this information is unknown to the agent, then this object will contain a zero-length string."

::= { entPhysicalEntry 10 }

entPhysicalSerialNum OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE (0..32))

MAX-ACCESS read-write

STATUS current

## DESCRIPTION

"The vendor-specific serial number string for the physical entity. The preferred value is the serial number string actually printed on the component itself (if present).

On the first instantiation of a physical entity, the value of entPhysicalSerialNum associated with that entity is set to the correct vendor-assigned serial number, if this information is available to the agent. If a serial number is unknown or non-existent, the entPhysicalSerialNum will be set to a zero-length string instead.

Note that implementations that can correctly identify the serial numbers of all installed physical entities do not need to provide write access to the entPhysicalSerialNum object. Agents that cannot provide non-volatile storage for the entPhysicalSerialNum strings are not required to implement write access for this object.

Not every physical component will have a serial number, or even need one. Physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)' (e.g., the repeater ports within a repeater module) do not need their own unique serial numbers. An agent does not have to provide write access for such entities and may return a zero-length string.

If write access is implemented for an instance of entPhysicalSerialNum and a value is written into the instance, the agent must retain the supplied value in the entPhysicalSerialNum instance (associated with the same physical entity) for as long as that entity remains instantiated. This includes instantiations across all re-initializations/reboots of the network management system, including those resulting in a change of the physical entity's entPhysicalIndex value."

```
::= { entPhysicalEntry 11 }
```

entPhysicalMfgName OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The name of the manufacturer of this physical component. The preferred value is the manufacturer name string actually printed on the component itself (if present).

Note that comparisons between instances of the entPhysicalModelName, entPhysicalFirmwareRev, entPhysicalSoftwareRev, and the entPhysicalSerialNum objects are only meaningful amongst entPhysicalEntries with the same value of entPhysicalMfgName.

If the manufacturer name string associated with the physical component is unknown to the agent, then this object will contain a zero-length string."

```
::= { entPhysicalEntry 12 }
```

entPhysicalModelName OBJECT-TYPE  
SYNTAX SnmpAdminString  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
    "The vendor-specific model name identifier string associated with this physical component. The preferred value is the customer-visible part number, which may be printed on the component itself.  
  
    If the model name string associated with the physical component is unknown to the agent, then this object will contain a zero-length string."  
 ::= { entPhysicalEntry 13 }

entPhysicalAlias OBJECT-TYPE  
SYNTAX SnmpAdminString (SIZE (0..32))  
MAX-ACCESS read-write  
STATUS current  
DESCRIPTION  
    "This object is an 'alias' name for the physical entity, as specified by a network manager, and provides a non-volatile 'handle' for the physical entity.  
  
    On the first instantiation of a physical entity, the value of entPhysicalAlias associated with that entity is set to the zero-length string. However, the agent may set the value to a locally unique default value, instead of a zero-length string.  
  
    If write access is implemented for an instance of entPhysicalAlias and a value is written into the instance, the agent must retain the supplied value in the entPhysicalAlias instance (associated with the same physical entity) for as long as that entity remains instantiated. This includes instantiations across all re-initializations/reboots of the network management system, including those resulting in a change of the physical entity's entPhysicalIndex value."  
 ::= { entPhysicalEntry 14 }

entPhysicalAssetID OBJECT-TYPE  
SYNTAX SnmpAdminString (SIZE (0..32))  
MAX-ACCESS read-write  
STATUS current

## DESCRIPTION

"This object is a user-assigned asset tracking identifier (as specified by a network manager) for the physical entity and provides non-volatile storage of this information.

On the first instantiation of a physical entity, the value of entPhysicalAssetID associated with that entity is set to the zero-length string.

Not every physical component will have an asset tracking identifier or even need one. Physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)' (e.g., the repeater ports within a repeater module) do not need their own unique asset tracking identifier. An agent does not have to provide write access for such entities and may instead return a zero-length string.

If write access is implemented for an instance of entPhysicalAssetID and a value is written into the instance, the agent must retain the supplied value in the entPhysicalAssetID instance (associated with the same physical entity) for as long as that entity remains instantiated. This includes instantiations across all re-initializations/reboots of the network management system, including those resulting in a change of the physical entity's entPhysicalIndex value.

If no asset tracking information is associated with the physical component, then this object will contain a zero-length string."

::= { entPhysicalEntry 15 }

## entPhysicalIsFRU OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"This object indicates whether or not this physical entity is considered a 'field replaceable unit' by the vendor. If this object contains the value 'true(1)', then this entPhysicalEntry identifies a field replaceable unit. For all entPhysicalEntries that represent components permanently contained within a field replaceable unit, the value 'false(2)' should be returned for this object."

::= { entPhysicalEntry 16 }

```
entPhysicalMfgDate OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object contains the date of manufacturing of the
        managed entity.  If the manufacturing date is unknown or
        not supported, the object is not instantiated.  The special
        value '0000000000000000'H may also be returned in this
        case."
    ::= { entPhysicalEntry 17 }
```

```
entPhysicalUris OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This object contains identification
        information about the physical entity.  The object
        contains URIs; therefore, the syntax of this object
        must conform to RFC 3986, Section 3.

        Multiple URIs may be present and are separated by white
        space characters.  Leading and trailing white space
        characters are ignored.

        If no URI identification information is known
        about the physical entity, the object is not
        instantiated.  A zero-length octet string may also be
        returned in this case."
    REFERENCE
        "RFC 3986, Uniform Resource Identifiers (URI): Generic
        Syntax, Section 2, August 1998."
    ::= { entPhysicalEntry 18 }
```

```
entPhysicalUUID OBJECT-TYPE
    SYNTAX      UUIDorZero
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object contains identification information
        about the physical entity.  The object contains a
        Universally Unique Identifier, the syntax of this object
        must conform to RFC 4122, Section 4.1.

        A zero-length octet string is returned if no UUID
        information is known."
```

## REFERENCE

"RFC 4122, A Universally Unique IDentifier (UUID) URN Namespace, [Section 4.1](#), July 2005."

```
::= { entPhysicalEntry 19 }
```

```
--          The Logical Entity Table
entLogicalTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF EntLogicalEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "This table contains one row per logical entity.  For agents
        that implement more than one naming scope, at least one
        entry must exist.  Agents that instantiate all MIB objects
        within a single naming scope are not required to implement
        this table."
    ::= { entityLogical 1 }

entLogicalEntry      OBJECT-TYPE
    SYNTAX      EntLogicalEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "Information about a particular logical entity.  Entities
        may be managed by this agent or other SNMP agents (possibly)
        in the same chassis."
    INDEX       { entLogicalIndex }
    ::= { entLogicalTable 1 }

EntLogicalEntry ::= SEQUENCE {
    entLogicalIndex      Integer32,
    entLogicalDescr      SnmpAdminString,
    entLogicalType       AutonomousType,
    entLogicalCommunity  OCTET STRING,
    entLogicalTAddress    TAddress,
    entLogicalTDomain     TDomain,
    entLogicalContextEngineID SnmpEngineIdOrNone,
    entLogicalContextName  SnmpAdminString
}

entLogicalIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS   not-accessible
    STATUS       current
```



## DESCRIPTION

"The value of this object uniquely identifies the logical entity. The value should be a small positive integer; index values for different logical entities are not necessarily contiguous."

::= { entLogicalEntry 1 }

## entLogicalDescr OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"A textual description of the logical entity. This object should contain a string that identifies the manufacturer's name for the logical entity and should be set to a distinct value for each version of the logical entity."

::= { entLogicalEntry 2 }

## entLogicalType OBJECT-TYPE

SYNTAX AutonomousType

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"An indication of the type of logical entity. This will typically be the OBJECT IDENTIFIER name of the node in the SMI's naming hierarchy that represents the major MIB module, or the majority of the MIB modules, supported by the logical entity. For example:

a logical entity of a regular host/router -> mib-2

a logical entity of a 802.1d bridge -> dot1dBridge

a logical entity of a 802.3 repeater -> snmpDot3RptrMgmt

If an appropriate node in the SMI's naming hierarchy cannot be identified, the value 'mib-2' should be used."

::= { entLogicalEntry 3 }

## entLogicalCommunity OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (0..255))

MAX-ACCESS read-only

STATUS deprecated

## DESCRIPTION

"An SNMPv1 or SNMPv2c community string, which can be used to access detailed management information for this logical entity. The agent should allow read access with this community string (to an appropriate subset of all managed objects) and may also return a community string based on the privileges of the request used to read this object. Note that an agent may return a community string with read-only privileges, even if this object is accessed with a

read-write community string. However, the agent must take care not to return a community string that allows more privileges than the community string used to access this object.

A compliant SNMP agent may wish to conserve naming scopes by representing multiple logical entities in a single 'default' naming scope. This is possible when the logical entities, represented by the same value of `entLogicalCommunity`, have no object instances in common. For example, 'bridge1' and 'repeater1' may be part of the main naming scope, but at least one additional community string is needed to represent 'bridge2' and 'repeater2'.

Logical entities 'bridge1' and 'repeater1' would be represented by `sysOREntries` associated with the 'default' naming scope.

For agents not accessible via SNMPv1 or SNMPv2c, the value of this object is the empty string. This object may also contain an empty string if a community string has not yet been assigned by the agent or if no community string with suitable access rights can be returned for a particular SNMP request.

Note that this object is deprecated. Agents that implement SNMPv3 access should use the `entLogicalContextEngineID` and `entLogicalContextName` objects to identify the context associated with each logical entity. SNMPv3 agents may return a zero-length string for this object or may continue to return a community string (e.g., tri-lingual agent support)."

::= { entLogicalEntry 4 }

`entLogicalTAddress` OBJECT-TYPE

SYNTAX           TAddress  
MAX-ACCESS   read-only  
STATUS       current  
DESCRIPTION

"The transport service address by which the logical entity receives network management traffic, formatted according to the corresponding value of `entLogicalTDomain`.

For `snmpUDPDomain`, a `TAddress` is 6 octets long: the initial 4 octets contain the IP-address in network-byte order, and the last 2 contain the UDP port in network-byte order. Consult [RFC 3417](#) for further information on `snmpUDPDomain`."

## REFERENCE

"Transport Mappings for the Simple Network Management Protocol (SNMP), STD 62, [RFC 3417](#)."  
::= { entLogicalEntry 5 }

## entLogicalTDomain OBJECT-TYPE

SYNTAX TDomain  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"Indicates the kind of transport service by which the logical entity receives network management traffic. Possible values for this object are presently found in [RFC 3417](#)."

## REFERENCE

"Transport Mappings for the Simple Network Management Protocol (SNMP), STD 62, [RFC 3417](#)."  
::= { entLogicalEntry 6 }

## entLogicalContextEngineID OBJECT-TYPE

SYNTAX SnmpEngineIdOrNone  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The authoritative contextEngineID that can be used to send an SNMP message concerning information held by this logical entity to the address specified by the associated 'entLogicalTAddress/entLogicalTDomain' pair.

This object, together with the associated entLogicalContextName object, defines the context associated with a particular logical entity and allows access to SNMP engines identified by a contextEngineID and contextName pair.

If no value has been configured by the agent, a zero-length string is returned, or the agent may choose not to instantiate this object at all."

::= { entLogicalEntry 7 }

## entLogicalContextName OBJECT-TYPE

SYNTAX SnmpAdminString  
MAX-ACCESS read-only  
STATUS current

## DESCRIPTION

"The contextName that can be used to send an SNMP message concerning information held by this logical entity to the address specified by the associated 'entLogicalTAddress/entLogicalTDomain' pair.

This object, together with the associated entLogicalContextEngineID object, defines the context associated with a particular logical entity and allows access to SNMP engines identified by a contextEngineID and contextName pair.

If no value has been configured by the agent, a zero-length string is returned, or the agent may choose not to instantiate this object at all."

::= { entLogicalEntry 8 }

## entLPMappingTable OBJECT-TYPE

SYNTAX SEQUENCE OF EntLPMappingEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"This table contains zero or more rows of logical entity to physical equipment associations. For each logical entity known by this agent, there are zero or more mappings to the physical resources, which are used to realize that logical entity.

An agent should limit the number and nature of entries in this table such that only meaningful and non-redundant information is returned. For example, in a system that contains a single power supply, mappings between logical entities and the power supply are not useful and should not be included.

Also, only the most appropriate physical component, which is closest to the root of a particular containment tree, should be identified in an entLPMapping entry.

For example, suppose a bridge is realized on a particular module, and all ports on that module are ports on this bridge. A mapping between the bridge and the module would be useful, but additional mappings between the bridge and each of the ports on that module would be redundant (because the entPhysicalContainedIn hierarchy can provide the same information). On the other hand, if more than one bridge were utilizing ports on this module, then mappings between each bridge and the ports it used would be appropriate.

Also, in the case of a single backplane repeater, a mapping for the backplane to the single repeater entity is not necessary."

::= { entityMapping 1 }

entLPMappingEntry OBJECT-TYPE

SYNTAX EntLPMappingEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Information about a particular logical-entity-to-physical-equipment association. Note that the nature of the association is not specifically identified in this entry. It is expected that sufficient information exists in the MIB modules used to manage a particular logical entity to infer how physical component information is utilized."

INDEX { entLogicalIndex, entLPPhysicalIndex }

::= { entLPMappingTable 1 }

EntLPMappingEntry ::= SEQUENCE {

entLPPhysicalIndex PhysicalIndex

}

entLPPhysicalIndex OBJECT-TYPE

SYNTAX PhysicalIndex

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of this object identifies the index value of a particular entPhysicalEntry associated with the indicated entLogicalEntity."

::= { entLPMappingEntry 1 }

-- logical entity/component to alias table

entAliasMappingTable OBJECT-TYPE

SYNTAX SEQUENCE OF EntAliasMappingEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains zero or more rows, representing mappings of logical entities and physical components to external MIB identifiers. Each physical port in the system may be associated with a mapping to an external identifier, which itself is associated with a particular logical

entity's naming scope. A 'wildcard' mechanism is provided to indicate that an identifier is associated with more than one logical entity."

```
 ::= { entityMapping 2 }
```

entAliasMappingEntry OBJECT-TYPE

```
SYNTAX      EntAliasMappingEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"Information about a particular binding between a logical entity/physical component pair and an external identifier. Each logical entity/physical component pair may be associated with one alias mapping. The logical entity index may also be used as a 'wildcard' (refer to the entAliasLogicalIndexOrZero object DESCRIPTION clause for details.)

Note that only entPhysicalIndex values that represent physical ports (i.e., associated entPhysicalClass value is 'port(10)') are permitted to exist in this table."

```
INDEX { entPhysicalIndex, entAliasLogicalIndexOrZero }
 ::= { entAliasMappingTable 1 }
```

EntAliasMappingEntry ::= SEQUENCE {

```
    entAliasLogicalIndexOrZero      Integer32,
    entAliasMappingIdentifier       RowPointer
}
```

entAliasLogicalIndexOrZero OBJECT-TYPE

```
SYNTAX      Integer32 (0..2147483647)
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"The value of this object identifies the logical entity that defines the naming scope for the associated instance of the entAliasMappingIdentifier object.

If this object has a non-zero value, then it identifies the logical entity named by the same value of entLogicalIndex.

If this object has a value of zero, then the mapping between the physical component and the alias identifier for this entAliasMapping entry is associated with all unspecified logical entities. That is, a value of zero (the default mapping) identifies any logical entity that does not have an explicit entry in this table for a particular entPhysicalIndex/entAliasMappingIdentifier pair.

For example, to indicate that a particular interface (e.g., physical component 33) is identified by the same value of ifIndex for all logical entities, the following instance might exist:

```
entAliasMappingIdentifier.33.0 = ifIndex.5
```

In the event an entPhysicalEntry is associated differently for some logical entities, additional entAliasMapping entries may exist, e.g.:

```
entAliasMappingIdentifier.33.0 = ifIndex.6
entAliasMappingIdentifier.33.4 = ifIndex.1
entAliasMappingIdentifier.33.5 = ifIndex.1
entAliasMappingIdentifier.33.10 = ifIndex.12
```

Note that entries with non-zero entAliasLogicalIndexOrZero index values have precedence over zero-indexed entries. In this example, all logical entities except 4, 5, and 10 associate physical entity 33 with ifIndex.6."

```
::= { entAliasMappingEntry 1 }
```

#### entAliasMappingIdentifier OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"The value of this object identifies a particular conceptual row associated with the indicated entPhysicalIndex and entLogicalIndex pair.

Because only physical ports are modeled in this table, only entries that represent interfaces or ports are allowed. If an ifEntry exists on behalf of a particular physical port, then this object should identify the associated ifEntry. For repeater ports, the appropriate row in the 'rpPtrPortGroupTable' should be identified instead.

For example, suppose a physical port was represented by entPhysicalEntry.3, entLogicalEntry.15 existed for a repeater, and entLogicalEntry.22 existed for a bridge. Then there might be two related instances of entAliasMappingIdentifier:

```
entAliasMappingIdentifier.3.15 == rpPtrPortGroupIndex.5.2
entAliasMappingIdentifier.3.22 == ifIndex.17
```

It is possible that other mappings (besides interfaces and repeater ports) may be defined in the future, as required.

Bridge ports are identified by examining the Bridge MIB and appropriate ifEntries associated with each 'dotldBasePort' and are thus not represented in this table."

```
::= { entAliasMappingEntry 2 }
```

```
-- physical mapping table
```

```
entPhysicalContainsTable OBJECT-TYPE
```

```
    SYNTAX      SEQUENCE OF EntPhysicalContainsEntry
```

```
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
```

```
    DESCRIPTION
```

"A table that exposes the container/'containeer' relationships between physical entities. This table provides all the information found by constructing the virtual containment tree for a given entPhysicalTable, but in a more direct format.

In the event a physical entity is contained by more than one other physical entity (e.g., double-wide modules), this table should include these additional mappings, which cannot be represented in the entPhysicalTable virtual containment tree."

```
::= { entityMapping 3 }
```

```
entPhysicalContainsEntry OBJECT-TYPE
```

```
    SYNTAX      EntPhysicalContainsEntry
```

```
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
```

```
    DESCRIPTION
```

"A single container/'containeer' relationship."

```
    INDEX      { entPhysicalIndex, entPhysicalChildIndex }
```

```
::= { entPhysicalContainsTable 1 }
```

```
EntPhysicalContainsEntry ::= SEQUENCE {
    entPhysicalChildIndex  PhysicalIndex
}
```

```
entPhysicalChildIndex OBJECT-TYPE
```

```
    SYNTAX      PhysicalIndex
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

"The value of entPhysicalIndex for the contained physical entity."



```
 ::= { entPhysicalContainsEntry 1 }

-- last change time stamp for the whole MIB
entLastChangeTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime at the time a conceptual row is
        created, modified, or deleted in any of these tables:
        - entPhysicalTable
        - entLogicalTable
        - entLPMappingTable
        - entAliasMappingTable
        - entPhysicalContainsTable
        "
 ::= { entityGeneral 1 }

-- Entity MIB Trap Definitions
entityMIBTraps          OBJECT IDENTIFIER ::= { entityMIB 2 }
entityMIBTrapPrefix     OBJECT IDENTIFIER ::= { entityMIBTraps 0 }

entConfigChange NOTIFICATION-TYPE
    STATUS      current
    DESCRIPTION
        "An entConfigChange notification is generated when the value
        of entLastChangeTime changes. It can be utilized by an NMS
        to trigger logical/physical entity table maintenance polls.

        An agent should not generate more than one entConfigChange
        'notification-event' in a given time interval (five seconds
        is the suggested default). A 'notification-event' is the
        transmission of a single trap or inform PDU to a list of
        notification destinations.

        If additional configuration changes occur within the
        throttling period, then notification-events for these
        changes should be suppressed by the agent until the current
        throttling period expires. At the end of a throttling
        period, one notification-event should be generated if any
        configuration changes occurred since the start of the
        throttling period. In such a case, another throttling
        period is started right away."
```

```

        An NMS should periodically check the value of
        entLastChangeTime to detect any missed entConfigChange
        notification-events, e.g., due to throttling or transmission
        loss."
 ::= { entityMIBTrapPrefix 1 }

-- conformance information
entityConformance OBJECT IDENTIFIER ::= { entityMIB 3 }

entityCompliances OBJECT IDENTIFIER ::= { entityConformance 1 }
entityGroups      OBJECT IDENTIFIER ::= { entityConformance 2 }

-- compliance statements
entityCompliance MODULE-COMPLIANCE
    STATUS deprecated
    DESCRIPTION
        "The compliance statement for SNMP entities that implement
        version 1 of the Entity MIB."
    MODULE -- this module
        MANDATORY-GROUPS {
            entityPhysicalGroup,
            entityLogicalGroup,
            entityMappingGroup,
            entityGeneralGroup,
            entityNotificationsGroup
        }
    ::= { entityCompliances 1 }

entity2Compliance MODULE-COMPLIANCE
    STATUS deprecated
    DESCRIPTION
        "The compliance statement for SNMP entities that implement
        version 2 of the Entity MIB."
    MODULE -- this module
        MANDATORY-GROUPS {
            entityPhysicalGroup,
            entityPhysical2Group,
            entityGeneralGroup,
            entityNotificationsGroup
        }
        GROUP entityLogical2Group
    DESCRIPTION
        "Implementation of this group is not mandatory for agents
        that model all MIB object instances within a single naming
        scope."
```

## GROUP entityMappingGroup

## DESCRIPTION

"Implementation of the entPhysicalContainsTable is mandatory for all agents. Implementation of the entLPMappingTable and entAliasMappingTables are not mandatory for agents that model all MIB object instances within a single naming scope.

Note that the entAliasMappingTable may be useful for all agents; however, implementation of the entityLogicalGroup or entityLogical2Group is required to support this table."

## OBJECT entPhysicalSerialNum

MIN-ACCESS not-accessible

## DESCRIPTION

"Read and write access is not required for agents that cannot identify serial number information for physical entities and/or cannot provide non-volatile storage for NMS-assigned serial numbers.

Write access is not required for agents that can identify serial number information for physical entities but cannot provide non-volatile storage for NMS-assigned serial numbers.

Write access is not required for physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)'."

## OBJECT entPhysicalAlias

MIN-ACCESS read-only

## DESCRIPTION

"Write access is required only if the associated entPhysicalClass value is equal to 'chassis(3)'."

## OBJECT entPhysicalAssetID

MIN-ACCESS not-accessible

## DESCRIPTION

"Read and write access is not required for agents that cannot provide non-volatile storage for NMS-assigned asset identifiers.

Write access is not required for physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)'."

## OBJECT entPhysicalClass

SYNTAX INTEGER {  
    other(1),

```
        unknown(2),
        chassis(3),
        backplane(4),
        container(5),
        powerSupply(6),
        fan(7),
        sensor(8),
        module(9),
        port(10),
        stack(11)
    }
    DESCRIPTION
        "Implementation of the 'cpu(12)' enumeration is not
        required."
    ::= { entityCompliances 2 }

entity3Compliance MODULE-COMPLIANCE
    STATUS deprecated
    DESCRIPTION
        "The compliance statement for SNMP entities that implement
        version 3 of the Entity MIB."
    MODULE -- this module
        MANDATORY-GROUPS {
            entityPhysicalGroup,
            entityPhysical2Group,
            entityPhysical3Group,
            entityGeneralGroup,
            entityNotificationsGroup
        }
        GROUP entityLogical2Group
        DESCRIPTION
            "Implementation of this group is not mandatory for agents
            that model all MIB object instances within a single naming
            scope."

        GROUP entityMappingGroup
        DESCRIPTION
            "Implementation of the entPhysicalContainsTable is mandatory
            for all agents. Implementation of the entLPMappingTable and
            entAliasMappingTables are not mandatory for agents that
            model all MIB object instances within a single naming scope.

            Note that the entAliasMappingTable may be useful for all
            agents; however, implementation of the entityLogicalGroup or
            entityLogical2Group is required to support this table."

        OBJECT entPhysicalSerialNum
        MIN-ACCESS not-accessible
```

## DESCRIPTION

"Read and write access is not required for agents that cannot identify serial number information for physical entities and/or cannot provide non-volatile storage for NMS-assigned serial numbers.

Write access is not required for agents that can identify serial number information for physical entities but cannot provide non-volatile storage for NMS-assigned serial numbers.

Write access is not required for physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)'."

OBJECT entPhysicalAlias

MIN-ACCESS read-only

## DESCRIPTION

"Write access is required only if the associated entPhysicalClass value is equal to 'chassis(3)'."

OBJECT entPhysicalAssetID

MIN-ACCESS not-accessible

## DESCRIPTION

"Read and write access is not required for agents that cannot provide non-volatile storage for NMS-assigned asset identifiers.

Write access is not required for physical entities for which the associated value of entPhysicalIsFRU is equal to 'false(2)'."

```
::= { entityCompliances 3 }
```

entity4Compliance MODULE-COMPLIANCE

STATUS current

## DESCRIPTION

"The compliance statement for SNMP entities that implement the full version 4 (full compliance) of the Entity MIB."

MODULE -- this module

MANDATORY-GROUPS {

```
    entityPhysicalGroup,  
    entityPhysical2Group,  
    entityPhysical3Group,  
    entityGeneralGroup,  
    entityNotificationsGroup,  
    entityPhysical4Group
```

}

GROUP entityLogical2Group

## DESCRIPTION

"Implementation of this group is not mandatory for agents that model all MIB object instances within a single naming scope."

## GROUP entityMappingGroup

## DESCRIPTION

"Implementation of the entPhysicalContainsTable is mandatory for all agents. Implementation of the entLPMappingTable and entAliasMappingTables are not mandatory for agents that model all MIB object instances within a single naming scope."

Note that the entAliasMappingTable may be useful for all agents; however, implementation of the entityLogicalGroup or entityLogical2Group is required to support this table."

## OBJECT entPhysicalSerialNum

MIN-ACCESS not-accessible

## DESCRIPTION

"Read and write access is not required for agents that cannot identify serial number information for physical entities and/or cannot provide non-volatile storage for NMS-assigned serial numbers."

Write access is not required for agents that can identify serial number information for physical entities but cannot provide non-volatile storage for NMS-assigned serial numbers."

Write access is not required for physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)'."

## OBJECT entPhysicalAlias

MIN-ACCESS read-only

## DESCRIPTION

"Write access is required only if the associated entPhysicalClass value is equal to 'chassis(3)'."

## OBJECT entPhysicalAssetID

MIN-ACCESS not-accessible

## DESCRIPTION

"Read and write access is not required for agents that cannot provide non-volatile storage for NMS-assigned asset identifiers."

```
        Write access is not required for physical entities for which
        the associated value of entPhysicalIsFRU is equal to
        'false(2)'.
    ::= { entityCompliances 4 }

entity4CRCompliance MODULE-COMPLIANCE
    STATUS    current
    DESCRIPTION
        "The compliance statement for SNMP entities that implement
        version 4 of the Entity MIB on devices with constrained
        resources."
    MODULE -- this module
        MANDATORY-GROUPS {
            entityPhysicalCRGroup,
            entityPhysical4Group
        }
    ::= { entityCompliances 5 }

-- MIB groupings
entityPhysicalGroup    OBJECT-GROUP
    OBJECTS {
        entPhysicalDescr,
        entPhysicalVendorType,
        entPhysicalContainedIn,
        entPhysicalClass,
        entPhysicalParentRelPos,
        entPhysicalName
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects used to represent physical
        system components for which a single agent provides
        management information."
    ::= { entityGroups 1 }

entityLogicalGroup    OBJECT-GROUP
    OBJECTS {
        entLogicalDescr,
        entLogicalType,
        entLogicalCommunity,
        entLogicalTAddress,
        entLogicalTDomain
    }
    STATUS    deprecated
```

## DESCRIPTION

"The collection of objects used to represent the list of logical entities for which a single agent provides management information."

::= { entityGroups 2 }

entityMappingGroup OBJECT-GROUP

OBJECTS {  
    entLPPPhysicalIndex,  
    entAliasMappingIdentifier,  
    entPhysicalChildIndex  
}

STATUS current

## DESCRIPTION

"The collection of objects used to represent the associations between multiple logical entities, physical components, interfaces, and port identifiers for which a single agent provides management information."

::= { entityGroups 3 }

entityGeneralGroup OBJECT-GROUP

OBJECTS {  
    entLastChangeTime  
}

STATUS current

## DESCRIPTION

"The collection of objects used to represent general entity information for which a single agent provides management information."

::= { entityGroups 4 }

entityNotificationsGroup NOTIFICATION-GROUP

NOTIFICATIONS { entConfigChange }

STATUS current

## DESCRIPTION

"The collection of notifications used to indicate Entity MIB data consistency and general status information."

::= { entityGroups 5 }

entityPhysical2Group OBJECT-GROUP

OBJECTS {  
    entPhysicalHardwareRev,  
    entPhysicalFirmwareRev,  
    entPhysicalSoftwareRev,  
    entPhysicalSerialNum,  
    entPhysicalMfgName,  
    entPhysicalModelName,  
    entPhysicalAlias,  
}



```
        entPhysicalAssetID,
        entPhysicalIsFRU
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects used to represent physical
        system components for which a single agent provides
        management information.  This group augments the objects
        contained in the entityPhysicalGroup."
    ::= { entityGroups 6 }

entityLogical2Group    OBJECT-GROUP
    OBJECTS {
        entLogicalDescr,
        entLogicalType,
        entLogicalTAddress,
        entLogicalTDomain,
        entLogicalContextEngineID,
        entLogicalContextName
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects used to represent the
        list of logical entities for which a single SNMP entity
        provides management information."
    ::= { entityGroups 7 }

entityPhysical3Group    OBJECT-GROUP
    OBJECTS {
        entPhysicalMfgDate,
        entPhysicalUris
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects used to represent physical
        system components for which a single agent provides
        management information.  This group augments the objects
        contained in the entityPhysicalGroup."
    ::= { entityGroups 8 }

entityPhysical4Group    OBJECT-GROUP
    OBJECTS {
        entPhysicalUUID
    }
    STATUS    current
```

## DESCRIPTION

"The collection of objects used to represent physical system components for which a single agent provides management information. This group augments the objects contained in the entityPhysicalGroup and entityPhysicalCRGroup."

::= { entityGroups 9 }

entityPhysicalCRGroup OBJECT-GROUP

OBJECTS {  
    entPhysicalClass,  
    entPhysicalName  
}

STATUS current

## DESCRIPTION

"The collection of objects used to represent physical system components for constrained resourced devices, for which a single agent provides management information."

::= { entityGroups 10 }

END

### 3.2. IANA-ENTITY-MIB

IANA-ENTITY-MIB DEFINITIONS ::= BEGIN

## IMPORTS

MODULE-IDENTITY, mib-2  
    FROM SNMPv2-SMI                   -- RFC 2578  
TEXTUAL-CONVENTION  
    FROM SNMPv2-TC                   -- RFC 2579  
;

ianaEntityMIB MODULE-IDENTITY

    LAST-UPDATED "201304050000Z"   -- April 5, 2013

    ORGANIZATION "IANA"

    CONTACT-INFO

        "Internet Assigned Numbers Authority  
        Postal: ICANN  
            12025 Waterfront Drive, Suite 300  
            Los Angeles, CA 90094-2536

        Phone: +1-310-301-5800

        EMail: iana@iana.org"

## DESCRIPTION

"This MIB module defines a TEXTUAL-CONVENTION that provides an indication of the general hardware type of a particular physical entity.

Copyright (c) 2013 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

The initial version of this MIB module was published in [RFC 6933](#); for full legal notices see the RFC itself."

REVISION "201304050000Z" -- April 5, 2013

DESCRIPTION "Initial version of this MIB as published in [RFC 6933](#)."

::= { mib-2 216 }

-- Textual Conventions

IANAPhysicalClass ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An enumerated value that provides an indication of the general hardware type of a particular physical entity. There are no restrictions as to the number of entPhysicalEntries of each entPhysicalClass, which must be instantiated by an agent.

The enumeration 'other' is applicable if the physical entity class is known but does not match any of the supported values.

The enumeration 'unknown' is applicable if the physical entity class is unknown to the agent.

The enumeration 'chassis' is applicable if the physical entity class is an overall container for networking equipment. Any class of physical entity, except a stack, may be contained within a chassis; a chassis may only be contained within a stack.

The enumeration 'backplane' is applicable if the physical entity class is some sort of device for aggregating and forwarding networking traffic, such as a shared backplane in a modular ethernet switch. Note that an agent may model a backplane as a single physical entity, which is actually implemented as multiple discrete physical components (within a chassis or stack).

The enumeration 'container' is applicable if the physical entity class is capable of containing one or more removable physical entities, possibly of different types. For example, each (empty or full) slot in a chassis will be modeled as a container. Note that all removable physical entities should be modeled within a container entity, such as field-replaceable modules, fans, or power supplies. Note that all known containers should be modeled by the agent, including empty containers.

The enumeration 'powerSupply' is applicable if the physical entity class is a power-supplying component.

The enumeration 'fan' is applicable if the physical entity class is a fan or other heat-reduction component.

The enumeration 'sensor' is applicable if the physical entity class is some sort of sensor, such as a temperature sensor within a router chassis.

The enumeration 'module' is applicable if the physical entity class is some sort of self-contained sub-system. If the enumeration 'module' is removable, then it should be modeled within a container entity; otherwise, it should be modeled directly within another physical entity (e.g., a chassis or another module).

The enumeration 'port' is applicable if the physical entity class is some sort of networking port, capable of receiving and/or transmitting networking traffic.

The enumeration 'stack' is applicable if the physical entity class is some sort of super-container (possibly virtual) intended to group together multiple chassis entities. A stack may be realized by a 'virtual' cable, a real interconnect cable attached to multiple chassis, or multiple interconnect cables. A stack should not be

modeled within any other physical entities, but a stack may be contained within another stack. Only chassis entities should be contained within a stack.

The enumeration 'cpu' is applicable if the physical entity class is some sort of central processing unit.

The enumeration 'energyObject' is applicable if the physical entity is some sort of energy object, i.e., a piece of equipment that is part of or attached to a communications network that is monitored, controlled, or aids in the management of another device for Energy Management.

The enumeration 'battery' is applicable if the physical entity class is some sort of battery."

```
SYNTAX      INTEGER  {
    other(1),
    unknown(2),
    chassis(3),
    backplane(4),
    container(5), -- e.g., chassis slot or daughter-card holder
    powerSupply(6),
    fan(7),
    sensor(8),
    module(9),      -- e.g., plug-in card or daughter-card
    port(10),
    stack(11),      -- e.g., stack of multiple chassis entities
    cpu(12),
    energyObject(13),
    battery (14)
}

END
```

### 3.3. UUID-TC-MIB

```
UUID-TC-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
    MODULE-IDENTITY, mib-2
        FROM SNMPv2-SMI                -- RFC 2578
    TEXTUAL-CONVENTION
        FROM SNMPv2-TC                -- RFC 2579
    ;
```

```
uuidTCMIB MODULE-IDENTITY
```

LAST-UPDATED "201304050000Z" -- April 5, 2013  
ORGANIZATION "IETF Energy Management Working Group"  
CONTACT-INFO "WG Email: eman@ietf.org  
Mailing list subscription info:  
<http://www.ietf.org/mailman/listinfo/eman>

Dan Romascanu  
Avaya  
Park Atidim, Bldg. #3  
Tel Aviv, 61581  
Israel  
Phone: +972-3-6458414  
Email: dromasca@avaya.com

Juergen Quittek  
NEC Europe Ltd.  
Network Research Division  
Kurfuersten-Anlage 36  
Heidelberg 69115  
Germany  
Phone: +49 6221 4342-115  
Email: quittek@neclab.eu

Mouli Chandramouli  
Cisco Systems, Inc.  
Sarjapur Outer Ring Road  
Bangalore 560103  
India  
Phone: +91 80 4429 2409  
Email: moulchan@cisco.com"

#### DESCRIPTION

"This MIB module defines TEXTUAL-CONVENTIONS representing Universally Unique IDentifiers (UUIDs).

Copyright (c) 2013 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

```
REVISION      "201304050000Z"  -- April 5, 2013
DESCRIPTION   "Initial version of this MIB as published in
               RFC 6933."
```

```
::= { mib-2 217 }
```

```
-- Textual Conventions
```

```
UUID ::= TEXTUAL-CONVENTION
  DISPLAY-HINT  "4x-2x-2x-1x1x-6x"
  STATUS       current
  DESCRIPTION   "Universally Unique Identifier information.  The syntax must
               conform to RFC 4122, Section 4.1."

  SYNTAX       OCTET STRING (SIZE (16))
```

```
UUIDorZero ::= TEXTUAL-CONVENTION
  DISPLAY-HINT  "4x-2x-2x-1x1x-6x"
  STATUS       current
  DESCRIPTION   "Universally Unique Identifier information.  The syntax must
               conform to RFC 4122, Section 4.1."
```

The semantics of the value zero-length OCTET STRING are object-specific and must therefore be defined as part of the description of any object that uses this syntax."

```
SYNTAX       OCTET STRING (SIZE (0|16))
```

```
END
```

## 4. Usage Examples

The following sections iterate the instance values for two example networking devices. These examples are kept simple to make them more understandable. Auxiliary components such as fans, sensors, empty slots, and sub-modules are not shown but might be modeled in real implementations.

### 4.1. Router/Bridge

The first example is a router containing two slots. Each slot contains a 3-port router/bridge module. Each port is represented in the ifTable. There are two logical instances of OSPF running and two logical bridges:

```

Physical entities -- entPhysicalTable:
1 Field-replaceable physical chassis:
  entPhysicalDescr.1 ==          'Acme Chassis Model 100'
  entPhysicalVendorType.1 ==     acmeProducts.chassisTypes.1
  entPhysicalContainedIn.1 ==     0
  entPhysicalClass.1 ==          chassis(3)
  entPhysicalParentRelPos.1 ==   0
  entPhysicalName.1 ==           '100-A'
  entPhysicalHardwareRev.1 ==    'A(1.00.02)'
  entPhysicalSoftwareRev.1 ==    ''
  entPhysicalFirmwareRev.1 ==    ''
  entPhysicalSerialNum.1 ==      'C100076544'
  entPhysicalMfgName.1 ==        'Acme'
  entPhysicalModelName.1 ==      '100'
  entPhysicalAlias.1 ==          'cl-SJ17-3-006:rack1:rtr-U3'
  entPhysicalAssetID.1 ==        '0007372293'
  entPhysicalIsFRU.1 ==          true(1)
  entPhysicalMfgDate.1 ==        '2002-5-26,13:30:30.0,-4:0'
  entPhysicalUris.1 ==           'URN:CLEI:CNME120ARA'

2 slots within the chassis:
  entPhysicalDescr.2 ==          'Acme Chassis Slot Type AA'
  entPhysicalVendorType.2 ==     acmeProducts.slotTypes.1
  entPhysicalContainedIn.2 ==     1
  entPhysicalClass.2 ==          container(5)
  entPhysicalParentRelPos.2 ==   1
  entPhysicalName.2 ==           'S1'
  entPhysicalHardwareRev.2 ==    'B(1.00.01)'
  entPhysicalSoftwareRev.2 ==    ''
  entPhysicalFirmwareRev.2 ==    ''
  entPhysicalSerialNum.2 ==      ''
  entPhysicalMfgName.2 ==        'Acme'
  entPhysicalModelName.2 ==      'AA'
  entPhysicalAlias.2 ==          ''
  entPhysicalAssetID.2 ==        ''
  entPhysicalIsFRU.2 ==          false(2)
  entPhysicalMfgDate.2 ==        '2002-7-26,12:22:12.0,-4:0'
  entPhysicalUris.2 ==           'URN:CLEI:CNME123ARA'

  entPhysicalDescr.3 ==          'Acme Chassis Slot Type AA'
  entPhysicalVendorType.3 ==     acmeProducts.slotTypes.1
  entPhysicalContainedIn.3 ==     1
  entPhysicalClass.3 ==          container(5)
  entPhysicalParentRelPos.3 ==   2
  entPhysicalName.3 ==           'S2'
  entPhysicalHardwareRev.3 ==    '1.00.07'
  entPhysicalSoftwareRev.3 ==    ''
  entPhysicalFirmwareRev.3 ==    ''
  entPhysicalSerialNum.3 ==      ''

```



```

entPhysicalMfgName.3 ==      'Acme'
entPhysicalModelName.3 ==    'AA'
entPhysicalAlias.3 ==        ''
entPhysicalAssetID.3 ==      ''
entPhysicalIsFRU.3 ==        false(2)
entPhysicalMfgDate.3 ==      '2002-7-26,12:12:12.0,-4:0'
entPhysicalUris.3 ==         'URN:CLEI:CNME123ARA'

```

## 2 Field-replaceable modules:

Slot 1 contains a module with 3 ports:

```

entPhysicalDescr.4 ==      'Acme Router-100'
entPhysicalVendorType.4 ==  acmeProducts.moduleTypes.14
entPhysicalContainedIn.4 == 2
entPhysicalClass.4 ==      module(9)
entPhysicalParentRelPos.4 == 1
entPhysicalName.4 ==        'M1'
entPhysicalHardwareRev.4 ==  '1.00.07'
entPhysicalSoftwareRev.4 ==  '1.4.1'
entPhysicalFirmwareRev.4 ==  'A(1.1)'
entPhysicalSerialNum.4 ==    'C100087363'
entPhysicalMfgName.4 ==      'Acme'
entPhysicalModelName.4 ==    'R100-FE'
entPhysicalAlias.4 ==        'rtr-U3:ml:SJ17-3-eng'
entPhysicalAssetID.4 ==      '0007372462'
entPhysicalIsFRU.4 ==        true(1)
entPhysicalMfgDate.4 ==      '2003-7-18,13:30:30.0,-4:0'
entPhysicalUris.4 ==         'URN:CLEI:CNRU123CAA'

```

```

entPhysicalDescr.5 ==      'Acme Ethernet-100 Port'
entPhysicalVendorType.5 ==  acmeProducts.portTypes.2
entPhysicalContainedIn.5 ==  4
entPhysicalClass.5 ==      port(10)
entPhysicalParentRelPos.5 == 1
entPhysicalName.5 ==        'P1'
entPhysicalHardwareRev.5 ==  'G(1.02)'
entPhysicalSoftwareRev.5 ==  ''
entPhysicalFirmwareRev.5 ==  '1.1'
entPhysicalSerialNum.5 ==    ''
entPhysicalMfgName.5 ==      'Acme'
entPhysicalModelName.5 ==    'FE-100'
entPhysicalAlias.5 ==        ''
entPhysicalAssetID.5 ==      ''
entPhysicalIsFRU.5 ==        false(2)
entPhysicalMfgDate.5 ==      '2003-7-18,14:20:22.0,-4:0'
entPhysicalUris.5 ==         'URN:CLEI:CNMES23ARA'

```

```

entPhysicalDescr.6 ==      'Acme Ethernet-100 Port'
entPhysicalVendorType.6 ==  acmeProducts.portTypes.2

```

```

entPhysicalContainedIn.6 ==      4
entPhysicalClass.6 ==          port(10)
entPhysicalParentRelPos.6 ==    2
entPhysicalName.6 ==            'P2'
entPhysicalHardwareRev.6 ==     'G(1.02)'
entPhysicalSoftwareRev.6 ==     ''
entPhysicalFirmwareRev.6 ==     '1.1'
entPhysicalSerialNum.6 ==       ''
entPhysicalMfgName.6 ==         'Acme'
entPhysicalModelName.6 ==       'FE-100'
entPhysicalAlias.6 ==           ''
entPhysicalAssetID.6 ==         ''
entPhysicalIsFRU.6 ==           false(2)
entPhysicalMfgDate.6 ==         '2003-7-19,10:15:15.0,-4:0'
entPhysicalUris.6 ==            'URN:CLEI:CNMES23ARA'

```

```

entPhysicalDescr.7 ==           'Acme Router-100 FDDI-Port'
entPhysicalVendorType.7 ==      acmeProducts.portTypes.3
entPhysicalContainedIn.7 ==      4
entPhysicalClass.7 ==           port(10)
entPhysicalParentRelPos.7 ==    3
entPhysicalName.7 ==            'P3'
entPhysicalHardwareRev.7 ==     'B(1.03)'
entPhysicalSoftwareRev.7 ==     '2.5.1'
entPhysicalFirmwareRev.7 ==     '2.5F'
entPhysicalSerialNum.7 ==       ''
entPhysicalMfgName.7 ==         'Acme'
entPhysicalModelName.7 ==       'FDDI-100'
entPhysicalAlias.7 ==           ''
entPhysicalAssetID.7 ==         ''
entPhysicalIsFRU.7 ==           false(2)

```

Slot 2 contains another 3-port module:

```

entPhysicalDescr.8 ==           'Acme Router-100 Comm Module'
entPhysicalVendorType.8 ==      acmeProducts.moduleTypes.15
entPhysicalContainedIn.8 ==      3
entPhysicalClass.8 ==           module(9)
entPhysicalParentRelPos.8 ==    1
entPhysicalName.8 ==            'M2'
entPhysicalHardwareRev.8 ==     '2.01.00'
entPhysicalSoftwareRev.8 ==     '3.0.7'
entPhysicalFirmwareRev.8 ==     'A(1.2)'
entPhysicalSerialNum.8 ==       'C100098732'
entPhysicalMfgName.8 ==         'Acme'
entPhysicalModelName.8 ==       'C100'
entPhysicalAlias.8 ==           'rtr-U3:m2:SJ17-2-eng'
entPhysicalAssetID.8 ==         '0007373982'
entPhysicalIsFRU.8 ==           true(1)

```

```

entPhysicalMfgDate.8 ==      '2002-5-26,13:30:15.0,-4:0'
entPhysicalUris.8 ==        'URN:CLEI:CNRT321MAA'

entPhysicalDescr.9 ==       'Acme Fddi-100 Port'
entPhysicalVendorType.9 ==  acmeProducts.portTypes.5
entPhysicalContainedIn.9 ==  8
entPhysicalClass.9 ==       port(10)
entPhysicalParentRelPos.9 == 1
entPhysicalName.9 ==        'FDDI Primary'
entPhysicalHardwareRev.9 ==  'CC(1.07)'
entPhysicalSoftwareRev.9 ==  '2.0.34'
entPhysicalFirmwareRev.9 == '1.1'
entPhysicalSerialNum.9 ==    ''
entPhysicalMfgName.9 ==      'Acme'
entPhysicalModelName.9 ==    'FDDI-100'
entPhysicalAlias.9 ==        ''
entPhysicalAssetID.9 ==      ''
entPhysicalIsFRU.9 ==        false(2)

entPhysicalDescr.10 ==      'Acme Ethernet-100 Port'
entPhysicalVendorType.10 == acmeProducts.portTypes.2
entPhysicalContainedIn.10 == 8
entPhysicalClass.10 ==      port(10)
entPhysicalParentRelPos.10 == 2
entPhysicalName.10 ==       'Ethernet A'
entPhysicalHardwareRev.10 == 'G(1.04)'
entPhysicalSoftwareRev.10 == ''
entPhysicalFirmwareRev.10 == '1.3'
entPhysicalSerialNum.10 ==   ''
entPhysicalMfgName.10 ==     'Acme'
entPhysicalModelName.10 ==   'FE-100'
entPhysicalAlias.10 ==       ''
entPhysicalAssetID.10 ==     ''
entPhysicalIsFRU.10 ==       false(2)
entPhysicalMfgDate.10 ==     '2002-7-26,13:30:15.0,-4:0'
entPhysicalUris.10 ==        'URN:CLEI:CNMES23ARA'

entPhysicalDescr.11 ==      'Acme Ethernet-100 Port'
entPhysicalVendorType.11 == acmeProducts.portTypes.2
entPhysicalContainedIn.11 == 8
entPhysicalClass.11 ==      port(10)
entPhysicalParentRelPos.11 == 3
entPhysicalName.11 ==       'Ethernet B'
entPhysicalHardwareRev.11 == 'G(1.04)'
entPhysicalSoftwareRev.11 == ''
entPhysicalFirmwareRev.11 == '1.3'
entPhysicalSerialNum.11 ==   ''
entPhysicalMfgName.11 ==     'Acme'

```

```

entPhysicalModelName.11 ==      'FE-100'
entPhysicalAlias.11 ==          ''
entPhysicalAssetID.11 ==        ''
entPhysicalIsFRU.11 ==          false(2)
entPhysicalMfgDate.11 ==        '2002-8-16,15:35:15.0,-4:0'
entPhysicalUris.11 ==           'URN:CLEI:CNMES23ARA'

```

Logical entities -- entLogicalTable; no SNMPv3 support

2 OSPF instances:

```

entLogicalDescr.1 ==            'Acme OSPF v1.1'
entLogicalType.1 ==             ospf
entLogicalCommunity.1 ==        'public-ospf1'
entLogicalTAddress.1 ==         192.0.2.1:161
entLogicalTDomain.1 ==          snmpUDPDomain
entLogicalContextEngineID.1 ==  ''
entLogicalContextName.1 ==      ''

```

```

entLogicalDescr.2 ==            'Acme OSPF v1.1'
entLogicalType.2 ==             ospf
entLogicalCommunity.2 ==        'public-ospf2'
entLogicalTAddress.2 ==         192.0.2.1:161
entLogicalTDomain.2 ==          snmpUDPDomain
entLogicalContextEngineID.2 ==  ''
entLogicalContextName.2 ==      ''

```

2 logical bridges:

```

entLogicalDescr.3 ==            'Acme Bridge v2.1.1'
entLogicalType.3 ==             dot1dBridge
entLogicalCommunity.3 ==        'public-bridge1'
entLogicalTAddress.3 ==         192.0.2.1:161
entLogicalTDomain.3 ==          snmpUDPDomain
entLogicalContextEngineID.3 ==  ''
entLogicalContextName.3 ==      ''

```

```

entLogicalDescr.4 ==            'Acme Bridge v2.1.1'
entLogicalType.4 ==             dot1dBridge
entLogicalCommunity.4 ==        'public-bridge2'
entLogicalTAddress.4 ==         192.0.2.1:161
entLogicalTDomain.4 ==          snmpUDPDomain
entLogicalContextEngineID.4 ==  ''
entLogicalContextName.4 ==      ''

```

Logical to Physical Mappings:

```

1st OSPF instance: uses module 1-port 1
entLPPPhysicalIndex.1.5 ==      5

```

2nd OSPF instance: uses module 2-port 1  
 entLPPPhysicalIndex.2.9 == 9

1st bridge group: uses module 1, all ports

Note that these mappings are included in the table because another logical entity (1st OSPF) utilizes one of the ports. If this were not the case, then a single mapping to the module (e.g., entLPPPhysicalIndex.3.4) would be present instead.

entLPPPhysicalIndex.3.5 == 5  
 entLPPPhysicalIndex.3.6 == 6  
 entLPPPhysicalIndex.3.7 == 7

2nd bridge group: uses module 2, all ports  
 entLPPPhysicalIndex.4.9 == 9  
 entLPPPhysicalIndex.4.10 == 10  
 entLPPPhysicalIndex.4.11 == 11

Physical to Logical to MIB Alias Mappings -- entAliasMappingTable:

Example 1: ifIndex values are global to all logical entities

entAliasMappingIdentifier.5.0 == ifIndex.1  
 entAliasMappingIdentifier.6.0 == ifIndex.2  
 entAliasMappingIdentifier.7.0 == ifIndex.3  
 entAliasMappingIdentifier.9.0 == ifIndex.4  
 entAliasMappingIdentifier.10.0 == ifIndex.5  
 entAliasMappingIdentifier.11.0 == ifIndex.6

Example 2: ifIndex values are not shared by all logical entities;  
 (Bridge-1 uses ifIndex values 101 - 103 and Bridge-2 uses  
 ifIndex values 204-206.)

entAliasMappingIdentifier.5.0 == ifIndex.1  
 entAliasMappingIdentifier.5.3 == ifIndex.101  
 entAliasMappingIdentifier.6.0 == ifIndex.2  
 entAliasMappingIdentifier.6.3 == ifIndex.102  
 entAliasMappingIdentifier.7.0 == ifIndex.3  
 entAliasMappingIdentifier.7.3 == ifIndex.103  
 entAliasMappingIdentifier.9.0 == ifIndex.4  
 entAliasMappingIdentifier.9.4 == ifIndex.204  
 entAliasMappingIdentifier.10.0 == ifIndex.5  
 entAliasMappingIdentifier.10.4 == ifIndex.205  
 entAliasMappingIdentifier.11.0 == ifIndex.6  
 entAliasMappingIdentifier.11.4 == ifIndex.206

## Physical Containment Tree -- entPhysicalContainsTable

chassis has two containers:

```
entPhysicalChildIndex.1.2 == 2
entPhysicalChildIndex.1.3 == 3
```

container 1 has a module:

```
entPhysicalChildIndex.2.4 == 4
```

container 2 has a module:

```
entPhysicalChildIndex.3.8 == 8
```

module 1 has 3 ports:

```
entPhysicalChildIndex.4.5 == 5
entPhysicalChildIndex.4.6 == 6
entPhysicalChildIndex.4.7 == 7
```

module 2 has 3 ports:

```
entPhysicalChildIndex.8.9 == 9
entPhysicalChildIndex.8.10 == 10
entPhysicalChildIndex.8.11 == 11
```

## 4.2. Repeaters

The second example is a 3-slot hub with 2 backplane ethernet segments. Slot three is empty, and the remaining slots contain ethernet repeater modules.

Note that this example assumes an older Repeater MIB implementation [RFC1516] rather than the new Repeater MIB [RFC2108]. The new version contains an object called 'rpPtrPortRpPtrId', which should be used to identify repeater port groupings, rather than using community strings or contexts.

## Physical entities -- entPhysicalTable:

1 Field-replaceable physical chassis:

```
entPhysicalDescr.1 == 'Acme Chassis Model 110'
entPhysicalVendorType.1 == acmeProducts.chassisTypes.2
entPhysicalContainedIn.1 == 0
entPhysicalClass.1 == chassis(3)
entPhysicalParentRelPos.1 == 0
entPhysicalName.1 == '110-B'
entPhysicalHardwareRev.1 == 'A(1.02.00)'
entPhysicalSoftwareRev.1 == ''
entPhysicalFirmwareRev.1 == ''
entPhysicalSerialNum.1 == 'C100079294'
entPhysicalMfgName.1 == 'Acme'
entPhysicalModelName.1 == '110'
entPhysicalAlias.1 == 'bldg09:floor1:rpPtr18:0067eea0229f'
```

```
entPhysicalAssetID.1 ==      '0007386327'
entPhysicalIsFRU.1 ==      true(1)

2 Chassis Ethernet Backplanes:
  entPhysicalDescr.2 ==      'Acme Ethernet Backplane Type A'
  entPhysicalVendorType.2 ==  acmeProducts.backplaneTypes.1
  entPhysicalContainedIn.2 ==  1
  entPhysicalClass.2 ==      backplane(4)
  entPhysicalParentRelPos.2 == 1
  entPhysicalName.2 ==      'B1'
  entPhysicalHardwareRev.2 == 'A(2.04.01)'
  entPhysicalSoftwareRev.2 == ''
  entPhysicalFirmwareRev.2 == ''
  entPhysicalSerialNum.2 ==  ''
  entPhysicalMfgName.2 ==    'Acme'
  entPhysicalModelName.2 ==  'BK-A'
  entPhysicalAlias.2 ==      ''
  entPhysicalAssetID.2 ==    ''
  entPhysicalIsFRU.2 ==      false(2)

  entPhysicalDescr.3 ==      'Acme Ethernet Backplane Type A'
  entPhysicalVendorType.3 ==  acmeProducts.backplaneTypes.1
  entPhysicalContainedIn.3 ==  1
  entPhysicalClass.3 ==      backplane(4)
  entPhysicalParentRelPos.3 == 2
  entPhysicalName.3 ==      'B2'
  entPhysicalHardwareRev.3 == 'A(2.04.01)'
  entPhysicalSoftwareRev.3 == ''
  entPhysicalFirmwareRev.3 == ''
  entPhysicalSerialNum.3 ==  ''
  entPhysicalMfgName.3 ==    'Acme'
  entPhysicalModelName.3 ==  'BK-A'
  entPhysicalAlias.3 ==      ''
  entPhysicalAssetID.3 ==    ''
  entPhysicalIsFRU.3 ==      false(2)

3 slots within the chassis:
  entPhysicalDescr.4 ==      'Acme Hub Slot Type RB'
  entPhysicalVendorType.4 ==  acmeProducts.slotTypes.5
  entPhysicalContainedIn.4 ==  1
  entPhysicalClass.4 ==      container(5)
  entPhysicalParentRelPos.4 == 1
  entPhysicalName.4 ==      'Slot 1'
  entPhysicalHardwareRev.4 == 'B(1.00.03)'
  entPhysicalSoftwareRev.4 == ''
  entPhysicalFirmwareRev.4 == ''
  entPhysicalSerialNum.4 ==  ''
  entPhysicalMfgName.4 ==    'Acme'
```

```

entPhysicalModelName.4 ==      'RB'
entPhysicalAlias.4 ==          ''
entPhysicalAssetID.4 ==        ''
entPhysicalIsFRU.4 ==          false(2)

entPhysicalDescr.5 ==          'Acme Hub Slot Type RB'
entPhysicalVendorType.5 ==     acmeProducts.slotTypes.5
entPhysicalContainedIn.5 ==     1
entPhysicalClass.5 ==          container(5)
entPhysicalParentRelPos.5 ==   2
entPhysicalName.5 ==           'Slot 2'
entPhysicalHardwareRev.5 ==    'B(1.00.03)'
entPhysicalSoftwareRev.5 ==    ''
entPhysicalFirmwareRev.5 ==   ''
entPhysicalSerialNum.5 ==      ''
entPhysicalMfgName.5 ==        'Acme'
entPhysicalModelName.5 ==      'RB'
entPhysicalAlias.5 ==          ''
entPhysicalAssetID.5 ==        ''
entPhysicalIsFRU.5 ==          false(2)

entPhysicalDescr.6 ==          'Acme Hub Slot Type RB'
entPhysicalVendorType.6 ==     acmeProducts.slotTypes.5
entPhysicalContainedIn.6 ==     1
entPhysicalClass.6 ==          container(5)
entPhysicalParentRelPos.6 ==   3
entPhysicalName.6 ==           'Slot 3'
entPhysicalHardwareRev.6 ==    'B(1.00.03)'
entPhysicalSoftwareRev.6 ==    ''
entPhysicalFirmwareRev.6 ==   ''
entPhysicalSerialNum.6 ==      ''
entPhysicalMfgName.6 ==        'Acme'
entPhysicalModelName.6 ==      'RB'
entPhysicalAlias.6 ==          ''
entPhysicalAssetID.6 ==        ''
entPhysicalIsFRU.6 ==          false(2)

Slot 1 contains a plug-in module with 4 10-BaseT ports:
entPhysicalDescr.7 ==          'Acme 10Base-T Module 114'
entPhysicalVendorType.7 ==     acmeProducts.moduleTypes.32
entPhysicalContainedIn.7 ==     4
entPhysicalClass.7 ==          module(9)
entPhysicalParentRelPos.7 ==   1
entPhysicalName.7 ==           'M1'
entPhysicalHardwareRev.7 ==    'A(1.02.01)'
entPhysicalSoftwareRev.7 ==    '1.7.2'
entPhysicalFirmwareRev.7 ==    'A(1.5)'
entPhysicalSerialNum.7 ==      'C100096244'

```



```
entPhysicalMfgName.7 ==      'Acme'
entPhysicalModelName.7 ==   '114'
entPhysicalAlias.7 ==       'bldg09:floor1:eng'
entPhysicalAssetID.7 ==     '0007962951'
entPhysicalIsFRU.7 ==       true(1)

entPhysicalDescr.8 ==       'Acme 10Base-T Port RB'
entPhysicalVendorType.8 ==  acmeProducts.portTypes.10
entPhysicalContainedIn.8 ==  7
entPhysicalClass.8 ==       port(10)
entPhysicalParentRelPos.8 == 1
entPhysicalName.8 ==        'Ethernet-A'
entPhysicalHardwareRev.8 ==  'A(1.04F)'
entPhysicalSoftwareRev.8 ==  ''
entPhysicalFirmwareRev.8 == '1.4'
entPhysicalSerialNum.8 ==   ''
entPhysicalMfgName.8 ==     'Acme'
entPhysicalModelName.8 ==   'RB'
entPhysicalAlias.8 ==       ''
entPhysicalAssetID.8 ==     ''
entPhysicalIsFRU.8 ==       false(2)

entPhysicalDescr.9 ==       'Acme 10Base-T Port RB'
entPhysicalVendorType.9 ==  acmeProducts.portTypes.10
entPhysicalContainedIn.9 ==  7
entPhysicalClass.9 ==       port(10)
entPhysicalParentRelPos.9 == 2
entPhysicalName.9 ==        'Ethernet-B'
entPhysicalHardwareRev.9 ==  'A(1.04F)'
entPhysicalSoftwareRev.9 ==  ''
entPhysicalFirmwareRev.9 == '1.4'
entPhysicalSerialNum.9 ==   ''
entPhysicalMfgName.9 ==     'Acme'
entPhysicalModelName.9 ==   'RB'
entPhysicalAlias.9 ==       ''
entPhysicalAssetID.9 ==     ''
entPhysicalIsFRU.9 ==       false(2)

entPhysicalDescr.10 ==      'Acme 10Base-T Port RB'
entPhysicalVendorType.10 == acmeProducts.portTypes.10
entPhysicalContainedIn.10 == 7
entPhysicalClass.10 ==      port(10)
entPhysicalParentRelPos.10 == 3
entPhysicalName.10 ==       'Ethernet-C'
entPhysicalHardwareRev.10 == 'B(1.02.07)'
entPhysicalSoftwareRev.10 == ''
entPhysicalFirmwareRev.10 == '1.4'
entPhysicalSerialNum.10 ==  ''
```

```

entPhysicalMfgName.10 ==      'Acme'
entPhysicalModelName.10 ==    'RB'
entPhysicalAlias.10 ==        ''
entPhysicalAssetID.10 ==      ''
entPhysicalIsFRU.10 ==        false(2)

entPhysicalDescr.11 ==        'Acme 10Base-T Port RB'
entPhysicalVendorType.11 ==    acmeProducts.portTypes.10
entPhysicalContainedIn.11 ==    7
entPhysicalClass.11 ==         port(10)
entPhysicalParentRelPos.11 ==  4
entPhysicalName.11 ==          'Ethernet-D'
entPhysicalHardwareRev.11 ==    'B(1.02.07)'
entPhysicalSoftwareRev.11 ==    ''
entPhysicalFirmwareRev.11 ==    '1.4'
entPhysicalSerialNum.11 ==      ''
entPhysicalMfgName.11 ==        'Acme'
entPhysicalModelName.11 ==      'RB'
entPhysicalAlias.11 ==          ''
entPhysicalAssetID.11 ==        ''
entPhysicalIsFRU.11 ==          false(2)

```

Slot 2 contains another ethernet module with 2 ports.

```

entPhysicalDescr.12 ==        'Acme 10Base-T Module Model 4'
entPhysicalVendorType.12 ==    acmeProducts.moduleTypes.30
entPhysicalContainedIn.12 ==    5
entPhysicalClass.12 ==         module(9)
entPhysicalParentRelPos.12 ==  1
entPhysicalName.12 ==          'M2'
entPhysicalHardwareRev.12 ==    'A(1.01.07)'
entPhysicalSoftwareRev.12 ==    '1.8.4'
entPhysicalFirmwareRev.12 ==    'A(1.8)'
entPhysicalSerialNum.12 ==      'C100102384'
entPhysicalMfgName.12 ==        'Acme'
entPhysicalModelName.12 ==      '4'
entPhysicalAlias.12 ==          'bldg09:floor1:devtest'
entPhysicalAssetID.12 ==        '0007968462'
entPhysicalIsFRU.12 ==          true(1)

entPhysicalDescr.13 ==        'Acme 802.3 AUI Port'
entPhysicalVendorType.13 ==    acmeProducts.portTypes.11
entPhysicalContainedIn.13 ==    12
entPhysicalClass.13 ==         port(10)
entPhysicalParentRelPos.13 ==  1
entPhysicalName.13 ==          'AUI'
entPhysicalHardwareRev.13 ==    'A(1.06F)'
entPhysicalSoftwareRev.13 ==    ''
entPhysicalFirmwareRev.13 ==    '1.5'

```

```

entPhysicalSerialNum.13 ==      ''
entPhysicalMfgName.13 ==       'Acme'
entPhysicalModelName.13 ==     ''
entPhysicalAlias.13 ==         ''
entPhysicalAssetID.13 ==       ''
entPhysicalIsFRU.13 ==         false(2)

entPhysicalDescr.14 ==         'Acme 10Base-T Port RD'
entPhysicalVendorType.14 ==    acmeProducts.portTypes.14
entPhysicalContainedIn.14 ==    12
entPhysicalClass.14 ==         port(10)
entPhysicalParentRelPos.14 ==  2
entPhysicalName.14 ==          'E2'
entPhysicalHardwareRev.14 ==   'B(1.01.02)'
entPhysicalSoftwareRev.14 ==   ''
entPhysicalFirmwareRev.14 ==   '2.1'
entPhysicalSerialNum.14 ==     ''
entPhysicalMfgName.14 ==       'Acme'
entPhysicalModelName.14 ==     ''
entPhysicalAlias.14 ==         ''
entPhysicalAssetID.14 ==       ''
entPhysicalIsFRU.14 ==         false(2)

```

Logical entities -- entLogicalTable; with SNMPv3 support

Repeater 1--comprised of any ports attached to backplane 1

```

entLogicalDescr.1 ==           'Acme repeater v3.1'
entLogicalType.1 ==            snmpDot3RptrMgt
entLogicalCommunity.1 ==       'public-repeater1'
entLogicalTAddress.1 ==        192.0.2.1:161
entLogicalTDomain.1 ==         snmpUDPDomain
entLogicalContextEngineID.1 == '80000777017c7d7e7f'H
entLogicalContextName.1 ==     'repeater1'

```

Repeater 2--comprised of any ports attached to backplane 2:

```

entLogicalDescr.2 ==           'Acme repeater v3.1'
entLogicalType.2 ==            snmpDot3RptrMgt
entLogicalCommunity.2 ==       'public-repeater2'
entLogicalTAddress.2 ==        192.0.2.1:161
entLogicalTDomain.2 ==         snmpUDPDomain
entLogicalContextEngineID.2 == '80000777017c7d7e7f'H
entLogicalContextName.2 ==     'repeater2'

```

Logical to Physical Mappings -- entLPMappingTable:

repeater1 uses backplane 1, slot 1-ports 1 & 2, slot 2-port 1

Note that a mapping to the module is not included, because this example represents a port-switchable hub. Even though all ports on the module could belong to the same repeater as a matter of configuration, the LP port mappings should not be replaced dynamically with a single mapping for the module (e.g., entLPPhysicalIndex.1.7). If all ports on the module shared a single backplane connection, then a single mapping for the module would be more appropriate.

```
entLPPhysicalIndex.1.2 ==      2
entLPPhysicalIndex.1.8 ==      8
entLPPhysicalIndex.1.9 ==      9
entLPPhysicalIndex.1.13 ==     13
```

```
repeater2 uses backplane 2, slot 1-ports 3 & 4, slot 2-port 2
entLPPhysicalIndex.2.3 ==      3
entLPPhysicalIndex.2.10 ==     10
entLPPhysicalIndex.2.11 ==     11
entLPPhysicalIndex.2.14 ==     14
```

Physical to Logical to MIB Alias Mappings -- entAliasMappingTable:

Repeater Port Identifier values are shared by both repeaters:

```
entAliasMappingIdentifier.8.0 == rptrPortGroupIndex.1.1
entAliasMappingIdentifier.9.0 == rptrPortGroupIndex.1.2
entAliasMappingIdentifier.10.0 == rptrPortGroupIndex.1.3
entAliasMappingIdentifier.11.0 == rptrPortGroupIndex.1.4
entAliasMappingIdentifier.13.0 == rptrPortGroupIndex.2.1
entAliasMappingIdentifier.14.0 == rptrPortGroupIndex.2.2
```

Physical Containment Tree -- entPhysicalContainsTable

chassis has two backplanes and three containers:

```
entPhysicalChildIndex.1.2 ==    2
entPhysicalChildIndex.1.3 ==    3
entPhysicalChildIndex.1.4 ==    4
entPhysicalChildIndex.1.5 ==    5
entPhysicalChildIndex.1.6 ==    6
```

container 1 has a module:

```
entPhysicalChildIndex.4.7 ==    7
```

container 2 has a module

```
entPhysicalChildIndex.5.12 ==   12
```

Note that in this example, container 3 is empty.

module 1 has 4 ports:

```
entPhysicalChildIndex.7.8 ==    8
entPhysicalChildIndex.7.9 ==    9
```

```
entPhysicalChildIndex.7.10 == 10
entPhysicalChildIndex.7.11 == 11
```

```
module 2 has 2 ports:
  entPhysicalChildIndex.12.13 == 13
  entPhysicalChildIndex.12.14 == 14
```

#### 4.3. EMAN Example

As an example, to illustrate the use of the MIB objects introduced with Energy Management (EMAN) applications, consider a router that has 16 slots with line cards. An example of the entPhysicalTable is given for 3 components of the router, a chassis, a slot, and a line card in that slot. The chassis contains the slot, and the slot contains the line card.

```
entPhysicalDescr.1 == 'ACME Series 16 Slots'
entPhysicalVendorType.1 == acmeProducts.chassisTypes.1
entPhysicalContainedIn.1 == 0
entPhysicalClass.1 == chassis(3)
entPhysicalParentRelPos.1 == -1
entPhysicalName.1 == 'Router 0 Chassis'
entPhysicalHardwareRev.1 == ''
entPhysicalSoftwareRev.1 == ''
entPhysicalFirmwareRev.1 == ''
entPhysicalSerialNum.1 == 'abcd1234'
entPhysicalMfgName.1 == 'ACME'
entPhysicalModelName.1 == 'ACME-16-LCC'
entPhysicalAlias.1 == ''
entPhysicalAssetID.1 == ''
entPhysicalIsFRU.1 == true(1)
entPhysicalMfgDate.1 == '2008-7-28,13:30:30.0,-4:0'
entPhysicalUri.1 == 'urn:f81d4fae-7dec-11d0-a765-00a0c91e6bf6'
entPhysicalUUID.1 == 'f81d4fae-7dec-11d0-a765-00a0c91e6bf6'
```

```
entPhysicalDescr.2 == 'ACME Line Card Slot'
entPhysicalVendorType.2 == acmeProducts.slotTypes.1
entPhysicalContainedIn.2 == 1
entPhysicalClass.2 == container(5)
entPhysicalParentRelPos.2 == 6
entPhysicalName.2 == 'Slot 6'
entPhysicalHardwareRev.2 == ''
entPhysicalFirmwareRev.2 == ''
entPhysicalSoftwareRev.2 == ''
entPhysicalSerialNum.2 == ''
entPhysicalMfgName.2 == 'ACME'
entPhysicalModelName.2 == ''
```

```
entPhysicalAlias.2 == ''
entPhysicalAssetID.2 == ''
entPhysicalIsFRU.2 == false(2)
entPhysicalUris.2 == 'urn:7dc53df5-703e-49b3-8670-b1c468f47f1f'
entPhysicalUUID.2 == '7dc53df5-703e-49b3-8670-b1c468f47f1f'

entPhysicalDescr.4 == 'ACME Series1 Line Card'
entPhysicalVendorType.4 == acmeProducts.moduleTypes.14
entPhysicalContainedIn.4 == 2
entPhysicalClass.4 == module(9)
entPhysicalParentRelPos.4 == 0
entPhysicalName.4 == 'Series1 Linecard'
entPhysicalHardwareRev.4 == ''
entPhysicalFirmwareRev.4 == ''
entPhysicalSoftwareRev.4 == ''
entPhysicalSerialNum.4 == ''
entPhysicalMfgName.4 == 'ACME'
entPhysicalModelName.4 == ''
entPhysicalAlias.4 == ''
entPhysicalAssetID.4 == ''
entPhysicalIsFRU.4 == true(1)
entPhysicalUris.4 == 'urn:01c47915-4777-11d8-bc70-0090272ff725'
entPhysicalUUID.4 == '01c47915-4777-11d8-bc70-0090272ff725'
```

## 5. Security Considerations

There are a number of management objects defined in these MIB modules with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

```
entPhysicalSerialNum
entPhysicalAlias
entPhysicalAssetID
entPhysicalUris
```

These objects contain information about the physical entities within a managed system, which may be used to identify the serial number, identification of assets and managed components, and handling of the managed objects. Their mis-configuration or disclosure may reveal sensitive information on assets, perturb the management of entities, or cause privacy issues if they allow tracking of values that are personally identifying.

Some of the readable objects in these MIB modules (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

```
entPhysicalDescr
entPhysicalVendorType
entPhysicalHardwareRev
entPhysicalFirmwareRev
entPhysicalSoftwareRev
entPhysicalMfgName
entPhysicalModelName
entPhysicalUUID
```

These objects expose information about the physical entities within a managed system, which may be used to identify the vendor, model, version, and specific device-identification information of each system component.

```
entLogicalDescr
entLogicalType
```

These objects expose the type of logical entities present in the managed system.

```
entLogicalCommunity
```

This object exposes community names associated with particular logical entities within the system.

```
entLogicalTAddress
entLogicalTDomain
```

These objects expose network addresses that can be used to communicate with an SNMP agent on behalf of particular logical entities within the system.

```
entLogicalContextEngineID
entLogicalContextName
```

These objects identify the authoritative SNMP engine that contains information on behalf of particular logical entities within the system.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in these MIB modules.

Implementations SHOULD provide the security features described by the SNMPv3 framework (see [RFC3410]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of these MIB modules is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 6. IANA Considerations

This document defines the first version of the IANA-maintained IANA-ENTITY-MIB module, which allows new physical classes to be added to the enumeration in IANAPhysicalClass. An Expert Review, as defined in RFC 5226 [RFC5226], is REQUIRED for each modification.

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
entityMIB	{ mib-2 47 }

IANA has allocated two OBJECT IDENTIFIERS under mib-2 for:

Descriptor	OBJECT IDENTIFIER value
-----	-----
ianaEntityMIB	{ mib-2 216 }
uuidTCMIB	{ mib-2 217 }



## 7. Acknowledgements

The first three versions of RFCs on the ENTITY MIB modules were authored by A. Bierman and K. McCloghrie. The authors would like to thank A. Bierman and K. McCloghrie for the earlier versions of the ENTITY MIB.

The motivation for the extension to [RFC 4133](#) stems from the requirements of the EMAN WG of the IETF.

The authors also thank Juergen Schoenwaelder for his review and comments for improving this document.

## 8. References

### 8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, [RFC 3411](#), December 2002.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, [RFC 3414](#), December 2002.
- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", [RFC 3826](#), June 2004.

- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC4122] Leach, P., Mealling, M., and R. Salz, "A Universally Unique IDentifier (UUID) URN Namespace", [RFC 4122](#), July 2005.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", [RFC 5591](#), June 2009.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", [RFC 5592](#), June 2009.
- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", [RFC 6353](#), July 2011.

## 8.2. Informative References

- [RFC1157] Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol (SNMP)", [RFC 1157](#), May 1990.
- [RFC1516] McMaster, D. and K. McCloghrie, "Definitions of Managed Objects for IEEE 802.3 Repeater Devices", [RFC 1516](#), September 1993.
- [RFC2108] de Graaf, K., Romascanu, D., McMaster, D., and K. McCloghrie, "Definitions of Managed Objects for IEEE 802.3 Repeater Devices using SMIV2", [RFC 2108](#), February 1997.
- [RFC2037] McCloghrie, K. and A. Bierman, "Entity MIB using SMIV2", [RFC 2037](#), October 1996.
- [RFC2737] McCloghrie, K. and A. Bierman, "Entity MIB (Version 2)", [RFC 2737](#), December 1999.
- [RFC2863] McCloghrie, K. and F. Kastenholtz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.

- [RFC3406] Daigle, L., van Gulik, D., Iannella, R., and P. Faltstrom, "Uniform Resource Names (URN) Namespace Definition Mechanisms", [BCP 66](#), [RFC 3406](#), October 2002.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC4133] Bierman, A. and K. McCloghrie, "Entity MIB (Version 3)", [RFC 4133](#), August 2005.
- [RFC4152] Tesink, K. and R. Fox, "A Uniform Resource Name (URN) Namespace for the Common Language Equipment Identifier (CLEI) Code", [RFC 4152](#), August 2005.
- [RFC4188] Norseth, K., Ed., and E. Bell, Ed., "Definitions of Managed Objects for Bridges", [RFC 4188](#), September 2005.
- [T1.213] ATIS T1.213-2001, "Coded Identification of Equipment Entities in the North American Telecommunications System for Information Exchange", 2001, <[www.ansi.org](http://www.ansi.org)>.
- [T1.213a] ATIS T1.213a, "Supplement to T1.213-2001, Coded Identification of Equipment Entities in the North American Telecommunications System for Information Exchange, to Correct the Representation of the Basic Code in Figure B.1", 2001, <[www.ansi.org](http://www.ansi.org)>.

## Authors' Addresses

Andy Bierman  
YumaWorks, Inc.  
274 Redwood Shores Parkway, #133  
Redwood City, CA 94065  
USA

Phone: +1 408-716-0466  
EMail: andy@yumaworks.com

Dan Romascanu  
Avaya  
Park Atidim, Bldg. #3  
Tel Aviv, 61581  
Israel

Phone: +972-3-6458414  
EMail: dromasca@avaya.com

Juergen Quittek  
NEC Europe Ltd.  
Network Research Division  
Kurfuersten-Anlage 36  
Heidelberg 69115  
Germany

Phone: +49 6221 4342-115  
EMail: quittek@neclab.eu

Mouli Chandramouli  
Cisco Systems, Inc.  
Sarjapur Outer Ring Road  
Bangalore 560103  
India

Phone: +91 80 4429 2409  
EMail: moulchan@cisco.com