Network Working Group
Request for Comments: 2155
Category: Standards Track

B. Clouston
Cisco Systems
B. Moore
IBM Corporation
June 1997

Definitions of Managed Objects for APPN using SMIv2

Status of this Memo

Table of Contents

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines objects for monitoring and controlling network devices with APPN (Advanced Peer-to-Peer Networking) capabilities. This memo identifies managed objects for the APPN protocol.

2. The SNMPv2 Network Management Framework

The SNMP Network Management Framework consists of several components. For the purpose of this specification, the applicable components of the Framework are the SMI and related documents [1, 2, 3], which define the mechanisms used for describing and naming objects for the purpose of management.

The Framework permits new objects to be defined for the purpose of experimentation and evaluation.

3. Overview

This document identifies a set of objects for monitoring the configuration and active characteristics of devices with APPN capabilities, and for controlling certain characteristics. APPN is the aspect of Systems Network Architecture (SNA) that supports peer-to-peer networking. These networks transport both independent and dependent LU session traffic. See the SNANAU APPC MIB [7] and the SNA NAU MIB [8] for management of these sessions. See also the DLUR MIB[9], and the HPR MIB[10] for management of extensions to the APPN architecture. In this document, we describe APPN managed objects.

An APPN network comprises various types of nodes, and transmission groups (TGs) that connect the nodes. Network nodes (NNs) provide directory and routing functions for session establishment. NNs may be session end points or intermediate nodes in a session. A border node is a type of network node that connects networks together for session establishment without fully merging them. End nodes (ENs) are session end points that receive directory and routing functions from network nodes, over control-point to control-point (CP-CP) sessions. Low-entry networking (LEN) nodes are also session end points, but do not support CP-CP sessions, and therefore need additional manual configuration definitions to establish sessions in an APPN network. ENs and LEN nodes may have minimal directory and routing functions to establish control sessions (ENs) or to connect into the APPN network (LEN nodes). Virtual routing nodes (VRNs) are not really nodes, but rather common definitions among actual nodes in a shared transport facility such as a local area network (LAN) that allow these actual nodes to temporarily establish a logical link with one another without defining each other’s link-level addressing information.

Ports and link stations are the node’s interface to the data link control (DLC), which provides the physical transport, or to another protocol such as Data Link Switching (DLSw), which provides transport over an IP network. See the SNADLC SDLC MIB[11], the SNADLC LLC MIB[12], and the DLSw MIB[13]. A link station uses a port to make a connection to another node. This connection establishes a TG between the two nodes.

The directory and routing functions enable an NN to find where an LU is located in the network, and calculate the optimal route for the session based on the requested class of service (COS). A network node saves the LU information in a directory database, which is built from LUs defined locally, LU registration from served end nodes, and LUs learned from network searches.

Each NN maintains a local COS database that assigns a routing weight, or relative cost, to each resource for each class of service. For example, the #INTER COS assigns a lower weight to TGs with a greater effective capacity, while the #BATCH COS favors TGs with a lower relative cost per byte.

A node saves network topology information (on NNs, VRNs, and TGs between them) in a network topology database. The topology information includes state and routing characteristics. Topology information is exchanged between NNs over CP-CP sessions such that the database is fully replicated at each NN. Information on TGs from NNs to ENs are kept in a local topology database. Local topology information is shared with other NNs only during the session establishment process, to give the NN responsible for route calculation the necessary information for end-to- end route calculation.

SNA names such as LU names, CP names, COS names, and mode names can be padded with blanks (space characters) in SNA formats. These blanks are nonsignificant. For example, in a BIND Request Unit (RU) a COS name of "#INTER" with a length of 6 is identical to a COS name of "#INTER " with a length of 8. However, in this MIB, nonsignificant blanks are not included by the agent. Using the COS name from the previous example, an agent would return a length of 6 and the string "#INTER" with no blanks for appnCosName, regardless of how it appears in the BIND RU or in internal storage. The lone exception is the all blank mode name, for which the agent returns a length of 8 and the string " " (8 blank spaces). The MIB variables that this applies to are identified by a textual convention syntax that also describes this behavior.

When an SNA name is functioning as a table index, an agent treats trailing blanks as significant. If a management station requests the objects from a row with index "#INTER ", the agent does not match this to the row with index "#INTER". Since an agent has no nonsignificant blanks in any of its table indices, the only reason for a Management Station to include them would be to start GetNext processing at a chosen point in a table. For example, a GetNext request with index "M " would start retrieval from a table at the first row with an 8-character index beginning with "M" or a letter after "M".

The SNA/APPN terms and overall architecture are documented in [4], [5], [6], and [14].

Highlights of the management functions supported by the APPN MIB module include the following:

- Activating and deactivating ports and link stations.
- Monitoring of configuration parameters related to the node, ports, link stations, virtual routing nodes, and classes of service.
- Monitoring of operational parameters related to ports, link stations, virtual routing nodes, topology, directory, and intermediate sessions.
- Historical information about link station errors during connection establishment, or that caused the connection to terminate.
- Deactivating intermediate sessions.
- Traps for SNA Management Services (SNA/MS) Alert conditions.

This MIB module does not support:

- Configuration of APPN nodes.
- Monitoring and control of endpoint sessions.
- Dependent LU Requester (DLUR) management.
- High-Performance Routing (HPR) management.

3.1. APPN MIB Structure

The APPN MIB module contains the following groups of objects:

- appnNode - objects related to the APPN node for all node types.
- appnNn - objects to represent the network nodes, virtual routing nodes, and TGs between these nodes that make up the APPN network topology database maintained in NNs.
- appnLocalTopology - objects to represent nodes and TGs between nodes in the local topology database maintained in all nodes.

- o appnDir - objects related to LU location information from the node's directory database.

- o appnCos - objects related to classes of service information.

- o appnSessIntermediate - objects related to intermediate sessions that pass through this node.

These groups are described below in more detail.

3.1.1. appnNode group

The appnNode group consists of the following tables and objects:

1) appnGeneralInfoAndCaps

This group of objects describes general information about the APPN node. The type of information includes the node type and the time since this node was initialized.

2) appnNnUniqueInfoAndCaps

This group of objects describes information specific to network nodes such as node routing characteristics.

3) appnEnUniqueInfoAndCaps

This group of objects describes information specific to end nodes, including its network node server.

4) appnPortInformation

This includes the appnPortTable, which describes the configuration and current status of the ports used by APPN, including the port state and DLC type.

5) appnLinkStationInformation

This includes the appnNodeLsTable, which describes the configuration and current status of the link stations used by APPN, including the link state and port name; and the appnLsStatusTable, which provides information about errors this node encountered with connections to adjacent nodes, such as the sense data captured during connection failures. It is a product option to decide how many appnLsStatusTable entries are kept.

6) appnVrnInfo

This includes the appnVrnTable, which describes the relationship between virtual routing nodes' TGs described in the appnLocalTgTable with ports in the appnPortTable.

3.1.2. appnNn group

The appnNn group consists of the following objects and tables

1) appnNnTopo

These objects contain general information about the network topology database including the number of nodes present, and the number of topology database updates (TDU) wars the node has detected.

2) appnNnTopology

This includes tables representing the APPN network topology database. This includes the network nodes, virtual routing nodes, and TGs between these nodes, as well as the information about these resources carried in topology updates. The tables are first indexed by the same flow reduction sequence number (FRSN) used in topology exchanges between NNs. This allows a management station to retrieve only incremental updates, since the agent will update the FRSN of new or changed resources.

3.1.3. appnLocalTopology group

The appnLocalTopology group consists of the following objects and tables:

1) appnLocalThisNode

a) appnLocalGeneral

Contains the local node and type.

b) appnLocalNnSpecific

These objects contain routing information about the local network node.

c) appnLocalTg

This table represents information about this node's local TGs.

2) appnLocalEnTopology

This table represents TG information for EN TGs learned by the NN via TG registration with the local node.

3.1.4. appnDir group

The appnDir group consists of the following objects and tables:

1) appnDirPerf

These objects represent information related to information about the directory database and directory searches involving this node.

2) appnDirTable

This table represents the directory database, listing LUs known to this node, along with the owning node of the LU and the serving NN of the owning node.

3.1.5. appnCos group

The appnCos group consists of the following tables:

1) appnCosModeTable

This table represents the mode to class of service mapping.

2) appnCosNameTable

This table represents the tranmission priority for each class of service.

3) appnCosNodeRowTable

This table represents the node-row information for each class of service, including the weight of each node.

3) appnCosTGRowTable

This table represents the TG-row information for each class of service, including the weight of each TG.

3.1.6. appnSessIntermediate group

The appnSessIntermediate group consists of the following objects and tables:

1) appnIsInGlobal

These objects allow control of the collection of intermediate session information such as Route Selection Control Vectors (RSCVs) and counters.

2) appnIsInTable

This table contains information on active intermediate sessions.

3) appnIsRtpTable

This table contains information on active intermediate sessions that are being transported on Rapid Transport Protocol (RTP) connections by High Performance Routing (HPR).

3.1.7. appnTraps

One APPN trap is defined. It is intended to correspond to SNA/MS Alerts, but is optional for a product to implement this trap. The trap identifies the Alert ID number and, where possible, the affected resource.

4. Definitions

```
APPN-MIB DEFINITIONS          ::= BEGIN

IMPORTS

        IANAifType
                FROM IANAifType-MIB

        DisplayString, VariablePointer, RowPointer, DateAndTime,
        TruthValue, TimeStamp, TEXTUAL-CONVENTION
                FROM SNMPv2-TC

        experimental, Counter32, Gauge32, Integer32, Unsigned32,
        TimeTicks, OBJECT-TYPE, MODULE-IDENTITY, NOTIFICATION-TYPE
                FROM SNMPv2-SMI

        MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
                FROM SNMPv2-CONF

        snanauMIB
                FROM SNA-NAU-MIB;

appnMIB MODULE-IDENTITY
        LAST-UPDATED  "9703201200Z"
        ORGANIZATION  "IETF SNA NAU MIB WG / AIW APPN MIBs SIG"
        CONTACT-INFO

                "

                        Bob Clouston
                        Cisco Systems
                        7025 Kit Creek Road
                        P.O. Box 14987
                        Research Triangle Park, NC 27709, USA
                        Tel:    1 919 472 2333
                        E-mail: clouston@cisco.com

                        Bob Moore
                        IBM Corporation
                        800 Park Offices Drive
                        RHJA/664
                        P.O. Box 12195
                        Research Triangle Park, NC 27709, USA
                        Tel:    1 919 254 4436
                        E-mail: remoore@ralvm6.vnet.ibm.com
                "
      DESCRIPTION
```

```
                "This is the MIB module for objects used to
                 manage network devices with APPN capabilities."

::= { snanauMIB 4 }
-- snanauMIB ::= { mib-2 34 }

-- ********************************************************************
-- Textual Conventions
-- ********************************************************************
SnaNodeIdentification ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "An SNA Node Identification consists of two parts, which
          together comprise four bytes of hexadecimal data.  In SNA the
          Node Identification is transported in bytes 2-5 of the XID.

          The block number is the first three digits of the Node
          Identification.  These 3 hexadecimal digits identify the
          product.

          The ID number is the last 5 digits of the Node Identification.
          These 5 hexadecimal digits are administratively defined and
          combined with the 3-digit block number form the 8-digit Node
          Identification.  A unique value is required for connections to
          SNA subarea.  In some implementations, the value 'bbb00000'
          (where 'bbb' represents a 3-digit block number) is returned to
          mean that the ID number is not unique on this node.

          An SNA Node Identification is represented as eight
          ASCII-encoded hexadecimal digits, using the characters '0' -
          '9' and 'A' - 'F'."

      SYNTAX OCTET STRING (SIZE (8))

SnaControlPointName ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "A fully qualified SNA control point name, consisting of a 1 to
          8 character network identifier (NetId), a period ('.'), and a 1
          to 8 character control point name (CpName).

          The NetId and CpName are constructed from the uppercase letters
          'A' - 'Z' and the numerics '0' - '9', all encoded in ASCII,
          with the restriction that the first character of each must be
          a letter.  Trailing blanks are not allowed.

          Earlier versions of SNA permitted three additional characters
          in NetIds and CpNames:  '#', '@', and '$'.  While this use of
```

```
          these characters has been retired, a Management Station should
          still accept them for backward compatibility."

      SYNTAX OCTET STRING (SIZE (3..17))

SnaClassOfServiceName ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "An SNA class-of-service (COS) name, ranging from 1 to 8
          ASCII characters.  COS names take one of two forms:

             - a user-defined COS name is constructed from the uppercase
               letters 'A' - 'Z' and the numerics '0' - '9', with the
               restriction that the first character of the name must be
               a letter.
             - an SNA-defined user-session COS name begins with the
               character '#', which is followed by up to seven
               additional characters from the set of uppercase letters
               and numerics.

          Trailing blanks are not allowed in either form of COS name.

          A zero-length string indicates that a COS name is not
          available."

      SYNTAX OCTET STRING (SIZE (0..8))

SnaModeName ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "An SNA mode name, ranging from 1 to 8 ASCII characters.
          Mode names take one of two forms:

             - a user-defined mode name is constructed from the
               uppercase letters 'A' - 'Z' and the numerics '0' - '9',
               with the restriction that the first character of the name
               must be a letter.
             - an SNA-defined user-session mode name begins with the
               character '#', which is followed by up to seven
               additional characters from the set of uppercase letters
               and numerics.

          Trailing blanks are not allowed in either form of mode name,
          with the single exception of the all-blank mode name, where
          a string consisting of 8 blanks is returned.

          A zero-length string indicates that a mode name is not
          available."
```

```
      SYNTAX OCTET STRING (SIZE (0..8))

SnaSenseData ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "To facilitate their display by a Management Station, sense
          data objects in the MIB are represented as OCTET STRINGS
          containing eight ASCII characters.  Eight '0' characters
          indicates that no sense data identifying an SNA error
          condition is available.

          An SNA sense data is represented as eight hexadecimal digits,
          using the characters '0' - '9' and 'A' - 'F'."

      SYNTAX OCTET STRING (SIZE (8))

DisplayableDlcAddress ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "DLC address of a port or link station, represented as an
          OCTET STRING containing 0 to 64 ASCII characters.
          A Management Station should use a value of this type only
          for display.  The 'real' DLC address, i.e., the sequence of
          bytes that flow in the DLC header, is often available in a
          DLC-specific MIB.

          The zero-length string indicates that the DLC address in
          question is not known to the agent."

      SYNTAX OCTET STRING (SIZE (0..64))

AppnNodeCounter ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "An object providing global statistics for the entire APPN
          node.  A Management Station can detect discontinuities in this
          counter by monitoring the appnNodeCounterDisconTime object."

      SYNTAX Counter32

AppnPortCounter ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "An object providing statistics for an APPN port.  A
          Management Station can detect discontinuities in this counter
          by monitoring the appnPortCounterDisconTime object."

      SYNTAX Counter32
```

```
AppnLinkStationCounter ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "An object providing statistics for an APPN link station.  A
          Management Station can detect discontinuities in this counter
          by monitoring the appnLsCounterDisconTime object."

      SYNTAX Counter32

AppnTopologyEntryTimeLeft ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "Number of days before deletion of this entry from the topology
          database.  Range is 0-15.  A value of 0 indicates that the
          entry is either in the process of being deleted, or is being
          marked for deletion at the next garbage collection cycle."

      SYNTAX INTEGER (0..15)

AppnTgDlcData ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "DLC-specific data related to a connection network transmission
          group.  For other TGs, a zero-length string is returned.

          Examples of the type of data returned by an object with this
          syntax include the following:

                Token-Ring      - MAC/SAP
                X.25 Switched   - dial digits
                X.21 Switched   - dial digits
                Circuit Switch  - dial digits

          This MIB does not specify formats for these or any other types
          of DLC-specific data.  Formats may, however, be specified in
          documents related to a particular DLC.

          The contents of an object with this syntax correspond to the
          contents of the DLC-specific subfields of cv46, documented in
          (6)."

      SYNTAX OCTET STRING  (SIZE (0..64))

AppnTgEffectiveCapacity ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "A value representing the effective capacity of a transmission
          group.  This is an administratively assigned value derived from
```

```
          the link bandwidth and maximum load factor.  It is encoded in
          the same way as byte 7 of cv47, and represents a floating-point
          number in units of 300 bits per second."

      SYNTAX OCTET STRING (SIZE (1))

AppnTgSecurity ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "A value representing the level of security on a transmission
          group.  A class of service definition includes an indication of
          the acceptable TG security value(s) for that class of service.

          The following seven values are defined:

            nonsecure(1) -
                              (X'01'):  none of the values listed below;
                              for example, satellite-connected or
                              located in a nonsecure country
            publicSwitchedNetwork(32) -
                              (X'20'):  public switched network; secure
                              in the sense that there is no
                              predetermined route that traffic will take
            undergroundCable(64) -
                              (X'40'):  underground cable; located in a
                              secure country (as determined by the
                              network administrator)
            secureConduit(96) -
                              (X'60'):  secure conduit, not guarded; for
                              example, pressurized pipe
            guardedConduit(128) -
                              (X'80'):  guarded conduit; protected
                              against physical tapping
            encrypted(160) -
                              (X'A0'):  link-level encryption is provided
            guardedRadiation(192) -
                              (X'C0'):  guarded conduit containing the
                              transmission medium; protected against
                              physical and radiation tapping"

      SYNTAX INTEGER {
                     nonsecure(1),               -- X'01'
                     publicSwitchedNetwork(32),  -- X'20'
                     undergroundCable(64),       -- X'40'
                     secureConduit(96),          -- X'60'
                     guardedConduit(128),        -- X'80'
                     encrypted(160),             -- X'A0'
                     guardedRadiation(192)       -- X'C0'
```

```
                    }

AppnTgDelay ::= TEXTUAL-CONVENTION
      STATUS current
      DESCRIPTION
          "Relative amount of time that it takes for a signal to travel
          the length of a logical link.  This time is represented in
          microseconds, using the same encoding scheme used in cv47 in a
          topology update.  Some of the more common values, along with
          their encoded hex values, are:

                    minimum(0),                X'00'
                    negligible(384),           X'4C'
                    terrestrial(9216),         X'71'
                    packet(147456),            X'91'
                    long(294912),              X'99'
                    maximum(2013265920)        X'FF'

          "

      SYNTAX OCTET STRING (SIZE (1))

-- ********************************************************************
  appnObjects             OBJECT IDENTIFIER ::= { appnMIB 1 }
-- ********************************************************************

-- ******************** The APPN Node Group ****************************

appnNode              OBJECT IDENTIFIER ::= { appnObjects 1 }
  appnGeneralInfoAndCaps      OBJECT IDENTIFIER ::= { appnNode 1 }
  appnNnUniqueInfoAndCaps     OBJECT IDENTIFIER ::= { appnNode 2 }
  appnEnUniqueCaps            OBJECT IDENTIFIER ::= { appnNode 3 }
  appnPortInformation         OBJECT IDENTIFIER ::= { appnNode 4 }
  appnLinkStationInformation  OBJECT IDENTIFIER ::= { appnNode 5 }
  appnVrnInfo                 OBJECT IDENTIFIER ::= { appnNode 6 }

-- This group provides global information about an APPN network node,
-- an APPN end node, or an LEN node.

-- The first section applies to all three node types.
-- The second section applies only to APPN network nodes.
-- The third section applies only to APPN end nodes and to LEN nodes.
-- The fourth section applies to all three node types.
-- The fifth section applies to all three node types.
-- The sixth section applies only to APPN network nodes.

-- APPN General Information
-- This section applies to both APPN network and end nodes, and to
```

```
-- LEN end nodes.

appnNodeCpName OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Administratively assigned network name for this node."

      ::= { appnGeneralInfoAndCaps 1 }

appnNodeMibVersion OBJECT-TYPE
      SYNTAX DisplayString  (SIZE (11))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The value of LAST-UPDATED from this module's MODULE-IDENTITY
          macro.  This object gives a Management Station an easy way of
          determining the level of the MIB supported by an agent."

      ::= { appnGeneralInfoAndCaps 2 }

appnNodeId OBJECT-TYPE
      SYNTAX SnaNodeIdentification
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "This node's Node Identification, which it sends in bytes
          2-5 of XID."

      ::= { appnGeneralInfoAndCaps 3 }

appnNodeType OBJECT-TYPE
      SYNTAX INTEGER {
                     networkNode(1),
                     endNode(2),
                     t21len(4)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Type of APPN node:

                networkNode(1) - APPN network node
                endNode(2)     - APPN end node
                t21len(4)      - LEN end node"

      ::= { appnGeneralInfoAndCaps 4 }
```

```
appnNodeUpTime OBJECT-TYPE
      SYNTAX TimeTicks
      UNITS "hundredths of a second"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Amount of time (in hundredths of a second) since the APPN node
          was last re-initialized."

      ::= { appnGeneralInfoAndCaps 5 }

appnNodeParallelTg OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node supports parallel TGs."

      ::= { appnGeneralInfoAndCaps 6 }

appnNodeAdaptiveBindPacing OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node supports adaptive bind pacing for
          dependent LUs."

      ::= { appnGeneralInfoAndCaps 7 }

appnNodeHprSupport OBJECT-TYPE
      SYNTAX INTEGER {
                 noHprSupport(1),
                 hprBaseOnly(2),
                 rtpTower(3),
                 controlFlowsOverRtpTower(4)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates this node's level of support for high-performance
          routing (HPR):

             noHprSupport(1)             - no HPR support
             hprBaseOnly(2)              - HPR base (option set 1400)
                                           supported
             rtpTower(3)                 - HPR base and RTP tower
                                           (option set 1401) supported
```

```
              controlFlowsOverRtpTower(4) - HPR base, RTP tower, and
                                            control flows over RTP
                                            (option set 1402) supported

          This object corresponds to cv4580, byte 9, bits 3-4."

      ::= { appnGeneralInfoAndCaps 8 }

appnNodeMaxSessPerRtpConn OBJECT-TYPE
      SYNTAX Gauge32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "This object represents a configuration parameter indicating
          the maximum number of sessions that the APPN node is to put on
          any HPR connection.  The value is zero if not applicable."

      ::= { appnGeneralInfoAndCaps 9 }

appnNodeHprIntRteSetups OBJECT-TYPE
      SYNTAX AppnNodeCounter
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The total number of HPR route setups received for routes
          passing through this node since the node was last
          re-initialized."

      ::= { appnGeneralInfoAndCaps 10 }

appnNodeHprIntRteRejects OBJECT-TYPE
      SYNTAX AppnNodeCounter
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The number of HPR route setups rejected by this node for
          routes passing through it since the node was last
          re-initialized."

      ::= { appnGeneralInfoAndCaps 11 }

appnNodeHprOrgRteSetups OBJECT-TYPE
      SYNTAX AppnNodeCounter
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The total number of HPR route setups sent for routes
          originating in this node since the node was last
```

```
            re-initialized."

        ::= { appnGeneralInfoAndCaps 12 }

appnNodeHprOrgRteRejects OBJECT-TYPE
        SYNTAX AppnNodeCounter
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of HPR route setups rejected by other nodes for
            routes originating in this node since the node was last
            re-initialized."

        ::= { appnGeneralInfoAndCaps 13 }

appnNodeHprEndRteSetups OBJECT-TYPE
        SYNTAX AppnNodeCounter
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The total number of HPR route setups received for routes
            ending in this node since the node was last re-initialized."

        ::= { appnGeneralInfoAndCaps 14 }

appnNodeHprEndRteRejects OBJECT-TYPE
        SYNTAX AppnNodeCounter
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of HPR route setups rejected by this node for
            routes ending in it since the node was last re-initialized."

        ::= { appnGeneralInfoAndCaps 15 }

appnNodeCounterDisconTime OBJECT-TYPE
        SYNTAX TimeStamp
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The value of the sysUpTime object the last time the APPN node
            was re-initialized."

        ::= { appnGeneralInfoAndCaps 16 }


-- ****************************************************************
-- APPN Network Node Information
```

```
-- This section provides global information about an APPN network node.

appnNodeNnCentralDirectory OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node supports central directory
          services.

          This object corresponds to cv4580, byte 8, bit 1."

      ::= { appnNnUniqueInfoAndCaps 1 }

appnNodeNnTreeCache OBJECT-TYPE
      SYNTAX INTEGER {
                     noCache(1),
                     cacheNoIncrUpdate(2),
                     cacheWithIncrUpdate(3)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates this node's level of support for caching of route
          trees.  Three levels are specified:

             noCache(1)             - caching of route trees is not
                                      supported
             cacheNoIncrUpdate(2)   - caching of route trees is
                                      supported, but without incremental
                                      updates
             cacheWithIncrUpdate(3) - caching of route trees with
                                      incremental updates is supported"

      ::= { appnNnUniqueInfoAndCaps 2 }

appnNodeNnRouteAddResist OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Route addition resistance.

          This administratively assigned value indicates the relative
          desirability of using this node for intermediate session
          traffic.  The value, which can be any integer 0-255, is used
          in route computation.  The lower the value, the more
          desirable the node is for intermediate routing.
```

```
          This object corresponds to cv4580, byte 6."

      ::= { appnNnUniqueInfoAndCaps 3 }

appnNodeNnIsr OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node supports intermediate session
          routing.

          This object corresponds to cv4580, byte 8, bit 2."

      ::= { appnNnUniqueInfoAndCaps 4 }

appnNodeNnFrsn OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The last flow-reduction sequence number (FRSN) sent by this
          node in a topology update to an adjacent network node."

      ::= { appnNnUniqueInfoAndCaps 5 }

appnNodeNnPeriBorderSup OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node has peripheral border node
          support.

          This object corresponds to cv4580, byte 9, bit 0."

      ::= { appnNnUniqueInfoAndCaps 6 }

appnNodeNnInterchangeSup OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node has interchange node support.

          This object corresponds to cv4580, byte 9, bit 1."

      ::= { appnNnUniqueInfoAndCaps 7 }
```

```
appnNodeNnExteBorderSup OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node has extended border node support.

          This object corresponds to cv4580, byte 9, bit 2."

      ::= { appnNnUniqueInfoAndCaps 8 }


appnNodeNnSafeStoreFreq OBJECT-TYPE
      SYNTAX INTEGER (0..32767)
      UNITS "TDUs"
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
          "The topology safe store frequency.

          If this number is not zero, then the topology database is saved
          each time the total number of topology database updates (TDUs)
          received by this node increases by this number.  A value of
          zero indicates that the topology database is not being saved."

      ::= { appnNnUniqueInfoAndCaps 9 }

appnNodeNnRsn OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Resource sequence number for this node, which it assigns and
          controls.

          This object corresponds to the numeric value in cv4580, bytes
          2-5."

      ::= { appnNnUniqueInfoAndCaps 10 }

appnNodeNnCongested OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node is congested.  Other network nodes
          stop routing traffic to this node while this flag is on.
```

```
          This object corresponds to cv4580, byte 7, bit 0."

      ::= { appnNnUniqueInfoAndCaps 11 }

appnNodeNnIsrDepleted OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicate whether intermediated session routing resources are
          depleted.  Other network nodes stop routing traffic through
          this node while this flag is on.

          This object corresponds to cv4580, byte 7, bit 1."

      ::= { appnNnUniqueInfoAndCaps 12 }

appnNodeNnQuiescing OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node is quiescing.

          This object corresponds to cv4580, byte 7, bit 5."

      ::= { appnNnUniqueInfoAndCaps 13 }

appnNodeNnGateway OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node has gateway services support.

          This object corresponds to cv4580, byte 8, bit 0."

      ::= { appnNnUniqueInfoAndCaps 14 }


-- ****************************************************************
-- APPN End Node Information

appnNodeEnModeCosMap OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Indicates whether this end node supports mode name to COS name
            mapping."

        ::= { appnEnUniqueCaps 1 }

appnNodeEnNnServer OBJECT-TYPE
        SYNTAX OCTET STRING (SIZE (0 | 3..17))
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The fully qualified name of the current NN server for this end
            node.  An NN server is identified using the format specified in
            the SnaControlPointName textual convention.  The value is a
            zero-length string when there is no active NN server."
        ::= { appnEnUniqueCaps 2 }

appnNodeEnLuSearch OBJECT-TYPE
        SYNTAX TruthValue
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Indicates whether the node is to be searched for LUs as part
            of a network broadcast search."

        ::= { appnEnUniqueCaps 3 }


-- ****************************************************************
-- APPN Port information
--

appnPortTable OBJECT-TYPE
        SYNTAX SEQUENCE OF AppnPortEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "The Port table describes the configuration and current status
            of the ports used by APPN.  When it is known to the APPN
            component, an OBJECT IDENTIFIER pointing to additional
            information related to the port is included.  This may, but
            need not, be a RowPointer to an ifTable entry for a DLC
            interface immediately 'below' the port."

        ::= { appnPortInformation 1 }

appnPortEntry OBJECT-TYPE
        SYNTAX AppnPortEntry
        MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
          "The port name is used as the index to this table."

      INDEX
             { appnPortName }

      ::= { appnPortTable 1 }

AppnPortEntry ::= SEQUENCE {
      appnPortName                  DisplayString,
      appnPortCommand               INTEGER,
      appnPortOperState             INTEGER,
      appnPortDlcType               IANAifType,
      appnPortPortType              INTEGER,
      appnPortSIMRIM                TruthValue,
      appnPortLsRole                INTEGER,
      appnPortNegotLs               TruthValue,
      appnPortDynamicLinkSupport    TruthValue,
      appnPortMaxRcvBtuSize         INTEGER,
      appnPortMaxIframeWindow       Gauge32,
      appnPortDefLsGoodXids         AppnPortCounter,
      appnPortDefLsBadXids          AppnPortCounter,
      appnPortDynLsGoodXids         AppnPortCounter,
      appnPortDynLsBadXids          AppnPortCounter,
      appnPortSpecific              RowPointer,
      appnPortDlcLocalAddr          DisplayableDlcAddress,
      appnPortCounterDisconTime     TimeStamp
                    }

appnPortName OBJECT-TYPE
      SYNTAX DisplayString (SIZE (1..10))
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name for this APPN port."

      ::= { appnPortEntry 1 }

appnPortCommand OBJECT-TYPE
      SYNTAX INTEGER {
                      deactivate(1),
                      activate(2),
                      recycle(3),
                      ready(4)
                     }
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
          "Object by which a Management Station can activate, deactivate,
          or recycle (i.e., cause to be deactivated and then immediately
          activated) a port, by setting the value to activate(1),
          deactivate(2), or recycle(3), respectively.  The value ready(4)
          is returned on GET operations until a SET has been processed;
          after that the value received on the most recent SET is
          returned."

      ::= { appnPortEntry 2 }

appnPortOperState OBJECT-TYPE
      SYNTAX INTEGER    {
                         inactive(1),
                         pendactive(2),
                         active(3),
                         pendinact(4)
                        }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates the current state of this port:

              inactive(1)   - port is inactive
              pendactive(2) - port is pending active
              active(3)     - port is active
              pendinact(4)  - port is pending inactive"


      ::= { appnPortEntry 3 }

appnPortDlcType OBJECT-TYPE
      SYNTAX IANAifType
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The type of DLC interface, distinguished according to the
          protocol immediately 'below' this layer."

      ::= { appnPortEntry 4 }

appnPortPortType OBJECT-TYPE
      SYNTAX INTEGER {
                      leased(1),
                      switched(2),
                      sharedAccessFacilities(3)
                      }
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
          "Identifies the type of line used by this port:

              leased(1)                 - leased line
              switched(2)               - switched line
              sharedAccessFacilities(3) - shared access facility, such
                                          as a LAN."

      ::= { appnPortEntry 5 }

appnPortSIMRIM OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether Set Initialization Mode (SIM) and Receive
          Initialization Mode (RIM) are supported for this port."

      ::= { appnPortEntry 6 }

appnPortLsRole OBJECT-TYPE
      SYNTAX INTEGER {
                     primary(1),
                     secondary(2),
                     negotiable(3),
                     abm(4)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
             "Initial role for link stations activated through this port.
             The values map to the following settings in the initial XID,
             where 'ABM' indicates asynchronous balanced mode and 'NRM'
             indicated normal response mode:

                 primary(1):     ABM support = 0     ( = NRM)
                                 role = 01           ( = primary)
                 secondary(2):   ABM support = 0     ( = NRM)
                                 role = 00           ( = secondary)
                 negotiable(3):  ABM support = 0     ( = NRM)
                                 role = 11           ( = negotiable)
                 abm(4):         ABM support = 1     ( = ABM)
                                 role = 11           ( = negotiable)"

      ::= { appnPortEntry 7 }

appnPortNegotLs OBJECT-TYPE
```

```
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node supports negotiable link stations
          for this port."

      ::= { appnPortEntry 8 }

appnPortDynamicLinkSupport OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node allows call-in on this port from
          nodes not defined locally."

      ::= { appnPortEntry 9 }

appnPortMaxRcvBtuSize OBJECT-TYPE
      SYNTAX INTEGER (99..32767)
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum Basic Transmission Unit (BTU) size that a link station
          on this port can receive.

          This object corresponds to bytes 21-22 of XID3."

      ::= { appnPortEntry 10 }

appnPortMaxIframeWindow OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "I-frames"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum number of I-frames that can be received by the XID
          sender before an acknowledgement is received."

      ::= { appnPortEntry 11 }

appnPortDefLsGoodXids OBJECT-TYPE
      SYNTAX AppnPortCounter
      UNITS "XID exchanges"
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
          "The total number of successful XID exchanges that have
          occurred on all defined link stations on this port since the
          last time this port was started."

      ::= { appnPortEntry 12 }

appnPortDefLsBadXids OBJECT-TYPE
      SYNTAX AppnPortCounter
      UNITS "XID exchanges"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The total number of unsuccessful XID exchanges that have
          occurred on all defined link stations on this port since the
          last time this port was started."

      ::= { appnPortEntry 13 }

appnPortDynLsGoodXids OBJECT-TYPE
      SYNTAX AppnPortCounter
      UNITS "XID exchanges"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The total number of successful XID exchanges that have
          occurred on all dynamic link stations on this port since the
          last time this port was started."

      ::= { appnPortEntry 14 }

appnPortDynLsBadXids OBJECT-TYPE
      SYNTAX AppnPortCounter
      UNITS "XID exchanges"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The total number of unsuccessful XID exchanges that have
          occurred on all dynamic link stations on this port since the
          last time this port was started."

      ::= { appnPortEntry 15 }

appnPortSpecific OBJECT-TYPE
      SYNTAX RowPointer
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Identifies the object, e.g., one in a DLC-specific MIB, that
            can provide additional information related to this port.
            If the agent is unable to identify such an object, the value
            0.0 is returned."

        ::= { appnPortEntry 16 }

appnPortDlcLocalAddr OBJECT-TYPE
        SYNTAX DisplayableDlcAddress
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Local DLC address of this port."

        ::= { appnPortEntry 17 }

appnPortCounterDisconTime OBJECT-TYPE
        SYNTAX TimeStamp
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The value of the sysUpTime object the last time the port was
            started."

        ::= { appnPortEntry 18 }

-- ****************************************************************
-- APPN Link Station Information
--

appnLsTable OBJECT-TYPE
        SYNTAX SEQUENCE OF AppnLsEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "This table contains detailed information about the link
            station configuration and its current status."

        ::= { appnLinkStationInformation 1 }

appnLsEntry OBJECT-TYPE
        SYNTAX AppnLsEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "This table is indexed by the link station name."

        INDEX
```

```
              { appnLsName }

      ::= { appnLsTable 1 }

AppnLsEntry ::= SEQUENCE {
      appnLsName                  DisplayString,
      appnLsCommand               INTEGER,
      appnLsOperState             INTEGER,

      appnLsPortName              DisplayString,
      appnLsDlcType               IANAifType,
      appnLsDynamic               TruthValue,

      appnLsAdjCpName             OCTET STRING,
      appnLsAdjNodeType           INTEGER,
      appnLsTgNum                 INTEGER,
      appnLsLimResource           TruthValue,
      appnLsActOnDemand           TruthValue,
      appnLsMigration             TruthValue,
      appnLsPartnerNodeId         SnaNodeIdentification,
      appnLsCpCpSessionSupport    TruthValue,

      appnLsMaxSendBtuSize        INTEGER,
-- performance data
      appnLsInXidBytes            AppnLinkStationCounter,
      appnLsInMsgBytes            AppnLinkStationCounter,
      appnLsInXidFrames           AppnLinkStationCounter,
      appnLsInMsgFrames           AppnLinkStationCounter,
      appnLsOutXidBytes           AppnLinkStationCounter,
      appnLsOutMsgBytes           AppnLinkStationCounter,
      appnLsOutXidFrames          AppnLinkStationCounter,
      appnLsOutMsgFrames          AppnLinkStationCounter,
-- propagation delay
      appnLsEchoRsps              AppnLinkStationCounter,
      appnLsCurrentDelay          Gauge32,
      appnLsMaxDelay              Gauge32,
      appnLsMinDelay              Gauge32,
      appnLsMaxDelayTime          DateAndTime,
-- XID Statistics
      appnLsGoodXids              AppnLinkStationCounter,
      appnLsBadXids               AppnLinkStationCounter,
-- DLC-specific
      appnLsSpecific              RowPointer,
      appnLsActiveTime            Unsigned32,
      appnLsCurrentStateTime      TimeTicks,
-- HPR-specific
      appnLsHprSup                INTEGER,
      appnLsErrRecoSup            TruthValue,
```

```
      appnLsForAnrLabel           OCTET STRING,
      appnLsRevAnrLabel           OCTET STRING,
      appnLsCpCpNceId             OCTET STRING,
      appnLsRouteNceId            OCTET STRING,
      appnLsBfNceId               OCTET STRING,

      appnLsLocalAddr             DisplayableDlcAddress,
      appnLsRemoteAddr            DisplayableDlcAddress,
      appnLsRemoteLsName          DisplayString,
      appnLsCounterDisconTime     TimeStamp
                    }

appnLsName OBJECT-TYPE
      SYNTAX DisplayString (SIZE (1..10))
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name for the link station.
           The name can be from one to ten characters."

      ::= { appnLsEntry 1 }

appnLsCommand OBJECT-TYPE
      SYNTAX INTEGER {
                      deactivate(1),
                      activate(2),
                      recycle(3),
                      ready(4)
                     }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
          "Object by which a Management Station can activate, deactivate,
          or recycle (i.e., cause to be deactivated and then immediately
          reactivated) a link station, by setting the value to
          activate(1), deactivate(2), or recycle(3), respectively.  The
          value ready(4) is returned on GET operations until a SET has
          been processed; after that the value received on the most
          recent SET is returned."

      ::= { appnLsEntry 2 }

appnLsOperState OBJECT-TYPE
      SYNTAX INTEGER    {
          inactive(1),
          sentConnectOut(2),    -- pending active
          pendXidExch(3),       -- pending active
          sendActAs(4),         -- pending active
```

```
            sendSetMode(5),       -- pending active
            otherPendingActive(6),-- pending active
            active(7),
            sentDeactAsOrd(8),    -- pending inactive
            sentDiscOrd(9),       -- pending inactive
            sentDiscImmed(10),    -- pending inactive
            otherPendingInact(11) -- pending inactive
                        }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "State of this link station.  The comments map these more
            granular states to the 'traditional' four states for SNA
            resources.  Values (2) through (5) represent the normal
            progression of states when a link station is being activated.
            Value (6) represents some other state of a link station in
            the process of being activated.  Values (8) through (10)
            represent different ways a link station can be deactivated.
            Value (11) represents some other state of a link station in
            the process of being deactivated."

        ::= { appnLsEntry 3 }

appnLsPortName OBJECT-TYPE
        SYNTAX DisplayString (SIZE (1..10))
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Administratively assigned name for the port associated with
            this link station.  The name can be from one to ten
            characters."

        ::= { appnLsEntry 4 }

appnLsDlcType OBJECT-TYPE
        SYNTAX IANAifType
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The type of DLC interface, distinguished according to the
            protocol immediately 'below' this layer."

        ::= { appnLsEntry 5 }

appnLsDynamic OBJECT-TYPE
        SYNTAX TruthValue
        MAX-ACCESS read-only
        STATUS current
```

```
      DESCRIPTION
          "Identifies whether this is a dynamic link station.  Dynamic
          link stations are created when links that have not been locally
          defined are established by adjacent nodes."

      ::= { appnLsEntry 6 }

appnLsAdjCpName OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0 | 3..17))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Fully qualified name of the adjacent node for this link
          station.  An adjacent node is identified using the format
          specified in the SnaControlPointName textual convention.

          The value of this object is determined as follows:

             1. If the adjacent node's name was received on XID, it
                is returned.

             2. If the adjacent node's name was not received on XID,
                but a locally-defined value is available, it is
                returned.

             3. Otherwise a string of length 0 is returned, indicating
                that no name is known for the adjacent node."

      ::= { appnLsEntry 7 }

appnLsAdjNodeType OBJECT-TYPE
      SYNTAX INTEGER {
                     networkNode(1),
                     endNode(2),
                     t21len(4),
                     unknown(255)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Node type of the adjacent node on this link:

                networkNode(1) - APPN network node
                endNode(2)     - APPN end node
                t21len(4)      - LEN end node
                unknown(255)   - the agent does not know the node type
                                 of the adjacent node
          "
```

```
      ::= { appnLsEntry 8 }

appnLsTgNum OBJECT-TYPE
      SYNTAX INTEGER (0..256)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number associated with the TG to this link station, with a
          range from 0 to 256.  A value of 256 indicates that the TG
          number has not been negotiated and is unknown at this time."

      ::= { appnLsEntry 9 }

appnLsLimResource OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the link station is a limited resource.  A
          link station that is a limited resource is deactivated when it
          is no longer in use."

      ::= { appnLsEntry 10 }

appnLsActOnDemand OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the link station is activatable on demand.

          Such a link station is reported in the topology as active
          regardless of its actual state, so that it can be considered in
          route calculations.  If the link station is inactive and is
          chosen for a route, it will be activated at that time."

      ::= { appnLsEntry 11 }

appnLsMigration OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this link station will be used for
          connections to down-level or migration partners.

          In general, migration nodes do not append their CP names on
          XID3.  Such nodes:  (1) will not support parallel TGs, (2)
```

```
          should be sent an ACTIVATE PHYSICAL UNIT (ACTPU), provided that
          the partner supports ACTPUs, and (3) should not be sent
          segmented BINDs.  However, if this node receives an XID3 with
          an appended CP name, then the partner node will not be treated
          as a migration node.

           In the case of DYNAMIC TGs this object should be set to 'no'."

      ::= { appnLsEntry 12 }

appnLsPartnerNodeId OBJECT-TYPE
      SYNTAX SnaNodeIdentification
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The partner's Node Identification, from bytes 2-5 of the XID
          received from the partner.  If this value is not available,
          then the characters '00000000' are returned."

      ::= { appnLsEntry 13 }

appnLsCpCpSessionSupport OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether CP-CP sessions are supported by this
          link station.  For a dynamic link, this object represents
          the default ('Admin') value."

      ::= { appnLsEntry 14 }

appnLsMaxSendBtuSize OBJECT-TYPE
      SYNTAX INTEGER (99..32767)
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Numeric value between 99 and 32767 inclusive indicating the
          maximum number of bytes in a Basic Transmission Unit (BTU) sent
          on this link.

          When the link state (returned by the appnLsOperState object) is
          inactive or pending active, the value configured at this node
          is returned.  When the link state is active, the value that was
          negotiated for it is returned.  This negotiated value is the
          smaller of the value configured at this node and the partner's
          maximum receive BTU length, received in XID."
```

```
      ::= { appnLsEntry 15 }

appnLsInXidBytes OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of XID bytes received.  All of the bytes in the SNA
          basic transmission unit (BTU), i.e., all of the bytes in the
          DLC XID Information Field, are counted."

      ::= { appnLsEntry 16 }

appnLsInMsgBytes OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of message (I-frame) bytes received.  All of the bytes
          in the SNA basic transmission unit (BTU), including the
          transmission header (TH), are counted."

      ::= { appnLsEntry 17 }

appnLsInXidFrames OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
      UNITS "XID frames"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of XID frames received."

      ::= { appnLsEntry 18 }

appnLsInMsgFrames OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
      UNITS "I-frames"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of message (I-frame) frames received."

      ::= { appnLsEntry 19 }

appnLsOutXidBytes OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
```

```
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of XID bytes sent.  All of the bytes in the SNA basic
          transmission unit (BTU), i.e., all of the bytes in the DLC XID
          Information Field, are counted."

      ::= { appnLsEntry 20 }

appnLsOutMsgBytes OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of message (I-frame) bytes sent.  All of the bytes
          in the SNA basic transmission unit (BTU), including the
          transmission header (TH), are counted."

      ::= { appnLsEntry 21 }

appnLsOutXidFrames OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
      UNITS "XID frames"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of XID frames sent."

      ::= { appnLsEntry 22 }

appnLsOutMsgFrames OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
      UNITS "I-frames"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of message (I-frame) frames sent."

      ::= { appnLsEntry 23 }

appnLsEchoRsps OBJECT-TYPE
      SYNTAX AppnLinkStationCounter
      UNITS "echo responses"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Number of echo responses returned from adjacent link station.
            A response should be returned for each test frame sent by this
            node.  Test frames are sent to adjacent nodes periodically to
            verify connectivity and to measure the actual round trip time,
            that is, the time interval from when the test frame is sent
            until when the response is received."


        ::= { appnLsEntry 24 }

appnLsCurrentDelay OBJECT-TYPE
        SYNTAX Gauge32
        UNITS "milliseconds"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The time that it took for the last test signal to be sent and
            returned from this link station to the adjacent link station.
            This time is represented in milliseconds."

        ::= { appnLsEntry 25 }

appnLsMaxDelay OBJECT-TYPE
        SYNTAX Gauge32
        UNITS "milliseconds"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The longest time it took for a test signal to be sent and
            returned from this link station to the adjacent link station.
            This time is represented in milliseconds .

            The value 0 is returned if no test signal has been sent and
            returned."

        ::= { appnLsEntry 26 }

appnLsMinDelay OBJECT-TYPE
        SYNTAX Gauge32
        UNITS "milliseconds"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The shortest time it took for a test signal to be sent and
            returned from this link station to the adjacent link station.
            This time is represented in milliseconds.

            The value 0 is returned if no test signal has been sent and
```

```
            returned."

        ::= { appnLsEntry 27 }

appnLsMaxDelayTime OBJECT-TYPE
        SYNTAX DateAndTime
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The time when the longest delay occurred.  This time can be
            used to identify when this high water mark occurred in relation
            to other events in the APPN node, for example, the time at
            which an APPC session was either terminated or failed to be
            established.  This latter time is available in the
            appcHistSessTime object in the APPC MIB.

            The value 00000000 is returned if no test signal has been sent
            and returned."

        ::= { appnLsEntry 28 }

appnLsGoodXids OBJECT-TYPE
        SYNTAX AppnLinkStationCounter
        UNITS "XID exchanges"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The total number of successful XID exchanges that have
            occurred on this link station since the time it was started."

        ::= { appnLsEntry 29 }

appnLsBadXids OBJECT-TYPE
        SYNTAX AppnLinkStationCounter
        UNITS "XID exchanges"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The total number of unsuccessful XID exchanges that have
            occurred on this link station since the time it was started."

        ::= { appnLsEntry 30 }

appnLsSpecific OBJECT-TYPE
        SYNTAX RowPointer
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
```

```
            "Identifies the object, e.g., one in a DLC-specific MIB, that
            can provide additional information related to this link
            station.

            If the agent is unable to identify such an object, the value
            0.0 is returned."

        ::= { appnLsEntry 31 }

appnLsActiveTime OBJECT-TYPE
        SYNTAX Unsigned32
        UNITS "hundredths of a second"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The cumulative amount of time since the node was last re-
            initialzed, measured in hundredths of a second, that this link
            station has been in the active state.  A zero value indicates
            that the link station has never been active since the node was
            last re-initialized."

        ::= { appnLsEntry 32 }

appnLsCurrentStateTime OBJECT-TYPE
        SYNTAX TimeTicks
        UNITS "hundredths of a second"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The amount of time, measured in hundredths of a second, that
            the link station has been in its current state."

        ::= { appnLsEntry 33 }

appnLsHprSup OBJECT-TYPE
        SYNTAX INTEGER {
                    noHprSupport(1),
                    hprBaseOnly(2),
                    rtpTower(3),
                    controlFlowsOverRtpTower(4)
                        }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Indicates the level of high performance routing (HPR) support
            over this link:

               noHprSupport(1)            - no HPR support
```

```
              hprBaseOnly(2)              - HPR base (option set 1400)
                                            supported
              rtpTower(3)                 - HPR base and RTP tower
                                            (option set 1401) supported
              controlFlowsOverRtpTower(4) - HPR base, RTP tower, and
                                            control flows over RTP
                                            (option set 1402) supported

          If the link is not active, the defined value is returned."

      ::= { appnLsEntry 34 }

appnLsErrRecoSup OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the link station is supporting
           HPR link-level error recovery."

      ::= { appnLsEntry 35 }

appnLsForAnrLabel OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..8))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The forward Automatic Network Routing (ANR) label for this
          link station.  If the link does not support HPR or the value is
          unknown, a zero-length string is returned."

      ::= { appnLsEntry 36 }

appnLsRevAnrLabel OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..8))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The reverse Automatic Network Routing (ANR) label for this
          link station.  If the link does not support HPR or the value is
          unknown, a zero-length string is returned."

      ::= { appnLsEntry 37 }

appnLsCpCpNceId OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..8))
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
          "The network connection endpoint identifier (NCE ID) for CP-CP
          sessions if this node supports the HPR transport tower, a
          zero-length string if the value is unknown or not meaningful
          for this node."

      ::= { appnLsEntry 38 }

appnLsRouteNceId OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..8))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The network connection endpoint identifier (NCE ID) for Route
          Setup if this node supports the HPR transport tower, a zero-
          length string if the value is unknown or not meaningful for
          this node."

      ::= { appnLsEntry 39 }

appnLsBfNceId OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..8))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The network connection endpoint identifier (NCE ID) for the
          APPN/HPR boundary function if this node supports the HPR
          transport tower, a zero-length string if the value is unknown
          or not meaningful for this node."

      ::= { appnLsEntry 40 }

appnLsLocalAddr OBJECT-TYPE
      SYNTAX DisplayableDlcAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Local address of this link station."

      ::= { appnLsEntry 41 }


appnLsRemoteAddr OBJECT-TYPE
      SYNTAX DisplayableDlcAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Address of the remote link station on this link."
```

```
      ::= { appnLsEntry 42 }

appnLsRemoteLsName OBJECT-TYPE
      SYNTAX DisplayString (SIZE (0..10))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Remote link station discovered from the XID exchange.
          The name can be from one to ten characters.  A zero-length
          string indicates that the value is not known."

      ::= { appnLsEntry 43 }

appnLsCounterDisconTime OBJECT-TYPE
      SYNTAX TimeStamp
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The value of the sysUpTime object the last time the link
          station was started."

      ::= { appnLsEntry 44 }



--**********************************************************************
-- This table provides information about errors this node encountered
-- with connections to adjacent nodes.  Entries are added for exceptional
-- conditions encountered establishing connections and exceptional
-- conditions that resulted in termination of a connection.  It is an
-- implementation option how many entries to keep in this table, and
-- how long to retain any individual entry.
--**********************************************************************

appnLsStatusTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnLsStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "This table contains information related to exceptional and
          potentially exceptional conditions that occurred during the
          activation, XID exchange, and termination of a connection.  No
          entries are created when these activities proceed normally."

      ::= { appnLinkStationInformation 2 }

appnLsStatusEntry OBJECT-TYPE
      SYNTAX AppnLsStatusEntry
```

```
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "This table is indexed by the LsStatusIndex, which is an
          integer that is continuously updated until it eventually
          wraps."

      INDEX
             { appnLsStatusIndex }

      ::= { appnLsStatusTable 1 }

AppnLsStatusEntry ::= SEQUENCE {
      appnLsStatusIndex              INTEGER,
      appnLsStatusTime               DateAndTime,
      appnLsStatusLsName             DisplayString,
      appnLsStatusCpName             DisplayString,
      appnLsStatusPartnerId          SnaNodeIdentification,
      appnLsStatusTgNum              INTEGER,
      appnLsStatusGeneralSense       SnaSenseData,
      appnLsStatusRetry              TruthValue,
      appnLsStatusEndSense           SnaSenseData,
      appnLsStatusXidLocalSense      SnaSenseData,
      appnLsStatusXidRemoteSense     SnaSenseData,
      appnLsStatusXidByteInError     INTEGER,
      appnLsStatusXidBitInError      INTEGER,
      appnLsStatusDlcType            IANAifType,
      appnLsStatusLocalAddr          DisplayableDlcAddress,
      appnLsStatusRemoteAddr         DisplayableDlcAddress
                    }


appnLsStatusIndex OBJECT-TYPE
      SYNTAX INTEGER (0..2147483647)
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Table index.  The value of the index begins at zero
           and is incremented up to a maximum value of 2**31-1
           (2,147,483,647) before wrapping."

      ::= { appnLsStatusEntry 1 }

appnLsStatusTime OBJECT-TYPE
      SYNTAX DateAndTime
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Time when the exception condition occurred.  This time can be
            used to identify when this event occurred in relation to other
            events in the APPN node, for example, the time at which an APPC
            session was either terminated or failed to be established.
            This latter time is available in the appcHistSessTime object in
            the APPC MIB."

        ::= { appnLsStatusEntry 2 }

appnLsStatusLsName OBJECT-TYPE
        SYNTAX DisplayString (SIZE (1..10))
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Administratively assigned name for the link station
            experiencing the condition."

        ::= { appnLsStatusEntry 3 }

appnLsStatusCpName OBJECT-TYPE
        SYNTAX DisplayString (SIZE (0 | 3..17))
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Fully qualified name of the adjacent node for this link
            station.  An adjacent node is identified using the format
            specified in the SnaControlPointName textual convention.

            The value of this object is determined as follows:

               1. If the adjacent node's name was received on XID, it
                  is returned.

               2. If the adjacent node's name was not received on XID,
                  but a locally-defined value is available, it is
                  returned.

               3. Otherwise a string of length 0 is returned, indicating
                  that no name is known for the adjacent node."

        ::= { appnLsStatusEntry 4 }

appnLsStatusPartnerId OBJECT-TYPE
        SYNTAX SnaNodeIdentification
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The partner's Node Identification, from bytes 2-5 of the XID
```

```
            received from the partner.  If this value is not available,
            then the characters '00000000' are returned."

        ::= { appnLsStatusEntry 5 }

appnLsStatusTgNum OBJECT-TYPE
        SYNTAX INTEGER (0..256)
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Number associated with the TG to this link station, with a
            range from 0 to 256.  A value of 256 indicates that the TG
            number was unknown at the time of the failure."

        ::= { appnLsStatusEntry 6 }

appnLsStatusGeneralSense OBJECT-TYPE
        SYNTAX SnaSenseData
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The error sense data associated with the start sequence of
            activation of a link up to the beginning of the XID sequence.

            This is the sense data that came from Configuration Services
            whenever the link did not activate or when it went inactive."

        ::= { appnLsStatusEntry 7 }

appnLsStatusRetry OBJECT-TYPE
        SYNTAX TruthValue
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Indicates whether the node will retry the start request to
            activate the link."

        ::= { appnLsStatusEntry 8 }

appnLsStatusEndSense OBJECT-TYPE
        SYNTAX SnaSenseData
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The sense data associated with the termination of the link
            connection to adjacent node.

            This is the sense data that came from the DLC layer."
```

```
      ::= { appnLsStatusEntry 9 }

appnLsStatusXidLocalSense OBJECT-TYPE
      SYNTAX SnaSenseData
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The sense data associated with the rejection of the XID.

          This is the sense data that came from the local node (this
          node) when it built the XID Negotiation Error control vector
          (cv22) to send to the remote node."

      ::= { appnLsStatusEntry 10 }

appnLsStatusXidRemoteSense OBJECT-TYPE
      SYNTAX SnaSenseData
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The sense data the adjacent node returned to this node
          indicating the reason the XID was rejected.

          This is the sense data that came from the remote node in the
          XID Negotiation Error control vector (cv22) it sent to the
          local node (this node)."

      ::= { appnLsStatusEntry 11 }

appnLsStatusXidByteInError OBJECT-TYPE
      SYNTAX INTEGER (0..65536)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "This object identifies the actual byte in the XID that caused
          the error.  The value 65536 indicates that the object has no
          meaning.

          For values in the range 0-65535, this object corresponds to
          bytes 2-3 of the XID Negotiation (X'22') control vector."

      ::= { appnLsStatusEntry 12 }

appnLsStatusXidBitInError OBJECT-TYPE
      SYNTAX INTEGER (0..8)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "This object identifies the actual bit in error (0 through 7)
            within the errored byte of the XID.  The value 8 indicates that
            this object has no meaning.

            For values in the range 0-7, this object corresponds to byte 4
            of the XID Negotiation (X'22') control vector."

        ::= { appnLsStatusEntry 13 }

appnLsStatusDlcType OBJECT-TYPE
        SYNTAX IANAifType
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The type of DLC interface, distinguished according to the
            protocol immediately 'below' this layer."

        ::= { appnLsStatusEntry 14 }

appnLsStatusLocalAddr OBJECT-TYPE
        SYNTAX DisplayableDlcAddress
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Local address of this link station."

        ::= { appnLsStatusEntry 15 }

appnLsStatusRemoteAddr OBJECT-TYPE
        SYNTAX DisplayableDlcAddress
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Address of the remote link station on this link."

        ::= { appnLsStatusEntry 16 }

-- ****************************************************************
-- APPN Virtual Routing Node Information
--

appnVrnTable OBJECT-TYPE
        SYNTAX SEQUENCE OF AppnVrnEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "This table relates a virtual routing node to an APPN port."
```

```
      ::= { appnVrnInfo 1 }

appnVrnEntry OBJECT-TYPE
      SYNTAX AppnVrnEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "This table is indexed by the virtual routing node name, TG
          number, and port name.  There will be a matching entry in the
          appnLocalTgTable to represent status and characteristics of the
          TG representing each virtual routing node definition."

      INDEX
             { appnVrnName, appnVrnTgNum, appnVrnPortName }

      ::= { appnVrnTable 1 }

AppnVrnEntry ::= SEQUENCE {
      appnVrnName             SnaControlPointName,
      appnVrnTgNum            INTEGER,
      appnVrnPortName         DisplayString
}

appnVrnName OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name of the virtual routing node.
          This is a fully qualified name, and matches the appnLocalTgDest
          name in the appnLocalTgTable."

      ::= { appnVrnEntry 1 }

appnVrnTgNum OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Number associated with the transmission group representing
          this virtual routing node definition."

      ::= { appnVrnEntry 2 }

appnVrnPortName OBJECT-TYPE
      SYNTAX DisplayString (SIZE (1..10))
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
          "The name of the port this virtual routing node definition is
          defined to."

      ::= { appnVrnEntry 3 }

-- ************** The APPN Topology Group ******************************

appnNn                OBJECT IDENTIFIER ::= { appnObjects 2 }
appnNnTopo          OBJECT IDENTIFIER ::= { appnNn 1 }
appnNnTopology      OBJECT IDENTIFIER ::= { appnNn 2 }

-- This group is used to represent the entire APPN network-node topology
-- including network nodes, virtual routing nodes and all TGs associated
-- with these nodes.
--
-- Network nodes
-- The APPN topology database consists of information about every APPN
-- network node in this network node's topology subnetwork.  This
-- information is learned over time as each network node exchanges
-- topology information with the network nodes adjacent to it.  The
-- database consists of information about each node, and information
-- about all of the transmission groups used by these nodes.
--
-- Virtual routing nodes
-- Information about virtual routing nodes (representing connection
-- networks) is treated in the same way as information about network
-- nodes, and is replicated at each network node.  The FRSN, node name,
-- and node type are the only meaningful fields for a virtual routing
-- node.  The other node objects return unspecified values.  Each
-- node that has defined a TG with this virtual routing node as the
-- destination also defines a TG on this virtual routing node.  There
-- is a TG record for each node that uses this virtual routing node.
--
-- The APPN node table represents node information from the APPN topology
-- database, with the FRSN and APPN CP fully qualified name serving as
-- the index.  The FRSN is the agent's relative time stamp of an update
-- to the network topology database.  After collecting the entire database
-- once, a management application can issue GET NEXT commands starting
-- from the last rows it has retrieved from the appnNnTopologyFRTable and
-- from the appnNnTgTopologyFRTable.  When the response to either of these
-- GET NEXT commands returns another row of its respective table, this
-- indicates a change to the agent's topology database.  The management
-- application can then retrieve only the updates to the table, using
-- GET NEXT commands starting from the last retrieved node or TG
-- entry.
--
-- The format of the actual APPN topology database is as follows:
```

```
--
-- Node table (entry for each node in network)
--   TG table (entry for each TG owned by node)
--
-- Due to SNMP's ASN.1 limitations, we cannot represent the TG table
-- within the node table in this way.  We define separate tables for
-- nodes and TGs, adding the node name to each TG entry to provide a
-- means of correlating the TG with its originating node.

appnNnTopoMaxNodes OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "node entries"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum number of node entries allowed in the APPN topology
          database.  It is an implementation choice whether to count only
          network-node entries, or to count all node entries.  If the
          number of node entries exceeds this value, APPN will issue an
          Alert and the node can no longer participate as a network node.
          The value 0 indicates that the local node has no defined limit,
          and the number of node entries is bounded only by memory."

      ::= { appnNnTopo 1 }

appnNnTopoCurNumNodes OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "node entries"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Current number of node entries in this node's topology
          database.  It is an implementation choice whether to count only
          network-node entries, or to count all node entries, but an
          implementation must make the same choice here that it makes for
          the appnNnTopoMaxNodes object.  If this value exceeds the
          maximum number of nodes allowed (appnNnTopoMaxNodes, if that
          field in not 0), APPN Alert CPDB002 is issued."

      ::= { appnNnTopo 2 }

appnNnTopoNodePurges OBJECT-TYPE
      SYNTAX AppnNodeCounter
      UNITS "node entries"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Total number of topology node records purged from this node's
```

```
            topology database since the node was last re-initialized."

        ::= { appnNnTopo 3 }

appnNnTopoTgPurges OBJECT-TYPE
        SYNTAX AppnNodeCounter
        UNITS "TG entries"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Total number of topology TG records purged from this node's
            topology database since the node was last re-initialized."

        ::= { appnNnTopo 4 }

appnNnTopoTotalTduWars OBJECT-TYPE
        SYNTAX AppnNodeCounter
        UNITS "TDU wars"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Number of TDU wars detected by this node since its last
            initialization."

        ::= { appnNnTopo 5 }



-- APPN network node topology table (using FRSN and name as index)

-- This table describes every APPN network node and virtual routing node
-- represented in this node's topology database.

appnNnTopologyFRTable OBJECT-TYPE
        SYNTAX SEQUENCE OF AppnNnTopologyFREntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "Portion of the APPN topology database that describes all of
            the APPN network nodes and virtual routing nodes known to this
            node."

        ::= { appnNnTopology 3 }

appnNnTopologyFREntry OBJECT-TYPE
        SYNTAX AppnNnTopologyFREntry
        MAX-ACCESS not-accessible
        STATUS current
```

```
      DESCRIPTION
          "The FRSN and the fully qualified node name are used to index
          this table."

      INDEX
             {appnNnNodeFRFrsn,
              appnNnNodeFRName}

      ::= { appnNnTopologyFRTable 1 }

AppnNnTopologyFREntry ::= SEQUENCE {
      appnNnNodeFRFrsn                    Unsigned32,
      appnNnNodeFRName                    SnaControlPointName,
      appnNnNodeFREntryTimeLeft           AppnTopologyEntryTimeLeft,
      appnNnNodeFRType                    INTEGER,

      appnNnNodeFRRsn                     Unsigned32,
      appnNnNodeFRRouteAddResist          INTEGER,
      appnNnNodeFRCongested               TruthValue,
      appnNnNodeFRIsrDepleted             TruthValue,
      appnNnNodeFRQuiescing               TruthValue,
      appnNnNodeFRGateway                 TruthValue,
      appnNnNodeFRCentralDirectory        TruthValue,
      appnNnNodeFRIsr                     TruthValue,
      appnNnNodeFRGarbageCollect          TruthValue,

      appnNnNodeFRHprSupport              INTEGER,
      appnNnNodeFRPeriBorderSup           TruthValue,
      appnNnNodeFRInterchangeSup          TruthValue,
      appnNnNodeFRExteBorderSup           TruthValue
}

appnNnNodeFRFrsn OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Flow reduction sequence numbers (FRSNs) are associated with
          Topology Database Updates (TDUs) and are unique only within
          each APPN network node.  A TDU can be associated with multiple
          APPN resources.  This FRSN indicates the last relative time
          this resource was updated at the agent node."

      ::= { appnNnTopologyFREntry 1 }

appnNnNodeFRName OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
          "Administratively assigned network name that is locally defined
          at each network node."

      ::= { appnNnTopologyFREntry 2 }

appnNnNodeFREntryTimeLeft OBJECT-TYPE
      SYNTAX AppnTopologyEntryTimeLeft
      UNITS "days"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of days before deletion of this network node entry."

      ::= { appnNnTopologyFREntry 3 }

appnNnNodeFRType OBJECT-TYPE
      SYNTAX INTEGER {
                     networkNode(1),
                     virtualRoutingNode(3)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Type of APPN node."

      ::= { appnNnTopologyFREntry 4 }

appnNnNodeFRRsn OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Resource sequence number, which is assigned and controlled by
          the network node that owns this resource.  An odd number
          indicates that information about the resource is inconsistent.

          This object corresponds to the numeric value in cv4580, bytes
          2-5."

      ::= { appnNnTopologyFREntry 5 }

appnNnNodeFRRouteAddResist OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
          "Route addition resistance.

          This administratively assigned value indicates the relative
          desirability of using this node for intermediate session
          traffic.  The value, which can be any integer 0-255, is used
          in route computation.  The lower the value, the more
          desirable the node is for intermediate routing.

          This object corresponds to cv4580, byte 6."

      ::= { appnNnTopologyFREntry 6 }

appnNnNodeFRCongested OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node is congested.  This node is not be
          included in route selection by other nodes when this congestion
          exists.

          This object corresponds to cv4580, byte 7, bit 0."

      ::= { appnNnTopologyFREntry 7 }

appnNnNodeFRIsrDepleted OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether intermediate session routing resources are
          depleted.  This node is not included in intermediate route
          selection by other nodes when resources are depleted.

          This object corresponds to cv4580, byte 7, bit 1."

      ::= { appnNnTopologyFREntry 8 }

appnNnNodeFRQuiescing OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node is quiescing.  This node is not
          included in route selection by other nodes when the node is
          quiescing.

          This object corresponds to cv4580, byte 7, bit 5."
```

```
      ::= { appnNnTopologyFREntry 9 }

appnNnNodeFRGateway OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node provide gateway services.

          This object corresponds to cv4580, byte 8, bit 0."


      ::= { appnNnTopologyFREntry 10 }

appnNnNodeFRCentralDirectory OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node supports central directory
          services.

          This object corresponds to cv4580, byte 8, bit 1."


      ::= { appnNnTopologyFREntry 11 }

appnNnNodeFRIsr OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node supports intermediate session
          routing (ISR).

          This object corresponds to cv4580, byte 8, bit 2."

      ::= { appnNnTopologyFREntry 12 }

appnNnNodeFRGarbageCollect OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the node has been marked for garbage
          collection (deletion from the topology database) upon the next
          garbage collection cycle.
```

```
          This object corresponds to cv4580, byte 7, bit 3."

      ::= { appnNnTopologyFREntry 13 }

appnNnNodeFRHprSupport OBJECT-TYPE
      SYNTAX INTEGER {
                 noHprSupport(1),
                 hprBaseOnly(2),
                 rtpTower(3),
                 controlFlowsOverRtpTower(4)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates the node's level of support for high-performance
          routing (HPR):

             noHprSupport(1)             - no HPR support
             hprBaseOnly(2)              - HPR base (option set 1400)
                                           supported
             rtpTower(3)                 - HPR base and RTP tower
                                           (option set 1401) supported
             controlFlowsOverRtpTower(4) - HPR base, RTP tower, and
                                           control flows over RTP
                                           (option set 1402) supported

          This object corresponds to cv4580, byte 9, bits 3-4."

      ::= { appnNnTopologyFREntry 14 }

appnNnNodeFRPeriBorderSup OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node has peripheral border node
          support.

          This object corresponds to cv4580, byte 9, bit 0."

      ::= { appnNnTopologyFREntry 15 }

appnNnNodeFRInterchangeSup OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node has interchange node support.
```

```
          This object corresponds to cv4580, byte 9, bit 1."

      ::= { appnNnTopologyFREntry 16 }

appnNnNodeFRExteBorderSup OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether this node has extended border node
           support.

          This object corresponds to cv4580, byte 9, bit 2."

      ::= { appnNnTopologyFREntry 17 }


--APPN transmission group (TG) table

-- This table describes the TGs associated with all the APPN network
-- nodes known to this node.   The originating (owning) node for each
-- TG is repeated here to provide a means of correlating the TGs with
-- the nodes.


appnNnTgTopologyFRTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnNnTgTopologyFREntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Portion of the APPN topology database that describes all of
          the APPN transmissions groups between nodes in the database."

      ::= { appnNnTopology 4 }

appnNnTgTopologyFREntry OBJECT-TYPE
      SYNTAX AppnNnTgTopologyFREntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "This table is indexed by four columns:  FRSN, TG owner fully
          qualified node name, TG destination fully qualified node name,
          and TG number."

      INDEX
             {appnNnTgFRFrsn,
              appnNnTgFROwner,
              appnNnTgFRDest,
```

```
               appnNnTgFRNum}

      ::= { appnNnTgTopologyFRTable 1 }

AppnNnTgTopologyFREntry ::= SEQUENCE {

      appnNnTgFRFrsn           Unsigned32,
      appnNnTgFROwner          SnaControlPointName,
      appnNnTgFRDest           SnaControlPointName,
      appnNnTgFRNum            INTEGER,
      appnNnTgFREntryTimeLeft  AppnTopologyEntryTimeLeft,

      appnNnTgFRDestVirtual    TruthValue,
      appnNnTgFRDlcData        AppnTgDlcData,

      appnNnTgFRRsn            Unsigned32,
      appnNnTgFROperational    TruthValue,
      appnNnTgFRQuiescing      TruthValue,
      appnNnTgFRCpCpSession    INTEGER,
      appnNnTgFREffCap         AppnTgEffectiveCapacity,
      appnNnTgFRConnCost       INTEGER,
      appnNnTgFRByteCost       INTEGER,
      appnNnTgFRSecurity       AppnTgSecurity,
      appnNnTgFRDelay          AppnTgDelay,
      appnNnTgFRUsr1           INTEGER,
      appnNnTgFRUsr2           INTEGER,
      appnNnTgFRUsr3           INTEGER,
      appnNnTgFRGarbageCollect TruthValue,
      appnNnTgFRSubareaNum     Unsigned32,

      appnNnTgFRHprSup         TruthValue,
      appnNnTgFRDestHprTrans   TruthValue,
      appnNnTgFRTypeIndicator  INTEGER,
      appnNnTgFRIntersubnet    TruthValue
}


appnNnTgFRFrsn OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Flow reduction sequence numbers (FRSNs) are associated with
          Topology Database Updates (TDUs) and are unique only within
          each APPN network node.  A TDU can be associated with multiple
          APPN resources.  This FRSN indicates the last time this
          resource was updated at this node."
```

```
      ::= { appnNnTgTopologyFREntry 1 }

appnNnTgFROwner OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name for the originating node for
          this TG.  This is the same name specified in the node table."

      ::= { appnNnTgTopologyFREntry 2 }

appnNnTgFRDest OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned fully qualified network name for the
          destination node for this TG."

      ::= { appnNnTgTopologyFREntry 3 }

appnNnTgFRNum OBJECT-TYPE
      SYNTAX INTEGER  (0..255)
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Number associated with this transmission group.  Range is
          0-255."

      ::= { appnNnTgTopologyFREntry 4 }

appnNnTgFREntryTimeLeft OBJECT-TYPE
      SYNTAX AppnTopologyEntryTimeLeft
      UNITS "days"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of days before deletion of this network node TG entry
          if it is not operational or has an odd (inconsistent) RSN."

      ::= { appnNnTgTopologyFREntry 5 }

appnNnTgFRDestVirtual OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Indicates whether the destination node is a virtual routing
            node."

        ::= { appnNnTgTopologyFREntry 6 }

appnNnTgFRDlcData OBJECT-TYPE
        SYNTAX AppnTgDlcData
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "DLC-specific data related to a link connection network."

        ::= { appnNnTgTopologyFREntry 7 }

appnNnTgFRRsn OBJECT-TYPE
        SYNTAX Unsigned32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Current owning node's resource sequence number for this
            resource.  An odd number indicates that information about the
            resource is inconsistent.

            This object corresponds to the numeric value in cv47, bytes
            2-5"

        ::= { appnNnTgTopologyFREntry 8 }

appnNnTgFROperational OBJECT-TYPE
        SYNTAX TruthValue
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Indicates whether the transmission group is operational.

            This object corresponds to cv47, byte 6, bit 0."

        ::= { appnNnTgTopologyFREntry 9 }

appnNnTgFRQuiescing OBJECT-TYPE
        SYNTAX TruthValue
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Indicates whether the transmission group is quiescing.

            This object corresponds to cv47, byte 6, bit 2."
```

```
      ::= { appnNnTgTopologyFREntry 10 }

appnNnTgFRCpCpSession OBJECT-TYPE
      SYNTAX INTEGER {
                     supportedUnknownStatus(1),
                     supportedActive(2),
                     notSupported(3),
                     supportedNotActive(4)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether CP-CP sessions are supported on this TG, and
          whether the TG owner's contention-winner session is active on
          this TG.  Some nodes in the network are not able to
          differentiate support and status of CP-CP sessions, and thus
          may report the 'supportedUnknownStatus' value.

          This object corresponds to cv47, byte 6, bits 3-4."

      ::= { appnNnTgTopologyFREntry 11 }


appnNnTgFREffCap OBJECT-TYPE
      SYNTAX AppnTgEffectiveCapacity
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Effective capacity for this TG."

      ::= { appnNnTgTopologyFREntry 12 }

appnNnTgFRConnCost OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Cost per connect time.

          This is an administratively assigned value representing the
          relative cost per unit of time to use this TG.  Range is from
          0, which means no cost, to 255, which indicates maximum cost.

          This object corresponds to cv47, byte 13."

      ::= { appnNnTgTopologyFREntry 13 }

appnNnTgFRByteCost OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Cost per byte transmitted.

          This is an administratively assigned value representing the
          relative cost of transmitting a byte over this TG.  Range is
          from 0, which means no cost, to 255, which indicates maximum
          cost.

          This object corresponds to cv47, byte 14."

      ::= { appnNnTgTopologyFREntry 14 }

appnNnTgFRSecurity OBJECT-TYPE
      SYNTAX AppnTgSecurity
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Administratively assigned security level of this TG.

          This object corresponds to cv47, byte 16."

      ::= { appnNnTgTopologyFREntry 15 }

appnNnTgFRDelay OBJECT-TYPE
      SYNTAX AppnTgDelay
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Administratively assigned delay associated with this TG.

          This object corresponds to cv47, byte 17."

      ::= { appnNnTgTopologyFREntry 16 }

appnNnTgFRUsr1 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "First user-defined TG characteristic for this TG.  This is
          an administratively assigned value associated with the TG.

          This object corresponds to cv47, byte 19."

      ::= { appnNnTgTopologyFREntry 17 }
```

```
appnNnTgFRUsr2 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Second user-defined TG characteristic for this TG.  This is
          an administratively assigned value associated with the TG.

          This object corresponds to cv47, byte 20."

      ::= { appnNnTgTopologyFREntry 18 }

appnNnTgFRUsr3 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Third user-defined TG characteristic for this TG.  This is
          an administratively assigned value associated with the TG.

          This object corresponds to cv47, byte 21."

      ::= { appnNnTgTopologyFREntry 19 }

appnNnTgFRGarbageCollect OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the TG has been marked for garbage
          collection (deletion from the topology database) upon the next
          garbage collection cycle.

          This object corresponds to cv47, byte 6, bit 1."

      ::= { appnNnTgTopologyFREntry 20 }

appnNnTgFRSubareaNum OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The subarea number associated with this TG.

          This object corresponds to cv4680, bytes m+2 through m+5."

      ::= { appnNnTgTopologyFREntry 21 }
```

```
appnNnTgFRHprSup OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether high performance routing (HPR)
          is supported over this TG.

          This object corresponds to cv4680, byte m+1, bit 2."

      ::= { appnNnTgTopologyFREntry 22 }

appnNnTgFRDestHprTrans OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the destination node supports
          high performance routing (HPR) transport tower.

          This object corresponds to cv4680, byte m+1, bit 7."

      ::= { appnNnTgTopologyFREntry 23 }

appnNnTgFRTypeIndicator OBJECT-TYPE
      SYNTAX INTEGER {
                      unknown(1),
                      appnOrBfTg(2),
                      interchangeTg(3),
                      virtualRouteTg(4)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates the type of the TG.

          This object corresponds to cv4680, byte m+1, bits 3-4."

      ::= { appnNnTgTopologyFREntry 24 }

appnNnTgFRIntersubnet OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the transmission group is an intersubnet TG,
          which defines a border between subnetworks.
```

```
          This object corresponds to cv4680, byte m+1, bit 5."

      ::= { appnNnTgTopologyFREntry 25 }

-- ************** The APPN Local Topology Group ************************
-- This MIB Group represents the local topology maintained in
-- both APPN end nodes and network nodes.  It consists of two
-- tables:
--    - a table containing information about all of the TGs owned
--      by this node, which is implemented by all node types.
--    - a table containing all of the information known to this node
--      about the TGs owned by its end nodes, which is implemented only
--      by network nodes.

appnLocalTopology     OBJECT IDENTIFIER ::= { appnObjects 3 }

-- APPN Local Transmission Group (TG) table
-- This table describes the TGs associated with this node only.

appnLocalTgTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnLocalTgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "TG Table describes all of the TGs owned by this node.  The TG
          destination can be a virtual node, network node, LEN node, or
          end node."

      ::= { appnLocalTopology 1 }

appnLocalTgEntry OBJECT-TYPE
      SYNTAX AppnLocalTgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "This table is indexed by the destination CPname and the TG
          number."

      INDEX
             {appnLocalTgDest,
              appnLocalTgNum}

      ::= { appnLocalTgTable 1 }

AppnLocalTgEntry ::= SEQUENCE {

      appnLocalTgDest         SnaControlPointName,
      appnLocalTgNum          INTEGER,
```

```
      appnLocalTgDestVirtual  TruthValue,
      appnLocalTgDlcData      AppnTgDlcData,
      appnLocalTgPortName     DisplayString,

      appnLocalTgQuiescing    TruthValue,
      appnLocalTgOperational  TruthValue,
      appnLocalTgCpCpSession  INTEGER,
      appnLocalTgEffCap       AppnTgEffectiveCapacity,
      appnLocalTgConnCost     INTEGER,
      appnLocalTgByteCost     INTEGER,
      appnLocalTgSecurity     AppnTgSecurity,
      appnLocalTgDelay        AppnTgDelay,
      appnLocalTgUsr1         INTEGER,
      appnLocalTgUsr2         INTEGER,
      appnLocalTgUsr3         INTEGER,

      appnLocalTgHprSup       INTEGER,
      appnLocalTgIntersubnet  TruthValue
                    }

appnLocalTgDest OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name of the destination node for
          this TG.  This is the fully qualified name of a network node,
          end node, LEN node, or virtual routing node."

      ::= { appnLocalTgEntry 1 }

appnLocalTgNum OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Number associated with this transmission group."

      ::= { appnLocalTgEntry 2 }

appnLocalTgDestVirtual OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the destination node for this TG is a
          virtual routing node."
```

```
      ::= { appnLocalTgEntry 3 }

appnLocalTgDlcData OBJECT-TYPE
      SYNTAX AppnTgDlcData
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "DLC-specific data related to a link connection network."

      ::= { appnLocalTgEntry 4 }

appnLocalTgPortName OBJECT-TYPE
      SYNTAX DisplayString (SIZE (0..10))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Administratively assigned name for the local port associated
          with this TG.  A zero-length string indicates that this value
          is unknown."

      ::= { appnLocalTgEntry 5 }

appnLocalTgQuiescing OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the transmission group is quiescing."

      ::= { appnLocalTgEntry 6 }

appnLocalTgOperational OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the transmission group is operational."

      ::= { appnLocalTgEntry 7 }

appnLocalTgCpCpSession OBJECT-TYPE
      SYNTAX INTEGER {
                     supportedUnknownStatus(1),
                     supportedActive(2),
                     notSupported(3),
                     supportedNotActive(4)
                     }
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
          "Indicates whether CP-CP sessions are supported on this TG, and
          whether the TG owner's contention-winner session is active on
          this TG.  Some nodes in the network are not able to
          differentiate support and status of CP-CP sessions, and thus
          may report the 'supportedUnknownStatus' value."

      ::= { appnLocalTgEntry 8 }

appnLocalTgEffCap OBJECT-TYPE
      SYNTAX AppnTgEffectiveCapacity
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Effective capacity for this TG."

      ::= { appnLocalTgEntry 9 }

appnLocalTgConnCost OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Cost per connect time:  a value representing the relative cost
          per unit of time to use the TG.  Range is from 0, which means
          no cost, to 255."

      ::= { appnLocalTgEntry 10 }

appnLocalTgByteCost OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Relative cost of transmitting a byte over this link.
          Range is from 0 (lowest cost) to 255."

      ::= { appnLocalTgEntry 11 }

appnLocalTgSecurity OBJECT-TYPE
      SYNTAX AppnTgSecurity
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Administratively assigned security level of this TG."

      ::= { appnLocalTgEntry 12 }
```

```
appnLocalTgDelay OBJECT-TYPE
      SYNTAX AppnTgDelay
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Administratively assigned delay associated with this TG."

      ::= { appnLocalTgEntry 13 }

appnLocalTgUsr1 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "First user-defined TG characteristic for this TG.  This is
          an administratively assigned value associated with the TG."

      ::= { appnLocalTgEntry 14 }

appnLocalTgUsr2 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Second user-defined TG characteristic for this TG.  This is
          an administratively assigned value associated with the TG."

      ::= { appnLocalTgEntry 15 }

appnLocalTgUsr3 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Third user-defined TG characteristic for this TG.  This is
          an administratively assigned value associated with the TG."

      ::= { appnLocalTgEntry 16 }

appnLocalTgHprSup OBJECT-TYPE
      SYNTAX INTEGER {
                 noHprSupport(1),
                 hprBaseOnly(2),
                 rtpTower(3),
                 controlFlowsOverRtpTower(4)
                     }
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
          "Indicates the level of high performance routing (HPR) support
          over this TG :

             noHprSupport(1)             - no HPR support
             hprBaseOnly(2)              - HPR base (option set 1400)
                                           supported
             rtpTower(3)                 - HPR base and RTP tower
                                           (option set 1401) supported
             controlFlowsOverRtpTower(4) - HPR base, RTP tower, and
                                           control flows over RTP
                                           (option set 1402) supported"

      ::= { appnLocalTgEntry 17 }

appnLocalTgIntersubnet OBJECT-TYPE
      SYNTAX TruthValue
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether the transmission group is an intersubnet TG,
          which defines a border between subnetworks."

      ::= { appnLocalTgEntry 18 }


-- APPN Local End Node Transmission Group (TG) table
-- This table describes the TGs associated with all of the end nodes
-- known to this node.

appnLocalEnTgTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnLocalEnTgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Table describing all of the TGs owned by the end nodes known
          to this node via TG registration.  This node does not represent
          its own view of the TG on behalf of the partner node in this
          table.  The TG destination can be a virtual routing node,
          network node, or end node."

      ::= { appnLocalTopology 2 }

appnLocalEnTgEntry OBJECT-TYPE
      SYNTAX AppnLocalEnTgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
```

```
          "This table requires multiple indexes to uniquely identify each
          TG.  They are originating CPname, destination CPname, and the
          TG number."

      INDEX
             {appnLocalEnTgOrigin,
              appnLocalEnTgDest,
              appnLocalEnTgNum}

      ::= { appnLocalEnTgTable 1 }

AppnLocalEnTgEntry ::= SEQUENCE {
      appnLocalEnTgOrigin        SnaControlPointName,
      appnLocalEnTgDest          SnaControlPointName,
      appnLocalEnTgNum           INTEGER,
      appnLocalEnTgEntryTimeLeft AppnTopologyEntryTimeLeft,

      appnLocalEnTgDestVirtual   TruthValue,
      appnLocalEnTgDlcData       AppnTgDlcData,

      appnLocalEnTgOperational   TruthValue,
      appnLocalEnTgCpCpSession   INTEGER,
      appnLocalEnTgEffCap        AppnTgEffectiveCapacity,
      appnLocalEnTgConnCost      INTEGER,
      appnLocalEnTgByteCost      INTEGER,
      appnLocalEnTgSecurity      AppnTgSecurity,
      appnLocalEnTgDelay         AppnTgDelay,
      appnLocalEnTgUsr1          INTEGER,
      appnLocalEnTgUsr2          INTEGER,
      appnLocalEnTgUsr3          INTEGER
                    }

appnLocalEnTgOrigin OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name of the origin node for this
          TG.  This is a fully qualified network name."

      ::= { appnLocalEnTgEntry 1 }

appnLocalEnTgDest OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name of the destination node for
```

```
            this TG.  This is the fully qualified name of a network node,
            end node, LEN node, or virtual routing node."

        ::= { appnLocalEnTgEntry 2 }

appnLocalEnTgNum OBJECT-TYPE
        SYNTAX INTEGER (0..255)
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "Number associated with this transmission group."

        ::= { appnLocalEnTgEntry 3 }

appnLocalEnTgEntryTimeLeft OBJECT-TYPE
        SYNTAX AppnTopologyEntryTimeLeft
        UNITS "days"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Number of days before deletion of this end node TG entry."

        ::= { appnLocalEnTgEntry 4 }

appnLocalEnTgDestVirtual OBJECT-TYPE
        SYNTAX TruthValue
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Indicates whether the destination node is a virtual routing
            node."

        ::= { appnLocalEnTgEntry 5 }

appnLocalEnTgDlcData OBJECT-TYPE
        SYNTAX AppnTgDlcData
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "DLC-specific data related to a link connection network."

        ::= { appnLocalEnTgEntry 6 }

appnLocalEnTgOperational OBJECT-TYPE
        SYNTAX TruthValue
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
```

```
            "Indicates whether the transmission group is operational."

        ::= { appnLocalEnTgEntry 7 }

appnLocalEnTgCpCpSession OBJECT-TYPE
        SYNTAX INTEGER {
                        supportedUnknownStatus(1),
                        supportedActive(2),
                        notSupported(3),
                        supportedNotActive(4)
                        }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Indicates whether CP-CP sessions are supported on this TG, and
            whether the TG owner's contention-winner session is active on
            this TG.  Some nodes in the network are not able to
            differentiate support and status of CP-CP sessions, and thus
            may report the 'supportedUnknownStatus' value."

        ::= { appnLocalEnTgEntry 8 }

appnLocalEnTgEffCap OBJECT-TYPE
        SYNTAX AppnTgEffectiveCapacity
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Effective capacity for this TG."

        ::= { appnLocalEnTgEntry 9 }

appnLocalEnTgConnCost OBJECT-TYPE
        SYNTAX INTEGER (0..255)
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Cost per connect time:  a value representing the relative cost
            per unit of time to use the TG.  Range is from 0, which means
            no cost, to 255."

        ::= { appnLocalEnTgEntry 10 }

appnLocalEnTgByteCost OBJECT-TYPE
        SYNTAX INTEGER (0..255)
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Relative cost of transmitting a byte over this link.
```

```
          Range is from 0, which means no cost, to 255."

      ::= { appnLocalEnTgEntry 11 }

appnLocalEnTgSecurity OBJECT-TYPE
      SYNTAX AppnTgSecurity
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Administratively assigned security level of this TG."

      ::= { appnLocalEnTgEntry 12 }

appnLocalEnTgDelay OBJECT-TYPE
      SYNTAX AppnTgDelay
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Administratively assigned delay associated with this TG."

      ::= { appnLocalEnTgEntry 13 }

appnLocalEnTgUsr1 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "First user-defined TG characteristic for this TG.  This is
          an administratively assigned value associated with the TG."

      ::= { appnLocalEnTgEntry 14 }

appnLocalEnTgUsr2 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Second user-defined TG characteristic for this TG.  This is
          an administratively assigned value associated with the TG."

      ::= { appnLocalEnTgEntry 15 }

appnLocalEnTgUsr3 OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Third user-defined TG characteristic for this TG.  This is
```

```
          an administratively assigned value associated with the TG."

      ::= { appnLocalEnTgEntry 16 }

-- ************** The APPN Directory Group ****************************
appnDir               OBJECT IDENTIFIER ::= { appnObjects 4 }
appnDirPerf  OBJECT IDENTIFIER ::= { appnDir 1 }

-- The APPN Directory Group

-- The APPN Directory Database

-- Each APPN network node maintains directories containing information on
-- which LUs (applications) are available and where they are located.
-- LUs can be located in an APPN network node or in any of its attached
-- end nodes.

appnDirMaxCaches OBJECT-TYPE
      SYNTAX Unsigned32
      UNITS "directory entries"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum number of cache entries allowed.  This is an
          administratively assigned value."

      ::= { appnDirPerf 1 }

appnDirCurCaches OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "directory entries"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Current number of cache entries."

      ::= { appnDirPerf 2 }

appnDirCurHomeEntries OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "directory entries"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Current number of home entries."

      ::= { appnDirPerf 3 }
```

```
appnDirRegEntries OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "directory entries"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Current number of registered entries."

      ::= { appnDirPerf 4 }

appnDirInLocates OBJECT-TYPE
      SYNTAX AppnNodeCounter
      UNITS "Locate messages"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of directed Locates received since the node was last
          re-initialized."

      ::= { appnDirPerf 5 }

appnDirInBcastLocates OBJECT-TYPE
      SYNTAX AppnNodeCounter
      UNITS "Locate messages"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of broadcast Locates received since the node was last
          re-initialized."

      ::= { appnDirPerf 6 }

appnDirOutLocates OBJECT-TYPE
      SYNTAX AppnNodeCounter
      UNITS "Locate messages"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of directed Locates sent since the node was last
          re-initialized."

      ::= { appnDirPerf 7 }

appnDirOutBcastLocates OBJECT-TYPE
      SYNTAX AppnNodeCounter
      UNITS "Locate messages"
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
          "Number of broadcast Locates sent since the node was last
          re-initialized."

      ::= { appnDirPerf 8 }

appnDirNotFoundLocates OBJECT-TYPE
      SYNTAX AppnNodeCounter
      UNITS "Locate messages"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of directed Locates returned with a 'not found' since
          the node was last re-initialized."

      ::= { appnDirPerf 9 }

appnDirNotFoundBcastLocates OBJECT-TYPE
      SYNTAX AppnNodeCounter
      UNITS "Locate messages"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of broadcast Locates returned with a 'not found' since
          the node was last re-initialized."

      ::= { appnDirPerf 10 }

appnDirLocateOutstands OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "Locate messages"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Current number of outstanding Locates, both directed and
          broadcast.  This value varies.  A value of zero indicates
          that no Locates are unanswered."

      ::= { appnDirPerf 11 }


--APPN Directory table
-- This table contains information about all known LUs.

appnDirTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnDirEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
          "Table containing information about all known LUs."

      ::= { appnDir 2 }

appnDirEntry OBJECT-TYPE
      SYNTAX AppnDirEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "This table is indexed by the LU name."

      INDEX
             {appnDirLuName}

      ::= { appnDirTable 1 }

AppnDirEntry ::= SEQUENCE {
      appnDirLuName                  DisplayString,
      appnDirNnServerName            SnaControlPointName,
      appnDirLuOwnerName             SnaControlPointName,
      appnDirLuLocation              INTEGER,
      appnDirType                    INTEGER
                    }

appnDirLuName OBJECT-TYPE
      SYNTAX DisplayString  (SIZE (1..17))
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Fully qualified network LU name in the domain of the
           serving network node.  Entries take one of three forms:

              - Explicit entries do not contain the character '*'.
              - Partial wildcard entries have the form 'ccc*', where
                'ccc' represents one to sixteen characters in a
                legal SNA LuName.
              - A full wildcard entry consists of the single
                character '*'"

      ::= { appnDirEntry 1 }

appnDirNnServerName OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Fully qualified control point (CP) name of the network node
```

```
          server.  For unassociated end node entries, a zero-length
          string is returned."

      ::= { appnDirEntry 2 }

appnDirLuOwnerName OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Fully qualified CP name of the node at which the LU is
          located.  This name is the same as the serving NN name when
          the LU is located at a network node.  It is also the same as
          the fully qualified LU name when this is the control point
          LU for this node."

      ::= { appnDirEntry 3 }

appnDirLuLocation OBJECT-TYPE
      SYNTAX INTEGER {
                     local(1),     --Local
                     domain(2),    --Domain
                     xdomain(3)    --Cross Domain
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Specifies the location of the LU with respect to the local
          node."

      ::= { appnDirEntry 4 }

appnDirType OBJECT-TYPE
      SYNTAX INTEGER {
                     home(1),      --defined as home entry
                     cache(2),     --learned over time
                     registered(3) --registered by end node
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Directory types are:
            1 - Home
                  The LU is in the domain of the local node, and the LU
                  information has been configured at the local node.

            2 - Cache
                  The LU has previously been located by a broadcast
```

```
                  search, and the location information has been saved.

            3 - Registered
                  The LU is at an end node that is in the domain
                  of the local network node.  Registered entries
                  are registered by the served end node."

      ::= { appnDirEntry 5 }


-- ************** The APPN Class of Service Group **********************

appnCos               OBJECT IDENTIFIER ::= { appnObjects 5 }

-- The APPN Class of Service (COS)

-- Class of Service is a means of expressing the quality of routes and
-- the transmission priority of traffic that flows on these routes.
-- The quality of routes is specified by two tables, a COS weight table
-- for TGs and a COS weight table for nodes.  Values in these COS tables
-- are administratively assigned at each APPN node, with seven default
-- tables specified by the APPN architecture.
-- ********************************************************************

appnCosModeTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnCosModeEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Table representing all of the defined mode names for this
          node.  The table contains the matching COS name for each
          mode name."

      ::= { appnCos 1 }

appnCosModeEntry OBJECT-TYPE
      SYNTAX AppnCosModeEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "This table is indexed by the mode name."

      INDEX
             {appnCosModeName}

      ::= { appnCosModeTable 1 }

AppnCosModeEntry ::= SEQUENCE {
```

```
      appnCosModeName     SnaModeName,
      appnCosModeCosName  SnaClassOfServiceName
                    }

appnCosModeName OBJECT-TYPE
      SYNTAX SnaModeName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name for this mode."

      ::= { appnCosModeEntry 1 }

appnCosModeCosName OBJECT-TYPE
      SYNTAX SnaClassOfServiceName
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Administratively assigned name for this class of service."

      ::= { appnCosModeEntry 2 }


-- ****************************************************************
appnCosNameTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnCosNameEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Table mapping all of the defined class-of-service names for
          this node to their network transmission priorities."

      ::= { appnCos 2 }

appnCosNameEntry OBJECT-TYPE
      SYNTAX AppnCosNameEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "The COS name is the index to this table."

      INDEX
             {appnCosName}

      ::= { appnCosNameTable 1 }

AppnCosNameEntry ::= SEQUENCE {
      appnCosName            SnaClassOfServiceName,
```

```
      appnCosTransPriority   INTEGER
                    }


appnCosName OBJECT-TYPE
      SYNTAX SnaClassOfServiceName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name for this class of service."

      ::= { appnCosNameEntry 1 }

appnCosTransPriority OBJECT-TYPE
      SYNTAX INTEGER {
                    low(1),               --X'01'
                    medium(2),            --X'02'
                    high(3),              --X'03'
                    network(4)            --X'04'
                    }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Transmission priority for this class of service:

              low(1)     - (X'01'):  low priority
              medium(2)  - (X'02'):  medium priority
              high(3)    - (X'03'):  high priority
              network(4) - (X'04'):  network priority"

      ::= { appnCosNameEntry 2 }

-- ****************************************************************
appnCosNodeRowTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnCosNodeRowEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "This table contains all node-row information for all classes
          of service defined in this node."

      ::= { appnCos 3 }

appnCosNodeRowEntry OBJECT-TYPE
      SYNTAX AppnCosNodeRowEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
```

```
          "A node entry for a given class of service."

      INDEX
             {appnCosNodeRowName,
              appnCosNodeRowIndex}

      ::= { appnCosNodeRowTable 1 }

AppnCosNodeRowEntry ::= SEQUENCE {
      appnCosNodeRowName                SnaClassOfServiceName,
      appnCosNodeRowIndex               INTEGER,
      appnCosNodeRowWgt                 DisplayString,
      appnCosNodeRowResistMin           INTEGER,
      appnCosNodeRowResistMax           INTEGER,
      appnCosNodeRowMinCongestAllow     INTEGER,
      appnCosNodeRowMaxCongestAllow     INTEGER
                    }

appnCosNodeRowName OBJECT-TYPE
      SYNTAX SnaClassOfServiceName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name for this class of service."

      ::= { appnCosNodeRowEntry 1 }

appnCosNodeRowIndex OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Subindex under appnCosNodeRowName, corresponding to a row in
          the node table for the class of service identified in
          appnCosNodeRowName.

          For each class of service, this subindex orders rows in the
          appnCosNodeRowTable in the same order as that used for route
          calculation in the APPN node."

      ::= { appnCosNodeRowEntry 2 }

appnCosNodeRowWgt OBJECT-TYPE
      SYNTAX DisplayString (SIZE (1..64))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Weight to be associated with the nodes that fit the criteria
```

```
          specified by this node row.

          This value can either be a character representation of an
          integer, or a formula for calculating the weight."

      ::= { appnCosNodeRowEntry 3 }

appnCosNodeRowResistMin OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Minimum route addition resistance value for this node.
          Range of values is 0-255.  The lower the value, the more
          desirable the node is for intermediate routing."

      ::= { appnCosNodeRowEntry 4 }

appnCosNodeRowResistMax OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum route addition resistance value for this node.
          Range of values is 0-255.  The lower the value, the more
          desirable the node is for intermediate routing."

      ::= { appnCosNodeRowEntry 5 }

appnCosNodeRowMinCongestAllow OBJECT-TYPE
      SYNTAX INTEGER (0..1)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether low congestion will be tolerated.  This
          object and appnCosNodeRowMaxCongestAllow together delineate a
          range of acceptable congestion states for a node.  For the
          ordered pair (minimum congestion allowed, maximum congestion
          allowed), the values are interpreted as follows:

           - (0,0):  only low congestion is acceptable
           - (0,1):  either low or high congestion is acceptable
           - (1,1):  only high congestion is acceptable.

          Note that the combination (1,0) is not defined, since it
          would identify a range whose lower bound was high congestion
          and whose upper bound was low congestion."
```

```
      ::= { appnCosNodeRowEntry 6 }

appnCosNodeRowMaxCongestAllow OBJECT-TYPE
      SYNTAX INTEGER (0..1)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether low congestion will be tolerated.  This
          object and appnCosNodeRowMinCongestAllow together delineate a
          range of acceptable congestion states for a node.  For the
          ordered pair (minimum congestion allowed, maximum congestion
          allowed), the values are interpreted as follows:

           - (0,0):  only low congestion is acceptable
           - (0,1):  either low or high congestion is acceptable
           - (1,1):  only high congestion is acceptable.

          Note that the combination (1,0) is not defined, since it
          would identify a range whose lower bound was high congestion
          and whose upper bound was low congestion."

      ::= { appnCosNodeRowEntry 7 }


-- ****************************************************************
appnCosTgRowTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnCosTgRowEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Table containing all the TG-row information for all classes of
          service defined in this node."

      ::= { appnCos 4 }

appnCosTgRowEntry OBJECT-TYPE
      SYNTAX AppnCosTgRowEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "A TG entry for a given class of service."

      INDEX
             {appnCosTgRowName,
              appnCosTgRowIndex}

      ::= { appnCosTgRowTable 1 }
```

```
AppnCosTgRowEntry ::= SEQUENCE {
      appnCosTgRowName                  SnaClassOfServiceName,
      appnCosTgRowIndex                 INTEGER,
      appnCosTgRowWgt                   DisplayString,
      appnCosTgRowEffCapMin             AppnTgEffectiveCapacity,
      appnCosTgRowEffCapMax             AppnTgEffectiveCapacity,
      appnCosTgRowConnCostMin           INTEGER,
      appnCosTgRowConnCostMax           INTEGER,
      appnCosTgRowByteCostMin           INTEGER,
      appnCosTgRowByteCostMax           INTEGER,
      appnCosTgRowSecurityMin           AppnTgSecurity,
      appnCosTgRowSecurityMax           AppnTgSecurity,
      appnCosTgRowDelayMin              AppnTgDelay,
      appnCosTgRowDelayMax              AppnTgDelay,
      appnCosTgRowUsr1Min               INTEGER,
      appnCosTgRowUsr1Max               INTEGER,
      appnCosTgRowUsr2Min               INTEGER,
      appnCosTgRowUsr2Max               INTEGER,
      appnCosTgRowUsr3Min               INTEGER,
      appnCosTgRowUsr3Max               INTEGER
                    }

appnCosTgRowName OBJECT-TYPE
      SYNTAX SnaClassOfServiceName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Administratively assigned name for this class of service."

      ::= { appnCosTgRowEntry 1 }

appnCosTgRowIndex OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Subindex under appnCosTgRowName, corresponding to a row in the
          TG table for the class of service identified in
          appnCosTgRowName.

          For each class of service, this subindex orders rows in the
          appnCosTgRowTable in the same order as that used for route
          calculation in the APPN node."

      ::= { appnCosTgRowEntry 2 }

appnCosTgRowWgt OBJECT-TYPE
      SYNTAX DisplayString (SIZE (1..64))
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Weight to be associated with the TGs that fit the criteria
          specified by this TG row.

          This value can either be a character representation of an
          integer, or a formula for calculating the weight."

      ::= { appnCosTgRowEntry 3 }

appnCosTgRowEffCapMin OBJECT-TYPE
      SYNTAX AppnTgEffectiveCapacity
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Minimum acceptable capacity for this class of service."

      ::= { appnCosTgRowEntry 4 }

appnCosTgRowEffCapMax OBJECT-TYPE
      SYNTAX AppnTgEffectiveCapacity
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum acceptable capacity for this class of service."

      ::= { appnCosTgRowEntry 5 }

appnCosTgRowConnCostMin OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Minimum acceptable cost per connect time for this class of
          service.

          Cost per connect time:  a value representing the relative
          cost per unit of time to use this TG.  Range is from 0, which
          means no cost, to 255."

      ::= { appnCosTgRowEntry 6 }

appnCosTgRowConnCostMax OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Maximum acceptable cost per connect time for this class of
            service.

            Cost per connect time:  a value representing the relative
            cost per unit of time to use this TG.  Range is from 0, which
            means no cost, to 255."

        ::= { appnCosTgRowEntry 7 }

appnCosTgRowByteCostMin OBJECT-TYPE
        SYNTAX INTEGER (0..255)
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Minimum acceptable cost per byte transmitted for this class
            of service.

            Cost per byte transmitted:  a value representing the relative
            cost per unit of time to use this TG.  Range is from 0, which
            means no cost, to 255."

        ::= { appnCosTgRowEntry 8 }

appnCosTgRowByteCostMax OBJECT-TYPE
        SYNTAX INTEGER (0..255)
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Maximum acceptable cost per byte transmitted for this class
            of service.

            Cost per byte transmitted:  a value representing the relative
            cost of transmitting a byte over this TG.  Range is from 0,
            which means no cost, to 255."

        ::= { appnCosTgRowEntry 9 }

appnCosTgRowSecurityMin OBJECT-TYPE
        SYNTAX AppnTgSecurity
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Minimum acceptable security for this class of service."

        ::= { appnCosTgRowEntry 10 }

appnCosTgRowSecurityMax OBJECT-TYPE
        SYNTAX AppnTgSecurity
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum acceptable security for this class of service."

      ::= { appnCosTgRowEntry 11 }

appnCosTgRowDelayMin OBJECT-TYPE
      SYNTAX AppnTgDelay
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Minimum acceptable propagation delay for this class of
          service."

      ::= { appnCosTgRowEntry 12 }

appnCosTgRowDelayMax OBJECT-TYPE
      SYNTAX AppnTgDelay
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum acceptable propagation delay for this class of
          service."

      ::= { appnCosTgRowEntry 13 }

appnCosTgRowUsr1Min OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Minimum acceptable value for this user-defined
          characteristic."

      ::= { appnCosTgRowEntry 14 }

appnCosTgRowUsr1Max OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum acceptable value for this user-defined
          characteristic."

      ::= { appnCosTgRowEntry 15 }

appnCosTgRowUsr2Min OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Minimum acceptable value for this user-defined
          characteristic."

      ::= { appnCosTgRowEntry 16 }

appnCosTgRowUsr2Max OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum acceptable value for this user-defined
          characteristic."

      ::= { appnCosTgRowEntry 17 }

appnCosTgRowUsr3Min OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Minimum acceptable value for this user-defined
          characteristic."

      ::= { appnCosTgRowEntry 18 }

appnCosTgRowUsr3Max OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Maximum acceptable value for this user-defined
          characteristic."

      ::= { appnCosTgRowEntry 19 }

-- ****************************************************************
-- Intermediate Session Information
-- ****************************************************************
appnSessIntermediate  OBJECT IDENTIFIER ::= { appnObjects 6 }

-- ****************************************************************
-- Intermediate Session Information Global Objects
-- ****************************************************************
-- The following simple objects allow the collection of intermediate
```

```
-- session Information to be started and stopped.
-- ****************************************************************
appnIsInGlobal OBJECT IDENTIFIER ::= { appnSessIntermediate 1 }

appnIsInGlobeCtrAdminStatus OBJECT-TYPE
      SYNTAX INTEGER {
                      notActive(1),
                      active(2),
                      ready(3)
                     }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
          "Object by which a Management Station can deactivate or
          activate capture of intermediate-session counts and names, by
          setting the value to notActive(1) or active(2), respectively.
          The value ready(3) is returned on GET operations until a SET
          has been processed; after that the value received on the most
          recent SET is returned.

          The counts referred to here are the eight objects in the
          AppnIsInTable, from appnIsInP2SFmdPius through
          appnIsInS2PNonFmdBytes.  The names are the four objects in this
          table, from appnIsInPriLuName through appnIsInCosName.

          Setting this object to the following values has the following
          effects:

              notActive(1)  stop collecting count data.  If a count
                            is queried, it returns the value 0.
                            Collection of names may, but need not be,
                            disabled.
              active(2)     start collecting count data.  If it is
                            supported, collection of names is enabled."

      ::= { appnIsInGlobal 1 }

appnIsInGlobeCtrOperStatus OBJECT-TYPE
      SYNTAX INTEGER {
                      notActive(1),
                      active(2)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Indicates whether or not the intermediate session counts
          are active.  The counts referred to here are the eight
          objects in the AppnIsInTable, from appnIsInP2SFmdPius through
```

```
          appnIsInS2PNonFmdBytes.  These eight counts are of type
          Unsigned32 rather than Counter32 because when this object
          enters the notActive state, either because a Management
          Station has set appnInInGlobeCtrAdminStatus to notActive or
          because of a locally-initiated transition, the counts are
          all reset to 0.

          The values for this object are:

              notActive(1):  collection of counts is not active; if it
                             is queried, a count returns the value 0.
              active(2):     collection of counts is active."

      ::= { appnIsInGlobal 2 }

appnIsInGlobeCtrStatusTime OBJECT-TYPE
      SYNTAX TimeTicks
      UNITS "hundredths of a second"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The time since the appnIsInGlobeCtrOperStatus object last
          changed, measured in hundredths of a second.  This time can be
          used to identify when this change occurred in relation to other
          events in the agent, such as the last time the APPN node was
          re-initialized."

      ::= { appnIsInGlobal 3 }

appnIsInGlobeRscv OBJECT-TYPE
      SYNTAX INTEGER {
                      notActive(1),
                      active(2)
                     }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
          "Indicates the current route selection control vector (RSCV)
          collection option in effect, and allows a Management Station to
          change the option.

          The values for this object are:

             notActive(1): collection of route selection control vectors
                           is not active.
             active(2):    collection of route selection control vectors
                           is active."
```

```
      ::= { appnIsInGlobal 4 }

appnIsInGlobeRscvTime OBJECT-TYPE
      SYNTAX TimeTicks
      UNITS "hundredths of a second"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The time since the appnIsInGlobeRscv object last changed,
          measured in hundredths of a second.  This time can be used to
          identify when this change occurred in relation to other events
          in the agent, such as the last time the APPN node was
          re-initialized."

      ::= { appnIsInGlobal 5 }


appnIsInGlobeActSess OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "sessions"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The number of currently active intermediate sessions."

      ::= { appnIsInGlobal 6 }

appnIsInGlobeHprBfActSess OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "sessions"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The number of currently active HPR intermediate sessions."

      ::= { appnIsInGlobal 7 }

-- ***************************************************************
-- Intermediate Session Information Table
-- ***************************************************************
-- This table contains information on intermediate sessions
-- which are currently active.
-- ***************************************************************
appnIsInTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnIsInEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
```

```
          "Intermediate Session Information Table"

      ::= { appnSessIntermediate 2 }

appnIsInEntry OBJECT-TYPE
      SYNTAX AppnIsInEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Entry of Intermediate Session Information Table."

      INDEX
             { appnIsInFqCpName,
               appnIsInPcid }

      ::= { appnIsInTable 1 }

AppnIsInEntry ::= SEQUENCE {
      appnIsInFqCpName            SnaControlPointName,
      appnIsInPcid                OCTET STRING,

      appnIsInSessState           INTEGER,
      appnIsInPriLuName           DisplayString,
      appnIsInSecLuName           DisplayString,
      appnIsInModeName            SnaModeName,
      appnIsInCosName             SnaClassOfServiceName,
      appnIsInTransPriority       INTEGER,

      appnIsInSessType            INTEGER,
      appnIsInSessUpTime          TimeTicks,
      appnIsInCtrUpTime           TimeTicks,

      appnIsInP2SFmdPius          Unsigned32,
      appnIsInS2PFmdPius          Unsigned32,
      appnIsInP2SNonFmdPius       Unsigned32,
      appnIsInS2PNonFmdPius       Unsigned32,
      appnIsInP2SFmdBytes         Unsigned32,
      appnIsInS2PFmdBytes         Unsigned32,
      appnIsInP2SNonFmdBytes      Unsigned32,
      appnIsInS2PNonFmdBytes      Unsigned32,

      appnIsInPsAdjCpName         SnaControlPointName,
      appnIsInPsAdjTgNum          INTEGER,
      appnIsInPsSendMaxBtuSize    INTEGER,
      appnIsInPsSendPacingType    INTEGER,
      appnIsInPsSendRpc           Gauge32,
      appnIsInPsSendNxWndwSize    Gauge32,
      appnIsInPsRecvPacingType    INTEGER,
```

```
      appnIsInPsRecvRpc           Gauge32,
      appnIsInPsRecvNxWndwSize    Gauge32,

      appnIsInSsAdjCpName         SnaControlPointName,
      appnIsInSsAdjTgNum          INTEGER,
      appnIsInSsSendMaxBtuSize    INTEGER,
      appnIsInSsSendPacingType    INTEGER,
      appnIsInSsSendRpc           Gauge32,
      appnIsInSsSendNxWndwSize    Gauge32,
      appnIsInSsRecvPacingType    INTEGER,
      appnIsInSsRecvRpc           Gauge32,
      appnIsInSsRecvNxWndwSize    Gauge32,

      appnIsInRouteInfo           OCTET STRING,

      appnIsInRtpNceId            OCTET STRING,
      appnIsInRtpTcid             OCTET STRING
                    }

appnIsInFqCpName OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "The network-qualified control point name of the node at which
          the session and PCID originated.  For APPN and LEN nodes, this
          is either CP name of the APPN node at which the origin LU is
          located or the CP name of the NN serving the LEN node at which
          the origin LU is located.  For resources served by a dependent
          LU requester (DLUR), it is the name of the owning system
          services control point (SSCP)."

      ::= { appnIsInEntry 1 }

appnIsInPcid OBJECT-TYPE
      SYNTAX OCTET STRING  (SIZE (8))
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "The procedure correlation identifier (PCID) of a session.  It
          is an 8-byte value assigned by the primary LU."

      ::= { appnIsInEntry 2 }

appnIsInSessState OBJECT-TYPE
      SYNTAX INTEGER    {
                         inactive(1),
                         pendactive(2),
```

```
                        active(3),
                        pendinact(4)
                    }
        MAX-ACCESS read-write
        STATUS current
        DESCRIPTION
            "Indicates the state of the session:

                inactive(1)   - session is inactive
                pendactive(2) - session is pending active
                active(3)     - session is active
                pendinact(4)  - session is pending inactive

            Active sessions can be deactivated by setting this object
            to inactive(1)."

        ::= { appnIsInEntry 3 }

appnIsInPriLuName OBJECT-TYPE
        SYNTAX DisplayString (SIZE (0..17))
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The primary LU name of the session.  A zero-length
            string indicates that this name is not available."

        ::= { appnIsInEntry 4 }

appnIsInSecLuName OBJECT-TYPE
        SYNTAX DisplayString (SIZE (0..17))
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The secondary LU name of the session.  A zero-length
            string indicates that this name is not available."

        ::= { appnIsInEntry 5 }

appnIsInModeName OBJECT-TYPE
        SYNTAX SnaModeName
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The mode name used for this session."

        ::= { appnIsInEntry 6 }

appnIsInCosName OBJECT-TYPE
```

```
      SYNTAX SnaClassOfServiceName
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The Class of Service (COS) name used for this session."

      ::= { appnIsInEntry 7 }

appnIsInTransPriority OBJECT-TYPE
      SYNTAX INTEGER {
                     low(1),              --X'01'
                     medium(2),           --X'02'
                     high(3),             --X'03'
                     network(4)           --X'04'
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Transmission priority for this class of service.  Values are:

              low(1)     - (X'01'):  low priority
              medium(2)  - (X'02'):  medium priority
              high(3)    - (X'03'):  high priority
              network(4) - (X'04'):  network priority"

      ::= { appnIsInEntry 8 }

appnIsInSessType OBJECT-TYPE
      SYNTAX INTEGER {
                     unknown(1),
                     lu62(2),
                     lu0thru3(3),
                     lu62dlur(4),
                     lu0thru3dlur(5)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The type of intermediate session.  Defined values are

              unknown      The session type is not known.

              lu62         A session between LUs of type 6.2
                           (as indicated by the LU type in Bind)

              lu0thru3     A session between LUs of type 0, 1, 2, or 3
                           (as indicated by the LU type in Bind)
```

```
              lu62dlur     A session between LUs of type 6.2
                           (as indicated by the LU type in Bind).
                           One of the LUs is a dependent LU supported
                           by the dependent LU requester (DLUR)
                           function at this node.

              lu0thru3dlur A session between LUs of type 0, 1, 2, or 3
                           (as indicated by the LU type in Bind)
                           One of the LUs is a dependent LU supported
                           by the dependent LU requester (DLUR)
                           function at this node."

      ::= { appnIsInEntry 9 }

appnIsInSessUpTime OBJECT-TYPE
      SYNTAX TimeTicks
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Length of time the session has been active, measured in
          hundredths of a second."

      ::= { appnIsInEntry 10 }

appnIsInCtrUpTime OBJECT-TYPE
      SYNTAX TimeTicks
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Length of time the session counters have been active, measured
          in hundredths of a second."

      ::= { appnIsInEntry 11 }

appnIsInP2SFmdPius OBJECT-TYPE
      SYNTAX Unsigned32
      UNITS "path information units (PIUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of function management data (FMD) path information
          units (PIUs) sent from the Primary LU to the Secondary LU since
          the counts were last activated."

      ::= { appnIsInEntry 12 }

appnIsInS2PFmdPius OBJECT-TYPE
      SYNTAX Unsigned32
```

```
      UNITS "path information units (PIUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of FMD PIUs sent from the Secondary LU to the Primary
          LU since the counts were last activated."

      ::= { appnIsInEntry 13 }

appnIsInP2SNonFmdPius OBJECT-TYPE
      SYNTAX Unsigned32
      UNITS "path information units (PIUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of non-FMD PIUs sent from the Primary LU to the
          Secondary LU since the counts were last activated."

      ::= { appnIsInEntry 14 }

appnIsInS2PNonFmdPius OBJECT-TYPE
      SYNTAX Unsigned32
      UNITS "path information units (PIUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of non-FMD PIUs sent from the Secondary LU to the
          Primary LU since the counts were last activated."

      ::= { appnIsInEntry 15 }

appnIsInP2SFmdBytes OBJECT-TYPE
      SYNTAX Unsigned32
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "Number of FMD bytes sent from the Primary LU to the Secondary
          LU since the counts were last activated."

      ::= { appnIsInEntry 16 }

appnIsInS2PFmdBytes OBJECT-TYPE
      SYNTAX Unsigned32
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Number of FMD bytes sent from the Secondary LU to the Primary
            LU since the counts were last activated."

        ::= { appnIsInEntry 17 }

appnIsInP2SNonFmdBytes OBJECT-TYPE
        SYNTAX Unsigned32
        UNITS "bytes"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Number of non-FMD bytes sent from the Primary LU to the
            Secondary LU since the counts were last activated."

        ::= { appnIsInEntry 18 }

appnIsInS2PNonFmdBytes OBJECT-TYPE
        SYNTAX Unsigned32
        UNITS "bytes"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Number of non-FMD bytes sent from the Secondary LU to the
            Primary LU since the counts were last activated."

        ::= { appnIsInEntry 19 }

appnIsInPsAdjCpName OBJECT-TYPE
        SYNTAX SnaControlPointName
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The primary stage adjacent CP name of this session.  If the
            session stage traverses an RTP connection, the CP name of the
            remote RTP endpoint is returned."

        ::= { appnIsInEntry 20 }

appnIsInPsAdjTgNum OBJECT-TYPE
        SYNTAX INTEGER (0..300)
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The primary stage adjacent transmission group (TG) number
            associated with this session.  If the session stage traverses
            an RTP connection, the value 256 is returned.

            Values between 257 and 300 are available for other possible
```

```
          TG 'stand-ins' that may be added to APPN in the future."

      ::= { appnIsInEntry 21 }

appnIsInPsSendMaxBtuSize OBJECT-TYPE
      SYNTAX INTEGER (99..32767)
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The primary stage maximum basic transmission unit (BTU) size
          for sending data."

      ::= { appnIsInEntry 22 }

appnIsInPsSendPacingType OBJECT-TYPE
      SYNTAX INTEGER {
                     fixed(1),
                     adaptive(2)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The primary stage type of pacing being used for sending data."

      ::= { appnIsInEntry 23 }

appnIsInPsSendRpc OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "message units (MUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The primary stage send residual pace count.  This represents
          the primary stage number of message units (MUs) that can still
          be sent in the current session window."

      ::= { appnIsInEntry 24 }

appnIsInPsSendNxWndwSize OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "message units (MUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The primary stage size of the next window which will be used
          to send data."
```

```
      ::= { appnIsInEntry 25 }

appnIsInPsRecvPacingType OBJECT-TYPE
      SYNTAX INTEGER {
                     fixed(1),
                     adaptive(2)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The primary stage type of pacing being used for receiving
          data."

      ::= { appnIsInEntry 26 }

appnIsInPsRecvRpc OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "message units (MUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The primary stage receive residual pace count.  This
          represents the primary stage number of message units (MUs) that
          can still be received in the current session window."

      ::= { appnIsInEntry 27 }

appnIsInPsRecvNxWndwSize OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "message units (MUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The primary stage size of the next window which will be used
          to receive data."

      ::= { appnIsInEntry 28 }

appnIsInSsAdjCpName OBJECT-TYPE
      SYNTAX SnaControlPointName
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage adjacent CP name of this session.  If the
          session stage traverses an RTP connection, the CP name of the
          remote RTP endpoint is returned."

      ::= { appnIsInEntry 29 }
```

```
appnIsInSsAdjTgNum OBJECT-TYPE
      SYNTAX INTEGER (0..300)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage adjacent transmission group (TG) number
          associated with this session.  If the session stage traverses
          an RTP connection, the value 256 is returned.

          Values between 257 and 300 are available for other possible
          TG 'stand-ins' that may be added to APPN in the future."

      ::= { appnIsInEntry 30 }

appnIsInSsSendMaxBtuSize OBJECT-TYPE
      SYNTAX INTEGER (99..32767)
      UNITS "bytes"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage maximum basic transmission unit (BTU) size
          for sending data."

      ::= { appnIsInEntry 31 }

appnIsInSsSendPacingType OBJECT-TYPE
      SYNTAX INTEGER {
                     fixed(1),
                     adaptive(2)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage type of pacing being used for sending
          data."

      ::= { appnIsInEntry 32 }

appnIsInSsSendRpc OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "message units (MUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage send residual pace count.  This represents
          the secondary stage number of message units (MUs) that can
          still be sent in the current session window."
```

```
      ::= { appnIsInEntry 33 }

appnIsInSsSendNxWndwSize OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "message units (MUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage size of the next window which will be used
          to send data."

      ::= { appnIsInEntry 34 }

appnIsInSsRecvPacingType OBJECT-TYPE
      SYNTAX INTEGER {
                     fixed(1),
                     adaptive(2)
                     }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage type of pacing being used for receiving
          data."

      ::= { appnIsInEntry 35 }

appnIsInSsRecvRpc OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "message units (MUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage receive residual pace count.  This
          represents the secondary stage number of message units (MUs)
          that can still be received in the current session window."

      ::= { appnIsInEntry 36 }

appnIsInSsRecvNxWndwSize OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "message units (MUs)"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The secondary stage size of the next window which will be used
          to receive data."

      ::= { appnIsInEntry 37 }
```

```
appnIsInRouteInfo OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..255))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The route selection control vector (RSCV X'2B') used for this
          session.  It is present for APPN nodes; but is not present for
          LEN nodes.  The format of this vector is described in SNA
          Formats.  If no RSCV is available, a zero-length string is
          returned."

      ::= { appnIsInEntry 38 }

appnIsInRtpNceId OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (1..8))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The HPR local Network Connection Endpoint of the session."

      ::= { appnIsInEntry 39 }

appnIsInRtpTcid OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (8))
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The RTP connection local TCID of the session."

      ::= { appnIsInEntry 40 }

-- ****************************************************************
-- Intermediate Session RTP Table
-- ****************************************************************
-- This table contains information on intermediate sessions that are
-- being transported on Rapid Transport Protocol (RTP) connections by
-- High Performance Routing (HPR).
-- ****************************************************************
appnIsRtpTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AppnIsRtpEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "A table indicating how many ISR sessions are transported by
          each RTP connection."

      ::= { appnSessIntermediate 3 }
```

```
appnIsRtpEntry OBJECT-TYPE
      SYNTAX AppnIsRtpEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "Entry of Intermediate Session RTP Table."

      INDEX
             { appnIsRtpNceId,
               appnIsRtpTcid }

      ::= { appnIsRtpTable 1 }

AppnIsRtpEntry ::= SEQUENCE {
      appnIsRtpNceId              OCTET STRING,
      appnIsRtpTcid               OCTET STRING,
      appnIsRtpSessions           Gauge32
                    }

appnIsRtpNceId OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (8))
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "The local Network Connection Endpoint of the RTP connection."

      ::= { appnIsRtpEntry  1 }

appnIsRtpTcid OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (8))
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
          "The local TCID of the RTP connection."

      ::= { appnIsRtpEntry  2 }

appnIsRtpSessions OBJECT-TYPE
      SYNTAX Gauge32
      UNITS "sessions"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The number of intermediate sessions using this RTP
          connection."

      ::= { appnIsRtpEntry  3 }
```

```
-- ************************************************************************
  appnTraps               OBJECT IDENTIFIER ::= { appnMIB 2 }
-- ************************************************************************

alertTrap NOTIFICATION-TYPE
      OBJECTS  { alertIdNumber, affectedObject }
      STATUS current
      DESCRIPTION
          "This trap carries a 32-bit SNA Management Services (SNA/MS)
          Alert ID Number, as specified in SNA/MS Formats."

      ::= { appnTraps 1 }

alertIdNumber OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (4))
      MAX-ACCESS accessible-for-notify
      STATUS current
      DESCRIPTION
          "A 32-bit SNA Management Services (SNA/MS) Alert ID Number, as
          specified in SNA/MS Formats."

      ::= { appnTraps 2 }

affectedObject OBJECT-TYPE
      SYNTAX VariablePointer
      MAX-ACCESS accessible-for-notify
      STATUS current
      DESCRIPTION
          "The MIB object associated with the Alert condition, if there
          is an object associated with it.  If no associated object can
          be identified, the value 0.0 is passed in the trap."

      ::= { appnTraps 3 }

-- ************************************************************************
-- Conformance information
-- ************************************************************************

appnConformance       OBJECT IDENTIFIER ::= {appnMIB 3 }

appnCompliances       OBJECT IDENTIFIER ::= {appnConformance 1 }
appnGroups            OBJECT IDENTIFIER ::= {appnConformance 2 }

-- Compliance statements
appnCompliance  MODULE-COMPLIANCE
        STATUS  current
        DESCRIPTION
            "The compliance statement for the SNMPv2 entities that
```

```
            implement the APPN MIB."

        MODULE  -- this module

--      Unconditionally mandatory groups
                MANDATORY-GROUPS  {
                        appnGeneralConfGroup,
                        appnPortConfGroup,
                        appnLinkConfGroup,
                        appnLocalTgConfGroup,
                        appnDirTableConfGroup
                 }

--      Conditionally mandatory groups
                GROUP  appnNnUniqueConfGroup
                DESCRIPTION
                    "The appnNnUniqueConfGroup is mandatory only for
                    network nodes."

                GROUP  appnEnUniqueConfGroup
                DESCRIPTION
                    "The appnEnUniqueConfGroup is mandatory only for end
                    nodes."
                GROUP  appnVrnConfGroup
                DESCRIPTION
                    "The appnVrnConfGroup is mandatory only for network
                    nodes and end nodes that implement virtual routing
                    node support."

                GROUP  appnNnTopoConfGroup
                DESCRIPTION
                    "The appnNnTopoConfGroup is mandatory only for
                    network nodes."

                GROUP  appnLocalEnTopoConfGroup
                DESCRIPTION
                    "The appnLocalEnTopoConfGroup is mandatory only for
                    network nodes."

                GROUP  appnLocalDirPerfConfGroup
                DESCRIPTION
                    "The appnLocalDirPerfConfGroup is mandatory only for
                    APPN network nodes and end nodes."

                GROUP  appnCosConfGroup
                DESCRIPTION
                    "The appnCosConfGroup is mandatory only for APPN
                    network nodes and end nodes."
```

```
                GROUP  appnIntSessConfGroup
                DESCRIPTION
                    "The appnIntSessConfGroup is mandatory only for
                    network nodes."

                GROUP  appnHprBaseConfGroup
                DESCRIPTION
                    "The appnHprBaseConfGroup is mandatory only for nodes
                    that implement the HPR base (APPN option set 1400)."

                GROUP  appnHprRtpConfGroup
                DESCRIPTION
                    "The appnHprRtpConfGroup is mandatory only for nodes
                    that implement the HPR RTP tower (APPN option set
                    1401)."

                GROUP  appnHprCtrlFlowsRtpConfGroup
                DESCRIPTION
                    "The appnHprCtrlFlowsRtpConfGroup is mandatory only
                    for nodes that implement the HPR Control Flows over
                    RTP tower (APPN option set 1402)."

                GROUP  appnHprBfConfGroup
                DESCRIPTION
                    "The appnHprBfConfGroup is mandatory only for nodes
                    that implement the APPN/HPR boundary function."

                GROUP  appnTrapConfGroup
                DESCRIPTION
                    "Traps are optional for all nodes."

                GROUP  appnTrapNotifGroup
                DESCRIPTION
                    "Traps are optional for all nodes."

        ::= {appnCompliances 1 }

-- Units of conformance
appnGeneralConfGroup  OBJECT-GROUP
        OBJECTS  {
                 appnNodeCpName,
                 appnNodeMibVersion,
                 appnNodeId,
                 appnNodeType,
                 appnNodeUpTime,
                 appnNodeParallelTg,
                 appnNodeAdaptiveBindPacing,
                 appnNodeHprSupport,
```

```
                appnNodeCounterDisconTime
                }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the instrumentation of
            APPN general information and capabilities."

        ::= { appnGroups 1 }

appnPortConfGroup  OBJECT-GROUP
        OBJECTS  {
                appnPortCommand,
                appnPortOperState,
                appnPortDlcType,
                appnPortPortType,
                appnPortSIMRIM,
                appnPortLsRole,
                appnPortNegotLs,
                appnPortDynamicLinkSupport,
                appnPortMaxRcvBtuSize,
                appnPortMaxIframeWindow,
                appnPortDefLsGoodXids,
                appnPortDefLsBadXids,
                appnPortDynLsGoodXids,
                appnPortDynLsBadXids,
                appnPortSpecific,
                appnPortDlcLocalAddr,
                appnPortCounterDisconTime
                }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the instrumentation of
            APPN port information."

        ::= { appnGroups 2 }

appnLinkConfGroup  OBJECT-GROUP
        OBJECTS  {
                appnLsCommand,
                appnLsOperState,
                appnLsPortName,
                appnLsDlcType,
                appnLsDynamic,
                appnLsAdjCpName,
                appnLsAdjNodeType,
                appnLsTgNum,
                appnLsLimResource,
                appnLsActOnDemand,
```

```
                appnLsMigration,
                appnLsPartnerNodeId,
                appnLsCpCpSessionSupport,
                appnLsMaxSendBtuSize,
                appnLsInXidBytes,
                appnLsInMsgBytes,
                appnLsInXidFrames,
                appnLsInMsgFrames,
                appnLsOutXidBytes,
                appnLsOutMsgBytes,
                appnLsOutXidFrames,
                appnLsOutMsgFrames,
                appnLsEchoRsps,
                appnLsCurrentDelay,
                appnLsMaxDelay,
                appnLsMinDelay,
                appnLsMaxDelayTime,
                appnLsGoodXids,
                appnLsBadXids,
                appnLsSpecific,
                appnLsActiveTime,
                appnLsCurrentStateTime,
                appnLsHprSup,
                appnLsLocalAddr,
                appnLsRemoteAddr,
                appnLsRemoteLsName,
                appnLsStatusTime,
                appnLsStatusLsName,
                appnLsStatusCpName,
                appnLsStatusPartnerId,
                appnLsStatusTgNum,
                appnLsStatusGeneralSense,
                appnLsStatusRetry,
                appnLsStatusEndSense,
                appnLsStatusXidLocalSense,
                appnLsStatusXidRemoteSense,
                appnLsStatusXidByteInError,
                appnLsStatusXidBitInError,
                appnLsStatusDlcType,
                appnLsStatusLocalAddr,
                appnLsStatusRemoteAddr,
                appnLsCounterDisconTime
                }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the instrumentation of
            APPN link information."
```

```
        ::= { appnGroups 3 }

appnLocalTgConfGroup  OBJECT-GROUP
        OBJECTS  {
                 appnLocalTgDestVirtual,
                 appnLocalTgDlcData,
                 appnLocalTgPortName,
                 appnLocalTgQuiescing,
                 appnLocalTgOperational,
                 appnLocalTgCpCpSession,
                 appnLocalTgEffCap,
                 appnLocalTgConnCost,
                 appnLocalTgByteCost,
                 appnLocalTgSecurity,
                 appnLocalTgDelay,
                 appnLocalTgUsr1,
                 appnLocalTgUsr2,
                 appnLocalTgUsr3,
                 appnLocalTgHprSup,
                 appnLocalTgIntersubnet
                 }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the instrumentation of
            APPN local TG information."

        ::= { appnGroups 4 }

appnDirTableConfGroup  OBJECT-GROUP
        OBJECTS  {
                 appnDirNnServerName,
                 appnDirLuOwnerName,
                 appnDirLuLocation,
                 appnDirType
                 }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the instrumentation of the
            APPN directory database."

        ::= { appnGroups 5 }

appnNnUniqueConfGroup  OBJECT-GROUP
        OBJECTS  {
                 appnNodeNnCentralDirectory,
                 appnNodeNnTreeCache,
                 appnNodeNnRouteAddResist,
                 appnNodeNnIsr,
```

```
                appnNodeNnFrsn,
                appnNodeNnPeriBorderSup,
                appnNodeNnInterchangeSup,
                appnNodeNnExteBorderSup,
                appnNodeNnSafeStoreFreq,
                appnNodeNnRsn,
                appnNodeNnCongested,
                appnNodeNnIsrDepleted,
                appnNodeNnQuiescing,
                appnNodeNnGateway
                }
        STATUS  current
        DESCRIPTION
            "The appnNnUniqueConfGroup is mandatory only for network
            nodes."

        ::= { appnGroups 6 }

appnEnUniqueConfGroup  OBJECT-GROUP
        OBJECTS  {
                appnNodeEnModeCosMap,
                appnNodeEnNnServer,
                appnNodeEnLuSearch
                }
        STATUS  current
        DESCRIPTION
            "The appnEnUniqueConfGroup is mandatory only for end nodes."

        ::= { appnGroups 7 }

appnVrnConfGroup       OBJECT-GROUP
        OBJECTS  {
                appnVrnPortName
                }
        STATUS  current
        DESCRIPTION
            "The appnVrnConfGroup is mandatory only for APPN network
            nodes and end nodes."

        ::= { appnGroups 8 }

appnNnTopoConfGroup    OBJECT-GROUP
        OBJECTS  {
                appnNnTopoMaxNodes,
                appnNnTopoCurNumNodes,
                appnNnTopoNodePurges,
                appnNnTopoTgPurges,
                appnNnTopoTotalTduWars,
```

```
                appnNnNodeFREntryTimeLeft,
                appnNnNodeFRType,
                appnNnNodeFRRsn,
                appnNnNodeFRRouteAddResist,
                appnNnNodeFRCongested,
                appnNnNodeFRIsrDepleted,
                appnNnNodeFRQuiescing,
                appnNnNodeFRGateway,
                appnNnNodeFRCentralDirectory,
                appnNnNodeFRIsr,
                appnNnNodeFRGarbageCollect,
                appnNnNodeFRHprSupport,
                appnNnNodeFRPeriBorderSup,
                appnNnNodeFRInterchangeSup,
                appnNnNodeFRExteBorderSup,
                appnNnTgFREntryTimeLeft,
                appnNnTgFRDestVirtual,
                appnNnTgFRDlcData,
                appnNnTgFRRsn,
                appnNnTgFROperational,
                appnNnTgFRQuiescing,
                appnNnTgFRCpCpSession,
                appnNnTgFREffCap,
                appnNnTgFRConnCost,
                appnNnTgFRByteCost,
                appnNnTgFRSecurity,
                appnNnTgFRDelay,
                appnNnTgFRUsr1,
                appnNnTgFRUsr2,
                appnNnTgFRUsr3,
                appnNnTgFRGarbageCollect,
                appnNnTgFRSubareaNum,
                appnNnTgFRHprSup,
                appnNnTgFRDestHprTrans,
                appnNnTgFRTypeIndicator,
                appnNnTgFRIntersubnet
                }
        STATUS  current
        DESCRIPTION
            "The appnNnTopoConfGroup is mandatory only for network
            nodes."

        ::= { appnGroups 9 }

appnLocalEnTopoConfGroup   OBJECT-GROUP
        OBJECTS  {
                appnLocalEnTgEntryTimeLeft,
                appnLocalEnTgDestVirtual,
```

```
                appnLocalEnTgDlcData,
                appnLocalEnTgOperational,
                appnLocalEnTgCpCpSession,
                appnLocalEnTgEffCap,
                appnLocalEnTgConnCost,
                appnLocalEnTgByteCost,
                appnLocalEnTgSecurity,
                appnLocalEnTgDelay,
                appnLocalEnTgUsr1,
                appnLocalEnTgUsr2,
                appnLocalEnTgUsr3
                }
        STATUS  current
        DESCRIPTION
            "The appnLocalEnTopoConfGroup is mandatory only for network
            nodes."

        ::= { appnGroups 10 }

appnLocalDirPerfConfGroup  OBJECT-GROUP
        OBJECTS  {
                appnDirMaxCaches,
                appnDirCurCaches,
                appnDirCurHomeEntries,
                appnDirRegEntries,
                appnDirInLocates,
                appnDirInBcastLocates,
                appnDirOutLocates,
                appnDirOutBcastLocates,
                appnDirNotFoundLocates,
                appnDirNotFoundBcastLocates,
                appnDirLocateOutstands
                }
        STATUS  current
        DESCRIPTION
            "The appnLocalDirPerfConfGroup is mandatory only for APPN
            network nodes and end nodes."

        ::= { appnGroups 11 }

appnCosConfGroup          OBJECT-GROUP
        OBJECTS  {
                appnCosModeCosName,
                appnCosTransPriority,
                appnCosNodeRowWgt,
                appnCosNodeRowResistMin,
                appnCosNodeRowResistMax,
                appnCosNodeRowMinCongestAllow,
```

```
                appnCosNodeRowMaxCongestAllow,
                appnCosTgRowWgt,
                appnCosTgRowEffCapMin,
                appnCosTgRowEffCapMax,
                appnCosTgRowConnCostMin,
                appnCosTgRowConnCostMax,
                appnCosTgRowByteCostMin,
                appnCosTgRowByteCostMax,
                appnCosTgRowSecurityMin,
                appnCosTgRowSecurityMax,
                appnCosTgRowDelayMin,
                appnCosTgRowDelayMax,
                appnCosTgRowUsr1Min,
                appnCosTgRowUsr1Max,
                appnCosTgRowUsr2Min,
                appnCosTgRowUsr2Max,
                appnCosTgRowUsr3Min,
                appnCosTgRowUsr3Max
                }
        STATUS  current
        DESCRIPTION
            "The appnCosConfGroup is mandatory only for APPN network
            nodes and end nodes."

        ::= { appnGroups 12 }

appnIntSessConfGroup    OBJECT-GROUP
        OBJECTS  {
                appnIsInGlobeCtrAdminStatus,
                appnIsInGlobeCtrOperStatus,
                appnIsInGlobeCtrStatusTime,
                appnIsInGlobeRscv,
                appnIsInGlobeRscvTime,
                appnIsInGlobeActSess,
                appnIsInSessState,
                appnIsInPriLuName,
                appnIsInSecLuName,
                appnIsInModeName,
                appnIsInCosName,
                appnIsInTransPriority,
                appnIsInSessType,
                appnIsInSessUpTime,
                appnIsInCtrUpTime,
                appnIsInP2SFmdPius,
                appnIsInS2PFmdPius,
                appnIsInP2SNonFmdPius,
                appnIsInS2PNonFmdPius,
                appnIsInP2SFmdBytes,
```

```
                appnIsInS2PFmdBytes,
                appnIsInP2SNonFmdBytes,
                appnIsInS2PNonFmdBytes,
                appnIsInPsAdjCpName,
                appnIsInPsAdjTgNum,
                appnIsInPsSendMaxBtuSize,
                appnIsInPsSendPacingType,
                appnIsInPsSendRpc,
                appnIsInPsSendNxWndwSize,
                appnIsInPsRecvPacingType,
                appnIsInPsRecvRpc,
                appnIsInPsRecvNxWndwSize,
                appnIsInSsAdjCpName,
                appnIsInSsAdjTgNum,
                appnIsInSsSendMaxBtuSize,
                appnIsInSsSendPacingType,
                appnIsInSsSendRpc,
                appnIsInSsSendNxWndwSize,
                appnIsInSsRecvPacingType,
                appnIsInSsRecvRpc,
                appnIsInSsRecvNxWndwSize,
                appnIsInRouteInfo
                }
        STATUS  current
        DESCRIPTION
            "The appnIntSessConfGroup is mandatory only for network
            nodes."

        ::= { appnGroups 13 }

appnHprBaseConfGroup    OBJECT-GROUP
        OBJECTS  {
                appnNodeHprIntRteSetups,
                appnNodeHprIntRteRejects,
                appnLsErrRecoSup,
                appnLsForAnrLabel,
                appnLsRevAnrLabel
                }
        STATUS  current
        DESCRIPTION
            "The appnHprBaseConfGroup is mandatory only for nodes that
            implement the HPR base (APPN option set 1400)."

        ::= { appnGroups 14 }

appnHprRtpConfGroup    OBJECT-GROUP
        OBJECTS  {
                appnNodeMaxSessPerRtpConn,
```

```
                appnNodeHprOrgRteSetups,
                appnNodeHprOrgRteRejects,
                appnNodeHprEndRteSetups,
                appnNodeHprEndRteRejects,
                appnLsBfNceId
                }
        STATUS  current
        DESCRIPTION
            "The appnHprRtpConfGroup is mandatory only for nodes that
            implement the HPR RTP tower (APPN option set 1401)."

        ::= { appnGroups 15 }

appnHprCtrlFlowsRtpConfGroup    OBJECT-GROUP
        OBJECTS  {
                appnLsCpCpNceId,
                appnLsRouteNceId
                }
        STATUS  current
        DESCRIPTION
            "The appnHprCtrlFlowsRtpConfGroup is mandatory only for nodes
            that implement the HPR Control Flows over RTP tower (APPN
            option set 1402)."

        ::= { appnGroups 16 }

appnHprBfConfGroup    OBJECT-GROUP
        OBJECTS  {
                appnIsInGlobeHprBfActSess,
                appnIsInRtpNceId,
                appnIsInRtpTcid,
                appnIsRtpSessions
                }
        STATUS  current
        DESCRIPTION
            "The appnHprBfConfGroup is mandatory only for nodes that
            implement the APPN/HPR boundary function."

        ::= { appnGroups 17 }

appnTrapConfGroup    OBJECT-GROUP
        OBJECTS  {
                alertIdNumber,
                affectedObject
                }
        STATUS  current
        DESCRIPTION
            "The appnTrapConfGroup is optional for all APPN nodes.  Nodes
```

```
            implementing this group shall also implement the
            appnTrapNotifGroup."

        ::= { appnGroups 18 }

appnTrapNotifGroup    NOTIFICATION-GROUP
        NOTIFICATIONS {
                      alertTrap
                      }
        STATUS  current
        DESCRIPTION
            "The appnTrapNotifGroup is optional for all APPN nodes.
            Nodes implementing this group shall also implement the
            appnTrapConfGroup."

        ::= { appnGroups 19 }

END
```

5. Acknowledgments

This MIB module is the product of the IETF SNA NAU MIB WG and the AIW APPN/HPR MIBs SIG. Thanks to Wayne Clark, Cisco Systems; Jim Cobban, Nortel; Rich Daugherty, IBM Corporation; Mark Regan, Cisco Systems; and Leo Temoshenko, IBM Corporation, for their contributions and review.

6. References

[1] SNMPv2 Working Group, Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Structure of Management Information for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1902, January 1996.

[2] SNMPv2 Working Group, Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Textual Conventions for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1903, January 1996.

[3] SNMPv2 Working Group, Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Conformance Statements for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1904, January 1996.

[4] IBM, Systems Network Architecture Technical Overview, GC30-3073.

[5] IBM, Systems Network Architecture APPN Architecture Reference, SC30-3422

[6] IBM, Systems Network Architecture Formats, SC30-3346.

[7] Allen, M., Clouston, B., Kielczewski, Z., Kwan, W., and B. Moore, "Definition of Managed Objects for APPC", RFC 2051, Wall Data Inc., Cisco Systems, Jupiter Technology Inc., IBM Corporation, December 1995.

[8] Kielczewski, Z., Kostick D., and K. Shih, "Definition of Managed Objects for SNA NAUs using SMIv2", RFC 1666, Eicon Technology Corporation, Bell Communications Research, Novell, August 1994.

[9] Clouston, B., and B. Moore, "Definitions of Managed Objects for DLUR", November 1996.

[10] Clouston, B., and B. Moore, "Definitions of Managed Objects for HPR", November 1996.

[11] SNA DLC Services MIB Working Group, Hilgeman, J., Nix, S., Bartky, A., and W. Clark, "Definitions of Managed Objects for SNA Data Link Control (SDLC) using SMIv2", RFC 1747, January 1995. URL: ftp://ds.internic.net/rfc/rfc1747.txt

[12] SNA DLC Services MIB Working Group, Berl, S., Nix, S., and W. Clark, "Definitions of Managed Objects for SNA Data Link Control: LLC", May 1995.

[13] Chen, D., Gayek, P., and S. Nix, "Definitions of Managed Objects for Data Link Switching using SNMPv2", RFC 2024, October 1995.

[14] IBM, Systems Network Architecture Management Services Formats, GC31-8302.

7. Security Considerations

In most cases, MIBs are not themselves security risks; if SNMP security is operating as intended, the use of a MIB to view information about a system, or to change some parameter at the system, is a tool, not a threat.

None of the read-only objects in the APPN MIB reports a password, user data, or anything else that is particularly sensitive. Some enterprises view their network configuration itself, as well as information about network usage and performance, as corporate assets; such enterprises may wish to restrict SNMP access to most of the objects in the MIB.

Four of the read-write objects in the MIB can affect network operations; it is recommended that SNMP access to these objects be restricted. The four objects are:

- appnNodeNnSafeStoreFreq: Setting this object to 0, or to a very large value, effectively turns off safe storing of topology data.

- appnPortCommand, appnLsCommand: These two objects allow an APPN port or link station to be activated, deactivated, or recycled via an SNMP operation. The latter two operations may disrupt current users of the network.

- appnIsInSessState: Setting this object to 'inactive' causes an active SNA session to be deactivated.

  Other read-write objects control the gathering of network management data; controlling access to these objects is less critical.

8. Authors' Addresses

Bob Clouston
Cisco Systems
7025 Kit Creek Road
P.O. Box 14987
Research Triangle Park, NC 27709, USA

Tel: 1 919 472 2333
E-mail: clouston@cisco.com

Bob Moore
IBM Corporation
800 Park Offices Drive
CNMA/664
P.O. Box 12195
Research Triangle Park, NC 27709, USA

Tel: 1 919 254 4436
E-mail: remoore@ralvm6.vnet.ibm.com