

Using the GOST 28147-89, GOST R 34.11-94,  
GOST R 34.10-94, and GOST R 34.10-2001 Algorithms with  
Cryptographic Message Syntax (CMS)

#### Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

#### Copyright Notice

Copyright (C) The Internet Society (2006).

#### Abstract

This document describes the conventions for using the cryptographic algorithms GOST 28147-89, GOST R 34.10-94, GOST R 34.10-2001, and GOST R 34.11-94 with the Cryptographic Message Syntax (CMS). The CMS is used for digital signature, digest, authentication, and encryption of arbitrary message contents.

## Table of Contents

1. Introduction .....	3
1.1. Terminology .....	3
2. Message Digest Algorithms .....	3
2.1. Message Digest Algorithm GOST R 34.11-94 .....	3
3. Signature Algorithms .....	4
3.1. Signature Algorithm GOST R 34.10-94 .....	4
3.2. Signature Algorithm GOST R 34.10-2001 .....	5
4. Key Management Algorithms .....	5
4.1. Key Agreement Algorithms .....	6
4.1.1. Key Agreement Algorithms Based on GOST R 34.10-94/2001 Public .....	6
4.2. Key Transport Algorithms .....	8
4.2.1. Key Transport Algorithm Based on GOST R 34.10-94/2001 Public .....	8
5. Content Encryption Algorithms .....	9
5.1. Content Encryption Algorithm GOST 28147-89 .....	10
6. MAC Algorithms .....	10
6.1. HMAC with GOST R 34.11-94 .....	10
7. Use with S/MIME .....	11
7.1. Parameter micalg .....	11
7.2. Attribute SMIMECapabilities .....	11
8. Security Considerations .....	12
9. Examples .....	12
9.1. Signed Message .....	12
9.2. Enveloped Message Using Key Agreement .....	14
9.3. Enveloped Message Using Key Transport .....	17
10. ASN.1 Modules .....	19
10.1. GostR3410-EncryptionSyntax .....	19
10.2. GostR3410-94-SignatureSyntax .....	21
10.3. GostR3410-2001-SignatureSyntax .....	22
11. Acknowledgements .....	23
12. References .....	24
12.1. Normative References .....	24
12.2. Informative References .....	25

## 1. Introduction

The Cryptographic Message Syntax [CMS] is used for digital signature, digest, authentication, and encryption of arbitrary message contents. This companion specification describes the use of cryptographic algorithms GOST 28147-89 [GOST28147], GOST R 34.10-94 [GOST3431095, GOSTR341094], GOST R 34.10-2001 [GOST3431004, GOSTR341001], and GOST R 34.11-94 [GOST3431195, GOSTR341194] in CMS, as proposed by the CRYPTO-PRO Company for the "Russian Cryptographic Software Compatibility Agreement" community. This document does not describe these cryptographic algorithms; they are defined in corresponding national standards.

The CMS values are generated using ASN.1 [X.208-88], using BER encoding [X.209-88]. This document specifies the algorithm identifiers for each algorithm, including ASN.1 for object identifiers and any associated parameters.

The fields in the CMS employed by each algorithm are identified.

### 1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

## 2. Message Digest Algorithms

This section specifies the conventions for using the digest algorithm GOST R 34.11-94 employed by CMS.

Digest values are located in the DigestedData digest field and the Message Digest authenticated attribute. In addition, digest values are input to signature algorithms.

### 2.1. Message Digest Algorithm GOST R 34.11-94

The hash function GOST R 34.11-94 has been developed by "GUBS of Federal Agency Government Communication and Information" and "All-Russian Scientific and Research Institute of Standardization". The algorithm GOST R 34.11-94 produces a 256-bit hash value of the arbitrary finite bit-length input. This document does not contain the full GOST R 34.11-94 specification, which can be found in [GOSTR341194] in Russian. [Schneier95], ch. 18.11, p. 454, contains a brief technical description in English.

The hash algorithm GOST R 34.11-94 has the following identifier:

```
id-GostR3411-94 OBJECT IDENTIFIER ::=
    { iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
      gostr3411(9) }
```

The AlgorithmIdentifier parameters field MUST be present, and the parameters field MUST contain NULL. Implementations MAY accept the GOST R 34.11-94 AlgorithmIdentifiers with absent parameters as well as NULL parameters.

This function is always used with default parameters id-GostR3411-94-CryptoProParamSet (see Section 8.2 of [CPALGS]).

When the Message Digest authenticated attribute is present, the DigestedData digest contains a 32-byte digest in little-endian representation:

```
GostR3411-94-Digest ::= OCTET STRING (SIZE (32))
```

### 3. Signature Algorithms

This section specifies the CMS procedures for the GOST R 34.10-94 and GOST R 34.10-2001 signature algorithms.

Signature algorithm identifiers are located in the SignerInfo signatureAlgorithm field of SignedData. Also, signature algorithm identifiers are located in the SignerInfo signatureAlgorithm field of countersignature attributes.

Signature values are located in the SignerInfo signature field of SignedData. Also, signature values are located in the SignerInfo signature field of countersignature attributes.

#### 3.1. Signature Algorithm GOST R 34.10-94

GOST R 34.10-94 has been developed by "GUBS of Federal Agency Government Communication and Information" and "All-Russian Scientific and Research Institute of Standardization". This signature algorithm MUST be used conjointly with the GOST R 34.11-94 message digest algorithm. This document does not contain the full GOST R 34.10-94 specification, which is fully described in [GOSTR341094] in Russian; and a brief description in English can be found in [Schneier95], ch. 20.3, p. 495.

The GOST R 34.10-94 signature algorithm has the following public key algorithm identifier:

id-GostR3410-94-signature OBJECT IDENTIFIER ::= id-GostR3410-94

id-GostR3410-94 is defined in Section 2.3.1 of [CPPK].

The signature algorithm GOST R 34.10-94 generates a digital signature in the form of two 256-bit numbers,  $r'$  and  $s$ . Its octet string representation consists of 64 octets, where the first 32 octets contain the big-endian representation of  $s$  and the second 32 octets contain the big-endian representation of  $r'$ .

GostR3410-94-Signature ::= OCTET STRING (SIZE (64))

### 3.2. Signature Algorithm GOST R 34.10-2001

GOST R 34.10-2001 has been developed by "GUBS of Federal Agency Government Communication and Information" and "All-Russian Scientific and Research Institute of Standardization". This signature algorithm MUST be used conjointly with GOST R 34.11-94. This document does not contain the full GOST R 34.10-2001 specification, which is fully described in [GOSTR341001].

The signature algorithm GOST R 34.10-2001 has the following public key algorithm identifier:

id-GostR3410-2001-signature OBJECT IDENTIFIER ::= id-GostR3410-2001

id-GostR3410-2001 is defined in Section 2.3.2 of [CPPK].

The signature algorithm GOST R 34.10-2001 generates a digital signature in the form of two 256-bit numbers,  $r$  and  $s$ . Its octet string representation consists of 64 octets, where the first 32 octets contain the big-endian representation of  $s$  and the second 32 octets contain the big-endian representation of  $r$ .

GostR3410-2001-Signature ::= OCTET STRING (SIZE (64))

## 4. Key Management Algorithms

This chapter describes the key agreement and key transport algorithms, based on the VKO GOST R 34.10-94 and VKO GOST R 34.10-2001 key derivation algorithms, and the CryptoPro and GOST 28147-89 key wrap algorithms, described in [CPALGS]. They MUST be used only with the content encryption algorithm GOST 28147-89, defined in Section 5 of this document.

#### 4.1. Key Agreement Algorithms

This section specifies the conventions employed by CMS implementations that support key agreement using both the VKO GOST R 34.10-94 and VKO GOST R 34.10-2001 algorithms, described in [CPALGS].

Key agreement algorithm identifiers are located in the EnvelopedData RecipientInfos KeyAgreeRecipientInfo keyEncryptionAlgorithm and AuthenticatedData RecipientInfos KeyAgreeRecipientInfo keyEncryptionAlgorithm fields.

Wrapped content-encryption keys are located in the EnvelopedData RecipientInfos KeyAgreeRecipientInfo RecipientEncryptedKeys encryptedKey field. Wrapped message-authentication keys are located in the AuthenticatedData RecipientInfos KeyAgreeRecipientInfo RecipientEncryptedKeys encryptedKey field.

##### 4.1.1. Key Agreement Algorithms Based on GOST R 34.10-94/2001 Public Keys

The EnvelopedData RecipientInfos KeyAgreeRecipientInfo field is used as follows:

The version MUST be 3.

The originator MUST be the originatorKey alternative. The originatorKey algorithm field MUST contain the object identifier id-GostR3410-94 or id-GostR3410-2001 and corresponding parameters (defined in Sections 2.3.1, 2.3.2 of [CPPK]).

The originatorKey publicKey field MUST contain the sender's public key.

keyEncryptionAlgorithm MUST be the id-GostR3410-94-CryptoPro-ESDH or the id-GostR3410-2001-CryptoPro-ESDH algorithm identifier, depending on the recipient public key algorithm. The algorithm identifier parameter field for these algorithms is KeyWrapAlgorithm, and this parameter MUST be present. The KeyWrapAlgorithm denotes the algorithm and parameters used to encrypt the content-encryption key with the pairwise key-encryption key generated using the VKO GOST R 34.10-94 or the VKO GOST R 34.10-2001 key agreement algorithms.

The algorithm identifiers and parameter syntax is:

```
id-GostR3410-94-CryptoPro-ESDH OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
    gostR3410-94-CryptoPro-ESDH(97) }
```

```
id-GostR3410-2001-CryptoPro-ESDH OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
    gostR3410-2001-CryptoPro-ESDH(96) }
```

```
KeyWrapAlgorithm ::= AlgorithmIdentifier
```

When `keyEncryptionAlgorithm` is `id-GostR3410-94-CryptoPro-ESDH`, `KeyWrapAlgorithm algorithm` MUST be the `id-Gost28147-89-CryptoPro-KeyWrap` algorithm identifier.

```
id-Gost28147-89-CryptoPro-KeyWrap OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
    keyWrap(13) cryptoPro(1) }
```

The CryptoPro Key Wrap algorithm is described in Sections 6.3 and 6.4 of [CPALGS].

When `keyEncryptionAlgorithm` is `id-GostR3410-2001-CryptoPro-ESDH`, `KeyWrapAlgorithm algorithm` MUST be either the `id-Gost28147-89-CryptoPro-KeyWrap` or `id-Gost28147-89-None-KeyWrap` algorithm identifier.

```
id-Gost28147-89-None-KeyWrap OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
    keyWrap(13) none(0) }
```

The GOST 28147-89 Key Wrap algorithm is described in Sections 6.1 and 6.2 of [CPALGS].

`KeyWrapAlgorithm algorithm` parameters MUST be present. The syntax for `KeyWrapAlgorithm algorithm` parameters is

```
Gost28147-89-KeyWrapParameters ::=
  SEQUENCE {
    encryptionParamSet Gost28147-89-ParamSet,
    ukm                 OCTET STRING (SIZE (8)) OPTIONAL
  }
Gost28147-89-ParamSet ::= OBJECT IDENTIFIER
```

`Gost28147-89-KeyWrapParameters ukm` MUST be absent.

`KeyAgreeRecipientInfo ukm` MUST be present and contain eight octets.

`encryptedKey` MUST encapsulate `Gost28147-89-EncryptedKey`, where `maskKey` MUST be absent.

```
Gost28147-89-EncryptedKey ::= SEQUENCE {  
    encryptedKey      Gost28147-89-Key,  
    maskKey           [0] IMPLICIT Gost28147-89-Key  
                        OPTIONAL,  
    macKey            Gost28147-89-MAC  
}
```

Using the secret key corresponding to the originatorKey publicKey and the recipient's public key, the algorithm VKO GOST R 34.10-94 or VKO GOST R 34.10-2001 (described in [CPALGS]) is applied to produce the KEK.

Then the key wrap algorithm, specified by KeyWrapAlgorithm, is applied to produce CEK\_ENC, CEK\_MAC, and UKM. Gost28147-89-KeyWrapParameters encryptionParamSet is used for all encryption operations.

The resulting encrypted key (CEK\_ENC) is placed in the Gost28147-89-EncryptedKey encryptedKey field, its mac (CEK\_MAC) is placed in the Gost28147-89-EncryptedKey macKey field, and UKM is placed in the KeyAgreeRecipientInfo ukm field.

#### 4.2. Key Transport Algorithms

This section specifies the conventions employed by CMS implementations that support key transport using both the VKO GOST R 34.10-94 and VKO GOST R 34.10-2001 algorithms, described in [CPALGS].

Key transport algorithm identifiers are located in the EnvelopedData RecipientInfos KeyTransRecipientInfo keyEncryptionAlgorithm field.

Key transport encrypted content-encryption keys are located in the EnvelopedData RecipientInfos KeyTransRecipientInfo encryptedKey field.

##### 4.2.1. Key Transport Algorithm Based on GOST R 34.10-94/2001 Public Keys

The EnvelopedData RecipientInfos KeyTransRecipientInfo field is used as follows:

The version MUST be 0 or 3.

keyEncryptionAlgorithm and parameters MUST be identical to the recipient public key algorithm and parameters.



encryptedKey encapsulates GostR3410-KeyTransport, which consists of encrypted content-encryption key, its MAC, GOST 28147-89 algorithm parameters used for key encryption, the sender's ephemeral public key, and UKM (UserKeyingMaterial; see [CMS], Section 10.2.6).

transportParameters MUST be present.

ephemeralPublicKey MUST be present and its parameters, if present, MUST be equal to the recipient public key parameters;

```
GostR3410-KeyTransport ::= SEQUENCE {
    sessionEncryptedKey  Gost28147-89-EncryptedKey,
    transportParameters
    [0] IMPLICIT GostR3410-TransportParameters OPTIONAL
}

GostR3410-TransportParameters ::= SEQUENCE {
    encryptionParamSet  OBJECT IDENTIFIER,
    ephemeralPublicKey  [0] IMPLICIT SubjectPublicKeyInfo OPTIONAL,
    ukm                  OCTET STRING
}
```

Using the secret key corresponding to the GostR3410-TransportParameters ephemeralPublicKey and the recipient's public key, the algorithm VKO GOST R 34.10-94 or VKO GOST R 34.10-2001 (described in [CPALGS]) is applied to produce the KEK.

Then the CryptoPro key wrap algorithm is applied to produce CEK\_ENC, CEK\_MAC, and UKM. GostR3410-TransportParameters encryptionParamSet is used for all encryption operations.

The resulting encrypted key (CEK\_ENC) is placed in the Gost28147-89-EncryptedKey encryptedKey field, its mac (CEK\_MAC) is placed in the Gost28147-89-EncryptedKey macKey field, and UKM is placed in the GostR3410-TransportParameters ukm field.

## 5. Content Encryption Algorithms

This section specifies the conventions employed by CMS implementations that support content encryption using GOST 28147-89.

Content encryption algorithm identifiers are located in the EnvelopedData EncryptedContentInfo contentEncryptionAlgorithm and the EncryptedData EncryptedContentInfo contentEncryptionAlgorithm fields.

Content encryption algorithms are used to encipher the content located in the EnvelopedData EncryptedContentInfo encryptedContent field and the EncryptedData EncryptedContentInfo encryptedContent field.

### 5.1. Content Encryption Algorithm GOST 28147-89

This section specifies the use of GOST 28147-89 algorithm for data encipherment.

GOST 28147-89 is fully described in [[GOST28147](#)] (in Russian).

This document specifies the following object identifier (OID) for this algorithm:

```
id-Gost28147-89 OBJECT IDENTIFIER ::=
    { iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
      gost28147-89(21) }
```

Algorithm parameters MUST be present and have the following structure:

```
Gost28147-89-Parameters ::=
    SEQUENCE {
        iv                      Gost28147-89-IV,
        encryptionParamSet     OBJECT IDENTIFIER
    }
```

```
Gost28147-89-IV ::= OCTET STRING (SIZE (8))
```

encryptionParamSet specifies the set of corresponding Gost28147-89-ParamSetParameters (see Section 8.1 of [[CPALGS](#)])

## 6. MAC Algorithms

This section specifies the conventions employed by CMS implementations that support the message authentication code (MAC) based on GOST R 34.11-94.

MAC algorithm identifiers are located in the AuthenticatedData macAlgorithm field.

MAC values are located in the AuthenticatedData mac field.

### 6.1. HMAC with GOST R 34.11-94

HMAC\_GOSTR3411 (K,text) function is based on hash function GOST R 34.11-94, as defined in Section 3 of [[CPALGS](#)].

This document specifies the following OID for this algorithm:

```
id-HMACGostR3411-94 OBJECT IDENTIFIER ::=
    { iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
      hmacgostr3411(10) }
```

This algorithm has the same parameters as the GOST R 34.11-94 digest algorithm and uses the same OIDs for their identification (see [CPPK]).

## 7. Use with S/MIME

This section defines the use of the algorithms defined in this document with S/MIME [RFC3851].

### 7.1. Parameter micalg

When using the algorithms defined in this document, micalg parameter SHOULD be set to "gostr3411-94"; otherwise, it MUST be set to "unknown".

### 7.2. Attribute SMIMECapabilities

The SMIMECapability value that indicates support for the GOST R 34.11-94 digest algorithm is the SEQUENCE with the capabilityID field containing the object identifier id-GostR3411-94 and no parameters. The DER encoding is:

```
30 08 06 06 2A 85 03 02 02 09
```

The SMIMECapability value that indicates support for the GOST 28147-89 encryption algorithm is the SEQUENCE with the capabilityID field containing the object identifier id-Gost28147-89 and no parameters. The DER encoding is:

```
30 08 06 06 2A 85 03 02 02 15
```

If the sender wishes to indicate support for a specific parameter set, SMIMECapability parameters MUST contain the Gost28147-89-Parameters structure. Recipients MUST ignore the Gost28147-89-Parameters iv field and assume that the sender supports the parameters specified in the Gost28147-89-Parameters encryptionParamSet field.

The DER encoding for the SMIMECapability, indicating support for GOST 28147-89 with id-Gost28147-89-CryptoPro-A-ParamSet (see [CPALGS]), is:

```
30 1D 06 06 2A 85 03 02 02 15 30 13 04 08 00 00
00 00 00 00 00 00 06 07 2A 85 03 02 02 1F 01
```

## 8. Security Considerations

Conforming applications **MUST** use unique values for `ukm` and `iv`. Recipients **MAY** verify that `ukm` and `iv`, specified by the sender, are unique.

It is **RECOMMENDED** that software applications verify that signature values, subject public keys, and algorithm parameters conform to [GOSTR341001] and [GOSTR341094] standards prior to their use.

Cryptographic algorithm parameters affect algorithm strength. The use of parameters not listed in [CPALGS] is **NOT RECOMMENDED** (see the Security Considerations section of [CPALGS]).

Use of the same key for signature and key derivation is **NOT RECOMMENDED**. When signed CMS documents are used as an analogue to a manual signing, in the context of Russian Federal Electronic Digital Signature Law [RFEDSL], signer certificate **MUST** contain the `keyUsage` extension, it **MUST** be critical, and `keyUsage` **MUST NOT** include `keyEncipherment` or `keyAgreement` (see [PROFILE], Section 4.2.1.3). Application **SHOULD** be submitted for examination by an authorized agency in appropriate levels of `target_of_evaluation` (TOE), according to [RFEDSL], [RFLIC], and [CRYPTOLIC].

## 9. Examples

Examples here are stored in the same format as the examples in [RFC4134] and can be extracted using the same program.

If you want to extract without the program, copy all the lines between the `"|>"` and `"|<"` markers, remove any page breaks, and remove the `"|"` in the first column of each line. The result is a valid Base64 blob that can be processed by any Base64 decoder.

### 9.1. Signed Message

This message is signed using the sample certificate from Section 4.2 of [CPPK]. The public key (x,y) from the same section can be used to verify the message signature.

```
0 296: SEQUENCE {
4   9:  OBJECT IDENTIFIER signedData
15 281:  [0] {
19 277:    SEQUENCE {
23   1:    INTEGER 1
```

```
26 12: SET {
28 10:   SEQUENCE {
30 6:     OBJECT IDENTIFIER id-GostR3411-94
38 0:     NULL
   :     }
   :   }
40 27: SEQUENCE {
42 9:   OBJECT IDENTIFIER data
53 14:  [0] {
55 12:   OCTET STRING 73 61 6D 70 6C 65 20 74 65 78 74 0A
   :   }
   : }
69 228: SET {
72 225:   SEQUENCE {
75 1:     INTEGER 1
78 129:   SEQUENCE {
81 109:   SEQUENCE {
83 31:     SET {
85 29:       SEQUENCE {
87 3:        OBJECT IDENTIFIER commonName
92 22:       UTF8String 'GostR3410-2001 example'
   :       }
   :     }
116 18:   SET {
118 16:     SEQUENCE {
120 3:       OBJECT IDENTIFIER organizationName
125 9:       UTF8String 'CryptoPro'
   :       }
   :     }
136 11:   SET {
138 9:     SEQUENCE {
140 3:       OBJECT IDENTIFIER countryName
145 2:       PrintableString 'RU'
   :       }
   :     }
149 41:   SET {
151 39:     SEQUENCE {
153 9:       OBJECT IDENTIFIER emailAddress
164 26:       IA5String 'GostR3410-2001@example.com'
   :       }
   :     }
   :   }
192 16:   INTEGER
   :       2B F5 C6 1E C2 11 BD 17 C7 DC D4 62 66 B4 2E 21
   :     }
210 10: SEQUENCE {
212 6:   OBJECT IDENTIFIER id-GostR3411-94
220 0:   NULL
```

```

      :      }
222  10:      SEQUENCE {
224    6:      OBJECT IDENTIFIER id-GostR3410-2001
232    0:      NULL
      :      }
234  64:      OCTET STRING
      :      C0 C3 42 D9 3F 8F FE 25 11 11 88 77 BF 89 C3 DB
      :      83 42 04 D6 20 F9 68 2A 99 F6 FE 30 3B E4 F4 C8
      :      F8 D5 B4 DA FB E1 C6 91 67 34 1F BC A6 7A 0D 12
      :      7B FD 10 25 C6 51 DB 8D B2 F4 8C 71 7E ED 72 A9
      :      }
      :      }
      :      }
      :      }
      :      }
      :      }

```

```

|>GostR3410-2001-signed.bin
|MIIBKAYJKoZIhvcNAQcCoIIBGTCCARUCAQExDDAKBgYqhQMCAgkFADAbBgkqhkiG
|9w0BBWgDgQMc2FtcGxliHRleHQMYHkMIHhAgEBMIGBMG0xHzAdBgNVBAMMFkdv
|c3RSMzQxMC0yMDAxIGV4YW1wbGUxEjAQBgNVBAoMCUNyeXB0b1BybzELMAkGA1UE
|BhMCUlUxKTAnBgkqhkiG9w0BCQEWGkdvc3RSMzQxMC0yMDAxQGV4YW1wbGUuY29t
|AhAr9cYewhG9F8fc1GJmtC4hMAoGBiqFAwICCQUAMAAoGBiqFAwICEwUABEDAw0LZ
|P4/+JRERiHe/icPbg0IEliD5aCqZ9v4wO+T0yPjVtNr74caRZzQfvKZ6DRJ7/RAl
|xlHbjbL0jHF+7XKp
|<GostR3410-2001-signed.bin

```

## 9.2. Enveloped Message Using Key Agreement

This message is encrypted using the sample certificate from [Section 4.2](#) of [CPPK] as a recipient certificate. The private key 'd' from the same section can be used to decrypt this message.

```

0  420: SEQUENCE {
4    9:  OBJECT IDENTIFIER envelopedData
15  405:  [0] {
19  401:    SEQUENCE {
23    1:      INTEGER 2
26  336:    SET {
30  332:      [1] {
34    1:        INTEGER 3
37  101:      [0] {
39    99:        [1] {
41  28:          SEQUENCE {
43    6:            OBJECT IDENTIFIER id-GostR3410-2001
51  18:            SEQUENCE {
53    7:              OBJECT IDENTIFIER
      :              id-GostR3410-2001-CryptoPro-XchA-ParamSet
62    7:              OBJECT IDENTIFIER

```

```

      :      id-GostR3411-94-CryptoProParamSet
      :      }
      :      }
71  67:      BIT STRING, encapsulates {
74  64:      OCTET STRING
      :      B3 55 39 F4 67 81 97 2B A5 C4 D9 84 1F 27 FB 81
      :      ED 08 32 E6 9A D4 F2 00 78 B8 FF 83 64 EA D2 1D
      :      B0 78 3C 7D FE 03 C1 F4 06 E4 3B CC 16 B9 C5 F6
      :      F6 19 37 1C 17 B8 A0 AA C7 D1 A1 94 B3 A5 36 20
      :      }
      :      }
      :      }
140 10:      [1] {
142  8:      OCTET STRING 2F F0 F6 D1 86 4B 32 8A
      :      }
152 30:      SEQUENCE {
154  6:      OBJECT IDENTIFIER id-GostR3410-2001-CryptoPro-ESDH
162 20:      SEQUENCE {
164  7:      OBJECT IDENTIFIER id-Gost28147-89-None-KeyWrap
173  9:      SEQUENCE {
175  7:      OBJECT IDENTIFIER
      :      id-Gost28147-89-CryptoPro-A-ParamSet
      :      }
      :      }
      :      }
184 179:     SEQUENCE {
187 176:     SEQUENCE {
190 129:     SEQUENCE {
193 109:     SEQUENCE {
195  31:     SET {
197  29:     SEQUENCE {
199  3:     OBJECT IDENTIFIER commonName
204 22:     UTF8String 'GostR3410-2001 example'
      :     }
      :     }
228 18:     SET {
230 16:     SEQUENCE {
232  3:     OBJECT IDENTIFIER organizationName
237  9:     UTF8String 'CryptoPro'
      :     }
      :     }
248 11:     SET {
250  9:     SEQUENCE {
252  3:     OBJECT IDENTIFIER countryName
257  2:     PrintableString 'RU'
      :     }
      :     }
261 41:     SET {

```

```

263  39:      SEQUENCE {
265    9:      OBJECT IDENTIFIER emailAddress
276   26:      IA5String 'GostR3410-2001@example.com'
      :      }
      :      }
      :      }
304   16:      INTEGER
      :      2B F5 C6 1E C2 11 BD 17 C7 DC D4 62 66 B4 2E 21
      :      }
322   42:      OCTET STRING, encapsulates {
324   40:      SEQUENCE {
326   32:      OCTET STRING
      :      16 A3 1C E7 CE 4E E9 0D F1 EC 74 69 04 68 1E C7
      :      9F 3A ED B8 3B 1F 1D 4A 7E F9 A5 D9 CB 19 D5 E8
360    4:      OCTET STRING
      :      93 FD 86 7E
      :      }
      :      }
      :      }
      :      }
      :      }
      :      }
366   56:      SEQUENCE {
368    9:      OBJECT IDENTIFIER data
379   29:      SEQUENCE {
381    6:      OBJECT IDENTIFIER id-Gost28147-89
389   19:      SEQUENCE {
391    8:      OCTET STRING B7 35 E1 7A 07 35 A2 1D
401    7:      OBJECT IDENTIFIER id-Gost28147-89-CryptoPro-A-ParamSet
      :      }
      :      }
410   12:      [0] 39 B1 8A F4 BF A9 E2 65 25 B6 55 C9
      :      }
      :      }
      :      }
      :      }

```

```

|>GostR3410-2001-keyagree.bin
|MIIBpAYJKoZIhvcNAQcDoIIBlTCCAQECAQIxggFQoYIBTAIBA6BloWMwHAYGKoUD
|AgITMBIGByqFAwICJAAGByqFAwICHgEDQwAEQLNVOFRngZcrpcTZhB8n+4HtCDLm
|mtTyAHi4/4Nk6tIdsHg8ff4DwfQG5DvMFrnF9vYZNxwXuKCqx9GhlLOlNiChCgQI
|L/D20YZLMoowHgYGKouDAgJgMBQGBYqFAwICDQAwCQYHKouDAgIfATCBszCBsDCB
|gTBtMR8wHQYDVQQDDDBZHb3N0UjM0MTAtMjAwMSbleGFTcGxlMRIwEAYDVQQKDAld
|cnlwdG9Qcm8xCzAJBgNVBAYTAJVMskwJwYJKoZIhvcNAQkBFhpHb3N0UjM0MTAt
|MjAwMUBleGFTcGxlLmNvbQIQK/XGHsIRvRfH3NRiZrQuIQQqMCgEIBajHOfOTukN
|8ex0aQRoHsefOu240x8dSn75pdnLGdXoBAST/YZ+MDgGCSqGSib3DQEHATAdBgYq
|hQMcAhUwEwQItzXhegcloh0GBYqFAwICHwGADDmxivS/qeJlJbZVyQ==
|<GostR3410-2001-keyagree.bin

```



### 9.3. Enveloped Message Using Key Transport

This message is encrypted using the sample certificate from [Section 4.2](#) of [CPPK] as a recipient certificate. The private key 'd' from the same section can be used to decrypt this message.

```
0  423: SEQUENCE {
4    9:  OBJECT IDENTIFIER envelopedData
15  408:  [0] {
19  404:    SEQUENCE {
23    1:    INTEGER 0
26  339:    SET {
30  335:      SEQUENCE {
34    1:      INTEGER 0
37  129:      SEQUENCE {
40  109:        SEQUENCE {
42    31:        SET {
44    29:          SEQUENCE {
46    3:            OBJECT IDENTIFIER commonName
51   22:            UTF8String 'GostR3410-2001 example'
      :          }
      :        }
75   18:      SET {
77   16:        SEQUENCE {
79    3:          OBJECT IDENTIFIER organizationName
84    9:          UTF8String 'CryptoPro'
      :        }
      :      }
95   11:      SET {
97    9:        SEQUENCE {
99    3:          OBJECT IDENTIFIER countryName
104   2:          PrintableString 'RU'
      :        }
      :      }
108  41:      SET {
110  39:        SEQUENCE {
112   9:          OBJECT IDENTIFIER emailAddress
123  26:          IA5String 'GostR3410-2001@example.com'
      :        }
      :      }
151  16:      INTEGER
      :      2B F5 C6 1E C2 11 BD 17 C7 DC D4 62 66 B4 2E 21
      :    }
169  28:      SEQUENCE {
171   6:        OBJECT IDENTIFIER id-GostR3410-2001
179  18:        SEQUENCE {
181   7:          OBJECT IDENTIFIER
```

```

      :      id-GostR3410-2001-CryptoPro-XchA-ParamSet
190   7:      OBJECT IDENTIFIER
      :      id-GostR3411-94-CryptoProParamSet
      :      }
      :      }
199 167:      OCTET STRING, encapsulates {
202 164:      SEQUENCE {
205 40:      SEQUENCE {
207 32:      OCTET STRING
      :      6A 2F A8 21 06 95 68 9F 9F E4 47 AA 9E CB 61 15
      :      2B 7E 41 60 BC 5D 8D FB F5 3D 28 1B 18 9A F9 75
241 4:      OCTET STRING
      :      36 6D 98 B7
      :      }
247 120:      [0] {
249 7:      OBJECT IDENTIFIER
      :      id-Gost28147-89-CryptoPro-A-ParamSet
258 99:      [0] {
260 28:      SEQUENCE {
262 6:      OBJECT IDENTIFIER id-GostR3410-2001
270 18:      SEQUENCE {
272 7:      OBJECT IDENTIFIER
      :      id-GostR3410-2001-CryptoPro-XchA-ParamSet
281 7:      OBJECT IDENTIFIER
      :      id-GostR3411-94-CryptoProParamSet
      :      }
      :      }
290 67:      BIT STRING encapsulates {
293 64:      OCTET STRING
      :      4D 2B 2F 33 90 E6 DC A3 DD 55 2A CD DF E0 EF FB
      :      31 F7 73 7E 4E FF BF 78 89 8A 2B C3 CD 31 94 04
      :      4B 0E 60 48 96 1F DB C7 5D 12 6F DA B2 40 8A 77
      :      B5 BD EA F2 EC 34 CB 23 9F 9B 8B DD 9E 12 C0 F6
      :      }
      :      }
359 8:      OCTET STRING
      :      97 95 E3 2C 2B AD 2B 0C
      :      }
      :      }
      :      }
      :      }
369 56:      SEQUENCE {
371 9:      OBJECT IDENTIFIER data
382 29:      SEQUENCE {
384 6:      OBJECT IDENTIFIER id-Gost28147-89
392 19:      SEQUENCE {
394 8:      OCTET STRING BC 10 8B 1F 0B FF 34 29

```

```

404      7:      OBJECT IDENTIFIER id-Gost28147-89-CryptoPro-A-ParamSet
      :      }
      :      }
413     12:      [0] AA 8E 72 1D EE 4F B3 2E E3 0F A1 37
      :      }
      :      }
      :      }
      :      }

```

```

|>GostR3410-2001-keytrans.bin
|MIIBpwYJKoZIhvcNAQcDoIIbMDCCAQCAQAxggFTMIIBTWIBADCBgTBtMR8wHQYD
|VQQDDBZHb3N0UjM0MTAtMjAwMSBleGFTcGxlMRIwEAYDVQQKDA1DcnlwdG9Qcm8x
|CzAJBgNVBAYTAlJVMskwJwYJKoZIhvcNAQkBFhpHb3N0UjM0MTAtMjAwMUBleGFT
|cGxlLmNvbQIQK/XGHsIRvRfH3NRiZrQuITAcBgYqhQMCAhMwEgYHKoUDAgIkAAAYH
|KoUDAgIeAQSBpzCBpDAoBCBqL6ghBpVon5/kR6qey2EVK35BYLxdjfv1PSgbGJr5
|dQQENm2Yt6B4BgcqhQMCAh8BoGMwHAYGKoUDAgITMBIGByqFAwICJAAGByqFAwIC
|HgEDQwAEQE0rLzOQ5tyj3VUqzd/g7/sx93N+Tv+/eImKK8PNMZQESw5gSJYf28dd
|Em/askCKd7W96vLsNMsjn5uL3Z4SwPYECJeV4ywrrSsMMDgGCSqGSib3DQEHATA
|BgYqhQMCAhUwEwQIvBCLHwv/NCKGBYqFAwICHwGADKqOch3uT7Mu4w+hNw==
|<GostR3410-2001-keytrans.bin

```

## 10. ASN.1 Modules

Additional ASN.1 modules, referenced here, can be found in [CPALGS].

### 10.1. GostR3410-EncryptionSyntax

```

GostR3410-EncryptionSyntax
{ iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
  other(1) modules(1) gostR3410-EncryptionSyntax(5) 2 }
DEFINITIONS ::=
BEGIN
-- EXPORTS All --
-- The types and values defined in this module are exported for
-- use in the other ASN.1 modules contained within the Russian
-- Cryptography "GOST" & "GOST R" Specifications, and for the use
-- of other applications which will use them to access Russian
-- Cryptography services. Other applications may use them for
-- their own purposes, but this will not constrain extensions and
-- modifications needed to maintain or improve the Russian
-- Cryptography service.
IMPORTS
    id-CryptoPro-algorithms,
    gost28147-89-EncryptionSyntax,
    gostR3410-94-PKISyntax,
    gostR3410-2001-PKISyntax,
    ALGORITHM-IDENTIFIER,
    cryptographic-Gost-Useful-Definitions

```

```

FROM Cryptographic-Gost-Useful-Definitions -- in [CPALGS]
  { iso(1) member-body(2) ru(643) rans(2)
    cryptopro(2) other(1) modules(1)
    cryptographic-Gost-Useful-Definitions(0) 1 }
id-GostR3410-94
FROM GostR3410-94-PKISyntax -- in [CPALGS]
  gostR3410-94-PKISyntax
id-GostR3410-2001
FROM GostR3410-2001-PKISyntax -- in [CPALGS]
  gostR3410-2001-PKISyntax
Gost28147-89-ParamSet,
Gost28147-89-EncryptedKey
FROM Gost28147-89-EncryptionSyntax -- in [CPALGS]
  gost28147-89-EncryptionSyntax
SubjectPublicKeyInfo
FROM PKIX1Explicit88 {iso(1) identified-organization(3)
dod(6) internet(1) security(5) mechanisms(5) pkix(7)
id-mod(0) id-pkix1-explicit-88(1)}
;
-- CMS/PKCS#7 key agreement algorithms & parameters
Gost28147-89-KeyWrapParameters ::=
  SEQUENCE {
    encryptionParamSet Gost28147-89-ParamSet,
    ukm OCTET STRING (SIZE (8)) OPTIONAL
  }
id-Gost28147-89-CryptoPro-KeyWrap OBJECT IDENTIFIER ::=
  { id-CryptoPro-algorithms keyWrap(13) cryptoPro(1) }
id-Gost28147-89-None-KeyWrap OBJECT IDENTIFIER ::=
  { id-CryptoPro-algorithms keyWrap(13) none(0) }
Gost28147-89-KeyWrapAlgorithms ALGORITHM-IDENTIFIER ::= {
  { Gost28147-89-KeyWrapParameters IDENTIFIED BY
    id-Gost28147-89-CryptoPro-KeyWrap } |
  { Gost28147-89-KeyWrapParameters IDENTIFIED BY
    id-Gost28147-89-None-KeyWrap }
}
id-GostR3410-2001-CryptoPro-ESDH OBJECT IDENTIFIER ::=
  { id-CryptoPro-algorithms
    gostR3410-2001-CryptoPro-ESDH(96) }
id-GostR3410-94-CryptoPro-ESDH OBJECT IDENTIFIER ::=
  { id-CryptoPro-algorithms
    gostR3410-94-CryptoPro-ESDH(97) }
-- CMS/PKCS#7 key transport algorithms & parameters
-- OID for CMS/PKCS#7 Key transport is id-GostR3410-94 from
--   GostR3410-94-PKISyntax or id-GostR3410-2001 from
--   GostR3410-2001-PKISyntax
-- Algorithms for CMS/PKCS#7 Key transport are
--   GostR3410-94-PublicKeyAlgorithms from
--   GostR3410-94-PKISyntax or

```

```

--      GostR3410-2001-PublicKeyAlgorithms from
--      GostR3410-2001-PKISyntax
-- SMIMECapability for CMS/PKCS#7 Key transport are
--      id-GostR3410-94 from GostR3410-94-PKISyntax or
--      id-GostR3410-2001 from GostR3410-2001-PKISyntax
id-GostR3410-94-KeyTransportSMIMECapability
    OBJECT IDENTIFIER ::= id-GostR3410-94
id-GostR3410-2001-KeyTransportSMIMECapability
    OBJECT IDENTIFIER ::= id-GostR3410-2001
GostR3410-KeyTransport ::=
    SEQUENCE {
        sessionEncryptedKey Gost28147-89-EncryptedKey,
        transportParameters [0]
            IMPLICIT GostR3410-TransportParameters OPTIONAL
    }
GostR3410-TransportParameters ::=
    SEQUENCE {
        encryptionParamSet Gost28147-89-ParamSet,
        ephemeralPublicKey [0]
            IMPLICIT SubjectPublicKeyInfo OPTIONAL,
        ukm
            OCTET STRING ( SIZE(8) )
    }
END -- GostR3410-EncryptionSyntax

```

## 10.2. GostR3410-94-SignatureSyntax

```

GostR3410-94-SignatureSyntax
    { iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
      other(1) modules(1) gostR3410-94-SignatureSyntax(3) 1 }
DEFINITIONS ::=
BEGIN
-- EXPORTS All --
-- The types and values defined in this module are exported for
-- use in the other ASN.1 modules contained within the Russian
-- Cryptography "GOST" & "GOST R" Specifications, and for the use
-- of other applications which will use them to access Russian
-- Cryptography services. Other applications may use them for
-- their own purposes, but this will not constrain extensions and
-- modifications needed to maintain or improve the Russian
-- Cryptography service.
IMPORTS
    gostR3410-94-PKISyntax, ALGORITHM-IDENTIFIER,
    cryptographic-Gost-Useful-Definitions
FROM Cryptographic-Gost-Useful-Definitions -- in [CPALGS]
    { iso(1) member-body(2) ru(643) rans(2)
      cryptopro(2) other(1) modules(1)
        cryptographic-Gost-Useful-Definitions(0) 1 }
    id-GostR3410-94,

```

```
GostR3410-94-PublicKeyParameters
FROM GostR3410-94-PKISyntax -- in [CPALGS]
    gostR3410-94-PKISyntax
;
-- GOST R 34.10-94 signature data type
GostR3410-94-Signature ::=
    OCTET STRING (SIZE (64))
-- GOST R 34.10-94 signature algorithm & parameters
GostR3410-94-CMSSignatureAlgorithms ALGORITHM-IDENTIFIER ::= {
    { GostR3410-94-PublicKeyParameters IDENTIFIED BY
        id-GostR3410-94 }
}
END -- GostR3410-94-SignatureSyntax
```

### 10.3. GostR3410-2001-SignatureSyntax

```
GostR3410-2001-SignatureSyntax
{ iso(1) member-body(2) ru(643) rans(2) cryptopro(2)
  other(1) modules(1) gostR3410-2001-SignatureSyntax(10) 1 }
DEFINITIONS ::=
BEGIN
-- EXPORTS All --
-- The types and values defined in this module are exported for
-- use in the other ASN.1 modules contained within the Russian
-- Cryptography "GOST" & "GOST R" Specifications, and for the use
-- of other applications which will use them to access Russian
-- Cryptography services. Other applications may use them for
-- their own purposes, but this will not constrain extensions and
-- modifications needed to maintain or improve the Russian
-- Cryptography service.
IMPORTS
    gostR3410-2001-PKISyntax, ALGORITHM-IDENTIFIER,
    cryptographic-Gost-Useful-Definitions
FROM Cryptographic-Gost-Useful-Definitions -- in [CPALGS]
    { iso(1) member-body(2) ru(643) rans(2)
      cryptopro(2) other(1) modules(1)
      cryptographic-Gost-Useful-Definitions(0) 1 }
    id-GostR3410-2001,
    GostR3410-2001-PublicKeyParameters -- in [CPALGS]
FROM GostR3410-2001-PKISyntax
    gostR3410-2001-PKISyntax
;
-- GOST R 34.10-2001 signature data type
GostR3410-2001-Signature ::=
    OCTET STRING (SIZE (64))
-- GOST R 34.10-2001 signature algorithms and parameters
GostR3410-2001-CMSSignatureAlgorithms
```

```
    ALGORITHM-IDENTIFIER ::= {  
        { GostR3410-2001-PublicKeyParameters IDENTIFIED BY  
          id-GostR3410-2001 }  
    }  
END -- GostR3410-2001-SignatureSyntax
```

## 11. Acknowledgements

This document was created in accordance with "Russian Cryptographic Software Compatibility Agreement", signed by FGUE STC "Atlas", CRYPTO-PRO, Factor-TS, MD PREI, Infotecs GmbH, SPRCIS (SPbRCZI), Cryptocom, R-Alpha. The aim of this agreement is to achieve mutual compatibility of the products and solutions.

The authors wish to thank:

Microsoft Corporation Russia for providing information about company products and solutions, and also for technical consulting in PKI.

RSA Security Russia and Demos Co Ltd for active collaboration and critical help in creation of this document.

Russ Housley (Vigil Security, LLC, housley@vigilsec.com) and Vasilij Sakharov (DEMOS Co Ltd, svp@dol.ru) for encouraging the authors to create this document.

Prihodko Dmitriy (VSTU, PrihodkoDV@volgablob.ru) for invaluable assistance in proofreading this document and verifying the form and the contents of the ASN.1 structures mentioned or used in this document.

## 12. References

### 12.1. Normative References

- [CMS] Housley, R., "Cryptographic Message Syntax (CMS)", [RFC 3852](#), July 2004.
- [CPALGS] Popov, V., Kurepkin, I., and S. Leontiev, "Additional Cryptographic Algorithms for Use with GOST 28147-89, GOST R 34.10-94, GOST R 34.10-2001, and GOST R 34.11-94 Algorithms", [RFC 4357](#), January 2006.
- [CPPK] Leontiev, S., Ed. and D. Shefanovskij, Ed., "Using the GOST R 34.10-94, GOST R 34.10-2001, and GOST R 34.11-94 Algorithms with the Internet X.509 Public Key Infrastructure Certificate and CRL Profile", [RFC 4491](#), May 2006.
- [GOST28147] "Cryptographic Protection for Data Processing System", GOST 28147-89, Gosudarstvennyi Standard of USSR, Government Committee of the USSR for Standards, 1989. (In Russian)
- [GOST3431195] "Information technology. Cryptographic Data Security. Cashing function.", GOST 34.311-95, Council for Standardization, Metrology and Certification of the Commonwealth of Independence States (EASC), Minsk, 1995. (In Russian)
- [GOST3431095] "Information technology. Cryptographic Data Security. Produce and check procedures of Electronic Digital Signature based on Asymmetric Cryptographic Algorithm.", GOST 34.310-95, Council for Standardization, Metrology and Certification of the Commonwealth of Independence States (EASC), Minsk, 1995. (In Russian)
- [GOST3431004] "Information technology. Cryptographic Data Security. Formation and verification processes of (electronic) digital signature based on Asymmetric Cryptographic Algorithm.", GOST 34.310-2004, Council for Standardization, Metrology and Certification of the Commonwealth of Independence States (EASC), Minsk, 2004. (In Russian)



- [GOSTR341094] "Information technology. Cryptographic Data Security. Produce and check procedures of Electronic Digital Signatures based on Asymmetric Cryptographic Algorithm.", GOST R 34.10-94, Gosudarstvennyi Standard of Russian Federation, Government Committee of the Russia for Standards, 1994. (In Russian)
- [GOSTR341001] "Information technology. Cryptographic data security. Signature and verification processes of [electronic] digital signature.", GOST R 34.10-2001, Gosudarstvennyi Standard of Russian Federation, Government Committee of the Russia for Standards, 2001. (In Russian)
- [GOSTR341194] "Information technology. Cryptographic Data Security. Hashing function.", GOST R 34.10-94, Gosudarstvennyi Standard of Russian Federation, Government Committee of the Russia for Standards, 1994. (In Russian)
- [PROFILE] Housley, R., Polk, W., Ford, W., and D. Solo, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 3280](#), April 2002.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3851] Ramsdell, B., "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.1 Message Specification", [RFC 3851](#), July 2004.
- [X.208-88] CCITT. Recommendation X.208: Specification of Abstract Syntax Notation One (ASN.1). 1988.
- [X.209-88] CCITT. Recommendation X.209: Specification of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1). 1988.

## 12.2. Informative References

- [CRYPTOLIC] "Russian Federal Government Regulation on Licensing of Selected Activity Categories in Cryptography Area", 23 Sep 2002 N 691.
- [RFC4134] Hoffman, P., "Examples of S/MIME Messages", [RFC 4134](#), July 2005.
- [RFEDSL] "Russian Federal Electronic Digital Signature Law", 10 Jan 2002 N 1-FZ.

- [RFLIC] "Russian Federal Law on Licensing of Selected Activity Categories", 08 Aug 2001 N 128-FZ.
- [Schneier95] B. Schneier, *Applied Cryptography*, Second Edition, John Wiley & Sons, Inc., 1995.

## Authors' Addresses

Serguei Leontiev, Ed.  
CRYPTO-PRO  
38, Obrastsova,  
Moscow, 127018, Russian Federation

EMail: lse@cryptopro.ru

Grigorij Chudov, Ed.  
CRYPTO-PRO  
38, Obrastsova,  
Moscow, 127018, Russian Federation

EMail: chudov@cryptopro.ru

Vladimir Popov  
CRYPTO-PRO  
38, Obrastsova,  
Moscow, 127018, Russian Federation

EMail: vpopov@cryptopro.ru

Alexandr Afanasiev  
Factor-TS  
office 711, 14, Presnenskij val,  
Moscow, 123557, Russian Federation

EMail: afal@factor-ts.ru

Nikolaj Nikishin  
Infotecs GmbH  
p/b 35, 80-5, Leningradskij prospekt,  
Moscow, 125315, Russian Federation

EMail: nikishin@infotecs.ru

Boleslav Izotov  
FGUE STC "Atlas"  
38, Obrastsova,  
Moscow, 127018, Russian Federation

EMail: izotov@nii.voskhod.ru

Elena Minaeva  
MD PREI  
build 3, 6A, Vtoroj Troitskij per.,  
Moscow, Russian Federation

E-Mail: [evminaeva@mail.ru](mailto:evminaeva@mail.ru)

Igor Ovcharenko  
MD PREI  
Office 600, 14, B.Novodmitrovskaya,  
Moscow, Russian Federation

E-Mail: [igori@mo.msk.ru](mailto:igori@mo.msk.ru)

Serguei Murugov  
R-Alpha  
4/1, Raspletina,  
Moscow, 123060, Russian Federation

E-Mail: [msm@top-cross.ru](mailto:msm@top-cross.ru)

Igor Ustinov  
Cryptocom  
office 239, 51, Leninskij prospekt,  
Moscow, 119991, Russian Federation

E-Mail: [igus@cryptocom.ru](mailto:igus@cryptocom.ru)

Anatolij Erkin  
SPRCIS (SPbRCZI)  
1, Obrucheva,  
St.Petersburg, 195220, Russian Federation

E-Mail: [erkin@nevsky.net](mailto:erkin@nevsky.net)

## Full Copyright Statement

Copyright (C) The Internet Society (2006).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

## Acknowledgement

Funding for the RFC Editor function is provided by the IETF Administrative Support Activity (IASA).