                      Fibre Channel Name Server MIB

Status of This Memo

   This document specifies an Internet standards track protocol for the
   Internet community, and requests discussion and suggestions for
   improvements. Please refer to the current edition of the "Internet
   Official Protocol Standards" (STD 1) for the standardization state
   and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Abstract

   This memo defines a portion of the Management Information Base (MIB)
   for use with network management protocols in the Internet community.
   In particular, it describes managed objects for information related
   to the Name Server function of a Fibre Channel network. The Fibre
   Channel Name Server provides a means for Fibre Channel ports to
   register and discover Fibre Channel names and attributes.

Table of Contents

1. Introduction

   This memo defines a portion of the Management Information Base (MIB)
   for use with network management protocols in the Internet community.
   In particular, it describes managed objects for information related
   to the Fibre Channel network's Name Server function, which provides a
   means for Fibre Channel ports to register and discover Fibre Channel
   attributes. Such attributes include names, addresses, types,
   features, etc., at various protocol layers.

2. The Internet-Standard Management Framework

   For a detailed overview of the documents that describe the current
   Internet-Standard Management Framework, please refer to section 7 of
   RFC 3410 [RFC3410].

   Managed objects are accessed via a virtual information store, termed
   the Management Information Base or MIB. MIB objects are generally
   accessed through the Simple Network Management Protocol (SNMP).
   Objects in the MIB are defined using the mechanisms defined in the
   Structure of Management Information (SMI). This memo specifies a MIB
   module that is compliant to the SMIv2, which is described in STD 58,
   RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580
   [RFC2580].

3. Short Overview of Fibre Channel

   The Fibre Channel (FC) is logically a bidirectional point-to-point
   serial data channel, structured for high performance. Fibre Channel
   provides a general transport vehicle for higher-level protocols such
   as Small Computer System Interface (SCSI) command sets, the High-
   Performance Parallel Interface (HIPPI) data framing, IP (Internet
   Protocol), IEEE 802.2, and others.

   Physically, Fibre Channel is an interconnection of multiple
   communication points, called N_Ports, interconnected either by a
   switching network, called a Fabric, or by a point-to-point link. A
   Fibre Channel "node" consists of one or more N_Ports. A Fabric may
   consist of multiple Interconnect Elements, some of which are
   switches. An N_Port connects to the Fabric via a port on a switch
   called an F_Port. When multiple FC nodes are connected to a single
   port on a switch via an "Arbitrated Loop" topology, the switch port
   is called an FL_Port, and the nodes' ports are called NL_Ports. The
   term Nx_Port is used to refer to either an N_Port or an NL_Port. The
   term Fx_Port is used to refer to either an F_Port or an FL_Port. A
   switch port, which is interconnected to another switch port via an

Inter-Switch Link (ISL), is called an E_Port. A B_Port connects a
bridge device with an E_Port on a switch; a B_Port provides a subset
of E_Port functionality.

Many Fibre Channel components, including the Fabric, each node, and
most ports, have globally-unique names. These globally-unique names
are typically formatted as World Wide Names (WWNs). More information
on WWNs can be found in [FC-FS]. WWNs are expected to be persistent
across agent and unit resets.

Fibre Channel frames contain 24-bit address identifiers, which
identify the frame's source and destination ports. Each FC port has
both an address identifier and a WWN. When a fabric is in use, the
FC address identifiers are dynamic and are assigned by a switch.
Each octet of a 24-bit address represents a level in an address
hierarchy, with a Domain_ID being the highest level of the hierarchy.

The Fibre Channel Name Server provides a way for N_Ports and NL_Ports
to register and discover Fibre Channel attributes. Such attributes
include names, addresses, types, features, etc., at various protocol
layers, including upper layer protocols specific to Fibre Channel
(which are sometimes called "FC-4s"). Communication with the Name
Server is via Fibre Channel's CT (Common Transport for Generic
Services) using "Information Units" (called CT_IUs) as either
requests, responses, or unsolicited.

Registrations may be performed by a third party. However, the Name
Server may refuse such third-party registration for unspecified
reasons. Once registered, the attributes are made available to
requestors.

Requestors could learn about new registrations via periodic polling
of the Name Server, but such polling would generate a considerable
overhead. To avoid this overhead, the Registered State Change
Notification (RSCN) mechanism defined in FC-FS [FC-FS] allows an
Nx_Port to register to receive an RSCN whenever an event occurs that
may affect the state of other Nx_Port(s), including changes in the
information registered with the Name Server.

The Fibre Channel Name Server is defined in the FC-GS specification,
The latest specification is [FC-GS-4]; the previous version was
[FC-GS-3].

4. Relationship to Other MIBs

   The first standardized MIB for Fibre Channel [RFC2837] was focused on
   Fibre Channel switches. It was obsoleted by the more generic Fibre
   Channel Management MIB [FC-MGMT], which defines basic information for
   Fibre Channel hosts and switches, including extensions to the
   standard IF-MIB [IF-MIB] for Fibre Channel interfaces.

   This MIB extends beyond [FC-MGMT] to cover the functionality, in
   Fibre Channel switches, of providing Fibre Channel's Name Server
   function.

   This MIB also imports some common textual conventions from
   T11-TC-MIB, defined in [FC-FAM-MIB].

5. MIB Overview

   This MIB module provides the means for monitoring the operation of,
   and configuring some parameters of, one or more instances of Fibre
   Channel Name Server functionality. (Note that there are no
   definitions in this MIB module of "managed actions" that can be
   invoked via SNMP.)

5.1. Fibre Channel Management Instance

   A Fibre Channel management instance is defined in [FC-MGMT] as a
   separable managed instance of Fibre Channel functionality. Fibre
   Channel functionality may be grouped into Fibre Channel management
   instances in whatever way is most convenient for the
   implementation(s). For example, one such grouping accommodates a
   single SNMP agent having multiple AgentX [RFC2741] sub-agents, with
   each sub-agent implementing a different Fibre Channel management
   instance.

   The object, fcmInstanceIndex, is IMPORTed from the FC-MGMT-MIB
   [FC-MGMT] as the index value to uniquely identify each Fibre Channel
   management instance within the same SNMP context ([RFC3411], section
   3.3.1).

5.2. Name Server Information Subset

   In addition to allowing for multiple Fibre Channel management
   instances, this MIB is based on the notion that the information
   registered with the Name Server is available as one or more subsets.
   The MIB allows the different subsets to be accessed either:

      - via different SNMP agents/contexts,
      - via different Fibre Channel management instances within the
        same SNMP agent/context, and/or
      - via the same Fibre Channel management instance within the
        same SNMP agent/context.

   The union of these subsets (across all agents/contexts in the
   network) represents the total set of information registered with the
   Name Server. Note that the intersection of the subsets is often
   non-empty, and the use of the term "subset" does not preclude any
   subset from containing the complete set of Name Server information.
   Each of these subsets is identified using an index value called a
   Name Server Information Subset Index.

   Thus, all objects in this MIB are in tables that are INDEXed by at
   least fcmInstanceIndex and t11NsInfoSubsetIndex, where the latter
   contains a Name Server Information Subset Index value.

5.3. Fabric Index

   The [FC-SW-3] standard for an interconnecting Fabric consisting of
   multiple Fabric Switch elements describes the operation of a single
   Fabric in a physical infrastructure. The current [FC-SW-4] standard
   also supports the operation of multiple Virtual Fabrics operating
   within one (or more) physical infrastructures. In such a scenario,
   each Fabric has, of course, its own management instrumentation. In
   order to accommodate this scenario, this MIB module defines all
   Fabric-related information in tables that are INDEXed by an arbitrary
   integer, named a "Fabric Index". In a Fabric that is conformant to
   [FC-SW-3], the value of this Fabric Index will always be 1.

5.4. The MIB Groups

   This section describes the six MIB groups contained in the MIB.

5.4.1. The t11NsDBGroup Group

   This group contains information about the operation of the Name
   Server function acting upon a Name Server Information Subset,
   including an indication of whether such operation is performed local
   to a particular Fibre Channel switch, or independently of a Fibre
   Channel switch. It also contains the information currently
   registered in a particular Name Server Information Subset.

5.4.2. Three Statistics Groups

   There are three groups of Name Server statistics objects:

        t11NsRequestStatsGroup -- stats about requests
        t11NsRscnStatsGroup   -- stats about (Name Server) RSCNs
        t11NsRejectStatsGroup -- stats about rejects

   Each of these groups is conditionally mandatory; specifically, each
   group contains objects for particular statistics such that
   implementation of the group is mandatory only for an implementation
   that counts/captures the group's particular statistics.

   The intent here is not to force implementations to capture these
   statistics, but rather to have all implementations that do capture
   them, provide access to them via the same MIB objects.

5.4.3. The t11NsNotifyGroup Group

   This group contains a set of notifications that provide for
   monitoring the rejections of Name Server Registration Requests.

5.4.4. The t11NsNotifyControlGroup Group

   This group contains objects for controlling the generation of, and
   for information to be included in, the notifications defined in the
   t11NsNotifyGroup group.

5.5. The Actual Values of Objects

   The objects defined in the t11NsRegTable represent the values
   registered with the Name Server. The SNMP agent MUST report the
   actual values, even if they are incorrectly formatted. This is the
   reason why, for example, the two objects that represent IP addresses,
   t11NsNodeIpAddress and t11NsPortIpAddress, have the SYNTAX of OCTET
   STRING, so that they are able to represent invalid values (which
   could not be represented using InetAddressType and InetAddress).

   Similarly, each set of (t11NsRejectReasonCode, t11NsRejReasonCodeExp,
   t11NsRejReasonVendorCode) objects must hold the values of the actual
   reject, explanation, and vendor-specific codes that were present in
   the generated Reject message (the "Reject CT_IU"), irrespective of
   whether or not such code values were appropriate.

6. The T11-FC-NAME-SERVER-MIB Module

T11-FC-NAME-SERVER-MIB DEFINITIONS ::= BEGIN

-- The MIB for management of the Fibre Channel functionality which
-- implements the Name Server function.

IMPORTS
    MODULE-IDENTITY,OBJECT-TYPE,
    NOTIFICATION-TYPE, Unsigned32,
    Counter32, Integer32, mib-2   FROM SNMPv2-SMI   -- [RFC2578]
    MODULE-COMPLIANCE, OBJECT-GROUP,
    NOTIFICATION-GROUP   FROM SNMPv2-CONF   -- [RFC2580]
    SnmpAdminString   FROM SNMP-FRAMEWORK-MIB -- [RFC3411]
    TruthValue, TEXTUAL-CONVENTION,
    TimeStamp   FROM SNMPv2-TC   -- [RFC2579]
    fcmInstanceIndex, FcPortType,
    FcAddressIdOrZero, FcClasses,
    FcNameIdOrZero   FROM FC-MGMT-MIB   -- [FC-MGMT]
    T11FabricIndex   FROM T11-TC-MIB   -- [FC-FAM-MIB]
    t11FamLocalSwitchWwn
                    FROM T11-FC-FABRIC-ADDR-MGR-MIB; -- [FC-FAM-MIB]

t11FcNameServerMIB MODULE-IDENTITY
    LAST-UPDATED "200603020000Z"
    ORGANIZATION "T11"
    CONTACT-INFO
            "   Claudio DeSanti
                    Cisco Systems, Inc.
                    170 West Tasman Drive
                    San Jose, CA 95134 USA
                    Phone: +1 408 853-9172
                    EMail: cds@cisco.com

                    Keith McCloghrie
                    Cisco Systems, Inc.
                    170 West Tasman Drive
                    San Jose, CA USA 95134
                    Phone: +1 408-526-5260
                    EMail: kzm@cisco.com"
    DESCRIPTION
            "The MIB module for the management of the functionality,
            which realizes the FC-GS-4 requirements for Name
            Server (NS).

            Copyright (C) The Internet Society (2006). This version of
            this MIB module is part of RFC 4438; see the RFC itself for
            full legal notices."

```
      REVISION     "200603020000Z"
      DESCRIPTION
            "Initial version of this MIB module, published as RFC 4438."
      ::= { mib-2 135 }

t11NsNotifications      OBJECT IDENTIFIER ::= { t11FcNameServerMIB 0 }
t11NsMIBObjects         OBJECT IDENTIFIER ::= { t11FcNameServerMIB 1 }
t11NsMIBConformance     OBJECT IDENTIFIER ::= { t11FcNameServerMIB 2 }
t11NsStatus             OBJECT IDENTIFIER ::= { t11NsMIBObjects 1 }
t11NsStatistics         OBJECT IDENTIFIER ::= { t11NsMIBObjects 2 }

-- Textual Conventions

T11NsGs4RejectReasonCode ::= TEXTUAL-CONVENTION
    STATUS     current
    DESCRIPTION
        "The FC-GS-4 reject reason code for a request.

          none(1)
              - no error.
          invalidCmdCode(2)
              - request contained an invalid command code.
          invalidVerLevel(3)
              - request contained an invalid version number.
          logicalError(4)
              - there was a logical error.
          invalidIUSize(5)
              - the CT_IU (Information Unit) size was invalid.
          logicalBusy(6)
              - the module is busy.
          protocolError(7)
              - there was a protocol error.
          unableToPerformCmdReq(8)
              - the command specified in the req could not be
                executed.  The details of exactly what failed
                will be in the corresponding reason code
                explanation.
          cmdNotSupported(9)
              - the command is not supported.
          serverNotAvailable(10)
              - the identified server was not available.
          couldNotEstabSession(11)
              - a server session could not be established.
          vendorError(12)
              - a vendor-specific error."
    REFERENCE
          "ANSI INCITS 387-2004, Fibre Channel - Generic
           Services-4 (FC-GS-4), section 4.4.3."
```

```
      SYNTAX  INTEGER {
              none(1),
              invalidCmdCode(2),
              invalidVerLevel(3),
              logicalError(4),
              invalidIUSize(5),
              logicalBusy(6),
              protocolError(7),
              unableToPerformCmdReq(8),
              cmdNotSupported(9),
              serverNotAvailable(10),
              couldNotEstabSession(11),
              vendorError(12)
             }

T11NsRejReasonCodeExpl ::= TEXTUAL-CONVENTION
    STATUS     current
    DESCRIPTION
        "The reject reason code explanation:

         noAdditionalExplanation(1)
            - no additional explanation.
         portIdentifierNotRegistered(2)
            - Port Identifier not registered.
         portNameNotRegistered(3)
            - Port Name not registered.
         nodeNameNotRegistered(4)
            - Node Name not registered.
         classOfServiceNotRegistered(5)
            - Class of Service not registered.
         nodeIpAddressNotRegistered(6)
            - 'IP Address (Node)' value not registered.
         ipaNotRegistered(7)
            - Initial Process Associator (IPA) not registered.
         fc4TypeNotRegistered(8)
            - FC-4 TYPEs not registered.
         symbolicPortNameNotRegistered(9)
            - Symbolic Port Name not registered.
         symbolicNodeNameNotRegistered(10)
            - Symbolic Node Name not registered.
         portTypeNotRegistered(11)
            - 'Port Type' not registered.
         portIpAddressNotRegistered(12)
            - 'IP Address (Port)' value not registered.
         fabricPortNameNotRegistered(13)
            - Fabric Port Name not registered.
         hardAddressNotRegistered(14)
            - 'Hard Address' not registered.
```

```
        fc4DescriptorNotRegistered(15)
            - FC-4 Descriptor not registered.
        fc4FeaturesNotRegistered(16)
            - FC-4 Features not registered.
        accessDenied(17)
            - Access denied.
        unacceptablePortIdentifier(18)
            - Unacceptable Port Identifier.
        databaseEmpty(19)
            - Database is empty.
        noObjectRegInSpecifiedScope(20)
            - no object has been registered in the specified
              scope.
        domainIdNotPresent(21)
            - Domain ID not present.
        portIdNotPresent(22)
            - Port number not present.
        noDeviceAttached(23)
            - No device attached.
        authorizationException(24)
            - Authorization Exception.
        authenticationException(25)
            - Authentication Exception.
        databaseFull(26)
            - Database full."
    REFERENCE
         "ANSI INCITS 387-2004, Fibre Channel - Generic
          Services-4 (FC-GS-4), sections 4.4.4 and 5.2.4"
    SYNTAX  INTEGER {
            noAdditionalExplanation(1),
            portIdentifierNotRegistered(2),
            portNameNotRegistered(3),
            nodeNameNotRegistered(4),
            classOfServiceNotRegistered(5),
            nodeIpAddressNotRegistered(6),
            ipaNotRegistered(7),
            fc4TypeNotRegistered(8),
            symbolicPortNameNotRegistered(9),
            symbolicNodeNameNotRegistered(10),
            portTypeNotRegistered(11),
            portIpAddressNotRegistered(12),
            fabricPortNameNotRegistered(13),
            hardAddressNotRegistered(14),
            fc4DescriptorNotRegistered(15),
            fc4FeaturesNotRegistered(16),
            accessDenied(17),
            unacceptablePortIdentifier(18),
            databaseEmpty(19),
```

```
            noObjectRegInSpecifiedScope(20),
            domainIdNotPresent(21),
            portIdNotPresent(22),
            noDeviceAttached(23),
            authorizationException(24),
            authenticationException(25),
            databaseFull(26)
          }

--
-- Information about a Name Server Information Subset
--

t11NsInfoSubsetTable OBJECT-TYPE
    SYNTAX         SEQUENCE OF T11NsInfoSubsetEntry
    MAX-ACCESS     not-accessible
    STATUS         current
    DESCRIPTION
          "This table contains one entry for each Name Server
          Information Subset within each Fibre Channel
          management instance."
    ::= { t11NsStatus 1 }

t11NsInfoSubsetEntry OBJECT-TYPE
    SYNTAX         T11NsInfoSubsetEntry
    MAX-ACCESS     not-accessible
    STATUS         current
    DESCRIPTION
          "This entry contains information about operations
          on a particular Name Server Information Subset
          within the Fibre Channel management instance
          identified by fcmInstanceIndex."
    INDEX { fcmInstanceIndex, t11NsInfoSubsetIndex }
    ::= { t11NsInfoSubsetTable 1 }

T11NsInfoSubsetEntry ::= SEQUENCE {
    t11NsInfoSubsetIndex               Unsigned32,
    t11NsInfoSubsetSwitchIndex         Unsigned32,
    t11NsInfoSubsetTableLastChange     TimeStamp,
    t11NsInfoSubsetNumRows             Integer32,
    t11NsInfoSubsetTotalRejects        Counter32,
    t11NsInfoSubsetRejReqNotfyEnable   TruthValue
}

t11NsInfoSubsetIndex OBJECT-TYPE
    SYNTAX         Unsigned32 (1..4294967295)
    MAX-ACCESS     not-accessible
    STATUS         current
```

      DESCRIPTION
            "An arbitrary integer value that uniquely identifies
            this Name Server Information Subset amongst all others
            within the same Fibre Channel management instance.

            It is mandatory to keep this value constant between
            restarts of the agent and to make every possible
            effort to keep it constant across such restarts."
      ::= { t11NsInfoSubsetEntry 1 }

t11NsInfoSubsetSwitchIndex OBJECT-TYPE
      SYNTAX   Unsigned32 (0..4294967295)
      MAX-ACCESS   read-only
      STATUS   current
      DESCRIPTION
            "The value of this object is zero when operations
            upon this Name Server Information Subset do not occur
            at a local Fibre Channel switch; otherwise, it is
            non-zero and identifies the local switch.

            The switch identified by a non-zero value of this
            object is the same switch as is identified by the
            same value of fcmSwitchIndex."
      REFERENCE
            "fcmSwitchIndex is defined in the FC-MGMT-MIB module"
      ::= { t11NsInfoSubsetEntry 2 }

t11NsInfoSubsetTableLastChange OBJECT-TYPE
      SYNTAX   TimeStamp
      MAX-ACCESS   read-only
      STATUS   current
      DESCRIPTION
            "The value of sysUpTime at the time of the last update
            to any entry in the t11NsRegTable with the same values
            of fcmInstanceIndex and t11NsInfoSubsetIndex. This
            includes creation of an entry, deletion of an entry, or
            modification of an existing entry. If no such update
            has taken place since the last re-initialization of the
            local network management subsystem, then this object
            contains a zero value."
      ::= { t11NsInfoSubsetEntry 3 }

t11NsInfoSubsetNumRows OBJECT-TYPE
      SYNTAX   Integer32 (0..2147483647)
      MAX-ACCESS   read-only
      STATUS   current
      DESCRIPTION
            "The number of Nx_Ports currently registered in this

            Name Server Information Subset, i.e., the number of
            rows in the t11NsRegTable with the same values of
            fcmInstanceIndex and t11NsInfoSubsetIndex."
    ::= { t11NsInfoSubsetEntry 4 }

t11NsInfoSubsetTotalRejects OBJECT-TYPE
    SYNTAX   Counter32
    MAX-ACCESS   read-only
    STATUS   current
    DESCRIPTION
            "The total number of (CT_IU) Requests for Name Server
            functions that were rejected for inclusion in this
            Name Server Information Subset, across all Fabrics
            for which it contains information.

            This counter has no discontinuities other than those
            that all Counter32s have when sysUpTime=0."
    ::= { t11NsInfoSubsetEntry 5 }

t11NsInfoSubsetRejReqNotfyEnable OBJECT-TYPE
    SYNTAX   TruthValue
    MAX-ACCESS   read-write
    STATUS   current
    DESCRIPTION
            "This object indicates whether 't11NsRejectRegNotify'
            notifications are generated by rejections of requests
            to register information in this Name Server Information
            Subset.

            If value of this object is 'true', then the
            notification is generated when a request is rejected.
            If it is 'false', the notification is not generated.

            The persistence of values of this object across an
            agent reboot is implementation-dependent."
    DEFVAL { false }
    ::= { t11NsInfoSubsetEntry 6 }

--
-- Registered Port Information
--

t11NsRegTable OBJECT-TYPE
    SYNTAX   SEQUENCE OF T11NsRegEntry
    MAX-ACCESS   not-accessible
    STATUS   current
    DESCRIPTION
            "This table contains entries for all Nx_Ports registered

          in the identified Name Server Information Subsets across
          all Fabrics for which such subsets contain information."
    ::= { t11NsStatus 2 }

t11NsRegEntry OBJECT-TYPE
    SYNTAX T11NsRegEntry
    MAX-ACCESS   not-accessible
    STATUS   current
    DESCRIPTION
          "An entry containing information about an Nx_Port
          represented by t11NsRegPortIdentifier that is registered
          with a Name Server Information Subset (identified by
          t11NsInfoSubsetIndex) within the Fibre Channel management
          instance (identified by fcmInstanceIndex) on the Fabric
          (identified by t11NsRegFabricIndex)."
    INDEX { fcmInstanceIndex, t11NsInfoSubsetIndex,
           t11NsRegFabricIndex, t11NsRegPortIdentifier }
    ::= { t11NsRegTable 1 }

T11NsRegEntry ::= SEQUENCE {
    t11NsRegFabricIndex   T11FabricIndex,
    t11NsRegPortIdentifier   FcAddressIdOrZero,
    t11NsRegPortName   FcNameIdOrZero,
    t11NsRegNodeName   FcNameIdOrZero,
    t11NsRegClassOfSvc   FcClasses,
    t11NsRegNodeIpAddress   OCTET STRING,
    t11NsRegProcAssoc   OCTET STRING,
    t11NsRegFc4Type   OCTET STRING,
    t11NsRegPortType   FcPortType,
    t11NsRegPortIpAddress   OCTET STRING,
    t11NsRegFabricPortName   FcNameIdOrZero,
    t11NsRegHardAddress   FcAddressIdOrZero,
    t11NsRegSymbolicPortName   SnmpAdminString,
    t11NsRegSymbolicNodeName   SnmpAdminString,
    t11NsRegFc4Features   OCTET STRING
    }

t11NsRegFabricIndex OBJECT-TYPE
    SYNTAX   T11FabricIndex
    MAX-ACCESS   not-accessible
    STATUS   current
    DESCRIPTION
          "A unique index value that uniquely identifies a
          particular Fabric.

          In a Fabric conformant to SW-3, only a single Fabric can
          operate within a single physical infrastructure, and thus,
          the value of this Fabric Index will always be 1.

           However, it is possible that future standards will define
           how multiple Fabrics, each with its own management
           instrumentation, could operate within one (or more) physical
           infrastructures. To allow for this future possibility, this
           index value is used to uniquely identify a particular
           Fabric within a physical infrastructure."
      ::= { t11NsRegEntry 1 }

t11NsRegPortIdentifier OBJECT-TYPE
      SYNTAX   FcAddressIdOrZero
      MAX-ACCESS   not-accessible
      STATUS   current
      DESCRIPTION
             "The Fibre Channel Address Identifier of this Nx_Port.
             If no Port Identifier has been registered, then the
             value of this object is the zero-length string."
      ::= { t11NsRegEntry 2 }

t11NsRegPortName OBJECT-TYPE
      SYNTAX   FcNameIdOrZero
      MAX-ACCESS   read-only
      STATUS   current
      DESCRIPTION
             "The Port_Name (WWN) of this Nx_Port.
             If this object has not been registered, then its value
             is the zero-length string."
      DEFVAL {''H}
      ::= { t11NsRegEntry 3 }

t11NsRegNodeName OBJECT-TYPE
      SYNTAX   FcNameIdOrZero
      MAX-ACCESS   read-only
      STATUS   current
      DESCRIPTION
             "The Node_Name (WWN) of this Nx_Port.
             If this object has not been registered, then its value
             is the zero-length string."
      DEFVAL {''H}
      ::= { t11NsRegEntry 4 }

t11NsRegClassOfSvc OBJECT-TYPE
      SYNTAX   FcClasses
      MAX-ACCESS   read-only
      STATUS   current
      DESCRIPTION
             "The class of service indicator. This object is an
             array of bits that contain a bit map of the classes of
             service supported by the associated port. If a bit in

            this object is 1, it indicates that the class of
            service is supported by the associated port. When a
            bit is set to 0, it indicates that no class of service
            is supported by this Nx_Port.

            If this object has not been not registered for a port,
            then the instance for that port is not instantiated."
       ::= { t11NsRegEntry 5 }

t11NsRegNodeIpAddress OBJECT-TYPE
    SYNTAX   OCTET STRING (SIZE (0 | 16))
    MAX-ACCESS   read-only
    STATUS   current
    DESCRIPTION
            "The IP address of the node of this Nx_Port, in
            network-byte order, either as a 32-bit IPv4 address or
            a 128-bit IPv6 address. For the former, the leftmost 96 bits
            (12 bytes) should contain x'00 00 00 00 00 00 00 00 00 00 FF
            FF', and the IPv4 address should be present in the rightmost
            32 bits.

            Note that the value of this object is the IP address value
            that is received in the FC-GS-4 message Register IP address
            (Node) RIP_NN. It is not validated against any IP address
            format.

            If no 'IP address (Node)' has been registered, then the
            value of this object is the zero-length string."
    REFERENCE
            "ANSI INCITS 387-2004, Fibre Channel - Generic
            Services-4 (FC-GS-4)"
    DEFVAL { ''H }
    ::= { t11NsRegEntry 6 }

t11NsRegProcAssoc OBJECT-TYPE
    SYNTAX   OCTET STRING (SIZE (0 | 8))
    MAX-ACCESS   read-only
    STATUS   current
    DESCRIPTION
            "The Fibre Channel Initial Process Associator (IPA).

            If no 'Initial Process Associator' has been registered,
            then the value of this object is the zero-length string."
    REFERENCE
            "ANSI INCITS 387-2004, Fibre Channel - Generic
            Services-4 (FC-GS-4)"
    DEFVAL { ''H }
    ::= { t11NsRegEntry 7 }

```
t11NsRegFc4Type OBJECT-TYPE
    SYNTAX        OCTET STRING (SIZE (0 | 32))
    MAX-ACCESS    read-only
    STATUS        current
    DESCRIPTION
            "The FC-4 protocol types supported by this Nx_Port.
            This is an array of 256 bits.  Each bit in the array
            corresponds to a Type value as defined by Fibre Channel
            standards and contained in the Type field of the frame
            header.  The order of the bits in the 256-bit (32-byte)
            value is the same as defined in FC-GS-4, section 5.2.3.8,
            and represented in network-byte order.

            If no 'FC-4 TYPEs' has been registered, then the
            value of this object is the zero-length string."
    REFERENCE
            "ANSI INCITS 387-2004, Fibre Channel - Generic
            Services-4 (FC-GS-4), section 5.2.3.8."
    DEFVAL  { ''H }
    ::= { t11NsRegEntry 8 }

t11NsRegPortType OBJECT-TYPE
    SYNTAX        FcPortType
    MAX-ACCESS    read-only
    STATUS        current
    DESCRIPTION
            "The port type of this port.

            If no 'Port Type' has been registered, then the value
            of this object is unidentified and is represented by
            the value 'unknown'."
    DEFVAL  { 1 }                 -- 'unknown', see [FC-MGMT]
    ::= { t11NsRegEntry 9 }

t11NsRegPortIpAddress OBJECT-TYPE
    SYNTAX        OCTET STRING (SIZE (0 | 16))
    MAX-ACCESS    read-only
    STATUS        current
    DESCRIPTION
            "The value that Fibre Channel calls an 'IP Address (Port)'
            that represents the IP address of the associated port.
            The value is either in 32-bit IPv4 format or 128-bit IPv6
            format, in network-byte order.  When this object contains an
            IPv4 address, the leftmost 96 bits (12 bytes) should contain
            x'00 00 00 00 00 00 00 00 00 00 FF FF'.  The IPv4 address
            should be present in the rightmost 32 bits.

            Note that the value of this object is the IP address value
```

                   that is received in the FC-GS-4 message Register IP address
                   (Port) RIPP_ID. It is not validated against any IP address
                   format.

                   If no 'IP address (Port)' has been registered, then the
                   value of this object is the zero-length string."
           REFERENCE
                   "ANSI INCITS 387-2004, Fibre Channel - Generic
                   Services-4, (FC-GS-4)"
           DEFVAL {''H}
           ::= { t11NsRegEntry 10 }

    t11NsRegFabricPortName OBJECT-TYPE
           SYNTAX   FcNameIdOrZero
           MAX-ACCESS   read-only
           STATUS   current
           DESCRIPTION
                   "The Fabric Port Name (WWN) of the Fx_Port to which
                   this Nx_Port is attached.

                   If no 'Fabric Port Name' has been registered, then the
                   value of this object is the zero-length string."
           DEFVAL {''H}
           ::= { t11NsRegEntry 11 }

    t11NsRegHardAddress OBJECT-TYPE
           SYNTAX   FcAddressIdOrZero
           MAX-ACCESS   read-only
           STATUS   current
           DESCRIPTION
                   "The format of this object is identical to the format
                   of Hard Address defined in the Discover Address (ADISC)
                   Extended Link Service (FC-FS).

                   Hard Address is the 24-bit NL_Port identifier that
                   consists of:
                     - the 8-bit Domain_ID in the most significant byte
                     - the 8-bit Area_ID in the next most significant
                       byte
                     - the 8-bit AL-PA (Arbitrated Loop Physical Address)
                       which an NL_Port attempts acquire during FC-AL
                       initialization in the least significant byte.

                   If the port is not an NL_Port, or if it is an NL_Port
                   but does not have a hard address, then all bits are
                   reported as zeros.

                   If no 'Hard Address' has been registered, then the

DeSanti, et al.   Standards Track   [Page 19]

```
        value of this object is the zero-length string."
    DEFVAL {''H}
    ::= { t11NsRegEntry 12 }


t11NsRegSymbolicPortName OBJECT-TYPE
    SYNTAX         SnmpAdminString (SIZE (0..255))
    MAX-ACCESS     read-only
    STATUS         current
    DESCRIPTION
            "The user-defined name of this port.

            If no 'Symbolic Port Name' has been registered, then
            the value of this object is the zero-length string."
    DEFVAL {''H}
    ::= { t11NsRegEntry 13 }


t11NsRegSymbolicNodeName OBJECT-TYPE
    SYNTAX         SnmpAdminString (SIZE (0..255))
    MAX-ACCESS     read-only
    STATUS         current
    DESCRIPTION
            "The user-defined name of the node of this port.

            If no 'Symbolic Node Name' has been registered, then
            the value of this object is the zero-length string."
    DEFVAL {''H}
    ::= { t11NsRegEntry 14 }



t11NsRegFc4Features OBJECT-TYPE
    SYNTAX         OCTET STRING (SIZE (0 | 128))
    MAX-ACCESS     read-only
    STATUS         current
    DESCRIPTION
            "The FC-4 Features associated with FC-4 Types on this
            port encoded as a 128-byte value in network-byte order,
            or the zero-length string if no 'FC-4 Features' have been
            registered.

            Section 5.2.3.15 of FC-GS-4 is the authoritative
            definition of the format of the 128-byte value,
            i.e., if different, FC-GS-4 takes precedence over the
            following description:

            The 128-byte value is an array of 4-bit values, one for
            each FC-4 Type value, positioned as follows: the 5 most
            significant bits of a Type value identify where it appears
            within the 128-byte value, specifically, within which word:
```

                    - Word 0 (of the 128-byte value) contains information
                      related to Types '00' through '07';
                    - Word 1 contains information related to Types
                      '08' through 0F';
                    - and so forth, up to Word 31, which contains
                      information related to Types 'F8' through 'FF'.

            The least significant of the eight 4-bit values in each
            Word represents an FC-4 Type with 000 as its 3 least
            significant bits, and most significant 4-bit value in
            each Word represents an FC-4 Type with 111 as its 3 least
            significant bits."
    REFERENCE
            "ANSI INCITS 387-2004, Fibre Channel - Generic
            Services-4 (FC-GS-4), section 5.2.3.15."
    DEFVAL {''H}
    ::= { t11NsRegEntry 15 }

--
-- Registered FC-4 Descriptors
--

t11NsRegFc4DescriptorTable OBJECT-TYPE
    SYNTAX   SEQUENCE OF T11NsRegFc4DescriptorEntry
    MAX-ACCESS   not-accessible
    STATUS   current
    DESCRIPTION
            "This table contains entries for all FC-4 Descriptors
            registered in the identified Name Server Information
            Subsets across all Fabrics for which such subsets
            contain information."
    ::= { t11NsStatus 3 }

t11NsRegFc4DescriptorEntry OBJECT-TYPE
    SYNTAX   T11NsRegFc4DescriptorEntry
    MAX-ACCESS   not-accessible
    STATUS   current
    DESCRIPTION
            "An entry in the t11NsRegFc4DescriptorTable,
            containing information about an FC-4 Descriptor
            that is associated with a particular FC-4 Type
            value. The particular FC-4 Descriptor was
            registered by an Nx_Port (identified by
            t11NsRegPortIdentifier) in a Name Server Information
            Subset (identified by t11NsInfoSubsetIndex) within
            the Fibre Channel management instance (identified by
            fcmInstanceIndex) on the Fabric (identified by

```
            t11NsRegFabricIndex).

            If no FC-4 Descriptors have been registered
            for a particular port, then there will be no
            entries in this table for that port."
     INDEX { fcmInstanceIndex, t11NsInfoSubsetIndex,
             t11NsRegFabricIndex, t11NsRegPortIdentifier,
             t11NsRegFc4TypeValue }
     ::= { t11NsRegFc4DescriptorTable 1 }

T11NsRegFc4DescriptorEntry ::= SEQUENCE {
    t11NsRegFc4TypeValue          Unsigned32,
    t11NsRegFc4Descriptor         OCTET STRING
}

t11NsRegFc4TypeValue OBJECT-TYPE
    SYNTAX          Unsigned32 (0..255)
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
            "An integer value that identifies an FC-4 Type value
            (representing a particular protocol type, as specified
            in FC-FS) for which an FC-4 Descriptor has been
            registered.

            An instance of this object contains a 'Type value'
            that corresponds to a '1' bit in the value of the
            t11NsRegFc4Type registered for the same port;
            this correspondence is as specified in FC-GS-4."
    REFERENCE
            "ANSI INCITS 387-2004, Fibre Channel - Generic
                Services-4 (FC-GS-4), section 5.2.3.8, and
            ANSI INCITS 373-2003, Fibre Channel - Framing and
                Signaling (FC-FS), section 9.6, Table 29."
    ::= { t11NsRegFc4DescriptorEntry 1 }

t11NsRegFc4Descriptor OBJECT-TYPE
    SYNTAX          OCTET STRING (SIZE (0..255))
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
            "The FC-4 Descriptor value that has been registered
            for the particular port on the particular Fabric, and
            for the FC-4 Type represented by the corresponding
            value of t11NsRegFc4TypeIndex.

            The format of an FC-4 Descriptor is dependent on the
            corresponding FC-4 Type value, but is represented in
```

```
              network-byte order."
      REFERENCE
              "ANSI INCITS 387-2004, Fibre Channel - Generic
              Services-4 (FC-GS-4), section 5.2.5.42"
      ::= { t11NsRegFc4DescriptorEntry 2 }


--
-- Name Server per-Fabric Statistics
--

t11NsStatsTable OBJECT-TYPE
      SYNTAX        SEQUENCE OF T11NsStatsEntry
      MAX-ACCESS    not-accessible
      STATUS        current
      DESCRIPTION
              "This table contains per-Fabric state and statistics
              for operations upon the identified Name Server
              Information Subsets."
      ::= { t11NsStatistics 1 }

t11NsStatsEntry OBJECT-TYPE
      SYNTAX        T11NsStatsEntry
      MAX-ACCESS    not-accessible
      STATUS        current
      DESCRIPTION
              "An entry in this table contains state and statistics
              for operations upon a Name Server Information Subset
              (identified by t11NsInfoSubsetIndex) within the Fibre
              Channel management instance (identified by
              fcmInstanceIndex) on the Fabric (identified by
              t11NsRegFabricIndex)."
      INDEX { fcmInstanceIndex, t11NsInfoSubsetIndex,
              t11NsRegFabricIndex }
      ::= { t11NsStatsTable 1 }

T11NsStatsEntry ::=  SEQUENCE {
      t11NsInGetReqs               Counter32,
      t11NsOutGetReqs              Counter32,
      t11NsInRegReqs               Counter32,
      t11NsInDeRegReqs             Counter32,
      t11NsInRscns                 Counter32,
      t11NsOutRscns                Counter32,
      t11NsRejects                 Counter32,
      t11NsDatabaseFull            TruthValue
 }

t11NsInGetReqs OBJECT-TYPE
```

```
    SYNTAX         Counter32
    MAX-ACCESS     read-only
    STATUS         current
    DESCRIPTION
            "The total number of (CT_IU) Get Requests
            received requesting information from this Name
            Server Information Subset on this Fabric.

            This counter has no discontinuities other than those
            that all Counter32s have when sysUpTime=0."
    ::= { t11NsStatsEntry 1 }

t11NsOutGetReqs OBJECT-TYPE
    SYNTAX         Counter32
    MAX-ACCESS     read-only
    STATUS         current
    DESCRIPTION
            "The total number of (CT_IU) Get Requests sent in
            order to obtain information needed in this Name Server
            Information Subset on this Fabric.

            This counter has no discontinuities other than those
            that all Counter32s have when sysUpTime=0."
    ::= { t11NsStatsEntry 2 }

t11NsInRegReqs OBJECT-TYPE
    SYNTAX         Counter32
    MAX-ACCESS     read-only
    STATUS         current
    DESCRIPTION
            "The total number of (CT_IU) Registration Requests
            received to register information in the Name Server
            Information Subset on this Fabric.

            This counter has no discontinuities other than those
            that all Counter32s have when sysUpTime=0."
    ::= { t11NsStatsEntry 3 }

t11NsInDeRegReqs OBJECT-TYPE
    SYNTAX         Counter32
    MAX-ACCESS     read-only
    STATUS         current
    DESCRIPTION
            "The total number of (CT_IU) De-registration Requests
            received to de-register information from this Name Server
            Information Subset on this Fabric.

            This counter has no discontinuities other than those
```

           that all Counter32s have when sysUpTime=0."
    ::= { t11NsStatsEntry 4 }

t11NsInRscns OBJECT-TYPE
    SYNTAX   Counter32
    MAX-ACCESS   read-only
    STATUS   current
    DESCRIPTION
           "The total number of received RSCNs, indicating
           Name Server-related changes relating to this Name
           Server Information Subset on this Fabric.

           This counter has no discontinuities other than those
           that all Counter32s have when sysUpTime=0."
    ::= { t11NsStatsEntry 5 }

t11NsOutRscns OBJECT-TYPE
    SYNTAX   Counter32
    MAX-ACCESS   read-only
    STATUS   current
    DESCRIPTION
           "The total number of transmitted RSCNs, indicating
           Name Server-related changes relating to this Name
           Server Information Subset on this Fabric.

           This counter has no discontinuities other than those
           that all Counter32s have when sysUpTime=0."
    ::= { t11NsStatsEntry 6 }

t11NsRejects OBJECT-TYPE
    SYNTAX   Counter32
    MAX-ACCESS   read-only
    STATUS   current
    DESCRIPTION
           "The total number of CT_IU Requests for Name
           Server functions on this Name Server Information
           Subset on this Fabric that were rejected.

           This counter has no discontinuities other than those
           that all Counter32s have when sysUpTime=0."
    ::= { t11NsStatsEntry 7 }

t11NsDatabaseFull OBJECT-TYPE
    SYNTAX   TruthValue
    MAX-ACCESS   read-only
    STATUS   current
    DESCRIPTION
           "An indication of whether the database containing this

                Name Server Information Subset is full. This object is
                set to 'true' only if the Name Server is unable to allocate
                space for a new entry for the corresponding Fabric, and it is
                set to 'false' whenever an existing entry is deleted for the
                corresponding Fabric."
        ::= { t11NsStatsEntry 8 }

--
-- Reject information objects
--

t11NsRejectTable OBJECT-TYPE
    SYNTAX   SEQUENCE OF T11NsRejectEntry
    MAX-ACCESS   not-accessible
    STATUS   current
    DESCRIPTION
            "This table contains information about the most recent
            Name Server Registration Request failures for various
            ports on various Fabrics.

            If no information is available about the most recent
            rejection of a Registration Request on a particular port
            on a particular Fabric, then there will no entry in this
            table for that port and Fabric.

            When a t11NsRejectRegNotify notification is sent for
            such a Registration Request failure, the values of the
            objects in the relevant entry of this table are updated
            immediately prior to generating the notification."
        ::= { t11NsStatus 4 }

t11NsRejectEntry OBJECT-TYPE
    SYNTAX T11NsRejectEntry
    MAX-ACCESS   not-accessible
    STATUS   current
    DESCRIPTION
            "An entry containing information about the most recent
            rejection of a request to register information in the Name
            Server Information Subset (identified by
            t11NsInfoSubsetIndex) within the Fibre Channel management
            instance (identified by fcmInstanceIndex) for a particular
            port (identified by t11NsRegPortIdentifier) on a particular
            Fabric (identified by t11NsRegFabricIndex)."
    INDEX { fcmInstanceIndex, t11NsInfoSubsetIndex,
            t11NsRegFabricIndex, t11NsRegPortIdentifier }
        ::= { t11NsRejectTable 1 }

T11NsRejectEntry ::= SEQUENCE {

```
    t11NsRejectCtCommandString   OCTET STRING,
    t11NsRejectReasonCode        T11NsGs4RejectReasonCode,
    t11NsRejReasonCodeExp        T11NsRejReasonCodeExpl,
    t11NsRejReasonVendorCode     OCTET STRING
}

t11NsRejectCtCommandString OBJECT-TYPE
    SYNTAX        OCTET STRING (SIZE (0..255))
    MAX-ACCESS    read-only
    STATUS        current
    DESCRIPTION
            "The binary content of the Registration Request,
            formatted as an octet string (in network byte
            order) containing the CT_IU, as described in
            Table 2 of [FC-GS-4] (including the preamble),
            which was most recently rejected for the particular
            Name Server Information Subset on the particular port
            on the particular Fabric.

            This object contains the zero-length string
            if and when the CT-IU's content is unavailable.

            When the length of this object is 255 octets, it
            contains the first 255 octets of the CT-IU (in
            network-byte order)."
    ::= { t11NsRejectEntry 1 }

t11NsRejectReasonCode OBJECT-TYPE
    SYNTAX        T11NsGs4RejectReasonCode
    MAX-ACCESS    read-only
    STATUS        current
    DESCRIPTION
            "A registration reject reason code.  This object
            contains the reason code of the most recent Name
            Server Registration Request failure for the
            particular port on the particular Fabric."
    ::= { t11NsRejectEntry 2 }

t11NsRejReasonCodeExp OBJECT-TYPE
    SYNTAX        T11NsRejReasonCodeExpl
    MAX-ACCESS    read-only
    STATUS        current
    DESCRIPTION
            "A registration reject reason code explanation.  This
            object contains the reason code explanation of the most
            recent Name Server Registration Request failure for the
            particular port on the particular Fabric."
    ::= { t11NsRejectEntry 3 }
```

```
t11NsRejReasonVendorCode OBJECT-TYPE
    SYNTAX        OCTET STRING (SIZE(1))
    MAX-ACCESS    read-only
    STATUS        current
    DESCRIPTION
            "A registration reject vendor-specific code.  This
            object contains the vendor-specific code of the most
            recent Name Server Registration Request failure for the
            particular port on the particular Fabric."
    ::= { t11NsRejectEntry 4 }


--
-- Notifications
--

t11NsRejectRegNotify NOTIFICATION-TYPE
    OBJECTS   { t11FamLocalSwitchWwn,
                t11NsRegPortName, t11NsRejectCtCommandString,
                t11NsRejectReasonCode, t11NsRejReasonCodeExp,
                t11NsRejReasonVendorCode }
    STATUS    current
    DESCRIPTION
            "This notification is generated whenever a request to
            register information in a Name Server Information
            Subset (for which the corresponding instance of
            t11NsInfoSubsetRejReqNotfyEnable is 'true') is
            rejected on a particular Fabric for a particular Nx_Port.

            The value of t11FamLocalSwitchWwn indicates the
            WWN of the switch that received the request.
            (If the WWN is unavailable, the value is set to
            the zero-length string.)

            The value of t11NsRejectCtCommandString indicates
            the rejected request, and the values of
            t11NsRejectReasonCode, t11NsRejReasonCodeExp, and
            t11NsRejReasonVendorCode indicate the reason for
            the rejection.

            The value of t11NsRegPortName represents the Port Name
            if it is able to be extracted out of the Registration
            Request, or otherwise the value as currently registered
            on the port."
    ::= { t11NsNotifications 1 }

--
-- Conformance
```

--

t11NsMIBCompliances OBJECT IDENTIFIER ::= {t11NsMIBConformance 1}
t11NsMIBGroups   OBJECT IDENTIFIER ::= {t11NsMIBConformance 2}

t11NsMIBCompliance MODULE-COMPLIANCE
    STATUS   current
    DESCRIPTION
            "The compliance statement for entities that
            implement the Fibre Channel Name Server."
    MODULE MANDATORY-GROUPS {t11NsDBGroup,
                            t11NsNotifyControlGroup,
                            t11NsNotifyGroup}

      OBJECT t11NsInfoSubsetRejReqNotfyEnable
      MIN-ACCESS read-only
      DESCRIPTION
            "Write access is not required."

      GROUP t11NsRequestStatsGroup
      DESCRIPTION
            "This group is mandatory only for an implementation
            that captures statistics related to Name Server
            requests."

      GROUP t11NsRscnStatsGroup
      DESCRIPTION
            "This group is mandatory only for an implementation
            that captures statistics related to Name
            Server-related RSCNs."

      GROUP t11NsRejectStatsGroup
      DESCRIPTION
            "This group is mandatory only for an implementation
            that captures statistics related to Name Server
            rejects."

    ::= { t11NsMIBCompliances 1 }

-- Units of conformance

t11NsDBGroup   OBJECT-GROUP
    OBJECTS { t11NsInfoSubsetSwitchIndex,
             t11NsInfoSubsetTableLastChange,
             t11NsInfoSubsetNumRows,
             t11NsRegPortName,
             t11NsRegNodeName,
             t11NsRegClassOfSvc,

```
                t11NsRegNodeIpAddress,
                t11NsRegProcAssoc,
                t11NsRegFc4Type,
                t11NsRegPortType,
                t11NsRegPortIpAddress,
                t11NsRegFabricPortName,
                t11NsRegHardAddress,
                t11NsRegSymbolicPortName,
                t11NsRegSymbolicNodeName,
                t11NsRegFc4Features,
                t11NsRegFc4Descriptor }
    STATUS current
    DESCRIPTION
            "A collection of objects for monitoring the information
            registered in a Name Server Information Subset."
    ::= { t11NsMIBGroups 1 }

t11NsRequestStatsGroup OBJECT-GROUP
    OBJECTS { t11NsInGetReqs,
                t11NsOutGetReqs,
                t11NsInRegReqs,
                t11NsInDeRegReqs,
                t11NsDatabaseFull}
    STATUS current
    DESCRIPTION
            "A collection of objects for displaying Name
            Server statistics and state for Name Server requests."
    ::= { t11NsMIBGroups 2 }

t11NsRscnStatsGroup OBJECT-GROUP
    OBJECTS { t11NsInRscns,
                t11NsOutRscns }
    STATUS current
    DESCRIPTION
            "A collection of objects for displaying Name
            Server statistics for Name Server-related RSCNs."
    ::= { t11NsMIBGroups 3 }

t11NsRejectStatsGroup OBJECT-GROUP
    OBJECTS { t11NsInfoSubsetTotalRejects,
                t11NsRejects }
    STATUS current
    DESCRIPTION
            "A collection of objects for displaying Name
            Server statistics for rejects."
    ::= { t11NsMIBGroups 4 }

t11NsNotifyControlGroup  OBJECT-GROUP
```

       OBJECTS { t11NsRejectCtCommandString,
                 t11NsRejectReasonCode,
                 t11NsRejReasonCodeExp,
                 t11NsRejReasonVendorCode,
                 t11NsInfoSubsetRejReqNotfyEnable }
       STATUS current
       DESCRIPTION
             "A collection of notification control and
              notification information objects for monitoring
              rejections of Name Server registrations."
       ::= { t11NsMIBGroups 5 }

t11NsNotifyGroup   NOTIFICATION-GROUP
       NOTIFICATIONS {t11NsRejectRegNotify }
       STATUS current
       DESCRIPTION
             "A collection of notifications for monitoring
              rejections of Name Server registrations."
       ::= { t11NsMIBGroups 6 }

END

7. Acknowledgements

   This document began life as a work item of the INCITS Task Group
   T11.5. We wish to acknowledge the many contributions and comments
   from the INCITS Technical Committee T11, including the following:

      T11 Chair: Robert Snively, Brocade
      T11 Vice Chair: Claudio DeSanti, Cisco Systems
      T11.5 Chair: Roger Cummings, Symantec
      T11.5 members, especially:
          Ken Hirata, Emulex
          Scott Kipp, McData
          Michael O'Donnell, McData
          Elizabeth G. Rodriguez, Dot Hill
          Steven L. Wilson, Brocade
          Bob Nixon, Emulex

   Thanks also to Orly Nicklass of RAD Data Communications, Bert Wijnen
   of Lucent, and those members of the IMSS WG who provided review
   comments.

8. Normative References

   [RFC2578]   McCloghrie, K., Perkins, D., and J. Schoenwaelder,
                "Structure of Management Information Version 2 (SMIv2)",
                STD 58, RFC 2578, April 1999.

   [RFC2579]   McCloghrie, K., Perkins, D., and J. Schoenwaelder,
                "Textual Conventions for SMIv2", STD 58, RFC 2579, April
                1999.

   [RFC2580]   McCloghrie, K., Perkins, D., and J. Schoenwaelder,
                "Conformance Statements for SMIv2", STD 58, RFC 2580,
                April 1999.

   [RFC3411]   Harrington, D., Presuhn, R., and B. Wijnen, "An
                Architecture for Describing Simple Network Management
                Protocol (SNMP) Management Frameworks", STD 62, RFC
                3411, December 2002.

   [FC-FS]   "Fibre Channel - Framing and Signaling (FC-FS)" ANSI
                INCITS 373-2003, April 2003.

   [FC-GS-3]   "Fibre Channel - Generic Services - 3 (FC-GS-3)", ANSI
                INCITS 348-2000, November 2000.

   [FC-GS-4]   "Fibre Channel - Generic Services - 4 (FC-GS-4)", ANSI
                INCITS 387-2004, February 2004.

   [FC-SW-3]   "Fibre Channel - Switch Fabric - 3 (FC-SW-3)", ANSI
                INCITS 384-2004, June 2004.

   [FC-SW-4]   "Fibre Channel - Switch Fabric - 4 (FC-SW-4)", ANSI
                INCITS 418-2006, 2006.

   [FC-MGMT]   McCloghrie, K., "Fibre Channel Management MIB", RFC
                4044, May 2005.

   [FC-FAM-MIB] DeSanti, C., Gaonkar, V., McCloghrie, K., and S. Gai,
                "Fibre Channel Fabric Address Manager MIB", RFC 4439,
                April 2006.

9. Informative References

    [RFC2741]   Daniele, M., Wijnen, B., Ellison, M., and D. Francisco,
                  "Agent Extensibility (AgentX) Protocol Version 1", RFC
                  2741, January 2000.

    [RFC2837]   Teow, K., "Definitions of Managed Objects for the Fabric
                  Element in Fibre Channel Standard", RFC 2837, May 2000.

    [RFC3410]   Case, J., Mundy, R., Partain, D., and B. Stewart,
                  "Introduction and Applicability Statements for
                  Internet-Standard Management Framework", RFC 3410,
                  December 2002.

    [IF-MIB]   McCloghrie, K. and F. Kastenholz, "The Interfaces Group
                  MIB", RFC 2863, June 2000.

10. IANA Considerations

    IANA has assigned a MIB OID to the T11-FC-NAME-SERVER-MIB module
    under the appropriate subtree.

11. Security Considerations

    There is one management object defined in this MIB module with a
    MAX-ACCESS clause of read-write and/or read-create. Such objects may
    be considered sensitive or vulnerable in some network environments.
    The support for SET operations in a non-secure environment without
    proper protection can have a negative effect on network operations.
    This object and its sensitivity/vulnerability is:

        t11NsInfoSubsetRejReqNotfyEnable -- the ability to enable/disable
                                            notifications.

    Such objects may be considered sensitive or vulnerable in some
    network environments. For example, the ability to change network
    topology or network speed may afford an attacker the ability to
    obtain better performance at the expense of other network users. The
    support for SET operations in a non-secure environment without proper
    protection can have a negative effect on network operations.

    Some of the readable objects in this MIB module (i.e., objects with a
    MAX-ACCESS other than not-accessible) may be considered sensitive or
    vulnerable in some network environments. It is thus important to
    control even GET and/or NOTIFY access to these objects and possibly
    to even encrypt the values of these objects when sending them over
    the network via SNMP. These are the tables and objects and their
    sensitivity/vulnerability:

   t11NsRegTable -- contains information about registered Nx_Ports.

   t11NsStatsTable -- contains statistics and state information about
                      the Name Server.

SNMP versions prior to SNMPv3 did not include adequate security.
Even if the network itself is secure (for example by using IPsec),
even then, there is no control as to who on the secure network is
allowed to access and GET/SET (read/change/create/delete) the objects
in this MIB module.

It is RECOMMENDED that implementors consider the security features as
provided by the SNMPv3 framework (see [RFC3410], section 8),
including full support for the SNMPv3 cryptographic mechanisms (for
authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT
RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to
enable cryptographic security. It is then a customer/operator
responsibility to ensure that the SNMP entity giving access to an
instance of this MIB module is properly configured to give access to
the objects only to those principals (users) that have legitimate
rights to indeed GET or SET (change/create/delete) them.

Authors' Addresses

   Claudio DeSanti
   Cisco Systems, Inc.
   170 West Tasman Drive
   San Jose, CA 95134 USA

   Phone: +1 408 853-9172
   EMail: cds@cisco.com

   Vinay Gaonkar
   Cisco Systems, Inc.
   170 West Tasman Drive
   San Jose, CA 95134 USA

   Phone: +1 408 527-8576
   EMail: vgaonkar@cisco.com

   H.K. Vivek
   Cisco Systems, Inc.
   71 Millers Rd
   Bangalore, India

   Phone: +91 80 2289933x5117
   EMail: hvivek@cisco.com

   Keith McCloghrie
   Cisco Systems, Inc.
   170 West Tasman Drive
   San Jose, CA USA 95134

   Phone: +1 408-526-5260
   EMail: kzm@cisco.com

   Silvano Gai
   Retired