                     Management Information Base for
 Data Over Cable Service Interface Specification (DOCSIS) Cable Modems
     and Cable Modem Termination Systems for Baseline Privacy Plus

Status of This Memo

Copyright Notice

Abstract

   This memo defines a portion of the Management Information Base (MIB)
   for use with network management protocols in the Internet community.
   In particular, it defines a set of managed objects for Simple Network
   Management Protocol (SNMP) based management of the Baseline Privacy
   Plus features of DOCSIS 1.1 and DOCSIS 2.0 (Data-over-Cable Service
   Interface Specification) compliant Cable Modems and Cable Modem
   Termination Systems.

Table of Contents

1. The Internet-Standard Management Framework

   For a detailed overview of the documents that describe the current
   Internet-Standard Management Framework, please refer to section 7 of
   RFC 3410 [RFC3410].

   Managed objects are accessed via a virtual information store, termed
   the Management Information Base or MIB. MIB objects are generally
   accessed through the Simple Network Management Protocol (SNMP).
   Objects in the MIB are defined using the mechanisms defined in the
   Structure of Management Information (SMI). This memo specifies a MIB
   module that is compliant to the SMIv2, which is described in STD 58,
   RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580
   [RFC2580].

2. Overview

   This MIB module (BPI+ MIB) provides a set of objects required for the
   management of the Baseline Privacy Interface Plus features of DOCSIS
   1.1 and DOCSIS 2.0 Cable Modem (CM) and Cable Modem Termination
   System (CMTS). The specification is derived from the operational
   model described in the DOCSIS Baseline Privacy Interface Plus
   Specification [DOCSIS].

   DOCSIS Baseline Privacy Plus is composed of four distinct functional
   and manageable areas:

   o Key exchange and data encryption

   o Cable modem authentication

   o Multicast encryption

   o Authentication of downloaded software images

   This MIB module is an extension of the DOCSIS 1.0 Baseline Privacy
   MIB module [RFC3083] (BPI MIB), which is derived from the Operational
   model described in the DOCSIS Baseline Privacy Interface
   Specification [DOCSIS-1.0]. The original Baseline Privacy MIB
   structure has mostly been preserved in the Baseline Privacy Plus MIB.
   Please note that the referenced DOCSIS specifications only require
   that Cable Modems process IPv4 customer traffic. Design choices in
   this MIB module reflect those requirements. Future versions of the
   DOCSIS specifications are expected to require support for IPv6 as
   well.

Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT","SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14, RFC 2119 [RFC2119].

2.1. Structure of the MIB

This MIB module is structured into several tables and objects.

2.1.1. Cable Modem

o The docsBpi2CmBaseTable contains authorization key exchange information for one CM MAC interface.

o The docsBpi2CmTEKTable contains traffic key exchange and data encryption information for a particular security association ID of the cable modem.

o Multicast Encryption information is maintained under Docsbpi2CmMulticastObjects. There is currently one multicast table object that manages IP multicast encryption, docsBpi2CmIpMulticastMapTable.

o Digital certificates used for cable modem authentication are accessible via docsBpi2CmDeviceCertTable.

o Cryptographic suite capabilities for a CM MAC are maintained in the docsBpi2CmCryptoSuiteTable.

2.1.2. Cable Modem Termination System

o The docsBpi2CmtsBaseTable contains default settings and summary counters for the cable modem termination system.

o The DocsBpi2CmtsAuthTable contains Authorization Key Exchange information for each CM MAC interface, as well as data from CM certificates used in cable modem authentication.

o The docsBpi2CmtsTEKTable contains traffic key exchange and data encryption information for a particular security association ID.

o Multicast Encryption information is maintained under Docsbpi2CmtsMulticastObjects. There are currently two multicast table objects. The Table docsBpi2CmtsIpMulticastMapTable is

specifically designed for IP multicast encryption, whereas
docsBpi2CmtsMulticastAuthTable is meant to manage all multicast
security associations.

In particular, the table docsBpi2CmtsIpMulticastMapTable
defines the object docsBpi2CmtsIpMulticastMask, which could be
a non-contiguous netmask; this is why the object syntax is
based on the INET-ADDRESS-MIB MIB Module [RFC4001] Textual
Convention InetAddress instead of InetAddressPrefixLength.

This is to facilitate the assignment of same DOCSIS Security
Association ID (SAID) to one or more IPv6 multicast group IDs
matching one or more IPv6 multicast scope types within an entry
in this table. For example, multicast scopes labeled
"unassigned" [RFC3513] may be allocated by administrators to a
particular SAID, regardless of their multicast scope; such
mapping transient multicast group 'Y' to SAID 'z' for ANY
multicast scope. The non-contiguous netmask will be FF10:Y.
See [RFC3513] for details on IPv6 multicast addressing.

o DocsBpi2CmtsCertObjects contains 2 manageable tables: one for
   provisioned cable modem certificates and one for certification
   authority certificates.

2.1.3. Common

o The docsBpi2CodeDownloadControl objects manage the authenticated
   software download process for a given device.

2.2. Relationship of BPI+ and BPI MIB Modules

This section describes the relationship between the BPI+ MIB module
defined in this document and the BPI MIB module defined in RFC 3083
[RFC3083]. The BPI+ protocol interface is an enhancement to the BPI
protocol, and it is a distinct protocol from BPI. The associated
BPI+ managed objects should be considered separate from the BPI MIB
objects defined in RFC 3083.

DOCSIS 1.1 and 2.0 systems implement both the BPI+ and BPI protocols
to be backward compatible with 1.0 systems. For more information
regarding the interoperability between BPI and BPI+ compliant
systems, refer to appendix C of the DOCSIS BPI+ specification
[DOCSIS]. For MIB modules requirements, refer to section 4.6.1,
Figure 9, of the DOCSIS 1.1 OSSI specification [DOCSIS-1.1] and to
section 7.6.1, Tables 7-9, of the DOCSIS 2.0 OSSI specification
[DOCSIS-2.0].

2.3. BPI+ MIB Module Relationship with the Interfaces Group MIB

   The BPI+ MIB module is the management framework of Baseline Privacy
   Plus Interface Specification [DOCSIS], which provides the MAC layer
   (Media Access Control) security services of DOCSIS through the
   Baseline Privacy Key Management (BPKM) protocol. The BPI+ MIB module
   objects are organized as extensions of the Radio Frequency (RF)
   Interface Management [RFC2670].

   The MIB table structures of this MIB Module are extensions of the
   DOCSIS CATV (Community Antenna Television) MAC layer interface
   (DocsCableMaclayer by [IANA]). In particular, the provisions of the
   Interface Group MIB [RFC2863] for counter discontinuities and system
   re-initialization apply to CM and CMTS to validate the difference
   between two consecutive counter polls.

   All BPI+ MIB module counters are 32 bits and are based on the minimum
   time to wrap up considerations of [RFC2863] and their possible
   frequency occurrence as BPI+ FSM (Finite State Machine) event
   counters. See [DOCSIS] for BPI+ FSM parameter guidelines.

3. Definitions

   DOCS-IETF-BPI2-MIB DEFINITIONS ::= BEGIN

   IMPORTS
           MODULE-IDENTITY, OBJECT-TYPE,
           Integer32,
           Unsigned32,
           Counter32,
           mib-2
               FROM SNMPv2-SMI   -- [RFC2578]
           SnmpAdminString
               FROM SNMP-FRAMEWORK-MIB   -- [RFC3411]
           TEXTUAL-CONVENTION,
           MacAddress,
           RowStatus,
           TruthValue,
           DateAndTime,
           StorageType
               FROM SNMPv2-TC   -- [RFC2579]
           OBJECT-GROUP,
           MODULE-COMPLIANCE
               FROM SNMPv2-CONF   -- [RFC2580]
           ifIndex
               FROM IF-MIB   -- [RFC2863]
           InetAddressType,
           InetAddress

```
                   FROM INET-ADDRESS-MIB;    -- [RFC4001]

     docsBpi2MIB     MODULE-IDENTITY
         LAST-UPDATED "200507200000Z" -- July 20, 2005
         ORGANIZATION "IETF IP over Cable Data Network (IPCDN)
                     Working Group"
         CONTACT-INFO "-------------------------------------
                     Stuart M. Green
                     E-mail: rubbersoul3@yahoo.com
                     -------------------------------------
                     Kaz Ozawa
                     Automotive Systems Development Center
                     TOSHIBA CORPORATION
                     1-1, Shibaura 1-Chome
                     Minato-ku, Tokyo 105-8001
                     Japan
                     Phone: +81-3-3457-8569
                     Fax: +81-3-5444-9325
                     E-mail: Kazuyoshi.Ozawa@toshiba.co.jp
                     -------------------------------------
                     Alexander Katsnelson
                     Postal:
                     Tel:    +1-303-680-3924
                     E-mail: katsnelson6@peoplepc.com
                     -------------------------------------
                     Eduardo Cardona
                     Postal:
                     Cable Television Laboratories, Inc.
                     858 Coal Creek Circle
                     Louisville, CO 80027- 9750
                     U.S.A.
                     Tel:    +1 303 661 9100
                     Fax:    +1 303 661 9199
                     E-mail: e.cardona@cablelabs.com
                     -------------------------------------

             IETF IPCDN Working Group
             General Discussion: ipcdn@ietf.org
             Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn.
             Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn.
             Co-chairs: Richard Woundy, rwoundy@cisco.com
                        Jean-Francois Mule, jfm@cablelabs.com"
         DESCRIPTION
            "This is the MIB module for the DOCSIS Baseline
             Privacy Plus Interface (BPI+) at cable modems (CMs)
             and cable modem termination systems (CMTSs).

             Copyright (C) The Internet Society (2005).  This
```

                  version of this MIB module is part of RFC 4131; see
                  the RFC itself for full legal notices."

             REVISION   "200507200000Z" -- July 20, 2005
             DESCRIPTION
                 "Initial version of the IETF BPI+ MIB module.
                  This version published as RFC 4131."
             ::= { mib-2 126 }

       -- Textual conventions

     DocsX509ASN1DEREncodedCertificate ::= TEXTUAL-CONVENTION
             STATUS   current
             DESCRIPTION
                 "An X509 digital certificate encoded as an ASN.1 DER
             object."
             SYNTAX   OCTET STRING (SIZE (0..4096))

     DocsSAId ::= TEXTUAL-CONVENTION
             DISPLAY-HINT "d"
             STATUS   current
             DESCRIPTION
                 "Security Association identifier (SAID)."
             REFERENCE
                  "DOCSIS Baseline Privacy Plus Interface
             specification, Section 2.1.3, BPI+ Security
             Associations"
             SYNTAX   Integer32 (1..16383)

     DocsSAIdOrZero ::= TEXTUAL-CONVENTION
             DISPLAY-HINT "d"
             STATUS   current
             DESCRIPTION
                 "Security Association identifier (SAID). The value
             zero indicates that the SAID is yet to be determined."
             REFERENCE
                  "DOCSIS Baseline Privacy Plus Interface
             specification, Section 2.1.3, BPI+ Security
                  Associations"
             SYNTAX   Unsigned32 (0 | 1..16383)

     DocsBpkmSAType ::= TEXTUAL-CONVENTION
             STATUS   current
             DESCRIPTION
                 "The type of security association (SA).
             The values of the named-numbers are associated
             with the BPKM SA-Type attributes:
             'primary' corresponds to code '1', 'static' to code '2',

            and 'dynamic' to code '3'.
            The 'none' value must only be used if the SA type has yet
            to be determined."
            REFERENCE
                  "DOCSIS Baseline Privacy Plus Interface
            specification, Section 4.2.2.24"
            SYNTAX   INTEGER {
                        none(0),
                        primary(1),
                        static(2),
                        dynamic(3)
                    }

    DocsBpkmDataEncryptAlg ::= TEXTUAL-CONVENTION
            STATUS   current
            DESCRIPTION
                "The list of data encryption algorithms defined for
            the DOCSIS interface in the BPKM cryptographic-suite
            parameter. The value 'none' indicates that the SAID
            being referenced has no data encryption."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.2.20."
            SYNTAX   INTEGER {
                        none(0),
                        des56CbcMode(1),
                        des40CbcMode(2),
                        t3Des128CbcMode(3),
                        aes128CbcMode(4),
                        aes256CbcMode(5)
                    }

    DocsBpkmDataAuthentAlg ::= TEXTUAL-CONVENTION
            STATUS   current
            DESCRIPTION
                "The list of data integrity algorithms defined for the
            DOCSIS interface in the BPKM cryptographic-suite parameter.
            The value 'none' indicates that no data integrity is used for
            the SAID being referenced."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.2.20."
            SYNTAX   INTEGER {
                        none(0),
                        hmacSha196(1)
                    }

        docsBpi2MIBObjects OBJECT IDENTIFIER ::= { docsBpi2MIB 1 }

```
     -- Cable Modem Group

     docsBpi2CmObjects OBJECT IDENTIFIER ::= { docsBpi2MIBObjects 1 }


     --
     -- The BPI+ base and authorization table for CMs,
     -- indexed by ifIndex
     --

     docsBpi2CmBaseTable OBJECT-TYPE
         SYNTAX               SEQUENCE OF    DocsBpi2CmBaseEntry
         MAX-ACCESS           not-accessible
         STATUS               current
         DESCRIPTION
             "This table describes the basic and authorization-
         related Baseline Privacy Plus attributes of each CM MAC
         interface."
         ::= { docsBpi2CmObjects 1 }

     docsBpi2CmBaseEntry OBJECT-TYPE
         SYNTAX               DocsBpi2CmBaseEntry
         MAX-ACCESS           not-accessible
         STATUS               current
         DESCRIPTION
             "Each entry contains objects describing attributes of
         one CM MAC interface.  An entry in this table exists for
         each ifEntry with an ifType of docsCableMaclayer(127)."
         INDEX                { ifIndex }
         ::= { docsBpi2CmBaseTable 1 }

     DocsBpi2CmBaseEntry ::= SEQUENCE {
         docsBpi2CmPrivacyEnable              TruthValue,
         docsBpi2CmPublicKey                  OCTET STRING,
         docsBpi2CmAuthState                  INTEGER,
         docsBpi2CmAuthKeySequenceNumber      Integer32,
         docsBpi2CmAuthExpiresOld             DateAndTime,
         docsBpi2CmAuthExpiresNew             DateAndTime,
         docsBpi2CmAuthReset                  TruthValue,
         docsBpi2CmAuthGraceTime              Integer32,
         docsBpi2CmTEKGraceTime               Integer32,
         docsBpi2CmAuthWaitTimeout            Integer32,
         docsBpi2CmReauthWaitTimeout          Integer32,
         docsBpi2CmOpWaitTimeout              Integer32,
         docsBpi2CmRekeyWaitTimeout           Integer32,
         docsBpi2CmAuthRejectWaitTimeout      Integer32,
         docsBpi2CmSAMapWaitTimeout           Integer32,
         docsBpi2CmSAMapMaxRetries            Integer32,
         docsBpi2CmAuthentInfos               Counter32,
```

```
        docsBpi2CmAuthRequests              Counter32,
        docsBpi2CmAuthReplies               Counter32,
        docsBpi2CmAuthRejects               Counter32,
        docsBpi2CmAuthInvalids              Counter32,
        docsBpi2CmAuthRejectErrorCode       INTEGER,
        docsBpi2CmAuthRejectErrorString     SnmpAdminString,
        docsBpi2CmAuthInvalidErrorCode      INTEGER,
        docsBpi2CmAuthInvalidErrorString    SnmpAdminString
        }

    docsBpi2CmPrivacyEnable  OBJECT-TYPE
        SYNTAX              TruthValue
        MAX-ACCESS          read-only
        STATUS              current
        DESCRIPTION
            "This object identifies whether this CM is
        provisioned to run Baseline Privacy Plus."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Appendix A.1.1."
        ::= { docsBpi2CmBaseEntry 1 }

    docsBpi2CmPublicKey      OBJECT-TYPE
        SYNTAX              OCTET STRING (SIZE (0..524))
        MAX-ACCESS          read-only
        STATUS              current
        DESCRIPTION
            "The value of this object is a DER-encoded
        RSAPublicKey ASN.1 type string, as defined in the RSA
        Encryption Standard (PKCS #1), corresponding to the
        public key of the CM."

        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.2.4."
        ::= { docsBpi2CmBaseEntry 2 }

    docsBpi2CmAuthState OBJECT-TYPE
        SYNTAX           INTEGER   {
                         start(1),
                         authWait(2),
                         authorized(3),
                         reauthWait(4),
                         authRejectWait(5),
                         silent(6)
                 }
        MAX-ACCESS       read-only
        STATUS           current
```

            DESCRIPTION
                "The value of this object is the state of the CM
            authorization FSM. The start state indicates that FSM is
            in its initial state."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.1.2.1."
            ::= { docsBpi2CmBaseEntry 3 }

        docsBpi2CmAuthKeySequenceNumber   OBJECT-TYPE
            SYNTAX   Integer32 (0..15)
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the most recent
            authorization key sequence number for this FSM."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Sections 4.2.1.2 and 4.2.2.10."
            ::= { docsBpi2CmBaseEntry 4 }

        docsBpi2CmAuthExpiresOld OBJECT-TYPE
            SYNTAX   DateAndTime
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the actual clock time for
            expiration of the immediate predecessor of the most recent
            authorization key for this FSM. If this FSM has only one
            authorization key, then the value is the time of activation
            of this FSM."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Sections 4.2.1.2 and 4.2.2.9."
            ::= { docsBpi2CmBaseEntry 5 }

        docsBpi2CmAuthExpiresNew OBJECT-TYPE
            SYNTAX   DateAndTime
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the actual clock time for
            expiration of the most recent authorization key for this
            FSM."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Sections 4.2.1.2 and 4.2.2.9."
            ::= { docsBpi2CmBaseEntry 6 }

```
     docsBpi2CmAuthReset OBJECT-TYPE
          SYNTAX          TruthValue
          MAX-ACCESS      read-write
          STATUS          current
          DESCRIPTION
               "Setting this object to 'true' generates a Reauthorize
          event in the authorization FSM.  Reading this object always
          returns FALSE.

          This object is for testing purposes only, and therefore it
          is not required to be associated with a last reset
          object."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.1.2.3.4."
          ::= { docsBpi2CmBaseEntry 7 }

     docsBpi2CmAuthGraceTime  OBJECT-TYPE
          SYNTAX          Integer32 (1..6047999)
          UNITS           "seconds"
          MAX-ACCESS      read-only
          STATUS          current
          DESCRIPTION
               "The value of this object is the grace time for an
          authorization key in seconds.  A CM is expected to start
          trying to get a new authorization key beginning
          AuthGraceTime seconds before the most recent authorization
          key actually expires."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Appendix A.1.1.1.3."
          ::= { docsBpi2CmBaseEntry 8 }

     docsBpi2CmTEKGraceTime   OBJECT-TYPE
          SYNTAX          Integer32 (1..302399)
          UNITS           "seconds"
          MAX-ACCESS      read-only
          STATUS          current
          DESCRIPTION
               "The value of this object is the grace time for
          the TEK in seconds.  The CM is expected to start trying to
          acquire a new TEK beginning TEK GraceTime seconds before
          the expiration of the most recent TEK."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Appendix A.1.1.1.6."
          ::= { docsBpi2CmBaseEntry 9 }
```

```
     docsBpi2CmAuthWaitTimeout     OBJECT-TYPE
         SYNTAX          Integer32 (1..30)
         UNITS           "seconds"
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the Authorize Wait
         Timeout in seconds."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Appendix A.1.1.1.1."
         ::= { docsBpi2CmBaseEntry 10 }

     docsBpi2CmReauthWaitTimeout    OBJECT-TYPE
         SYNTAX          Integer32 (1..30)
         UNITS           "seconds"
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the Reauthorize Wait
         Timeout in seconds."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Appendix A.1.1.1.2."
         ::= { docsBpi2CmBaseEntry 11 }

     docsBpi2CmOpWaitTimeout  OBJECT-TYPE
         SYNTAX          Integer32 (1..10)
         UNITS           "seconds"
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the Operational Wait
         Timeout in seconds."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Appendix A.1.1.1.4."
         ::= { docsBpi2CmBaseEntry 12 }

     docsBpi2CmRekeyWaitTimeout     OBJECT-TYPE
         SYNTAX          Integer32 (1..10)
         UNITS           "seconds"
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the Rekey Wait Timeout
         in seconds."
         REFERENCE
```

```
                    "DOCSIS Baseline Privacy Plus Interface Specification,
             Appendix A.1.1.1.5."
             ::= { docsBpi2CmBaseEntry 13 }

      docsBpi2CmAuthRejectWaitTimeout    OBJECT-TYPE
             SYNTAX          Integer32 (1..600)
             UNITS           "seconds"
             MAX-ACCESS      read-only
             STATUS          current
             DESCRIPTION
                    "The value of this object is the Authorization Reject
             Wait Timeout in seconds."
             REFERENCE
                    "DOCSIS Baseline Privacy Plus Interface Specification,
             Appendix A.1.1.1.7."
             ::= { docsBpi2CmBaseEntry 14 }

      docsBpi2CmSAMapWaitTimeout    OBJECT-TYPE
             SYNTAX          Integer32 (1..10)
             UNITS           "seconds"
             MAX-ACCESS      read-only
             STATUS          current
             DESCRIPTION
                    "The value of this object is the retransmission
             interval, in seconds, of SA Map Requests from the MAP Wait
             state."
             REFERENCE
                    "DOCSIS Baseline Privacy Plus Interface Specification,
             Appendix A.1.1.1.8."
             ::= { docsBpi2CmBaseEntry 15 }

      docsBpi2CmSAMapMaxRetries    OBJECT-TYPE
             SYNTAX          Integer32 (0..10)
             UNITS           "count"
             MAX-ACCESS      read-only
             STATUS          current
             DESCRIPTION
                    "The value of this object is the maximum number of
             Map Request retries allowed."
             REFERENCE
                    "DOCSIS Baseline Privacy Plus Interface Specification,
             Appendix A.1.1.1.9."
             ::= { docsBpi2CmBaseEntry 16 }

      docsBpi2CmAuthentInfos    OBJECT-TYPE
             SYNTAX          Counter32
             MAX-ACCESS      read-only
             STATUS          current
```

```
        DESCRIPTION
             "The value of this object is the number of times
        the CM has transmitted an Authentication Information
        message.  Discontinuities in the value of this counter can
        occur at re-initialization of the management system, and at
        other times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.9."
        ::= { docsBpi2CmBaseEntry 17 }

    docsBpi2CmAuthRequests   OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
             "The value of this object is the number of times the CM
        has transmitted an Authorization Request message.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.1."
        ::= { docsBpi2CmBaseEntry 18 }

    docsBpi2CmAuthReplies    OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
             "The value of this object is the number of times the CM
        has received an Authorization Reply message.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.2."
        ::= { docsBpi2CmBaseEntry 19 }

    docsBpi2CmAuthRejects    OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
```

```
        DESCRIPTION
             "The value of this object is the number of times the CM
        has received an Authorization Reject message.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.3."
        ::= { docsBpi2CmBaseEntry 20 }

    docsBpi2CmAuthInvalids   OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
             "The value of this object is the count of times the CM
        has received an Authorization Invalid message.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.7."
        ::= { docsBpi2CmBaseEntry 21 }

    docsBpi2CmAuthRejectErrorCode OBJECT-TYPE
        SYNTAX          INTEGER {
                            none(1),
                            unknown(2),
                            unauthorizedCm(3),
                            unauthorizedSaid(4),
                            permanentAuthorizationFailure(8),
                            timeOfDayNotAcquired(11)
                            }
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
             "The value of this object is the enumerated
        description of the Error-Code in the most recent
        Authorization Reject message received by the CM.  This has
        the value unknown(2) if the last Error-Code value was 0 and
        none(1) if no Authorization Reject message has been received
        since reboot."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
```

```
          Sections 4.2.1.3 and 4.2.2.15."
          ::= { docsBpi2CmBaseEntry 22 }

     docsBpi2CmAuthRejectErrorString    OBJECT-TYPE
          SYNTAX          SnmpAdminString (SIZE (0..128))
          MAX-ACCESS      read-only
          STATUS          current
          DESCRIPTION
              "The value of this object is the text string in the
          most recent Authorization Reject message received by the
          CM.  This is a zero length string if no Authorization
          Reject message has been received since reboot."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Sections 4.2.1.3 and 4.2.2.6."
          ::= { docsBpi2CmBaseEntry 23 }

     docsBpi2CmAuthInvalidErrorCode     OBJECT-TYPE
          SYNTAX          INTEGER {
                              none(1),
                              unknown(2),
                              unauthorizedCm(3),
                              unsolicited(5),
                              invalidKeySequence(6),
                              keyRequestAuthenticationFailure(7)
                              }
          MAX-ACCESS      read-only
          STATUS          current
          DESCRIPTION
              "The value of this object is the enumerated
          description of the Error-Code in the most recent
          Authorization Invalid message received by the CM.  This has
          the value unknown(2) if the last Error-Code value was 0 and
          none(1) if no Authorization Invalid message has been received
          since reboot."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Sections 4.2.1.7 and 4.2.2.15."
          ::= { docsBpi2CmBaseEntry 24 }

     docsBpi2CmAuthInvalidErrorString   OBJECT-TYPE
          SYNTAX          SnmpAdminString (SIZE (0..128))
          MAX-ACCESS      read-only
          STATUS          current
          DESCRIPTION
              "The value of this object is the text string in the
          most recent Authorization Invalid message received by the
          CM.  This is a zero length string if no Authorization
```

```
        Invalid message has been received since reboot."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.2.1.7 and 4.2.2.6."
        ::= { docsBpi2CmBaseEntry 25 }

--
-- The CM TEK Table, indexed by ifIndex and SAID
--

docsBpi2CmTEKTable  OBJECT-TYPE
    SYNTAX          SEQUENCE OF    DocsBpi2CmTEKEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
         "This table describes the attributes of each CM
    Traffic Encryption Key (TEK) association.  The CM maintains
    (no more than) one TEK association per SAID per CM MAC
    interface."
    ::= { docsBpi2CmObjects 2 }

docsBpi2CmTEKEntry  OBJECT-TYPE
    SYNTAX          DocsBpi2CmTEKEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
         "Each entry contains objects describing the TEK
    association attributes of one SAID.  The CM MUST create one
    entry per SAID, regardless of whether the SAID was obtained
    from a Registration Response message, from an Authorization
    Reply message, or from any dynamic SAID establishment
    mechanisms."
    INDEX     { ifIndex, docsBpi2CmTEKSAId }
    ::= { docsBpi2CmTEKTable 1 }

DocsBpi2CmTEKEntry ::= SEQUENCE {
    docsBpi2CmTEKSAId                   DocsSAId,
    docsBpi2CmTEKSAType                 DocsBpkmSAType,
    docsBpi2CmTEKDataEncryptAlg         DocsBpkmDataEncryptAlg,
    docsBpi2CmTEKDataAuthentAlg         DocsBpkmDataAuthentAlg,
    docsBpi2CmTEKState                  INTEGER,
    docsBpi2CmTEKKeySequenceNumber      Integer32,
    docsBpi2CmTEKExpiresOld             DateAndTime,
    docsBpi2CmTEKExpiresNew             DateAndTime,
    docsBpi2CmTEKKeyRequests            Counter32,
    docsBpi2CmTEKKeyReplies             Counter32,
    docsBpi2CmTEKKeyRejects             Counter32,
    docsBpi2CmTEKInvalids               Counter32,
```

```
        docsBpi2CmTEKAuthPends            Counter32,
        docsBpi2CmTEKKeyRejectErrorCode   INTEGER,
        docsBpi2CmTEKKeyRejectErrorString SnmpAdminString,
        docsBpi2CmTEKInvalidErrorCode     INTEGER,
        docsBpi2CmTEKInvalidErrorString   SnmpAdminString
        }

    docsBpi2CmTEKSAId   OBJECT-TYPE
        SYNTAX          DocsSAId
        MAX-ACCESS      not-accessible
        STATUS          current
        DESCRIPTION
            "The value of this object is the DOCSIS Security
        Association ID (SAID)."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.2.12."
        ::= { docsBpi2CmTEKEntry 1 }

    docsBpi2CmTEKSAType OBJECT-TYPE
        SYNTAX          DocsBpkmSAType
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the type of security
        association."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 2.1.3."
        ::= { docsBpi2CmTEKEntry 2 }

    docsBpi2CmTEKDataEncryptAlg   OBJECT-TYPE
        SYNTAX     DocsBpkmDataEncryptAlg
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the data encryption
        algorithm for this SAID."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.2.20."
        ::= { docsBpi2CmTEKEntry 3 }

    docsBpi2CmTEKDataAuthentAlg   OBJECT-TYPE
        SYNTAX     DocsBpkmDataAuthentAlg
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
```

                   "The value of this object is the data authentication
              algorithm for this SAID."
              REFERENCE
                   "DOCSIS Baseline Privacy Plus Interface Specification,
              Section 4.2.2.20."
              ::= { docsBpi2CmTEKEntry 4 }

         docsBpi2CmTEKState OBJECT-TYPE
              SYNTAX   INTEGER {
                                   start(1),
                                   opWait(2),
                                   opReauthWait(3),
                                   operational(4),
                                   rekeyWait(5),
                                   rekeyReauthWait(6)
                                   }
              MAX-ACCESS   read-only
              STATUS   current
              DESCRIPTION
                   "The value of this object is the state of the
              indicated TEK FSM. The start(1) state indicates that the
              FSM is in its initial state."
              REFERENCE
                   "DOCSIS Baseline Privacy Plus Interface Specification,
              Section 4.1.3.1."
              ::= { docsBpi2CmTEKEntry 5 }

         docsBpi2CmTEKKeySequenceNumber   OBJECT-TYPE
              SYNTAX   Integer32 (0..15)
              MAX-ACCESS   read-only
              STATUS   current
              DESCRIPTION
                   "The value of this object is the most recent TEK
              key sequence number for this TEK FSM."
              REFERENCE
                   "DOCSIS Baseline Privacy Plus Interface Specification,
              Sections 4.2.2.10 and 4.2.2.13."
              ::= { docsBpi2CmTEKEntry 6 }

         docsBpi2CmTEKExpiresOld OBJECT-TYPE
              SYNTAX   DateAndTime
              MAX-ACCESS   read-only
              STATUS   current
              DESCRIPTION
                   "The value of this object is the actual clock time for
              expiration of the immediate predecessor of the most recent
              TEK for this FSM. If this FSM has only one TEK, then the
              value is the time of activation of this FSM."

```
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.2.1.5 and 4.2.2.9."
        ::= { docsBpi2CmTEKEntry 7 }

    docsBpi2CmTEKExpiresNew  OBJECT-TYPE
        SYNTAX          DateAndTime
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the actual clock time for
        expiration of the most recent TEK for this FSM."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.2.1.5 and 4.2.2.9."
        ::= { docsBpi2CmTEKEntry 8 }

    docsBpi2CmTEKKeyRequests OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the number of times the CM
        has transmitted a Key Request message.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."

        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.4."
        ::= { docsBpi2CmTEKEntry 9 }

    docsBpi2CmTEKKeyReplies  OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the number of times the CM
        has received a Key Reply message, including a message whose
        authentication failed.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
```

               Section 4.2.1.5."
            ::= { docsBpi2CmTEKEntry 10 }

       docsBpi2CmTEKKeyRejects OBJECT-TYPE
            SYNTAX   Counter32
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the number of times the CM
            has received a Key Reject message, including a message
            whose authentication failed.
            Discontinuities in the value of this counter can occur at
            re-initialization of the management system, and at other
            times as indicated by the value of
            ifCounterDiscontinuityTime."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.1.6."
            ::= { docsBpi2CmTEKEntry 11 }

       docsBpi2CmTEKInvalids   OBJECT-TYPE
            SYNTAX   Counter32
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the number of times the CM
            has received a TEK Invalid message, including a message
            whose authentication failed.
            Discontinuities in the value of this counter can occur at
            re-initialization of the management system, and at other
            times as indicated by the value of
            ifCounterDiscontinuityTime."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.1.8."
            ::= { docsBpi2CmTEKEntry 12 }

       docsBpi2CmTEKAuthPends   OBJECT-TYPE
            SYNTAX   Counter32
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the count of times an
            Authorization Pending (Auth Pend) event occurred in this
            FSM.
            Discontinuities in the value of this counter can occur at
            re-initialization of the management system, and at other
            times as indicated by the value of

```
        ifCounterDiscontinuityTime."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.1.3.3.3."
        ::= { docsBpi2CmTEKEntry 13 }

   docsBpi2CmTEKKeyRejectErrorCode     OBJECT-TYPE
        SYNTAX          INTEGER {
                            none(1),
                            unknown(2),
                            unauthorizedSaid(4)
                            }
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the enumerated
        description of the Error-Code in the most recent Key Reject
        message received by the CM.  This has the value unknown(2) if
        the last Error-Code value was 0 and none(1) if no Key
        Reject message has been received since registration."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.1.2.6 and 4.2.2.15."
        ::= { docsBpi2CmTEKEntry 14 }

   docsBpi2CmTEKKeyRejectErrorString  OBJECT-TYPE
        SYNTAX          SnmpAdminString (SIZE (0..128))
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the text string in the
        most recent Key Reject message received by the CM.  This is
        a zero length string if no Key Reject message has been
        received since registration."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.1.2.6 and 4.2.2.6."
        ::= { docsBpi2CmTEKEntry 15 }

   docsBpi2CmTEKInvalidErrorCode OBJECT-TYPE
        SYNTAX          INTEGER {
                            none(1),
                            unknown(2),
                            invalidKeySequence(6)
                            }
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
```

          "The value of this object is the enumerated
       description of the Error-Code in the most recent TEK Invalid
       message received by the CM. This has the value unknown(2) if
       the last Error-Code value was 0 and none(1) if no TEK
       Invalid message has been received since registration."
       REFERENCE
           "DOCSIS Baseline Privacy Plus Interface Specification,
       Sections 4.1.2.8 and 4.2.2.15."
       ::= { docsBpi2CmTEKEntry 16 }

    docsBpi2CmTEKInvalidErrorString   OBJECT-TYPE
       SYNTAX   SnmpAdminString (SIZE (0..128))
       MAX-ACCESS   read-only
       STATUS   current
       DESCRIPTION
           "The value of this object is the text string in the
       most recent TEK Invalid message received by the CM. This is
       a zero length string if no TEK Invalid message has been
       received since registration."
       REFERENCE
           "DOCSIS Baseline Privacy Plus Interface Specification,
       Sections 4.1.2.8 and 4.2.2.6."
       ::= { docsBpi2CmTEKEntry 17 }

    --
    -- The CM Multicast Objects Group
    --

    docsBpi2CmMulticastObjects OBJECT IDENTIFIER
        ::= { docsBpi2CmObjects 3 }

    --
    -- The CM Dynamic IP Multicast Mapping Table, indexed by
    -- docsBpi2CmIpMulticastIndex and by ifIndex
    --

    docsBpi2CmIpMulticastMapTable OBJECT-TYPE
       SYNTAX   SEQUENCE OF DocsBpi2CmIpMulticastMapEntry
       MAX-ACCESS   not-accessible
       STATUS   current
       DESCRIPTION
           "This table maps multicast IP addresses to SAIDs per
       CM MAC Interface.
       It is intended to map multicast IP addresses associated
       with SA MAP Request messages."
       ::= { docsBpi2CmMulticastObjects 1 }

    docsBpi2CmIpMulticastMapEntry OBJECT-TYPE

```
        SYNTAX          DocsBpi2CmIpMulticastMapEntry
        MAX-ACCESS      not-accessible
        STATUS          current
        DESCRIPTION
            "Each entry contains objects describing the mapping of
        one multicast IP address to one SAID, as well as
        associated state, message counters, and error information.

        An entry may be removed from this table upon the reception
        of an SA Map Reject."
        INDEX     { ifIndex, docsBpi2CmIpMulticastIndex }
        ::= { docsBpi2CmIpMulticastMapTable 1 }

    DocsBpi2CmIpMulticastMapEntry ::= SEQUENCE {
        docsBpi2CmIpMulticastIndex             Unsigned32,
        docsBpi2CmIpMulticastAddressType       InetAddressType,
        docsBpi2CmIpMulticastAddress           InetAddress,
        docsBpi2CmIpMulticastSAId              DocsSAIdOrZero,
        docsBpi2CmIpMulticastSAMapState        INTEGER,
        docsBpi2CmIpMulticastSAMapRequests     Counter32,
        docsBpi2CmIpMulticastSAMapReplies      Counter32,
        docsBpi2CmIpMulticastSAMapRejects      Counter32,
        docsBpi2CmIpMulticastSAMapRejectErrorCode INTEGER,
        docsBpi2CmIpMulticastSAMapRejectErrorString SnmpAdminString
        }

    docsBpi2CmIpMulticastIndex        OBJECT-TYPE
        SYNTAX          Unsigned32 (1..4294967295)
        MAX-ACCESS      not-accessible
        STATUS          current
        DESCRIPTION
            "The index of this row."
        ::= { docsBpi2CmIpMulticastMapEntry 1 }

    docsBpi2CmIpMulticastAddressType   OBJECT-TYPE
        SYNTAX          InetAddressType
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The type of Internet address for
        docsBpi2CmIpMulticastAddress."
        ::= { docsBpi2CmIpMulticastMapEntry 2 }

    docsBpi2CmIpMulticastAddress  OBJECT-TYPE
        SYNTAX          InetAddress
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
```

                "This object represents the IP multicast address
          to be mapped. The type of this address is determined by
          the value of the docsBpi2CmIpMulticastAddressType object."
          REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 5.4."
          ::= { docsBpi2CmIpMulticastMapEntry 3 }

     docsBpi2CmIpMulticastSAId   OBJECT-TYPE
          SYNTAX   DocsSAIdOrZero
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
                "This object represents the SAID to which the IP
          multicast address has been mapped. If no SA Map Reply has
          been received for the IP address, this object should have
          the value 0."
          REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.2.12."
          ::= { docsBpi2CmIpMulticastMapEntry 4 }

     docsBpi2CmIpMulticastSAMapState   OBJECT-TYPE
          SYNTAX   INTEGER {
                          start(1),
                          mapWait(2),
                          mapped(3)
                     }
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
                "The value of this object is the state of the SA
          Mapping FSM for this IP."
          REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 5.3.1."
          ::= { docsBpi2CmIpMulticastMapEntry 5 }

     docsBpi2CmIpMulticastSAMapRequests OBJECT-TYPE
          SYNTAX   Counter32
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
                "The value of this object is the number of times the
          CM has transmitted an SA Map Request message for this IP.
          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other
          times as indicated by the value of

```
            ifCounterDiscontinuityTime."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.1.10."
            ::= { docsBpi2CmIpMulticastMapEntry 6 }

      docsBpi2CmIpMulticastSAMapReplies  OBJECT-TYPE
            SYNTAX          Counter32
            MAX-ACCESS      read-only
            STATUS          current
            DESCRIPTION
                "The value of this object is the number of times the
            CM has received an SA Map Reply message for this IP.
            Discontinuities in the value of this counter can occur at
            re-initialization of the management system, and at other
            times as indicated by the value of
            ifCounterDiscontinuityTime."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.1.11."
            ::= { docsBpi2CmIpMulticastMapEntry 7 }

      docsBpi2CmIpMulticastSAMapRejects  OBJECT-TYPE
            SYNTAX          Counter32
            MAX-ACCESS      read-only
            STATUS          current
            DESCRIPTION
                "The value of this object is the number of times the
            CM has received an SA MAP Reject message for this IP.
            Discontinuities in the value of this counter can occur at
            re-initialization of the management system, and at other
            times as indicated by the value of
            ifCounterDiscontinuityTime."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.1.12."
            ::= { docsBpi2CmIpMulticastMapEntry 8 }

      docsBpi2CmIpMulticastSAMapRejectErrorCode    OBJECT-TYPE
            SYNTAX          INTEGER {
                            none(1),
                            unknown(2),
                            noAuthForRequestedDSFlow(9),
                            dsFlowNotMappedToSA(10)
                            }
            MAX-ACCESS      read-only
            STATUS          current
            DESCRIPTION
```

```
             "The value of this object is the enumerated
        description of the Error-Code in the most recent SA Map
        Reject message sent in response to an SA Map Request for
        This IP.  It has the value none(1) if no SA MAP Reject
        message has been received since entry creation."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.2.1.12 and 4.2.2.15."
        ::= { docsBpi2CmIpMulticastMapEntry 9 }

    docsBpi2CmIpMulticastSAMapRejectErrorString  OBJECT-TYPE
        SYNTAX          SnmpAdminString (SIZE (0..128))
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
             "The value of this object is the text string in
        the most recent SA Map Reject message sent in response to
        an SA Map Request for this IP.  It is a zero length string
        if no SA Map Reject message has been received since entry
        creation."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.2.1.12 and 4.2.2.6."
        ::= { docsBpi2CmIpMulticastMapEntry 10 }

    --
    -- CM Cert Objects
    --

    docsBpi2CmCertObjects OBJECT IDENTIFIER
        ::= { docsBpi2CmObjects 4 }


    --
    -- CM Device Cert Table
    --

    docsBpi2CmDeviceCertTable  OBJECT-TYPE
        SYNTAX                  SEQUENCE OF DocsBpi2CmDeviceCertEntry
        MAX-ACCESS              not-accessible
        STATUS                  current
        DESCRIPTION
             "This table describes the Baseline Privacy Plus
        device certificates for each CM MAC interface."
        ::= { docsBpi2CmCertObjects 1 }

    docsBpi2CmDeviceCertEntry  OBJECT-TYPE
        SYNTAX             DocsBpi2CmDeviceCertEntry
        MAX-ACCESS         not-accessible
```

```
        STATUS              current
        DESCRIPTION
            "Each entry contains the device certificates of
        one CM MAC interface.  An entry in this table exists for
        each ifEntry with an ifType of docsCableMaclayer(127)."
        INDEX              { ifIndex }
        ::= { docsBpi2CmDeviceCertTable 1 }

    DocsBpi2CmDeviceCertEntry ::= SEQUENCE {
        docsBpi2CmDeviceCmCert
                            DocsX509ASN1DEREncodedCertificate,
        docsBpi2CmDeviceManufCert
                            DocsX509ASN1DEREncodedCertificate
        }

    docsBpi2CmDeviceCmCert   OBJECT-TYPE
        SYNTAX          DocsX509ASN1DEREncodedCertificate
        MAX-ACCESS        read-write
        STATUS              current
        DESCRIPTION
            "The X509 DER-encoded cable modem certificate.
        Note:  This object can be set only when the value is the
        zero-length OCTET STRING; otherwise, an error of
        'inconsistentValue' is returned.  Once the object
        contains the certificate, its access MUST be read-only
        and persists after re-initialization of the
        managed system."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.1."
        ::= { docsBpi2CmDeviceCertEntry 1 }

    docsBpi2CmDeviceManufCert     OBJECT-TYPE
        SYNTAX          DocsX509ASN1DEREncodedCertificate
        MAX-ACCESS    read-only
        STATUS          current
        DESCRIPTION
            "The X509 DER-encoded manufacturer certificate that
        signed the cable modem certificate."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.1."
        ::= { docsBpi2CmDeviceCertEntry 2 }

    --
    -- CM Crypto Suite Table
    --
```

```
     docsBpi2CmCryptoSuiteTable    OBJECT-TYPE
         SYNTAX         SEQUENCE OF    DocsBpi2CmCryptoSuiteEntry
         MAX-ACCESS     not-accessible
         STATUS         current
         DESCRIPTION
             "This table describes the Baseline Privacy Plus
         cryptographic suite capabilities for each CM MAC
         interface."
         ::= { docsBpi2CmObjects 5 }

     docsBpi2CmCryptoSuiteEntry    OBJECT-TYPE
         SYNTAX         DocsBpi2CmCryptoSuiteEntry
         MAX-ACCESS     not-accessible
         STATUS         current
         DESCRIPTION
             "Each entry contains a cryptographic suite pair
         that this CM MAC supports."
         INDEX    { ifIndex, docsBpi2CmCryptoSuiteIndex }
         ::= { docsBpi2CmCryptoSuiteTable 1 }

     DocsBpi2CmCryptoSuiteEntry ::= SEQUENCE {
         docsBpi2CmCryptoSuiteIndex             Unsigned32,
         docsBpi2CmCryptoSuiteDataEncryptAlg
                                    DocsBpkmDataEncryptAlg,
         docsBpi2CmCryptoSuiteDataAuthentAlg
                                    DocsBpkmDataAuthentAlg
         }

     docsBpi2CmCryptoSuiteIndex OBJECT-TYPE
         SYNTAX         Unsigned32 (1..1000)
         MAX-ACCESS     not-accessible
         STATUS         current
         DESCRIPTION
             "The index for a cryptographic suite row."
         ::= { docsBpi2CmCryptoSuiteEntry 1 }

     docsBpi2CmCryptoSuiteDataEncryptAlg    OBJECT-TYPE
         SYNTAX    DocsBpkmDataEncryptAlg
         MAX-ACCESS     read-only
         STATUS         current
         DESCRIPTION
             "The value of this object is the data encryption
         algorithm for this cryptographic suite capability."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Section 4.2.2.20."
         ::= { docsBpi2CmCryptoSuiteEntry 2 }
```

```
     docsBpi2CmCryptoSuiteDataAuthentAlg     OBJECT-TYPE
         SYNTAX     DocsBpkmDataAuthentAlg
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the data authentication
         algorithm for this cryptographic suite capability."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Section 4.2.2.20."
         ::= { docsBpi2CmCryptoSuiteEntry 3 }

     -- Cable Modem Termination System Group

   docsBpi2CmtsObjects OBJECT IDENTIFIER ::= { docsBpi2MIBObjects 2 }

     --
     -- SPECIAL NOTE:  For the following CMTS tables, when a CM is
     -- running in BPI mode, replace SAID (Security Association ID)
     -- with SID (Service ID).  The CMTS is required to map SAIDs and
     -- SIDs to one contiguous space.
     --


     --
     -- The BPI+ base table for CMTSs, indexed by ifIndex
     --

     docsBpi2CmtsBaseTable    OBJECT-TYPE
         SYNTAX                  SEQUENCE OF    DocsBpi2CmtsBaseEntry
         MAX-ACCESS              not-accessible
         STATUS                  current
         DESCRIPTION
             "This table describes the basic Baseline Privacy
         attributes of each CMTS MAC interface."
         ::= { docsBpi2CmtsObjects 1 }

     docsBpi2CmtsBaseEntry    OBJECT-TYPE
         SYNTAX                  DocsBpi2CmtsBaseEntry
         MAX-ACCESS              not-accessible
         STATUS                  current
         DESCRIPTION
             "Each entry contains objects describing attributes of
         one CMTS MAC interface.  An entry in this table exists for
         each ifEntry with an ifType of docsCableMaclayer(127)."
         INDEX     { ifIndex }
         ::= { docsBpi2CmtsBaseTable 1 }

     DocsBpi2CmtsBaseEntry ::= SEQUENCE {
```

```
        docsBpi2CmtsDefaultAuthLifetime              Integer32,
        docsBpi2CmtsDefaultTEKLifetime               Integer32,
        docsBpi2CmtsDefaultSelfSignedManufCertTrust  INTEGER,
            docsBpi2CmtsCheckCertValidityPeriods         TruthValue,
            docsBpi2CmtsAuthentInfos                     Counter32,
            docsBpi2CmtsAuthRequests                     Counter32,
            docsBpi2CmtsAuthReplies                      Counter32,
            docsBpi2CmtsAuthRejects                      Counter32,
            docsBpi2CmtsAuthInvalids                     Counter32,
            docsBpi2CmtsSAMapRequests                    Counter32,
            docsBpi2CmtsSAMapReplies                     Counter32,
            docsBpi2CmtsSAMapRejects                     Counter32
            }

    docsBpi2CmtsDefaultAuthLifetime    OBJECT-TYPE
        SYNTAX          Integer32 (1..6048000)
        UNITS           "seconds"
        MAX-ACCESS      read-write
        STATUS          current
        DESCRIPTION
            "The value of this object is the default lifetime, in
        seconds, that the CMTS assigns to a new authorization key.
        This object value persists after re-initialization of the
        managed system."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Appendix A.2."
        DEFVAL { 604800 }
        ::= { docsBpi2CmtsBaseEntry 1 }

    docsBpi2CmtsDefaultTEKLifetime     OBJECT-TYPE
        SYNTAX          Integer32 (1..604800)
        UNITS           "seconds"
        MAX-ACCESS      read-write
        STATUS          current
        DESCRIPTION
            "The value of this object is the default lifetime, in
        seconds, that the CMTS assigns to a new Traffic Encryption
        Key (TEK).
        This object value persists after re-initialization of the
        managed system."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Appendix A.2."
        DEFVAL { 43200 }
        ::= { docsBpi2CmtsBaseEntry 2 }

    docsBpi2CmtsDefaultSelfSignedManufCertTrust  OBJECT-TYPE
```

```
        SYNTAX    INTEGER {
                trusted (1),
                untrusted (2)
                }
        MAX-ACCESS      read-write
        STATUS          current
        DESCRIPTION
            "This object determines the default trust of
        self-signed manufacturer certificate entries, contained
        in docsBpi2CmtsCACertTable, and created after this
        object is set.
        This object need not persist after re-initialization
        of the managed system."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.4.1"
        ::= { docsBpi2CmtsBaseEntry 3 }

    docsBpi2CmtsCheckCertValidityPeriods    OBJECT-TYPE
        SYNTAX          TruthValue
        MAX-ACCESS      read-write
        STATUS          current
        DESCRIPTION
            "Setting this object to 'true' causes all chained and
        root certificates in the chain to have their validity
        periods checked against the current time of day, when
        the CMTS receives an Authorization Request from the
        CM.
        A 'false' setting causes all certificates in the chain
        not to have their validity periods checked against the
        current time of day.
        This object need not persist after re-initialization
        of the managed system."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.4.2"
        ::= { docsBpi2CmtsBaseEntry 4 }

    docsBpi2CmtsAuthentInfos OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the number of times the
        CMTS has received an Authentication Information message
        from any CM.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
```

           times as indicated by the value of
           ifCounterDiscontinuityTime."
           REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
           Section 4.2.1.9."
           ::= { docsBpi2CmtsBaseEntry 5 }

      docsBpi2CmtsAuthRequests OBJECT-TYPE
           SYNTAX   Counter32
           MAX-ACCESS   read-only
           STATUS   current
           DESCRIPTION
                   "The value of this object is the number of times the
           CMTS has received an Authorization Request message from any
           CM.
           Discontinuities in the value of this counter can occur at
           re-initialization of the management system, and at other
           times as indicated by the value of
           ifCounterDiscontinuityTime."
           REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
           Section 4.2.1.1."
           ::= { docsBpi2CmtsBaseEntry 6 }

      docsBpi2CmtsAuthReplies OBJECT-TYPE
           SYNTAX   Counter32
           MAX-ACCESS   read-only
           STATUS   current
           DESCRIPTION
                   "The value of this object is the number of times the
           CMTS has transmitted an Authorization Reply message to any
           CM.
           Discontinuities in the value of this counter can occur at
           re-initialization of the management system, and at other
           times as indicated by the value of
           ifCounterDiscontinuityTime."
           REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
           Section 4.2.1.2."
           ::= { docsBpi2CmtsBaseEntry 7 }

      docsBpi2CmtsAuthRejects OBJECT-TYPE
           SYNTAX   Counter32
           MAX-ACCESS   read-only
           STATUS   current
           DESCRIPTION
                   "The value of this object is the number of times the
           CMTS has transmitted an Authorization Reject message to any

```
        CM.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.3."
        ::= { docsBpi2CmtsBaseEntry 8 }

    docsBpi2CmtsAuthInvalids OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
                "The value of this object is the number of times
        the CMTS has transmitted an Authorization Invalid message
        to any CM.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.7."
        ::= { docsBpi2CmtsBaseEntry 9 }

    docsBpi2CmtsSAMapRequests     OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
             "The value of this object is the number of times the
        CMTS has received an SA Map Request message from any CM.
        Discontinuities in the value of this counter can occur at
        re-initialization of the management system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 4.2.1.10."
        ::= { docsBpi2CmtsBaseEntry 10 }

    docsBpi2CmtsSAMapReplies OBJECT-TYPE
        SYNTAX          Counter32
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
```

             "The value of this object is the number of times the
         CMTS has transmitted an SA Map Reply message to any CM.
         Discontinuities in the value of this counter can occur at
         re-initialization of the management system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Section 4.2.1.11."
         ::= { docsBpi2CmtsBaseEntry 11 }

     docsBpi2CmtsSAMapRejects OBJECT-TYPE
         SYNTAX   Counter32
         MAX-ACCESS   read-only
         STATUS   current
         DESCRIPTION
             "The value of this object is the number of times the
         CMTS has transmitted an SA Map Reject message to any CM.
         Discontinuities in the value of this counter can occur at
         re-initialization of the management system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Section 4.2.1.12."
         ::= { docsBpi2CmtsBaseEntry 12 }

     --
     -- The CMTS Authorization Table, indexed by ifIndex and CM MAC
     -- address
     --

     docsBpi2CmtsAuthTable   OBJECT-TYPE
         SYNTAX   SEQUENCE OF   DocsBpi2CmtsAuthEntry
         MAX-ACCESS   not-accessible
         STATUS   current
         DESCRIPTION
             "This table describes the attributes of each CM
         authorization association. The CMTS maintains one
         authorization association with each Baseline Privacy-
         enabled CM, registered on each CMTS MAC interface,
         regardless of whether the CM is authorized or rejected."
         ::= { docsBpi2CmtsObjects 2 }

     docsBpi2CmtsAuthEntry   OBJECT-TYPE
         SYNTAX   DocsBpi2CmtsAuthEntry
         MAX-ACCESS   not-accessible
         STATUS   current

         DESCRIPTION
               "Each entry contains objects describing attributes of
         one authorization association. The CMTS MUST create one
         entry per CM per MAC interface, based on the receipt of an
         Authorization Request message, and MUST not delete the
         entry until the CM loses registration."
         INDEX   { ifIndex, docsBpi2CmtsAuthCmMacAddress }
         ::= { docsBpi2CmtsAuthTable 1 }

     DocsBpi2CmtsAuthEntry ::= SEQUENCE {
         docsBpi2CmtsAuthCmMacAddress   MacAddress,
         docsBpi2CmtsAuthCmBpiVersion   INTEGER,
         docsBpi2CmtsAuthCmPublicKey   OCTET STRING,
         docsBpi2CmtsAuthCmKeySequenceNumber Integer32,
         docsBpi2CmtsAuthCmExpiresOld   DateAndTime,
         docsBpi2CmtsAuthCmExpiresNew   DateAndTime,
         docsBpi2CmtsAuthCmLifetime   Integer32,
         docsBpi2CmtsAuthCmReset   INTEGER,
         docsBpi2CmtsAuthCmInfos   Counter32,
         docsBpi2CmtsAuthCmRequests   Counter32,
         docsBpi2CmtsAuthCmReplies   Counter32,
         docsBpi2CmtsAuthCmRejects   Counter32,
         docsBpi2CmtsAuthCmInvalids   Counter32,
         docsBpi2CmtsAuthRejectErrorCode   INTEGER,
         docsBpi2CmtsAuthRejectErrorString   SnmpAdminString,
         docsBpi2CmtsAuthInvalidErrorCode   INTEGER,
         docsBpi2CmtsAuthInvalidErrorString   SnmpAdminString,
         docsBpi2CmtsAuthPrimarySAId   DocsSAIdOrZero,
         docsBpi2CmtsAuthBpkmCmCertValid   INTEGER,
         docsBpi2CmtsAuthBpkmCmCert
                             DocsX509ASN1DEREncodedCertificate,
         docsBpi2CmtsAuthCACertIndexPtr   Unsigned32
         }

     docsBpi2CmtsAuthCmMacAddress OBJECT-TYPE
         SYNTAX   MacAddress
         MAX-ACCESS   not-accessible
         STATUS   current
         DESCRIPTION
               "The value of this object is the physical address of
         the CM to which the authorization association applies."
         ::= { docsBpi2CmtsAuthEntry 1 }

     docsBpi2CmtsAuthCmBpiVersion OBJECT-TYPE
         SYNTAX   INTEGER {
                      bpi (0),
                      bpiPlus (1)
                       }

          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
              "The value of this object is the version of Baseline
          Privacy for which this CM has registered. The value
          'bpiplus' represents the value of BPI-Version Attribute of
          the Baseline Privacy Key Management BPKM attribute
          BPI-Version (1). The value 'bpi' is used to represent the
          CM registered using DOCSIS 1.0 Baseline Privacy."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.2.22; ANSI/SCTE 22-2 2002(formerly DSS 02-03)
          Data-Over-Cable Service Interface Specification DOCSIS 1.0
          Baseline Privacy Interface (BPI)"
          ::= { docsBpi2CmtsAuthEntry 2 }

      docsBpi2CmtsAuthCmPublicKey   OBJECT-TYPE
          SYNTAX   OCTET STRING (SIZE (0..524))
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
              "The value of this object is a DER-encoded
          RSAPublicKey ASN.1 type string, as defined in the RSA
          Encryption Standard (PKCS #1), corresponding to the
          public key of the CM. This is the zero-length OCTET
          STRING if the CMTS does not retain the public key."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.2.4."
          ::= { docsBpi2CmtsAuthEntry 3 }

      docsBpi2CmtsAuthCmKeySequenceNumber   OBJECT-TYPE
          SYNTAX   Integer32 (0..15)
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
              "The value of this object is the most recent
          authorization key sequence number for this CM."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Sections 4.2.1.2 and 4.2.2.10."
          ::= { docsBpi2CmtsAuthEntry 4 }

      docsBpi2CmtsAuthCmExpiresOld OBJECT-TYPE
          SYNTAX   DateAndTime
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION

        "The value of this object is the actual clock time
    for expiration of the immediate predecessor of the most
    recent authorization key for this FSM. If this FSM has only
    one authorization key, then the value is the time of
    activation of this FSM.
    Note: This object has no meaning for CMs running in BPI
    mode; therefore, this object is not instantiated for entries
    associated to those CMs."
    REFERENCE
        "DOCSIS Baseline Privacy Plus Interface Specification,
    Sections 4.2.1.2 and 4.2.2.9."
    ::= { docsBpi2CmtsAuthEntry 5 }

docsBpi2CmtsAuthCmExpiresNew OBJECT-TYPE
    SYNTAX   DateAndTime
    MAX-ACCESS   read-only
    STATUS   current
    DESCRIPTION
            "The value of this object is the actual clock
    time for expiration of the most recent authorization key
    for this FSM."
    REFERENCE
        "DOCSIS Baseline Privacy Plus Interface Specification,
    Sections 4.2.1.2 and 4.2.2.9."
    ::= { docsBpi2CmtsAuthEntry 6 }

docsBpi2CmtsAuthCmLifetime   OBJECT-TYPE
    SYNTAX   Integer32 (1..6048000)
    UNITS   "seconds"
    MAX-ACCESS   read-write
    STATUS   current
    DESCRIPTION
        "The value of this object is the lifetime, in seconds,
    that the CMTS assigns to an authorization key for this CM."
    REFERENCE
        "DOCSIS Baseline Privacy Plus Interface Specification,
    Section 4.2.1.2 and Appendix A.2."
    ::= { docsBpi2CmtsAuthEntry 7 }

docsBpi2CmtsAuthCmReset OBJECT-TYPE
    SYNTAX   INTEGER {
                        noResetRequested(1),
                        invalidateAuth(2),
                        sendAuthInvalid(3),
                        invalidateTeks(4)
                        }
    MAX-ACCESS   read-write
    STATUS   current

DESCRIPTION
     "Setting this object to invalidateAuth(2) causes the
CMTS to invalidate the current CM authorization key(s), but
not to transmit an Authorization Invalid message nor to
invalidate the primary SAID's TEKs. Setting this object to
sendAuthInvalid(3) causes the CMTS to invalidate the
current CM authorization key(s), and to transmit an
Authorization Invalid message to the CM, but not to
invalidate the primary SAID's TEKs. Setting this object to
invalidateTeks(4) causes the CMTS to invalidate the current
CM authorization key(s), to transmit an Authorization
Invalid message to the CM, and to invalidate the TEKs
associated with this CM's primary SAID.
For BPI mode, substitute all of the CM's unicast
TEKs for the primary SAID's TEKs in the previous
paragraph.
Reading this object returns the most recently set
value of this object or, if the object has not been set
since entry creation, returns noResetRequested(1)."
REFERENCE
     "DOCSIS Baseline Privacy Plus Interface Specification,
Sections 4.1.2.3.4, 4.1.2.3.5, and 4.1.3.3.5."
::= { docsBpi2CmtsAuthEntry 8 }

docsBpi2CmtsAuthCmInfos   OBJECT-TYPE
     SYNTAX   Counter32
     MAX-ACCESS   read-only
     STATUS   current
     DESCRIPTION
          "The value of this object is the number of times the
     CMTS has received an Authentication Information message
     from this CM.
     Discontinuities in the value of this counter can occur at
     re-initialization of the management system, and at other
     times as indicated by the value of
     ifCounterDiscontinuityTime."
     REFERENCE
          "DOCSIS Baseline Privacy Plus Interface Specification,
     Section 4.2.1.9."
     ::= { docsBpi2CmtsAuthEntry 9 }

docsBpi2CmtsAuthCmRequests   OBJECT-TYPE
     SYNTAX   Counter32
     MAX-ACCESS   read-only
     STATUS   current
     DESCRIPTION
          "The value of this object is the number of times the
     CMTS has received an Authorization Request message from

          this CM.
          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other
          times as indicated by the value of
          ifCounterDiscontinuityTime."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.1.1."
          ::= { docsBpi2CmtsAuthEntry 10 }

     docsBpi2CmtsAuthCmReplies   OBJECT-TYPE
          SYNTAX   Counter32
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
              "The value of this object is the number of times the
          CMTS has transmitted an Authorization Reply message to this
          CM.
          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other
          times as indicated by the value of
          ifCounterDiscontinuityTime."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.1.2."
          ::= { docsBpi2CmtsAuthEntry 11 }

     docsBpi2CmtsAuthCmRejects   OBJECT-TYPE
          SYNTAX   Counter32
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
              "The value of this object is the number of times the
          CMTS has transmitted an Authorization Reject message to
          this CM.
          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other
          times as indicated by the value of
          ifCounterDiscontinuityTime."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.1.3."
          ::= { docsBpi2CmtsAuthEntry 12 }

     docsBpi2CmtsAuthCmInvalids   OBJECT-TYPE
          SYNTAX   Counter32
          MAX-ACCESS   read-only
          STATUS   current

             DESCRIPTION
                 "The value of this object is the number of times the
             CMTS has transmitted an Authorization Invalid message to
             this CM.
             Discontinuities in the value of this counter can occur at
             re-initialization of the management system, and at other
             times as indicated by the value of
             ifCounterDiscontinuityTime."
             REFERENCE
                 "DOCSIS Baseline Privacy Plus Interface Specification,
             Section 4.2.1.7."
             ::= { docsBpi2CmtsAuthEntry 13 }

         docsBpi2CmtsAuthRejectErrorCode   OBJECT-TYPE
             SYNTAX   INTEGER {
                               none(1),
                               unknown(2),
                               unauthorizedCm(3),
                               unauthorizedSaid(4),
                               permanentAuthorizationFailure(8),
                               timeOfDayNotAcquired(11)
                               }
             MAX-ACCESS   read-only
             STATUS   current
             DESCRIPTION
                 "The value of this object is the enumerated
             description of the Error-Code in the most recent
             Authorization Reject message transmitted to the CM. This has
             the value unknown(2) if the last Error-Code value was 0 and
             none(1) if no Authorization Reject message has been
             transmitted to the CM since entry creation."
             REFERENCE
                 "DOCSIS Baseline Privacy Plus Interface Specification,
             Sections 4.2.1.3 and 4.2.2.15."
             ::= { docsBpi2CmtsAuthEntry 14 }

         docsBpi2CmtsAuthRejectErrorString OBJECT-TYPE
             SYNTAX   SnmpAdminString (SIZE (0..128))
             MAX-ACCESS   read-only
             STATUS   current
             DESCRIPTION
                 "The value of this object is the text string in the
             most recent Authorization Reject message transmitted to the
             CM. This is a zero length string if no Authorization
             Reject message has been transmitted to the CM since entry
             creation."
             REFERENCE
                 "DOCSIS Baseline Privacy Plus Interface Specification,

            Sections 4.2.1.3 and 4.2.2.6."
            ::= { docsBpi2CmtsAuthEntry 15 }

        docsBpi2CmtsAuthInvalidErrorCode   OBJECT-TYPE
            SYNTAX   INTEGER {
                                none(1),
                                unknown(2),
                                unauthorizedCm(3),
                                unsolicited(5),
                                invalidKeySequence(6),
                                keyRequestAuthenticationFailure(7)
                                }
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the enumerated
            description of the Error-Code in the most recent
            Authorization Invalid message transmitted to the CM. This
            has the value unknown(2) if the last Error-Code value was 0
            and none(1) if no Authorization Invalid message has been
            transmitted to the CM since entry creation."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Sections 4.2.1.7 and 4.2.2.15."
            ::= { docsBpi2CmtsAuthEntry 16 }

        docsBpi2CmtsAuthInvalidErrorString OBJECT-TYPE
            SYNTAX   SnmpAdminString (SIZE (0..128))
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the text string in the
            most recent Authorization Invalid message transmitted to
            the CM. This is a zero length string if no Authorization
            Invalid message has been transmitted to the CM since entry
            creation."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Sections 4.2.1.7 and 4.2.2.6."
            ::= { docsBpi2CmtsAuthEntry 17 }

        docsBpi2CmtsAuthPrimarySAId   OBJECT-TYPE
            SYNTAX   DocsSAIdOrZero
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the Primary Security
            Association identifier. For BPI mode, the value must be

                any unicast SID."
            REFERENCE
                 "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 2.1.3."
            ::= { docsBpi2CmtsAuthEntry 18 }

        docsBpi2CmtsAuthBpkmCmCertValid   OBJECT-TYPE
            SYNTAX   INTEGER {
                            unknown (0),
                            validCmChained (1),
                            validCmTrusted (2),
                            invalidCmUntrusted (3),
                            invalidCAUntrusted (4),
                            invalidCmOther (5),
                            invalidCAOther (6)
                            }
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                 "Contains the reason why a CM's certificate is deemed
            valid or invalid.
            Return unknown(0) if the CM is running BPI mode.
            ValidCmChained(1) means the certificate is valid
                because it chains to a valid certificate.
            ValidCmTrusted(2) means the certificate is valid
                because it has been provisioned (in the
                docsBpi2CmtsProvisionedCmCert table) to be trusted.
            InvalidCmUntrusted(3) means the certificate is invalid
                because it has been provisioned (in the
                docsBpi2CmtsProvisionedCmCert table) to be untrusted.
            InvalidCAUntrusted(4) means the certificate is invalid
                because it chains to an untrusted certificate.
            InvalidCmOther(5) and InvalidCAOther(6) refer to
                errors in parsing, validity periods, etc., which are
                attributable to the CM certificate or its chain,
                respectively; additional information may be found
                in docsBpi2AuthRejectErrorString for these types
                of errors."
            REFERENCE
                 "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 9.4.2."
            ::= { docsBpi2CmtsAuthEntry 19 }

        docsBpi2CmtsAuthBpkmCmCert   OBJECT-TYPE
            SYNTAX   DocsX509ASN1DEREncodedCertificate
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION

                "The X509 CM Certificate sent as part of a BPKM
          Authorization Request.
          Note: The zero-length OCTET STRING must be returned if the
          Entire certificate is not retained in the CMTS."
          REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 9.2."
          ::= { docsBpi2CmtsAuthEntry 20 }

     docsBpi2CmtsAuthCACertIndexPtr   OBJECT-TYPE
          SYNTAX   Unsigned32 (0..4294967295)
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
                "A row index into docsBpi2CmtsCACertTable.
                 Returns the index in docsBpi2CmtsCACertTable to which
                 CA certificate this CM is chained to. A value of
                 0 means it could not be found or not applicable."
          REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 9.2."
          ::= { docsBpi2CmtsAuthEntry 21 }

     --
     -- The CMTS TEK Table, indexed by ifIndex and SAID
     --

     docsBpi2CmtsTEKTable   OBJECT-TYPE
          SYNTAX   SEQUENCE OF   DocsBpi2CmtsTEKEntry
          MAX-ACCESS   not-accessible
          STATUS   current
          DESCRIPTION
                "This table describes the attributes of each
          Traffic Encryption Key (TEK) association. The CMTS
          Maintains one TEK association per SAID on each CMTS MAC
          interface."
          ::= { docsBpi2CmtsObjects 3 }

     docsBpi2CmtsTEKEntry   OBJECT-TYPE
          SYNTAX   DocsBpi2CmtsTEKEntry
          MAX-ACCESS   not-accessible
          STATUS   current
          DESCRIPTION
                "Each entry contains objects describing attributes of
          one TEK association on a particular CMTS MAC interface. The
          CMTS MUST create one entry per SAID per MAC interface,
          based on the receipt of a Key Request message, and MUST not
          delete the entry before the CM authorization for the SAID

```
        permanently expires."
        INDEX     { ifIndex, docsBpi2CmtsTEKSAId }
        ::= { docsBpi2CmtsTEKTable 1 }

DocsBpi2CmtsTEKEntry ::= SEQUENCE {
    docsBpi2CmtsTEKSAId                 DocsSAId,
    docsBpi2CmtsTEKSAType               DocsBpkmSAType,
    docsBpi2CmtsTEKDataEncryptAlg       DocsBpkmDataEncryptAlg,
    docsBpi2CmtsTEKDataAuthentAlg       DocsBpkmDataAuthentAlg,
    docsBpi2CmtsTEKLifetime             Integer32,
    docsBpi2CmtsTEKKeySequenceNumber    Integer32,
    docsBpi2CmtsTEKExpiresOld           DateAndTime,
    docsBpi2CmtsTEKExpiresNew           DateAndTime,
    docsBpi2CmtsTEKReset                TruthValue,
    docsBpi2CmtsKeyRequests             Counter32,
    docsBpi2CmtsKeyReplies              Counter32,
    docsBpi2CmtsKeyRejects              Counter32,
    docsBpi2CmtsTEKInvalids             Counter32,
    docsBpi2CmtsKeyRejectErrorCode      INTEGER,
    docsBpi2CmtsKeyRejectErrorString    SnmpAdminString,
    docsBpi2CmtsTEKInvalidErrorCode     INTEGER,
    docsBpi2CmtsTEKInvalidErrorString   SnmpAdminString
}

docsBpi2CmtsTEKSAId OBJECT-TYPE
    SYNTAX          DocsSAId
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "The value of this object is the DOCSIS Security
    Association ID (SAID)."
    REFERENCE
        "DOCSIS Baseline Privacy Plus Interface Specification,
    Section 4.2.2.12."
    ::= { docsBpi2CmtsTEKEntry 1 }

docsBpi2CmtsTEKSAType    OBJECT-TYPE
    SYNTAX          DocsBpkmSAType
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The value of this object is the type of security
    association.  'dynamic' does not apply to CMs running in
    BPI mode.  Unicast BPI TEKs must utilize the 'primary'
    encoding, and multicast BPI TEKs must utilize the 'static'
    encoding."
    REFERENCE
        "DOCSIS Baseline Privacy Plus Interface Specification,
```

```
            Section 2.1.3."
            ::= { docsBpi2CmtsTEKEntry 2 }

     docsBpi2CmtsTEKDataEncryptAlg OBJECT-TYPE
            SYNTAX     DocsBpkmDataEncryptAlg
            MAX-ACCESS      read-only
            STATUS          current
            DESCRIPTION
                "The value of this object is the data encryption
            algorithm for this SAID."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.2.20."
            ::= { docsBpi2CmtsTEKEntry 3 }

     docsBpi2CmtsTEKDataAuthentAlg OBJECT-TYPE
            SYNTAX     DocsBpkmDataAuthentAlg
            MAX-ACCESS      read-only
            STATUS          current
            DESCRIPTION
                "The value of this object is the data authentication
            algorithm for this SAID."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.2.20."
            ::= { docsBpi2CmtsTEKEntry 4 }

     docsBpi2CmtsTEKLifetime  OBJECT-TYPE
            SYNTAX          Integer32 (1..604800)
            UNITS           "seconds"
            MAX-ACCESS      read-write
            STATUS          current
            DESCRIPTION
                "The value of this object is the lifetime, in
            seconds, that the CMTS assigns to keys for this TEK
            association."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 4.2.1.5 and Appendix A.2."
            ::= { docsBpi2CmtsTEKEntry 5 }


     docsBpi2CmtsTEKKeySequenceNumber   OBJECT-TYPE
            SYNTAX             Integer32 (0..15)
            MAX-ACCESS         read-only
            STATUS             current
            DESCRIPTION
                "The value of this object is the most recent TEK
```

          key sequence number for this SAID."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Sections 4.2.2.10 and 4.2.2.13."
          ::= { docsBpi2CmtsTEKEntry 6 }

     docsBpi2CmtsTEKExpiresOld   OBJECT-TYPE
          SYNTAX   DateAndTime
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
               "The value of this object is the actual clock time
          for expiration of the immediate predecessor of the most
          recent TEK for this FSM. If this FSM has only one TEK, then
          the value is the time of activation of this FSM."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Sections 4.2.1.5 and 4.2.2.9."
          ::= { docsBpi2CmtsTEKEntry 7 }

     docsBpi2CmtsTEKExpiresNew   OBJECT-TYPE
          SYNTAX   DateAndTime
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
               "The value of this object is the actual clock time
          for expiration of the most recent TEK for this FSM."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Sections 4.2.1.5 and 4.2.2.9."
          ::= { docsBpi2CmtsTEKEntry 8 }

     docsBpi2CmtsTEKReset   OBJECT-TYPE
          SYNTAX   TruthValue
          MAX-ACCESS   read-write
          STATUS   current
          DESCRIPTION
               "Setting this object to 'true' causes the CMTS to
          invalidate all currently active TEKs and to generate new
          TEKs for the associated SAID; the CMTS MAY also generate
          unsolicited TEK Invalid messages, to optimize the TEK
          synchronization between the CMTS and the CM(s). Reading
          this object always returns FALSE."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.1.3.3.5."
          ::= { docsBpi2CmtsTEKEntry 9 }

```
     docsBpi2CmtsKeyRequests  OBJECT-TYPE
         SYNTAX          Counter32
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the number of times the
         CMTS has received a Key Request message.
         Discontinuities in the value of this counter can occur at
         re-initialization of the management system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Section 4.2.1.4."
         ::= { docsBpi2CmtsTEKEntry 10 }

     docsBpi2CmtsKeyReplies  OBJECT-TYPE
         SYNTAX          Counter32
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the number of times the
         CMTS has transmitted a Key Reply message.
         Discontinuities in the value of this counter can occur at
         re-initialization of the management system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Section 4.2.1.5."
         ::= { docsBpi2CmtsTEKEntry 11 }

     docsBpi2CmtsKeyRejects  OBJECT-TYPE
         SYNTAX          Counter32
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the number of times the
         CMTS has transmitted a Key Reject message.
         Discontinuities in the value of this counter can occur at
         re-initialization of the management system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Section 4.2.1.6."
         ::= { docsBpi2CmtsTEKEntry 12 }
```

```
     docsBpi2CmtsTEKInvalids  OBJECT-TYPE
         SYNTAX          Counter32
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the number of times the
         CMTS has transmitted a TEK Invalid message.
         Discontinuities in the value of this counter can occur at
         re-initialization of the management system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Section 4.2.1.8."
         ::= { docsBpi2CmtsTEKEntry 13 }

     docsBpi2CmtsKeyRejectErrorCode     OBJECT-TYPE
         SYNTAX          INTEGER {
                             none(1),
                             unknown(2),
                             unauthorizedSaid(4)
                             }
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the enumerated
         description of the Error-Code in the most recent Key Reject
         message sent in response to a Key Request for this SAID.
         This has the value unknown(2) if the last Error-Code value
         was 0 and none(1) if no Key Reject message has been
         received since registration."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
         Sections 4.2.1.6 and 4.2.2.15."
         ::= { docsBpi2CmtsTEKEntry 14 }

    docsBpi2CmtsKeyRejectErrorString   OBJECT-TYPE
         SYNTAX          SnmpAdminString (SIZE (0..128))
         MAX-ACCESS      read-only
         STATUS          current
         DESCRIPTION
             "The value of this object is the text string in
         the most recent Key Reject message sent in response to a
         Key Request for this SAID.  This is a zero length string if
         no Key Reject message has been received since
         registration."
         REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
```

```
        Sections 4.2.1.6 and 4.2.2.6."
        ::= { docsBpi2CmtsTEKEntry 15 }

   docsBpi2CmtsTEKInvalidErrorCode     OBJECT-TYPE
        SYNTAX           INTEGER {
                            none(1),
                            unknown(2),
                            invalidKeySequence(6)
                            }
        MAX-ACCESS        read-only
        STATUS            current
        DESCRIPTION
            "The value of this object is the enumerated
        description of the Error-Code in the most recent TEK
        Invalid message sent in association with this SAID.  This
        has the value unknown(2) if the last Error-Code value was 0
        and none(1) if no TEK Invalid message has been received
        since registration."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.2.1.8 and 4.2.2.15."
        ::= { docsBpi2CmtsTEKEntry 16 }

   docsBpi2CmtsTEKInvalidErrorString  OBJECT-TYPE
        SYNTAX           SnmpAdminString (SIZE (0..128))
        MAX-ACCESS       read-only
        STATUS           current
        DESCRIPTION
            "The value of this object is the text string in
        the most recent TEK Invalid message sent in association
        with this SAID.  This is a zero length string if no TEK
        Invalid message has been received since registration."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Sections 4.2.1.8 and 4.2.2.6."
        ::= { docsBpi2CmtsTEKEntry 17 }

   --
   -- The CMTS Multicast Objects Group
   --

   docsBpi2CmtsMulticastObjects OBJECT IDENTIFIER
        ::= { docsBpi2CmtsObjects 4 }

   --
   -- The CMTS IP Multicast Mapping Table, indexed by
   -- docsBpi2CmtsIpMulticastIndex, and by ifIndex
   --
```

```
     docsBpi2CmtsIpMulticastMapTable        OBJECT-TYPE
         SYNTAX          SEQUENCE OF DocsBpi2CmtsIpMulticastMapEntry
         MAX-ACCESS      not-accessible
         STATUS          current
         DESCRIPTION
             "This table maps multicast IP addresses to SAIDs.
         If a multicast IP address is mapped by multiple rows
         in the table, the row with the lowest
         docsBpi2CmtsIpMulticastIndex must be utilized for the
         mapping."
         ::= { docsBpi2CmtsMulticastObjects 1 }

     docsBpi2CmtsIpMulticastMapEntry        OBJECT-TYPE
         SYNTAX          DocsBpi2CmtsIpMulticastMapEntry
         MAX-ACCESS      not-accessible
         STATUS          current
         DESCRIPTION
             "Each entry contains objects describing the mapping of
         a set of multicast IP address and the mask to one SAID
         associated to a CMTS MAC Interface, as well as associated
         message counters and error information."
         INDEX     { ifIndex, docsBpi2CmtsIpMulticastIndex }
         ::= { docsBpi2CmtsIpMulticastMapTable 1 }

     DocsBpi2CmtsIpMulticastMapEntry ::= SEQUENCE {
         docsBpi2CmtsIpMulticastIndex         Unsigned32,
         docsBpi2CmtsIpMulticastAddressType   InetAddressType,
         docsBpi2CmtsIpMulticastAddress       InetAddress,
         docsBpi2CmtsIpMulticastMask          InetAddress,
         docsBpi2CmtsIpMulticastSAId          DocsSAIdOrZero,
         docsBpi2CmtsIpMulticastSAType        DocsBpkmSAType,
         docsBpi2CmtsIpMulticastDataEncryptAlg
                                         DocsBpkmDataEncryptAlg,
         docsBpi2CmtsIpMulticastDataAuthentAlg
                                         DocsBpkmDataAuthentAlg,
         docsBpi2CmtsIpMulticastSAMapRequests   Counter32,
         docsBpi2CmtsIpMulticastSAMapReplies    Counter32,
         docsBpi2CmtsIpMulticastSAMapRejects    Counter32,
         docsBpi2CmtsIpMulticastSAMapRejectErrorCode
                                              INTEGER,
         docsBpi2CmtsIpMulticastSAMapRejectErrorString
                                              SnmpAdminString,
         docsBpi2CmtsIpMulticastMapControl      RowStatus,
         docsBpi2CmtsIpMulticastMapStorageType  StorageType
         }

     docsBpi2CmtsIpMulticastIndex        OBJECT-TYPE
         SYNTAX          Unsigned32 (1..4294967295)
```

```
        MAX-ACCESS     not-accessible
        STATUS         current
        DESCRIPTION
             "The index of this row.  Conceptual rows having the
        value 'permanent' need not allow write-access to any
        columnar objects in the row."
        ::= { docsBpi2CmtsIpMulticastMapEntry 1 }

    docsBpi2CmtsIpMulticastAddressType OBJECT-TYPE
        SYNTAX         InetAddressType
        MAX-ACCESS     read-create
        STATUS         current
        DESCRIPTION
             "The type of Internet address for
        docsBpi2CmtsIpMulticastAddress
        and docsBpi2CmtsIpMulticastMask."
        DEFVAL { ipv4 }
        ::= { docsBpi2CmtsIpMulticastMapEntry 2 }

    docsBpi2CmtsIpMulticastAddress         OBJECT-TYPE
        SYNTAX         InetAddress
        MAX-ACCESS     read-create
        STATUS         current
        DESCRIPTION
             "This object represents the IP multicast address
        to be mapped, in conjunction with
        docsBpi2CmtsIpMulticastMask.  The type of this address is
        determined by the value of the object
        docsBpi2CmtsIpMulticastAddressType."
        ::= { docsBpi2CmtsIpMulticastMapEntry 3 }

    docsBpi2CmtsIpMulticastMask       OBJECT-TYPE
        SYNTAX         InetAddress
        MAX-ACCESS     read-create
        STATUS         current
        DESCRIPTION
             "This object represents the IP multicast address mask
        for this row.
        An IP multicast address matches this row if the logical
        AND of the address with docsBpi2CmtsIpMulticastMask is
        identical to the logical AND of
        docsBpi2CmtsIpMulticastAddr with
        docsBpi2CmtsIpMulticastMask.  The type of this address is
        determined by the value of the object
        docsBpi2CmtsIpMulticastAddressType.
        Note: For IPv6, this object need not represent a
        contiguous netmask; e.g., to associate a SAID to a
        multicast group matching 'any' multicast scope.  The TC
```

                InetAddressPrefixLength is not used, as it only
                represents contiguous netmask."
                ::= { docsBpi2CmtsIpMulticastMapEntry 4 }

        docsBpi2CmtsIpMulticastSAId   OBJECT-TYPE
                SYNTAX   DocsSAIdOrZero
                MAX-ACCESS   read-create
                STATUS   current
                DESCRIPTION
                    "This object represents the multicast SAID to be
                used in this IP multicast address mapping entry."
                ::= { docsBpi2CmtsIpMulticastMapEntry 5 }

        docsBpi2CmtsIpMulticastSAType OBJECT-TYPE
                SYNTAX   DocsBpkmSAType
                MAX-ACCESS   read-create
                STATUS   current
                DESCRIPTION
                    "The value of this object is the type of security
                association. 'dynamic' does not apply to CMs running in
                BPI mode. Unicast BPI TEKs must utilize the 'primary'
                encoding, and multicast BPI TEKs must utilize the 'static'
                encoding. By default, SNMP created entries set this object
                to 'static' if not set at row creation."
                REFERENCE
                    "DOCSIS Baseline Privacy Plus Interface Specification,
                Section 2.1.3."
                ::= { docsBpi2CmtsIpMulticastMapEntry 6 }

        docsBpi2CmtsIpMulticastDataEncryptAlg   OBJECT-TYPE
                SYNTAX   DocsBpkmDataEncryptAlg
                MAX-ACCESS   read-create
                STATUS   current
                DESCRIPTION
                    "The value of this object is the data encryption
                algorithm for this IP."
                REFERENCE
                    "DOCSIS Baseline Privacy Plus Interface Specification,
                Section 4.2.2.20."
                DEFVAL { des56CbcMode }
                ::= { docsBpi2CmtsIpMulticastMapEntry 7 }

        docsBpi2CmtsIpMulticastDataAuthentAlg   OBJECT-TYPE
                SYNTAX   DocsBpkmDataAuthentAlg
                MAX-ACCESS   read-create
                STATUS   current
                DESCRIPTION
                    "The value of this object is the data authentication

          algorithm for this IP."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.2.20."
          DEFVAL { none }
          ::= { docsBpi2CmtsIpMulticastMapEntry 8 }

     docsBpi2CmtsIpMulticastSAMapRequests   OBJECT-TYPE
          SYNTAX   Counter32
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
              "The value of this object is the number of times the
          CMTS has received an SA Map Request message for this IP.
          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other
          times as indicated by the value of
          ifCounterDiscontinuityTime."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.1.10."
          ::= { docsBpi2CmtsIpMulticastMapEntry 9 }

     docsBpi2CmtsIpMulticastSAMapReplies   OBJECT-TYPE
          SYNTAX   Counter32
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
              "The value of this object is the number of times the
          CMTS has transmitted an SA Map Reply message for this IP.
          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other
          times as indicated by the value of
          ifCounterDiscontinuityTime."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.1.11."
          ::= { docsBpi2CmtsIpMulticastMapEntry 10 }

     docsBpi2CmtsIpMulticastSAMapRejects   OBJECT-TYPE
          SYNTAX   Counter32
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
              "The value of this object is the number of times the
          CMTS has transmitted an SA Map Reject message for this IP.
          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other

          times as indicated by the value of
          ifCounterDiscontinuityTime."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 4.2.1.12."
          ::= { docsBpi2CmtsIpMulticastMapEntry 11 }

     docsBpi2CmtsIpMulticastSAMapRejectErrorCode OBJECT-TYPE
          SYNTAX   INTEGER {
                               none(1),
                               unknown(2),
                               noAuthForRequestedDSFlow(9),
                               dsFlowNotMappedToSA(10)
                               }
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
               "The value of this object is the enumerated
          description of the Error-Code in the most recent SA Map
          Reject message sent in response to an SA Map Request for
          this IP. It has the value unknown(2) if the last Error-Code
          Value was 0 and none(1) if no SA MAP Reject message has
          been received since entry creation."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Sections 4.2.1.12 and 4.2.2.15."
          ::= { docsBpi2CmtsIpMulticastMapEntry 12 }

     docsBpi2CmtsIpMulticastSAMapRejectErrorString   OBJECT-TYPE
          SYNTAX   SnmpAdminString (SIZE (0..128))
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
               "The value of this object is the text string in
          the most recent SA Map Reject message sent in response to
          an SA Map Request for this IP. It is a zero length string
          if no SA Map Reject message has been received since entry
          creation."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Sections 4.2.1.12 and 4.2.2.6."
          ::= { docsBpi2CmtsIpMulticastMapEntry 13 }

     docsBpi2CmtsIpMulticastMapControl OBJECT-TYPE
          SYNTAX   RowStatus
          MAX-ACCESS   read-create
          STATUS   current
          DESCRIPTION

```
        "This object controls and reflects the IP multicast
   address mapping entry.  There is no restriction on the
   ability to change values in this row while the row is
   active.
   A created row can be set to active only after the
   Corresponding instances of docsBpi2CmtsIpMulticastAddress,
   docsBpi2CmtsIpMulticastMask, docsBpi2CmtsIpMulticastSAId,
   and docsBpi2CmtsIpMulticastSAType have all been set."
   ::= { docsBpi2CmtsIpMulticastMapEntry 14 }

docsBpi2CmtsIpMulticastMapStorageType    OBJECT-TYPE
   SYNTAX          StorageType
   MAX-ACCESS      read-only
   STATUS          current
   DESCRIPTION
        "The storage type for this conceptual row.
   Conceptual rows having the value 'permanent' need not allow
   write-access to any columnar objects in the row."
   ::= { docsBpi2CmtsIpMulticastMapEntry 15 }


--
-- The CMTS Multicast SAID Authorization Table,
-- indexed by ifIndex by
-- multicast SAID by CM MAC address
--

docsBpi2CmtsMulticastAuthTable           OBJECT-TYPE
   SYNTAX          SEQUENCE OF DocsBpi2CmtsMulticastAuthEntry
   MAX-ACCESS      not-accessible
   STATUS          current
   DESCRIPTION
        "This table describes the multicast SAID
   authorization for each CM on each CMTS MAC interface."
   ::= { docsBpi2CmtsMulticastObjects 2 }

docsBpi2CmtsMulticastAuthEntry           OBJECT-TYPE
   SYNTAX          DocsBpi2CmtsMulticastAuthEntry
   MAX-ACCESS      not-accessible
   STATUS          current
   DESCRIPTION
        "Each entry contains objects describing the key
   authorization of one cable modem for one multicast SAID
   for one CMTS MAC interface.
   Row entries persist after re-initialization of
   the managed system."
   INDEX     { ifIndex, docsBpi2CmtsMulticastAuthSAId,
         docsBpi2CmtsMulticastAuthCmMacAddress }
   ::= { docsBpi2CmtsMulticastAuthTable 1 }
```

```
     DocsBpi2CmtsMulticastAuthEntry ::= SEQUENCE
          {
          docsBpi2CmtsMulticastAuthSAId              DocsSAId,
          docsBpi2CmtsMulticastAuthCmMacAddress      MacAddress,
          docsBpi2CmtsMulticastAuthControl           RowStatus
          }

     docsBpi2CmtsMulticastAuthSAId OBJECT-TYPE
          SYNTAX          DocsSAId
          MAX-ACCESS      not-accessible
          STATUS          current
          DESCRIPTION
               "This object represents the multicast SAID for
          authorization."
          ::= { docsBpi2CmtsMulticastAuthEntry 1 }

     docsBpi2CmtsMulticastAuthCmMacAddress    OBJECT-TYPE
          SYNTAX          MacAddress
          MAX-ACCESS      not-accessible
          STATUS          current
          DESCRIPTION
               "This object represents the MAC address of the CM
          to which the multicast SAID authorization applies."
          ::= { docsBpi2CmtsMulticastAuthEntry 2 }

     docsBpi2CmtsMulticastAuthControl    OBJECT-TYPE
          SYNTAX          RowStatus
          MAX-ACCESS      read-create
          STATUS          current
          DESCRIPTION
               "The status of this conceptual row for the
          authorization of multicast SAIDs to CMs."
          ::= { docsBpi2CmtsMulticastAuthEntry 3 }

     --
     -- CMTS Cert Objects
     --

     docsBpi2CmtsCertObjects OBJECT IDENTIFIER
          ::= { docsBpi2CmtsObjects 5 }


     --
     -- CMTS Provisioned CM Cert Table
     --

     docsBpi2CmtsProvisionedCmCertTable OBJECT-TYPE
          SYNTAX          SEQUENCE OF
                            DocsBpi2CmtsProvisionedCmCertEntry
```

```
        MAX-ACCESS      not-accessible
        STATUS          current
        DESCRIPTION
            "A table of CM certificate trust entries provisioned
        to the CMTS.  The trust object for a certificate in this
        table has an overriding effect on the validity object of a
        certificate in the authorization table, as long as the
        entire contents of the two certificates are identical."
        ::= { docsBpi2CmtsCertObjects 1 }

    docsBpi2CmtsProvisionedCmCertEntry OBJECT-TYPE
        SYNTAX          DocsBpi2CmtsProvisionedCmCertEntry
        MAX-ACCESS      not-accessible
        STATUS          current
        DESCRIPTION
            "An entry in the CMTS's provisioned CM certificate
        table.  Row entries persist after re-initialization of
        the managed system."
        REFERENCE
            "Data-Over-Cable Service Interface Specifications:
        Operations Support System Interface Specification
        SP-OSSIv2.0-I05-040407, Section 6.2.14"
        INDEX { docsBpi2CmtsProvisionedCmCertMacAddress }
        ::= { docsBpi2CmtsProvisionedCmCertTable 1 }

    DocsBpi2CmtsProvisionedCmCertEntry ::= SEQUENCE
        {
        docsBpi2CmtsProvisionedCmCertMacAddress MacAddress,
        docsBpi2CmtsProvisionedCmCertTrust      INTEGER,
        docsBpi2CmtsProvisionedCmCertSource     INTEGER,
        docsBpi2CmtsProvisionedCmCertStatus     RowStatus,
        docsBpi2CmtsProvisionedCmCert
                            DocsX509ASN1DEREncodedCertificate
        }

    docsBpi2CmtsProvisionedCmCertMacAddress OBJECT-TYPE
        SYNTAX          MacAddress
        MAX-ACCESS      not-accessible
        STATUS          current
        DESCRIPTION
            "The index of this row."
        ::= { docsBpi2CmtsProvisionedCmCertEntry 1 }

    docsBpi2CmtsProvisionedCmCertTrust      OBJECT-TYPE
        SYNTAX     INTEGER {
                        trusted(1),
                        untrusted(2)
                        }
```

```
        MAX-ACCESS      read-create
        STATUS     current
        DESCRIPTION
            "Trust state for the provisioned CM certificate entry.
        Note: Setting this object need only override the validity
        of CM certificates sent in future authorization requests;
        instantaneous effect need not occur."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.4.1."
        DEFVAL { untrusted }
        ::= { docsBpi2CmtsProvisionedCmCertEntry 2 }

    docsBpi2CmtsProvisionedCmCertSource      OBJECT-TYPE
        SYNTAX     INTEGER {
                            snmp(1),
                            configurationFile(2),
                            externalDatabase(3),
                            other(4)
                            }
        MAX-ACCESS read-only
        STATUS   current
        DESCRIPTION
            "This object indicates how the certificate reached the
        CMTS.  Other(4) means that it originated from a source not
        identified above."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.4.1."
        ::= { docsBpi2CmtsProvisionedCmCertEntry 3 }

    docsBpi2CmtsProvisionedCmCertStatus OBJECT-TYPE
        SYNTAX   RowStatus
        MAX-ACCESS read-create
        STATUS   current
        DESCRIPTION
            "The status of this conceptual row.  Values in this row
        cannot be changed while the row is 'active'."
        ::= { docsBpi2CmtsProvisionedCmCertEntry 4 }

    docsBpi2CmtsProvisionedCmCert OBJECT-TYPE
        SYNTAX          DocsX509ASN1DEREncodedCertificate
        MAX-ACCESS      read-create
        STATUS          current
        DESCRIPTION
            "An X509 DER-encoded Certificate Authority
        certificate.
        Note: The zero-length OCTET STRING must be returned, on
```

```
        reads, if the entire certificate is not retained in the
        CMTS."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.2."
        ::= { docsBpi2CmtsProvisionedCmCertEntry 5 }

   --
   -- CMTS CA Cert Table
   --

   docsBpi2CmtsCACertTable OBJECT-TYPE
        SYNTAX          SEQUENCE OF DocsBpi2CmtsCACertEntry
        MAX-ACCESS      not-accessible
        STATUS          current
        DESCRIPTION
             "The table of known Certificate Authority certificates
        acquired by this device."
        ::= { docsBpi2CmtsCertObjects 2 }

   docsBpi2CmtsCACertEntry OBJECT-TYPE
        SYNTAX          DocsBpi2CmtsCACertEntry
        MAX-ACCESS      not-accessible
        STATUS          current
        DESCRIPTION
             "A row in the Certificate Authority certificate
        table.  Row entries with the trust status 'trusted',
        'untrusted', or 'root' persist after re-initialization
         of the managed system."
        REFERENCE
             "Data-Over-Cable Service Interface Specifications:
        Operations Support System Interface Specification
        SP-OSSIv2.0-I05-040407, Section 6.2.14"
        INDEX   { docsBpi2CmtsCACertIndex }
        ::= {docsBpi2CmtsCACertTable 1 }

   DocsBpi2CmtsCACertEntry ::= SEQUENCE {
        docsBpi2CmtsCACertIndex            Unsigned32,
        docsBpi2CmtsCACertSubject          SnmpAdminString,
        docsBpi2CmtsCACertIssuer           SnmpAdminString,
        docsBpi2CmtsCACertSerialNumber     OCTET STRING,
        docsBpi2CmtsCACertTrust            INTEGER,
        docsBpi2CmtsCACertSource           INTEGER,
        docsBpi2CmtsCACertStatus           RowStatus,
        docsBpi2CmtsCACert
                             DocsX509ASN1DEREncodedCertificate,
        docsBpi2CmtsCACertThumbprint       OCTET STRING
        }
```

        docsBpi2CmtsCACertIndex OBJECT-TYPE
            SYNTAX   Unsigned32 (1.. 4294967295)
            MAX-ACCESS   not-accessible
            STATUS   current
            DESCRIPTION
                "The index for this row."
            ::= { docsBpi2CmtsCACertEntry 1 }

        docsBpi2CmtsCACertSubject OBJECT-TYPE
            SYNTAX   SnmpAdminString
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The subject name exactly as it is encoded in the
            X509 certificate.
            The organizationName portion of the certificate's subject
            name must be present. All other fields are optional. Any
            optional field present must be prepended with <CR>
            (carriage return, U+000D) <LF> (line feed, U+000A).
            Ordering of fields present must conform to the following:

            organizationName <CR> <LF>
            countryName <CR> <LF>
            stateOrProvinceName <CR> <LF>
            localityName <CR> <LF>
            organizationalUnitName <CR> <LF>
            organizationalUnitName=<Manufacturing Location> <CR> <LF>
            commonName"
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section 9.2.4"
            ::= { docsBpi2CmtsCACertEntry 2 }

        docsBpi2CmtsCACertIssuer OBJECT-TYPE
            SYNTAX   SnmpAdminString
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The issuer name exactly as it is encoded in the
            X509 certificate.
            The commonName portion of the certificate's issuer
            name must be present. All other fields are optional. Any
            optional field present must be prepended with <CR>
            (carriage return, U+000D) <LF> (line feed, U+000A).
            Ordering of fields present must conform to the following:

            CommonName <CR><LF>
            countryName <CR><LF>

```
        stateOrProvinceName <CR><LF>
        localityName <CR><LF>
        organizationName <CR><LF>
        organizationalUnitName <CR><LF>
        organizationalUnitName=<Manufacturing Location>"
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.2.4"
        ::= { docsBpi2CmtsCACertEntry 3 }

    docsBpi2CmtsCACertSerialNumber OBJECT-TYPE
        SYNTAX          OCTET STRING (SIZE (1..32))
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
             "This CA certificate's serial number, represented as
        an octet string."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.2.2"
        ::= { docsBpi2CmtsCACertEntry 4 }

    docsBpi2CmtsCACertTrust OBJECT-TYPE
        SYNTAX     INTEGER {
                         trusted (1),
                         untrusted (2),
                         chained (3),
                         root (4)
                         }
        MAX-ACCESS      read-create
        STATUS     current
        DESCRIPTION
             "This object controls the trust status of this
        certificate.  Root certificates must be given root(4)
        trust; manufacturer certificates must not be given root(4)
        trust.  Trust on root certificates must not change.
        Note: Setting this object need only affect the validity of
        CM certificates sent in future authorization requests;
        instantaneous effect need not occur."
        REFERENCE
             "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.4.1"
        DEFVAL { chained }
        ::= { docsBpi2CmtsCACertEntry 5 }

    docsBpi2CmtsCACertSource OBJECT-TYPE
        SYNTAX     INTEGER {
                snmp (1),
```

```
                    configurationFile (2),
                    externalDatabase (3),
                    other (4),
                    authentInfo (5),
                    compiledIntoCode (6)
                    }
        MAX-ACCESS     read-only
        STATUS     current
        DESCRIPTION
              "This object indicates how the certificate reached
        the CMTS.  Other(4) means that it originated from a source
        not identified above."
        REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
        Section 9.4.1"
        ::= { docsBpi2CmtsCACertEntry 6 }

    docsBpi2CmtsCACertStatus OBJECT-TYPE
        SYNTAX         RowStatus
        MAX-ACCESS     read-create
        STATUS         current
        DESCRIPTION
              "The status of this conceptual row.  An attempt
        to set writable columnar values while this row is active
        behaves as follows:
        - Sets to the object docsBpi2CmtsCACertTrust are allowed.
        - Sets to the object docsBpi2CmtsCACert will return an
          error of 'inconsistentValue'.
        A newly created entry cannot be set to active until the
        value of docsBpi2CmtsCACert is being set."
        ::= { docsBpi2CmtsCACertEntry 7 }

    docsBpi2CmtsCACert  OBJECT-TYPE
        SYNTAX         DocsX509ASN1DEREncodedCertificate
        MAX-ACCESS     read-create
        STATUS         current
        DESCRIPTION
              "An X509 DER-encoded Certificate Authority
        certificate.
        To help identify certificates, either this object or
        docsBpi2CmtsCACertThumbprint must be returned by a CMTS for
        self-signed CA certificates.

        Note: The zero-length OCTET STRING must be returned, on
        reads, if the entire certificate is not retained in the
        CMTS."
        REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
```

          Section 9.2."
          ::= { docsBpi2CmtsCACertEntry 8 }

     docsBpi2CmtsCACertThumbprint OBJECT-TYPE
          SYNTAX   OCTET STRING (SIZE (20))
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
               "The SHA-1 hash of a CA certificate.
          To help identify certificates, either this object or
          docsBpi2CmtsCACert must be returned by a CMTS for
          self-signed CA certificates.

          Note: The zero-length OCTET STRING must be returned, on
          reads, if the CA certificate thumb print is not retained
          in the CMTS."
          REFERENCE
               "DOCSIS Baseline Privacy Plus Interface Specification,
          Section 9.4.3"
          ::= { docsBpi2CmtsCACertEntry 9 }

     --
     -- Authenticated Software Download Objects
     --

     --
     -- Note: the authenticated software download objects are a
     -- CM requirement only.
     --

     docsBpi2CodeDownloadControl OBJECT IDENTIFIER
          ::= { docsBpi2MIBObjects 4 }

     docsBpi2CodeDownloadStatusCode   OBJECT-TYPE
          SYNTAX   INTEGER {
                          configFileCvcVerified (1),
                          configFileCvcRejected (2),
                          snmpCvcVerified (3),
                          snmpCvcRejected (4),
                          codeFileVerified (5),
                          codeFileRejected (6),
                          other (7)
                          }
          MAX-ACCESS   read-only
          STATUS   current
          DESCRIPTION
               "The value indicates the result of the latest config
          file CVC verification, SNMP CVC verification, or code file

                verification."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Sections D.3.3.2 and D.3.5.1."
            ::= { docsBpi2CodeDownloadControl 1 }

        docsBpi2CodeDownloadStatusString   OBJECT-TYPE
            SYNTAX   SnmpAdminString
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object indicates the additional
            information to the status code. The value will include
            the error code and error description, which will be defined
            separately."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section D.3.7"
            ::= { docsBpi2CodeDownloadControl 2 }

        docsBpi2CodeMfgOrgName   OBJECT-TYPE
            SYNTAX   SnmpAdminString
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the device manufacturer's
            organizationName."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section D.3.2.2."
            ::= { docsBpi2CodeDownloadControl 3 }

        docsBpi2CodeMfgCodeAccessStart   OBJECT-TYPE
            SYNTAX   DateAndTime (SIZE(11))
            MAX-ACCESS   read-only
            STATUS   current
            DESCRIPTION
                "The value of this object is the device manufacturer's
            current codeAccessStart value. This value will always
            refer to Greenwich Mean Time (GMT), and the value
            format must contain TimeZone information (fields 8-10)."
            REFERENCE
                "DOCSIS Baseline Privacy Plus Interface Specification,
            Section D.3.2.2."
            ::= { docsBpi2CodeDownloadControl 4 }

        docsBpi2CodeMfgCvcAccessStart OBJECT-TYPE
            SYNTAX   DateAndTime (SIZE(11))

```
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the device manufacturer's
        current cvcAccessStart value.  This value will always
        refer to Greenwich Mean Time (GMT), and the value
        format must contain TimeZone information (fields 8-10)."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section D.3.2.2."
        ::= { docsBpi2CodeDownloadControl 5 }

    docsBpi2CodeCoSignerOrgName   OBJECT-TYPE
        SYNTAX          SnmpAdminString
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the co-signer's
        organizationName.  The value is a zero length string if
        the co-signer is not specified."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section D.3.2.2."
        ::= { docsBpi2CodeDownloadControl 6 }

    docsBpi2CodeCoSignerCodeAccessStart     OBJECT-TYPE
        SYNTAX          DateAndTime (SIZE(11))
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the co-signer's current
        codeAccessStart value.  This value will always refer to
        Greenwich Mean Time (GMT), and the value format must contain
        TimeZone information (fields 8-10).
        If docsBpi2CodeCoSignerOrgName is a zero
        length string, the value of this object is meaningless."
        REFERENCE
            "DOCSIS Baseline Privacy Plus Interface Specification,
        Section D.3.2.2."
        ::= { docsBpi2CodeDownloadControl 7 }

    docsBpi2CodeCoSignerCvcAccessStart OBJECT-TYPE
        SYNTAX          DateAndTime (SIZE(11))
        MAX-ACCESS      read-only
        STATUS          current
        DESCRIPTION
            "The value of this object is the co-signer's current
        cvcAccessStart value.  This value will always refer to
```

          Greenwich Mean Time (GMT), and the value format must contain
          TimeZone information (fields 8-10).
          If docsBpi2CodeCoSignerOrgName is a zero
          length string, the value of this object is meaningless."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section D.3.2.2."
          ::= { docsBpi2CodeDownloadControl 8 }

      docsBpi2CodeCvcUpdate   OBJECT-TYPE
          SYNTAX   DocsX509ASN1DEREncodedCertificate
          MAX-ACCESS   read-write
          STATUS   current
          DESCRIPTION
              "Setting a CVC to this object triggers the device
          to verify the CVC and update the cvcAccessStart values.
          The content of this object is then discarded.
          If the device is not enabled to upgrade codefiles, or if
          the CVC verification fails, the CVC will be rejected.
          Reading this object always returns the zero-length OCTET
          STRING."
          REFERENCE
              "DOCSIS Baseline Privacy Plus Interface Specification,
          Section D.3.3.2.2."
          ::= { docsBpi2CodeDownloadControl 9 }

      --
      -- The BPI+ MIB Conformance Statements (with a placeholder for
      -- notifications)
      --

      docsBpi2Notification   OBJECT IDENTIFIER
          ::= { docsBpi2MIB 0 }
      docsBpi2Conformance OBJECT IDENTIFIER
          ::= { docsBpi2MIB 2 }
      docsBpi2Compliances OBJECT IDENTIFIER
          ::= { docsBpi2Conformance 1 }
      docsBpi2Groups   OBJECT IDENTIFIER
          ::= { docsBpi2Conformance 2 }

      docsBpi2CmCompliance MODULE-COMPLIANCE
          STATUS   current
          DESCRIPTION
              "This is the compliance statement for CMs that
          implement the DOCSIS Baseline Privacy Interface Plus."

          MODULE -- docsBpi2MIB

```
            -- unconditionally mandatory group
            MANDATORY-GROUPS {
                    docsBpi2CmGroup,
                    docsBpi2CodeDownloadGroup
            }

        -- constrain on Encryption algorithms
        OBJECT docsBpi2CmTEKDataEncryptAlg
            SYNTAX    DocsBpkmDataEncryptAlg {
                                none(0),
                                des56CbcMode(1),
                                des40CbcMode(2)
                    }
            DESCRIPTION
                "It is compliant to support des56CbcMode(1) and
            des40CbcMode(2) for data encryption algorithms."

        -- constrain on Integrity algorithms
        OBJECT docsBpi2CmTEKDataAuthentAlg
            SYNTAX    DocsBpkmDataAuthentAlg {
                                none(0)
                    }
            DESCRIPTION
                "It is compliant to not support data message
            authentication algorithms."

        -- constrain on IP addressing
        OBJECT    docsBpi2CmIpMulticastAddressType
            SYNTAX InetAddressType { ipv4(1) }
            DESCRIPTION
                "An implementation is only required to support IPv4
            addresses.  Support for other address types may be defined
            in future versions of this MIB module."

        -- constrain on IP addressing
        OBJECT    docsBpi2CmIpMulticastAddress
            SYNTAX  InetAddress (SIZE(4))
            DESCRIPTION
                "An implementation is only required to support IPv4
            addresses Other address types support may be defined in
            future versions of this MIB module."

        -- constrain on Encryption algorithms
        OBJECT docsBpi2CmCryptoSuiteDataEncryptAlg
            SYNTAX    DocsBpkmDataEncryptAlg {
                                none(0),
                                des56CbcMode(1),
                                des40CbcMode(2)
```

```
                    }
            DESCRIPTION
                "It is compliant to only support des56CbcMode(1)
            and des40CbcMode(2) for data encryption algorithms."

        -- constrain on Integrity algorithms
        OBJECT docsBpi2CmCryptoSuiteDataAuthentAlg
            SYNTAX    DocsBpkmDataAuthentAlg {
                                none(0)
                    }
            DESCRIPTION
                "It is compliant to not support data message
            authentication algorithms."

        ::= { docsBpi2Compliances 1 }


        docsBpi2CmtsCompliance MODULE-COMPLIANCE
            STATUS          current
            DESCRIPTION
                "This is the compliance statement for CMTSs that
            implement the DOCSIS Baseline Privacy Interface Plus."

            MODULE  -- docsBpi2MIB
            -- unconditionally mandatory group
            MANDATORY-GROUPS {
                    docsBpi2CmtsGroup
            }

        -- unconditionally optional group
        GROUP     docsBpi2CodeDownloadGroup
            DESCRIPTION
                "This group is optional for CMTSes.  The implementation
            decision of this group is left to the vendor"

        -- constrain on mandatory range

        OBJECT    docsBpi2CmtsDefaultAuthLifetime
            SYNTAX    Integer32 (86400..6048000)
            DESCRIPTION
                "The refined range corresponds to the minimum and
            maximum values in operational networks."

        -- constrain on mandatory range

        OBJECT    docsBpi2CmtsDefaultTEKLifetime
            SYNTAX    Integer32 (1800..604800)
            DESCRIPTION
```

              "The refined range corresponds to the minimum and
          maximum values in operational networks."

     -- constrain on mandatory range

     OBJECT   docsBpi2CmtsAuthCmLifetime
         SYNTAX   Integer32 (86400..6048000)
         DESCRIPTION
              "The refined range corresponds to the minimum and
          maximum values in operational networks."

     -- constrain on Encryption algorithms

   OBJECT   docsBpi2CmtsTEKDataEncryptAlg
         SYNTAX   DocsBpkmDataEncryptAlg {
                            none(0),
                            des56CbcMode(1),
                            des40CbcMode(2)
                }
         DESCRIPTION
              "It is compliant to only support des56CbcMode(1)
          and des40CbcMode(2) for data encryption."

     -- constrain on Integrity algorithms

   OBJECT docsBpi2CmtsTEKDataAuthentAlg
         SYNTAX   DocsBpkmDataAuthentAlg {
                            none(0)
                }
         DESCRIPTION
              "It is compliant to not support data message
          authentication algorithms."

     -- constrain on mandatory range

     OBJECT   docsBpi2CmtsTEKLifetime
         SYNTAX   Integer32 (1800..604800)
         DESCRIPTION
              "The refined range corresponds to the minimum and
          maximum values in operational networks."

     -- constrain on access
     -- constrain on IP Addressing

     OBJECT   docsBpi2CmtsIpMulticastAddressType
         SYNTAX   InetAddressType { ipv4(1) }
         MIN-ACCESS read-only
         DESCRIPTION

```
                "Write access is not required.
            An implementation is only required to support IPv4
            addresses.  Support for other address types may be defined
            in future versions of this MIB module."

        OBJECT    docsBpi2CmtsIpMulticastAddress
            SYNTAX  InetAddress (SIZE(4))
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required.
            An implementation is only required to support IPv4
            addresses.  Support for other address types may be defined
            in future versions of this MIB module."

        OBJECT    docsBpi2CmtsIpMulticastMask
            SYNTAX  InetAddress (SIZE(4))
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required.
            An implementation is only required to support IPv4
            addresses.  Support for other address types may be defined
            in future versions of this MIB module."

        -- constrain on access

        OBJECT    docsBpi2CmtsIpMulticastSAId
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

        OBJECT    docsBpi2CmtsIpMulticastSAType
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

        -- constrain on access
        -- constrain on Encryption algorithms

        OBJECT    docsBpi2CmtsIpMulticastDataEncryptAlg
            SYNTAX    DocsBpkmDataEncryptAlg {
                              none(0),
                              des56CbcMode(1),
                              des40CbcMode(2)
                      }
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required.
            It is compliant to only support des56CbcMode(1)
```

```
        and des40CbcMode(2) for data encryption"

    -- constrain on access
    -- constrain on Integrity algorithms

    OBJECT    docsBpi2CmtsIpMulticastDataAuthentAlg
        SYNTAX    DocsBpkmDataAuthentAlg {
                            none(0)
                }
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required.
        It is compliant to not support data message
        authentication algorithms."

    -- constrain on access

    OBJECT    docsBpi2CmtsMulticastAuthControl
        MIN-ACCESS  read-only
        DESCRIPTION
        "Write access is not required."

        ::= { docsBpi2Compliances 2 }

    docsBpi2CmGroup      OBJECT-GROUP
        OBJECTS    {
            docsBpi2CmPrivacyEnable,
            docsBpi2CmPublicKey,
            docsBpi2CmAuthState,
            docsBpi2CmAuthKeySequenceNumber,
            docsBpi2CmAuthExpiresOld,
            docsBpi2CmAuthExpiresNew,
            docsBpi2CmAuthReset,
            docsBpi2CmAuthGraceTime,
            docsBpi2CmTEKGraceTime,
            docsBpi2CmAuthWaitTimeout,
            docsBpi2CmReauthWaitTimeout,
            docsBpi2CmOpWaitTimeout,
            docsBpi2CmRekeyWaitTimeout,
            docsBpi2CmAuthRejectWaitTimeout,
            docsBpi2CmSAMapWaitTimeout,
            docsBpi2CmSAMapMaxRetries,
            docsBpi2CmAuthentInfos,
            docsBpi2CmAuthRequests,
            docsBpi2CmAuthReplies,
            docsBpi2CmAuthRejects,
            docsBpi2CmAuthInvalids,
            docsBpi2CmAuthRejectErrorCode,
```

```
                docsBpi2CmAuthRejectErrorString,
                docsBpi2CmAuthInvalidErrorCode,
                docsBpi2CmAuthInvalidErrorString,
                docsBpi2CmTEKSAType,
                docsBpi2CmTEKDataEncryptAlg,
                docsBpi2CmTEKDataAuthentAlg,
                docsBpi2CmTEKState,
                docsBpi2CmTEKKeySequenceNumber,
                docsBpi2CmTEKExpiresOld,
                docsBpi2CmTEKExpiresNew,
                docsBpi2CmTEKKeyRequests,
                docsBpi2CmTEKKeyReplies,
                docsBpi2CmTEKKeyRejects,
                docsBpi2CmTEKInvalids,
                docsBpi2CmTEKAuthPends,
                docsBpi2CmTEKKeyRejectErrorCode,
                docsBpi2CmTEKKeyRejectErrorString,
                docsBpi2CmTEKInvalidErrorCode,
                docsBpi2CmTEKInvalidErrorString,
                docsBpi2CmIpMulticastAddressType,
                docsBpi2CmIpMulticastAddress,
                docsBpi2CmIpMulticastSAId,
                docsBpi2CmIpMulticastSAMapState,
                docsBpi2CmIpMulticastSAMapRequests,
                docsBpi2CmIpMulticastSAMapReplies,
                docsBpi2CmIpMulticastSAMapRejects,
                docsBpi2CmIpMulticastSAMapRejectErrorCode,
                docsBpi2CmIpMulticastSAMapRejectErrorString,
                docsBpi2CmDeviceCmCert,
                docsBpi2CmDeviceManufCert,
                docsBpi2CmCryptoSuiteDataEncryptAlg,
                docsBpi2CmCryptoSuiteDataAuthentAlg
                }
         STATUS          current
         DESCRIPTION
             "This collection of objects provides CM BPI+ status
         and control."
     ::= { docsBpi2Groups 1 }

     docsBpi2CmtsGroup   OBJECT-GROUP
         OBJECTS {
                docsBpi2CmtsDefaultAuthLifetime,
                docsBpi2CmtsDefaultTEKLifetime,
                docsBpi2CmtsDefaultSelfSignedManufCertTrust,
                docsBpi2CmtsCheckCertValidityPeriods,
                docsBpi2CmtsAuthentInfos,
                docsBpi2CmtsAuthRequests,
                docsBpi2CmtsAuthReplies,
```

                    docsBpi2CmtsAuthRejects,
                    docsBpi2CmtsAuthInvalids,
                    docsBpi2CmtsSAMapRequests,
                    docsBpi2CmtsSAMapReplies,
                    docsBpi2CmtsSAMapRejects,
                    docsBpi2CmtsAuthCmBpiVersion,
                    docsBpi2CmtsAuthCmPublicKey,
                    docsBpi2CmtsAuthCmKeySequenceNumber,
                    docsBpi2CmtsAuthCmExpiresOld,
                    docsBpi2CmtsAuthCmExpiresNew,
                    docsBpi2CmtsAuthCmLifetime,
                    docsBpi2CmtsAuthCmReset,
                    docsBpi2CmtsAuthCmInfos,
                    docsBpi2CmtsAuthCmRequests,
                    docsBpi2CmtsAuthCmReplies,
                    docsBpi2CmtsAuthCmRejects,
                    docsBpi2CmtsAuthCmInvalids,
                    docsBpi2CmtsAuthRejectErrorCode,
                    docsBpi2CmtsAuthRejectErrorString,
                    docsBpi2CmtsAuthInvalidErrorCode,
                    docsBpi2CmtsAuthInvalidErrorString,
                    docsBpi2CmtsAuthPrimarySAId,
                    docsBpi2CmtsAuthBpkmCmCertValid,
                    docsBpi2CmtsAuthBpkmCmCert,
                    docsBpi2CmtsAuthCACertIndexPtr,
                    docsBpi2CmtsTEKSAType,
                    docsBpi2CmtsTEKDataEncryptAlg,
                    docsBpi2CmtsTEKDataAuthentAlg,
                    docsBpi2CmtsTEKLifetime,
                    docsBpi2CmtsTEKKeySequenceNumber,
                    docsBpi2CmtsTEKExpiresOld,
                    docsBpi2CmtsTEKExpiresNew,
                    docsBpi2CmtsTEKReset,
                    docsBpi2CmtsKeyRequests,
                    docsBpi2CmtsKeyReplies,
                    docsBpi2CmtsKeyRejects,
                    docsBpi2CmtsTEKInvalids,
                    docsBpi2CmtsKeyRejectErrorCode,
                    docsBpi2CmtsKeyRejectErrorString,
                    docsBpi2CmtsTEKInvalidErrorCode,
                    docsBpi2CmtsTEKInvalidErrorString,
                    docsBpi2CmtsIpMulticastAddressType,
                    docsBpi2CmtsIpMulticastAddress,
                    docsBpi2CmtsIpMulticastMask,
                    docsBpi2CmtsIpMulticastSAId,
                    docsBpi2CmtsIpMulticastSAType,
                    docsBpi2CmtsIpMulticastDataEncryptAlg,
                    docsBpi2CmtsIpMulticastDataAuthentAlg,

```
            docsBpi2CmtsIpMulticastSAMapRequests,
            docsBpi2CmtsIpMulticastSAMapReplies,
            docsBpi2CmtsIpMulticastSAMapRejects,
            docsBpi2CmtsIpMulticastSAMapRejectErrorCode,
            docsBpi2CmtsIpMulticastSAMapRejectErrorString,
            docsBpi2CmtsIpMulticastMapControl,
            docsBpi2CmtsIpMulticastMapStorageType,
            docsBpi2CmtsMulticastAuthControl,
            docsBpi2CmtsProvisionedCmCertTrust,
            docsBpi2CmtsProvisionedCmCertSource,
            docsBpi2CmtsProvisionedCmCertStatus,
            docsBpi2CmtsProvisionedCmCert,
            docsBpi2CmtsCACertSubject,
            docsBpi2CmtsCACertIssuer,
            docsBpi2CmtsCACertSerialNumber,
            docsBpi2CmtsCACertTrust,
            docsBpi2CmtsCACertSource,
            docsBpi2CmtsCACertStatus,
            docsBpi2CmtsCACert,
            docsBpi2CmtsCACertThumbprint
            }
        STATUS         current
        DESCRIPTION
            "This collection of objects provides CMTS BPI+ status
        and control."
    ::= { docsBpi2Groups 2 }

    docsBpi2CodeDownloadGroup OBJECT-GROUP
            OBJECTS {
            docsBpi2CodeDownloadStatusCode,
            docsBpi2CodeDownloadStatusString,
            docsBpi2CodeMfgOrgName,
            docsBpi2CodeMfgCodeAccessStart,
            docsBpi2CodeMfgCvcAccessStart,
            docsBpi2CodeCoSignerOrgName,
            docsBpi2CodeCoSignerCodeAccessStart,
            docsBpi2CodeCoSignerCvcAccessStart,
            docsBpi2CodeCvcUpdate
            }
        STATUS         current
        DESCRIPTION
            "This collection of objects provides authenticated
        software download support."
    ::= { docsBpi2Groups 3 }

    END
```

4. Acknowledgements

   Kaz Ozawa: Authenticated Software Download objects and general
            suggestions.

   Rich Woundy: BPI MIB and general MIB expertise.

   Mike St. Johns: BPI MIB and first version of BPI+ MIB.

   Bert Wijnen: Extensive comments in MIB syntax and accuracy.

   Thanks to Mike Sabin and Manson Wong for reviewing early BPI+ MIB
   drafts and to Jean-Francois Mule for contributing to the last
   versions.

5. Normative References

   [RFC2119]   Bradner, S., "Key words for use in RFCs to Indicate
                Requirement Levels", BCP 14, RFC 2119, March 1997.

   [RFC2578]   McCloghrie, K., Perkins, D., and J. Schoenwaelder,
                "Structure of Management Information Version 2 (SMIv2)",
                STD 58, RFC 2578, April 1999.

   [RFC2579]   McCloghrie, K., Perkins, D., and J. Schoenwaelder,
                "Textual Conventions for SMIv2", STD 58, RFC 2579, April
                1999.

   [RFC2580]   McCloghrie, K., Perkins, D., and J. Schoenwaelder,
                "Conformance Statements for SMIv2", STD 58, RFC 2580,
                April 1999.

   [RFC3411]   Harrington, D., Presuhn, R., and B. Wijnen, "An
                Architecture for Describing Simple Network Management
                Protocol (SNMP) Management Frameworks", STD 62, RFC
                3411, December 2002.

   [RFC4001]   Daniele, M., Haberman, B., Routhier, S., and J.
                Schoenwaelder, "Textual Conventions for Internet Network
                Addresses", RFC 4001, February 2005.

   [RFC2863]   McCloghrie, K. and F. Kastenholz, "The Interfaces Group
                MIB", RFC 2863, June 2000.

   [RFC2670]   St. Johns, M., "Radio Frequency (RF) Interface
                  Management Information Base for MCNS/DOCSIS compliant RF
                  interfaces", RFC 2670, August 1999.

   [DOCSIS]   "Data-Over-Cable Service Interface Specifications:
                  Baseline Privacy Plus Interface Specification SP-BPI+-
                  I11-040407", DOCSIS, April 2004, available at
                  http://www.cablemodem.com.
                  http://www.cablelabs.com/specifications/archives.

6. Informative References

   [RFC3083]   Woundy, R., "Baseline Privacy Interface Management
                  Information Base for DOCSIS Compliant Cable Modems and
                  Cable Modem Termination Systems", RFC 3083, March 2001.

   [RFC3410]   Case, J., Mundy, R., Partain, D., and B. Stewart,
                  "Introduction and Applicability Statements for
                  Internet-Standard Management Framework", RFC 3410,
                  December 2002.

   [RFC3513]   Hinden, R. and S. Deering, "Internet Protocol Version 6
                  (IPv6) Addressing Architecture", RFC 3513, April 2003.

   [DOCSIS-1.0] "Data-Over-Cable Service Interface Specifications:
                  DOCSIS 1.0 Baseline Privacy Interface (BPI) ANSI/SCTE
                  22-2 2202, Available at http://www.scte.org.

   [DOCSIS-1.1] "Data-Over-Cable Service Interface Specifications:
                  Operations Support System Interface Specification SP-
                  OSSIv1.1-I07-030730", DOCSIS 1.1 July 2003, available at
                  http://www.cablemodem.com.
                  http://www.cablelabs.com/specifications/archives.

   [DOCSIS-2.0] "Data-Over-Cable Service Interface Specifications:
                  Operations Support System Interface Specification SP-
                  OSSIv2.0-I05-040407", DOCSIS 2.0 April 2004,
                  http://www.cablemodem.com.
                  http://www.cablelabs.com/specifications/archives.

   [IANA]   "Protocol Numbers and Assignment Services", IANA,
                  http://www.iana.org/assignments/ianaiftype-mib.

7. Security Considerations

   There are a number of management objects defined in this MIB module
   with a MAX-ACCESS clause of read-write and/or read-create. Such
   objects may be considered sensitive or vulnerable in some network
   environments. The support for SET operations in a non-secure
   environment without proper protection can have a negative effect on
   network operations. These are the tables and objects and their
   sensitivity/vulnerability:

   - The following objects, if SNMP SET maliciously, could constitute
     denial of service or theft of service attacks or compromise the
     intended data privacy of users:

   Objects related to the Baseline Privacy Key Management (BPKM)

      docsBpi2CmAuthReset,
      docsBpi2CmtsAuthCmReset,
      docsBpi2CmtsTEKReset:
          These objects are used for initiating a re-key process. A
          malicious massive SET attack may cause CMTS processing
          overload and may compromise the service.

      docsBpi2CmtsDefaultAuthLifetime,
      docsBpi2CmtsDefaultTEKLifetime,
      docsBpi2CmtsAuthCmLifetime,
      docsBpi2CmtsTEKLifetime:
          To minimize the risk of malicious or unintended short periods
          of time when key updates may lead to degradation or denial of
          service, implementers are encouraged to follow these objects'
          range constraints, as defined in the docsBpi2CmtsCompliance
          MODULE-COMPLIANCE clause for operational deployments.

      docsBpi2CmtsDefaultSelfSignedManufCertTrust:
          A malicious SET in a self-signed certificate as reject
          message, which may constitute denial of service. This object
          is designed for testing purposes; therefore, it is not
          RECOMMENDED for use in commercial deployments [DOCSIS].
          Administrators can make use of View-based Access Control
          (VACM) introduced in section 7.9 of [RFC3410] to restrict
          write access to this object.

      docsBpi2CmtsCheckCertValidityPeriods:
          A malicious SET in this object that enables the period
          validity and a wrong clock time in the CMTS could cause denial
          of service, as CM authorization requests will be rejected.

      For more details in the validation of CM certificates, refer to
      section 9 of [DOCSIS] .

   Objects related to the CM only:

      Objects in docsBpi2CmDeviceCertTable

      docsBpi2CmDeviceCmCert:
         This object is not harmful, considering that a CM received a
         Certificate during the manufacturing process. Therefore, the
         object access becomes read-only. See the object DESCRIPTION
         clause in section 3 for details.

      Objects for Secure Software Download in table
      docsBpi2CodeDownloadControl:

      docsBpi2CodeCvcUpdate:
         A malicious SET on this object may not constitute a risk,
         since the CM holds the DOCSIS root key to verify the CVC
         authenticity. The operator, if configured, could receive a
         notification for event occurrences, which may lead to
         detecting the source of the attack. Moreover, [DOCSIS]
         recommends that CMs CVC be regularly updated to minimize the
         risk of potential code-signing keys being compromised (e.g.,
         by configuration file).

      Objects related to the CMTS only:

      Objects in docsBpi2CmtsProvisionedCmCertTable and
      docsBpi2CmtsCACertTable containing CM Certificates and Certificate
      Authority information, respectively:

      docsBpi2CmtsProvisionedCmCertTrust,
      docsBpi2CmtsProvisionedCmCertStatus,
      docsBpi2CmtsProvisionedCmCert,
      docsBpi2CmtsCACertStatus,
      docsBpi2CmtsCACert:
         A malicious SET on these objects may constitute a denial of
         service attack that will be experienced after the CMs perform
         authorization requests. It does not affect CMs in the
         authorized state.

      Objects in multicast tables docsBpi2CmtsIpMulticastMapTable and
      docsBpi2CmtsMulticastAuthTable:

      docsBpi2CmtsIpMulticastAddressType,
      docsBpi2CmtsIpMulticastAddress,
      docsBpi2CmtsIpMulticastMaskType,

docsBpi2CmtsIpMulticastMask,
docsBpi2CmtsIpMulticastSAId,
docsBpi2CmtsIpMulticastSAType:
    Malicious SET on these objects may cause misconfiguration,
    causing interruption of the users' active multicast
    applications.

docsBpi2CmtsIpMulticastDataEncryptAlg,
docsBpi2CmtsIpMulticastDataAuthentAlg:
    Malicious SETs on these objects may create service
    misconfiguration, causing service interruption or theft of
    service if encryption algorithms are removed for the multicast
    groups.

docsBpi2CmtsIpMulticastMapControl,
docsBpi2CmtsMulticastAuthControl:
    Malicious SETs on these objects may remove and/or disable
    customers and/or multicast groups, causing service disruption.
    This may also constitute theft of service by authorizing non-
    subscribed users to multicast groups or by adding other
    multicast groups in the forward path.

Some of the readable objects in this MIB module (i.e., objects with a
MAX-ACCESS other than not-accessible) may be considered sensitive or
vulnerable in some network environments. It is thus important to
control even GET and/or NOTIFY access to these objects and possibly
to even encrypt the values of these objects when sending them over
the network via SNMP. These are the tables and objects and their
sensitivity/vulnerability:

Objects in docsBpi2CmBaseTable, docsBpi2CmTEKTable,
docsBpi2CmtsBaseTable, docsBpi2CmtsAuthTable,
docsBpi2CmtsTEKTable, docsBpi2CmtsProvisionedCmCertTable, and
docsBpi2CmtsCACertTable:
    If this information is accessible, attackers may use it to
    distinguish users configured to work without data encryption
    (e.g., docsBpi2CmPrivacyEnable) and to know current Baseline
    Privacy parameters in the network.

Objects in docsBpi2CmIpMulticastMapTable and
docsBpi2CmtsMulticastAuthTable:
    In addition to the vulnerabilities around BPI plus multicast
    objects described in the previous part, the read-only objects
    of this table may help attackers monitor the status of the
    intrusion.

        Objects in docsBpi2CodeDownloadControl:
            In addition to the vulnerability of the read-write object
            docsBpi2CodeCvcUpdate, attackers may be able to monitor the
            status of a denial of service using Secure Software Download.

   SNMP versions prior to SNMPv3 did not include adequate security.
   Even if the network itself is secure (for example by using IPSec),
   even then, there is no control as to who on the secure network is
   allowed to access and GET/SET (read/change/create/delete) the objects
   in this MIB module.

   It is RECOMMENDED that implementers consider the security features as
   provided by the SNMPv3 framework (see [RFC3410], section 8),
   including full support for the SNMPv3 cryptographic mechanisms (for
   authentication and privacy).

   Further, deployment of SNMP versions prior to SNMPv3 is NOT
   RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to
   enable cryptographic security. It is then a customer/operator
   responsibility to ensure that the SNMP entity giving access to an
   instance of this MIB module is properly configured to give access to
   the objects only to those principals (users) that have legitimate
   rights to indeed GET or SET (change/create/delete) them.

   BPI+ Encryption Algorithms:

   The BPI+ Traffic Encryption Keys (TEK) defined in the DOCSIS BPI+
   specification [DOCSIS] use 40-bit or 56-bit DES for encryption (DES
   CBC mode). Currently, there is no mechanism or algorithm defined for
   data integrity.

   Due to the DES cryptographic weaknesses, future revisions of the
   DOCSIS BPI+ specification should introduce more advanced encryption
   algorithms, as proposed in the DocsBpkmDataEncryptAlg textual
   convention, to overcome the progress in cheaper and faster hardware
   or software decryption tools. Future revisions of the DOCSIS BPI+
   specification [DOCSIS] should also adopt authentication algorithms,
   as described in the DocsBpkmDataAuthentAlg textual convention.

   It is important to note that frequent key changes do not necessarily
   help in mitigating or reducing the risks of a DES attack. Indeed,
   the traffic encryption keys, which are configured on a per cable
   modem basis and per BPI+ multicast group, can be utilized to decrypt
   old traffic, even when they are no longer in active use.

   Note that, not exempt to the same recommendations above, the CM BPI+
   authorization protocol uses triple DES encryption, which offers
   improved robustness in comparison to DES for CM authorization and TEK
   re-key management.

8. IANA Considerations

   The MIB module in this document uses the following IANA-assigned
   OBJECT IDENTIFIER value, recorded in the SMI Numbers registry:

      Descriptor   OBJECT IDENTIFIER Value
      ----------   -----------------------
      docsBpi2MIB   { mib-2 126 }

Authors' Addresses

   Stuart M. Green

   EMail: rubbersoul3@yahoo.com

   Kaz Ozawa
   Automotive Systems Development Center
   TOSHIBA CORPORATION
   1-1, Shibaura 1-Chome
   Minato-ku, Tokyo 105-8001
   Japan

   Phone: +81-3-3457-8569
   Fax: +81-3-5444-9325
   EMail: Kazuyoshi.Ozawa@toshiba.co.jp

   Alexander Katsnelson

   Phone: +1-303-680-3924
   EMail: katsnelson6@peoplepc.com

   Eduardo Cardona
   Cable Television Laboratories, Inc.
   858 Coal Creek Circle
   Louisville, CO 80027- 9750
   U.S.A.

   Phone: +1 303 661 9100
   EMail: e.cardona@cablelabs.com

Full Copyright Statement

   Copyright (C) The Internet Society (2005).

   This document is subject to the rights, licenses and restrictions
   contained in BCP 78, and except as set forth therein, the authors
   retain all their rights.

   This document and the information contained herein are provided on an
   "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS
   OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET
   ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED,
   INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE
   INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED
   WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

   The IETF takes no position regarding the validity or scope of any
   Intellectual Property Rights or other rights that might be claimed to
   pertain to the implementation or use of the technology described in
   this document or the extent to which any license under such rights
   might or might not be available; nor does it represent that it has
   made any independent effort to identify any such rights. Information
   on the procedures with respect to rights in RFC documents can be
   found in BCP 78 and BCP 79.

   Copies of IPR disclosures made to the IETF Secretariat and any
   assurances of licenses to be made available, or the result of an
   attempt made to obtain a general license or permission for the use of
   such proprietary rights by implementers or users of this
   specification can be obtained from the IETF on-line IPR repository at
   http://www.ietf.org/ipr.

   The IETF invites any interested party to bring to its attention any
   copyrights, patents or patent applications, or other proprietary
   rights that may cover technology that may be required to implement
   this standard. Please address the information to the IETF at ietf-
   ipr@ietf.org.

Acknowledgement

   Funding for the RFC Editor function is currently provided by the
   Internet Society.