           Definitions of Managed Objects for the Fourth Version of the
                Border Gateway Protocol (BGP-4) using SMIv2

Status of this Memo

   This document specifies an Internet standards track protocol for the
   Internet community, and requests discussion and suggestions for
   improvements. Please refer to the current edition of the "Internet
   Official Protocol Standards" (STD 1) for the standardization state
   and status of this protocol. Distribution of this memo is unlimited.

1. Introduction

   This memo defines a portion of the Management Information Base (MIB)
   for use with network management protocols in the Internet community.
   In particular, it describes managed objects used for managing the
   Border Gateway Protocol Version 4 or lower [1, 2].

2. The SNMPv2 Network Management Framework

   The SNMPv2 Network Management Framework consists of four major
   components. They are:

      RFC 1442 which defines the SMI, the mechanisms used for describing
      and naming objects for the purpose of management.

      STD 17, RFC 1213 defines MIB-II, the core set of managed objects
      forthe Internet suite of protocols.

      RFC 1445 which defines the administrative and other architectural
      aspects of the framework.

      RFC 1448 which defines the protocol used for network access to
      managed objects.

   The Framework permits new objects to be defined for the purpose of
   experimentation and evaluation.

3. Object Definitions

   Managed objects are accessed via a virtual information store, termed
   the Management Information Base or MIB. Objects in the MIB are
   defined using the subset of Abstract Syntax Notation One (ASN.1)
   defined in the SMI. In particular, each object type is named by an
   OBJECT IDENTIFIER, an administratively assigned name. The object
   type together with an object instance serves to uniquely identify a
   specific instantiation of the object. For human convenience, we
   often use a textual string, termed the descriptor, to refer to the
   object type.

4. Overview

   These objects are used to control and manage a BGP-4 implementation.

   Apart from a few system-wide scalar objects, this MIB is broken into
   three tables: the BGP Peer Table, the BGP Received Path Attribute
   Table, and the BGP-4 Received Path Attribute Table. The BGP Peer
   Table contains information about state and current activity of
   connections with the BGP peers. The Received Path Attribute Table
   contains path attributes received from all peers running BGP version
   3 or less. The BGP-4 Received Path Attribute Table contains path
   attributes received from all BGP-4 peers. The actual attributes used
   in determining a route are a subset of the received attribute tables
   after local routing policy has been applied.

5. Definitions

BGP4-MIB DEFINITIONS ::= BEGIN

                IMPORTS
                    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
                    IpAddress, Integer32, Counter32, Gauge32
                        FROM SNMPv2-SMI
                    mib-2
                        FROM RFC1213-MIB;

                bgp MODULE-IDENTITY
                    LAST-UPDATED "9405050000Z"
                    ORGANIZATION "IETF BGP Working Group"
                    CONTACT-INFO
                            "   John Chu (Editor)
                        Postal: IBM Corp.
                                P.O.Box 218
                                Yorktown Heights, NY 10598
                                US

```
                        Tel: +1 914 945 3156
                        Fax: +1 914 945 2141
                     E-mail: jychu@watson.ibm.com"
                 DESCRIPTION
                         "The MIB module for BGP-4."
             ::= { mib-2 15 }

         bgpVersion OBJECT-TYPE
             SYNTAX     OCTET STRING (SIZE (1..255))
             MAX-ACCESS read-only
             STATUS     current
             DESCRIPTION
                     "Vector of supported BGP protocol version
                     numbers.  Each peer negotiates the version
                     from this vector.  Versions are identified
                     via the string of bits contained within this
                     object.  The first octet contains bits 0 to
                     7, the second octet contains bits 8 to 15,
                     and so on, with the most significant bit
                     referring to the lowest bit number in the
                     octet (e.g., the MSB of the first octet
                     refers to bit 0).  If a bit, i, is present
                     and set, then the version (i+1) of the BGP
                     is supported."
             ::= { bgp 1 }

         bgpLocalAs OBJECT-TYPE
             SYNTAX     INTEGER (0..65535)
             MAX-ACCESS read-only
             STATUS     current
             DESCRIPTION
                     "The local autonomous system number."
             ::= { bgp 2 }




         -- BGP Peer table.  This table contains, one entry per
         -- BGP peer, information about the BGP peer.

         bgpPeerTable OBJECT-TYPE
             SYNTAX     SEQUENCE OF BgpPeerEntry
             MAX-ACCESS not-accessible
             STATUS     current
             DESCRIPTION
                     "BGP peer table.  This table contains,
                     one entry per BGP peer, information about
                     the connections with BGP peers."
             ::= { bgp 3 }
```

```
                    bgpPeerEntry OBJECT-TYPE
                        SYNTAX      BgpPeerEntry
                        MAX-ACCESS not-accessible
                        STATUS      current
                        DESCRIPTION
                               "Entry containing information about the
                                connection with a BGP peer."
                        INDEX { bgpPeerRemoteAddr }
                        ::= { bgpPeerTable 1 }

                    BgpPeerEntry ::= SEQUENCE {
                            bgpPeerIdentifier
                                IpAddress,
                            bgpPeerState
                                INTEGER,
                            bgpPeerAdminStatus
                                INTEGER,
                            bgpPeerNegotiatedVersion
                                Integer32,
                            bgpPeerLocalAddr
                                IpAddress,
                            bgpPeerLocalPort
                                INTEGER,
                            bgpPeerRemoteAddr
                                IpAddress,
                            bgpPeerRemotePort
                                INTEGER,
                            bgpPeerRemoteAs
                                INTEGER,
                            bgpPeerInUpdates
                                Counter32,
                            bgpPeerOutUpdates
                                Counter32,
                            bgpPeerInTotalMessages
                                Counter32,
                            bgpPeerOutTotalMessages
                                Counter32,
                            bgpPeerLastError
                                OCTET STRING,
                            bgpPeerFsmEstablishedTransitions
                                Counter32,
                            bgpPeerFsmEstablishedTime
                                Gauge32,
                            bgpPeerConnectRetryInterval
                                INTEGER,
                            bgpPeerHoldTime
                                INTEGER,
                            bgpPeerKeepAlive
```

```
                        INTEGER,
                    bgpPeerHoldTimeConfigured
                        INTEGER,
                    bgpPeerKeepAliveConfigured
                        INTEGER,
                    bgpPeerMinASOriginationInterval
                        INTEGER,
                    bgpPeerMinRouteAdvertisementInterval
                        INTEGER,
                    bgpPeerInUpdateElapsedTime
                        Gauge32
                    }

            bgpPeerIdentifier OBJECT-TYPE
                SYNTAX      IpAddress
                MAX-ACCESS read-only
                STATUS     current
                DESCRIPTION
                        "The BGP Identifier of this entry's BGP
                        peer."
                ::= { bgpPeerEntry 1 }

            bgpPeerState OBJECT-TYPE
                SYNTAX      INTEGER {
                                idle(1),
                                connect(2),
                                active(3),
                                opensent(4),
                                openconfirm(5),
                                established(6)
                        }
                MAX-ACCESS read-only
                STATUS     current
                DESCRIPTION
                        "The BGP peer connection state."
                ::= { bgpPeerEntry 2 }

            bgpPeerAdminStatus OBJECT-TYPE
                SYNTAX      INTEGER {
                                stop(1),
                                start(2)
                        }
                MAX-ACCESS read-write
                STATUS     current
                DESCRIPTION
                        "The desired state of the BGP connection.
                        A transition from 'stop' to 'start' will
                        cause the BGP Start Event to be generated.
```

                         A transition from 'start' to 'stop' will
                         cause the BGP Stop Event to be generated.
                         This parameter can be used to restart BGP
                         peer connections. Care should be used in
                         providing write access to this object
                         without adequate authentication."
                 ::= { bgpPeerEntry 3 }

         bgpPeerNegotiatedVersion OBJECT-TYPE
             SYNTAX   Integer32
             MAX-ACCESS read-only
             STATUS   current
             DESCRIPTION
                     "The negotiated version of BGP running
                     between the two peers."
             ::= { bgpPeerEntry 4 }

         bgpPeerLocalAddr OBJECT-TYPE
             SYNTAX   IpAddress
             MAX-ACCESS read-only
             STATUS   current
             DESCRIPTION
                     "The local IP address of this entry's BGP
                     connection."
             ::= { bgpPeerEntry 5 }

         bgpPeerLocalPort OBJECT-TYPE
             SYNTAX   INTEGER (0..65535)
             MAX-ACCESS read-only
             STATUS   current
             DESCRIPTION
                     "The local port for the TCP connection
                     between the BGP peers."
             ::= { bgpPeerEntry 6 }

         bgpPeerRemoteAddr OBJECT-TYPE
             SYNTAX   IpAddress
             MAX-ACCESS read-only
             STATUS   current
             DESCRIPTION
                     "The remote IP address of this entry's BGP
                     peer."
             ::= { bgpPeerEntry 7 }

         bgpPeerRemotePort OBJECT-TYPE
             SYNTAX   INTEGER (0..65535)
             MAX-ACCESS read-only
             STATUS   current

```
        DESCRIPTION
                "The remote port for the TCP connection
                between the BGP peers.  Note that the
                objects bgpPeerLocalAddr,
                bgpPeerLocalPort, bgpPeerRemoteAddr and
                bgpPeerRemotePort provide the appropriate
                reference to the standard MIB TCP
                connection table."
        ::= { bgpPeerEntry 8 }

    bgpPeerRemoteAs OBJECT-TYPE
        SYNTAX      INTEGER (0..65535)
        MAX-ACCESS read-only
        STATUS      current
        DESCRIPTION
                "The remote autonomous system number."
        ::= { bgpPeerEntry 9 }

    bgpPeerInUpdates OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS read-only
        STATUS      current
        DESCRIPTION
                "The number of BGP UPDATE messages
                received on this connection.  This object
                should be initialized to zero (0) when the
                connection is established."
        ::= { bgpPeerEntry 10 }

    bgpPeerOutUpdates OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS read-only
        STATUS      current
        DESCRIPTION
                "The number of BGP UPDATE messages
                transmitted on this connection.  This
                object should be initialized to zero (0)
                when the connection is established."
        ::= { bgpPeerEntry 11 }

    bgpPeerInTotalMessages OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS read-only
        STATUS      current
        DESCRIPTION
                "The total number of messages received
                from the remote peer on this connection.
                This object should be initialized to zero
```

                             when the connection is established."
                    ::= { bgpPeerEntry 12 }

            bgpPeerOutTotalMessages OBJECT-TYPE
                SYNTAX   Counter32
                MAX-ACCESS read-only
                STATUS   current
                DESCRIPTION
                        "The total number of messages transmitted to
                        the remote peer on this connection. This
                        object should be initialized to zero when
                        the connection is established."
                    ::= { bgpPeerEntry 13 }

            bgpPeerLastError OBJECT-TYPE
                SYNTAX   OCTET STRING (SIZE (2))
                MAX-ACCESS read-only
                STATUS   current
                DESCRIPTION
                        "The last error code and subcode seen by this
                        peer on this connection. If no error has
                        occurred, this field is zero. Otherwise, the
                        first byte of this two byte OCTET STRING
                        contains the error code, and the second byte
                        contains the subcode."
                    ::= { bgpPeerEntry 14 }

            bgpPeerFsmEstablishedTransitions OBJECT-TYPE
                SYNTAX   Counter32
                MAX-ACCESS read-only
                STATUS   current
                DESCRIPTION
                        "The total number of times the BGP FSM
                        transitioned into the established state."
                    ::= { bgpPeerEntry 15 }

            bgpPeerFsmEstablishedTime OBJECT-TYPE
                SYNTAX   Gauge32
                MAX-ACCESS read-only
                STATUS   current
                DESCRIPTION
                        "This timer indicates how long (in
                        seconds) this peer has been in the
                        Established state or how long
                        since this peer was last in the
                        Established state. It is set to zero when
                        a new peer is configured or the router is
                        booted."

```
                    ::= { bgpPeerEntry 16 }

            bgpPeerConnectRetryInterval OBJECT-TYPE
                SYNTAX      INTEGER (1..65535)
                MAX-ACCESS read-write
                STATUS      current
                DESCRIPTION
                        "Time interval in seconds for the
                        ConnectRetry timer.  The suggested value
                        for this timer is 120 seconds."
                ::= { bgpPeerEntry 17 }

            bgpPeerHoldTime OBJECT-TYPE
                SYNTAX      INTEGER  ( 0 | 3..65535 )
                MAX-ACCESS read-only
                STATUS      current
                DESCRIPTION
                        "Time interval in seconds for the Hold
                        Timer established with the peer.  The
                        value of this object is calculated by this
                        BGP speaker by using the smaller of the
                        value in bgpPeerHoldTimeConfigured and the
                        Hold Time received in the OPEN message.
                        This value must be at lease three seconds
                        if it is not zero (0) in which case the
                        Hold Timer has not been established with
                        the peer, or, the value of
                        bgpPeerHoldTimeConfigured is zero (0)."
                ::= { bgpPeerEntry 18 }

            bgpPeerKeepAlive OBJECT-TYPE
                SYNTAX      INTEGER ( 0 | 1..21845 )
                MAX-ACCESS read-only
                STATUS      current
                DESCRIPTION
                        "Time interval in seconds for the KeepAlive
                        timer established with the peer.  The value
                        of this object is calculated by this BGP
                        speaker such that, when compared with
                        bgpPeerHoldTime, it has the same
                        proportion as what
                        bgpPeerKeepAliveConfigured has when
                        compared with bgpPeerHoldTimeConfigured.
                        If the value of this object is zero (0),
                        it indicates that the KeepAlive timer has
                        not been established with the peer, or,
                        the value of bgpPeerKeepAliveConfigured is
                        zero (0)."
```

```
                    ::= { bgpPeerEntry 19 }

            bgpPeerHoldTimeConfigured OBJECT-TYPE
                SYNTAX     INTEGER ( 0 | 3..65535 )
                MAX-ACCESS read-write
                STATUS     current
                DESCRIPTION
                        "Time interval in seconds for the Hold Time
                        configured for this BGP speaker with this
                        peer.  This value is placed in an OPEN
                        message sent to this peer by this BGP
                        speaker, and is compared with the Hold
                        Time field in an OPEN message received
                        from the peer when determining the Hold
                        Time (bgpPeerHoldTime) with the peer.
                        This value must not be less than three
                        seconds if it is not zero (0) in which
                        case the Hold Time is NOT to be
                        established with the peer.  The suggested
                        value for this timer is 90 seconds."
                ::= { bgpPeerEntry 20 }

            bgpPeerKeepAliveConfigured OBJECT-TYPE
                SYNTAX     INTEGER ( 0 | 1..21845 )
                MAX-ACCESS read-write
                STATUS     current
                DESCRIPTION
                        "Time interval in seconds for the
                        KeepAlive timer configured for this BGP
                        speaker with this peer.  The value of this
                        object will only determine the
                        KEEPALIVE messages' frequency relative to
                        the value specified in
                        bgpPeerHoldTimeConfigured; the actual
                        time interval for the KEEPALIVE messages
                        is indicated by bgpPeerKeepAlive.  A
                        reasonable maximum value for this timer
                        would be configured to be one
                        third of that of
                        bgpPeerHoldTimeConfigured.
                        If the value of this object is zero (0),
                        no periodical KEEPALIVE messages are sent
                        to the peer after the BGP connection has
                        been established.  The suggested value for
                        this timer is 30 seconds."
                ::= { bgpPeerEntry 21 }
```

```
                  bgpPeerMinASOriginationInterval OBJECT-TYPE
                      SYNTAX     INTEGER (1..65535)
                      MAX-ACCESS read-write
                      STATUS     current
                      DESCRIPTION
                              "Time interval in seconds for the
                              MinASOriginationInterval timer.
                              The suggested value for this timer is 15
                              seconds."
                      ::= { bgpPeerEntry 22 }

                  bgpPeerMinRouteAdvertisementInterval OBJECT-TYPE
                      SYNTAX     INTEGER (1..65535)
                      MAX-ACCESS read-write
                      STATUS     current
                      DESCRIPTION
                              "Time interval in seconds for the
                              MinRouteAdvertisementInterval timer.
                              The suggested value for this timer is 30
                              seconds."
                      ::= { bgpPeerEntry 23 }

                  bgpPeerInUpdateElapsedTime OBJECT-TYPE
                      SYNTAX     Gauge32
                      MAX-ACCESS read-only
                      STATUS     current
                      DESCRIPTION
                              "Elapsed time in seconds since the last BGP
                              UPDATE message was received from the peer.
                              Each time bgpPeerInUpdates is incremented,
                              the value of this object is set to zero
                              (0)."
                      ::= { bgpPeerEntry 24 }



                  bgpIdentifier OBJECT-TYPE
                      SYNTAX     IpAddress
                      MAX-ACCESS read-only
                      STATUS     current
                      DESCRIPTION
                              "The BGP Identifier of local system."
                      ::= { bgp 4 }
```

```
                -- Received Path Attribute Table.  This table contains,
                -- one entry per path to a network, path attributes
                -- received from all peers running BGP version 3 or
                -- less.  This table is deprecated.

                bgpRcvdPathAttrTable OBJECT-TYPE
                    SYNTAX     SEQUENCE OF BgpPathAttrEntry
                    MAX-ACCESS not-accessible
                    STATUS     obsolete
                    DESCRIPTION
                            "The BGP Received Path Attribute Table
                            contains information about paths to
                            destination networks received from all
                            peers running BGP version 3 or less."
                    ::= { bgp 5 }

                bgpPathAttrEntry OBJECT-TYPE
                    SYNTAX     BgpPathAttrEntry
                    MAX-ACCESS not-accessible
                    STATUS     obsolete
                    DESCRIPTION
                            "Information about a path to a network."
                    INDEX { bgpPathAttrDestNetwork,
                            bgpPathAttrPeer        }
                    ::= { bgpRcvdPathAttrTable 1 }

                BgpPathAttrEntry ::= SEQUENCE {
                    bgpPathAttrPeer
                        IpAddress,
                    bgpPathAttrDestNetwork
                        IpAddress,
                    bgpPathAttrOrigin
                        INTEGER,
                    bgpPathAttrASPath
                        OCTET STRING,
                    bgpPathAttrNextHop
                        IpAddress,
                    bgpPathAttrInterASMetric
                        Integer32
                }

                bgpPathAttrPeer OBJECT-TYPE
                    SYNTAX     IpAddress
                    MAX-ACCESS read-only
                    STATUS     obsolete
                    DESCRIPTION
                            "The IP address of the peer where the path
                            information was learned."
```

```
                ::= { bgpPathAttrEntry 1 }

         bgpPathAttrDestNetwork OBJECT-TYPE
             SYNTAX      IpAddress
             MAX-ACCESS read-only
             STATUS      obsolete
             DESCRIPTION
                     "The address of the destination network."
             ::= { bgpPathAttrEntry 2 }

         bgpPathAttrOrigin OBJECT-TYPE
             SYNTAX      INTEGER {
                         igp(1),-- networks are interior
                         egp(2),-- networks learned via EGP
                         incomplete(3) -- undetermined
                     }
             MAX-ACCESS read-only
             STATUS      obsolete
             DESCRIPTION
                 "The ultimate origin of the path information."
             ::= { bgpPathAttrEntry 3 }

         bgpPathAttrASPath OBJECT-TYPE
             SYNTAX      OCTET STRING (SIZE (2..255))
             MAX-ACCESS read-only
             STATUS      obsolete
             DESCRIPTION
                     "The set of ASs that must be traversed to
                     reach the network.  This object is
                     probably best represented as SEQUENCE OF
                     INTEGER.  For SMI compatibility, though,
                     it is represented as OCTET STRING.  Each
                     AS is represented as a pair of octets
                     according to the following algorithm:

                         first-byte-of-pair = ASNumber / 256;
                         second-byte-of-pair = ASNumber & 255;"
             ::= { bgpPathAttrEntry 4 }

         bgpPathAttrNextHop OBJECT-TYPE
             SYNTAX      IpAddress
             MAX-ACCESS read-only
             STATUS      obsolete
             DESCRIPTION
                     "The address of the border router that
                     should be used for the destination
                     network."
             ::= { bgpPathAttrEntry 5 }
```

```
                   bgpPathAttrInterASMetric OBJECT-TYPE
                       SYNTAX     Integer32
                       MAX-ACCESS read-only
                       STATUS     obsolete
                       DESCRIPTION
                               "The optional inter-AS metric.  If this
                               attribute has not been provided for this
                               route, the value for this object is 0."
                       ::= { bgpPathAttrEntry 6 }



                   -- BGP-4 Received Path Attribute Table.  This table
                   -- contains, one entry per path to a network, path
                   -- attributes received from all peers running BGP-4.

                   bgp4PathAttrTable OBJECT-TYPE
                       SYNTAX     SEQUENCE OF Bgp4PathAttrEntry
                       MAX-ACCESS not-accessible
                       STATUS     current
                       DESCRIPTION
                               "The BGP-4 Received Path Attribute Table
                               contains information about paths to
                               destination networks received from all
                               BGP4 peers."
                       ::= { bgp 6 }

                   bgp4PathAttrEntry OBJECT-TYPE
                       SYNTAX     Bgp4PathAttrEntry
                       MAX-ACCESS not-accessible
                       STATUS     current
                       DESCRIPTION
                               "Information about a path to a network."
                       INDEX { bgp4PathAttrIpAddrPrefix,
                               bgp4PathAttrIpAddrPrefixLen,
                               bgp4PathAttrPeer           }
                       ::= { bgp4PathAttrTable 1 }

                   Bgp4PathAttrEntry ::= SEQUENCE {
                       bgp4PathAttrPeer
                           IpAddress,
                       bgp4PathAttrIpAddrPrefixLen
                           INTEGER,
                       bgp4PathAttrIpAddrPrefix
                           IpAddress,
                       bgp4PathAttrOrigin
                           INTEGER,
                       bgp4PathAttrASPathSegment
```

```
                          OCTET STRING,
                bgp4PathAttrNextHop
                     IpAddress,
                bgp4PathAttrMultiExitDisc
                     INTEGER,
                bgp4PathAttrLocalPref
                     INTEGER,
                bgp4PathAttrAtomicAggregate
                     INTEGER,
                bgp4PathAttrAggregatorAS
                     INTEGER,
                bgp4PathAttrAggregatorAddr
                     IpAddress,
                bgp4PathAttrCalcLocalPref
                     INTEGER,
                bgp4PathAttrBest
                     INTEGER,
                bgp4PathAttrUnknown
                     OCTET STRING

          }

          bgp4PathAttrPeer OBJECT-TYPE
              SYNTAX      IpAddress
              MAX-ACCESS read-only
              STATUS      current
              DESCRIPTION
                     "The IP address of the peer where the path
                     information was learned."
              ::= { bgp4PathAttrEntry 1 }

          bgp4PathAttrIpAddrPrefixLen OBJECT-TYPE
              SYNTAX      INTEGER (0..32)
              MAX-ACCESS read-only
              STATUS      current
              DESCRIPTION
                     "Length in bits of the IP address prefix
                     in the Network Layer Reachability
                     Information field."
              ::= { bgp4PathAttrEntry 2 }

          bgp4PathAttrIpAddrPrefix OBJECT-TYPE
              SYNTAX      IpAddress
              MAX-ACCESS read-only
              STATUS      current
              DESCRIPTION
                     "An IP address prefix in the Network Layer
                     Reachability Information field.  This object
```

```
                        is an IP address containing the prefix with
                        length specified by
                        bgp4PathAttrIpAddrPrefixLen.
                        Any bits beyond the length specified by
                        bgp4PathAttrIpAddrPrefixLen are zeroed."
                ::= { bgp4PathAttrEntry 3 }

         bgp4PathAttrOrigin OBJECT-TYPE
             SYNTAX     INTEGER {
                                    igp(1),-- networks are interior
                                    egp(2),-- networks learned
                                           -- via EGP
                                    incomplete(3) -- undetermined
                                 }
             MAX-ACCESS read-only
             STATUS     current
             DESCRIPTION
                        "The ultimate origin of the path
                        information."
             ::= { bgp4PathAttrEntry 4 }

         bgp4PathAttrASPathSegment OBJECT-TYPE
             SYNTAX     OCTET STRING (SIZE (2..255))
             MAX-ACCESS read-only
             STATUS     current
             DESCRIPTION
                        "The sequence of AS path segments.  Each AS
                        path segment is represented by a triple
                        <type, length, value>.

                        The type is a 1-octet field which has two
                        possible values:
                             1      AS_SET: unordered set of ASs a
                                        route in the UPDATE
                                        message has traversed
                             2      AS_SEQUENCE: ordered set of ASs
                                        a route in the UPDATE
                                        message has traversed.

                        The length is a 1-octet field containing the
                        number of ASs in the value field.

                        The value field contains one or more AS
                        numbers, each AS is represented in the octet
                        string as a pair of octets according to the
                        following algorithm:
```

```
                              first-byte-of-pair = ASNumber / 256;
                              second-byte-of-pair = ASNumber & 255;"
                ::= { bgp4PathAttrEntry 5 }

        bgp4PathAttrNextHop OBJECT-TYPE
            SYNTAX      IpAddress
            MAX-ACCESS read-only
            STATUS      current
            DESCRIPTION
                    "The address of the border router that
                    should be used for the destination
                    network."
            ::= { bgp4PathAttrEntry 6 }

        bgp4PathAttrMultiExitDisc OBJECT-TYPE
            SYNTAX      INTEGER (-1..2147483647)
            MAX-ACCESS read-only
            STATUS      current
            DESCRIPTION
                    "This metric is used to discriminate
                    between multiple exit points to an
                    adjacent autonomous system.  A value of -1
                    indicates the absence of this attribute."
            ::= { bgp4PathAttrEntry 7 }

        bgp4PathAttrLocalPref OBJECT-TYPE
            SYNTAX      INTEGER (-1..2147483647)
            MAX-ACCESS read-only
            STATUS      current
            DESCRIPTION
                    "The originating BGP4 speaker's degree of
                    preference for an advertised route.  A
                    value of -1 indicates the absence of this
                    attribute."
            ::= { bgp4PathAttrEntry 8 }

        bgp4PathAttrAtomicAggregate OBJECT-TYPE
            SYNTAX      INTEGER {
                            lessSpecificRrouteNotSelected(1),
                            lessSpecificRouteSelected(2)
                        }
            MAX-ACCESS read-only
            STATUS      current
            DESCRIPTION
                    "Whether or not the local system has
                    selected a less specific route without
                    selecting a more specific route."
            ::= { bgp4PathAttrEntry 9 }
```

```
            bgp4PathAttrAggregatorAS OBJECT-TYPE
                SYNTAX     INTEGER (0..65535)
                MAX-ACCESS read-only
                STATUS     current
                DESCRIPTION
                        "The AS number of the last BGP4 speaker that
                        performed route aggregation.  A value of
                        zero (0) indicates the absence of this
                        attribute."
                ::= { bgp4PathAttrEntry 10 }

            bgp4PathAttrAggregatorAddr OBJECT-TYPE
                SYNTAX     IpAddress
                MAX-ACCESS read-only
                STATUS     current
                DESCRIPTION
                        "The IP address of the last BGP4 speaker
                        that performed route aggregation.  A value
                        of 0.0.0.0 indicates the absence of this
                        attribute."
                ::= { bgp4PathAttrEntry 11 }

            bgp4PathAttrCalcLocalPref OBJECT-TYPE
                SYNTAX     INTEGER (-1..2147483647)
                MAX-ACCESS read-only
                STATUS     current
                DESCRIPTION
                        "The degree of preference calculated by the
                        receiving BGP4 speaker for an advertised
                        route.  A value of -1 indicates the
                        absence of this attribute."
                ::= { bgp4PathAttrEntry 12 }

             bgp4PathAttrBest OBJECT-TYPE
                SYNTAX     INTEGER {
                            false(1),-- not chosen as best route
                            true(2) -- chosen as best route
                        }
                MAX-ACCESS read-only
                STATUS     current
                DESCRIPTION
                        "An indication of whether or not this route
                        was chosen as the best BGP4 route."
                ::= { bgp4PathAttrEntry 13 }

           bgp4PathAttrUnknown OBJECT-TYPE
                SYNTAX     OCTET STRING (SIZE(0..255))
                MAX-ACCESS read-only
```

```
                    STATUS     current
                    DESCRIPTION
                            "One or more path attributes not understood
                             by this BGP4 speaker.  Size zero (0)
                             indicates the absence of such
                             attribute(s).  Octets beyond the maximum
                             size, if any, are not recorded by this
                             object."
                    ::= { bgp4PathAttrEntry 14 }


             -- Traps.

             bgpTraps                    OBJECT IDENTIFIER ::= { bgp 7 }

             bgpEstablished NOTIFICATION-TYPE
                 OBJECTS { bgpPeerLastError,
                           bgpPeerState       }
                 STATUS  current
                 DESCRIPTION
                         "The BGP Established event is generated when
                          the BGP FSM enters the ESTABLISHED state."
                 ::= { bgpTraps 1 }

             bgpBackwardTransition NOTIFICATION-TYPE
                 OBJECTS { bgpPeerLastError,
                           bgpPeerState       }
                 STATUS  current
                 DESCRIPTION
                         "The BGPBackwardTransition Event is generated
                          when the BGP FSM moves from a higher numbered
                          state to a lower numbered state."
                 ::= { bgpTraps 2 }

     END
```

6. Acknowledgements

   We would like to acknowledge the assistance of all the members of the
   Interconnectivity Working Group, and particularly the following
   individuals:

        Yakov Rekhter, IBM
        Rob Coltun, University of Maryland
        Guy Almes, ANS
        Jeff Honig, Cornell Theory Center
        Marshall T. Rose, Dover Beach Consulting, Inc.
        Dennis Ferguson, ANS
        Mike Mathis, PSC
        John Krawczyk, Wellfleet Communications Inc.
        Curtis Villamizar, ANS
        Dave LeRoy, Pencom Systems
        Paul Traina, cisco Systems
        Andrew Partan, UUNET
        Robert Snyder, cisco Systems
        Dimitry Haskin, Wellfleet Communications Inc.
        Peder Chr Norgaard, Telebit Communications A/S
        Joel Halpern, Network Systems Corporation

7. References

   [1] Rekhter, Y., and T. Li, "A Border Gateway Protocol 4 (BGP-4)",
       RFC 1654, T.J. Watson Research Center, IBM Corp., cisco Systems,
       July 1994.

   [2] Rekhter, Y., and P. Gross, Editors, "Application of the Border
       Gateway Protocol in the Internet", RFC 1655 T.J. Watson Research
       Center, IBM Corp., MCI, July 1994.

8. Security Considerations

   Security issues are not discussed in this memo.

9. Authors' Addresses

   Steven Willis
   Wellfleet Communications Inc.
   15 Crosby Drive
   Bedford, MA 01730

   Phone: (617) 275-2400
   EMail: swillis@wellfleet.com

   John Burruss
   Wellfleet Communications Inc.
   15 Crosby Drive
   Bedford, MA 01730

   Phone: (617) 275-2400
   EMail: jburruss@wellfleet.com

   John Chu
   IBM Corp.
   P.O.Box 218
   Yorktown Heights, NY 10598

   Phone: (914) 945-3156
   EMail: jychu@watson.ibm.com