        Protocol for Carrying Authentication and Network Access (PANA)
                Threat Analysis and Security Requirements

Status of This Memo

Copyright Notice

Abstract

   This document discusses the threats to protocols used to carry
   authentication for network access. The security requirements arising
   from these threats will be used as additional input to the Protocol
   for Carrying Authentication for Network Access (PANA) Working Group
   for designing the IP based network access authentication protocol.

Table of Contents

1. Introduction

    The Protocol for Carrying Authentication for Network Access (PANA)
    Working Group is developing methods for authenticating clients to the
    access network using IP based protocols. This document discusses the
    threats to such IP based protocols.

    A client wishing to get access to the network must carry on multiple
    steps. First, it needs to discover the IP address of the PANA
    authentication agent (PAA) and then execute an authentication
    protocol to authenticate itself to the network. Once the client is
    authenticated, there might be other messages exchanged during the
    lifetime of the network access. This document discusses the threats
    in these steps without discussing any solutions. The requirements
    arising out of these threats will be used as input to the PANA
    Working Group. The use of word co-located in this document means
    that the referred entities are present on the same node.

2. Keywords

    The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT",
    "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this
    document are to be interpreted as described in [KEYWORDS].

3. Terminology and Definitions

    Client Access Device

       A network element (e.g., notebook computer, PDA) that requires
       access to a provider's network.

    Network Access Server (NAS)

       Network device that provides access to the network.

    PANA Client (PaC)

       An entity in the edge subnet that seeks to obtain network access
       from a PANA authentication agent within a network. A PANA client
       is associated with a device and a set of credentials to prove its
       identity within the scope of PANA.

    PANA Authentication Agent (PAA)

       An entity whose responsibility is to authenticate the PANA client
       and to grant network access service to the client's device.

   Authentication Server (AS)

      An entity that authenticates the PANA client. It may be
      co-located with the PANA authentication agent or part of the
      back-end infrastructure.

   Device Identifier (DI)

      The identifier used by the network to control and police the
      network access of a client. Depending on the access technology,
      the identifier might contain the IP address, link-layer address,
      switch port number, etc., of a device. The PANA authentication
      agent keeps a table for binding device identifiers to the PANA
      clients. At most one PANA client should be associated with a DI
      on a PANA authentication agent.

   Enforcement Point (EP)

      A node capable of filtering packets sent by the PANA client by
      using the DI information authorized by PANA authentication agent.

   Compound methods

      Authentication protocol in which methods are used in a sequence
      one after another or in which methods are tunneled inside another
      independently established tunnel between the client and server
      [TUN-EAP].

4. Usage Scenarios

      PANA is intended to be used in an environment where there is no a
      priori trust relationship or security association between the PaC
      and other nodes, such as the PAA and EP. In these environments,
      one may observe the following:

      o The link between PaC and PAA may be a shared medium (e.g.,
         Ethernet) or may not be a shared medium (e.g., DSL network).

      o All the PaCs may be authenticated to the access network at
         layer 2 (e.g., 3GPP2 CDMA network) and share a security
         association with a layer 2 authentication agent (e.g., BTS).
         The PaCs still don't trust each other; any PaC can pretend to
         be a PAA, spoof IP addresses, and launch various other attacks.

   The scenarios mentioned above affect the threat model of PANA. This
   document discusses the various threats in the context of the above
   network access scenarios for a better understanding of the threats.
   In the following discussion, any reference to a link that is not

shared (or non-shared) is assumed to be physically secure. If such
an assumption cannot be made about the link, then the case becomes
the same as that for a link being shared by more than one node.

5. Trust Relationships

   PANA authentication involves a client (PaC), a PANA agent (PAA), an
   Authentication server (AS), and an Enforcement point (EP). The AS
   here refers to the AAA server that resides in the home realm of the
   PaC.

   The entities that have a priori trust relationships before PANA
   begins are as follows:

      1) PAA and AS: The PaC belonging to the same administrative domain
         that the AS does often has to use resources provided by a PAA
         that belongs to another administrative domain. A PAA
         authenticates the PaC before providing local network access.
         The credentials provided by the PaC for authentication may or
         may not be understood by the PAA. If the PAA does not
         understand the credentials, it needs to communicate with the AS
         in a different domain to verify the credentials. The threats
         in the communication path between the PAA and AS are already
         covered in [RAD-EAP]. To counter these threats, the
         communication between the PAA and AS is secured by using a
         static or dynamic security association.

      2) PAA and EP: The PAA and EP belong to the same administrative
         domain. Hence, the network operator can set up a security
         association to protect the traffic exchanged between them.
         This document discusses the threats in this path.

      3) PaC and AS: The PaC and AS belong to the same administrative
         domain and share a trust relationship. When the PaC uses a
         different domain than its home for network access, it provides
         its credentials to the PAA in the visited network for
         authentication. The information provided by the PaC traverses
         the PaC-PAA and PAA-AS paths. The threats in the PAA-AS path
         are already discussed in [RAD-EAP]. This document discusses
         the threats in the PaC-PAA path.

   It is possible that some of the entities such as the PAA, AS, and EP
   are co-located. In those cases, it can be safely assumed that there
   are no significant external threats in their communication.

   The entities that do not have any trust relationship before PANA
   begins are as follows:

1) PaC and PAA: The PaC and PAA normally belong to two different
   administrative domains. They do not necessarily share a trust
   relationship initially. They establish a security association
   in the process of authentication. All messages exchanged
   between the PaC and PAA are subject to various threats, which
   are discussed in this document.

2) PaC and EP: The EP belongs to the same administrative domain as
   the PAA. Hence, the PaC and EP do not necessarily share a
   trust relationship initially. When the PaC is successfully
   authenticated, it may result in key establishment between the
   PaC and PAA, which can be further used to secure the link
   between the PaC and EP. For example, the EAP keying framework,
   [EAP-KEY], defines a three party EAP exchange in which the
   clients derive the transient sessions keys to secure the link
   between the peer and NAS in their final step. Similarly, PANA
   will provide the ability to establish keys between the PaC and
   EP that can be used to secure the link further. This is
   discussed further in Section 6.4 below.

6. Threat Scenarios

   First, the PaC needs to discover the PAA. This involves either
   sending solicitations or waiting for advertisements. Once it has
   discovered the PAA, the two will enter authentication exchange. Once
   the access is granted, the PaC will most likely exchange data with
   other nodes in the Internet. These steps are vulnerable to man-in-
   the-middle (MITM), denial of service (DoS), and service theft
   attacks, which are discussed below.

   The threats are grouped by the various stages the client goes through
   to gain access to the network. Section 6.1 discusses the threats
   related to PAA discovery. Section 6.2 discusses the threats related
   to authentication itself. Section 6.3 discusses the threats involved
   when leaving the network. Section 6.4 discusses service theft.
   Section 6.5 discusses the threats in the PAA-EP path. Section 6.6
   discusses the miscellaneous threats.

   Some of the threats discussed in the following sections may be
   specific to shared links. The threat may be absent on non-shared
   links. Hence, it is only required to prevent the threat on shared
   links. Instead of specifying a separate set of requirements for
   shared links and non-shared links, this document specifies one set of
   requirements with the following wording: "PANA MUST be able to
   prevent threat X". This means that the PANA protocol should be
   capable of preventing threat X. The feature that prevents threat X
   may or may not be used depending on the deployment.

6.1. PAA Discovery

   The PAA is discovered by sending solicitations or receiving
   advertisements. The following are possible threats.

   T6.1.1: A malicious node can pretend to be a PAA by sending a spoofed
           advertisement.

   In existing dial-up networks, the clients authenticate to the network
   but generally do not verify the authenticity of the messages coming
   from Network Access Server (NAS). This mostly works because the link
   between the device and the NAS is not shared with other nodes
   (assuming that nobody tampers with the physical link), and clients
   trust the NAS and the phone network to provide the service. Spoofing
   attacks are not present in this environment, as the PaC may assume
   that the other end of the link is the PAA.

   In environments where the link is shared, this threat is present, as
   any node can pretend to be a PAA. Even if the nodes are
   authenticated at layer 2, the threat remains present. It is
   difficult to protect the discovery process, as there is no a priori
   trust relationship between the PAA and PaC. In deployments where EP
   can police the packets that are sent among the PaCs, it is possible
   to filter out the unauthorized PANA packets (e.g., PAA advertisements
   sent by PaC) to prevent this threat.

   The advertisement may be used to include information (such as
   supported authentication methods) other than the discovery of the PAA
   itself. This can lead to a bidding down attack, as a malicious node
   can send a spoofed advertisement with capabilities that indicate
   authentication methods less secure than those that the real PAA
   supports, thereby fooling the PaC into negotiating an authentication
   method less secure than would otherwise be available.

   Requirement 1

   PANA MUST not assume that the discovery process is protected.

6.2. Authentication

   This section discusses the threats specific to the authentication
   protocol. Section 6.2.1 discusses the possible threat associated
   with success/failure indications that are transmitted to PaC at the
   end of the authentication. Section 6.2.2 discusses the man-in-the-
   middle attack when compound methods are used. Section 6.2.3
   discusses the replay attack, and Section 6.2.4 discusses the device
   identifier attack.

6.2.1. Success or Failure Indications

   Some authentication protocols (e.g., EAP) have a special message to
   indicate success or failure. An attacker can send a false
   authentication success or failure message to the PaC. By sending a
   false failure message, the attacker can prevent the client from
   accessing the network. By sending a false success message, the
   attacker can prematurely end the authentication exchange, effectively
   denying service for the PaC.

   If the link is not shared, then this threat is absent, as ingress
   filtering can prevent the attacker from impersonating the PAA.

   If the link is shared, it is easy to spoof these packets. If layer 2
   provides per-packet encryption with pair-wise keys, it might make it
   hard for the attacker to guess the success or failure packet that the
   client would accept. Even if the node is already authenticated at
   layer 2, it can still pretend to be a PAA and spoof the success or
   failure.

   This attack is possible if the success or failure indication is not
   protected by using a security association between the PaC and the
   PAA. In order to avoid this attack, the PaC and PAA should mutually
   authenticate each other. In this process, they should be able to
   establish keys to protect the success or failure indications. It may
   not always be possible to protect the indication, as the keys may not
   be established prior to transmitting the success or failure packet.
   If the client is re-authenticating to the network, it can use the
   previously established security association to protect the success or
   failure indications. Similarly, all PANA messages exchanged during
   the authentication prior to key establishment may not be protected.

      Requirement 2

   PANA MUST be able to mutually authenticate the PaC and PAA. PANA
   MUST be able to establish keys between the PaC and PAA to protect the
   PANA messages.

6.2.2. MITM Attack

   A malicious node can claim to be the PAA to the real PaC and claim to
   be the PaC to the real PAA. This is a man-in-the-middle (MITM)
   attack, whereby the PaC is fooled to think that it is communicating
   with the real PAA and the PAA is fooled to think that it is
   communicating with the real PaC.

If the link is not shared, this threat is absent, as ingress
filtering can prevent the attacker from acting as a man-in-the-
middle.

If the link is shared, this threat is present. Even if the layer 2
provides per-packet protection, the attacker can act as a man-in-
the-middle and launch this attack. An instance of MITM attack, in
which compound authentication methods are used is described in
[TUN-EAP]. In these attacks, the server first authenticates to the
client. As the client has not proven its identity yet, the server
acts as the man-in-the-middle, tunneling the identity of the
legitimate client to gain access to the network. The attack is
possible because there is no verification that the same entities
participated among the compound methods. It is not possible to do
such verification if compound methods are used without being able to
create a cryptographic binding among them. This implies that PANA
will be vulnerable to such attacks if compound methods are used
without being able to cryptographically bind them. Note that the
attack does not exist if the keys derived during the tunnel
establishment are not used to authenticate the client (e.g., tunnel
keys are used for just protecting the identity of the client).

   Requirement 3

   When compound authentication methods are used in PANA, the methods
   MUST be cryptographically bound.

6.2.3. Replay Attack

A malicious node can replay the messages that caused authentication
failure or success at a later time to create false failures or
success. The attacker can also potentially replay other messages of
the PANA protocol to deny service to the PaC.

If the link is not shared, this threat is absent, as ingress
filtering can prevent the attacker from impersonating the PAA to
replay the packets.

If the link is shared, this threat is present. If the packets are
encrypted at layer 2 by using pair-wise keys, it will make it hard
for the attacker to learn the unencrypted (i.e., original) packet
that needs to be replayed. Even if layer 2 provides replay
protection, the attacker can still replay the PANA messages (layer 3)
for denying service to the client.

   Requirement 4

   PANA MUST be able to protect itself against replay attacks.

6.2.4. Device Identifier Attack

   When the client is successfully authenticated, the PAA sends access
   control information to the EP for granting access to the network.
   The access control information typically contains the device
   identifier of the PaC, which is either obtained from the IP headers
   and MAC headers of the packets exchanged during the authentication
   process or carried explicitly in the PANA protocol field. The
   attacker can gain unauthorized access into the network by taking the
   following steps.

      o An attacker pretends to be a PAA and sends advertisements. The
         PaC is fooled and starts exchanging packets with the attacker.

      o The attacker modifies the IP source address on the packet,
         adjusts the UDP/TCP checksum, and forwards the packet to the
         real PAA. It also does the same on return packets.

      o When the real PaC is successfully authenticated, the attacker
         gains access to the network, as the packets contained the IP
         address (and potentially the MAC address also) of the attacker.

   If the link is not shared, this threat is absent, as the attacker
   cannot impersonate the PAA and intercept the packets from the PaC.

   If the link is shared, this threat is present. If the layer 2
   provides per-packet protection, it is not possible to change the MAC
   address, and hence this threat may be absent in such cases if EP
   filters on both the IP and MAC address.

      Requirement 5

   PANA MUST be able to protect the device identifier against spoofing
   when it is exchanged between the PaC and PAA.

6.3. PaC Leaving the Network

   When the PaC leaves the network, it can inform the PAA before
   disconnecting from the network so that the resources used by PaC can
   be accounted properly. The PAA may also choose to revoke the access
   anytime it deems necessary. The following are possible threats:

   T6.3.1: A malicious node can pretend to be a PAA and revoke the
           access to PaC.

   T6.3.2: A malicious node can pretend to be a real PaC and transmit a
           disconnect message.

      T6.3.3: The PaC can leave the network without notifying the PAA or EP
              (e.g., the Ethernet cable is unplugged, system crash). An
              attacker can pretend to be the PaC and start using the
              network.

   If the link is not shared, threats T6.3.1 and T6.3.2 are absent.
   Threat T6.3.3 may still be present. If there is no layer 2
   indication, or if the layer 2 indication cannot be relied upon, then
   threat T6.3.3 is still present on non-shared links.

   If the link is shared, all of the above threats are present, as any
   node on the link can spoof the disconnect message. Even if layer 2
   has per-packet authentication, the attacker can pretend to be a PaC
   (e.g., by spoofing the IP address) and disconnect from the network.
   Similarly, any node can pretend to be a PAA and revoke the access to
   the PaC. Therefore, T6.3.1 and T6.3.2 are possible even on links
   where layer 2 is secured. Threat T6.3.3 can be prevented if layer 2
   provides per-packet authentication. The attacker cannot subsume the
   PaC that left the network without knowing the keys that protect the
   packet at layer 2.

      Requirement 6

      PANA MUST be able to protect disconnect and revocation messages.
      PANA MUST NOT depend on the PaC sending a disconnect message.

6.4. Service Theft

   An attacker can gain unauthorized access into the network by stealing
   the service from another client. Once the real PaC is successfully
   authenticated, the EP will have filters in place to prevent
   unauthorized access into the network. The filters will be based on
   something that will be carried on every packet. For example, the
   filter could be based on the IP and MAC addresses, where the packets
   will be dropped unless the packets coming with certain IP addresses
   also match the MAC addresses. The following are possible threats:

      T6.4.1: An attacker can spoof both the IP and MAC addresses of an
              authorized client to gain unauthorized access. The attacker
              can launch this attack easily by just sniffing the wire for
              IP and MAC addresses. This lets the attacker use the network
              without any authorization, getting a free service.

      T6.4.2: The PaC can leave the network without notifying the PAA or EP
              (e.g., the Ethernet cable is unplugged, system crash). An
              attacker can pretend to be the PaC and start using the
              network.

   Service theft allows the possibility of exploiting the weakness in
   other authentication protocols that use IP address for
   authentication. It also allows the interception of traffic destined
   for other nodes by spoofing the IP address.

   If the link is not shared, T6.4.1 is absent, as there is only one
   client on the link, and ingress filtering can prevent the use of the
   authorized IP and MAC addresses by the attacker on another link.
   Threat T6.4.2 exists, as the attacker can use the IP or MAC address
   of the real PaC to gain access to the network.

   If the link is shared, both the threats are present. If layer 2
   provides per-packet protection using pair-wise keys, both the threats
   can be prevented.

   Requirement 7

   PANA MUST securely bind the authenticated session to the device
   identifier of the client, to prevent service theft. PANA MUST be
   able to bootstrap a shared secret between the PaC and PAA that can be
   further used to set up a security association between the PaC and EP
   to provide cryptographic protection against service theft.

6.5. PAA-EP Communication

   After a successful authentication, the PAA needs to communicate the
   access control information of the PaC to the EP so that the PaC will
   be allowed to access the network. The information communicated would
   contain at least the device identifier of the PaC. If strong
   security is needed, the PAA will communicate a shared secret known
   only to the PaC and PAA, for setting up a security association
   between the PaC and EP. The following are possible threats:

   T6.5.1: An attacker can eavesdrop to learn the information
           communicated between the PAA and EP. The attacker can
           further use this information to spoof the real PaC and also
           to set up security association for gaining access to the
           network. This threat is absent if the attacker cannot
           eavesdrop on the link; e.g., the PAA and EP communicate on a
           link separate from that of visiting PaCs.

   T6.5.2: An attacker can pretend to be a PAA and send false
           information to an EP to gain access to the network. In the
           case of stronger security, the attacker has to send its own
           device identifier and also a shared secret, so that the EP
           will let the attacker access the network.

If the communication between the PAA and EP is protected, these
threats are absent.

Requirement 8

The communication between the PAA and EP MUST be protected against
eavesdropping and spoofing attacks.

6.6. Miscellaneous Attacks

   T6.6.1: There are various forms of DoS attacks that can be launched
           on the PAA or AS. A few are mentioned below. As it is hard
           to defend against some of the DoS attacks, the protocol
           should be designed carefully to mitigate or prevent such
           attacks.

           o An attacker can bombard the PAA with lots of
              authentication requests. If the PAA and AS are not co-
              located, the PAA may have to allocate resources to store
              some state about the PaC locally before it receives the
              response from the back-end AS. This can deplete memory
              resources on the PAA.

           o With minimal effort, an attacker can force the PAA or AS
              to make computationally intensive operations with minimal
              effort, that can deplete the CPU resources of the PAA or
              AS.

   T6.6.2: PaC acquires an IP address by using stateful or stateless
           mechanisms before PANA authentication begins [PANAREQ]. When
           the IP addresses are assigned before the client
           authentication, it opens up the possibility of DoS attacks in
           which unauthenticated malicious nodes can deplete the IP
           address space by acquiring multiple IP addresses or deny
           allocation to others by responding to every duplicate address
           detection (DAD) query.

           Depleting a /64 IPv6 link-local address space or a /8 RFC1918
           private address space requires a brute-force attack. Such an
           attack is part of a DoS class that can equally target the
           link capacity or the CPU cycles on the target system by
           bombarding arbitrary packets. Therefore, solely handling the
           IP address depletion attack is not going to improve the
           security, as a more general solution is needed to tackle the
           whole class of brute-force attacks.

           The DAD attack can be prevented by deploying secure address
           resolution that does not depend on the client authentication,

such as [SEND]. The attack may also be prevented if the EP
is placed between the PaCs to monitor the ND/ARP activity and
to detect DAD attacks (excessive NA/ARP replies). If none of
these solutions are applicable to a deployment, the PaCs can
send arbitrary packets to each other without going through
the EP, which enables a class of attacks that are based on
interfering with the PANA messaging (See T6.1.1). Since
there will always be a threat in this class (e.g., insecure
discovery), it is not going to improve the overall security
by addressing DAD.

7. Summary of Requirements

   1. PANA MUST not assume that the discovery process is protected.

   2. PANA MUST be able to mutually authenticate the PaC and PAA. PANA
      MUST be able to establish keys between the PaC and PAA to protect
      the PANA messages.

   3. When compound authentication methods are used in PANA, the methods
      MUST be cryptographically bound.

   4. PANA MUST be able to protect itself against replay attacks.

   5. PANA MUST be able to protect the device identifier against
      spoofing when it is exchanged between the PaC and PAA.

   6. PANA MUST be able to protect disconnect and revocation messages.
      PANA MUST NOT depend on whether the PaC sends a disconnect
      message.

   7. PANA MUST securely bind the authenticated session to the device
      identifier of the client, to prevent service theft. PANA MUST be
      able to bootstrap a shared secret between the PaC and PAA that can
      be further used to set up a security association between the PaC
      and EP to provide cryptographic protection against service theft.

   8. The communication between the PAA and EP MUST be protected against
      eavesdropping and spoofing attacks.

8. Security Considerations

   This document discusses various threats with IP based network access
   authentication protocol. Though this document discusses the threats
   for shared and unshared links separately, it may be difficult to make
   such a distinction in practice (e.g., a dial-up link may be a point-
   to-point IP tunnel). Hence, the link should be assumed to be a
   shared link for most of the threats in this document.

9. Normative References

   [KEYWORDS]   Bradner, S., "Key words for use in RFCs to Indicate
                   Requirement Levels", BCP 14, RFC 2119, March 1997.

10. Informative References

   [PANAREQ]   Yegin, A., Ed., Ohba, Y., Penno, R., Tsirtsis, G., and
                   C. Wang, "Protocol for Carrying Authentication for
                   Network Access (PANA) Requirements and Terminology",
                   Work in Progress, August 2004.

   [EAP-KEY]   Aboba, B., et al., "EAP keying framework", Work in
                   Progress.

   [RAD-EAP]   Aboba, B. and P. Calhoun, "RADIUS (Remote
                   Authentication Dial In User Service) Support For
                   Extensible Authentication Protocol (EAP)", RFC 3579,
                   September 2003.

   [TUN-EAP]   Puthenkulam, J., et al., "The compound authentication
                   binding problem", Work in Progress.

   [SEND]   Arkko, J., Ed., Kempf, J., Zill, B., and P. Nikander,
                   "SEcure Neighbor Discovery (SEND)", RFC 3971, March
                   2005.

Author's Address

   Mohan Parthasarathy
   Nokia
   313 Fairchild Drive
   Mountain View, CA-94303

   EMail: mohanp@sbcglobal.net