

Internet Engineering Task Force (IETF)
Request for Comments: 7852
Updates: [6443](#), [6881](#)
Category: Standards Track
ISSN: 2070-1721

R. Gellens

B. Rosen
NeuStar
H. Tschofenig

R. Marshall
TeleCommunication Systems, Inc.
J. Winterbottom
Winterb Consulting Services
July 2016

Additional Data Related to an Emergency Call

Abstract

When an emergency call is sent to a Public Safety Answering Point (PSAP), the originating device, the access network provider to which the device is connected, and all service providers in the path of the call have information about the call, the caller, or the location, which is helpful for the PSAP to have in handling the emergency. This document describes data structures and mechanisms to convey such data to the PSAP. The intent is that every emergency call carry as much of the information described here as possible using the mechanisms described here.

The mechanisms permit the data to be conveyed by reference (as an external resource) or by value (within the body of a SIP message or a location object). This follows the tradition of prior emergency services standardization work where data can be conveyed by value within the call signaling (i.e., in the body of the SIP message) or by reference.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in [Section 2 of RFC 7841](#).

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc7852>.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	4
2. Terminology	6
3. Document Scope	7
4. Data Structures	7
4.1. Data Provider Information.	9
4.1.1. Data Provider String	9
4.1.2. Data Provider ID	9
4.1.3. Data Provider ID Series	10
4.1.4. Type of Data Provider	11
4.1.5. Data Provider Contact URI	12
4.1.6. Data Provider Language(s) Supported	13
4.1.7. xCard of Data Provider	14
4.1.8. Subcontractor Principal	14
4.1.9. Subcontractor Priority	15
4.1.10. ProviderInfo Example	15
4.2. Service Information	18
4.2.1. Service Environment	18
4.2.2. Service Type	19
4.2.3. Service Mobility Environment	21
4.2.4. EmergencyCallData.ServiceInfo Example	22
4.3. Device Information	22
4.3.1. Device Classification	22
4.3.2. Device Manufacturer	23
4.3.3. Device Model Number	24
4.3.4. Unique Device Identifier	24
4.3.5. Device/Service-Specific Additional Data Structure	25
4.3.6. Device/Service-Specific Additional Data Structure Type	26
4.3.7. EmergencyCallData.DeviceInfo Example	27
4.4. Owner/Subscriber Information	27
4.4.1. Subscriber Data Privacy Indicator	27
4.4.2. xCard for Subscriber's Data	28

4.4.3. EmergencyCallData.SubscriberInfo Example	29
4.5. Comment	31
4.5.1. Comment	31
4.5.2. EmergencyCallData.Comment Example	32
5. Issues with Getting New Types of Data into Use	32
5.1. Choosing between Defining a New Type of Block or a New Type of Device/Service-Specific Additional Data	33
6. Data Transport Mechanisms	33
6.1. Transmitting Blocks Using Call-Info	36
6.2. Transmitting Blocks by Reference Using the <provided-by> Element	37
6.3. Transmitting Blocks by Value Using the <provided-by> Element	38
6.4. The Content-Disposition Parameter	39
7. Examples	41
8. XML Schemas	53
8.1. EmergencyCallData.ProviderInfo XML Schema	54
8.2. EmergencyCallData.ServiceInfo XML Schema	56
8.3. EmergencyCallData.DeviceInfo XML Schema	57
8.4. EmergencyCallData.SubscriberInfo XML Schema	59
8.5. EmergencyCallData.Comment XML Schema	60
8.6. provided-by XML Schema	61
9. Security Considerations	62
10. Privacy Considerations	64
11. IANA Considerations	67
11.1. Emergency Call Additional Data Registry	67
11.1.1. Provider ID Series Registry	67
11.1.2. Service Environment Registry	68
11.1.3. Service Type Registry	68
11.1.4. Service Mobility Registry	68
11.1.5. Type of Provider Registry	69
11.1.6. Device Classification Registry	69
11.1.7. Device ID Type Registry	69
11.1.8. Device/Service Data Type Registry	70
11.1.9. Emergency Call Data Types Registry	70
11.2. 'EmergencyCallData' Purpose Parameter Value	72
11.3. URN Sub-Namespace Registration for <provided-by> Registry Entry	72
11.4. MIME Registrations	72
11.4.1. MIME Content-Type Registration for 'application/EmergencyCallData.ProviderInfo+xml' . . .	72
11.4.2. MIME Content-Type Registration for 'application/EmergencyCallData.ServiceInfo+xml' . . .	73
11.4.3. MIME Content-Type Registration for 'application/EmergencyCallData.DeviceInfo+xml' . . .	74
11.4.4. MIME Content-Type Registration for 'application/EmergencyCallData.SubscriberInfo+xml' . .	75

11.4.5.	MIME Content-Type Registration for 'application/EmergencyCallData.Comment+xml'	76
11.5.	URN Sub-Namespace Registration	78
11.5.1.	Registration for urn:ietf:params:xml:ns:EmergencyCallData	78
11.5.2.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo	78
11.5.3.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo	79
11.5.4.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo	80
11.5.5.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo	81
11.5.6.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:Comment	81
11.6.	Schema Registrations	82
11.7.	vCard Parameter Value Registration	83
12.	References	84
12.1.	Normative References	84
12.2.	Informative References	85
Appendix A.	XML Schema for vCard/xCard	89
Appendix B.	XML Validation	111
	Acknowledgments	112
	Authors' Addresses	113

1. Introduction

When an IP-based emergency call is initiated, a rich set of data from multiple data sources is conveyed to the Public Safety Answering Point (PSAP). This data includes information about the calling party identity, the multimedia capabilities of the device, the request for emergency services, location information, and metadata about the sources of the data. In addition, the device, the access network provider, and any service provider in the call path has even more information that is useful for a PSAP when handling an emergency.

This document extends the basic set of data communicated with an emergency call based on the Session Initiation Protocol (SIP), as described in [RFC 6443](#) [RFC6443] and [RFC 6881](#) [RFC6881], in order to carry additional data that is useful to an entity or call taker handling the call. This data is "additional" to the basic information found in the emergency call signaling used. The intent is that every emergency call carry as much of the information described here as possible using the mechanisms described here.

This document defines three categories of this additional data that can be transmitted with an emergency call:

Data Associated with a Location: Primary location data is conveyed in the Presence Information Data Format Location Object (PIDF-LO) data structure as defined in RFC 4119 [RFC4119] and extended by RFC 5139 [RFC5139] and RFC 6848 [RFC6848] (for civic location information), RFC 5491 [RFC5491] and RFC 5962 [RFC5962] (for geodetic location information), and RFC 7035 [RFC7035] (for relative location). This primary location data identifies the location or estimated location of the caller. However, there might exist additional, secondary data that is specific to the location, such as floor plans, tenant and building owner contact data, heating, ventilation, and air conditioning (HVAC) status, etc. Such secondary location data is not included in the location data structure but can be transmitted using the mechanisms defined in this document. Although this document does not define any structures for such data, future documents can do so following the procedures defined here.

Data Associated with a Call: While some information is carried in the call setup procedure itself (as part of the SIP headers as well as in the body of the SIP message), there is additional data known by the device making the call, the access network to which the device is connected, and service providers along the path of the call. This information includes service provider contact information, subscriber identity and contact information, the type of service the service provider and the access network provide, what type of device is being used, etc. Some data is broadly applicable, while other data is dependent on the type of device or service. For example, a medical monitoring device might have sensor data. The data structures defined in this document (Data Provider Information, Device Information, and Owner/Subscriber Information) all fall into the category of "Data Associated with a Call". Note that the owner/subscriber information includes the subscriber's vCard, which might contain personal information such as birthday, anniversary, etc., but the data block itself is still considered to be about the call, not the caller.

Data Associated with a Caller: This is personal data about a caller, such as medical information and emergency contact data. Although this document does not define any structures within this category, future documents can do so following the procedures defined here.

While this document defines data structures only within the category of Data Associated with a Call, by establishing the overall framework of Additional Data, along with general mechanisms for transport of such data, extension points, and procedures for future extensions, it

minimizes the work needed to carry data in the other categories. Other specifications can make use of the facilities provided here.

For interoperability, there needs to be a common way for the information conveyed to a PSAP to be encoded and identified. Identification allows emergency services authorities to know during call processing which types of data are present and to determine if they wish to access it. A common encoding allows the data to be successfully accessed.

This document defines an extensible set of data structures, and mechanisms to transmit this data either by value or by reference, either in the SIP call signaling or in the PIDF-LO. The data structures are usable by other communication systems and transports as well. The data structures are defined in [Section 4](#), and the transport mechanisms (using SIP and HTTPS) are defined in [Section 6](#).

Each data structure described in this document is encoded as a "block" of information. Each block is an XML structure with an associated Multipurpose Internet Mail Extensions (MIME) media type for identification within transport such as SIP and HTTPS. The set of blocks is extensible. Registries are defined to identify the block types that can be used and to allow blocks to be included in emergency call signaling.

Much of the information supplied by service providers and devices is private and confidential. Service providers and devices generally go to lengths to protect this information; disclosing it in the context of an emergency call is a trade-off to protect the greater interest of the customer in an emergency.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document also uses terminology from [[RFC5012](#)]. We use the term "service provider" to refer to an Application Service Provider (ASP). A Voice Service Provider (VSP) is a special type of ASP. With the term "Access Network Provider", we refer to the Internet Access Provider (IAP) and the Internet Service Provider (ISP) without further distinguishing these two entities, since the difference between the two is not relevant for this document. Note that the roles of an ASP and access network provider might be provided by a single company. An Emergency Services Provider is an entity directly involved in providing emergency services. This includes PSAPs,

dispatch, police, fire, emergency medical, other responders, and other similar agencies.

Within each data block definition (see [Section 4](#)), the values for the 'Use:' label are specified as one of the following:

'Required': means it MUST be present in the data structure.

'Conditional': means it MUST be present if the specified condition(s) is met. It MAY be present if the condition(s) is not met.

'Optional': means it MAY be present.

vCard [[RFC6350](#)] is a data format for representing and exchanging a variety of information about individuals and other entities. For applications that use XML, the format defined in vCard is not immediately applicable. For this reason, an XML-based encoding of the information elements defined in the vCard specification has been defined, and the name of that specification is xCard [[RFC6351](#)]. Since the term vCard is more familiar to most readers, we use the terms xCard and vCard interchangeably.

3. Document Scope

The scope of this document is explicitly limited to emergency calls. The data structures defined here are not appropriate to be conveyed in non-emergency calls because they carry sensitive and private data. However, in certain private-use situations between a specialized service provider (such as a vehicle telematics service provider) and dedicated equipment (such as in a vehicle) where the endpoints have a preexisting relationship and privacy issues are addressed within the relationship, the mechanisms and data structures defined here can be used with communications within the limited context of the preexisting relationship.

4. Data Structures

This section defines the following five data structures, each as a data block. For each block, we define the MIME media type and the XML encoding. The five data structures are:

'Data Provider': This block supplies name and contact information for the entity that created the data. [Section 4.1](#) provides the details.

'Service Information': This block supplies information about the service. The description can be found in [Section 4.2](#).

'Device Information': This block supplies information about the device placing the call. Device information can be found in [Section 4.3](#).

'Owner/Subscriber': This block supplies information about the owner of the device or about the subscriber. Details can be found in [Section 4.4](#).

'Comment': This block provides a way to supply free form human-readable text to the PSAP or emergency responders. This simple structure is defined in [Section 4.5](#).

Each block contains a mandatory <DataProviderReference> element. The purpose of the <DataProviderReference> element is to associate all blocks added by the same data provider as a unit. The <DataProviderReference> element associates the data provider block to each of the other blocks added as a unit. Consequently, when a data provider adds additional data to an emergency call (such as device information), it MUST add information about itself (via the data provider block), and the blocks added contain the same value in the <DataProviderReference> element. All blocks added by a single entity at the same time MUST have the same <DataProviderReference> value. (In certain situations, the same provider might process a call more than once, likely in different roles, and in such cases, each time it processes the call, it adds a new set of blocks with a new <DataProviderReference> value.) The value of the <DataProviderReference> element has the same syntax and properties (specifically, world-uniqueness) as the value of the 'Message-ID' message body header field specified in [RFC 5322](#) [[RFC5322](#)] except that the <DataProviderReference> element is not enclosed in brackets (the '<' and '>' symbols are omitted). In other words, the value of a <DataProviderReference> element is syntactically a msg-id as specified in [RFC 5322](#) [[RFC5322](#)].

Each block is added to the "Additional Data Blocks" registry created in [Section 11.1.9](#) and categorized as providing data about the caller. New blocks added to the registry in the future MUST also be categorized per the description of the three categories in [Section 1](#). See [Sections 5](#) and [5.1](#) for additional considerations when adding new blocks or types of data.

Note that the xCard format is reused in some of the data structures to provide contact information. In an xCard, there is no way to specify a 'main' telephone number (that is, a primary or main contact number, typically of an enterprise, as opposed to a direct-dial number of an individual). These numbers are useful to emergency responders who are called to a large enterprise. This document adds a new parameter value called 'main-number' to the 'TYPE' parameter of

the 'tel' property. It can be used in any xCard in an emergency call additional data block.

4.1. Data Provider Information

This block is intended to be supplied by any service provider in the path of the call, or the access network provider, and the device. It includes identification and contact information. This block **MUST** be supplied by any entity that provides any other block; it **SHOULD** be supplied by every service provider in the call path and by the access network provider if those entities do not add any other blocks. Devices **SHOULD** use this block to provide identifying information. The MIME media type is 'application/EmergencyCallData.ProviderInfo+xml'. An access network provider **SHOULD** provide this block either by value or by reference in the <provided-by> element of a PIDF-LO.

4.1.1. Data Provider String

Data Element: Data Provider String

Use: Conditional. Optional for blocks supplied by the originating device; mandatory otherwise.

XML Element: <DataProviderString>

Description: This is a plaintext string suitable for displaying the name of the service provider that supplied the data structure. If the device creates the structure, it **SHOULD** use the value of the contact header field in the SIP INVITE.

Reason for Need: Inform the call taker of the identity of the entity providing the data.

How Used by Call Taker: Allows the call taker to interpret the data in this structure. The source of the information often influences how the information is used, believed, or verified.

4.1.2. Data Provider ID

Data Element: Data Provider ID

Use: Conditional. Optional for blocks supplied by the originating device; mandatory otherwise. This data **MUST** be provided by all entities other than the originating device in order to uniquely identify the service provider or access provider.

XML Element: <ProviderID>

Description: A jurisdiction-specific code for, or the fully qualified domain name of, the access network provider or service provider shown in the <DataProvidedBy> element that created the structure. NOTE: The value SHOULD be assigned by an organization appropriate for the jurisdiction. In the United States, if the provider is registered with NENA, the provider's NENA Company ID MUST appear here. Additional information can be found at the National Emergency Number Association (NENA) Company Identifier Program <<http://www.nena.org/?page=cid2014>> or the NENA Company ID <<http://www.nena.org/?page=CompanyID>>. The NENA Company ID MUST be in the form of a URI in the following format: urn:nena:companyid:<NENA Company ID>. If the organization does not have an identifier registered with a jurisdiction-specific emergency services registrar (such as NENA), then the value MAY be the fully qualified domain name of the service provider or access provider. The device MAY use its IP address or fully qualified domain name (and set the 'Data Provider ID Series' element to 'domain').

Reason for Need: Inform the call taker of the identity of the entity providing the data.

How Used by Call Taker: Where jurisdictions have lists of providers, the Data Provider ID provides useful information about the data source. The Data Provider ID uniquely identifies the source of the data, which might be needed especially during unusual circumstances and for routine logging.

4.1.3. Data Provider ID Series

Data Element: Data Provider ID Series

Use: Conditional. Optional for blocks supplied by the originating device; mandatory otherwise.

XML Element: <ProviderIDSeries>

Description: Identifies the issuer of the <ProviderID>. The "Provider ID Series" registry created in [Section 11.1.1](#) initially contains the entries shown in Figure 1.

Reason for Need: Identifies how to interpret the Data Provider ID. The combination of ProviderIDSeries and ProviderID MUST be globally unique.

How Used by Call Taker: Determines which provider ID registry to consult for more information.

Name	Source	URL
NENA	National Emergency Number Association	http://www.nena.org
EENA	European Emergency Number Association	http://www.eena.org
domain	(The ID is a fully qualified domain name)	(not applicable)

Figure 1: Provider ID Series Registry

4.1.4. Type of Data Provider

Data Element: Type of Data Provider

Use: Required

XML Element: <TypeOfProvider>

Description: Identifies the type of data provider supplying the data. The registry containing all valid values is created in [Section 11.1.5](#), and the initial set of values is shown in Figure 2.

Reason for Need: Identifies the category of data provider.

How Used by Call Taker: This information can be helpful when deciding whom to contact when further information is needed.

Token	Description
Client	Originating client/device
Access Network Provider	Access network service provider
Telecom Provider	Telecom service provider (including native and over-the-top VoIP services)
Telematics Provider	A sensor-based service provider, especially vehicle based
Language Translation Provider	A spoken language translation service
Emergency Service Provider	An emergency service provider conveying information to another emergency service provider
Emergency Modality Translation	An emergency-call-specific modality translation service, e.g., for sign language
Relay Provider	An interpretation service, e.g., video relay for sign language interpretation
Other	Any other type of service provider

Figure 2: Type of Data Provider Registry

4.1.1.5. Data Provider Contact URI

Data Element: Data Provider Contact URI

Use: Required

XML Element: <ContactURI>

Description: When provided by a service provider or an access network provider, this information is expected to be a URI to a 24/7 support organization tasked to provide PSAP support for this emergency call. When provided by a device, this MUST be the contact information of the user or owner of the device. (Ideally, this is the contact information of the device user, but when the

owner and user are separate (e.g., the device owner is an organization), this MAY be the contact information of the owner.) The Data Provider Contact URI SHOULD be a tel URI [RFC3966] in E.164 format and fully specified with a country code. If a tel URI is not available, a generic SIP URI is acceptable. Note that this contact information is not used by PSAPs for callbacks (a call from a PSAP directly related to a recently terminated emergency call, placed by the PSAP using a SIP Priority header field set to 'psap-callback', as described in [RFC7090]).

Reason for Need: Additional data providers might need to be contacted in error cases or other unusual circumstances.

How Used by Call Taker: To contact the supplier of the additional data for assistance in handling the call.

4.1.6. Data Provider Language(s) Supported

Data Element: Data Provider Language(s) supported

Use: Required

XML Element: <Language>

Description: This field encodes the language used by the entity at the Data Provider Contact URI. The content of this field consists of a single token from the Language Subtag Registry, which can be found at [LanguageSubtagRegistry], and is defined in [RFC5646]. Multiple instances of this element MAY occur, but the order is significant and the preferred language SHOULD appear first. The content MUST reflect the languages supported at the contact URI.

(Note that this field informs the PSAP of the language(s) used by the data provider. If the PSAP needs to contact the data provider, it can be helpful to know in advance the language(s) used by the data provider. If the PSAP uses a communication protocol to reach the data provider, that protocol might have language facilities of its own (such as the 'language' media feature tag, defined in RFC 3840 [RFC3840], and the more extensive language negotiation mechanism proposed in [HUMAN-LANG]), and if so, those are independent of this field.)

Reason for Need: This information indicates if the emergency service authority can directly communicate with the service provider or if an interpreter will be needed.

How Used by Call Taker: If the call taker cannot speak any language supported by the service provider, a translation service will need to be added to the conversation. Alternatively, other persons at the PSAP, besides the call taker, might be consulted for help (depending on the urgency and the type of interaction).

4.1.7. xCard of Data Provider

Data Element: xCard of Data Provider

Use: Optional

XML Element: <DataProviderContact>

Description: Per [RFC6351], the xCard structure is represented within a <vcard> element. Although multiple <vcard> elements can be contained in a structure, only one <vcard> element SHOULD be provided. If more than one appears, the first SHOULD be used. There are many fields in the xCard, and the creator of the data structure is encouraged to provide all available information. N, ORG, ADR, TEL, and EMAIL are suggested at a minimum. N SHOULD contain the name of the support group or device owner as appropriate. If more than one TEL property is provided, a parameter from the "vCard Property Values" registry SHOULD be specified for each TEL. For encoding of the vCard, this specification uses the XML-based encoding specified in [RFC6351], which is referred to in this document as 'xCard'.

Reason for Need: Information needed to determine additional contact information.

How Used by Call Taker: Assists the call taker by providing additional contact information aside from what is included in the SIP INVITE or the PIDF-LO.

4.1.8. Subcontractor Principal

When the entity providing the data is a subcontractor, the Data Provider Type is set to that of the primary service provider, and this entry is supplied to provide information regarding the subcontracting entity.

Data Element: Subcontractor Principal

Use: Conditional. This data is required if the entity providing the data is a subcontractor.

XML Element: <SubcontractorPrincipal>

Description: Some providers outsource their obligations to handle aspects of emergency services to specialized providers. If the data provider is a subcontractor to another provider, this element contains the DataProviderString of the service provider to indicate which provider the subcontractor is working for.

Reason for Need: Identify the entity the subcontractor works for.

How Used by Call Taker: Allows the call taker to understand what the relationship is between data providers and the service providers in the path of the call.

4.1.9. Subcontractor Priority

Data Element: Subcontractor Priority

Use: Conditional. This data is required if the entity providing the data is a subcontractor.

XML Element: <SubcontractorPriority>

Description: If the subcontractor is supposed to be contacted first, then this element MUST have the value 'sub'. If the provider the subcontractor is working for is supposed to be contacted first, then this element MUST have the value 'main'.

Reason for Need: Inform the call taker whom to contact first, if support is needed.

How Used by Call Taker: To decide which entity to contact first if assistance is needed.

4.1.10. ProviderInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<ad:EmergencyCallData.ProviderInfo
  xmlns:ad="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
  <ad:DataProviderReference>string0987654321@example.org
  </ad:DataProviderReference>
  <ad:DataProviderString>Example VoIP Provider
  </ad:DataProviderString>
  <ad:ProviderID>urn:nena:companyid:ID123</ad:ProviderID>
  <ad:ProviderIDSeries>NENA</ad:ProviderIDSeries>
  <ad:TypeOfProvider>Telecom Provider</ad:TypeOfProvider>
  <ad:ContactURI>tel:+1-201-555-0123</ad:ContactURI>
  <ad:Language>en</ad:Language>
  <ad:DataProviderContact
    xmlns="urn:ietf:params:xml:ns:vccard-4.0">
```

```
<vcard>
  <fn><text>Hannes Tschofenig</text></fn>
  <n>
    <surname>Hannes</surname>
    <given>Tschofenig</given>
    <additional/>
    <prefix/>
    <suffix>Dipl. Ing.</suffix>
  </n>
  <bday><date>--0203</date></bday>
  <anniversary>
    <date-time>20090808T1430-0500</date-time>
  </anniversary>
  <gender><sex>M</sex></gender>
  <lang>
    <parameters><pref><integer>1</integer></pref>
    </parameters>
    <language-tag>de</language-tag>
  </lang>
  <lang>
    <parameters><pref><integer>2</integer></pref>
    </parameters>
    <language-tag>en</language-tag>
  </lang>
  <org>
    <parameters><type><text>work</text></type>
    </parameters>
    <text>Example VoIP Provider</text>
  </org>
  <adr>
    <parameters>
      <type><text>work</text></type>
      <label><text>Hannes Tschofenig
        Linnoitustie 6
        Espoo , Finland
        02600</text></label>
    </parameters>
    <pobox/>
    <ext/>
    <street>Linnoitustie 6</street>
    <locality>Espoo</locality>
    <region>Uusimaa</region>
    <code>02600</code>
    <country>Finland</country>
  </adr>
  <tel>
    <parameters>
      <type>
```



```

        <text>work</text>
        <text>voice</text>
    </type>
</parameters>
<uri>tel:+358 50 4871445</uri>
</tel>
<tel>
    <parameters>
        <type>
            <text>work</text>
            <text>main-number</text>
            <text>voice</text>
        </type>
    </parameters>
    <uri>tel:+358 50 5050505</uri>
</tel>
<email>
    <parameters><type><text>work</text></type>
</parameters>
    <text>hannes.tschofenig@nsn.com</text>
</email>
<geo>
    <parameters><type><text>work</text></type>
</parameters>
    <uri>geo:60.210796,24.812924</uri>
</geo>
<key>
    <parameters><type><text>home</text></type>
</parameters>
    <uri>
        http://www.example.com/key.asc
    </uri>
</key>
<tz><text>Finland/Helsinki</text></tz>
<url>
    <parameters><type><text>home</text></type>
</parameters>
    <uri>http://www.tschofenig.priv.at</uri>
</url>
</vcard>
</ad:DataProviderContact>
</ad:EmergencyCallData.ProviderInfo>

```

Figure 3: EmergencyCallData.ProviderInfo Example

4.2. Service Information

This block describes the service that the service provider provides to the caller. It SHOULD be included by all service providers in the path of the call. The MIME media type is 'application/EmergencyCallData.ServiceInfo+xml'.

4.2.1. Service Environment

Data Element: Service Environment

Use: Conditional. Required unless the 'ServiceType' value is 'wireless'.

XML Element: <ServiceEnvironment>

Description: This element indicates whether a call is from a business or residence. Currently, the only valid entries are 'Business', 'Residence', and 'Unknown', as shown in Figure 4. New values can be defined via the registry created in [Section 11.1.2](#).

Reason for Need: To provide context and a hint when determining equipment and manpower requirements.

How Used by Call Taker: Information can be used to provide context and a hint to assist in determining equipment and manpower requirements for emergency responders. This is non-authoritative; there are situations where the service provider does not know the type of service (e.g., anonymous prepaid service). The type of service does not necessarily reflect the nature of the premises (e.g., a business line installed in a residence or cellular service). The registry does not contain all possible values for all situations. Hence, this is at best advisory information, but since it mimics a similar capability in some current emergency calling systems (e.g., a field in the Automatic Location Information (ALI) used with legacy North American wireline systems), it is known to be valuable to PSAPs. The service provider uses its best information (such as a rate plan, facilities used to deliver service, or a service description) to determine the information and is not responsible for determining the actual characteristics of the location from which the call originated. Because the usefulness is unknown (and less clear) for cellular, this element is OPTIONAL for commercial mobile radio services (e.g., cellular) and REQUIRED otherwise.

Token	Description
Business	Business service
Residence	Residential service
Unknown	Type of service unknown (e.g., anonymous pre-paid service)

Figure 4: Service Environment Registry

4.2.2. Service Type

Data Element: Service Delivered by Provider to End User

Use: Required

XML Element: <ServiceType>

Description: This defines the type of service over which the call is placed (similar to the Class of Service delivered with legacy emergency calls in some regions). The implied mobility of this service cannot be relied upon. A registry is created in [Section 11.1.3](#). The initial set of values is shown in Figure 5. More than one value MAY be returned. For example, a VoIP inmate telephone service is a reasonable combination.

Reason for Need: Knowing the type of service can assist the PSAP in the handling of the call.

How Used by Call Taker: Call takers often use this information to determine what kinds of questions to ask callers and how much to rely on supportive information. As the information is not always available, and the registry is not all encompassing, this is at best advisory information, but since it mimics a similar capability in some legacy emergency calling systems, it is known to be valuable.

Name	Description
wireless	Wireless Telephone Service: Includes CDMA, GSM, Wi-Fi, WiMAX, and LTE (but not satellite)

coin	Fixed public pay/coin telephones: Any device operated by coin or credit card
one-way	One-way outbound service
temp	Soft dial tone/quick service/warm disconnect/suspended
MLTS-hosted	Hosted multi-line telephone system such as Centrex
MLTS-local	Local multi-line telephone system, including all PBXs, key systems, and Shared Tenant Services
sensor-unattended	These are devices that generate DATA ONLY. This is a one-way information transmit without interactive media.
sensor-attended	Devices that are supported by a monitoring service provider or that are capable of supporting interactive media
POTS	Wireline: Plain Old Telephone Service
OTT	An over-the-top service that provides communication over arbitrary Internet access (fixed, nomadic, mobile)
digital	Wireline non-OTT digital phone service
OPX	Off-premise extension
relay	A service where a human third-party agent provides additional assistance. This includes sign language relay/interpretation, telematics services that provide a human on the call, and similar services.

Figure 5: Service Delivered by Provider to End User Registry

The initial set of values has been collected from sources of currently used systems, including [NENA-02-010], [nc911], [NANP], and [LERG].

4.2.3. Service Mobility Environment

Data Element: Service Mobility Environment

Use: Required

XML Element: <ServiceMobility>

Description: This provides the service provider's view of the mobility of the caller's device. As the service provider might not know the characteristics of the actual device or access network used, the value should be treated as advisory and not be relied upon. A registry is created in [Section 11.1.4](#) with the initial valid entries shown in Figure 6.

Reason for Need: Knowing the service provider's belief of mobility can assist the PSAP with the handling of the call.

How Used by Call Taker: To determine whether to assume the location of the caller might change.

Token	Description
Mobile	The device is able to move at any time
Fixed	The device is not expected to move unless the service is relocated
Nomadic	The device is not expected to change its point of attachment while on a call
Unknown	No information is known about the service mobility environment for the device

Figure 6: Service Mobility Registry

4.2.4. EmergencyCallData.ServiceInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<svc:EmergencyCallData.ServiceInfo
  xmlns:svc="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo">
  <svc:DataProviderReference>2468.IBOC.MLTS.1359@example.org
</svc:DataProviderReference>
  <svc:ServiceEnvironment>Business</svc:ServiceEnvironment>
  <svc:ServiceType>MLTS-hosted</svc:ServiceType>
  <svc:ServiceMobility>Fixed</svc:ServiceMobility>
</svc:EmergencyCallData.ServiceInfo>
```

Figure 7: EmergencyCallData.ServiceInfo Example

4.3. Device Information

This block provides information about the device used to place the call. It SHOULD be provided by any service provider that knows what device is being used and by the device itself. The MIME media type is 'application/EmergencyCallData.DeviceInfo+xml'.

4.3.1. Device Classification

Data Element: Device Classification

Use: Optional

XML Element: <DeviceClassification>

Description: This data element defines the kind of device making the emergency call. If the device provides the data structure, the device information SHOULD be provided. If the service provider provides the structure and it knows what the device is, the service provider SHOULD provide the device information. Often the carrier does not know what the device is. It is possible to receive two Device Information blocks: one provided by the device and one from the service provider. This information describes the device, not how it is being used. This data element defines the kind of device making the emergency call. A registry is created in [Section 11.1.6](#) with the initial set of values as shown in Figure 8.

Reason for Need: The device classification implies the capability of the calling device and assists in identifying the meaning of the emergency call location information that is being presented. For example, does the device require human intervention to initiate a call, or is this call the result of programmed instructions? Does the calling device have the ability to update location or

condition changes? Is this device interactive or a one-way reporting device?

How Used by Call Taker: Can provide the call taker context regarding the caller, the capabilities of the calling device, or the environment in which the device is being used and can assist in understanding the location information and capabilities of the calling device. For example, a cordless handset might be outside or next door.

Token	Description
cordless	Cordless handset
fixed	Fixed phone
satellite	Satellite phone
sensor-fixed	Fixed (non-mobile) sensor/alarm device
desktop	Soft client on desktop PC
laptop	Soft client on laptop-type device
tablet	Soft client on tablet-type device
alarm-monitored	Alarm system
sensor-mobile	Mobile sensor device
aircraft	Aircraft telematics device
automobile	Automobile/cycle/off-road telematics
truck	Truck/construction telematics
farm	Farm equipment telematics
marine	Marine telematics
personal	Personal telematics device
feature-phone	Cellular feature phone (not smartphone)
smart-phone	Cellular smartphone (native)
smart-phone-app	Soft client app on smartphone
unknown-device	Soft client on unknown device type
game	Gaming console
text-only	Other text device
NA	Not Available

Figure 8: Device Classification Registry Initial Values

4.3.2. Device Manufacturer

Data Element: Device Manufacturer

Use: Optional

XML Element: <DeviceMfgr>

Description: The plain language name of the manufacturer of the device.

Reason for Need: Used by PSAP management for post-mortem investigation/resolution.

How Used by Call Taker: Probably not used by the call taker but by PSAP management.

4.3.3. Device Model Number

Data Element: Device Model Number

Use: Optional

XML Element: <DeviceModelNr>

Description: Model number of the device.

Reason for Need: Used by PSAP management for after-action investigation/resolution.

How Used by Call Taker: Probably not used by the call taker but by PSAP management.

4.3.4. Unique Device Identifier

Data Element: Unique Device Identifier

Use: Optional

XML Element: <UniqueDeviceID>

XML Attribute: <TypeOfDeviceID>

Description: A string that identifies the specific device (or the device's current Subscriber Identification Module (SIM)) making the call or creating an event. Note that more than one <UniqueDeviceID> can be present to supply more than one of the identifying values.

The <TypeOfDeviceID> attribute identifies the type of device identifier. A registry is created in [Section 11.1.7](#) with an initial set of values shown in Figure 9.

Reason for Need: Uniquely identifies the device (or, in the case of International Mobile Subscriber Identity (IMSI), a SIM), independent of any signaling identifiers present in the call signaling stream.

How Used by Call Taker: Probably not used by the call taker; might be used by PSAP management during an investigation. (For example, if a PSAP experiences repeated false/accidental calls and there is no callback number or it isn't usable, the PSAP might need to try to track down the device using various means, e.g., contacting service providers in the area.) In the case of handsets without current service, it might be possible to determine who last had service. Another example might be a disconnected call where the call taker believes there is a need for assistance but was not able to obtain a location or other information.

Example: `<UniqueDeviceID TypeOfDeviceID="SN">12345</UniqueDeviceID>`

Token	Description
MEID	Mobile Equipment Identifier (CDMA)
ESN	Electronic Serial Number (GSM)
MAC	Media Access Control Address (IEEE)
WiMAX	Device Certificate Unique ID
IMEI	International Mobile Equipment ID (GSM)
IMSI	International Mobile Subscriber ID (GSM)
UDI	Unique Device Identifier
RFID	Radio Frequency Identification
SN	Manufacturer Serial Number

Figure 9: Registry of Device Identifier Types

4.3.5. Device/Service-Specific Additional Data Structure

Data Element: Device/service-specific additional data structure

Use: Optional

XML Element: `<DeviceSpecificData>`

Description: A URI representing additional data whose schema is specific to the device or service that created it. (For example, a medical device or medical device monitoring service might have a defined set of medical data.) The URI, when dereferenced, MUST yield a data structure defined by the device/service-specific

additional data type value. Different data can be created by each classification, e.g., a data set created by a medical device.

Reason for Need: Provides device/service-specific data that can be used by the call taker and/or responders.

How Used by Call Taker: Provide information to guide call takers to select appropriate responders, give appropriate pre-arrival instructions to callers, and advise responders of what to be prepared for. May be used by responders to guide assistance provided.

4.3.6. Device/Service-Specific Additional Data Structure Type

Data Element: Type of device/service-specific additional data structure

Use: Conditional. MUST be provided when a device/service-specific additional data URI is provided.

XML Element: <DeviceSpecificType>

Description: A value from the registry defined in [Section 11.1.8](#) to describe the type of data located at the device/service-specific additional data structure. The initial values shown in Figure 10 currently only include IEEE 1512, which is the United States Department of Transportation (USDOT) model for traffic incidents.

Reason for Need: This data element allows identification of externally defined schemas, which might have additional data that can assist in emergency response.

How Used by Call Taker: This data element allows the end user (call taker or first responder) to know what type of additional data is available to aid in providing the needed emergency services.

Note: This mechanism is not appropriate for information specific to a location or a caller (person).

Token	Description	Specification
IEEE1512	Common Incident Management Message Set (USDOT model for traffic incidents)	IEEE 1512-2006

Figure 10: Device/Service Data Type Registry

The IEEE 1512-2006 specifications can be found at [[IEEE-1512-2006](#)].

4.3.7. EmergencyCallData.DeviceInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<dev:EmergencyCallData.DeviceInfo
  xmlns:dev="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo">
  <dev:DataProviderReference>d4b3072df.201409182208075@example.org
  </dev:DataProviderReference>
  <dev:DeviceClassification>fixed</dev:DeviceClassification>
  <dev:DeviceMfgr>Nokia</dev:DeviceMfgr>
  <dev:DeviceModelNr>Lumia 800</dev:DeviceModelNr>
  <dev:UniqueDeviceID TypeOfDeviceID="IMEI">35788104
  </dev:UniqueDeviceID>
</dev:EmergencyCallData.DeviceInfo>
```

Figure 11: EmergencyCallData.DeviceInfo Example

4.4. Owner/Subscriber Information

This block describes the owner of the device (if provided by the device) or the subscriber information (if provided by a service provider). The contact location is not necessarily the location of the caller or incident but is rather the nominal contact address. The MIME media type is 'application/EmergencyCallData.SubscriberInfo+xml'.

In some jurisdictions, some or all parts of the subscriber-specific information are subject to privacy constraints. These constraints vary but dictate which information can be displayed and logged. A general privacy indicator expressing a desire for privacy by the subscriber is provided. The interpretation of how this is applied is left to the receiving jurisdiction as the custodians of the local regulatory requirements. This matches an equivalent privacy flag provided in some legacy emergency call systems.

4.4.1. Subscriber Data Privacy Indicator

Attribute: 'privacyRequested', Boolean.

Use: Conditional. This attribute MUST be provided if the owner/subscriber information block is not empty.

Description: The subscriber data privacy indicator specifically expresses the subscriber's desire for privacy. In some jurisdictions, subscriber services can have a specific "Type of Service" that prohibits information, such as the name of the subscriber, from being displayed. This attribute is provided to

explicitly indicate whether the subscriber service includes such constraints. The interpretation of this indicator is left to each jurisdiction (in keeping with the semantics of the privacy indicator provided in some legacy emergency call systems). Because the interpretation of this indicator varies based on local regulations, this document cannot describe the exact semantics nor indicate which fields are affected (the application of this indicator might affect the display of data contained in any of the blocks).

Reason for Need: Some jurisdictions require subscriber privacy to be observed when processing emergency calls.

How Used by Call Taker: Where privacy is indicated, the call taker might not have access to some aspects of the subscriber information.

4.4.2. xCard for Subscriber's Data

Data Element: xCard for Subscriber's Data

Use: Conditional. Subscriber data MUST be provided unless it is not available. Some services, such as prepaid phones, non-initialized phones, etc., do not have information about the subscriber.

XML Element: <SubscriberData>

Description: Information known by the service provider or device about the subscriber, e.g., Name, Address, Individual Telephone Number, Main Telephone Number, and any other data. <n>, <org> (if appropriate), <adr>, <tel>, and <email> are suggested at a minimum. If more than one <tel> property is provided, a parameter from the "vCard Property Values" registry MUST be specified on each <tel>. While some data (such as <anniversary>) might not seem obviously relevant for emergency services, any data is potentially useful in some emergency circumstances.

Reason for Need: When the caller is unable to provide information, this data can be used to obtain it.

How Used by Call Taker: Obtaining critical information about the caller and possibly the location when it is not able to be obtained otherwise. While the location here is not necessarily that of a caller, in some circumstances it can be helpful in locating the caller when other means have failed.

4.4.3. EmergencyCallData.SubscriberInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<sub:EmergencyCallData.SubscriberInfo
  xmlns:sub=
    "urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
  privacyRequested="false">
  <sub:DataProviderReference>FEABFECD901@example.org
</sub:DataProviderReference>
  <sub:SubscriberData xmlns="urn:ietf:params:xml:ns:vcard-4.0">
    <vcard>
      <fn><text>Simon Perreault</text></fn>
      <n>
        <surname>Perreault</surname>
        <given>Simon</given>
        <additional/>
        <prefix/>
        <suffix>ing. jr</suffix>
        <suffix>M.Sc.</suffix>
      </n>
      <bday><date>--0203</date></bday>
      <anniversary>
        <date-time>20090808T1430-0500</date-time>
      </anniversary>
      <gender><sex>M</sex></gender>
      <lang>
        <parameters><pref><integer>1</integer></pref>
        </parameters>
        <language-tag>fr</language-tag>
      </lang>
      <lang>
        <parameters><pref><integer>2</integer></pref>
        </parameters>
        <language-tag>en</language-tag>
      </lang>
      <org>
        <parameters><type><text>work</text></type>
        </parameters>
        <text>Viagenie</text>
      </org>
      <adr>
        <parameters>
          <type><text>work</text></type>
          <label><text>Simon Perreault
            2875 boul. Laurier, suite D2-630
            Quebec, QC, Canada
            G1V 2M2</text></label>
        </parameters>
```

```
<pobox/>
<ext/>
<street>2875 boul. Laurier,
      suite D2-630</street>
<locality>Quebec</locality>
<region>QC</region>
<code>G1V 2M2</code>
<country>Canada</country>
</adr>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
    </type>
  </parameters>
  <uri>tel:+1-418-656-9254;ext=102</uri>
</tel>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
      <text>main-number</text>
    </type>
  </parameters>
  <uri>tel:+1-418-555-0000</uri>
</tel>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>text</text>
      <text>voice</text>
      <text>cell</text>
      <text>video</text>
    </type>
  </parameters>
  <uri>tel:+1-418-262-6501</uri>
</tel>
<email>
  <parameters><type><text>work</text></type>
</parameters>
  <text>simon.perreault@viagenie.ca</text>
</email>
<geo>
  <parameters><type><text>work</text></type>
</parameters>
```

```

        <uri>geo:46.766336,-71.28955</uri>
    </geo>
    <key>
        <parameters><type><text>work</text></type>
        </parameters>
        <uri>
http://www.viagenie.ca/simon.perreault/simon.asc
        </uri>
    </key>
    <tz><text>America/Montreal</text></tz>
    <url>
        <parameters><type><text>home</text></type>
        </parameters>
        <uri>http://nomis80.org</uri>
    </url>
</vcard>
</sub:SubscriberData>
</sub:EmergencyCallData.SubscriberInfo>

```

Figure 12: EmergencyCallData.SubscriberInfo Example

4.5. Comment

This block provides a mechanism for the data provider to supply extra, human-readable information to the PSAP. It is not intended for a general purpose extension mechanism nor does it aim to provide machine-readable content. The MIME media type is 'application/EmergencyCallData.Comment+xml'.

4.5.1. Comment

Data Element: EmergencyCallData.Comment

Use: Optional

XML Element: <Comment>

Description: Human-readable text providing additional information to the PSAP staff.

Reason for Need: Explanatory information for values in the data structure.

How Used by Call Taker: To interpret the data provided.

4.5.2. EmergencyCallData.Comment Example

```
<?xml version="1.0" encoding="UTF-8"?>
<com:EmergencyCallData.Comment
  xmlns:com="urn:ietf:params:xml:ns:EmergencyCallData:Comment">
  <com:DataProviderReference>string0987654321@example.org
</com:DataProviderReference>
  <com:Comment xml:lang="en">This is an example text.</com:Comment>
</com:EmergencyCallData.Comment>
```

Figure 13: EmergencyCallData.Comment Example

5. Issues with Getting New Types of Data into Use

This document describes two mechanisms that allow extension of the kind of data provided with an emergency call: define a new block or define a new device/service-specific additional data URL for the DeviceInfo block (Section 4.3.5). While defining new data types and getting a new device or application to send the new data might be easy, getting PSAPs and responders to actually retrieve the data and use it will be difficult. New mechanism providers should understand that acquiring and using new forms of data usually require software upgrades at the PSAP and/or responders, as well as training of call takers and responders in how to interpret and use the information. Legal and operational review might also be needed. Overwhelming a call taker or responder with too much information is highly discouraged. Thus, the barrier to supporting new data is quite high.

The mechanisms this document describes are meant to encourage development of widely supported, common data formats for classes of devices. If all manufacturers of a class of device use the same format, and the data can be shown to improve outcomes, then PSAPs and responders can be encouraged to upgrade their systems and train their staff to use the data. Variations, however well intentioned, are unlikely to be supported.

Implementors should consider that data from sensor-based devices in some cases might not be useful to call takers or PSAPs (and privacy, liability, or other considerations might preclude the PSAP from accessing or handling the data) but might be of use to responders. Each data item provided with the call in conformance with this document can be accessed by responders or other entities in the emergency services, whether or not the data is accessed by the PSAP.

5.1. Choosing between Defining a New Type of Block or a New Type of Device/Service-Specific Additional Data

For devices that have device- or service-specific data, there are two choices to carry it. A new block can be defined, or the device/service-specific additional data URL in the DeviceInfo block can be used and a new type defined for it. The data passed would likely be the same in either case. Considerations for choosing the mechanism under which to register include:

Applicability: Information that will be supported by many kinds of devices or services are more appropriately defined as separate blocks.

Privacy: Information sent as a device/service-specific additional data URL in the DeviceInfo block is by reference (not by value), which inherently provides some additional privacy protection (since the requester needs to supply a certificate which is verified by the supplier).

Size: Information that can be very large might be better sent in the DeviceInfo block, rather than in a new block, so that implementations are unable to send the data by value. Conversely, data that is small might best be sent in a separate block so that it can be sent by value.

Availability of a server: Providing the data via the DeviceInfo block requires that a server be available from which to retrieve the data. Providing the data via a new block allows it to be sent by value.

6. Data Transport Mechanisms

This section defines how to convey additional data to an emergency service provider. Two different means are specified: the first uses call signaling; the second uses the <provided-by> element of a PIDF-LO [RFC4119].

1. First, the ability to embed a Uniform Resource Identifier (URI) in an existing SIP header field, the Call-Info header field, is defined. The URI points to the additional data structure. The Call-Info header field is specified in [Section 20.9 of \[RFC3261\]](#).

This document adds a new compound token starting with the value 'EmergencyCallData' for the Call-Info 'purpose' parameter. If the 'purpose' parameter is set to a value starting with 'EmergencyCallData', then the Call-Info header field contains either an HTTPS URL pointing to an external resource or a Content

Indirection (CID) URI that allows the data structure to be placed in the body of the SIP message. The 'purpose' parameter also indicates the kind of data (by its MIME media subtype) that is available at the URI.

As the data is conveyed using a URI in the SIP signaling, the data itself can reside on an external resource or can be contained within the body of the SIP message. When the URI refers to data at an external resource, the data is said to be passed by reference. When the URI refers to data contained within the body of the SIP message, the data is said to be passed by value. A PSAP or emergency responder is able to examine the type of data provided and selectively access the data it is interested in, while forwarding all of it (the values or references) to downstream entities.

To be conveyed in a SIP body, additional data about a call is defined as a series of MIME objects (also referred to as a "block" of data). Each block defined in this document is an XML data structure identified by its MIME media type. (Blocks defined by others can be encoded in XML or not, as identified by their MIME registration.) As usual, whenever more than one MIME part is included in the body of a message, MIME multipart (i.e., 'multipart/mixed') encloses them all.

This document defines a set of XML schemas and MIME media types used for each block defined here. When additional data is passed by value in the SIP signaling, each CID URL points to one block in the body. Multiple URIs are used within a Call-Info header field (or multiple Call-Info header fields) to point to multiple blocks. When additional data is provided by reference (in SIP signaling or the <provided-by> element of a PIDF-LO), each HTTPS URL references one block; the data is retrieved with an HTTPS GET operation, which returns the block as an object (the blocks defined here are returned as XML objects).

2. Second, the ability to embed additional data structures in the <provided-by> element of a PIDF-LO [RFC4119] is defined.

In addition to service providers in the call path, the access network provider generally has similar information that can be valuable to the PSAP. When the access network provider and service provider are separate entities, the access network does not participate in the application-layer signaling (and hence cannot add a Call-Info header field to the SIP message) but can provide location information in a PIDF-LO. When the access network provider supplies location information in the form of a PIDF-LO from a location server via a location configuration

protocol, it has the ability to add the data structures defined in this document (or references to them) within the PIDF-LO.

The data in these data structures is not specific to the location itself, but rather provides descriptive information having to do with the immediate circumstances about the provider's provision of the location (e.g., the identity of the access network provider, how to contact that entity, what kind of service the access network provides, subscriber information, etc.). This data is similar in nearly every respect to the data known by service providers in the path of the call. The <provided-by> element of the PIDF-LO is a mechanism for the access network provider to supply the information. This document describes a namespace per [RFC4119] for inclusion in the <provided-by> element of a PIDF-LO for adding information known to the access network provider. The access network provider SHOULD provide additional data within a <provided-by> element of a PIDF-LO it returns for emergency use (e.g., if requested with an HTTP-Enabled Location Delivery (HELD) 'responseTime' attribute of 'emergencyRouting' or 'emergencyDispatch' [RFC5985]).

One or more blocks of data registered in the "Emergency Call Additional Data" registry, as defined in [Section 11.1.9](#), can be included or referenced in the SIP signaling (using the Call-Info header field) or in the <provided-by> element of a PIDF-LO. For interoperability, only blocks in the registry are permitted to be sent using the mechanisms specified in this document. Since multiple entities are expected to provide sets of data, the data itself needs information describing the source. Consequently, each entity adding additional data MUST supply a 'Data Provider' block. All other blocks are optional, but each entity SHOULD supply all blocks where it has at least some of the information in the block.

Note that, as with any mechanism, failures are possible. For example, a block (provided by value or by reference) might not be the type indicated by the 'purpose' parameter, or might be badly formed, etc. The general principle that applies to emergency calls is that it is more important for the call to go through than for everything to be correct. Thus, most PSAPs will process a call if at all possible, even if data is missing or other failures occur.

6.1. Transmitting Blocks Using Call-Info

A URI to a block MAY be inserted in any SIP request or response method (most often INVITE or MESSAGE), using a Call-Info header field containing a 'purpose' value starting with 'EmergencyCallData', a dot ('.'), and the type of data available at the URI. The type of data is denoted by including the root of the MIME media subtype (the 'EmergencyCallData' prefix is not repeated), omitting any suffix such as '+xml'. For example, when referencing a block with MIME media type 'application/EmergencyCallData.ProviderInfo+xml', the 'purpose' parameter is set to 'EmergencyCallData.ProviderInfo'. An example Call-Info header field for this would be:

```
Call-Info: https://www.example.com/23sedde3;  
          purpose="EmergencyCallData.ProviderInfo"
```

A Call-Info header field with a 'purpose' value starting with 'EmergencyCallData' only has meaning in the context of an emergency call (as ascertained by the presence of an emergency service URN in a Request-URI header field of a SIP message), test emergency calls (using an appropriate service URN), and some private-use calls where the endpoints have a preexisting relationship and privacy concerns do not apply because of the relationship; use in other contexts is undefined and is likely to unnecessarily expose confidential data.

If the data is provided by reference, an HTTPS URI MUST be included, and consequently, Transport Layer Security (TLS) protection is used during the retrieval of the information.

The data can also be supplied by value in any SIP request or response method that is permitted to contain a body (i.e., not a BYE request) [RFC3261]. In this case, CID [RFC2392] is used, with the CID URL referencing the MIME body part containing the data. Note that [RFC3261] forbids proxies from altering message bodies, so entities in the call path that add blocks by value need to do so using an appropriate SIP entity (e.g., a back-to-back user agent).

Transmitting data by value is especially useful in certain cases, such as when the data exists in or is generated by the originating device but is not intended for very large data blocks. Additional security and privacy considerations apply to data transmitted by value, as discussed in Sections 9 and 10, respectively.

More than one Call-Info header field with a 'purpose' value starting with 'EmergencyCallData' can be expected, but at least one MUST be provided. The device MUST provide one unless it knows that a service provider is in the path of the call. The device MAY insert one if it uses a service provider. Each service provider in the path of an

emergency call MUST insert its own. For example, a device, a telematics service provider in the call path, as well as the mobile carrier handling the call will each provide one. There might be circumstances where there is a service provider who is unaware that the call is an emergency call and cannot reasonably be expected to determine that it is an emergency call. In that case, that service provider is not expected to provide EmergencyCallData.

When blocks are transmitted by value, the 'purpose' parameter in a Call-Info header field identifies the data, and the CID URL points to the data block in the body (which has a matching Content-ID body part header field). When a data block is carried in a signed or encrypted body part, the enclosing multipart (e.g., 'multipart/signed' or 'multipart/encrypted') has the same Content-ID as the data part. This allows an entity to identify and access the data blocks it is interested in without having to dive deeply into the message structure or decrypt parts it is not interested in.

6.2. Transmitting Blocks by Reference Using the <provided-by> Element

The <EmergencyCallDataReference> element is used to transmit an additional data block by reference within a <provided-by> element of a PIDF-LO. The <EmergencyCallDataReference> element has two attributes: 'ref' to specify the URL and 'purpose' to indicate the type of data block referenced. The value of 'ref' is an HTTPS URL that resolves to a data structure with information about the call. The value of 'purpose' is the same as used in a Call-Info header field (as specified in [Section 6.1](#)).

For example, to reference a block with MIME media type 'application/EmergencyCallData.ProviderInfo+xml', the 'purpose' parameter is set to 'EmergencyCallData.ProviderInfo'. An example <EmergencyCallDataReference> element for this would be:

```
<EmergencyCallDataReference ref="https://www.example.com/23sedde3"
  purpose="EmergencyCallData.ProviderInfo"/>
```

The <EmergencyCallDataReference> element transmits one data block; multiple data blocks are transmitted by using multiple <EmergencyCallDataReference> elements. Multiple <EmergencyCallDataReference> elements MAY be included as child elements inside the <provided-by> element.

The following is a simplified example:

```
<provided-by>
  <EmergencyCallDataReference
    purpose="EmergencyCallData.ServiceInfo"
    ref="https://example.com/ref2" />

  <EmergencyCallDataReference
    purpose="EmergencyCallData.ProviderInfo"
    ref="https://example.com/ref3" />

  <EmergencyCallDataReference
    purpose="EmergencyCallData.Comment"
    ref="https://example.com/ref4" />
</provided-by>
```

Example <provided-by> by Reference

For an example in context, Figure 18 shows a PIDF-LO example with an <EmergencyCallDataReference> element pointing to an EmergencyCallData.ServiceInfo data block with the URL in the 'ref' attribute and the 'purpose' attribute set to 'EmergencyCallData.ServiceInfo'.

6.3. Transmitting Blocks by Value Using the <provided-by> Element

It is RECOMMENDED that access networks supply the data specified in this document by reference, because PIDF-LOs can be fetched by a client or other entity and stored locally, so providing the data by value risks exposing private information to a larger audience.

The <EmergencyCallDataValue> element is used to transmit one or more additional data blocks by value within a <provided-by> element of a PIDF-LO. Each block being transmitted is placed (as a child element) inside the <EmergencyCallDataValue> element. (The same XML structure as would be contained in the corresponding MIME media type body part is placed inside the <EmergencyCallDataValue> element.) Multiple <EmergencyCallDataValue> elements MAY be included as child elements in the <provided-by> element.

The following is a simplified example:

```
<provided-by>

  <EmergencyCallDataValue>

    <EmergencyCallData.ProviderInfo
      xmlns=
        "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
      <DataProviderReference>flurbit735@es.example.com
        </DataProviderReference>
      <DataProviderString>Access Network Examples, Inc.
        </DataProviderString>
      <ProviderID>urn:nena:companyid:Test</ProviderID>
      <ProviderIDSeries>NENA</ProviderIDSeries>
      <TypeOfProvider>Access Network Provider
        </TypeOfProvider>
      <ContactURI>tel:+1-555-555-0897</ContactURI>
      <Language>en</Language>
    </EmergencyCallData.ProviderInfo>

    <EmergencyCallData.Comment
      xmlns=
        "urn:ietf:params:xml:ns:EmergencyCallData:Comment">
      <DataProviderReference>flurbit735@es.example.com
        </DataProviderReference>
      <Comment xml:lang="en">This is an example text.
        </Comment>
    </EmergencyCallData.Comment>

  </EmergencyCallDataValue>

</provided-by>
```

Example <provided-by> by Value

For an example in context, Figure 18 shows a PIDF-LO example that contains a <provided-by> element with the <EmergencyCallData.ProviderInfo> and the <EmergencyCallData.Comment> elements as child elements of an <EmergencyCallDataValue> element.

6.4. The Content-Disposition Parameter

[RFC 5621](#) [[RFC5621](#)] discusses the handling of message bodies in SIP. It updates and clarifies handling originally defined in [RFC 3261](#) [[RFC3261](#)] based on implementation experience. While [RFC 3261](#) did not mandate support for 'multipart' message bodies, 'multipart/mixed' MIME bodies are used by many extensions (including this document)

today. For example, adding a PIDF-LO, a Session Description Protocol (SDP), and additional data in the body of a SIP message requires a 'multipart' message body.

[RFC 3204](#) [[RFC3204](#)] and [RFC 3459](#) [[RFC3459](#)] define the 'handling' parameter for the Content-Disposition header field. These RFCs describe how a User Agent Server (UAS) reacts if it receives a message body whose content type or disposition type it does not understand. If the 'handling' parameter has the value 'optional', the UAS ignores the message body. If the 'handling' parameter has the value 'required', the UAS returns a 415 (Unsupported Media Type) response. The 'by-reference' disposition type of [RFC 5621](#) [[RFC5621](#)] allows a SIP message to contain a reference to the body part, and the SIP User Agent (UA) processes the body part according to the reference. This is the case for a Call-Info header field containing a CID URL.

As an example, a SIP message indicates the 'Content-Disposition' parameter in the body of the SIP message as shown in Figure 14.

```
Content-Type: application/sdp
...Omit Content-Disposition here; defaults are ok

...SDP goes in here

--boundary1
Content-Type: application/pidf+xml
Content-ID: <target123@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

...PIDF-LO goes in here

--boundary1
Content-Type: application/EmergencyCallData.ProviderInfo+xml
Content-ID: <1234567890@atlanta.example.com>
Content-Disposition: by-reference; handling=optional

...Data provider information data goes in here

--boundary1--
```

Figure 14: Example for Use of the Content-Disposition Parameter in SIP

7. Examples

This section illustrates a longer and more complex example, as shown in Figure 15. In this example, additional data is added by the end device, included by the VoIP provider, and provided by the access network provider (via the PIDF-LO).

```

O  +-----+      [=====]      [=====]
/|\  | UA |      [ Access  ]      [ VoIP    ]
|    +-----+      [ Network]      [ Provider]
/ \   [ Provider ]      [ example.org ]
      [           ]      [           ]
(1)   [           ] (2)   [           ]
Emergency Call [           ] Emergency Call [           ]
----->
+Device Info   [           ] +Device Info   [           ]
+Data Prov. Info [ ^       ] +Data Provider Info [ |       ]
+Location URI   [=====] +Location URI   [=====]
      .
      .
+Location      . [=====]
+Owner/Subscriber Info . [           ] (3)
+Device Info   . (4) [           ] <-----+
+Data Provider Info #3 .....>           ] Emergency Call
      [           ] +Device Info
      [ PSAP      ] +Data Prov. Info #2
      [           ] +Location URI
      [=====]

```

Legend:

```

--- Emergency Call Setup Procedure
... Location Retrieval/Response

```

Figure 15: Additional Data Example Flow

The example scenario starts with the end device itself adding device information, owner/subscriber information, a location URI, and data provider information to the outgoing emergency call setup message (see step #1 in Figure 15). The SIP INVITE example is shown in Figure 16.

```

INVITE urn:service:sos SIP/2.0
Via: SIPs/2.0/TLS server.example.com;branch=z9hG4bK74bf9
Max-Forwards: 70
To: <urn:service:sos>
From: Hannes Tschofenig <sips:hannes@example.com>;tag=9fxced76sl
Call-ID: 3848276298220188511@example.com
Call-Info: <http://www.example.com/hannes/photo.jpg>
           ;purpose=icon,
           <http://www.example.com/hannes/> ;purpose=info,
           <cid:1234567890@atlanta.example.com>
           ;purpose=EmergencyCallData.ProviderInfo,
           <cid:0123456789@atlanta.example.com>
           ;purpose=EmergencyCallData.DeviceInfo
Geolocation: <https://ls.example.net:9768/357yc6s64ceyoiuy5ax3o>
Geolocation-Routing: yes
Accept: application/sdp, application/pidf+xml,
       application/EmergencyCallData.ProviderInfo+xml
CSeq: 31862 INVITE
Contact: <sips:hannes@example.com>
Content-Type: multipart/mixed; boundary=boundary1
Content-Length: ...

--boundary1
Content-Type: application/sdp

...SDP goes here

--boundary1
Content-Type: application/EmergencyCallData.DeviceInfo+xml
Content-ID: <0123456789@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

<?xml version="1.0" encoding="UTF-8"?>
<dev:EmergencyCallData.DeviceInfo
  xmlns:dev=
    "urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo">
  <dev:DataProviderReference>
    d4b3072df09876543@[93.184.216.119]
  </dev:DataProviderReference>
  <dev:DeviceClassification>laptop</dev:DeviceClassification>
  <dev:UniqueDeviceID
    TypeOfDeviceID="MAC">00-0d-4b-30-72-df

```

```

        </dev:UniqueDeviceID>
    </dev:EmergencyCallData.DeviceInfo>

--boundary1
Content-Type: application/EmergencyCallData.ProviderInfo+xml
Content-ID: <1234567890@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

<?xml version="1.0" encoding="UTF-8"?>
<pi:EmergencyCallData.ProviderInfo
  xmlns:pi=
    "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
  <pi:DataProviderReference>d4b3072df09876543@[93.184.216.119]
    </pi:DataProviderReference>
  <pi:DataProviderString>Hannes Tschofenig</pi:DataProviderString>
  <pi:TypeOfProvider>Client</pi:TypeOfProvider>
  <pi:ContactURI>tel:+1-555-555-0123</pi:ContactURI>
  <pi:Language>en</pi:Language>
  <pi:DataProviderContact
    xmlns="urn:ietf:params:xml:ns:vcard-4.0">
    <vcard>
      <fn><text>Hannes Tschofenig</text></fn>
      <n>
        <surname>Hannes</surname>
        <given>Tschofenig</given>
        <additional/>
        <prefix/>
        <suffix>Dipl. Ing.</suffix>
      </n>
      <bday><date>--0203</date></bday>
      <anniversary>
        <date-time>20090808T1430-0500</date-time>
      </anniversary>
      <gender><sex>M</sex></gender>
      <lang>
        <parameters><pref><integer>1</integer></pref>
      </parameters>
      <language-tag>de</language-tag>
    </lang>
    <lang>
      <parameters><pref><integer>2</integer></pref>
    </parameters>
    <language-tag>en</language-tag>
  </lang>
  <adr>
    <parameters>
      <type><text>work</text></type>
      <label><text>Hannes Tschofenig

```

```
        Linnoitustie 6
        Espoo, Finland
        02600</text></label>
    </parameters>
    <pobox/>
    <ext/>
    <street>Linnoitustie 6</street>
    <locality>Espoo</locality>
    <region>Uusimaa</region>
    <code>02600</code>
    <country>Finland</country>
</adr>
<adr>
    <parameters>
        <type><text>home</text></type>
        <label><text>Hannes Tschofenig
            c/o Hotel DuPont
            42 W 11th St
            Wilmington, DE 19801
            USA</text></label>
    </parameters>
    <pobox/>
    <ext/>
    <street>42 W 11th St</street>
        <locality>Wilmington</locality>
        <region>DE</region>
        <code>19801</code>
        <country>USA</country>
</adr>
<tel>
    <parameters>
        <type>
            <text>work</text>
            <text>voice</text>
        </type>
    </parameters>
    <uri>tel:+358 50 4871445</uri>
</tel>
<tel>
    <parameters>
        <type>
            <text>home</text>
            <text>voice</text>
        </type>
    </parameters>
    <uri>tel:+1-555-555-0123</uri>
</tel>
<tel>
```

```

        <parameters>
          <type>
            <text>work</text>
            <text>voice</text>
            <text>main-number</text>
          </type>
        </parameters>
        <uri>tel:+1-302-594-3100</uri>
      </tel>
      <email>
        <parameters><type><text>work</text></type>
        </parameters>
        <text>hannes.tschofenig@nsn.com</text>
      </email>
      <geo>
        <parameters><type><text>work</text></type>
        </parameters>
        <uri>geo:60.210796,24.812924</uri>
      </geo>
      <geo>
        <parameters><type><text>home</text></type>
        </parameters>
        <uri>geo:39.746537,-75.548027</uri>
      </geo>
      <key>
        <parameters>
          <type><text>home</text></type>
        </parameters>
        <uri>https://www.example.com/key.asc</uri>
      </key>
      <tz><text>Finland/Helsinki</text></tz>
      <url>
        <parameters><type><text>home</text></type>
        </parameters>
        <uri>http://example.com/hannes.tschofenig
        </uri>
      </url>
    </vcard>
  </pi:DataProviderContact>
</pi:EmergencyCallData.ProviderInfo>
--boundary1--

```

Figure 16: End Device Sending SIP INVITE with Additional Data

In this example, information available to the access network provider is included in the call setup message only indirectly via the use of the location reference. The PSAP has to retrieve it via a separate lookup step. Since the access network provider and the VoIP service

provider are two independent entities in this scenario, the access network provider is not involved in application-layer exchanges; the SIP INVITE transits the access network transparently, as illustrated in steps #1 and #2 (the access network does not alter the SIP INVITE).

The VoIP service provider receives the message and determines, based on the service URN, that the incoming request is an emergency call. It performs typical emergency-services-related tasks (such as location-based routing) and adds additional data, namely service and subscriber information as well as data provider information #2, to the outgoing message. For the example, we assume a VoIP service provider deploys a back-to-back user agent allowing additional data to be included in the body of the SIP message (rather than by reference), which allows us to illustrate the use of multiple data provider info blocks. The resulting message is shown in Figure 17. The SIP INVITE is sent to the PSAP in step #3.

```

INVITE sips:psap@example.org SIP/2.0
Via: SIP/2.0/TLS server.example.com;branch=z9hG4bK74bf9
Max-Forwards: 70
To: <urn:service:sos>
From: Hannes Tschofenig <sips:hannes@example.com>;tag=9fxced76sl
Call-ID: 3848276298220188511@example.com
Call-Info: <http://www.example.com/hannes/photo.jpg>;
    purpose=icon,
    <http://www.example.com/hannes/>; purpose=info,
    <cid:1234567890@atlanta.example.com>;
    purpose=EmergencyCallData.ProviderInfo
    <cid:0123456789@atlanta.example.com>;
    purpose=EmergencyCallData.DeviceInfo
Call-Info: <cid:bloorpyhex@atlanta.example.com>;
    purpose=EmergencyCallData.ServiceInfo
Call-Info: <cid:aaabbb@atlanta.example.com>;
    purpose=EmergencyCallData.ProviderInfo
Geolocation: <https://ls.example.net:9768/357yc6s64ceyoiuy5ax3o>
Geolocation-Routing: yes
Accept: application/sdp, application/pidf+xml,
    application/EmergencyCallData.ProviderInfo+xml
CSeq: 31862 INVITE
Contact: <sips:hannes@example.com>
Content-Type: multipart/mixed; boundary=boundary1
Content-Length: ...

--boundary1
Content-Type: application/sdp

...SDP goes here

```

```
--boundary1
Content-Type: application/EmergencyCallData.DeviceInfo+xml
Content-ID: <0123456789@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

<?xml version="1.0" encoding="UTF-8"?>
<dev:EmergencyCallData.DeviceInfo
  xmlns:dev=
    "urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo">
  <dev:DataProviderReference>d4b3072df09876543@[93.184.216.119]
</dev:DataProviderReference>
  <dev:DeviceClassification>laptop</dev:DeviceClassification>
  <dev:UniqueDeviceID
    TypeOfDeviceID="MAC">00-0d-4b-30-72-df</dev:UniqueDeviceID>
</dev:EmergencyCallData.DeviceInfo>

--boundary1
Content-Type: application/EmergencyCallData.ProviderInfo+xml
Content-ID: <1234567890@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

<?xml version="1.0" encoding="UTF-8"?>
<pi:EmergencyCallData.ProviderInfo
  xmlns:pi=
    "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
  <pi:DataProviderReference>d4b3072df09876543@[93.184.216.119]
</pi:DataProviderReference>
  <pi:DataProviderString>Hannes Tschofenig
</pi:DataProviderString>
  <pi:TypeOfProvider>Client</pi:TypeOfProvider>
  <pi:ContactURI>tel:+1-555-555-0123</pi:ContactURI>
  <pi:Language>en</pi:Language>
  <pi:DataProviderContact
    xmlns="urn:ietf:params:xml:ns:vcard-4.0">
    <vcard>
      <fn><text>Hannes Tschofenig</text></fn>
      <n>
        <surname>Hannes</surname>
        <given>Tschofenig</given>
        <additional/>
        <prefix/>
        <suffix>Dipl. Ing.</suffix>
      </n>
      <bday><date>--0203</date></bday>
      <anniversary>
        <date-time>20090808T1430-0500</date-time>
      </anniversary>
      <gender><sex>M</sex></gender>
```

```
<lang>
  <parameters><pref><integer>1</integer></pref>
  </parameters>
  <language-tag>de</language-tag>
</lang>
<lang>
  <parameters><pref><integer>2</integer></pref>
  </parameters>
  <language-tag>en</language-tag>
</lang>
<adr>
  <parameters>
    <type><text>work</text></type>
    <label><text>Hannes Tschofenig
      Linnoitustie 6
      Espoo, Finland
      02600</text></label>
  </parameters>
  <pobox/>
  <ext/>
  <street>Linnoitustie 6</street>
  <locality>Espoo</locality>
  <region>Uusimaa</region>
  <code>02600</code>
  <country>Finland</country>
</adr>
<adr>
  <parameters>
    <type><text>home</text></type>
    <label><text>Hannes Tschofenig
      c/o Hotel DuPont
      42 W 11th St
      Wilmington, DE 19801
      USA</text></label>
  </parameters>
  <pobox/>
  <ext/>
  <street>42 W 11th St</street>
  <locality>Wilmington</locality>
  <region>DE</region>
  <code>19801</code>
  <country>USA</country>
</adr>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
```



```

        </type>
      </parameters>
      <uri>tel:+358 50 4871445</uri>
    </tel>
    <tel>
      <parameters>
        <type>
          <text>home</text>
          <text>voice</text>
        </type>
      </parameters>
      <uri>tel:+1-555-555-0123</uri>
    </tel>
    <email>
      <parameters><type><text>work</text></type>
      </parameters>
      <text>hannes.tschofenig@nsn.com</text>
    </email>
    <geo>
      <parameters><type><text>work</text></type>
      </parameters>
      <uri>geo:60.210796,24.812924</uri>
    </geo>
    <geo>
      <parameters><type><text>home</text></type>
      </parameters>
      <uri>geo:39.746537,-75.548027</uri>
    </geo>
    <key>
      <parameters>
        <type><text>home</text></type>
      </parameters>
      <uri>https://www.example.com/key.asc</uri>
    </key>
    <tz><text>Finland/Helsinki</text></tz>
    <url>
      <parameters><type><text>home</text></type>
      </parameters>
      <uri>http://example.com/hannes.tschofenig</uri>
    </url>
  </vcard>
</pi:DataProviderContact>
</pi:EmergencyCallData.ProviderInfo>

--boundary1
Content-Type: application/EmergencyCallData.ServiceInfo+xml
Content-ID: <bloorpyhex@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

```

```
<?xml version="1.0" encoding="UTF-8"?>
<svc:EmergencyCallData.ServiceInfo
  xmlns:svc=
    "urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo">
  <svc:DataProviderReference>string0987654321@example.org
</svc:DataProviderReference>
  <svc:ServiceEnvironment>Residence</svc:ServiceEnvironment>
  <svc:ServiceType>VOIP</svc:ServiceType>
  <svc:ServiceMobility>Unknown</svc:ServiceMobility>
</svc:EmergencyCallData.ServiceInfo>
```

--boundary1

Content-Type: application/EmergencyCallData.ProviderInfo+xml

Content-ID: <aaabbb@atlanta.example.com>

Content-Disposition: by-reference;handling=optional

```
<?xml version="1.0" encoding="UTF-8"?>
<pi:EmergencyCallData.ProviderInfo
  xmlns:pi=
    "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
  <pi:DataProviderReference>string0987654321@example.org
</pi:DataProviderReference>
  <pi:DataProviderString>Exemplar VoIP Provider
</pi:DataProviderString>
  <pi:ProviderID>urn:nena:companyid:ID123</pi:ProviderID>
  <pi:ProviderIDSeries>NENA</pi:ProviderIDSeries>
  <pi:TypeOfProvider>Service Provider</pi:TypeOfProvider>
  <pi:ContactURI>sip:voip-provider@example.com</pi:ContactURI>
  <pi:Language>en</pi:Language>
  <pi:DataProviderContact
    xmlns="urn:ietf:params:xml:ns:vcard-4.0">
    <vcard>
      <fn><text>John Doe</text></fn>
      <n>
        <surname>John</surname>
        <given>Doe</given>
        <additional/>
        <prefix/>
        <suffix/>
      </n>
      <bday><date>--0203</date></bday>
      <anniversary>
        <date-time>20090808T1430-0500</date-time>
      </anniversary>
      <gender><sex>M</sex></gender>
      <lang>
        <parameters><pref><integer>1</integer></pref>
      </parameters>
```

```
<language-tag>en</language-tag>
</lang>
<org>
  <parameters><type><text>work</text></type>
  </parameters>
  <text>Exemplar VoIP Provider</text>
</org>
<adr>
  <parameters>
    <type><text>work</text></type>
    <label><text>John Doe
      123 Middle Street
      The Sticks, IA 50055</text></label>
  </parameters>
  <pobox/>
  <ext/>
  <street>123 Middle Street</street>
  <locality>The Sticks</locality>
  <region>IA</region>
  <code>50055</code>
  <country>USA</country>
</adr>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
      <text>main-number</text>
    </type>
  </parameters>
  <uri>sips:john.doe@example.com</uri>
</tel>
<email>
  <parameters><type><text>work</text></type>
  </parameters>
  <text>john.doe@example.com</text>
</email>
<geo>
  <parameters><type><text>work</text></type>
  </parameters>
  <uri>geo:41.761838,-92.963268</uri>
</geo>
<tz><text>America/Chicago</text></tz>
<url>
  <parameters><type><text>home</text></type>
  </parameters>
  <uri>http://www.example.com/john.doe</uri>
</url>
```

```

    </vcard>
  </pi:DataProviderContact>
</pi:EmergencyCallData.ProviderInfo>
--boundary1--

```

Figure 17: VoIP Provider Sending SIP INVITE with Additional Data

Finally, the PSAP requests location information from the access network provider. The response is shown in Figure 18. Along with the location information, additional data is provided in the <provided-by> element of the PIDF-LO. This request and response is step #4.

```

<?xml version="1.0" encoding="UTF-8"?>
<presence xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
  xmlns:gbp="urn:ietf:params:xml:ns:pidf:geopriv10:basicPolicy"
  xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
  entity="pres:alice@atlanta.example.com">
  <dm:device id="target123-1">
    <gp:geopriv>
      <gp:location-info>
        <civicAddress
          xmlns="urn:ietf:params:xml:ns:pidf:geopriv10:civicAddr">
          <country>US</country>
          <A1>DE</A1>
          <A3>Wilmington</A3>
          <PRD>W</PRD>
          <RD>11th</RD>
          <STS>Street</STS>
          <HNO>42</HNO>
          <NAM>The Hotel DuPont</NAM>
          <PC>19801</PC>
        </civicAddress>
      </gp:location-info>
      <gp:usage-rules>
        <gbp:retransmission-allowed>true
      </gbp:retransmission-allowed>
        <gbp:retention-expiry>2013-12-10T20:00:00Z
      </gbp:retention-expiry>
      </gp:usage-rules>
      <gp:method>802.11</gp:method>

      <gp:provided-by
        xmlns="urn:ietf:params:xml:ns:EmergencyCallData">

```

```

<EmergencyCallDataReference
  purpose="EmergencyCallData.ServiceInfo"
  ref="https://example.com/ref2" />

<EmergencyCallDataValue>
  <EmergencyCallData.ProviderInfo
    xmlns=
      "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
    <DataProviderReference>88QV4FpfZ976T@example.com
    </DataProviderReference>
    <DataProviderString>Diamond State Exemplar
    </DataProviderString>
    <ProviderID>urn:nena:companyid:diamond</ProviderID>
    <ProviderIDSeries>NENA</ProviderIDSeries>
    <TypeOfProvider>Access Network Provider</TypeOfProvider>
    <ContactURI>tel:+1-302-555-0000</ContactURI>
    <Language>en</Language>
  </EmergencyCallData.ProviderInfo>

  <EmergencyCallData.Comment
    xmlns="urn:ietf:params:xml:ns:EmergencyCallData:Comment">
    <DataProviderReference>88QV4FpfZ976T@example.com
    </DataProviderReference>
    <Comment xml:lang="en">This is an example text.</Comment>
  </EmergencyCallData.Comment>

</EmergencyCallDataValue>
</gp:provided-by>

</gp:geopriv>
<dm:deviceID>mac:00-0d-4b-30-72-df</dm:deviceID>
<dm:timestamp>2013-07-09T20:57:29Z</dm:timestamp>
</dm:device>
</presence>

```

Figure 18: Access Network Provider Returning PIDF-LO
with Additional Data

8. XML Schemas

This section defines the XML schemas of the five data blocks. Additionally, the provided-by schema is specified.

8.1. EmergencyCallData.ProviderInfo XML Schema

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:pi="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2009/01/xml.xsd"/>

  <xs:import namespace="urn:ietf:params:xml:ns:vcard-4.0"
    schemaLocation="vcard.xsd"/>

  <xs:element
    name="EmergencyCallData.ProviderInfo"
    type="pi:ProviderInfoType"/>

  <xs:simpleType name="SubcontractorPriorityType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="sub"/>
      <xs:enumeration value="main"/>
    </xs:restriction>
  </xs:simpleType>

  <xs:complexType name="ProviderInfoType">
    <xs:sequence>
      <xs:element name="DataProviderReference"
        type="xs:token" minOccurs="1" maxOccurs="1"/>

      <xs:element name="DataProviderString"
        type="xs:string" minOccurs="1" maxOccurs="1"/>

      <xs:element name="ProviderID"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:element name="ProviderIDSeries"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:element name="TypeOfProvider"
        type="xs:token" minOccurs="1" maxOccurs="1"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

```

<xs:element name="ContactURI" type="xs:anyURI"
  minOccurs="1" maxOccurs="1"/>

<xs:element name="Language" minOccurs="1" maxOccurs="unbounded">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern
value="([a-z]{2,3}((-[a-z]{3}){0,3})?|[a-z]{4,8})
(-[a-z]{4})?(-([a-z]{2}|\d{3}))?(-([0-9a-z]{5,8}|
\d[0-9a-z]{3}))*(-([0-9a-wyz](-[0-9a-z]{2,8})+)*
(-x(-[0-9a-z]{1,8})+)?|x(-[0-9a-z]{1,8})+|[a-z]{1,3}
(-[0-9a-z]{2,8}){1,2})"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>

  <xs:element name="DataProviderContact"
    minOccurs="0" maxOccurs="1">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0"
          maxOccurs="unbounded" ref="xc:vcard"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>

  <xs:element name="SubcontractorPrincipal"
    type="xs:string" minOccurs="0" maxOccurs="1"/>

  <xs:element name="SubcontractorPriority"
    type="pi:SubcontractorPriorityType"
    minOccurs="0" maxOccurs="1"/>

  <xs:any namespace="##other" processContents="lax"
    minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>

</xs:schema>

```

Figure 19: EmergencyCallData.ProviderInfo XML Schema

8.2. EmergencyCallData.ServiceInfo XML Schema

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:svc="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:element name="EmergencyCallData.ServiceInfo"
    type="svc:ServiceInfoType"/>

  <xs:complexType name="ServiceInfoType">
    <xs:sequence>
      <xs:element name="DataProviderReference"
        type="xs:token" minOccurs="1" maxOccurs="1"/>

      <xs:element name="ServiceEnvironment"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:element name="ServiceType"
        type="xs:string" minOccurs="1"
        maxOccurs="unbounded"/>

      <xs:element name="ServiceMobility"
        type="xs:string" minOccurs="1" maxOccurs="1"/>

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>

</xs:schema>
```

Figure 20: EmergencyCallData.ServiceInfo XML Schema

8.3. EmergencyCallData.DeviceInfo XML Schema

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:dev="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:element name="EmergencyCallData.DeviceInfo"
    type="dev:DeviceInfoType"/>

  <xs:complexType name="DeviceInfoType">
    <xs:sequence>
      <xs:element name="DataProviderReference"
        type="xs:token" minOccurs="1" maxOccurs="1"/>

      <xs:element name="DeviceClassification"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:element name="DeviceMfgr"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:element name="DeviceModelNr"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:element name="UniqueDeviceID" minOccurs="0"
        maxOccurs="unbounded">
        <xs:complexType>
          <xs:simpleContent>
            <xs:extension base="xs:string">
              <xs:attribute name="TypeOfDeviceID"
                type="xs:string"
                use="required"/>
            </xs:extension>
          </xs:simpleContent>
        </xs:complexType>
      </xs:element>

      <xs:element name="DeviceSpecificData"
        type="xs:anyURI" minOccurs="0" maxOccurs="1"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

```
<xs:element name="DeviceSpecificType"
  type="xs:string" minOccurs="0" maxOccurs="1"/>

  <xs:any namespace="##other" processContents="lax"
    minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>

</xs:schema>
```

Figure 21: EmergencyCallData.DeviceInfo XML Schema

8.4. EmergencyCallData.SubscriberInfo XML Schema

```
<?xml version="1.0"?>
  <xs:schema
    targetNamespace=
      "urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    xmlns:sub=
      "urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
    xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0"
    xmlns:xml="http://www.w3.org/XML/1998/namespace"
    elementFormDefault="qualified"
    attributeFormDefault="unqualified">

    <xs:import namespace="http://www.w3.org/XML/1998/namespace"
      schemaLocation="http://www.w3.org/2001/xml.xsd"/>

    <xs:import namespace="urn:ietf:params:xml:ns:vcard-4.0"
      schemaLocation="vcard.xsd"/>

    <xs:element name="EmergencyCallData.SubscriberInfo"
      type="sub:SubscriberInfoType"/>

    <xs:complexType name="SubscriberInfoType">
      <xs:sequence>
        <xs:element name="DataProviderReference" type="xs:token"
          minOccurs="1" maxOccurs="1"/>
        <xs:element name="SubscriberData">
          <xs:complexType>
            <xs:sequence>
              <xs:element ref="xc:vcard"
                maxOccurs="unbounded"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>

        <xs:any namespace="##other" processContents="lax"
          minOccurs="0" maxOccurs="unbounded"/>

      </xs:sequence>
      <xs:attribute name="privacyRequested"
        type="xs:boolean" use="required"/>
    </xs:complexType>
  </xs:schema>
```

Figure 22: EmergencyCallData.SubscriberInfo XML Schema

8.5. EmergencyCallData.Comment XML Schema

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:Comment"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:com="urn:ietf:params:xml:ns:EmergencyCallData:Comment"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:element name="EmergencyCallData.Comment"
    type="com:CommentType"/>

  <xs:complexType name="CommentType">
    <xs:sequence>
      <xs:element name="DataProviderReference"
        type="xs:token" minOccurs="1" maxOccurs="1"/>

      <xs:element name="Comment"
        type="com:CommentSubType" minOccurs="0"
        maxOccurs="unbounded"/>

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="CommentSubType">
    <xs:simpleContent>
      <xs:extension base="xs:string">
        <xs:attribute ref="xml:lang"/>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>

</xs:schema>
```

Figure 23: EmergencyCallData.Comment XML Schema

8.6. provided-by XML Schema

This section defines the provided-by schema.

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace="urn:ietf:params:xml:ns:EmergencyCallData"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:ad="urn:ietf:params:xml:ns:EmergencyCallData"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  xmlns:pi="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo"
  xmlns:svc="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo"
  xmlns:dev="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo"
  xmlns:sub="urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
  xmlns:com="urn:ietf:params:xml:ns:EmergencyCallData:Comment"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo"
    schemaLocation="ProviderInfo.xsd"/>
  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo"
    schemaLocation="ServiceInfo.xsd"/>
  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo"
    schemaLocation="DeviceInfo.xsd"/>
  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
    schemaLocation="SubscriberInfo.xsd"/>
  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:Comment"
    schemaLocation="Comment.xsd"/>
  <xs:element name="EmergencyCallDataReference" type="ad:ByRefType"/>
  <xs:element name="EmergencyCallDataValue"
    type="ad:EmergencyCallDataValueType"/>
  <!-- Additional Data By Reference -->
  <xs:complexType name="ByRefType">
    <xs:sequence>
      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute name="purpose" type="xs:token" use="required"/>
    <xs:attribute name="ref" type="xs:anyURI" use="required"/>
  </xs:complexType>
  <!-- Additional Data By Value -->
  <xs:complexType name="EmergencyCallDataValueType">
    <xs:sequence>
```

```
<xs:element ref="pi:EmergencyCallData.ProviderInfo"
  minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="svc:EmergencyCallData.ServiceInfo"
  minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="dev:EmergencyCallData.DeviceInfo"
  minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="sub:EmergencyCallData.SubscriberInfo"
  minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="com:EmergencyCallData.Comment"
  minOccurs="0" maxOccurs="unbounded"/>
<xs:any namespace="##other" processContents="lax"
  minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
</xs:schema>
```

Figure 24: provided-by XML Schema

9. Security Considerations

The data structures described in this document contain information usually considered private. When information is provided by value, entities that are a party to the SIP signaling (such as proxy servers and back-to-back user agents) will have access to it and need to protect it against inappropriate disclosure. An entity that is able to eavesdrop on the SIP signaling will also have access. Some Internet access types (such as in-the-clear Wi-Fi) are more vulnerable than others (such as 3G or 4G cellular data traffic) to eavesdropping. Mechanisms that protect against eavesdropping (such as TLS version 1.2 or later) SHOULD be preferentially used whenever feasible. (This requirement is not a "MUST" because there is an existing deployed base of clear-text SIP, and also because, as an emergency call, it is more important for the call to go through than for it to be protected; for example, the call MUST proceed even if the TLS negotiation or certificate verification fails for whatever reason.) When information is provided by reference, TLS mutual authentication is REQUIRED. That is, HTTPS is REQUIRED for dereferencing, the requester MUST use a client certificate to authenticate the HTTP request, and the provider of the information is REQUIRED to validate the credentials provided by the requester. While the creation of a public key infrastructure (PKI) that has global scope might be difficult, the alternatives to creating devices and services that can provide critical information securely are more daunting. The provider of the information MAY enforce any policy it wishes to use, but PSAPs and responder agencies are strongly advised to deploy a PKI so that providers of additional data can check the certificate of the client (the requester) and decide the appropriate policy to enforce based on that certificate.

TLS MUST be version 1.2 or later. It is RECOMMENDED to use only cipher suites that offer Perfect Forward Secrecy (PFS) and avoid Cipher Block Chaining (CBC) and to follow the recommendations in [BCP 195 \[RFC7525\]](#).

Ideally, the PSAP and emergency responders will be given credentials signed by an authority trusted by the data provider. In most circumstances, nationally recognized credentials are sufficient; the emergency services community within a country can arrange a PKI, data providers can be provisioned with the root Certification Authority (CA) public key for the country. Some nations are developing a PKI for this and related purposes. Since calls could be made from devices where the device and/or the service provider(s) is not local to the emergency services authorities, globally recognized credentials are useful. This might be accomplished by extending the notion of the "forest guide" described in [\[RFC5582\]](#) to allow the forest guide to provide the credential of the PKI root for areas for which it has coverage information, but standards for such a mechanism are not yet available. In its absence, the data provider needs to obtain by out-of-band means the root CA credentials for any areas to which it is willing to provide additional data. With the credential of the root CA for a national emergency services PKI, the data provider server can validate the credentials of an entity requesting additional data by reference.

The data provider also needs a credential that can be verified by the emergency services to know that it is receiving data from an authorized server. The emergency services authorities could provide credentials, distinguishable from credentials provided to emergency responders and PSAPs, which could be used to validate data providers. Such credentials would have to be acceptable to any PSAP or responder that could receive a call with additional data supplied by that provider. This would be extensible to global credential validation using the forest guide as mentioned above. In the absence of such credentials, the emergency services authorities could maintain a list of local data providers' credentials as provided to them out of band. At a minimum, the emergency services authorities could obtain a credential from the DNS entry of the domain in the additional data URI (e.g., using DNS-Based Authentication of Named Entities (DANE) [\[RFC6698\]](#)) to at least validate that the server is known to the domain providing the URI.

When devices provide data by reference, the credential validation issues are similar to when service providers do so, and while the solutions are the same, the challenges of doing so for every device are obviously more difficult, especially when considering root certificate updates, revocation lists, etc. However, in general, devices are not expected to provide data directly by reference, but

rather to either provide data by value or upload the data to a server that can more reliably make it available and more easily enforce security policy. Devices that do provide data directly by reference, which might include fixed-location sensors, will need to be capable of handling this.

Neither service providers nor devices will supply private information unless the call is recognized as an emergency call. In cellular telephony systems (such as those using 3GPP IMS), there are different procedures for an originating device to place an emergency call versus a normal call. If a call that is really an emergency call is initiated as a normal call and the cellular service provider recognizes this, 3GPP IMS permits the service provider to either accept the call anyway or reject it with a specific code that instructs the device to retry the call as an emergency call. Service providers ought to choose the latter, otherwise the device will not include the information specified in this document (since the device didn't recognize the call as being an emergency call).

10. Privacy Considerations

This document enables functionality for conveying additional information about the caller and the caller's device and service to the callee. Some of this information is personal data and therefore privacy concerns arise. An explicit privacy indicator for information directly relating to the caller's identity is defined and use is mandatory. However, observance of this request for privacy and which information it relates to is determined by the destination jurisdiction (which replicates functionality provided in some legacy emergency services systems).

There are a number of privacy concerns with non-emergency real-time communication services that are also applicable to emergency calling. Data protection regulation worldwide has, however, decided to create exceptions for emergency services since the drawbacks of disclosing personal data are outweighed by the benefit for the emergency caller. Hence, the data protection rights of individuals are commonly waived for emergency situations. There are, however, still various countries that offer some degree of anonymity for the caller towards PSAP call takers.

The functionality defined in this document far exceeds the amount of information sharing available in the legacy POTS system. For this reason, there are additional privacy threats to consider, which are described in more detail in [RFC6973].

Stored Data Compromise: There is an increased risk of stored data compromise since additional data is collected and stored in databases. Without adequate measures to secure stored data from unauthorized or inappropriate access at access network providers, service providers, end devices, as well as PSAPs, individuals are exposed to potential financial, reputational, or physical harm.

Misattribution: If the personal data collected and conveyed is incorrect or inaccurate, then this can lead to misattribution. Misattribution occurs when data or communications related to one individual are attributed to another.

Identification: By the nature of the additional data and its capability to provide much richer information about the caller, the call, and the location, the calling party is identified in a much better way. Some users could feel uncomfortable with this degree of information sharing even in emergency services situations.

Secondary Use: There is a risk of secondary use, which is the use of collected information about an individual without the individual's consent for a purpose different from that for which the information was collected. The stated purpose of the additional data is for emergency services purposes, but theoretically the same information could be used for any other call as well. Additionally, parties involved in the emergency call could retain the obtained information and reuse it for other, non-emergency services purposes. While technical measures are not in place to prevent such secondary reuse, policy, legal, regulatory, and other non-technical approaches can be effective.

Disclosure: When the data defined in this document is not properly protected (while in transit with traditional communication security techniques and while stored using access control mechanisms), there is the risk of disclosure, which is the revelation of private information about an individual.

To mitigate these privacy risks, the following countermeasures can be taken:

In regions where callers can elect to suppress certain personally identifying information, network or PSAP functionality can inspect privacy flags within the SIP headers to determine what information can be passed, stored, or displayed to comply with local policy or law. [RFC 3325](#) [RFC3325] defines the 'id' priv-value token. The presence of this privacy type in a Privacy header field indicates

that the user would like the network asserted identity to be kept private with respect to SIP entities outside the trust domain with which the user authenticated, including the PSAP.

This document defines various data structures that contain privacy-sensitive data such as, for example, identifiers for the device (e.g., serial number and MAC address) or account/SIM (e.g., IMSI), contact information for the user, and location of the caller. Local regulations may govern which data is provided in emergency calls, but in general, the emergency call system is aided by the information described in this document. There is a trade-off between the privacy considerations and the utility of the data. For protection, this specification requires all retrieval of data passed by reference to be protected against eavesdropping and alteration via communication security techniques (namely TLS). Furthermore, security safeguards are required to prevent unauthorized access to stored data. Various security incidents over at least the past few decades have shown that data breaches are not uncommon and are often caused by lack of proper access control frameworks, software bugs (such as buffer overflows), or missing input parsing (such as SQL injection attacks). The risks of data breaches have increased with the obligation for emergency services to retain emergency-call-related data for extended periods (e.g., several years are the norm).

Finally, it is also worth highlighting the nature of the SIP communication architecture, which introduces additional complications for privacy. Some forms of data can be sent by value in the SIP signaling or by reference (a URL in the SIP signaling). When data is sent by value, all intermediaries have access to the data. As such, these intermediaries could also introduce additional privacy risk. Therefore, in situations where the conveyed information is privacy sensitive and intermediaries are involved, transmitting by reference might be appropriate, assuming the source of the data can operate a sufficient dereferencing infrastructure and that proper access control policies are available for distinguishing the different entities dereferencing the reference. Without access control policies, any party in possession of the reference is able to resolve the reference and to obtain the data, including intermediaries.

11. IANA Considerations

11.1. Emergency Call Additional Data Registry

This document creates a new registry called 'Emergency Call Additional Data' with a number of sub-registries.

For several of the sub-registries, "Expert Review" is the criteria for adding new entries. As discussed in [Section 5](#), it can be counterproductive to register new types of data, and as discussed in [Section 10](#), data sent as part of an emergency call can be very privacy sensitive. In some cases, it is anticipated that various standards bodies dealing with emergency services might need to register new values, and in those cases, text below advises the designed expert to verify that the entity requesting the registration is relevant (e.g., a recognized emergency-services-related Standards Development Organization (SDO)). In other cases, especially those where the trade-off between the potential benefit versus danger of new registrations is more conservative (such as [Section 11.1.9](#)), "Specification Required" is the criteria, which is a higher hurdle and also implicitly includes an "Expert Review".

The following sub-registries are created for this registry.

11.1.1. Provider ID Series Registry

This document creates a new sub-registry called "Provider ID Series". As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is a legitimate issuer of service provider IDs suitable for use in Additional Call Data.

Private entities issuing or using internally generated IDs are encouraged to register here and to ensure that all IDs they issue or use are unique. This guarantees that IDs issued or used by the entity are globally unique and distinguishable from other IDs issued or used by the same or a different entity. (Some organizations, such as NENA, issue IDs that are unique among all IDs they issue, so an entity using a combination of its NENA ID and the fact that it is from NENA is globally unique. Other entities might not have an ID issued by an organization such as NENA, so they are permitted to use their domain name, but if so, it needs to be unique.)

The content of this registry includes:

Name: An identifier to be used in the 'ProviderIDSeries' element.

Source: The full name of the organization issuing the identifiers.

URL: A URL to the organization for further information.

The initial set of values is listed in Figure 1.

11.1.2. Service Environment Registry

This document creates a new sub-registry called "Service Environment". As defined in [RFC5226], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is relevant for this service element (e.g., a recognized emergency-services-related SDO) and that the new value is distinct from existing values, and its use is unambiguous.

The content of this registry includes:

Token: The value to be used in the <ServiceEnvironment> element.

Description: A short description of the value.

The initial set of values is listed in Figure 4.

11.1.3. Service Type Registry

This document creates a new sub-registry called "Service Type". As defined in [RFC5226], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is relevant for this service element (e.g., a recognized emergency-services-related SDO) and that the requested value is clearly distinct from other values so that there is no ambiguity as to when the value is to be used or which value is to be used.

The content of this registry includes:

Name: The value to be used in the <ServiceType> element.

Description: A short description of the value.

The initial set of values is listed in Figure 5.

11.1.4. Service Mobility Registry

This document creates a new sub-registry called "Service Mobility". As defined in [RFC5226], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is relevant for this service element (e.g., a recognized emergency-services-related SDO) and that the requested value is clearly distinct from other values so that there is no ambiguity as to when the value is to be used or which value is to be used.

The content of this registry includes:

Token: The value used in the <ServiceMobility> element.

Description: A short description of the value.

The initial set of values is listed in Figure 6.

11.1.5. Type of Provider Registry

This document creates a new sub-registry called "Type of Provider". As defined in [RFC5226], this registry operates under "Expert Review" rules. The expert should determine that the proposed new value is distinct from existing values and appropriate for use in the <TypeOfServiceProvider> element

The content of this registry includes:

Token: The value used in the <TypeOfProvider> element.

Description: A short description of the type of service provider.

The initial set of values is defined in Figure 2.

11.1.6. Device Classification Registry

This document creates a new sub-registry called "Device Classification". As defined in [RFC5226], this registry operates under "Expert Review" rules. The expert should consider whether the proposed class is unique from existing classes, and the definition of the class will be clear to implementors and PSAPs/responders.

The content of this registry includes:

Token: Value used in the <DeviceClassification> element.

Description: Short description identifying the device type.

The initial set of values is defined in Figure 8.

11.1.7. Device ID Type Registry

This document creates a new sub-registry called "Device ID Type". As defined in [RFC5226], this registry operates under "Expert Review" rules. The expert should ascertain that the proposed type is well understood and provides information that PSAPs and responders are able to use to uniquely identify a device. (For example, a biometric

fingerprint used to authenticate a device would not normally be used by a PSAP or responder to identify a device.)

The content of this registry includes:

Token: The value to be placed in the <TypeOfDeviceID> element.

Description: Short description identifying the type of the device ID.

The initial set of values is defined in Figure 9.

11.1.8. Device/Service Data Type Registry

This document creates a new sub-registry called "Device/Service Data Type". As defined in [RFC5226], this registry operates under "Specification Required" rules, which include an explicit "Expert Review". The designated expert should ascertain that the proposed type is well understood and provides information useful to PSAPs and responders. The specification must contain a complete description of the data and a precise format specification suitable to allow interoperable implementations.

The content of this registry includes:

Token: The value to be placed in the <DeviceSpecificType> element.

Description: Short description identifying the data.

Specification: Citation for the specification of the data.

The initial set of values is listed in Figure 10.

11.1.9. Emergency Call Data Types Registry

This document creates a new sub-registry called "Emergency Call Data Types". As defined in [RFC5226], this registry operates under "Specification Required" rules, which include an explicit "Expert Review". The expert is responsible for verifying that the document contains a complete and clear specification, and the proposed functionality does not obviously duplicate existing functionality. The expert is also responsible for verifying that the block is correctly categorized per the description of the categories in [Section 1](#).

The registry contains an entry for every data block that can be sent with an emergency call using the mechanisms as specified in this document. Each data block is identified by the 'root' of its MIME

media subtype (which is the part after 'EmergencyCallData.'). If the MIME media subtype does not start with 'EmergencyCallData.', then it cannot be registered here nor used in a Call-Info header field as specified in this document. The subtype MAY exist under any MIME media type (although most commonly under 'application/', this is NOT REQUIRED); however, to be added to the registry, the 'root' needs to be unique regardless of the MIME media type.

The content of this registry includes:

Token: The root of the data's MIME media subtype (not including the 'EmergencyCallData' prefix and any suffix such as '+xml').

Data About: A hint as to if the block is considered descriptive of the call, the caller, or the location (or is applicable to more than one), which can help PSAPs and other entities determine if they wish to process the block. Note that this is only a hint; entities need to consider the block's contents, not just this field, when determining if they wish to process the block (which is why the field only exists in the registry and is not contained within the block). The value MUST be either 'The Call', 'The Caller', 'The Location', or 'Multiple'. New values are created by extending this registry in a subsequent RFC.

Reference: The document that describes the data object.

Note that the tokens in this registry are part of the 'EmergencyCallData' compound value; when used as a value of the 'purpose' parameter of a Call-Info header field, the values listed in this registry are prefixed by 'EmergencyCallData.' per the 'EmergencyCallData' registration; see [Section 11.2](#).

The initial set of values is listed in Figure 25.

Token	Data About	Reference
ProviderInfo	The Call	RFC 7852
ServiceInfo	The Call	RFC 7852
DeviceInfo	The Call	RFC 7852
SubscriberInfo	The Call	RFC 7852
Comment	The Call	RFC 7852

Figure 25: Additional Data Blocks Registry

11.2. 'EmergencyCallData' Purpose Parameter Value

This document defines the 'EmergencyCallData' value for the 'purpose' parameter of the Call-Info header field [RFC3261]. IANA has added this document to the list of references for the 'purpose' value of Call-Info in the "Header Field Parameters and Parameter Values" sub-registry of the "Session Initiation Protocol (SIP) Parameters" registry. Note that 'EmergencyCallData' is a compound value; when used as a value of the 'purpose' parameter of a Call-Info header field, 'EmergencyCallData' is immediately followed by a dot ('.') and a value from the "Emergency Call Data Types" registry; see [Section 11.1.9](#).

11.3. URN Sub-Namespace Registration for <provided-by> Registry Entry

This section registers the namespace specified in [Section 11.5.1](#) in the provided-by registry established by [RFC 4119](#), for usage within the <provided-by> element of a PIDF-LO.

The schema for the <provided-by> element used by this document is specified in [Section 8.6](#).

11.4. MIME Registrations

11.4.1. MIME Content-Type Registration for 'application/ EmergencyCallData.ProviderInfo+xml'

This specification requests the registration of a new MIME media type according to the procedures of [RFC 6838](#) [RFC6838] and guidelines in [RFC 7303](#) [RFC7303].

Type name: application

Subtype name: EmergencyCallData.ProviderInfo+xml

Mandatory parameters: N/A

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303](#) [RFC7303].

Security considerations: This content type is designed to carry the data provider information, which is a sub-category of additional data about an emergency call. Since this data can contain personal information, appropriate precautions are needed

to limit unauthorized access, inappropriate disclosure, and eavesdropping of personal information. Please refer to Sections 9 and 10 for more information.

Interoperability considerations: N/A

Published specification: RFC 7852

Applications that use this media type: Emergency Services

Additional information:

Magic Number: N/A

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information:
Hannes Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <iesg@ietf.org>

11.4.2. MIME Content-Type Registration for 'application/ EmergencyCallData.ServiceInfo+xml'

This specification requests the registration of a new MIME media type according to the procedures of RFC 6838 [RFC6838] and guidelines in RFC 7303 [RFC7303].

Type name: application

Subtype name: EmergencyCallData.ServiceInfo+xml

Mandatory parameters: N/A

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See Section 3.2 of RFC 7303 [RFC7303].

Security considerations: This content type is designed to carry the service information, which is a sub-category of additional data about an emergency call. Since this data can contain personal information, appropriate precautions are needed to limit unauthorized access, inappropriate disclosure, and eavesdropping of personal information. Please refer to Sections 9 and 10 for more information.

Interoperability considerations: N/A

Published specification: RFC 7852

Applications that use this media type: Emergency Services

Additional information:

Magic Number: N/A

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information:
Hannes Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <iesg@ietf.org>

11.4.3. MIME Content-Type Registration for 'application/ EmergencyCallData.DeviceInfo+xml'

This specification requests the registration of a new MIME media type according to the procedures of RFC 6838 [RFC6838] and guidelines in RFC 7303 [RFC7303].

Type name: application

Subtype name: EmergencyCallData.DeviceInfo+xml

Mandatory parameters: N/A

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303 \[RFC7303\]](#).

Security considerations: This content type is designed to carry device information, which is a sub-category of additional data about an emergency call. Since this data contains personal information, appropriate precautions need to be taken to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to Sections 9 and 10 for more information.

Interoperability considerations: N/A

Published specification: [RFC 7852](#)

Applications that use this media type: Emergency Services

Additional information:

Magic Number: N/A

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information:
Hannes Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address [<ecrit@ietf.org>](mailto:ecrit@ietf.org).

Change controller: The IESG [<iesg@ietf.org>](mailto:iesg@ietf.org)

11.4.4. MIME Content-Type Registration for 'application/ EmergencyCallData.SubscriberInfo+xml'

This specification requests the registration of a new MIME media type according to the procedures of [RFC 6838 \[RFC6838\]](#) and guidelines in [RFC 7303 \[RFC7303\]](#).

Type name: application

Subtype name: EmergencyCallData.SubscriberInfo+xml

Mandatory parameters: N/A

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303 \[RFC7303\]](#).

Security considerations: This content type is designed to carry owner/subscriber information, which is a sub-category of additional data about an emergency call. Since this data contains personal information, appropriate precautions need to be taken to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to Sections 9 and 10 for more information.

Interoperability considerations: N/A

Published specification: [RFC 7852](#)

Applications that use this media type: Emergency Services

Additional information:

Magic Number: N/A

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information:
Hannes Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address [<ecrit@ietf.org>](mailto:ecrit@ietf.org).

Change controller: The IESG [<iesg@ietf.org>](mailto:iesg@ietf.org)

11.4.5. MIME Content-Type Registration for 'application/ EmergencyCallData.Comment+xml'

This specification requests the registration of a new MIME media type according to the procedures of [RFC 6838 \[RFC6838\]](#) and guidelines in [RFC 7303 \[RFC7303\]](#).

Type name: application

Subtype name: EmergencyCallData.Comment+xml

Mandatory parameters: N/A

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303](#) [RFC7303].

Security considerations: This content type is designed to carry a comment, which is a sub-category of additional data about an emergency call. This data can contain personal information. Appropriate precautions are needed to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to Sections 9 and 10 for more information.

Interoperability considerations: N/A

Published specification: [RFC 7852](#)

Applications that use this media type: Emergency Services

Additional information:

Magic Number: N/A

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information:
Hannes Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address [<ecrit@ietf.org>](mailto:ecrit@ietf.org).

Change controller: The IESG [<iesg@ietf.org>](mailto:iesg@ietf.org)

11.5. URN Sub-Namespace Registration

11.5.1. Registration for urn:ietf:params:xml:ns:EmergencyCallData

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [RFC3688].

URI: urn:ietf:params:xml:ns:EmergencyCallData

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml-basic/xhtml-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data</title>
</head>
<body>
  <h1>Namespace for Additional Data Related to an Emergency Call
    </h1>
  <p>See <a href="http://www.rfc-editor.org/rfc/rfc7852.txt">
    RFC 7852</a>.</p>
</body>
</html>
END
```

11.5.2. Registration for urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [RFC3688].

URI: urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml-basic/xhtml-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Data Provider Information</title>
</head>
<body>
  <h1>Namespace for Additional Data Related to an Emergency Call
    </h1>
  <h2>Data Provider Information</h2>
  <p>See <a href="http://www.rfc-editor.org/rfc/rfc7852.txt">
    RFC 7852</a>.</p>
</body>
</html>
END
```

11.5.3. Registration for

urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo

This section registers a new XML namespace, as per the guidelines in RFC 3688 [RFC3688].

URI: urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml-basic/xhtml-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Service Information</title>
</head>
<body>
```

```
<h1>Namespace for Additional Data Related to an Emergency Call
</h1>
<h2>Service Information</h2>
<p>See <a href="http://www.rfc-editor.org/rfc/rfc7852.txt">
  RFC 7852</a>.</p>
</body>
</html>
END
```

11.5.4. Registration for urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo

This section registers a new XML namespace, as per the guidelines in RFC 3688 [RFC3688].

URI: urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml-basic/xhtml-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Device Information</title>
</head>
<body>
  <h1>Namespace for Additional Data Related to an Emergency Call
  </h1>
  <h2>Device Information</h2>
  <p>See <a href="http://www.rfc-editor.org/rfc/rfc7852.txt">
    RFC 7852</a>.</p>
</body>
</html>
END
```


11.5.5. Registration for urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [RFC3688].

URI: urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml-basic/xhtml-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Owner/Subscriber Information</title>
</head>
<body>
  <h1>Namespace for Additional Data Related to an Emergency Call
    </h1>
  <h2> Owner/Subscriber Information</h2>
  <p>See <a href="http://www.rfc-editor.org/rfc/rfc7852.txt">
    RFC 7852</a>.</p>
</body>
</html>
END
```

11.5.6. Registration for urn:ietf:params:xml:ns:EmergencyCallData:Comment

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [RFC3688].

URI: urn:ietf:params:xml:ns:EmergencyCallData:Comment

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml-basic/xhtml-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:Comment
  </title>
</head>
<body>
  <h1>Namespace for Additional Data Related to an Emergency Call
  </h1>
  <h2> Comment</h2>
  <p>See <a href="http://www.rfc-editor.org/rfc/rfc7852.txt">
    RFC 7852</a>.</p>
</body>
</html>
END
```

11.6. Schema Registrations

This specification registers the following schemas, as per the guidelines in RFC 3688 [RFC3688].

ID: EmergencyCallData
URI: urn:ietf:params:xml:schema:EmergencyCallData
Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).
XML: The XML schema can be found in Section 8.6.

ID: EmergencyCallData:ProviderInfo
URI: urn:ietf:params:xml:schema:EmergencyCallData:ProviderInfo
Registrant Contact: IETF, ECRIT working group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).
XML: The XML schema can be found in Figure 19.

ID: EmergencyCallData:ServiceInfo
URI: urn:ietf:params:xml:schema:EmergencyCallData:ServiceInfo
Registrant Contact: IETF, ECRIT working group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).
XML: The XML schema can be found in Figure 20.

ID: EmergencyCallData:DeviceInfo
URI: urn:ietf:params:xml:schema:EmergencyCallData:DeviceInfo
Registrant Contact: IETF, ECRIT working group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in Figure 21.

ID: EmergencyCallData:SubscriberInfo
URI: urn:ietf:params:xml:schema:EmergencyCallData:SubscriberInfo
Registrant Contact: IETF, ECRIT working group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).
XML: The XML schema can be found in [Section 8.4](#).

ID: EmergencyCallData:Comment
URI: urn:ietf:params:xml:schema:EmergencyCallData:Comment
Registrant Contact: IETF, ECRIT working group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).
XML: The XML schema can be found in [Section 8.5](#).

ID: vcard-4.0
URI: urn:ietf:params:xml:ns:vcard-4.0
Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).
XML: The XML schema can be found in [Appendix A](#).

11.7. vCard Parameter Value Registration

This document registers a new value in the "vCard Parameter Values" registry as defined by [\[RFC6350\]](#) with the following template:

Value: main-number

Purpose: The main telephone number, typically of an enterprise, as opposed to a direct-dial number of an individual employee

Conformance: This value can be used with the 'TYPE' parameter applied on the 'TEL' property

Example(s): TEL;VALUE=uri;TYPE="main,voice";PREF=1:tel:+1-418-656-9000

12. References

12.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <http://www.rfc-editor.org/info/rfc2119>.
- [RFC2392] Levinson, E., "Content-ID and Message-ID Uniform Resource Locators", [RFC 2392](#), DOI 10.17487/RFC2392, August 1998, <http://www.rfc-editor.org/info/rfc2392>.
- [RFC3204] Zimmerer, E., Peterson, J., Vemuri, A., Ong, L., Audet, F., Watson, M., and M. Zonoun, "MIME media types for ISUP and QSIG Objects", [RFC 3204](#), DOI 10.17487/RFC3204, December 2001, <http://www.rfc-editor.org/info/rfc3204>.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), DOI 10.17487/RFC3261, June 2002, <http://www.rfc-editor.org/info/rfc3261>.
- [RFC3459] Burger, E., "Critical Content Multi-purpose Internet Mail Extensions (MIME) Parameter", [RFC 3459](#), DOI 10.17487/RFC3459, January 2003, <http://www.rfc-editor.org/info/rfc3459>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <http://www.rfc-editor.org/info/rfc3688>.
- [RFC3966] Schulzrinne, H., "The tel URI for Telephone Numbers", [RFC 3966](#), DOI 10.17487/RFC3966, December 2004, <http://www.rfc-editor.org/info/rfc3966>.
- [RFC4119] Peterson, J., "A Presence-based GEOPRIV Location Object Format", [RFC 4119](#), DOI 10.17487/RFC4119, December 2005, <http://www.rfc-editor.org/info/rfc4119>.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), DOI 10.17487/RFC5226, May 2008, <http://www.rfc-editor.org/info/rfc5226>.

- [RFC5322] Resnick, P., Ed., "Internet Message Format", RFC 5322, DOI 10.17487/RFC5322, October 2008, <<http://www.rfc-editor.org/info/rfc5322>>.
- [RFC5621] Camarillo, G., "Message Body Handling in the Session Initiation Protocol (SIP)", RFC 5621, DOI 10.17487/RFC5621, September 2009, <<http://www.rfc-editor.org/info/rfc5621>>.
- [RFC5646] Phillips, A., Ed. and M. Davis, Ed., "Tags for Identifying Languages", BCP 47, RFC 5646, DOI 10.17487/RFC5646, September 2009, <<http://www.rfc-editor.org/info/rfc5646>>.
- [RFC6350] Perreault, S., "vCard Format Specification", RFC 6350, DOI 10.17487/RFC6350, August 2011, <<http://www.rfc-editor.org/info/rfc6350>>.
- [RFC6351] Perreault, S., "xCard: vCard XML Representation", RFC 6351, DOI 10.17487/RFC6351, August 2011, <<http://www.rfc-editor.org/info/rfc6351>>.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", BCP 13, RFC 6838, DOI 10.17487/RFC6838, January 2013, <<http://www.rfc-editor.org/info/rfc6838>>.
- [RFC7303] Thompson, H. and C. Lilley, "XML Media Types", RFC 7303, DOI 10.17487/RFC7303, July 2014, <<http://www.rfc-editor.org/info/rfc7303>>.

12.2. Informative References

- [ECRIT-WG-wiki]
IETF ECRIT WG Wiki, "Additional Data Examples", July 2015, <<http://tools.ietf.org/wg/ecrit/trac/attachment/wiki/WikiStart/additional-data-examples.zip>>.
- [Err3047] RFC Errata, Erratum ID 3047, RFC 6351.
- [HUMAN-LANG]
Gellens, R., "Negotiating Human Language in Real-Time Communications", Work in Progress, [draft-ietf-slim-negotiating-human-language-04](#), July 2016.
- [IANA-XML-Schemas]
IANA, "IETF XML Registry", <<http://www.iana.org/assignments/xml-registry>>.

- [IEEE-1512-2006]
IEEE, "IEEE Standard for Common Incident Management Message Sets for Use by Emergency Management Centers", IEEE Std 1512-2006, DOI 10.1109/IEEESTD.2006.224678, August 2006, <<https://standards.ieee.org/findstds/standard/1512-2006.html>>.
- [LanguageSubtagRegistry]
IANA, "Language Subtag Registry", <<http://www.iana.org/assignments/language-subtag-registry>>.
- [LERG] Telcordia Technologies, Inc., "LERG Routing Guide", ANI II Digits Definitions, June 2015.
- [NANP] North American Numbering Plan Administration (NANPA), "ANI II Digits Assignments", September 2015, <http://nanpa.com/number_resource_info/ani_ii_assignments.html>.
- [nc911] North Carolina 911 Board, "Wireless 911 for Telecommunicators", January 2009, <https://www.nc911.nc.gov/pdf/A_TelecommunicatorReference.pdf>.
- [NENA-02-010]
National Emergency Number Association (NENA), "NENA Standard Data Formats for 9-1-1 Data Exchange & GIS Mapping", NENA-02-010, Version 9, December 2010, <<http://www.nena.org>>.
- [RFC3325] Jennings, C., Peterson, J., and M. Watson, "Private Extensions to the Session Initiation Protocol (SIP) for Asserted Identity within Trusted Networks", RFC 3325, DOI 10.17487/RFC3325, November 2002, <<http://www.rfc-editor.org/info/rfc3325>>.
- [RFC3840] Rosenberg, J., Schulzrinne, H., and P. Kyzivat, "Indicating User Agent Capabilities in the Session Initiation Protocol (SIP)", RFC 3840, DOI 10.17487/RFC3840, August 2004, <<http://www.rfc-editor.org/info/rfc3840>>.
- [RFC5012] Schulzrinne, H. and R. Marshall, Ed., "Requirements for Emergency Context Resolution with Internet Technologies", RFC 5012, DOI 10.17487/RFC5012, January 2008, <<http://www.rfc-editor.org/info/rfc5012>>.

- [RFC5139] Thomson, M. and J. Winterbottom, "Revised Civic Location Format for Presence Information Data Format Location Object (PIDF-LO)", [RFC 5139](#), DOI 10.17487/RFC5139, February 2008, <<http://www.rfc-editor.org/info/rfc5139>>.
- [RFC5491] Winterbottom, J., Thomson, M., and H. Tschafenig, "GEOPRIV Presence Information Data Format Location Object (PIDF-LO) Usage Clarification, Considerations, and Recommendations", [RFC 5491](#), DOI 10.17487/RFC5491, March 2009, <<http://www.rfc-editor.org/info/rfc5491>>.
- [RFC5582] Schulzrinne, H., "Location-to-URL Mapping Architecture and Framework", [RFC 5582](#), DOI 10.17487/RFC5582, September 2009, <<http://www.rfc-editor.org/info/rfc5582>>.
- [RFC5962] Schulzrinne, H., Singh, V., Tschafenig, H., and M. Thomson, "Dynamic Extensions to the Presence Information Data Format Location Object (PIDF-LO)", [RFC 5962](#), DOI 10.17487/RFC5962, September 2010, <<http://www.rfc-editor.org/info/rfc5962>>.
- [RFC5985] Barnes, M., Ed., "HTTP-Enabled Location Delivery (HELD)", [RFC 5985](#), DOI 10.17487/RFC5985, September 2010, <<http://www.rfc-editor.org/info/rfc5985>>.
- [RFC6443] Rosen, B., Schulzrinne, H., Polk, J., and A. Newton, "Framework for Emergency Calling Using Internet Multimedia", [RFC 6443](#), DOI 10.17487/RFC6443, December 2011, <<http://www.rfc-editor.org/info/rfc6443>>.
- [RFC6698] Hoffman, P. and J. Schlyter, "The DNS-Based Authentication of Named Entities (DANE) Transport Layer Security (TLS) Protocol: TLSA", [RFC 6698](#), DOI 10.17487/RFC6698, August 2012, <<http://www.rfc-editor.org/info/rfc6698>>.
- [RFC6848] Winterbottom, J., Thomson, M., Barnes, R., Rosen, B., and R. George, "Specifying Civic Address Extensions in the Presence Information Data Format Location Object (PIDF-LO)", [RFC 6848](#), DOI 10.17487/RFC6848, January 2013, <<http://www.rfc-editor.org/info/rfc6848>>.
- [RFC6881] Rosen, B. and J. Polk, "Best Current Practice for Communications Services in Support of Emergency Calling", [BCP 181](#), [RFC 6881](#), DOI 10.17487/RFC6881, March 2013, <<http://www.rfc-editor.org/info/rfc6881>>.

- [RFC6973] Cooper, A., Tschofenig, H., Aboba, B., Peterson, J., Morris, J., Hansen, M., and R. Smith, "Privacy Considerations for Internet Protocols", RFC 6973, DOI 10.17487/RFC6973, July 2013, <<http://www.rfc-editor.org/info/rfc6973>>.
- [RFC7035] Thomson, M., Rosen, B., Stanley, D., Bajko, G., and A. Thomson, "Relative Location Representation", RFC 7035, DOI 10.17487/RFC7035, October 2013, <<http://www.rfc-editor.org/info/rfc7035>>.
- [RFC7090] Schulzrinne, H., Tschofenig, H., Holmberg, C., and M. Patel, "Public Safety Answering Point (PSAP) Callback", RFC 7090, DOI 10.17487/RFC7090, April 2014, <<http://www.rfc-editor.org/info/rfc7090>>.
- [RFC7525] Sheffer, Y., Holz, R., and P. Saint-Andre, "Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS)", BCP 195, RFC 7525, DOI 10.17487/RFC7525, May 2015, <<http://www.rfc-editor.org/info/rfc7525>>.

Appendix A. XML Schema for vCard/xCard

This section contains the vCard/xCard XML schema version of the Relax NG schema defined in [RFC 6351](#) [[RFC6351](#)] for use with the XML schemas defined in this document. In addition to mapping the Relax NG schema to an XML schema, this specification applies an erratum raised for [RFC 6351](#) regarding the type definition; see RFC Erratum ID 3047 [[Err3047](#)].

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema
  targetNamespace="urn:ietf:params:xml:ns:vcard-4.0"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:ns1="urn:ietf:params:xml:ns:vcard-4.0"
  elementFormDefault="qualified">
  <!--
    3.3
    iana-token = xsd:string { pattern = "[a-zA-Z0-9-]+" }
    x-name = xsd:string { pattern = "x-[a-zA-Z0-9-]+" }
  -->
  <xs:simpleType name="iana-token">
    <xs:annotation>
      <xs:documentation>Section 3.3: vCard Format Specification
    </xs:documentation>
    </xs:annotation>
    <xs:restriction base="xs:string"/>
  </xs:simpleType>
  <xs:simpleType name="x-name">
    <xs:restriction base="xs:string"/>
  </xs:simpleType>
  <!--
    4.1
  -->
  <xs:element name="text" type="xs:string"/>
  <xs:group name="value-text-list">
    <xs:sequence>
      <xs:element ref="ns1:text" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:group>
  <!-- 4.2 -->
  <xs:element name="uri" type="xs:anyURI"/>
  <!-- 4.3.1 -->
  <xs:element name="date"
    substitutionGroup="ns1:value-date-and-or-time">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:pattern
          value="\d{8}|\d{4}-\d\d|--\d\d(\d\d)?|---\d\d"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
```

```
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.3.2 -->
<xs:element name="time"
  substitutionGroup="ns1:value-date-and-or-time">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value=
"(\d\d(\d\d(\d\d)?)?|-\d\d(\d\d)?|--\d\d)(Z|[\+-]\d\d(\d\d)?)" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.3.3 -->
<xs:element name="date-time"
  substitutionGroup="ns1:value-date-and-or-time">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value=
"(\d{8}|--\d{4}|---\d\d)T\d\d(\d\d(\d\d)?)?(Z|[\+-]\d\d(\d\d)?)" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.3.4 -->
<xs:element name="value-date-and-or-time" abstract="true" />
<!-- 4.3.5 -->
<xs:complexType name="value-timestamp">
  <xs:sequence>
    <xs:element ref="ns1:timestamp" />
  </xs:sequence>
</xs:complexType>
<xs:element name="timestamp">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="\d{8}T\d{6}(Z|[\+-]\d\d(\d\d)?)" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.4 -->
<xs:element name="boolean" type="xs:boolean" />
<!-- 4.5 -->
<xs:element name="integer" type="xs:integer" />
<!-- 4.6 -->
<xs:element name="float" type="xs:float" />
<!-- 4.7 -->
<xs:element name="utc-offset">
  <xs:simpleType>
    <xs:restriction base="xs:string">
```

```

        <xs:pattern value="[+\\-]\\d\\d(\\d\\d)?"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
<!-- 4.8 -->
<xs:element name="language-tag">
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:pattern value=
"([a-z]{2,3}((-[a-z]{3}){0,3})?|[a-z]{4,8})(-[a-z]{4})?
(-([a-z]{2}|\\d{3}))?(-([0-9a-z]{5,8}|\\d[0-9a-z]{3})) *
(-[0-9a-wyz](-[0-9a-z]{2,8})+)*(-x(-[0-9a-z]{1,8})+)?
|x(-[0-9a-z]{1,8})+|[a-z]{1,3}(-[0-9a-z]{2,8}){1,2}"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<!--
    5.1
-->
<xs:group name="param-language">
    <xs:annotation>
        <xs:documentation>Section 5: Parameters</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element ref="ns1:language" minOccurs="0"/>
    </xs:sequence>
</xs:group>
<xs:element name="language">
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="ns1:language-tag"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<!-- 5.2 -->
<xs:group name="param-pref">
    <xs:sequence>
        <xs:element ref="ns1:pref" minOccurs="0"/>
    </xs:sequence>
</xs:group>
<xs:element name="pref">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="integer">
                <xs:simpleType>
                    <xs:restriction base="xs:integer">
                        <xs:minInclusive value="1"/>
                        <xs:maxInclusive value="100"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<!-- 5.4 -->
<xs:group name="param-altid">
  <xs:sequence>
    <xs:element ref="ns1:altid" minOccurs="0"/>
  </xs:sequence>
</xs:group>
<xs:element name="altid">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.5 -->
<xs:group name="param-pid">
  <xs:sequence>
    <xs:element ref="ns1:pid" minOccurs="0"/>
  </xs:sequence>
</xs:group>
<xs:element name="pid">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="text" maxOccurs="unbounded">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:pattern value="\d+(\.\d+)?"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.6 -->
<xs:group name="param-type">
  <xs:sequence>
    <xs:element ref="ns1:type" minOccurs="0"/>
  </xs:sequence>
</xs:group>
<xs:element name="type">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="text" maxOccurs="unbounded">
```

```
        <xs:simpleType>
          <xs:restriction base="xs:token">
            <xs:enumeration value="work"/>
            <xs:enumeration value="home"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.7 -->
<xs:group name="param-mediatype">
  <xs:sequence>
    <xs:element ref="ns1:mediatype" minOccurs="0"/>
  </xs:sequence>
</xs:group>
<xs:element name="mediatype">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.8 -->
<xs:group name="param-calscale">
  <xs:sequence>
    <xs:element ref="ns1:calscale" minOccurs="0"/>
  </xs:sequence>
</xs:group>
<xs:element name="calscale">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="text">
        <xs:simpleType>
          <xs:restriction base="xs:token">
            <xs:enumeration value="gregorian"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.9 -->
<xs:group name="param-sort-as">
  <xs:sequence>
    <xs:element ref="ns1:sort-as" minOccurs="0"/>
  </xs:sequence>
</xs:group>
```

```
<xs:element name="sort-as">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.10 -->
<xs:group name="param-geo">
  <xs:sequence>
    <xs:element name="geo" minOccurs="0">
      <xs:complexType>
        <xs:sequence>
          <xs:element ref="ns1:uri"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:group>
<!-- 5.11 -->
<xs:group name="param-tz">
  <xs:sequence>
    <xs:element name="tz" minOccurs="0">
      <xs:complexType>
        <xs:choice>
          <xs:element ref="ns1:text"/>
          <xs:element ref="ns1:uri"/>
        </xs:choice>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:group>
<!--
6.1.3
-->
<xs:element name="source">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
```

```
<xs:element ref="ns1:uri"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.1.4 -->
<xs:element name="kind">
  <xs:complexType>
    <xs:sequence>
      <xs:annotation>
        <xs:documentation>
          The text value must be one of: individual, group, org,
          location or a ns1:x-name or a ns1:iana-token value
        </xs:documentation>
      </xs:annotation>
      <xs:element name="text" type="xs:token"
        minOccurs="1" maxOccurs="1"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.1 -->
<xs:element name="fn">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.2 -->
<xs:element name="n">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-sort-as"/>
            <xs:group ref="ns1:param-altid"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element ref="ns1:surname"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:element ref="ns1:given"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:element ref="ns1:additional"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:element ref="ns1:prefix"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:element ref="ns1:suffix"
      minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="surname" type="xs:string"/>
<xs:element name="given" type="xs:string"/>
<xs:element name="additional" type="xs:string"/>
<xs:element name="prefix" type="xs:string"/>
<xs:element name="suffix" type="xs:string"/>
<!-- 6.2.3 -->
<xs:element name="nickname">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:group ref="ns1:value-text-list"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.4 -->
<xs:element name="photo">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>

```



```
        <xs:group ref="ns1:param-pid"/>
        <xs:group ref="ns1:param-pref"/>
        <xs:group ref="ns1:param-type"/>
        <xs:group ref="ns1:param-mediatype"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element ref="ns1:uri"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.2.5 -->
<xs:element name="bday">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-calscale"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:choice>
        <xs:element ref="ns1:value-date-and-or-time"/>
        <xs:element ref="ns1:text"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.6 -->
<xs:element name="anniversary">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-calscale"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:choice>
        <xs:element ref="ns1:value-date-and-or-time"/>
        <xs:element ref="ns1:text"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
</xs:element>
<!-- 6.2.7 -->
<xs:element name="gender">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:sex"/>
      <xs:element ref="ns1:identity" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="sex">
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:enumeration value=" "/>
      <xs:enumeration value="M"/>
      <xs:enumeration value="F"/>
      <xs:enumeration value="O"/>
      <xs:enumeration value="N"/>
      <xs:enumeration value="U"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="identity" type="xs:string"/>
<!-- 6.3.1 -->
<xs:group name="param-label">
  <xs:sequence>
    <xs:element ref="ns1:label" minOccurs="0"/>
  </xs:sequence>
</xs:group>
<xs:element name="label">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="adr">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-geo"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        <xs:group ref="ns1:param-tz"/>
        <xs:group ref="ns1:param-label"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="ns1:pobox"
    minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="ns1:ext"
    minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="ns1:street"
    minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="ns1:locality"
    minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="ns1:region"
    minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="ns1:code"
    minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="ns1:country"
    minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="pobox" type="xs:string"/>
<xs:element name="ext" type="xs:string"/>
<xs:element name="street" type="xs:string"/>
<xs:element name="locality" type="xs:string"/>
<xs:element name="region" type="xs:string"/>
<xs:element name="code" type="xs:string"/>
<xs:element name="country" type="xs:string"/>
<!-- 6.4.1 -->
<xs:element name="tel">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="parameters" minOccurs="0">
                <xs:complexType>
                    <xs:sequence>
                        <xs:group ref="ns1:param-altid"
                            minOccurs="0"/>
                        <xs:group ref="ns1:param-pid"
                            minOccurs="0"/>
                        <xs:group ref="ns1:param-pref"
                            minOccurs="0"/>
                        <xs:element name="type" minOccurs="0">
                            <xs:complexType>
                                <xs:sequence>
                                    <xs:element name="text"
                                        type="xs:string"
                                        maxOccurs="unbounded">
```

```
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:group ref="ns1:param-mediatype"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:choice>
  <xs:element ref="ns1:text"/>
  <xs:element ref="ns1:uri"/>
</xs:choice>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.4.2 -->
<xs:element name="email">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.4.3 -->
<xs:element name="impp">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        <xs:element ref="ns1:uri"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <!-- 6.4.4 -->
  <xs:element name="lang">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="parameters" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:group ref="ns1:param-altid"/>
              <xs:group ref="ns1:param-pid"/>
              <xs:group ref="ns1:param-pref"/>
              <xs:group ref="ns1:param-type"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element ref="ns1:language-tag"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <!-- 6.5.1 -->
  <xs:group name="property-tz">
    <xs:sequence>
      <xs:element name="tz">
        <xs:complexType>
          <xs:sequence>
            <xs:element name="parameters" minOccurs="0">
              <xs:complexType>
                <xs:sequence>
                  <xs:group ref="ns1:param-altid"/>
                  <xs:group ref="ns1:param-pid"/>
                  <xs:group ref="ns1:param-pref"/>
                  <xs:group ref="ns1:param-type"/>
                  <xs:group
                    ref="ns1:param-mediatype"/>
                </xs:sequence>
              </xs:complexType>
            </xs:element>
            <xs:choice>
              <xs:element ref="ns1:text"/>
              <xs:element ref="ns1:uri"/>
              <xs:element ref="ns1:utc-offset"/>
            </xs:choice>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:group>

```

```
</xs:sequence>
</xs:group>
<!-- 6.5.2 -->
<xs:group name="property-geo">
  <xs:sequence>
    <xs:element name="geo">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="parameters" minOccurs="0">
            <xs:complexType>
              <xs:sequence>
                <xs:group ref="ns1:param-altid"/>
                <xs:group ref="ns1:param-pid"/>
                <xs:group ref="ns1:param-pref"/>
                <xs:group ref="ns1:param-type"/>
                <xs:group
                  ref="ns1:param-mediatype"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
          <xs:element ref="ns1:uri"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:group>
<!-- 6.6.1 -->
<xs:element name="title">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.6.2 -->
<xs:element name="role">
  <xs:complexType>
```

```
<xs:sequence>
  <xs:element name="parameters" minOccurs="0">
    <xs:complexType>
      <xs:sequence>
        <xs:group ref="ns1:param-language"/>
        <xs:group ref="ns1:param-altid"/>
        <xs:group ref="ns1:param-pid"/>
        <xs:group ref="ns1:param-pref"/>
        <xs:group ref="ns1:param-type"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element ref="ns1:text"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.6.3 -->
<xs:element name="logo">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.6.4 -->
<xs:element name="org">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        <xs:group ref="ns1:param-sort-as"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:group ref="ns1:value-text-list"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.6.5 -->
<xs:element name="member">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.6.6 -->
<xs:element name="related">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:element name="type" minOccurs="0">
              <xs:complexType>
                <xs:sequence>
                  <xs:element name="text" maxOccurs="unbounded">
                    <xs:simpleType>
                      <xs:restriction base="xs:token">
                        <xs:enumeration value="work"/>
                        <xs:enumeration value="home"/>
                        <xs:enumeration value="contact"/>
                        <xs:enumeration value="acquaintance"/>
                        <xs:enumeration value="friend"/>
                        <xs:enumeration value="met"/>
                      </xs:restriction>
                    </xs:simpleType>
                  </xs:sequence>
                </xs:complexType>
              </xs:element>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
```



```
        <xs:enumeration value="co-worker"/>
        <xs:enumeration value="colleague"/>
        <xs:enumeration value="co-resident"/>
        <xs:enumeration value="neighbor"/>
        <xs:enumeration value="child"/>
        <xs:enumeration value="parent"/>
        <xs:enumeration value="sibling"/>
        <xs:enumeration value="spouse"/>
        <xs:enumeration value="kin"/>
        <xs:enumeration value="muse"/>
        <xs:enumeration value="crush"/>
        <xs:enumeration value="date"/>
        <xs:enumeration value="sweetheart"/>
        <xs:enumeration value="me"/>
        <xs:enumeration value="agent"/>
        <xs:enumeration value="emergency"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:group ref="ns1:param-mediatype"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:choice>
  <xs:element ref="ns1:uri"/>
  <xs:element ref="ns1:text"/>
</xs:choice>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.7.1 -->
<xs:element name="categories">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:group ref="ns1:value-text-list"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.2 -->
<xs:element name="note">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.3 -->
<xs:element name="prodid">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.4 -->
<xs:element name="rev" type="ns1:value-timestamp"/>
<!-- 6.7.5 -->
<xs:element name="sound">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        <xs:element ref="ns1:uri"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <!-- 6.7.6 -->
  <xs:element name="uid">
    <xs:complexType>
      <xs:sequence>
        <xs:element ref="ns1:uri"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <!-- 6.7.7 -->
  <xs:element name="clientpidmap">
    <xs:complexType>
      <xs:sequence>
        <xs:element ref="ns1:sourceid"/>
        <xs:element ref="ns1:uri"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="sourceid" type="xs:positiveInteger"/>
  <!-- 6.7.8 -->
  <xs:element name="url">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="parameters" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:group ref="ns1:param-altid"/>
              <xs:group ref="ns1:param-pid"/>
              <xs:group ref="ns1:param-pref"/>
              <xs:group ref="ns1:param-type"/>
              <xs:group ref="ns1:param-mediatype"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element ref="ns1:uri"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <!-- 6.8.1 -->
  <xs:element name="key">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="parameters" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
```

```
        <xs:group ref="ns1:param-altid"/>
        <xs:group ref="ns1:param-pid"/>
        <xs:group ref="ns1:param-pref"/>
        <xs:group ref="ns1:param-type"/>
        <xs:group ref="ns1:param-mediatype"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:choice>
    <xs:element ref="ns1:uri"/>
    <xs:element ref="ns1:text"/>
  </xs:choice>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.9.1 -->
<xs:element name="fburl">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.9.2 -->
<xs:element name="caladruri">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters" minOccurs="0">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        </xs:element>
        <xs:element ref="ns1:uri"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.9.3 -->
<xs:element name="caluri">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="parameters" minOccurs="0">
                <xs:complexType>
                    <xs:sequence>
                        <xs:group ref="ns1:param-altid"/>
                        <xs:group ref="ns1:param-pid"/>
                        <xs:group ref="ns1:param-pref"/>
                        <xs:group ref="ns1:param-type"/>
                        <xs:group ref="ns1:param-mediatype"/>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
            <xs:element ref="ns1:uri"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<!-- Top-level grammar -->
<xs:group name="property">
    <xs:sequence>
        <xs:element ref="ns1:adr" minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element ref="ns1:anniversary" minOccurs="0"
            maxOccurs="1"/>
        <xs:element ref="ns1:bday" minOccurs="0"
            maxOccurs="1"/>
        <xs:element ref="ns1:caladruri" minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element ref="ns1:caluri" minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element ref="ns1:categories" minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element ref="ns1:clientpidmap" minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element ref="ns1:email" minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element ref="ns1:fburl" minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element ref="ns1:fn" minOccurs="1"
            maxOccurs="unbounded"/>
        <xs:group ref="ns1:property-geo" minOccurs="0"
```

```
    maxOccurs="unbounded"/>
<xs:element ref="ns1:impp" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:key" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:kind" minOccurs="0"
  maxOccurs="1"/>
<xs:element ref="ns1:lang" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:logo" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:member" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:n" minOccurs="0"
  maxOccurs="1"/>
<xs:element ref="ns1:nickname" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:note" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:org" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:photo" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:prodid" minOccurs="0"
  maxOccurs="1"/>
<xs:element ref="ns1:related" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:rev" minOccurs="0"
  maxOccurs="1"/>
<xs:element ref="ns1:role" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:gender" minOccurs="0"
  maxOccurs="1"/>
<xs:element ref="ns1:sound" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:source" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:tel" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:title" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:group ref="ns1:property-tz" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element ref="ns1:uid" minOccurs="0"
  maxOccurs="1"/>
<xs:element ref="ns1:url" minOccurs="0"
  maxOccurs="unbounded"/>
</xs:sequence>
```

```
</xs:group>
<xs:element name="vcards">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:vcard" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="vcardType">
  <xs:sequence>
    <xs:group ref="ns1:property"/>
    <xs:element ref="ns1:group" minOccurs="0"
      maxOccurs="unbounded"/>
    <xs:any namespace="##other" processContents="lax"
      minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="vcard" type="ns1:vcardType"/>
<xs:element name="group">
  <xs:complexType>
    <xs:group ref="ns1:property"/>
    <xs:attribute name="name" use="required"/>
  </xs:complexType>
</xs:element>
</xs:schema>
```

Appendix B. XML Validation

This document defines a number of XML schemas and contains various examples. Extracting the XML and validating the examples against the schemas can be challenging, especially due to the formatting limitations introduced by IETF RFCs. For those readers who copy the XML schemas and examples directly from this document, please consider that errors might be introduced due to line breaks and extra whitespaces in the regular expressions contained in the vCard schema in [Appendix A](#). To validate the PIDF-LO from Figure 18, it is also necessary to consult the referenced RFCs and copy the schemas necessary for successful validation.

The XML schemas found in this document include a 'SchemaLocation' attribute. Depending on the location of the downloaded schema files, you may need to adjust this schema location or configure your XML editor to point to the location.

For the convenience of the reader, the schemas are available at [[IANA-XML-Schemas](#)], and the XML examples are available at the IETF ECRIT working group wiki page [[ECRIT-WG-wiki](#)].

Acknowledgments

This work was originally started in NENA and has benefited from a large number of participants involved in NENA standardization efforts, originally in the Long Term Definition working group, the Data Technical Committee, and most recently in the Additional Data working group. The authors are grateful for the initial work and extended comments provided by many NENA participants, including Delaine Arnold, Marc Berryman, Guy Caron, Brian Dupras, Mark Fletcher, James Leyerle, Kathy McMahon, Christian Militeau, Ira Pyles, Matt Serra, and Robert (Bob) Sherry. Amursana Khiyod, Robert Sherry, Frank Rahoi, Scott Ross, and Tom Klepetka provided valuable feedback regarding the vCard/xCard use in this specification.

We would also like to thank Paul Kyzivat, Gunnar Hellstrom, Martin Thomson, Keith Drage, Laura Liess, Chris Santer, Barbara Stark, Chris Santer, Archie Cobbs, Magnus Nystrom, Stephen Farrell, Amanda Baber, Dan Banks, Andrew Newton, Philip Reichl, and Francis Dupont for their review comments. Alissa Cooper, Guy Caron, Ben Campbell, and Barry Leiba deserve special mention for their detailed and extensive review comments, which were very helpful and appreciated.

Authors' Addresses

Randall Gellens
San Diego, CA 92121
United States

Email: rg+ietf@randy.pensive.org

Brian Rosen
NeuStar
470 Conrad Dr.
Mars, PA 16046
United States

Phone: +1 724 382 1051
Email: br@brianrosen.net

Hannes Tschofenig
Hall in Tirol 6060
Austria

Email: Hannes.tschofenig@gmx.net
URI: <http://www.tschofenig.priv.at>

Roger Marshall
TeleCommunication Systems, Inc.
2401 Elliott Avenue
Seattle, WA 98121
United States

Phone: +1 206 792 2424
Email: rmarshall@telecomsys.com
URI: <http://www.telecomsys.com>

James Winterbottom
Winterb Consulting Services
Gwynneville, NSW 2500
Australia

Phone: +61 448 266004
Email: a.james.winterbottom@gmail.com