                Manufacturer Usage Description Specification

Abstract

   This memo specifies a component-based architecture for Manufacturer
   Usage Descriptions (MUDs). The goal of MUD is to provide a means for
   end devices to signal to the network what sort of access and network
   functionality they require to properly function. The initial focus
   is on access control. Later work can delve into other aspects.

   This memo specifies two YANG modules, IPv4 and IPv6 DHCP options, a
   Link Layer Discovery Protocol (LLDP) TLV, a URL, an X.509 certificate
   extension, and a means to sign and verify the descriptions.

Status of This Memo

   This is an Internet Standards Track document.

   This document is a product of the Internet Engineering Task Force
   (IETF). It represents the consensus of the IETF community. It has
   received public review and has been approved for publication by the
   Internet Engineering Steering Group (IESG). Further information on
   Internet Standards is available in Section 2 of RFC 7841.

   Information about the current status of this document, any errata,
   and how to provide feedback on it may be obtained at
   https://www.rfc-editor.org/info/rfc8520.

Copyright Notice

Table of Contents

1. Introduction

   The Internet has largely been constructed for general purpose
   computers, those devices that may be used for a purpose that is
   specified by those who own the device. In [RFC1984], it was presumed
   that an end device would be most capable of protecting itself. This
   made sense when the typical device was a workstation or a mainframe,
   and it continues to make sense for general purpose computing devices
   today, including laptops, smart phones, and tablets.

   [RFC7452] discusses design patterns for, and poses questions about,
   smart objects. Let us then posit a group of objects that are
   specifically not intended to be used for general purpose computing
   tasks. These devices, which this memo refers to as Things, have a
   specific purpose. By definition, therefore, all other uses are not
   intended. If a small number of communication patterns follows from
   those small number of uses, the combination of these two statements
   can be restated as a Manufacturer Usage Description (MUD) that can be
   applied at various points within a network. MUD primarily addresses
   threats to the device rather than the device as a threat. In some
   circumstances, however, MUD may offer some protection in the latter
   case, depending on how the MUD URL is communicated and how devices
   and their communications are authenticated.

   We use the notion of "manufacturer" loosely in this context to refer
   to the entity or organization that will state how a device is
   intended to be used. For example, in the context of a light bulb,
   this might indeed be the light bulb manufacturer. In the context of
   a smarter device that has a built in Linux stack, it might be an
   integrator of that device. The key points are that the device itself
   is assumed to serve a limited purpose, and that there exists an
   organization in the supply chain of that device that will take
   responsibility for informing the network about that purpose.

   The intent of MUD is to provide the following:

   o Substantially reduce the threat surface on a device to those
      communications intended by the manufacturer.

   o Provide a means to scale network policies to the ever-increasing
      number of types of devices in the network.

   o Provide a means to address at least some vulnerabilities in a way
      that is faster than the time it might take to update systems.
      This will be particularly true for systems that are no longer
      supported.

   o Keep the cost of implementation of such a system to the bare
      minimum.

   o Provide a means of extensibility for manufacturers to express
      other device capabilities or requirements.

   MUD consists of three architectural building blocks:

   o A URL that can be used to locate a description;

   o The description itself, including how it is interpreted; and

   o A means for local network management systems to retrieve the
      description.

   MUD is most effective when the network is able to identify in some
   way the remote endpoints that Things will talk to.

   In this specification, we describe each of these building blocks and
   how they are intended to be used together. However, they may also be
   used separately, independent of this specification, by local
   deployments for their own purposes.

1.1. What MUD Doesn't Do

   MUD is not intended to address network authorization of general
   purpose computers, as their manufacturers cannot envision a specific
   communication pattern to describe. In addition, even those devices
   that have a single or small number of uses might have very broad
   communication patterns. MUD on its own is not for them either.

   Although MUD can provide network administrators with some additional
   protection when device vulnerabilities exist, it will never replace
   the need for manufacturers to patch vulnerabilities.

   Finally, no matter what the manufacturer specifies in a MUD file,
   these are not directives, but suggestions. How they are instantiated
   locally will depend on many factors and will be ultimately up to the
   local network administrator, who must decide what is appropriate in a
   given circumstances.

1.2. A Simple Example

   A light bulb is intended to light a room. It may be remotely
   controlled through the network, and it may make use of a rendezvous
   service (which could be accessed by an application on a smart phone).
   What we can say about that light bulb, then, is that all other
   network access is unwanted. It will not contact a news service, nor

   speak to the refrigerator, and it has no need of a printer or other
   devices. It has no social networking friends. Therefore, applying
   an access list to it that states it will only connect to the single
   rendezvous service will not impede performing its function; at the
   same time, this will allow the network to provide the light bulb and
   other devices an additional layer of protection.

1.3. Terminology

   MUD: Manufacturer Usage Description.

   MUD file: a file containing YANG-based JSON that describes a Thing
      and associated suggested specific network behavior.

   MUD file server: a web server that hosts a MUD file.

   MUD manager: the system that requests and receives the MUD file from
      the MUD server. After it has processed a MUD file, it may direct
      changes to relevant network elements.

   MUD controller: a synonym that has been used in the past for MUD
      manager.

   MUD URL: a URL that can be used by the MUD manager to receive the
      MUD file.

   Thing: the device emitting a MUD URL.

   Manufacturer: the entity that configures the Thing to emit the MUD
      URL and the one who asserts a recommendation in a MUD file. The
      manufacturer might not always be the entity that constructs a
      Thing. It could, for instance, be a systems integrator, or even a
      component provider.

   The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT",
   "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and
   "OPTIONAL" in this document are to be interpreted as described in
   BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all
   capitals, as shown here.

1.4. Determining Intended Use

   The notion of intended use is in itself not new. Network
   administrators apply access lists every day to allow for only such
   use. This notion of white listing was well described by Chapman and
   Zwicky in [FW95]. Profiling systems that make use of heuristics to
   identify types of systems have existed for years as well.

A Thing could just as easily tell the network what sort of access it
requires without going into what sort of system it is. This would,
in effect, be the converse of [RFC7488]. In seeking a general
solution, however, we assume that a device will implement
functionality necessary to fulfill its limited purpose. This is
basic economic constraint. Unless the network would refuse access to
such a device, its developers would have no reason to provide the
network any information. To date, such an assertion has held true.

1.5. Finding a Policy: The MUD URL

Our work begins with the device emitting a Universal Resource Locator
(URL) [RFC3986]. This URL serves both to classify the device type
and to provide a means to locate a policy file.

MUD URLs MUST use the "https" scheme [RFC7230].

In this memo, three means are defined to emit the MUD URL, as
follows:

o A DHCP option [RFC2131] [RFC8415] that the DHCP client uses to
   inform the DHCP server. The DHCP server may take further actions,
   such as acting as the MUD manager or passing the MUD URL along to
   the MUD manager.

o An X.509 constraint. The IEEE has developed IEEE 802.1AR
   [IEEE8021AR] to provide a certificate-based approach to
   communicate device characteristics, which itself relies on
   [RFC5280]. The MUD URL extension is non-critical, as required by
   IEEE 802.1AR. Various means may be used to communicate that
   certificate, including the Tunnel Extensible Authentication
   Protocol (TEAP) [RFC7170].

o Finally, a Link Layer Discovery Protocol (LLDP) frame is defined
   [IEEE8021AB].

It is possible that there may be other means for a MUD URL to be
learned by a network. For instance, some devices may already be
fielded or have very limited ability to communicate a MUD URL, and
yet they can be identified through some means, such as a serial
number or a public key. In these cases, manufacturers may be able to
map those identifiers to particular MUD URLs (or even the files
themselves). Similarly, there may be alternative resolution
mechanisms available for situations where Internet connectivity is
limited or does not exist. Such mechanisms are not described in this
memo, but they are possible. Implementors are encouraged to allow
for the flexibility of how MUD URLs may be learned.

1.6. Processing of the MUD URL

   MUD managers that are able to do so SHOULD retrieve MUD URLs and
   signature files as per [RFC7230], using the GET method [RFC7231].
   They MUST validate the certificate using the rules in [RFC2818],
   Section 3.1.

   Requests for MUD URLs SHOULD include an "Accept" header field
   ([RFC7231], Section 5.3.2) containing "application/mud+json", an
   "Accept-Language" header field ([RFC7231], Section 5.3.5), and a
   "User-Agent" header field ([RFC7231], Section 5.5.3).

   MUD managers SHOULD automatically process 3xx response status codes.

   If a MUD manager is not able to fetch a MUD URL, other means MAY be
   used to import MUD files and associated signature files. So long as
   the signature of the file can be validated, the file can be used. In
   such environments, controllers SHOULD warn administrators when cache-
   validity expiry is approaching so that they may check for new files.

   It may not be possible for a MUD manager to retrieve a MUD file at
   any given time. Should a MUD manager fail to retrieve a MUD file, it
   SHOULD consider the existing one safe to use, at least for a time.
   After some period, it SHOULD log that it has been unable to retrieve
   the file. There may be very good reasons for such failures,
   including the possibility that the MUD manager is in an offline
   environment, the local Internet connection has failed, or the remote
   Internet connection has failed. It is also possible that an attacker
   is attempting to interfere with the deployment of a device. How to
   handle such circumstances is a local decision.

1.7. Types of Policies

   When the MUD URL is resolved, the MUD manager retrieves a file that
   describes what sort of communications a device is designed to have.
   The manufacturer may specify either specific hosts for cloud-based
   services or certain classes for access within an operational network.
   An example of a class might be "devices of a specified manufacturer
   type", where the manufacturer type itself is indicated simply by the
   authority component (e.g., the domain name) of the MUD URL. Another
   example might be to allow or disallow local access. Just like other
   policies, these may be combined. For example:

   o Allow access to devices of the same manufacturer

   o Allow access to and from controllers via the Constrained
      Application Protocol (COAP) [RFC7252]

   o Allow access to local DNS/NTP

   o Deny all other access

   A printer might have a description that states:

   o Allow access for port IPP or port LPD

   o Allow local access for port HTTP

   o Deny all other access

   In this way, anyone can print to the printer, but local access would
   be required for the management interface.

   The files that are retrieved are intended to be closely aligned to
   existing network architectures so that they are easy to deploy. We
   make use of YANG [RFC7950] because it provides accurate and adequate
   models for use by network devices. JSON [RFC8259] is used as a
   serialization format for compactness and readability, relative to
   XML. Other formats may be chosen with later versions of MUD.

   While the policy examples given here focus on access control, this is
   not intended to be the sole focus. By structuring the model
   described in this document with clear extension points, other
   descriptions could be included. One that often comes to mind is
   quality of service.

   The YANG modules specified here are extensions of [RFC8519]. The
   extensions to this model allow for a manufacturer to express classes
   of systems that a manufacturer would find necessary for the proper
   function of the device. Two modules are specified. The first module
   specifies a means for domain names to be used in Access Control Lists
   (ACLs) so that devices that have their controllers in the cloud may
   be appropriately authorized with domain names, where the mapping of
   those names to addresses may rapidly change.

   The other module abstracts away IP addresses into certain classes
   that are instantiated into actual IP addresses through local
   processing. Through these classes, manufacturers can specify how the
   device is designed to communicate, so that network elements can be
   configured by local systems that have local topological knowledge.
   That is, the deployment populates the classes that the manufacturer
   specifies. The abstractions below map to zero or more hosts, as
   follows:

   Manufacturer: A device made by a particular manufacturer, as
      identified by the authority component of its MUD URL.

same-manufacturer: Devices that have the same authority component of
   their MUD URL.

controller: Devices that the local network administrator admits to
   the particular class.

my-controller: Devices intended to serve as controllers for the MUD
   URL that the Thing emitted.

local: The class of IP addresses that are scoped within some
   administrative boundary. By default, it is suggested that this be
   the local subnet.

The "manufacturer" classes can be easily specified by the
manufacturer, whereas controller classes are initially envisioned to
be specified by the administrator.

Because manufacturers do not know who will be using their devices, it
is important for functionality referenced in usage descriptions to be
relatively ubiquitous and mature. For these reasons, the YANG-based
configuration in a MUD file is limited to the modules either
specified or referenced in this document, or specified in documented
extensions.

1.8. The Manufacturer Usage Description Architecture

With these components laid out, we now have the basis for an
architecture. This leads us to ASCII art.

```
  ......................................
  .                    _____  .         _____
  .                   |            | .        |             |
  .                   |    MUD     |-->get URL-->|    MUD      |
  .                   |  Manager   | .(https) | File Server |
  .  End system network |_____|<-MUD file<-<|_____|
  .                          .       .
  .                          .       .
  . _____               _____   .
  .|       | (DHCP et al.) | router |  .
  .| Thing |---->MUD URL-->|   or   |  .
  .|_____|              | switch |  .
  .                       |_____|  .
  ......................................
```

Figure 1: MUD Architecture

   In the above diagram, the switch or router collects MUD URLs and
   forwards them to the MUD manager (a network management system) for
   processing. This happens in different ways, depending on how the URL
   is communicated. For instance, in the case of DHCP, the DHCP server
   might receive the URL and then process it. In the case of IEEE
   802.1X [IEEE8021X], the switch would carry the URL via a certificate
   to the authentication server via the Extensible Authentication
   Protocol (EAP) over Radius [RFC3748], which would then process it.
   One method to do this is TEAP, as described in [RFC7170]. The
   certificate extension is described below.

   The information returned by the MUD file server is valid for as long
   as the Thing is connected. There is no expiry. However, if the MUD
   manager has detected that the MUD file for a Thing has changed, it
   SHOULD update the policy expeditiously, taking into account whatever
   approval flow is required in a deployment. In this way, new
   recommendations from the manufacturer can be processed in a timely
   fashion.

   The information returned by the MUD file server (a web server) is
   valid for the duration of the Thing's connection, or as specified in
   the description. Thus, if the Thing is disconnected, any associated
   configuration in the switch can be removed. Similarly, from time to
   time the description may be refreshed, based on new capabilities or
   communication patterns or vulnerabilities.

   The web server is typically run by or on behalf of the manufacturer.
   Its domain name is that of the authority found in the MUD URL. For
   legacy cases where Things cannot emit a URL, if the switch is able to
   determine the appropriate URL, it may proxy it. In a trivial case,
   it may hardcode a MUD URL on a switch port or a map from some
   available identifier such as an L2 address or certificate hash to a
   MUD URL.

   The role of the MUD manager in this environment is to do the
   following:

   o receive MUD URLs,

   o fetch MUD files,

   o translate abstractions in the MUD files to specific network
      element configuration,

   o maintain and update any required mappings of the abstractions, and

   o update network elements with appropriate configuration.

A MUD manager may be a component of an Authentication, Authorization, and Accounting (AAA) system or a network management system. Communication within those systems and from those systems to network elements is beyond the scope of this memo.

1.9. Order of Operations

As mentioned above, MUD contains architectural building blocks, so the order of operation may vary. However, here is one clear intended example:

1. Thing emits a URL.

2. That URL is forwarded to a MUD manager by the nearest switch (how this happens depends on the way in which the MUD URL is emitted).

3. The MUD manager retrieves the MUD file and signature from the MUD file server, assuming it doesn't already have copies. After validating the signature, it may test the URL against a web or domain reputation service, and it may test any hosts within the file against those reputation services, as it deems fit.

4. The MUD manager may query the administrator for permission to add the Thing and associated policy. If the Thing is known or the Thing type is known, it may skip this step.

5. The MUD manager instantiates local configuration based on the abstractions defined in this document.

6. The MUD manager configures the switch nearest the Thing. Other systems may be configured as well.

7. When the Thing disconnects, policy is removed.

2. The MUD Model and Semantic Meaning

A MUD file consists of a YANG model instance that has been serialized in JSON [RFC7951]. For purposes of MUD, the nodes that can be modified are access lists as augmented by this model. The MUD file is limited to the serialization of only the following YANG schema:

o ietf-access-control-list [RFC8519]

o ietf-mud (RFC 8520)

o ietf-acldns (RFC 8520)

Extensions may be used to add additional schema. This is described
further on.

To provide the widest possible deployment, publishers of MUD files
SHOULD make use of the abstractions in this memo and avoid the use of
IP addresses. A MUD manager SHOULD NOT automatically implement any
MUD file that contains IP addresses, especially those that might have
local significance. The addressing of one side of an access list is
implicit, based on whether it is applied as to-device-policy or
from-device-policy.

With the exceptions of the "name" of the ACL, "type", "name" of the
Access Control Entry (ACE), and TCP and UDP source and destination
port information, publishers of MUD files SHOULD limit the use of ACL
model leaf nodes expressed to those found in this specification.
Absent any extensions, MUD files are assumed to implement only the
following ACL model features:

o match-on-ipv4, match-on-ipv6, match-on-tcp, match-on-udp,
   match-on-icmp

Furthermore, only "accept" or "drop" actions SHOULD be included. A
MUD manager MAY choose to interpret "reject" as "drop". A MUD
manager SHOULD ignore all other actions. This is because
manufacturers do not have sufficient context within a local
deployment to know whether reject is appropriate. That is a decision
that should be left to a network administrator.

Given that MUD does not deal with interfaces, the support of the
"ietf-interfaces" module [RFC8343] is not required. Specifically,
the support of interface-related features and branches (e.g.,
interface-attachment and interface-stats) of the ACL YANG module is
not required.

In fact, MUD managers MAY ignore any particular component of a
description or MAY ignore the description in its entirety, and they
SHOULD carefully inspect all MUD descriptions. Publishers of MUD
files MUST NOT include other nodes except as described in
Section 3.9. See that section for more information.

2.1. The IETF-MUD YANG Module

   This module is structured into three parts:

   o The first component, the "mud" container, holds information that
      is relevant to retrieval and validity of the MUD file itself, as
      well as policy intended to and from the Thing.

   o The second component augments the matching container of the ACL
      model to add several nodes that are relevant to the MUD URL, or
      they are otherwise abstracted for use within a local environment.

   o The third component augments the tcp-acl container of the ACL
      model to add the ability to match on the direction of initiation
      of a TCP connection.

   A valid MUD file will contain two root objects: a "mud" container and
   an "acls" container. Extensions may add additional root objects as
   required. As a reminder, when parsing acls, elements within a
   "match" block are logically ANDed. In general, a single abstraction
   in a match statement should be used. For instance, it makes little
   sense to match both "my-controller" and "controller" with an
   argument, since they are highly unlikely to be the same value.

   A simplified graphical representation of the data models is used in
   this document. The meaning of the symbols in these diagrams is
   explained in [RFC8340].

```
module: ietf-mud
  +--rw mud!
     +--rw mud-version          uint8
     +--rw mud-url              inet:uri
     +--rw last-update          yang:date-and-time
     +--rw mud-signature?       inet:uri
     +--rw cache-validity?      uint8
     +--rw is-supported         boolean
     +--rw systeminfo?          string
     +--rw mfg-name?            string
     +--rw model-name?          string
     +--rw firmware-rev?        string
     +--rw software-rev?        string
     +--rw documentation?       inet:uri
     +--rw extensions*          string
     +--rw from-device-policy
     |  +--rw acls
     |     +--rw access-list* [name]
     |        +--rw name     -> /acl:acls/acl/name
     +--rw to-device-policy
        +--rw acls
           +--rw access-list* [name]
              +--rw name     -> /acl:acls/acl/name

  augment /acl:acls/acl:acl/acl:aces/acl:ace/acl:matches:
    +--rw mud
       +--rw manufacturer?       inet:host
       +--rw same-manufacturer?  empty
       +--rw model?              inet:uri
       +--rw local-networks?     empty
       +--rw controller?         inet:uri
       +--rw my-controller?      empty
  augment
    /acl:acls/acl:acl/acl:aces/acl:ace/acl:matches
       /acl:l4/acl:tcp/acl:tcp:
    +--rw direction-initiated?   direction
```

3. MUD Model Definitions for the Root "mud" Container

3.1. mud-version

   This node specifies the integer version of the MUD specification.
   This memo specifies version 1.

3.2. MUD URL

   This URL identifies the MUD file. This is useful when the file and
   associated signature are manually uploaded, say, in an offline mode.

3.3. to-device-policy and from-device-policy Containers

   [RFC8519] describes access lists. In the case of MUD, a MUD file
   must be explicit in describing the communication pattern of a Thing,
   and that includes indicating what is to be permitted or denied in
   either direction of communication. Hence, each of these containers
   indicates the appropriate direction of a flow in association with a
   particular Thing. They contain references to specific access lists.

3.4. last-update

   This is a date-and-time value of when the MUD file was generated.
   This is akin to a version number. Its form is taken from [RFC6991].

3.5. cache-validity

   This uint8 is the period of time in hours that a network management
   station MUST wait since its last retrieval before checking for an
   update. It is RECOMMENDED that this value be no less than 24, and it
   MUST NOT be more than 168 for any Thing that is supported. This
   period SHOULD be no shorter than any period determined through HTTP
   caching directives (e.g., "cache-control" or "Expires"). N.B., the
   expiring of this timer does not require the MUD manager to discard
   the MUD file, nor terminate access to a Thing. See Section 16 for
   more information.

3.6. is-supported

   This boolean is an indication from the manufacturer to the network
   administrator as to whether or not the Thing is supported. In this
   context, a Thing is said to not be supported if the manufacturer
   intends never to issue a firmware or software update to the Thing or
   never to update the MUD file. A MUD manager MAY still periodically
   check for updates.

3.7. systeminfo

   This is a textual UTF-8 description of the Thing to be connected.
   The intent is for administrators to be able to see a brief
   displayable description of the Thing. It SHOULD NOT exceed 60
   characters worth of display space.

3.8. mfg-name, software-rev, model-name, and firmware-rev

   These optional fields are filled in as specified by [RFC8348]. Note
   that firmware-rev and software-rev MUST NOT be populated in a MUD
   file if the device can be upgraded but the MUD URL cannot be. This
   would be the case, for instance, with MUD URLs that are contained in
   802.1AR certificates.

3.9. extensions

   This optional leaf-list names MUD extensions that are used in the MUD
   file. Note that MUD extensions MUST NOT be used in a MUD file
   without the extensions being declared. Implementations MUST ignore
   any node in this file that they do not understand.

   Note that extensions can either extend the MUD file as described in
   the previous paragraph or reference other work. An extension example
   can be found in Appendix B.

4. Augmentation to the ACL Model

   Note that in this section, when we use the term "match", we are
   referring to the ACL model "matches" node.

4.1. manufacturer

   This node consists of a hostname that would be matched against the
   authority component of another Thing's MUD URL. In its simplest
   form, "manufacturer" and "same-manufacturer" may be implemented as
   access lists. In more complex forms, additional network capabilities
   may be used. For example, if one saw the line "manufacturer" :
   "flobbidy.example.com", then all Things that registered with a MUD
   URL that contained flobbity.example.com in its authority section
   would match.

4.2. same-manufacturer

   This null-valued node is an equivalent for when the manufacturer
   element is used to indicate that the authority found in another
   Thing's MUD URL matches that of the authority found in this Thing's
   MUD URL. For example, if the Thing's MUD URL were
   "https://b1.example.com/ThingV1", then all devices that had a MUD URL
   with an authority section of b1.example.com would match.

4.3. documentation

   This URI consists of a URL that points to documentation relating to
   the device and the MUD file. This can prove particularly useful when
   the "controller" class is used, so that its use can be explained.

4.4. model

   This string matches the entire MUD URL, thus covering the model that
   is unique within the context of the authority. It may contain not
   only model information, but versioning information as well, and any
   other information that the manufacturer wishes to add. The intended
   use is for devices of this precise class to match, to permit or deny
   communication between one another.

4.5. local-networks

   This null-valued node expands to include local networks. Its default
   expansion is that packets must not traverse toward a default route
   that is received from the router. However, administrators may expand
   the expression as is appropriate in their deployments.

4.6. controller

   This URI specifies a value that a controller will register with the
   MUD manager. The node then is expanded to the set of hosts that are
   so registered. This node may also be a URN. In this case, the URN
   describes a well-known service, such as DNS or NTP, that has been
   standardized. Both of those URNs may be found in Section 17.7.

   When "my-controller" is used, it is possible that the administrator
   will be prompted to populate that class for each and every model.
   Use of "controller" with a named class allows the user to populate
   that class only once for many different models that a manufacturer
   may produce.

   Controller URIs MAY take the form of a URL (e.g., "http[s]://").
   However, MUD managers MUST NOT resolve and retrieve such files, and
   it is RECOMMENDED that there be no such file at this time, as their
   form and function may be defined at a point in the future. For now,
   URLs should serve simply as class names and may be populated by the
   local deployment administrator.

   Great care should be taken by MUD managers when invoking the
   controller class in the form of URLs. For one thing, it requires
   some understanding by the administrator as to when it is appropriate.

   Pre-registration in such classes by controllers with the MUD server
   is encouraged. The mechanism to do that is beyond the scope of this
   work.

4.7. my-controller

   This null-valued node signals to the MUD manager to use whatever
   mapping it has for this MUD URL to a particular group of hosts. This
   may require prompting the administrator for class members. Future
   work should seek to automate membership management.

4.8. direction-initiated

   This MUST only be applied to TCP. This matches the direction in
   which a TCP connection is initiated. When the direction initiated is
   "from-device", packets that are transmitted in the direction of a
   Thing MUST be dropped unless the Thing has first initiated a TCP
   connection. By way of example, this node may be implemented in its
   simplest form by looking at naked SYN bits, but it may also be
   implemented through more stateful mechanisms.

   When applied, this matches packets when the flow was initiated in the
   corresponding direction. [RFC6092] specifies IPv6 guidance best
   practices. While that document is scoped specifically to IPv6, its
   contents are applicable for IPv4 as well.

5. Processing of the MUD File

   To keep things relatively simple in addition to whatever definitions
   exist, we also apply two additional default behaviors:

   o Anything not explicitly permitted is denied.

   o Local DNS and NTP are, by default, permitted to and from the
      Thing.

   An explicit description of the defaults can be found in Appendix A.
   These are applied AFTER all other explicit rules. Thus, a default
   behavior can be changed with a "drop" action.

6. What Does a MUD URL Look Like?

   MUD URLs are required to use the "https" scheme, in order to
   establish the MUD file server's identity and assure integrity of the
   MUD file.

   Any "https://" URL can be a MUD URL. For example:

     https://things.example.org/product_abc123/v5
     https://www.example.net/mudfiles/temperature_sensor/
     https://example.com/lightbulbs/colour/v1

   A manufacturer may construct a MUD URL in any way, so long as it
   makes use of the "https" scheme.

7. The MUD YANG Model

```
   <CODE BEGINS>file "ietf-mud@2019-01-28.yang"
   module ietf-mud {
     yang-version 1.1;
     namespace "urn:ietf:params:xml:ns:yang:ietf-mud";
     prefix ietf-mud;

     import ietf-access-control-list {
       prefix acl;
     }
     import ietf-yang-types {
       prefix yang;
     }
     import ietf-inet-types {
       prefix inet;
     }

     organization
       "IETF OPSAWG (Operations and Management Area Working Group)";
     contact
       "WG Web: <https://datatracker.ietf.org/wg/opsawg/>
        WG List: opsawg@ietf.org

        Author: Eliot Lear
                lear@cisco.com

        Author: Ralph Droms
                rdroms@gmail.com

        Author: Dan Romascanu
                dromasca@gmail.com
       ";
     description
       "This YANG module defines a component that augments the
        IETF description of an access list.  This specific module
        focuses on additional filters that include local, model,
        and same-manufacturer.
```

```
      This module is intended to be serialized via JSON and stored
      as a file, as described in RFC 8520.

      The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
      NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
      'MAY', and 'OPTIONAL' in this document are to be interpreted as
      described in BCP 14 (RFC 2119) (RFC 8174) when, and only when,
      they appear in all capitals, as shown here.

      Copyright (c) 2019 IETF Trust and the persons identified as
      authors of the code.  All rights reserved.

      Redistribution and use in source and binary forms, with or
      without modification, is permitted pursuant to, and subject
      to the license terms contained in, the Simplified BSD License
      set forth in Section 4.c of the IETF Trust's Legal Provisions
      Relating to IETF Documents
      (http://trustee.ietf.org/license-info).

      This version of this YANG module is part of RFC 8520; see
      the RFC itself for full legal notices.";

  revision 2019-01-28 {
    description
      "Initial proposed standard.";
    reference
      "RFC 8520: Manufacturer Usage Description
       Specification";
  }

  typedef direction {
    type enumeration {
      enum to-device {
        description
          "packets or flows destined to the target
           Thing.";
      }
      enum from-device {
        description
          "packets or flows destined from
           the target Thing.";
      }
    }
    description
      "Which way are we talking about?";
  }

  container mud {
```

```
          presence "Enabled for this particular MUD URL";
          description
            "MUD-related information, as specified
             by RFC 8520.";
          uses mud-grouping;
        }

      grouping mud-grouping {
        description
          "Information about when support ends (or ended)
           and when to refresh.";
        leaf mud-version {
          type uint8;
          mandatory true;
          description
            "This is the version of the MUD
             specification.  This memo specifies version 1.";
        }
        leaf mud-url {
          type inet:uri;
          mandatory true;
          description
            "This is the MUD URL associated with the entry found
             in a MUD file.";
        }
        leaf last-update {
          type yang:date-and-time;
          mandatory true;
          description
            "This is intended to be when the current MUD file
             was generated.  MUD managers SHOULD NOT check
             for updates between this time plus cache validity.";
        }
        leaf mud-signature {
          type inet:uri;
          description
            "A URI that resolves to a signature as
             described in this specification.";
        }
        leaf cache-validity {
          type uint8 {
            range "1..168";
          }
          units "hours";
          default "48";
          description
            "The information retrieved from the MUD server is
             valid for these many hours, after which it should
```

```
           be refreshed.  N.B., MUD manager implementations
           need not discard MUD files beyond this period.";
      }
      leaf is-supported {
        type boolean;
        mandatory true;
        description
          "This boolean indicates whether or not the Thing is
           currently supported by the manufacturer.";
      }
      leaf systeminfo {
        type string;
        description
          "A UTF-8 description of this Thing.  This
           should be a brief description that may be
           displayed to the user to determine whether
           to allow the Thing on the
           network.";
      }
      leaf mfg-name {
        type string;
        description
          "Manufacturer name, as described in
           the ietf-hardware YANG module.";
      }
      leaf model-name {
        type string;
        description
          "Model name, as described in the
           ietf-hardware YANG module.";
      }
      leaf firmware-rev {
        type string;
        description
          "firmware-rev, as described in the
           ietf-hardware YANG module.  Note that this field
           MUST NOT be included when the device can be
           updated but the MUD URL cannot.";
      }
      leaf software-rev {
        type string;
        description
          "software-rev, as described in the
           ietf-hardware YANG module.  Note that this field
           MUST NOT be included when the device can be
           updated but the MUD URL cannot.";
      }
      leaf documentation {
```

```
            type inet:uri;
            description
              "This URL points to documentation that
               relates to this device and any classes that it uses
               in its MUD file.  A caution: MUD managers need
               not resolve this URL on their own but rather simply
               provide it to the administrator.  Parsing HTML is
               not an intended function of a MUD manager.";
          }
          leaf-list extensions {
            type string {
              length "1..40";
            }
            description
              "A list of extension names that are used in this MUD
               file.  Each name is registered with the IANA and
               described in an RFC.";
          }
          container from-device-policy {
            description
              "The policies that should be enforced on traffic
               coming from the device.  These policies are not
               necessarily intended to be enforced at a single
               point but may be rendered by the controller to any
               relevant enforcement points in the network or
               elsewhere.";
            uses access-lists;
          }
          container to-device-policy {
            description
              "The policies that should be enforced on traffic
               going to the device.  These policies are not
               necessarily intended to be enforced at a single
               point but may be rendered by the controller to any
               relevant enforcement points in the network or
               elsewhere.";
            uses access-lists;
          }
        }

      grouping access-lists {
        description
          "A grouping for access lists in the context of device
           policy.";
        container access-lists {
          description
            "The access lists that should be applied to traffic
             to or from the device.";
```

```
        list access-list {
          key "name";
          description
            "Each entry on this list refers to an ACL that
             should be present in the overall access list
             data model.  Each ACL is identified by name and
             type.";
          leaf name {
            type leafref {
              path "/acl:acls/acl:acl/acl:name";
            }
            description
              "The name of the ACL for this entry.";
          }
        }
      }
    }

    augment "/acl:acls/acl:acl/acl:aces/acl:ace/acl:matches" {
      description
        "adding abstractions to avoid the need of IP addresses.";
      container mud {
        description
          "MUD-specific matches.";
        leaf manufacturer {
          type inet:host;
          description
            "A domain that is intended to match the authority
             section of the MUD URL.  This node is used to specify
             one or more manufacturers a device should
             be authorized to access.";
        }
        leaf same-manufacturer {
          type empty;
          description
            "This node matches the authority section of the MUD URL
             of a Thing.  It is intended to grant access to all
             devices with the same authority section.";
        }
        leaf model {
          type inet:uri;
          description
            "Devices of the specified model type will match if
             they have an identical MUD URL.";
        }
        leaf local-networks {
          type empty;
          description
```

```
                  "IP addresses will match this node if they are
                   considered local addresses.  A local address may be
                   a list of locally defined prefixes and masks
                   that indicate a particular administrative scope.";
          }
          leaf controller {
            type inet:uri;
            description
              "This node names a class that has associated with it
               zero or more IP addresses to match against.  These
               may be scoped to a manufacturer or via a standard
               URN.";
          }
          leaf my-controller {
            type empty;
            description
              "This node matches one or more network elements that
               have been configured to be the controller for this
               Thing, based on its MUD URL.";
          }
        }
      }
      augment "/acl:acls/acl:acl/acl:aces/acl:ace/acl:matches"
            + "/acl:l4/acl:tcp/acl:tcp" {
        description
          "add direction-initiated";
        leaf direction-initiated {
          type direction;
          description
            "This node matches based on which direction a
             connection was initiated.  The means by which that
             is determined is discussed in this document.";
        }
      }
    }
    <CODE ENDS>
```

8. The Domain Name Extension to the ACL Model

   This module specifies an extension to the IETF-ACL model such that
   domain names may be referenced by augmenting the "matches" node.
   Different implementations may deploy differing methods to maintain
   the mapping between the IP address and domain name, if indeed any are
   needed. However, the intent is that resources that are referred to
   using a name should be authorized (or not) within an access list.

   The structure of the change is as follows:

   module: ietf-acldns
     augment /acl:acls/acl:acl/acl:aces/acl:ace/
       acl:matches/acl:l3/acl:ipv4/acl:ipv4:
       +--rw src-dnsname?   inet:host
       +--rw dst-dnsname?   inet:host
     augment /acl:acls/acl:acl/acl:aces/acl:ace/
       acl:matches/acl:l3/acl:ipv6/acl:ipv6:
       +--rw src-dnsname?   inet:host
       +--rw dst-dnsname?   inet:host

   The choice of these particular points in the access control list
   model is based on the assumption that we are in some way referring to
   IP-related resources, as that is what the DNS returns. A domain name
   in our context is defined in [RFC6991]. The augmentations are
   replicated across IPv4 and IPv6 to allow MUD file authors the ability
   to control the IP version that the Thing may utilize.

   The following nodes are defined.

8.1. src-dnsname

   The argument corresponds to a domain name of a source as specified by
   inet:host. A number of means may be used to resolve hosts. What is
   important is that such resolutions be consistent with ACLs that are
   required by Things to properly operate.

8.2. dst-dnsname

   The argument corresponds to a domain name of a destination as
   specified by inet:host. See the previous section (Section 8.1)
   relating to resolution.

   Note that when using either of these with a MUD file, because access
   is associated with a particular Thing, MUD files MUST NOT contain
   either a src-dnsname in an ACL associated with from-device-policy or
   a dst-dnsname associated with to-device-policy.

8.3. The ietf-acldns Model

```
<CODE BEGINS>file "ietf-acldns@2019-01-28.yang"
module ietf-acldns {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-acldns";
  prefix ietf-acldns;

  import ietf-access-control-list {
    prefix acl;
  }
  import ietf-inet-types {
    prefix inet;
  }

  organization
    "IETF OPSAWG (Operations and Management Area Working Group)";
  contact
    "WG Web: <https://datatracker.ietf.org/wg/opsawg/>
     WG List: opsawg@ietf.org

     Author: Eliot Lear
             lear@cisco.com

     Author: Ralph Droms
             rdroms@gmail.com

     Author: Dan Romascanu
             dromasca@gmail.com
    ";
  description
    "This YANG module defines a component that augments the
     IETF description of an access list to allow DNS names
     as matching criteria.

     Copyright (c) 2019 IETF Trust and the persons identified as
     authors of the code.  All rights reserved.

     Redistribution and use in source and binary forms, with or
     without modification, is permitted pursuant to, and subject
     to the license terms contained in, the Simplified BSD License
     set forth in Section 4.c of the IETF Trust's Legal Provisions
     Relating to IETF Documents
     (http://trustee.ietf.org/license-info).";

  revision 2019-01-28 {
    description
      "Base version of dnsname extension of the ACL model.";
```

```
      reference
        "RFC 8520: Manufacturer Usage Description
         Specification";
    }

    grouping dns-matches {
      description
        "Domain names for matching.";
      leaf src-dnsname {
        type inet:host;
        description
          "domain name to be matched against.";
      }
      leaf dst-dnsname {
        type inet:host;
        description
          "domain name to be matched against.";
      }
    }

    augment "/acl:acls/acl:acl/acl:aces/acl:ace/acl:matches"
          + "/acl:l3/acl:ipv4/acl:ipv4" {
      description
        "Adding domain names to matching.";
      uses dns-matches;
    }
    augment "/acl:acls/acl:acl/acl:aces/acl:ace/acl:matches"
          + "/acl:l3/acl:ipv6/acl:ipv6" {
      description
        "Adding domain names to matching.";
      uses dns-matches;
    }
  }
  <CODE ENDS>
```

9. MUD File Example

   This example contains two access lists that are intended to provide
   outbound access to a cloud service on TCP port 443.

```
   {
     "ietf-mud:mud": {
       "mud-version": 1,
       "mud-url": "https://lighting.example.com/lightbulb2000",
       "last-update": "2019-01-28T11:20:51+01:00",
       "cache-validity": 48,
       "is-supported": true,
       "systeminfo": "The BMS Example Light Bulb",
       "from-device-policy": {
         "access-lists": {
           "access-list": [
             {
               "name": "mud-76100-v6fr"
             }
           ]
         }
       },
       "to-device-policy": {
         "access-lists": {
           "access-list": [
             {
               "name": "mud-76100-v6to"
             }
           ]
         }
       }
     },
     "ietf-access-control-list:acls": {
       "acl": [
         {
           "name": "mud-76100-v6to",
           "type": "ipv6-acl-type",
           "aces": {
             "ace": [
               {
                 "name": "cl0-todev",
                 "matches": {
                   "ipv6": {
                     "ietf-acldns:src-dnsname": "test.example.com",
                     "protocol": 6
                   },
                   "tcp": {
                     "ietf-mud:direction-initiated": "from-device",
```

```
                  "source-port": {
                    "operator": "eq",
                    "port": 443
                  }
                }
              },
              "actions": {
                "forwarding": "accept"
              }
            }
          ]
        }
      },
      {
        "name": "mud-76100-v6fr",
        "type": "ipv6-acl-type",
        "aces": {
          "ace": [
            {
              "name": "cl0-frdev",
              "matches": {
                "ipv6": {
                  "ietf-acldns:dst-dnsname": "test.example.com",
                  "protocol": 6
                },
                "tcp": {
                  "ietf-mud:direction-initiated": "from-device",
                  "destination-port": {
                    "operator": "eq",
                    "port": 443
                  }
                }
              },
              "actions": {
                "forwarding": "accept"
              }
            }
          ]
        }
      }
    ]
  }
}
```

   In this example, two policies are declared: one from the Thing and
   the other to the Thing. Each policy names an access list that
   applies to the Thing and one that applies from the Thing. Within
   each access list, access is permitted to packets flowing to or from

the Thing that can be mapped to the domain name of
"service.bms.example.com". For each access list, the enforcement
point should expect that the Thing initiated the connection.

10. The MUD URL DHCP Option

The IPv4 MUD URL client option has the following format:

```
   +------+-----+-----------------------------
   | code | len |  MUDstring
   +------+-----+-----------------------------
```

Code OPTION_MUD_URL_V4 (161) has been assigned by IANA. len is a
single octet that indicates the length of the MUD string in octets.
The MUDstring is defined as follows:

```
 MUDstring = mudurl [ " " reserved ]
 mudurl = URI; a URL [RFC3986] that uses the "https" scheme [RFC7230]
 reserved = 1*( OCTET ) ; from [RFC5234]
```

The entire option MUST NOT exceed 255 octets. If a space follows the
MUD URL, a reserved string that will be defined in future
specifications follows. MUD managers that do not understand this
field MUST ignore it.

The IPv6 MUD URL client option has the following format:

```
    0                   1                   2                   3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
   +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
   |          OPTION_MUD_URL_V6     |        option-length          |
   +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
   |                          MUDstring                            |
   |                                                               |
   +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
```

OPTION_MUD_URL_V6 (112).

option-length contains the length of the MUDstring, as defined above,
in octets.

The intent of this option is to provide both a new Thing classifier
to the network as well as some recommended configuration to the
routers that implement the policy. However, it is entirely the
purview of the network system as managed by the network administrator
to decide what to do with this information. The key function of this

   option is simply to identify the type of Thing to the network in a
   structured way such that the policy can be easily found with existing
   toolsets.

10.1. Client Behavior

   A DHCPv4 client MAY emit a DHCPv4 option, and a DHCPv6 client MAY
   emit a DHCPv6 option. These options are singletons, as specified in
   [RFC7227]. Because clients are intended to have at most one MUD URL
   associated with them, they may emit at most one MUD URL option via
   DHCPv4 and one MUD URL option via DHCPv6. In the case where both v4
   and v6 DHCP options are emitted, the same URL MUST be used.

10.2. Server Behavior

   A DHCP server may ignore these options or take action based on
   receipt of these options. When a server consumes this option, it
   will either forward the URL and relevant client information (such as
   the gateway address or giaddr and requested IP address, and lease
   length) to a network management system or retrieve the usage
   description itself by resolving the URL.

   DHCP servers may implement MUD functionality themselves or they may
   pass along appropriate information to a network management system or
   MUD manager. A DHCP server that does process the MUD URL MUST adhere
   to the process specified in [RFC2818] and [RFC5280] to validate the
   TLS certificate of the web server hosting the MUD file. Those
   servers will retrieve the file, process it, and create and install
   the necessary configuration on the relevant network element. Servers
   SHOULD monitor the gateway for state changes on a given interface. A
   DHCP server that does not provide MUD functionality and has forwarded
   a MUD URL to a MUD manager MUST notify the MUD manager of any
   corresponding change to the DHCP state of the client (such as
   expiration or explicit release of a network address lease).

   Should the DHCP server fail, in the case when it implements the MUD
   manager functionality, any backup mechanisms SHOULD include the MUD
   state, and the server SHOULD resolve the status of clients upon its
   restart, similar to what it would do absent MUD manager
   functionality. In the case where the DHCP server forwards
   information to the MUD manager, the MUD manager will either make use
   of redundant DHCP servers for information or clear state based on
   other network information, such as monitoring port status on a switch
   via SNMP, Radius accounting, or similar mechanisms.

10.3. Relay Requirements

   There are no additional requirements for relays.

11. The Manufacturer Usage Description (MUD) URL X.509 Extension

   This section defines an X.509 non-critical certificate extension that
   contains a single URL that points to an online Manufacturer Usage
   Description concerning the certificate subject. The URI must be
   represented as described in Section 7.4 of [RFC5280].

   Any Internationalized Resource Identifiers (IRIs) MUST be mapped to
   URIs as specified in Section 3.1 of [RFC3987] before they are placed
   in the certificate extension.

   The semantics of the URL are defined Section 6 of this document.

   The choice of id-pe is based on guidance found in Section 4.2.2 of
   [RFC5280]:

        These extensions may be used to direct applications to on-line
        information about the issuer or the subject.

   The MUD URL is precisely that: online information about the
   particular subject.

   In addition, a separate new extension is defined as id-pe-mudsigner.
   This contains the subject field of the signing certificate of the MUD
   file. Processing of this field is specified in Section 13.2.

   The purpose of this signature is to make a claim that the MUD file
   found on the server is valid for a given device, independent of any
   other factors. There are several security considerations below in
   Section 16.

   A new content-type id-ct-mud is also defined. While signatures are
   detached today, should a MUD file be transmitted as part of a
   Cryptographic Message Syntax (CMS) message, this content-type SHOULD
   be used.

   This module imports from [RFC5912] and [RFC6268]. The new extension
   is identified as follows:

   <CODE BEGINS>
```
    MUDURLExtnModule-2016 { iso(1) identified-organization(3) dod(6)
                internet(1) security(5) mechanisms(5) pkix(7)
                id-mod(0) id-mod-mudURLExtn2016(88) }
     DEFINITIONS IMPLICIT TAGS ::= BEGIN

     -- EXPORTS ALL --

    IMPORTS

      -- RFC 5912
      EXTENSION
      FROM PKIX-CommonTypes-2009
          { iso(1) identified-organization(3) dod(6) internet(1)
            security(5) mechanisms(5) pkix(7) id-mod(0)
            id-mod-pkixCommon-02(57) }

      -- RFC 5912
      id-ct
      FROM PKIXCRMF-2009
          { iso(1) identified-organization(3) dod(6) internet(1)
            security(5)  mechanisms(5) pkix(7) id-mod(0)
            id-mod-crmf2005-02(55) }

      -- RFC 6268
      CONTENT-TYPE
      FROM CryptographicMessageSyntax-2010
        { iso(1) member-body(2) us(840) rsadsi(113549)
          pkcs(1) pkcs-9(9) smime(16) modules(0) id-mod-cms-2009(58) }

      -- RFC 5912
      id-pe, Name
      FROM PKIX1Explicit-2009
          { iso(1) identified-organization(3) dod(6) internet(1)
            security(5) mechanisms(5) pkix(7) id-mod(0)
            id-mod-pkix1-explicit-02(51) } ;

    --
    -- Certificate Extensions
    --

    MUDCertExtensions EXTENSION ::=
       { ext-MUDURL | ext-MUDsigner, ... }

    ext-MUDURL EXTENSION ::=
```

```
      { SYNTAX MUDURLSyntax IDENTIFIED BY id-pe-mud-url }

   id-pe-mud-url OBJECT IDENTIFIER ::= { id-pe 25 }

   MUDURLSyntax ::= IA5String

   ext-MUDsigner EXTENSION ::=
      { SYNTAX MUDsignerSyntax IDENTIFIED BY id-pe-mudsigner }

   id-pe-mudsigner OBJECT IDENTIFIER ::= { id-pe 30 }

   MUDsignerSyntax ::= Name

   --
   -- CMS Content Types
   --

   MUDContentTypes CONTENT-TYPE ::=
      { ct-mud, ... }

    ct-mud CONTENT-TYPE ::=
       { -- directly include the content
         IDENTIFIED BY id-ct-mudtype }
       -- The binary data that is in the form
       -- "application/mud+json" is directly encoded as the
       -- signed data.  No additional ASN.1 encoding is added.

   id-ct-mudtype OBJECT IDENTIFIER ::= { id-ct 41 }

   END
<CODE ENDS>
```

   While this extension can appear in either an 802.AR manufacturer
   certificate (IDevID) or a deployment certificate (LDevID), of course
   it is not guaranteed in either, nor is it guaranteed to be carried
   over. It is RECOMMENDED that MUD manager implementations maintain a
   table that maps a Thing to its MUD URL based on IDevIDs.

12. The Manufacturer Usage Description LLDP Extension

   The IEEE802.1AB Link Layer Discovery Protocol (LLDP) is a one-hop,
   vendor-neutral link-layer protocol used by end host network Things
   for advertising their identity, capabilities, and neighbors on an
   IEEE 802 local area network. Its Type-Length-Value (TLV) design
   allows for "vendor-specific" extensions to be defined. IANA has a
   registered IEEE 802 organizationally unique identifier (OUI) defined
   as documented in [RFC7042]. The MUD LLDP extension uses a subtype
   defined in this document to carry the MUD URL.

The LLDP vendor-specific frame has the following format:

```
+--------+--------+----------+---------+--------------
|TLV Type|  len   |   OUI    |subtype  | MUDString
|  =127  |        |= 00 00 5E|  = 1    |
|(7 bits)|(9 bits)|(3 octets)|(1 octet)|(1-255 octets)
+--------+--------+----------+---------+--------------
```

where:

o TLV Type = 127 indicates a vendor-specific TLV

o len = indicates the TLV string length

o OUI = 00 00 5E is the organizationally unique identifier of IANA

o subtype = 1 (as assigned by IANA for the MUDstring)

o MUDstring = the length MUST NOT exceed 255 octets

The intent of this extension is to provide both a new Thing
classifier to the network as well as some recommended configuration
to the routers that implement the policy. However, it is entirely
the purview of the network system as managed by the network
administrator to decide what to do with this information. The key
function of this extension is simply to identify the type of Thing to
the network in a structured way such that the policy can be easily
found with existing toolsets.

Hosts, routers, or other network elements that implement this option
are intended to have at most one MUD URL associated with them, so
they may transmit at most one MUD URL value.

Hosts, routers, or other network elements that implement this option
may ignore these options or take action based on receipt of these
options. For example, they may fill in information in the respective
extensions of the LLDP Management Information Base (MIB). LLDP
operates in a one-way direction. Link Layer Discovery Protocol Data
Units (LLDPDUs) are not exchanged as information requests by one
Thing and responses sent by another Thing. The other Things do not
acknowledge LLDP information received from a Thing. No specific
network behavior is guaranteed. When a Thing consumes this
extension, it may either forward the URL and relevant remote Thing
information to a MUD manager or retrieve the usage description by
resolving the URL in accordance with normal HTTP semantics.

13. The Creating and Processing of Signed MUD Files

   Because MUD files contain information that may be used to configure
   network access lists, they are sensitive. To ensure that they have
   not been tampered with, it is important that they be signed. We make
   use of DER-encoded Cryptographic Message Syntax (CMS) [RFC5652] for
   this purpose.

13.1. Creating a MUD File Signature

   A MUD file MUST be signed using CMS as an opaque binary object. In
   order to make successful verification more likely, intermediate
   certificates SHOULD be included. The signature is stored at the
   location specified in the MUD file. Signatures are transferred using
   content-type "application/pkcs7-signature".

   For example:

   % openssl cms -sign -signer mancertfile -inkey mankey \
              -in mudfile -binary -outform DER -binary \
              -certfile intermediatecert -out mudfile.p7s

   Note: A MUD file may need to be re-signed if the signature expires.

13.2. Verifying a MUD File Signature

   Prior to processing the rest of a MUD file, the MUD manager MUST
   retrieve the MUD signature file by retrieving the value of "mud-
   signature" and validating the signature across the MUD file. The Key
   Usage Extension in the signing certificate MUST be present and have
   the bit digitalSignature(0) set. When the id-pe-mudsigner extension
   is present in a device's X.509 certificate, the MUD signature file
   MUST have been generated by a certificate whose subject matches the
   contents of that id-pe-mudsigner extension. If these conditions are
   not met, or if it cannot validate the chain of trust to a known trust
   anchor, the MUD manager MUST cease processing the MUD file until an
   administrator has given approval.

   The purpose of the signature on the file is to assign accountability
   to an entity, whose reputation can be used to guide administrators on
   whether or not to accept a given MUD file. It is already common
   place to check web reputation on the location of a server on which a
   file resides. While it is likely that the manufacturer will be the
   signer of the file, this is not strictly necessary, and it may not be
   desirable. For one thing, in some environments, integrators may
   install their own certificates. For another, what is more important
   is the accountability of the recommendation, and not just the
   relationship between the Thing and the file.

An example:

    % openssl cms -verify -in mudfile.p7s -inform DER -content mudfile

Note the additional step of verifying the common trust root.

14. Extensibility

One of our design goals is to see that MUD files are able to be
understood by as broad a cross-section of systems as is possible.
Coupled with the fact that we have also chosen to leverage existing
mechanisms, we are left with no ability to negotiate extensions and a
limited desire for those extensions in any event. As such, a two-
tier extensibility framework is employed, as follows:

1. At a coarse grain, a protocol version is included in a MUD URL.
    This memo specifies MUD version 1. Any and all changes are
    entertained when this version is bumped. Transition approaches
    between versions would be a matter for discussion in future
    versions.

2. At a finer grain, only extensions that would not incur additional
    risk to the Thing are permitted. Specifically, adding nodes to
    the mud container is permitted with the understanding that such
    additions will be ignored by unaware implementations. Any such
    extensions SHALL be standardized through the IETF process and
    MUST be named in the "extensions" list. MUD managers MUST ignore
    YANG nodes they do not understand and SHOULD create an exception
    to be resolved by an administrator, so as to avoid any policy
    inconsistencies.

15. Deployment Considerations

Because MUD consists of a number of architectural building blocks, it
is possible to assemble different deployment scenarios. One key
aspect is where to place policy enforcement. In order to protect the
Thing from other Things within a local deployment, policy can be
enforced on the nearest switch or access point. In order to limit
unwanted traffic within a network, it may also be advisable to
enforce policy as close to the Internet as possible. In some
circumstances, policy enforcement may not be available at the closest
hop. At that point, the risk of lateral infection (infection of
devices that reside near one another) is increased to the number of
Things that are able to communicate without protection.

A caution about some of the classes: admission of a Thing into the
"manufacturer" and "same-manufacturer" class may have impact on the
access of other Things. Put another way, the admission may grow the

   access list on switches connected to other Things, depending on how
   access is managed. Some care should be given on managing that access
   list growth. Alternative methods such as additional network
   segmentation can be used to keep that growth within reason.

   Because as of this writing MUD is a new concept, one can expect a
   great many devices to not have implemented it. It remains a local
   deployment decision as to whether a device that is first connected
   should be allowed broad or limited access. Furthermore, as mentioned
   in the introduction, a deployment may choose to ignore a MUD policy
   in its entirety and simply take into account the MUD URL as a
   classifier to be used as part of a local policy decision.

   Finally, please see directly below information regarding device
   lifetimes and use of domain names.

16. Security Considerations

   Based on how a MUD URL is emitted, a Thing may be able to lie about
   what it is, thus gaining additional network access. This can happen
   in a number of ways when a device emits a MUD URL using DHCP or LLDP,
   such as being inappropriately admitted to a class such as
   "same-manufacturer", being given access to a device such as
   "my-controller", or being permitted access to an Internet resource,
   where such access would otherwise be disallowed. Whether that is the
   case will depend on the deployment. Implementations SHOULD be
   configurable to disallow additive access for devices using MUD URLs
   that are not emitted in a secure fashion such as in a certificate.
   Similarly, implementations SHOULD NOT grant elevated permissions
   (beyond those of devices presenting no MUD policy) to devices that do
   not strongly bind their identity to their L2/L3 transmissions. When
   insecure methods are used by the MUD manager, the classes SHOULD NOT
   contain devices that use both insecure and secure methods, in order
   to prevent privilege escalation attacks, and MUST NOT contain devices
   with the same MUD URL that are derived from both strong and weak
   authentication methods.

   Devices may forge source (L2/L3) information. Deployments should
   apply appropriate protections to bind communications to the
   authentication that has taken place. For 802.1X authentication, IEEE
   802.1AE (MACsec) [IEEE8021AE] is one means by which this may happen.
   A similar approach can be used with 802.11i (Wi-Fi Protected Access 2
   (WPA2)) [IEEE80211i]. Other means are available with other lower-
   layer technologies. Implementations using session-oriented access
   that is not cryptographically bound should take care to remove state
   when any form of break in the session is detected.

A rogue certification authority (CA) may sign a certificate that
contains the same subject name as is listed in the MUDsigner field in
the manufacturer certificate, thus seemingly permitting a substitute
MUD file for a device. There are two mitigations available: First,
if the signer changes, this may be flagged as an exception by the MUD
manager. Second, if the MUD file also changes, the MUD manager
SHOULD seek administrator approval (it should do this in any case).
In all circumstances, the MUD manager MUST maintain a cache of
trusted CAs for this purpose. When such a rogue is discovered, it
SHOULD be removed.

Additional mitigations are described below.

When certificates are not present, Things claiming to be of a certain
manufacturer SHOULD NOT be included in that manufacturer grouping
without additional validation of some form. This will be relevant
when the MUD manager makes use of primitives such as "manufacturer"
for the purpose of accessing Things of a particular type. Similarly,
network management systems may be able to fingerprint the Thing. In
such cases, the MUD URL can act as a classifier that can be proven or
disproven. Fingerprinting may have other advantages as well: when
802.1AR certificates are used, because they themselves cannot change,
fingerprinting offers the opportunity to add artifacts to the MUD
string in the form of the reserved field discussed in Section 10.
The meaning of such artifacts is left as future work.

MUD managers SHOULD NOT accept a usage description for a Thing with
the same Media Access Control (MAC) address that has indicated a
change of the URL authority without some additional validation (such
as review by a network administrator). New Things that present some
form of unauthenticated MUD URL SHOULD be validated by some external
means when they would be given increased network access.

It may be possible for a rogue manufacturer to inappropriately
exercise the MUD file parser, in order to exploit a vulnerability.
There are two recommended approaches to address this threat. The
first is to validate that the signer of the MUD file is known to and
trusted by the MUD manager. The second is to have a system do a
primary scan of the file to ensure that it is both parseable and
believable at some level. MUD files will likely be relatively small,
to start with. The number of ACEs used by any given Thing should be
relatively small as well. It may also be useful to limit retrieval
of MUD URLs to only those sites that are known to have decent web or
domain reputations.

Use of a URL necessitates the use of domain names. If a domain name
changes ownership, the new owner of that domain may be able to
provide MUD files that MUD managers would consider valid. MUD

managers SHOULD cache certificates used by the MUD file server. When
a new certificate is retrieved for whatever reason, the MUD manager
should check to see if ownership of the domain has changed. A fair
programmatic approximation of this is when the name servers for the
domain have changed. If the actual MUD file has changed, the MUD
manager MAY check the WHOIS database to see if registration ownership
of a domain has changed. If a change has occurred, or if for some
reason it is not possible to determine whether ownership has changed,
further review may be warranted. Note, this remediation does not
take into account the case of a Thing that was produced long ago and
only recently fielded, or the case where a new MUD manager has been
installed.

The release of a MUD URL by a Thing reveals what the Thing is and
provides an attacker with guidance on what vulnerabilities may be
present.

While the MUD URL itself is not intended to be unique to a specific
Thing, the release of the URL may aid an observer in identifying
individuals when combined with other information. This is a privacy
consideration.

In addressing both of these concerns, implementors should take into
account what other information they are advertising through
mechanisms such as Multicast DNS (mDNS) [RFC6872]; how a Thing might
otherwise be identified, perhaps through how it behaves when it is
connected to the network; and whether a Thing is intended to be used
by individuals or carry personal identifying information, and then
apply appropriate data minimization techniques. One approach is to
make use of TEAP [RFC7170] as the means to share information with
authorized components in the network. Network elements may also
assist in limiting access to the MUD URL through the use of
mechanisms such as DHCPv6-Shield [RFC7610].

There is the risk of the MUD manager itself being spied on to
determine what things are connected to the network. To address this
risk, MUD managers may choose to make use of TLS proxies that they
trust that would aggregate other information.

Please note that the security considerations mentioned in Section 3.7
of [RFC8407] are not applicable in this case because the YANG
serialization is not intended to be accessed via NETCONF. However,
for those who try to instantiate this model in a network element via
the Network Configuration Protocol (NETCONF), all objects in each
model in this document exhibit similar security characteristics as
[RFC8519]. The basic purpose of MUD is to configure access, so by
its very nature, it can be disruptive if used by unauthorized
parties.

17. IANA Considerations

17.1. YANG Module Registrations

   The following YANG modules have been registered in the "YANG Module
   Names" registry:

      Name: ietf-mud
      URN: urn:ietf:params:xml:ns:yang:ietf-mud
      Prefix: ietf-mud
      Registrant contact: The IESG
      Reference: RFC 8520

      Name: ietf-acldns
      URI: urn:ietf:params:xml:ns:yang:ietf-acldns
      Prefix: ietf-acldns
      Registrant contact: The IESG
      Reference: RFC 8520

17.2. URI Registrations

   IANA has added the following entries to the "IETF XML registry":

   URI: urn:ietf:params:xml:ns:yang:ietf-acldns
   Registrant Contact: The IESG.
   XML: N/A. The requested URI is an XML namespace.

   URI: urn:ietf:params:xml:ns:yang:ietf-mud
   Registrant Contact: The IESG.
   XML: N/A. The requested URI is an XML namespace.

17.3. DHCPv4 and DHCPv6 Options

   The IANA has allocated OPTION_MUD_URL_V4 (161) in the "Dynamic Host
   Configuration Protocol (DHCP) and Bootstrap Protocol (BOOTP)
   Parameters" registry, and OPTION_MUD_URL_V6 (112) in the "Dynamic
   Host Configuration Protocol for IPv6 (DHCPv6)" registry, as described
   in Section 10.

17.4. PKIX Extensions

   IANA has made the following assignments for:

   o The MUDURLExtnModule-2016 ASN.1 module (88) in the "SMI Security
      for PKIX Module Identifier" registry (1.3.6.1.5.5.7.0).

   o id-pe-mud-url object identifier (25) from the "SMI Security for
      PKIX Certificate Extension" registry (1.3.6.1.5.5.7.1).

   o id-pe-mudsigner object identifier (30) from the "SMI Security for
      PKIX Certificate Extension" registry.

   o id-ct-mudtype object identifier (41) from the "SMI Security for
      S/MIME CMS Content Type" registry.

   o The use of these values is specified in Section 11.

17.5. Media Type Registration for MUD Files

   The following media type is defined for the transfer of MUD files:

   o Type name: application

   o Subtype name: mud+json

   o Required parameters: N/A

   o Optional parameters: N/A

   o Encoding considerations: 8bit; "application/mud+json" values are
      represented as JSON objects; UTF-8 encoding MUST be employed
      [RFC3629].

   o Security considerations: See Security Considerations of RFC 8520
      and Section 12 of [RFC8259].

   o Interoperability considerations: N/A

   o Published specification: RFC 8520

   o Applications that use this media type: MUD managers as specified
      by RFC 8520.

   o Fragment identifier considerations: N/A

   o Additional information:
      Magic number(s): N/A
      File extension(s): N/A
      Macintosh file type code(s): N/A

   o Person & email address to contact for further information:
      Eliot Lear <lear@cisco.com>, Ralph Droms <rdroms@gmail.com>,
      Dan Romascanu <dromasca@gmail.com>

   o Intended usage: COMMON

   o Restrictions on usage: none

   o Author:
      Eliot Lear <lear@cisco.com>
      Ralph Droms <rdroms@gmail.com>
      Dan Romascanu <dromasca@gmail.com>

   o Change controller: IESG

   o Provisional registration? (standards tree only): No.

17.6. IANA LLDP TLV Subtype Registry

   IANA has created a new registry titled "IANA Link Layer Discovery
   Protocol (LLDP) TLV Subtypes" under "IEEE 802 Numbers". The policy
   for this registry is Expert Review [RFC8126]. The maximum number of
   entries in the registry is 256.

   IANA has populated the initial registry as follows:

   LLDP subtype value: 1 (All the other 255 values are initially marked
   as "Unassigned".)

   Description: the Manufacturer Usage Description (MUD) Uniform
   Resource Locator (URL)

   Reference: RFC 8520

17.7. The MUD Well-Known Universal Resource Name (URNs)

   The following parameter registry has been added in accordance with
   [RFC3553].

      Registry name: MUD Well-Known Universal Resource Name (URN)
      Specification: RFC 8520
      Repository: https://www.iana.org/assignments/mud
      Index value: Encoded identically to a TCP/UDP port service
                    name, as specified in Section 5.1 of [RFC6335]

   The following entries have been added to the "MUD Well-Known
   Universal Resource Name (URN)" registry:

   "urn:ietf:params:mud:dns" refers to the service specified by
   [RFC1123]. "urn:ietf:params:mud:ntp" refers to the service specified
   by [RFC5905].

17.8. Extensions Registry

   The IANA has established a registry of extensions as follows:

      Registry name: MUD Extensions
      Registry policy: Standards Action
      Reference: RFC 8520
      Extension name: UTF-8-encoded string, not to exceed 40 characters.

   Each extension MUST follow the rules specified in this specification.
   As is usual, the IANA issues early allocations in accordance with
   [RFC7120].

18. References

18.1. Normative References

   [IEEE8021AB]
               IEEE, "IEEE Standard for Local and Metropolitan Area
               Networks-- Station and Media Access Control Connectivity
               Discovery", IEEE 802.1AB.

   [RFC1123]   Braden, R., Ed., "Requirements for Internet Hosts -
               Application and Support", STD 3, RFC 1123,
               DOI 10.17487/RFC1123, October 1989,
               <https://www.rfc-editor.org/info/rfc1123>.

   [RFC2119]   Bradner, S., "Key words for use in RFCs to Indicate
               Requirement Levels", BCP 14, RFC 2119,
               DOI 10.17487/RFC2119, March 1997,
               <https://www.rfc-editor.org/info/rfc2119>.

   [RFC2131]   Droms, R., "Dynamic Host Configuration Protocol",
               RFC 2131, DOI 10.17487/RFC2131, March 1997,
               <https://www.rfc-editor.org/info/rfc2131>.

   [RFC2818]   Rescorla, E., "HTTP Over TLS", RFC 2818,
               DOI 10.17487/RFC2818, May 2000,
               <https://www.rfc-editor.org/info/rfc2818>.

   [RFC3629]   Yergeau, F., "UTF-8, a transformation format of ISO
               10646", STD 63, RFC 3629, DOI 10.17487/RFC3629, November
               2003, <https://www.rfc-editor.org/info/rfc3629>.

   [RFC3748]   Aboba, B., Blunk, L., Vollbrecht, J., Carlson, J., and H.
               Levkowetz, Ed., "Extensible Authentication Protocol
               (EAP)", RFC 3748, DOI 10.17487/RFC3748, June 2004,
               <https://www.rfc-editor.org/info/rfc3748>.

   [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform
              Resource Identifier (URI): Generic Syntax", STD 66,
              RFC 3986, DOI 10.17487/RFC3986, January 2005,
              <https://www.rfc-editor.org/info/rfc3986>.

   [RFC3987] Duerst, M. and M. Suignard, "Internationalized Resource
              Identifiers (IRIs)", RFC 3987, DOI 10.17487/RFC3987,
              January 2005, <https://www.rfc-editor.org/info/rfc3987>.

   [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax
              Specifications: ABNF", STD 68, RFC 5234,
              DOI 10.17487/RFC5234, January 2008,
              <https://www.rfc-editor.org/info/rfc5234>.

   [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S.,
              Housley, R., and W. Polk, "Internet X.509 Public Key
              Infrastructure Certificate and Certificate Revocation List
              (CRL) Profile", RFC 5280, DOI 10.17487/RFC5280, May 2008,
              <https://www.rfc-editor.org/info/rfc5280>.

   [RFC5652] Housley, R., "Cryptographic Message Syntax (CMS)", STD 70,
              RFC 5652, DOI 10.17487/RFC5652, September 2009,
              <https://www.rfc-editor.org/info/rfc5652>.

   [RFC5905] Mills, D., Martin, J., Ed., Burbank, J., and W. Kasch,
              "Network Time Protocol Version 4: Protocol and Algorithms
              Specification", RFC 5905, DOI 10.17487/RFC5905, June 2010,
              <https://www.rfc-editor.org/info/rfc5905>.

   [RFC5912] Hoffman, P. and J. Schaad, "New ASN.1 Modules for the
              Public Key Infrastructure Using X.509 (PKIX)", RFC 5912,
              DOI 10.17487/RFC5912, June 2010,
              <https://www.rfc-editor.org/info/rfc5912>.

   [RFC6268] Schaad, J. and S. Turner, "Additional New ASN.1 Modules
              for the Cryptographic Message Syntax (CMS) and the Public
              Key Infrastructure Using X.509 (PKIX)", RFC 6268,
              DOI 10.17487/RFC6268, July 2011,
              <https://www.rfc-editor.org/info/rfc6268>.

   [RFC6335] Cotton, M., Eggert, L., Touch, J., Westerlund, M., and S.
              Cheshire, "Internet Assigned Numbers Authority (IANA)
              Procedures for the Management of the Service Name and
              Transport Protocol Port Number Registry", BCP 165,
              RFC 6335, DOI 10.17487/RFC6335, August 2011,
              <https://www.rfc-editor.org/info/rfc6335>.

   [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types",
              RFC 6991, DOI 10.17487/RFC6991, July 2013,
              <https://www.rfc-editor.org/info/rfc6991>.

   [RFC7120] Cotton, M., "Early IANA Allocation of Standards Track Code
              Points", BCP 100, RFC 7120, DOI 10.17487/RFC7120, January
              2014, <https://www.rfc-editor.org/info/rfc7120>.

   [RFC7227] Hankins, D., Mrugalski, T., Siodelski, M., Jiang, S., and
              S. Krishnan, "Guidelines for Creating New DHCPv6 Options",
              BCP 187, RFC 7227, DOI 10.17487/RFC7227, May 2014,
              <https://www.rfc-editor.org/info/rfc7227>.

   [RFC7230] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer
              Protocol (HTTP/1.1): Message Syntax and Routing",
              RFC 7230, DOI 10.17487/RFC7230, June 2014,
              <https://www.rfc-editor.org/info/rfc7230>.

   [RFC7231] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer
              Protocol (HTTP/1.1): Semantics and Content", RFC 7231,
              DOI 10.17487/RFC7231, June 2014,
              <https://www.rfc-editor.org/info/rfc7231>.

   [RFC7610] Gont, F., Liu, W., and G. Van de Velde, "DHCPv6-Shield:
              Protecting against Rogue DHCPv6 Servers", BCP 199,
              RFC 7610, DOI 10.17487/RFC7610, August 2015,
              <https://www.rfc-editor.org/info/rfc7610>.

   [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language",
              RFC 7950, DOI 10.17487/RFC7950, August 2016,
              <https://www.rfc-editor.org/info/rfc7950>.

   [RFC7951] Lhotka, L., "JSON Encoding of Data Modeled with YANG",
              RFC 7951, DOI 10.17487/RFC7951, August 2016,
              <https://www.rfc-editor.org/info/rfc7951>.

   [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC
              2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174,
              May 2017, <https://www.rfc-editor.org/info/rfc8174>.

   [RFC8259] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data
              Interchange Format", STD 90, RFC 8259,
              DOI 10.17487/RFC8259, December 2017,
              <https://www.rfc-editor.org/info/rfc8259>.

   [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams",
              BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018,
              <https://www.rfc-editor.org/info/rfc8340>.

   [RFC8348] Bierman, A., Bjorklund, M., Dong, J., and D. Romascanu, "A
              YANG Data Model for Hardware Management", RFC 8348,
              DOI 10.17487/RFC8348, March 2018,
              <https://www.rfc-editor.org/info/rfc8348>.

   [RFC8415] Mrugalski, T., Siodelski, M., Volz, B., Yourtchenko, A.,
              Richardson, M., Jiang, S., Lemon, T., and T. Winters,
              "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)",
              RFC 8415, DOI 10.17487/RFC8415, November 2018,
              <https://www.rfc-editor.org/info/rfc8415>.

   [RFC8519] Jethanandani, M., Agarwal, S., Huang, L., and D. Blair,
              "YANG Data Model for Network Access Control Lists (ACLs)",
              RFC 8519, DOI 10.17487/RFC8519, March 2019,
              <https://www.rfc-editor.org/info/rfc8519>.

18.2. Informative References

   [FW95]   Chapman, D. and E. Zwicky, "Building Internet Firewalls",
              First Edition, November 1995.

   [IEEE80211i]
              IEEE, "IEEE Standard for information technology-
              Telecommunications and information exchange between
              systems-Local and metropolitan area networks-Specific
              requirements-Part 11: Wireless LAN Medium Access Control
              (MAC) and Physical Layer (PHY) specifications: Amendment
              6: Medium Access Control (MAC) Security Enhancements",
              IEEE 802.11i.

   [IEEE8021AE]
              IEEE, "IEEE Standard for Local and metropolitan area
              networks-Media Access Control (MAC) Security",
              IEEE 802.1AE.

   [IEEE8021AR]
              IEEE, "IEEE Standard for Local and metropolitan area
              networks - Secure Device Identity", IEEE 802.1AR.

   [IEEE8021X]
              IEEE, "IEEE Standard for Local and metropolitan area
              networks--Port-Based Network Access Control", IEEE 802.1X.

   [RFC1984] IAB and IESG, "IAB and IESG Statement on Cryptographic
              Technology and the Internet", BCP 200, RFC 1984,
              DOI 10.17487/RFC1984, August 1996,
              <https://www.rfc-editor.org/info/rfc1984>.

   [RFC3553] Mealling, M., Masinter, L., Hardie, T., and G. Klyne, "An
              IETF URN Sub-namespace for Registered Protocol
              Parameters", BCP 73, RFC 3553, DOI 10.17487/RFC3553, June
              2003, <https://www.rfc-editor.org/info/rfc3553>.

   [RFC6092] Woodyatt, J., Ed., "Recommended Simple Security
              Capabilities in Customer Premises Equipment (CPE) for
              Providing Residential IPv6 Internet Service", RFC 6092,
              DOI 10.17487/RFC6092, January 2011,
              <https://www.rfc-editor.org/info/rfc6092>.

   [RFC6872] Gurbani, V., Ed., Burger, E., Ed., Anjali, T., Abdelnur,
              H., and O. Festor, "The Common Log Format (CLF) for the
              Session Initiation Protocol (SIP): Framework and
              Information Model", RFC 6872, DOI 10.17487/RFC6872,
              February 2013, <https://www.rfc-editor.org/info/rfc6872>.

   [RFC7042] Eastlake 3rd, D. and J. Abley, "IANA Considerations and
              IETF Protocol and Documentation Usage for IEEE 802
              Parameters", BCP 141, RFC 7042, DOI 10.17487/RFC7042,
              October 2013, <https://www.rfc-editor.org/info/rfc7042>.

   [RFC7170] Zhou, H., Cam-Winget, N., Salowey, J., and S. Hanna,
              "Tunnel Extensible Authentication Protocol (TEAP) Version
              1", RFC 7170, DOI 10.17487/RFC7170, May 2014,
              <https://www.rfc-editor.org/info/rfc7170>.

   [RFC7252] Shelby, Z., Hartke, K., and C. Bormann, "The Constrained
              Application Protocol (CoAP)", RFC 7252,
              DOI 10.17487/RFC7252, June 2014,
              <https://www.rfc-editor.org/info/rfc7252>.

   [RFC7452] Tschofenig, H., Arkko, J., Thaler, D., and D. McPherson,
              "Architectural Considerations in Smart Object Networking",
              RFC 7452, DOI 10.17487/RFC7452, March 2015,
              <https://www.rfc-editor.org/info/rfc7452>.

   [RFC7488] Boucadair, M., Penno, R., Wing, D., Patil, P., and T.
              Reddy, "Port Control Protocol (PCP) Server Selection",
              RFC 7488, DOI 10.17487/RFC7488, March 2015,
              <https://www.rfc-editor.org/info/rfc7488>.

   [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for
              Writing an IANA Considerations Section in RFCs", BCP 26,
              RFC 8126, DOI 10.17487/RFC8126, June 2017,
              <https://www.rfc-editor.org/info/rfc8126>.

   [RFC8343] Bjorklund, M., "A YANG Data Model for Interface
              Management", RFC 8343, DOI 10.17487/RFC8343, March 2018,
              <https://www.rfc-editor.org/info/rfc8343>.

   [RFC8407] Bierman, A., "Guidelines for Authors and Reviewers of
              Documents Containing YANG Data Models", BCP 216, RFC 8407,
              DOI 10.17487/RFC8407, October 2018,
              <https://www.rfc-editor.org/info/rfc8407>.

Appendix A. Default MUD Nodes

   What follows is the portion of a MUD file that permits DNS traffic to
   a controller that is registered with the URN
   "urn:ietf:params:mud:dns" and traffic NTP to a controller that is
   registered with "urn:ietf:params:mud:ntp". This is considered the
   default behavior, and the ACEs are in effect appended to whatever
   other "ace" entries that a MUD file contains. To block DNS or NTP,
   one repeats the matching statement but replaces the "forwarding"
   action "accept" with "drop". Because ACEs are processed in the order
   they are received, the defaults would not be reached. A MUD manager
   might further decide to optimize to simply not include the defaults
   when they are overridden.

   Four "acl" list entries that implement default MUD nodes are listed
   below. Two are for IPv4 and two are for IPv6 (one in each direction
   for both versions of IP). Note that neither the access list name nor
   the ace name need be retained or used in any way by local
   implementations; they are simply there for the sake of completeness.

```
     "ietf-access-control-list:acls": {
        "acl": [
          {
            "name": "mud-59776-v4to",
            "type": "ipv4-acl-type",
            "aces": {
              "ace": [
                {
                  "name": "ent0-todev",
                  "matches": {
                    "ietf-mud:mud": {
                      "controller": "urn:ietf:params:mud:dns"
                    },
                    "ipv4": {
                      "protocol": 17
                    },
                    "udp": {
                      "source-port": {
                        "operator": "eq",
                        "port": 53
                      }
                    }
                  },
                  "actions": {
                    "forwarding": "accept"
                  }
                },
                {
```

```
                "name": "ent1-todev",
                "matches": {
                  "ietf-mud:mud": {
                    "controller": "urn:ietf:params:mud:ntp"
                  },
                  "ipv4": {
                    "protocol": 17
                  },
                  "udp": {
                    "source-port": {
                      "operator": "eq",
                      "port": 123
                    }
                  }
                },
                "actions": {
                  "forwarding": "accept"
                }
              }
            ]
          }
        },
        {
          "name": "mud-59776-v4fr",
          "type": "ipv4-acl-type",
          "aces": {
            "ace": [
              {
                "name": "ent0-frdev",
                "matches": {
                  "ietf-mud:mud": {
                    "controller": "urn:ietf:params:mud:dns"
                  },
                  "ipv4": {
                    "protocol": 17
                  },
                  "udp": {
                    "destination-port": {
                      "operator": "eq",
                      "port": 53
                    }
                  }
                },
                "actions": {
                  "forwarding": "accept"
                }
              },
              {
```

```
                        "name": "ent1-frdev",
                        "matches": {
                          "ietf-mud:mud": {
                            "controller": "urn:ietf:params:mud:ntp"
                          },
                          "ipv4": {
                            "protocol": 17
                          },
                          "udp": {
                            "destination-port": {
                              "operator": "eq",
                              "port": 123
                            }
                          }
                        },
                        "actions": {
                          "forwarding": "accept"
                        }
                      }
                    ]
                  }
                },
                {
                  "name": "mud-59776-v6to",
                  "type": "ipv6-acl-type",
                  "aces": {
                    "ace": [
                      {
                        "name": "ent0-todev",
                        "matches": {
                          "ietf-mud:mud": {
                            "controller": "urn:ietf:params:mud:dns"
                          },
                          "ipv6": {
                            "protocol": 17
                          },
                          "udp": {
                            "source-port": {
                              "operator": "eq",
                              "port": 53
                            }
                          }
                        },
                        "actions": {
                          "forwarding": "accept"
                        }
                      },
                      {
```

```
                  "name": "ent1-todev",
                  "matches": {
                    "ietf-mud:mud": {
                      "controller": "urn:ietf:params:mud:ntp"
                    },
                    "ipv6": {
                      "protocol": 17
                    },
                    "udp": {
                      "source-port": {
                        "operator": "eq",
                        "port": 123
                      }
                    }
                  },
                  "actions": {
                    "forwarding": "accept"
                  }
                }
              ]
            }
          },
          {
            "name": "mud-59776-v6fr",
            "type": "ipv6-acl-type",
            "aces": {
              "ace": [
                {
                  "name": "ent0-frdev",
                  "matches": {
                    "ietf-mud:mud": {
                      "controller": "urn:ietf:params:mud:dns"
                    },
                    "ipv6": {
                      "protocol": 17
                    },
                    "udp": {
                      "destination-port": {
                        "operator": "eq",
                        "port": 53
                      }
                    }
                  },
                  "actions": {
                    "forwarding": "accept"
                  }
                },
                {
```

```
                "name": "ent1-frdev",
                "matches": {
                  "ietf-mud:mud": {
                    "controller": "urn:ietf:params:mud:ntp"
                  },
                  "ipv6": {
                    "protocol": 17
                  },
                  "udp": {
                    "destination-port": {
                      "operator": "eq",
                      "port": 123
                    }
                  }
                },
                "actions": {
                  "forwarding": "accept"
                }
              }
            ]
          }
        }
      ]
    }
```

Appendix B. A Sample Extension: DETNET-indicator

   In this sample extension, we augment the core MUD model to indicate
   whether the device implements DETNET. If a device claims not to use
   DETNET, but then later attempts to do so, a notification or exception
   might be generated. Note that this example is intended only for
   illustrative purposes.

 Extension Name: "Example-Extension" (to be used in the extensions list)
 Standard: RFC 8520 (but do not register the example)

   This extension augments the MUD model to include a single node, using
   the following sample module that has the following tree structure:

```
   module: ietf-mud-detext-example
     augment /ietf-mud:mud:
       +--rw is-detnet-required?   boolean
```

The model is defined as follows:

```
<CODE BEGINS>file "ietf-mud-detext-example@2019-01-28.yang"
module ietf-mud-detext-example {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-mud-detext-example";
  prefix ietf-mud-detext-example;

  import ietf-mud {
    prefix ietf-mud;
  }

  organization
    "IETF OPSAWG (Operations and Management Area Working Group)";
  contact
    "WG Web: <https://datatracker.ietf.org/wg/opsawg/>
     WG List: opsawg@ietf.org

     Author: Eliot Lear
             lear@cisco.com

     Author: Ralph Droms
             rdroms@gmail.com

     Author: Dan Romascanu
             dromasca@gmail.com
    ";
  description
    "Sample extension to a MUD module to indicate a need
     for DETNET support.";

  revision 2019-01-28 {
    description
      "Initial revision.";
    reference
      "RFC 8520: Manufacturer Usage Description
       Specification";
  }

  augment "/ietf-mud:mud" {
    description
      "This adds a simple extension for a manufacturer
       to indicate whether DETNET is required by a
       device.";
    leaf is-detnet-required {
      type boolean;
      description
        "This value will equal 'true' if a device requires
```

```
            DETNET to properly function.";
        }
      }
    }
    <CODE ENDS>

    Using the previous example, we now show how the extension would be
    expressed:

    {
      "ietf-mud:mud": {
        "mud-version": 1,
        "mud-url": "https://lighting.example.com/lightbulb2000",
        "last-update": "2019-01-28T11:20:51+01:00",
        "cache-validity": 48,
        "extensions": [
            "ietf-mud-detext-example"
         ],
        "ietf-mud-detext-example:is-detnet-required": "false",
        "is-supported": true,
        "systeminfo": "The BMS Example Light Bulb",
        "from-device-policy": {
          "access-lists": {
            "access-list": [
              {
                "name": "mud-76100-v6fr"
              }
            ]
          }
        },
        "to-device-policy": {
          "access-lists": {
            "access-list": [
              {
                "name": "mud-76100-v6to"
              }
            ]
          }
        }
      },
      "ietf-access-control-list:acls": {
        "acl": [
          {
            "name": "mud-76100-v6to",
            "type": "ipv6-acl-type",
            "aces": {
              "ace": [
                {
```

```
                "name": "cl0-todev",
                "matches": {
                  "ipv6": {
                    "ietf-acldns:src-dnsname": "test.example.com",
                    "protocol": 6
                  },
                  "tcp": {
                    "ietf-mud:direction-initiated": "from-device",
                    "source-port": {
                      "operator": "eq",
                      "port": 443
                    }
                  }
                },
                "actions": {
                  "forwarding": "accept"
                }
              }
            ]
          }
        },
        {
          "name": "mud-76100-v6fr",
          "type": "ipv6-acl-type",
          "aces": {
            "ace": [
              {
                "name": "cl0-frdev",
                "matches": {
                  "ipv6": {
                    "ietf-acldns:dst-dnsname": "test.example.com",
                    "protocol": 6
                  },
                  "tcp": {
                    "ietf-mud:direction-initiated": "from-device",
                    "destination-port": {
                      "operator": "eq",
                      "port": 443
                    }
                  }
                },
                "actions": {
                  "forwarding": "accept"
                }
              }
            ]
          }
        }
```

```
      ]
    }
  }
```

Acknowledgments

   The authors would like to thank Einar Nilsen-Nygaard, who
   singlehandedly updated the model to match the updated ACL model,
   Bernie Volz, Tom Gindin, Brian Weis, Sandeep Kumar, Thorsten Dahm,
   John Bashinski, Steve Rich, Jim Bieda, Dan Wing, Joe Clarke, Henk
   Birkholz, Adam Montville, Jim Schaad, and Robert Sparks for their
   valuable advice and reviews. Russ Housley entirely rewrote
   Section 11 to be a complete module. Adrian Farrel provided the basis
   for the privacy considerations text. Kent Watsen provided a thorough
   review of the architecture and the YANG model. The remaining errors
   in this work are entirely the responsibility of the authors.

Authors' Addresses

   Eliot Lear
   Cisco Systems
   Richtistrasse 7
   Wallisellen CH-8304
   Switzerland

   Phone: +41 44 878 9200
   Email: lear@cisco.com

   Ralph Droms
   Google
   355 Main St., 5th Floor
   Cambridge, MA 02142
   United States of America

   Phone: +1 978 376 3731
   Email: rdroms@gmail.com

   Dan Romascanu

   Phone: +972 54 5555347
   Email: dromasca@gmail.com