Computing The Least Solution

Consider the system

$$x = f(x, y, z)$$

$$y = g(x, y, z)$$

$$z = h(x, y, z)$$

Computing The Least Solution

Consider the system

$$x = f(x, y, z)$$

$$y = g(x, y, z)$$

$$z = h(x, y, z)$$

 Obvious strategy: Evaluate all equations at every step, until solution converges.

$$[\langle \bot, \bot, \bot \rangle, \langle f(\bot), g(\bot), h(\bot) \rangle, \langle f^2(\bot), g^2(\bot), h^2(\bot) \rangle, \dots,]$$

Computing The Least Solution

Consider the system

$$x = f(x, y, z)$$

$$y = g(x, y, z)$$

$$z = h(x, y, z)$$

 Obvious strategy: Evaluate all equations at every step, until solution converges.

$$[\langle \bot, \bot, \bot \rangle, \langle f(\bot), g(\bot), h(\bot) \rangle, \langle f^2(\bot), g^2(\bot), h^2(\bot) \rangle, \dots,]$$

- This strategy corresponds exactly to the Jacobi method in iterative solvers for linear systems.
- The general approach is called round-robin scheduling of equations.

Worklist-Based Algorithm

 Obvious point: it is not necessary to re-evaluate a function if its inputs have not changed.

Worklist-Based Algorithm

 Obvious point: it is not necessary to re-evaluate a function if its inputs have not changed.

- Worklist-based algorithm:
 - Initialize worklist with all equations.
 - Initialize solution vector v to the vector of all \perp s.
 - While the worklist is not empty:
 - Pick an equation from the worklist.
 - Evaluate RHS of this equation with the current value of the solution vector and update the entry corresponding to LHS variable in the solution vector 12
 - Add all equations that use this variable in their RHS to the worklist.

Worklist-Based Algorithm

- Obvious point: it is not necessary to re-evaluate a function if its inputs have not changed.
- Worklist-based algorithm:
 - Initialize worklist with all equations.
 - Initialize solution vector v to the vector of all \perp s.
 - While the worklist is not empty:
 - Pick an equation from the worklist.
 - Evaluate RHS of this equation with the current value of the solution vector and update the entry corresponding to LHS variable in the solution vector *v*.
 - Add all equations that use this variable in their RHS to the worklist.
- You can show that this algorithm will compute the least solution to the system of equations.