

Towards Inheritance Via Types

- Type inclusion (aka subtyping)
 - A type A is said to be **included in**, or **is a subtype of**, another type B when all the values of type A are also values of type B .
 - That is, when A and B are interpreted as sets of values, $A \subseteq B$.
 - Equivalently, the type B is said to be a **supertype** of type A .
 - We will write this relation as $A \sqsubseteq B$.

Towards Inheritance Via Types

- Type inclusion (aka subtyping)
 - A type A is said to be included in, or is a subtype of, another type B when all the values of type A are also values of type B .
 - That is, when A and B are interpreted as sets of values, $A \subseteq B$.
 - Equivalently, the type B is said to be a supertype of type A .
 - We will write this relation as $A \sqsubseteq B$.
- Examples of subtypes.
 - [Function types]
$$D \rightarrow R \sqsubseteq D' \rightarrow R' \equiv D' \sqsubseteq D \wedge R \sqsubseteq R'$$
or,
$$\frac{D' \sqsubseteq D \quad R \sqsubseteq R'}{D \rightarrow R \sqsubseteq D' \rightarrow R'}.$$
 - [Record types]
$$\mathbf{REC}(a_1:t_1, \dots, a_n:t_n, \dots, a_m:t_m) \sqsubseteq \mathbf{REC}(a_1:u_1, \dots, a_n:u_n) \equiv \forall i \in [1, n]. t_i \sqsubseteq u_i.$$

Towards Inheritance Via Types

- Type inclusion (aka subtyping)
 - A type A is said to be included in, or is a subtype of, another type B when all the values of type A are also values of type B .
 - That is, when A and B are interpreted as sets of values, $A \subseteq B$.
 - Equivalently, the type B is said to be a supertype of type A .
 - We will write this relation as $A \sqsubseteq B$.
- Examples of subtypes.
 - [Function types]
$$D \rightarrow R \sqsubseteq D' \rightarrow R' \equiv D' \sqsubseteq D \wedge R \sqsubseteq R'$$
or, $\frac{D' \sqsubseteq D \quad R \sqsubseteq R'}{D \rightarrow R \sqsubseteq D' \rightarrow R'}$.
 - [Record types]
$$\mathbf{REC}(a_1:t_1, \dots, a_n:t_n, \dots, a_m:t_m) \sqsubseteq \mathbf{REC}(a_1:u_1, \dots, a_n:u_n) \equiv \forall i \in [1, n]. t_i \sqsubseteq u_i.$$
- Subtyping on record types corresponds to the concept of inheritance (subclasses) in programming languages.

Name Spaces, Take 4: Classes + Inheritance

- By the typing judgment rule for records,
 $\text{Point3D} \sqsubseteq \text{Point2D}$.
 - Ignoring field ordering issue.

```
typedef struct _Point2D {  
    int x, y;  
    int get_x(struct _Point2D*);  
    int get_y(struct _Point2D*);  
    double dist(struct _Point2D*);  
} Point2D;
```

```
typedef struct _Point3D {  
    int x, y, z;  
    int get_x(struct _Point3D*);  
    int get_y(struct _Point3D*);  
    int get_z(struct _Point3D*);  
    double dist(struct _Point3D*);  
} Point3D;
```

Name Spaces, Take 4: Classes + Inheritance

- By the typing judgment rule for records,
 $\text{Point3D} \sqsubseteq \text{Point2D}$.
 - Ignoring field ordering issue.
- We indicate this in the source language with special syntactic sugar.

```
typedef struct _Point2D {  
    int x, y;  
    int get_x(struct _Point2D*);  
    int get_y(struct _Point2D*);  
    double dist(struct _Point2D*);  
} Point2D;
```

```
typedef struct _Point3D {  
    int x, y, z;  
    int get_x(struct _Point3D*);  
    int get_y(struct _Point3D*);  
    int get_z(struct _Point3D*);  
    double dist(struct _Point3D*);  
} Point3D;
```

```
class Point2D {  
    int x, y;  
    int get_x(void);  
    int get_y(void);  
    double dist(void);  
};  
  
class Point3D extends Point2D {  
    int z;  
    int get_z(void);  
    double dist(void); // overrides  
};
```

Name Spaces, Take 4: Classes + Inheritance

- By the typing judgment rule for records,
 $\text{Point3D} \sqsubseteq \text{Point2D}$.
 - Ignoring field order issue.
- We indicate this in the source language with special syntactic sugar.
 - The members common to `Point2D` and `Point3D` are inherited from the supertype.

```
typedef struct _Point2D {  
    int x, y;  
    int get_x(struct _Point2D*);  
    int get_y(struct _Point2D*);  
    double dist(struct _Point2D*);  
} Point2D;
```

```
typedef struct _Point3D {  
    int x, y, z;  
    int get_x(struct _Point3D*);  
    int get_y(struct _Point3D*);  
    int get_z(struct _Point3D*);  
    double dist(struct _Point3D*);  
} Point3D;
```

```
class Point2D {  
    int x, y;  
    int get_x(void);  
    int get_y(void);  
    double dist(void);  
};  
  
class Point3D extends Point2D {  
    int z;  
    int get_z(void);  
    double dist(void); // overrides  
};
```

Name Spaces, Take 4: Classes + Inheritance

- By the typing judgment rule for records,
 $\text{Point3D} \sqsubseteq \text{Point2D}$.
 - Ignoring field order issue.
- We indicate this in the source language with special syntactic sugar.
 - The members common to `Point2D` and `Point3D` are inherited from the supertype.
 - Additional (`z`, `get_z`) and overridden members (`dist`) are explicitly indicated in `Point3D`.

```
typedef struct _Point2D {
    int x, y;
    int get_x(struct _Point2D*);
    int get_y(struct _Point2D*);
    double dist(struct _Point2D*);
} Point2D;
```

```
typedef struct _Point3D {
    int x, y, z;
    int get_x(struct _Point3D*);
    int get_y(struct _Point3D*);
    int get_z(struct _Point3D*);
    double dist(struct _Point3D*);
} Point3D;
```

```
class Point2D {
    int x, y;
    int get_x(void);
    int get_y(void);
    double dist(void);
};

class Point3D extends Point2D {
    int z;
    int get_z(void);
    double dist(void); // overrides
};
```

Name Spaces, Take 4: Classes + Inheritance

- By the typing judgment rule for records,
 $\text{Point3D} \sqsubseteq \text{Point2D}$.
 - Ignoring field order issue.
- We indicate this in the source language with special syntactic sugar.
 - The members common to `Point2D` and `Point3D` are inherited from the supertype.
 - Additional (`z`, `get_z`) and overridden members (`dist`) are explicitly indicated in `Point3D`.
 - The type signatures of the instance methods now have an *implicit* object reference (`this` or `self`) as the first argument.

```
typedef struct _Point2D {  
    int x, y;  
    int get_x(struct _Point2D*);  
    int get_y(struct _Point2D*);  
    double dist(struct _Point2D*);  
} Point2D;
```

```
typedef struct _Point3D {  
    int x, y, z;  
    int get_x(struct _Point3D*);  
    int get_y(struct _Point3D*);  
    int get_z(struct _Point3D*);  
    double dist(struct _Point3D*);  
} Point3D;
```

```
class Point2D {  
    int x, y;  
    int get_x(void);  
    int get_y(void);  
    double dist(void);  
};  
  
class Point3D extends Point2D {  
    int z;  
    int get_z(void);  
    double dist(void); // overrides  
};
```


Run-Time Memory View

1. How are objects and classes laid out in memory?
2. How are names mapped to methods?
3. What are the rules for name visibility?

```
class Point2D {  
    int x, y;  
    int get_x(void);  
    int get_y(void);  
    double dist(void);  
};  
class Point3D extends Point2D {  
    int z;  
    int get_z(void);  
    double dist(void); // overrides  
};  
Point2D p1, p2; Point3D q = new();
```