

A Simple Language

- This is very much like LiveOak-0.

Program \rightarrow *Decls* ; *Expn*

Decls \rightarrow *Decls* ; *Decls* | **id** : *Type*

Type \rightarrow **char** | **int** | *Type* [**num**] | &*Type*

Expn \rightarrow **literal** | **num** | **id** |

Expn mod *Expn* | *Expn* [*Expn*] | **Expn*

- How do we type-check programs in this language?
 - What effect do declarations have on judgments?
 - What are the typing rules for expressions?
- Initial environment
 - $F = \{\text{mod: } \mathbf{int} \times \mathbf{int} \rightarrow \mathbf{int}\}$
 - $G = \emptyset$

Effect of Declarations

- Variable bindings will *extend* the context component G of the environment.
- If we encounter the declaration $x: T$ in an existing context G , the resulting context G' will be written as
$$G' = (G, x: T)$$

- Typing rule for declarations

$$\frac{}{F, G \vdash x: T} \quad x: T \in G$$

- The allowable forms of T will be determined by the *Type* sublanguage.

Type Inference for Expressions

$Exprn \rightarrow \text{literal} \mid \text{num} \mid \text{id} \mid Exprn \text{ mod } Exprn \mid Exprn [Exprn] \mid *Exprn$

Type Inference for Expressions

$Exprn \rightarrow \text{literal} \mid \text{num} \mid \text{id} \mid Exprn \text{ mod } Exprn \mid Exprn [Exprn] \mid *Exprn$

- $\frac{}{F, G \vdash \text{literal}:\text{char}} \qquad \frac{}{F, G \vdash \text{num}:\text{int}}$

Type Inference for Expressions

$Exprn \rightarrow \text{literal} \mid \text{num} \mid \text{id} \mid Exprn \text{ mod } Exprn \mid Exprn [Exprn] \mid *Exprn$

- $\frac{}{F, G \vdash \text{literal} : \text{char}} \qquad \frac{}{F, G \vdash \text{num} : \text{int}}$
- $\frac{}{F, G \vdash x : T} \quad x : T \in G$

Type Inference for Expressions

$Exprn \rightarrow \text{literal} \mid \text{num} \mid \text{id} \mid Exprn \text{ mod } Exprn \mid Exprn [Exprn] \mid *Exprn$

- $$\frac{}{F, G \vdash \text{literal} : \text{char}} \qquad \frac{}{F, G \vdash \text{num} : \text{int}}$$
- $$\frac{}{F, G \vdash x : T} \quad x : T \in G$$
- $$\frac{F, G \vdash e_1 : \text{int} \quad F, G \vdash e_2 : \text{int}}{F, G \vdash e_1 \text{ mod } e_2 : \text{int}}$$

Type Inference for Expressions

$Exprn \rightarrow \text{literal} \mid \text{num} \mid \text{id} \mid Exprn \text{ mod } Exprn \mid Exprn [Exprn] \mid *Exprn$

- $$\frac{}{F, G \vdash \text{literal} : \text{char}} \qquad \frac{}{F, G \vdash \text{num} : \text{int}}$$
- $$\frac{}{F, G \vdash x : T} \quad x : T \in G$$
- $$\frac{F, G \vdash e_1 : \text{int} \quad F, G \vdash e_2 : \text{int}}{F, G \vdash e_1 \text{ mod } e_2 : \text{int}}$$
- $$\frac{F, G \vdash e : \text{ARRAY}(N, T)}{F, G \vdash e[x] : T} \quad 0 \leq \text{val}(x) < N$$

Type Inference for Expressions

$Exprn \rightarrow \text{literal} \mid \text{num} \mid \text{id} \mid Exprn \text{ mod } Exprn \mid Exprn [Exprn] \mid *Exprn$

- $$\frac{}{F, G \vdash \text{literal} : \text{char}} \qquad \frac{}{F, G \vdash \text{num} : \text{int}}$$
- $$\frac{}{F, G \vdash x : T} \quad x : T \in G$$
- $$\frac{F, G \vdash e_1 : \text{int} \quad F, G \vdash e_2 : \text{int}}{F, G \vdash e_1 \text{ mod } e_2 : \text{int}}$$
- $$\frac{F, G \vdash e : \text{ARRAY}(N, T)}{F, G \vdash e[x] : T} \quad 0 \leq \text{val}(x) < N$$
- $$\frac{F, G \vdash e : \text{PTR}(T)}{F, G \vdash *e : T}$$

Ternary Choice Operator

Type → **char** | **int** | **bool** | *Type*[**num**] | &*Type*

Expn → **literal** | **num** | **id** | *Expn* mod *Expn* | *Expn*[*Expn*] | **Expn*
| *Expn* ? *Expn* : *Expn*

Ternary Choice Operator

Type \rightarrow **char** | **int** | **bool** | *Type*[**num**] | &*Type*

Expn \rightarrow **literal** | **num** | **id** | *Expn* mod *Expn* | *Expn*[*Expn*] | **Expn*
| *Expn* ? *Expn* : *Expn*

$$\bullet \frac{F, G \vdash e_1 : \mathbf{bool} \quad F, G \vdash e_2 : T \quad F, G \vdash e_3 : T'}{F, G \vdash e_1 ? e_2 : e_3 : T} T \equiv T'$$

Ternary Choice Operator

Type \rightarrow **char** | **int** | **bool** | *Type*[**num**] | &*Type*

Expn \rightarrow **literal** | **num** | **id** | *Expn* mod *Expn* | *Expn*[*Expn*] | **Expn*
| *Expn* ? *Expn* : *Expn*

$$\bullet \frac{F, G \vdash e_1 : \mathbf{bool} \quad F, G \vdash e_2 : T \quad F, G \vdash e_3 : T'}{F, G \vdash e_1 ? e_2 : e_3 : T} T \equiv T'$$

$$\bullet \frac{F, G \vdash e_1 : \mathbf{bool} \quad F, G \vdash e_2 : T \quad F, G \vdash e_3 : T'}{F, G \vdash e_1 ? e_2 : e_3 : \mathbf{error}} T \not\equiv T'$$

Adding and Checking Statements

Program \rightarrow *Decls* ; *Stmt*

Decls \rightarrow *Decls* ; *Decls* | **id** : *Type*

Type \rightarrow **char** | **int** | *Type* [**num**] | &*Type*

Expn \rightarrow **literal** | **num** | **id** | *Expn* mod *Expn* | *Expn* [*Expn*] | **Expn*

Stmt \rightarrow **id** = *Expn* | *Stmt* ; *Stmt* | **if** *Expn* **then** *Stmt* | **while** *Expn* **do** *Stmt*

Adding and Checking Statements

Program \rightarrow *Decls* ; *Stmt*

Decls \rightarrow *Decls* ; *Decls* | **id** : *Type*

Type \rightarrow **char** | **int** | *Type* [**num**] | &*Type*

Expn \rightarrow **literal** | **num** | **id** | *Expn* mod *Expn* | *Expn* [*Expn*] | **Expn*

Stmt \rightarrow **id** = *Expn* | *Stmt* ; *Stmt* | **if** *Expn* **then** *Stmt* | **while** *Expn* **do** *Stmt*

- $$\frac{F, G \vdash e : T'}{F, G \vdash x = e \text{ is valid}} \quad x : T \in G, T \equiv T'$$

Adding and Checking Statements

Program \rightarrow *Decls* ; *Stmt*

Decls \rightarrow *Decls* ; *Decls* | **id** : *Type*

Type \rightarrow **char** | **int** | *Type* [**num**] | &*Type*

Expn \rightarrow **literal** | **num** | **id** | *Expn* mod *Expn* | *Expn* [*Expn*] | **Expn*

Stmt \rightarrow **id** = *Expn* | *Stmt* ; *Stmt* | **if** *Expn* **then** *Stmt* | **while** *Expn* **do** *Stmt*

- $$\frac{F, G \vdash e : T'}{F, G \vdash x = e \text{ is valid}} \quad x : T \in G, T \equiv T'$$
- $$\frac{F, G \vdash e : T'}{F, G \vdash x = e \text{ is invalid}} \quad x : T \in G, T \not\equiv T'$$

Adding and Checking Statements

Program \rightarrow *Decls* ; *Stmt*

Decls \rightarrow *Decls* ; *Decls* | **id** : *Type*

Type \rightarrow **char** | **int** | *Type* [**num**] | &*Type*

Expn \rightarrow **literal** | **num** | **id** | *Expn* mod *Expn* | *Expn* [*Expn*] | **Expn*

Stmt \rightarrow **id** = *Expn* | *Stmt* ; *Stmt* | **if** *Expn* **then** *Stmt* | **while** *Expn* **do** *Stmt*

- $$\frac{F, G \vdash e : T'}{F, G \vdash x = e \text{ is valid}} \quad x : T \in G, T \equiv T'$$
- $$\frac{F, G \vdash e : T'}{F, G \vdash x = e \text{ is invalid}} \quad x : T \in G, T \not\equiv T'$$
- [Effect of declaration]
$$\frac{F, (G, x : T) \vdash s \text{ is valid}}{F, G \vdash x : T ; s \text{ is valid}} \quad x \notin G$$