

TEST PROJECT

Module A

Submitted by:

Assessment Browser:

Google Chrome

Postman





介绍

随着移动设备的快速发展，手机已成为生活中拍照的主流方式。“EAPhoto”专门帮助用户打印手机拍摄的照片。根据不同的需求，用户可以选择纸张尺寸、画框，甚至未来的礼品包装。传统网站已无法满足“EAPhoto”快速增长的业务。您需要开发一个网站来扩大在线业务。

该模块分为两部分。在第一部分中，您可以根据需求完成后端API开发工作，在第二部分中，您将使用第一部分中开发的API制作前端应用程序功能。

First 3 hours – Api开发

该项目第一阶段的说明：第一个阶段的任务是创建一个restful API，前端程序可以使用它来进行数据通信。在没有特殊指令的情况下，请求所需字段为空的情况应返回422错误。

图片上传后应给出原图地址（original_url）、编辑后的地址（edited_url）与增加画框后的地址（framed_url），此处可以不制作对应功能，但是URL需要要有区分，且URL必须为http://开头并能够正常访问上传的图片。

数据库

您可以使用素材提供的数据库，或者由您根据所需功能自行创建。

数据库搭建完成后，需要提供SQL导出文件，将其存储在工作目录中，命名为database-dump.sql。

如果您选择自行创建数据库,请创建用户档案：

管理员用户：

Email: admin@eaphoto.com

密码: admin

授权用户：

Email: user@eaphoto.com



密码: user

REST API 身份认证

当平台用户登录时，API将返回用户的登录标识token。客户端将存储该token，并将其作为HTTP请求头(Headers)中的Authorization与每个请求一起发送到后端。后端将根据token判断登录状态。

如果用户注销，token将从数据库中删除。

您可以使用任何形式的token（例如UUID或任何机器在合理时间内无法猜到的东西）。

管理员API

1. 授权

a. Login (/admin/login)

描述: 管理员登录。

Request Method: POST

Request Parameters:

- email
- password

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": {
    "id": 1,
    "email": "sample@email.com",
    "full_name": "Sample User",
    "token": "AUTHORIZATION_TOKEN",
    "create_time": "2022-01-01 00:00"
  }
}
```



```
}
```

Data for wrong data:

Status Code: 422

Body:

```
{  
  msg: "data cannot be processed"  
}
```

Data for wrong user credential:

Status Code: 401

Body:

```
{  
  msg: "user credentials are invalid"  
}
```

b. Logout (/admin/logout)

描述: 管理员登出。

Request Method: POST

Response Result:

Data for success:

Status Code: 200

Body:

```
{  
  msg: "success"  
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{  
  msg: "unauthorized"  
}
```

Body Result Sample for Success:

```
{  
  "msg": "success"  
}
```



2. Size

a. Get All Sizes (/admin/size)

描述:管理员获取所有的Size。

Request Method: GET

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": [
    {
      "id": 1,
      "size": "5 Inch",
      "width": 5,
      "height": 5,
      "price": 1.2
    },...
  ]
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

b. Update Size (/admin/size/{size_id})

描述: 管理员可以更新Size。

Request Parameters:

- price

Request Method: Patch

Response Result:



Data for success:

Status Code: 200

Body:

```
{
  "msg": "success" ,
  "data": {
    "id": 1 ,
    "size": "5 Inch" ,
    "width": 5,
    "height": 5,
    "price": 1.2
  }
}
```

Data for size not found:

Status Code: 404

Body:

```
{
  msg: "not found"
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

3. Frame

a. Get All Frames (/admin/frame)

描述: 管理员获取所有的Frame。

Request Method: Get

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success" ,
```



```
{
  "data": [
    {
      "id": 1 ,
      "url": "http://IMAGE_URL" ,
      "price": 1.2,
      "name": "Frame",
      "size": "5 Inch"
    },...
  ]
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

b. Update Frame (/admin/frame/{frame_id})

描述: 管理员可以更新Frame。

Request Parameters:

- frame_name (nullable)
- size_id (nullable)
- price (nullable)

Request Method: Patch

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success" ,
  "data": {
    "id": 1 ,
    "url": "http://IMAGE_URL" ,
    "price": 1.2,
    "name": "Frame",
    "size": "5 Inch"
  }
}
```



```
}
```

```
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{  
    msg: "unauthorized"  
}
```

4. Order

a. Get All Orders(/admin/order)

描述: 管理员获取所有的Order。

Request Method: Get

Response Result:

Data for success:

Status Code: 200

Body:

msg: "success"

data:

```
{  
    "msg": "success",  
    "data": [  
        {  
            "id": 1,  
            "full_name": "Matthew",  
            "phone_number": "10001000",  
            "shipping_address": "Where",  
            "card_number": "3223222222",  
            "name_on_card": "Matthew XXX",  
            "exp_date": "2024-02-20",  
            "cvv": "246",  
            "total": 10,  
            "urder_placed": "2022-02-02 00:00",  
            "status": "Valid",  
            "photos": [  
                {  
                    "id": 1,
```




```
        "edited_url": "http://IMAGE_URL",
        "original_url": "http://IMAGE_URL",
        "framed_url": "http://IMAGE_URL",
        "frame_name": "Frame",
        "size": "5 Inch",
        "print_price": 1.2,
        "frame_price": 1.2
    },...
]
},...
]
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
    msg: "unauthorized"
}
```

b. Cancel Order(/admin/order/cancel/{order_id})

描述: 管理员可以取消一个Order, Order的状态变更为"Invalid".

Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{
    "msg": "success",
}
```

Data for order not found:

Status Code: 404

Body:

```
{
    msg: "not found"
}
```



Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

c. Complete Order(/admin/order/complete/{order_id})

描述: 管理员可以完成一个Order, Order的状态变更为"Completed".

Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
}
```

Data for order not found:

Status Code: 404

Body:

```
{
  msg: "not found"
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```



5. User

a. Get All Users(/admin/user)

描述: 管理员获取所有的User。

Request Method: Get

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": [
    {
      "id": 1,
      "email": "sampleuser@eap.mail",
      "username": "sample_user",
      "create_time": "2022-01-01 00:00",
      "cart_total": 300
    },...
  ]
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

b. Reset User Password (/admin/user/reset/{user_id})

描述: 管理员可以重置一个用户的密码，将密码重置为8位随机数。

Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
```



```
    "data": {  
      "id": 1,  
      "password": "PASSWORD"  
    }  
  }  
}
```

Data for account not found:

Status Code: 404

Body:

```
{  
  "msg": "not found"  
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{  
  "msg": "unauthorized"  
}
```

c. Delete a User(/admin/user/{user_id})

描述: 管理员可以删除User。

Request Method: Delete

Response Result:

Data for success:

Status Code: 200

Body:

```
{  
  "msg": "success",  
}
```

Data for account not found:

Status Code: 404

Body:

```
{  
  "msg": "not found"  
}
```



Data for unauthorized:

Status Code: 401

Body:

```
{
  "msg": "unauthorized"
}
```

d. Reset a User`s Cart(/admin/cart/reset/{user_id})

描述: 管理员可以清除某个用户的购物车。

Request Method: POST

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
}
```

Data for account not found:

Status Code: 404

Body:

```
{
  "msg": "not found"
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  "msg": "unauthorized"
}
```

6. Admin

a. Get All Admins(/admin/admin)

描述: 管理员获取所有的Admin。



Request Method: Get

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success" ,
  "data": [
    {
      "id": 1,
      "email": "sampleadmin@eap.mail"
      "full_name": "Admin Name",
      "create_time": "2022-01-01 00:00"
    },...
  ]
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

b. Create Admin(/admin/admin)

描述: 管理员能够创建新的管理员, Email不能与别的管理员重复。

Request Parameters:

- email
- full_name
- password
- repeat_password

Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success" ,
```



```
    "data": {  
      "id": 1,  
      "email": "sampleadmin@eap.mail"  
      "full_name": "Admin Name",  
      "create_time": "2022-01-01 00:00"  
    }  
  }  
}
```

Data for wrong data:

Status Code: 422

Body:

```
{  
  msg: "data cannot be processed"  
}
```

Data for duplicate email:

Status Code: 422

Body:

```
{  
  msg: "email has already been used"  
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{  
  msg: "unauthorized"  
}
```

c. Reset Admin Password (/admin/admin/reset/{admin_id})

描述: 管理员可以重置一个管理员的密码, 将密码重置为8位随机数。

Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{  
  "msg": "success",
```



```
    "data": {  
      "id": 1,  
      "password": "PASSWORD"  
    }  
  }  
}
```

Data for account not found:

Status Code: 404

Body:

```
{  
  "msg": "not found"  
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{  
  "msg": "unauthorized"  
}
```

d. Delete an Admin(/admin/admin/{admin_id})

描述: 管理员能够删除Admin。

Request Method: Delete

Response Result:

Data for success:

Status Code: 200

Body:

```
{  
  "msg": "success",  
}
```

Data for account not found:

Status Code: 404

Body:

```
{  
  "msg": "not found"  
}
```




Data for unauthorized:

Status Code: 401

Body:

```
{
  "msg": "unauthorized"
}
```

授权用户API

1. Auth

a. Login (/client/login)

描述: 用户能够登陆。

Request Method: POST

Request Parameters:

- email
- password

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": {
    "id": 1,
    "email": "sample@email.com",
    "username": "sample_user",
    "token": "AUTHORIZATION_TOKEN",
    "create_time": "2022-01-01 00:00"
  }
}
```

Data for wrong data:

Status Code: 422

Body:

```
{
```



```
    msg: "data cannot be processed"
  }
```

Data for wrong user credential:

Status Code: 401

Body:

```
{
  msg: "user credentials are invalid"
}
```

b. Register (/client/register)

描述: 游客可以注册为用户。Email不能与别的用户重复。

Request Method: POST

Request Parameters:

- email
- username
- password
- repeat_password

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": {
    "id": 1,
    "email": "sample@email.com",
    "username": "sample_user",
    "token": "AUTHORIZATION_TOKEN",
    "create_time": "2022-01-01 00:00"
  }
}
```

Data for wrong data:

Status Code: 422

Body:

```
{
  msg: "data cannot be processed"
}
```



```
}
```

Data for duplicate email:

Status Code: 422

Body:

```
{
  "msg": "email has already been used"
}
```

c. Logout (/client/logout)

描述:用户登出。

Request Method: POST

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success"
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  "msg": "unauthorized"
}
```

d. Reset Password (/client/user/reset)

描述:用户可以重新设置自己的密码。

Request Parameters:

- original_password
- new_password
- repeat_password (字段值必须与“new_password”字段相同，否则返回422错误)

Request Method: POST

Response Result:

Data for success:



Status Code: 200

Body:

```
{
  "msg": "success",
  "data": {
    "id": 1,
    "email": "sample@email.com",
    "username": "sample_user",
    "create_time": "2022-01-01 00:00",
  }
}
```

Data for wrong data:

Status Code: 422

Body:

```
{
  msg: "data cannot be processed"
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

2. Size

a. Get All Sizes (/client/size)

描述: 用户获取所有的Size。

Request Method: GET

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": [
```



```
{
  "id": 1 ,
  "size": "5 Inch" ,
  "width": 5,
  "height": 5 ,
  "price": 1.2
},...
]
```

3. Photo

a. Upload Photo (/client/photo)

描述: 用户可以上传图片

Request Parameters:

- image (上传文件类型限制为 “png”, “jpg”, “gif”)
- size_id

Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success" ,
  "data": {
    "id": 1 ,
    "edited_url": "http://IMAGE_URL" ,
    "original_url": "http://IMAGE_URL" ,
    "framed_url": "http://IMAGE_URL"
  }
}
```

Data for size not found:

Status Code: 404

Body:

```
{
  msg: "not found"
```



```
}
```

Data for wrong data:

Status Code: 422

Body:

```
{  
  "msg": "data cannot be processed"  
}
```

b. Delete a Photo (/client/photo/{photo_id})

描述: 用户可以删除图片。

Request Method: Delete

Response Result:

Data for success:

Status Code: 200

Body:

```
{  
  "msg": "success"  
}
```

Data for photo not found:

Status Code: 404

Body:

```
{  
  "msg": "not found"  
}
```

c. Set Frame for Photo (/client/photo/frame/{photo_id}/{frame_id})

描述: 用户可以为图片选取相框。

Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{  
  "msg": "success",
```



```
    "data": {
      "id": 1,
      "frame_url": "https://IMAGE_URL"
    }
  }
```

Data for photo or frame not found:

Status Code: 404

Body:

```
{
  msg: "not found"
}
```

4. Frame

a. Get All Frames (/client/frame)

描述: 用户获取所有的Frame。

Request Method: Get

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": [
    {
      "id": 1,
      "url": "http://IMAGE_URL",
      "price": 1.2,
      "name": "Frame",
      "size": "5 Inch"
    },...
  ]
}
```



5. Cart

a. Get Cart(/client/cart)

描述: 获取用户的购物车。

Request Method: Get

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": [
    {
      "id": 1,
      "edited_url": "http://IMAGE_URL",
      "original_url": "http://IMAGE_URL",
      "framed_url": "http://IMAGE_URL",
      "frame_name": "Frame",
      "size": "5 Inch",
      "print_price": 1.2,
      "frame_price": 1.2,
    },...
  ]
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

b. Add Photos to Cart(/client/cart)

描述: 用户为购物车添加图片。

Request Parameters:

- photo_id_list (array)



Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success"
}
```

Data for photo can not found:

Status Code: 404

Body:

```
{
  msg: "not found"
}
```

Data for wrong data:

Status Code: 422

Body:

```
{
  msg: "data cannot be processed"
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

c. Delete Photo From a User`s Cart(/client/cart/photo/{photo_id})

描述: 用户可以从购物车中删除图片

Request Method: DELETE

Response Result:

Data for success:

Status Code: 200

Body:

```
{
```



```
    "msg": "success"
  }
```

Data for photo can not found:

Status Code: 404

Body:

```
{
  msg: "not found"
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

6. Order

a. Get My Orders(/client/order)

描述: 用户获取自己的订单。

Request Method: Get

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success",
  "data": [
    {
      "id": 1,
      "full_name": "Matthew",
      "phone_number": "10001000",
      "shipping_address": "Where",
      "card_number": "3223222222",
      "name_on_card": "Matthew XXX",
      "exp_date": "2024-02-20",
      "cvv": "246",
```



```
{
  "total": 10,
  "order_placed": "2022-02-02 00:00",
  "status": "Valid",
  "photos": [
    {
      "id": 1,
      "edited_url": "http://IMAGE_URL",
      "original_url": "http://IMAGE_URL",
      "framed_url": "http://IMAGE_URL",
      "frame_name": "Frame",
      "size": "5 Inch",
      "print_price": 1.2,
      "frame_price": 1.2
    },...
  ]
},...
]
```

Data for unauthorized:

Status Code: 401

Body:

```
{
  msg: "unauthorized"
}
```

b. Create Order(/client/order)

描述: 用户可以创建订单

Request Parameters:

- full_name
- phone_number
- shipping_address
- card_number
- name_on_card
- exp_date (YYYY-MM-DD)
- cvv (The field value length must be equals 3.)
- photo_id_list (array)



Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{
  "msg": "success" ,
  "data": {
    "id": 1 ,
    "full_name": "Matthew" ,
    "phone_number": "10001000",
    "shipping_address": "Where",
    "card_number": "3223222222",
    "name_on_card": "Matthew XXX",
    "exp_date": "2024-02-20",
    "cvv": "246",
    "total": 10,
    "order_placed": "2022-02-02 00:00",
    "status": "Valid",
    "photos": [
      {
        "id": 1,
        "edited_url": "http://IMAGE_URL" ,
        "original_url": "http://IMAGE_URL" ,
        "framed_url": "http://IMAGE_URL" ,
        "frame_name": "Frame",
        "size": "5 Inch" ,
        "print_price": 1.2,
        "frame_price": 1.2
      },...
    ]
  }
}
```

Data for photo not found:

Status Code: 404

Body:

```
{
  msg: "not found"
```



```
}
```

Data for wrong data:

Status Code: 422

Body:

```
{  
  msg: "data cannot be processed"  
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{  
  msg: "unauthorized"  
}
```

c. Cancel Order(/client/order/cancel/{order_id})

描述: 用户可以取消订单, Order的状态变更为"Invalid".

Request Method: Post

Response Result:

Data for success:

Status Code: 200

Body:

```
{  
  msg: "success"  
}
```

Data for order not found:

Status Code: 404

Body:

```
{  
  msg: "not found"  
}
```

Data for unauthorized:

Status Code: 401

Body:

```
{
```



msg: "unauthorized"

}

选手须知

- 在功能未完全开发完成的情况下，请优先保证裁判能够通过站点目录访问作品，裁判将通过路径 /XX_Module_A/api/v1 访问API服务。
- 您应该考虑代码的质量。
- 所有作品都是在服务器端评测，无本地评测过程。
- 作品完成后请保存至站点目录 /XX_Module_A 中，XX是您的工位号。