

## Maps Place Add API (POST):

This API Will add new place into Server

**Complete URL :** <https://rahulshettyacademy.com/maps/api/place/add/json?key=qaclick123>

**Base URL:** <https://rahulshettyacademy.com>

**Resource:** /maps/api/place/add/json

**Query Parameters:** key =qaclick123

**Http Method:** POST

**Sample Body :**

```
{
  "location": {
    "lat": -38.383494,
    "lng": 33.427362
  },
  "accuracy": 50,
  "name": "Frontline house",
  "phone_number": "(+91) 983 893 3937",
  "address": "29, side layout, cohen 09",
  "types": [
    "shoe park",
```

```
"shop"  
  
],  
  
"website": "http://google.com",  
  
"language": "French-IN"  
}
```

## Sample Response

```
{  
  
  "status": "OK",  
  
  "place_id": "928b51f64aed18713b0d164d9be8d67f",  
  
  "scope": "APP",  
  
  "reference":  
  "736f3c9bec384af62a184a1936d42bb0736f3c9bec384af62a184a1936d42bb0",  
  
  "id": "736f3c9bec384af62a184a1936d42bb0"  
}
```

## Google Maps Delete API (POST):

This API Will delete existing place from Server

**Complete URL:** <https://rahulshettyacademy.com/maps/api/place/delete/json?key=qaclick123>

**Base URL:** <https://rahulshettyacademy.com>

**Resource:** /maps/api/place/delete/json

**Query Parameters:** key

**Http request :** POST

**Sample Body :**

```
{  
  "place_id": "928b51f64aed18713b0d164d9be8d67f"  
}
```

**Sample Response**

```
{  
  "status": "OK"  
}
```

**Google Maps get Place API (GET):**

**This API Will get existing place details from Server**

**Complete URL :** [http://rahulshettyacademy.com/maps/api/place/get/json?place\\_id=xxxx&key=qaclick123](http://rahulshettyacademy.com/maps/api/place/get/json?place_id=xxxx&key=qaclick123)

**Base URL:** <https://rahulshettyacademy.com>

**Resource:** /maps/api/place/get/json

**Parameters:** key, place\_id //( place\_id value comes from Add place response)

**Http request:** GET

Note: Key value is hardcoded and it is always qaclick123

**Sample Response for the Provided Place\_Id**

```
{  
  
  "location":{  
  
    "lat" : -38.383494,  
  
    "lng" : 33.427362  
  
  },
```

```
"accuracy":50,  
  
"name":"Frontline house",  
  
"phone_number":"+91) 983 893 3937",  
  
"address" : "29, side layout, cohen 09",  
  
"types": ["shoe park","shop"],  
  
"website" : "http://google.com",  
  
"language" : "French-IN"  
  
}
```

## Google Maps Put Place API (PUT):

This API Will update existing place in Server with new values

**Complete URL :** `http://rahulshettyacademy.com/maps/api/place/update/json?place_id=xxxx&key=qaclick123`

**Base URL :** <https://rahulshettyacademy.com>

**Resource:** `/maps/api/place/update/json`

**Query Parameters:** `key, place_id` //(place\_id value comes from Add place response)

**Http Method:** PUT

Note: Key value is hardcoded and it is always qaclick123

### Sample Request:

```
{  
  "place_id": "8d2573bdf6ceec0e474c5f388fa917fb",  
  "address": "70 winter walk, USA",  
  "key": "qaclick123"  
}
```

### Sample Response for the Provided Place\_Id

```
{
```

"location":{

"lat" : -38.383494,

"lng" : 33.427362

},

"accuracy":50,

"name":"Frontline house",

"phone\_number":"+91 983 893 3937",

"address" : "29, side layout, cohen 09",

"types": ["shoe park","shop"],

"website" : "http://google.com",

"language" : "French-IN"

}