


## NOTE:

- To fit chain 08B1 (12.7 mm = 1/2" pitch)
- Debur and break sharp edges



_							
	С	03.05.2023	В	03.10.2022	Α	13.06.2022	
	ECO	NO: 006941	ECO	NO: 006738	ECO NO: 006715		
	AND	ES UPDATED GENERAL ERANCE ED			FIRS	T RELEASE	
	ÇİZEN: DRAWN:	CAGLAR OZTURK	DRAWN: ÇİZEN:	KEMAL DURAK	DRAWN: ÇİZEN:	KEMAL DURAK	
	KONTROL: CHECKED:	MEHMET SOGUT	CHECKED: KONTROL:	FURKAN KELASOVALI	CHECKED: KONTROL:	CAN OZBERKMEN	
	ONAY: APP.:	ORAL VATAN	APP.: ONAY:	ORAL VATAN	APP.: ONAY:	FURKAN KELASOVALI	

ik sharp euge	:5								
MATERIAL: MALZEME:	STAINLESS STEEL AISI 316 -(EN 1.4401)	[				GULATION: G. İŞARET:		-	
HARDNESS: SERTLİK:	-	_				ORMES: ARTNAM	RMES: RTNAMELER:		
PART NAME: PARÇA ADI:							WEIGHT AĞIRLIK		KEMAL DURAK
			0.439kg	CHECKED: KONTROL:	CAN OZBERKMEN				
MOTOR OUTPUT SPROCKET							0.439kg	APP.: ONAY:	FURKAN KELASOVALI
DWG NO: RESİM NO:	FQK.141004.AA		SSR:	PAGE SAYFA	1/1	SCALE ÖLÇEK		MODEL: MODEL:	EQUAD
FH				FORMAT EBAT	GENEL T ISO 2768 LINE	UNSPECIFIED TOLERANCES GENEL TOLERANS ISO 2768-mk LINEAR: +/- 0.25 mm ANGULAR: +/- 1°		VERSION: VERSIYON:	
Fernhay LTD Elizabeth House 13-19 London Road Newbury Berkshire RG14 1JL United Kingdom									