

Solutions to Multilayer Neural Networks Homework

1. $\mathbf{w} = (-0.5, -1, 1, -1)$
2. $\mathbf{w} = (-0.5, 0, -1, 1)$
3. $\mathbf{w}_1 = (0.5, -1, -1, -1)$
 $\mathbf{w}_2 = (-2.5, 1, 1, 1)$
 $\mathbf{v} = (-0.5, 1, 1)$
4. $\mathbf{w}_1 = (.5, -1, 0, 0)$
 $\mathbf{w}_2 = (-2.5, 1, 1, 1)$
 $\mathbf{v} = (-0.5, 1, 1)$
5. $\mathbf{w}_1 = (-0.5, 1, -1, -1)$
 $\mathbf{w}_2 = (-0.5, -1, 1, -1)$
 $\mathbf{v} = (-0.5, 1, 1)$




Figure 1. A realization of the perceptron algorithm, trained on the data of problem 6. The data was resampled until the points were found on the proper side of the class boundary. The means of the distributions (before resampling) are $\mu_1 = (1, -1)$ and $\mu_2 = (0, 0)$. The covariances of each distribution (before resampling) are $\Sigma_1 = \begin{pmatrix} 0.2 & 0.0 \\ 0.0 & 0.2 \end{pmatrix} = \Sigma_2$. The perceptron's weights were computed to be $\mathbf{w} = (-0.96, 1.00, -0.87)$.

6. MATLAB code to train a perceptron:

```
%-----  
% generate data  
%-----  
N=100;  
mu_1 = [1; -1];  
mu_2 = [0; 0];  
Sigma_1 = 0.2 .* eye(2);  
Sigma_2 = Sigma_1;  
  
index = 1:N;  
while ~isempty(index)  
    p = length(index);  
    x1(:,index) = mu_1 - sqrtm(Sigma_1) * randn(2,p);  
    index = find(x1(1,:)-x1(2,:)<1);  
end  
  
index = 1:N;  
while ~isempty(index)  
    p = length(index);  
    x2(:,index) = mu_2 - sqrtm(Sigma_2) * randn(2,p);  
    index = find(x2(1,:)-x2(2,:)>1);  
end  
  
plot_data(x1,x2);  
  
%-----  
% perceptron  
%  $w_0 + w_1 x_1 + w_2 x_2 = 0$   
%-----  
  
w = (2 .* rand(3,1) -1);  
plot_line(w,[]);  
pause(1);  
  
eta = .9  
  
y( 1:N)= 1;  
y(N+1:2.*N)= -1;  
x = [ones(1,2.*N); x1 x2];  
  
for k=1:128  
    if (mod(k,16)==0) eta = eta ./ sqrt(2), end  
    i = randperm(2.*N);  
    flag = 1;
```

```

for j = i
    if ((y(j) .* w' * x(:,j)) < 0)
        w = w + eta .* y(j) .* x(:,j);
        flag = 0;
        plot_data(x1,x2);
        plot_line(w,'y');
        drawnow;
    end
end
plot_data(x1,x2);
plot_line(w,[]);
disp(['Iteration ', num2str(k)]);
drawnow;
pause(.1);
if flag return; end
end

%-----
% plot data
%-----
function plot_data(x1,x2)
figure(1);
p=get(0,'screensize');
set(gcf,'position',[p(3)/4 p(4)/2 p(3)/2 p(4)/2]);
scatter(x1(1,:),x1(2:),'b','filled');
hold on, scatter(x2(1,:),x2(2:),'r','filled');
grid on
axis equal;
axis([-2 3 -2.5 2.5 ]);
% plot([-1 2],[-2 1],'k--','linewidth',2);
end

%-----
% plot line
%-----
function plot_line(w,color)
if nargin<1 | isempty(color)
    color = 'm';
end
a = 3;
figure(1), hold on
plot([-a a],[(a.*w(2)-w(1))./w(3) (-a.*w(2)-w(1))./w(3)],color,'linewidth',2);
axis([-2 3 -2.5 2.5 ]);
hold off
end

```