CONVERTING 'C' CODE INTO ONE_STACK

The easiest way to understand this is by comparing this with basic 'C' code.

```
Int *iPtr = malloc (sizeof (int) * 10);

for (int y=0; y < 10; y++) {
    *(iPtr + y) = y * y;
    Printf ("%P %d \n", iPtr+y, *(iPtr+y));
}
free (iPtr);
iPtr = NULL;
```

- start:

```
∅ int y def-i
80 int mem-alloc iPtr def-i

{ iPtr peek 8int y peek * + dup
  y peek dup *
  [poke]
  Print-ptr-nnl "▽▽" print-str-nnl pop
  [peek] print-i pop
  y peek ++ y poke
} y peek 10 int < loop

iPtr peek pop-free
∅ int iPtr poke
```

Here we can use a function to swap chars in a string:

```
func:   swap-chars      ; expects 2 pointers to the string

        str-1 def-i
        str-2 def-i

        str-1 peek byte-at char-1 def-i
        str-1 peek str-2 peek byte-at 0 int upd-byte
        pop

        str-2 peek char-1 peek 0 int upd-byte
        pop
        return
```

This replicates swap in 'c':

```
void swap (char *x, char *y) {
    char temp = *x;
    *x = *y;
    *y = temp;
}
```