

AMORE++

pre-alpha (active development aiming to release a beta version this summer (2011))

Generated by Doxygen 1.7.4

Wed Jun 8 2011 01:21:53

Contents

1	The AMORE++ package	1
1.1	Introduction	1
1.2	Motivation	1
1.3	Road Map	1
2	Class Index	3
2.1	Class Hierarchy	3
3	Class Index	5
3.1	Class List	5
4	File Index	7
4.1	File List	7
5	Class Documentation	9
5.1	CompareId Struct Reference	9
5.1.1	Detailed Description	9
5.1.2	Member Function Documentation	9
5.1.2.1	operator()	9
5.1.2.2	operator()	9
5.1.2.3	operator()	10
5.1.2.4	operator()	10
5.2	Con Class Reference	10
5.2.1	Detailed Description	11
5.2.2	Constructor & Destructor Documentation	11
5.2.2.1	Con	11
5.2.2.2	Con	11

5.2.2.3	Con	12
5.2.2.4	~Con	12
5.2.3	Member Function Documentation	12
5.2.3.1	getFrom	12
5.2.3.2	getId	13
5.2.3.3	getWeight	14
5.2.3.4	setFrom	15
5.2.3.5	setWeight	16
5.2.3.6	show	16
5.2.3.7	validate	17
5.2.4	Member Data Documentation	18
5.2.4.1	from	18
5.2.4.2	weight	18
5.3	Container< T > Class Template Reference	19
5.3.1	Detailed Description	22
5.3.2	Member Typedef Documentation	23
5.3.2.1	const_iterator	23
5.3.2.2	iterator	23
5.3.3	Constructor & Destructor Documentation	23
5.3.3.1	Container	23
5.3.3.2	Container	23
5.3.4	Member Function Documentation	23
5.3.4.1	append	23
5.3.4.2	begin	25
5.3.4.3	empty	26
5.3.4.4	end	26
5.3.4.5	load	27
5.3.4.6	operator[]	28
5.3.4.7	push_back	28
5.3.4.8	reserve	29
5.3.4.9	resize	29
5.3.4.10	show	30
5.3.4.11	size	31
5.3.4.12	store	32

5.3.4.13	validate	32
5.3.5	Member Data Documentation	33
5.3.5.1	collection	33
5.4	Neuron Class Reference	33
5.4.1	Detailed Description	35
5.4.2	Constructor & Destructor Documentation	35
5.4.2.1	Neuron	35
5.4.2.2	Neuron	36
5.4.2.3	Neuron	36
5.4.2.4	~Neuron	36
5.4.3	Member Function Documentation	36
5.4.3.1	getConId	36
5.4.3.2	getFrom	37
5.4.3.3	getId	37
5.4.3.4	getWeight	38
5.4.3.5	numOfCons	38
5.4.3.6	setFrom	39
5.4.3.7	setId	39
5.4.3.8	setWeight	40
5.4.3.9	show	40
5.4.3.10	validate	41
5.4.4	Member Data Documentation	41
5.4.4.1	con	41
5.4.4.2	id	42
5.4.4.3	outputValue	42
5.5	VecCon Class Reference	42
5.5.1	Detailed Description	45
5.5.2	Constructor & Destructor Documentation	45
5.5.2.1	VecCon	45
5.5.2.2	VecCon	46
5.5.3	Member Function Documentation	46
5.5.3.1	buildAndAppend	46
5.5.3.2	erase	47
5.5.3.3	getFrom	49

5.5.3.4	getId	51
5.5.3.5	getWeight	52
5.5.3.6	getWeight	54
5.5.3.7	numOfCons	55
5.5.3.8	select	57
5.5.3.9	setFrom	59
5.5.3.10	setWeight	61
5.5.3.11	setWeight	62
5.5.3.12	validate	64
5.6	vecMLPneuron Class Reference	66
5.6.1	Detailed Description	66
5.6.2	Member Function Documentation	66
5.6.2.1	buildAndAppend	66
5.6.2.2	getId	66
5.7	VecNeuron Class Reference	66
5.7.1	Detailed Description	69
5.7.2	Constructor & Destructor Documentation	69
5.7.2.1	VecNeuron	69
5.7.2.2	VecNeuron	69
5.7.2.3	~VecNeuron	69
5.7.3	Member Function Documentation	70
5.7.3.1	getId	70
5.7.3.2	numOfNeurons	70
6	File Documentation	71
6.1	pkg/AMORE/src/AMORE.h File Reference	71
6.1.1	Define Documentation	72
6.1.1.1	foreach	72
6.1.1.2	size_type	72
6.1.2	Typedef Documentation	72
6.1.2.1	ConPtr	72
6.1.2.2	ContainerConPtr	72
6.1.2.3	ContainerNeuronPtr	73
6.1.2.4	NeuronPtr	73

6.1.2.5	NeuronWeakPtr	73
6.1.2.6	VecConPtr	73
6.1.2.7	VecNeuronPtr	73
6.2	pkg/AMORE/src/Con.cpp File Reference	73
6.3	pkg/AMORE/src/Con.h File Reference	74
6.4	pkg/AMORE/src/Container.cpp File Reference	75
6.5	pkg/AMORE/src/Container.h File Reference	75
6.6	pkg/AMORE/src/Neuron.cpp File Reference	75
6.7	pkg/AMORE/src/Neuron.h File Reference	77
6.8	pkg/AMORE/src/VecCon.cpp File Reference	77
6.9	pkg/AMORE/src/VecCon.h File Reference	78
6.10	pkg/AMORE/src/VecMLPneuron.h File Reference	78
6.11	pkg/AMORE/src/VecNeuron.cpp File Reference	79
6.12	pkg/AMORE/src/VecNeuron.h File Reference	79

Chapter 1

The AMORE++ package

1.1 Introduction

Here you will find the documentation of the C++ component of the AMORE++ R package. The AMORE++ package is a new version of the publicly available AMORE package for neural network training and simulation under R

1.2 Motivation

Since the release of the previous version of the AMORE many things have changed in the R programming world. The advent of the Reference Classes and of packages like Rcpp, inline and RUnit compel us to write a better version of the package in order to provide a more useful framework for neural network training and simulation.

1.3 Road Map

This project is currently very active and the development team intends to provide a beta version as soon as this summer (2011)

Chapter 2

Class Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

CompareId	9
Con	10
Container< T >	19
Container< Con >	19
VecCon	42
Container< Neuron >	19
VecNeuron	66
Neuron	33
vecMLPneuron	66

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

CompareId	9
Con (A class to handle the information needed to describe an input connection)	10
Container< T >	19
Neuron (A class to handle the information contained in a general Neuron) . .	33
VecCon (A vector of connections)	42
vecMLPneuron (A vector of connections)	66
VecNeuron (A vector of neurons)	66

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

pkg/AMORE/src/ AMORE.h	71
pkg/AMORE/src/ Con.cpp	73
pkg/AMORE/src/ Con.h	74
pkg/AMORE/src/ Container.cpp	75
pkg/AMORE/src/ Container.h	75
pkg/AMORE/src/ Neuron.cpp	75
pkg/AMORE/src/ Neuron.h	77
pkg/AMORE/src/ VecCon.cpp	77
pkg/AMORE/src/ VecCon.h	78
pkg/AMORE/src/ VecMLPneuron.h	78
pkg/AMORE/src/ VecNeuron.cpp	79
pkg/AMORE/src/ VecNeuron.h	79

Chapter 5

Class Documentation

5.1 CompareId Struct Reference

Public Member Functions

- bool `operator()` (const `ConPtr` `a`, const `ConPtr` `b`)
- bool `operator()` (const `ConPtr` `a`, const int `b`)
- bool `operator()` (const int `a`, const `ConPtr` `b`)
- bool `operator()` (const int `a`, const int `b`)

5.1.1 Detailed Description

Definition at line 395 of file `VecCon.cpp`.

5.1.2 Member Function Documentation

5.1.2.1 `bool CompareId::operator() (const ConPtr a, const ConPtr b)` `[inline]`

Definition at line 399 of file `VecCon.cpp`.

```
{  
    return a->getId() < b->getId();  
}
```

5.1.2.2 `bool CompareId::operator() (const int a, const int b)` `[inline]`

Definition at line 420 of file `VecCon.cpp`.

```
{  
    return a < b;  
}
```

5.1.2.3 `bool CompareId::operator() (const int a, const ConPtr b)` `[inline]`

Definition at line 413 of file VecCon.cpp.

```
{  
    return a < b->getId();  
}
```

5.1.2.4 `bool CompareId::operator() (const ConPtr a, const int b)` `[inline]`

Definition at line 406 of file VecCon.cpp.

```
{  
    return a->getId() < b;  
}
```

The documentation for this struct was generated from the following file:

- [pkg/AMORE/src/VecCon.cpp](#)

5.2 Con Class Reference

A class to handle the information needed to describe an input connection.

```
#include <Con.h>
```

Public Member Functions

- [Con \(\)](#)
Default Constructor.
- [Con \(NeuronPtr from\)](#)
Constructor.
- [Con \(NeuronPtr from, double weight\)](#)
Constructor.
- [~Con \(\)](#)
Default Destructor.
- [NeuronPtr getFrom \(\)](#)
from field accessor.
- `void` [setFrom \(NeuronPtr from\)](#)
from field accessor.
- `int` [getId \(\)](#)
A getter of the Id of the [Neuron](#) pointed by the from field.
- `double` [getWeight \(\)](#)
weight field accessor.

- void `setWeight` (double `weight`)
weight field accessor.
- bool `show` ()
Pretty print of the `Con` information.
- bool `validate` ()
Object validator.

Private Attributes

- `NeuronWeakPtr from`
A smart pointer to the `Neuron` used as input during simulation or training.
- double `weight`
A double variable that contains the weight of the connection.

5.2.1 Detailed Description

A class to handle the information needed to describe an input connection.

The `Con` class provides a simple class for a connection described by a pair of values: a pointer to a `Neuron` object used as the `from` field and the `weight` used to propagate the value of that `Neuron` object.

Definition at line 16 of file `Con.h`.

5.2.2 Constructor & Destructor Documentation

5.2.2.1 `Con::Con ()`

Default Constructor.

Definition at line 17 of file `Con.cpp`.

```
    :  
    weight(0), from()  
{  
}
```

5.2.2.2 `Con::Con (NeuronPtr from)`

Constructor.

Definition at line 40 of file `Con.cpp`.

```
    :  
    from(from), weight(0)  
{  
}
```

5.2.2.3 Con::Con (NeuronPtr from, double weight)

Constructor.

Definition at line 29 of file Con.cpp.

```

        :
        from(from), weight(weight)
    {
    }

```

5.2.2.4 Con::~Con ()

Default Destructor.

Definition at line 47 of file Con.cpp.

```

{
}

```

5.2.3 Member Function Documentation

5.2.3.1 NeuronPtr Con::getFrom ()

from field accessor.

This method allows access to the address stored in the private [from](#) field (a pointer to a [Neuron](#) object).*

Returns

A pointer to the [Neuron](#) object referred to by the [from](#) field.

```

//=====
//Usage example:
//=====
// Data set up
NeuronPtr ptShNeuron ( new Neuron(1) );           // Neuron
Id is set 1
ConPtr ptShCon( new Con(ptShNeuron) );           // from p
oints to ptShNeuron and weight is set to 0
// Test
ptShNeuron = ptShCon->getFrom() ;
int result = ptShNeuron->getId();

// Now, result is equal to 1.

```

See also

[getId](#) and the unit test files, e.g., `runit.Cpp.Con.R`, for further examples.

Definition at line 73 of file Con.cpp.

References from.

```
{
    return (from.lock());
}
```

5.2.3.2 int Con::getId ()

A getter of the Id of the [Neuron](#) pointed by the from field.

This method gets the Id of the [Neuron](#) referred to by the [from](#) field

Returns

The value of the Id (an integer).

```
//=====
//Usage example:
//=====
// Data set up
NeuronPtr ptShNeuron ( new Neuron(16) );           // Neuron
Id is set to 16
ConPtr ptShCon( new Con(ptShNeuron) );             // from p
oints to ptShNeuron and weight is set to 0
// Test
int result = ptShCon->getId();

// Now, result is equal to 16.
```

See also

[getFrom](#), [setFrom](#) and the unit test files, e.g., `runit.Cpp.Con.R`, for further examples.


Definition at line 125 of file `Con.cpp`.

References from.

Referenced by `show()`, and `validate()`.

```
{
    if (from.use_count() != 0)
    {
        NeuronPtr ptNeuron(from);
        return (ptNeuron->getId());
    }
    else
    {
        return (NA_INTEGER);
    }
}
```

Here is the caller graph for this function:



5.2.3.3 double Con::getWeight ()

weight field accessor.

This method allows access to the value stored in the private field [weight](#)

Returns

The value of [weight](#) (double)

```

//=====
//Usage example:
//=====
// Data set up
std::vector<double> result;
NeuronPtr ptShNeuron ( new Neuron(16) );           /
/ Neuron Id is set to 16
ConPtr ptShCon( new Con(ptShNeuron, 12.4) ); // from poi
nts to ptShNeuron and weight is set to 12.4
// Test
result.push_back( ptShCon->getWeight() );
ptShCon->setWeight(2.2);
result.push_back( ptShCon->getWeight() );

// Now, result is a numeric vector that contains the values 12.4 and 2.2
.

```

See also

[setWeight](#) and the unit test files, e.g., `runit.Cpp.Con.R`, for further examples.

Definition at line 161 of file `Con.cpp`.

References [weight](#).


Referenced by `show()`, and `validate()`.

```

{
    return (weight);
}

```

Here is the caller graph for this function:



5.2.3.4 void Con::setFrom (NeuronPtr from_)

from field accessor.

This method sets the value of the [from](#) field with the address used as parameter.

Parameters

<i>f</i>	A pointer to the neuron that is to be inserted in the from field.
----------	---

```

//=====
//Usage example:
//=====
// Data set up
NeuronPtr ptShNeuron ( new Neuron(1) );           // Neuron
Id is set to 1
ConPtr ptShCon( new Con() );
ptShCon->setFrom( ptShNeuron );

// Test
ptShNeuron = ptShCon->getFrom() ;
int result = ptShNeuron->getId();

// Now, result is equal to 1
  
```

See also

[getFrom](#) and [getId](#) contain usage examples. For further examples see the unit test files, e.g., `runit.Cpp.Con.R`

Definition at line 100 of file `Con.cpp`.

References from.

```

{
    from = from_;
}
  
```

5.2.3.5 void Con::setWeight (double w)

weight field accessor.

This method sets the value of the [weight](#) field.

Parameters

w	The new value (double) to be set in the weight field.
----------	---

```
//=====
//Usage example:
//=====
// Data set up

                                std::vector<double> result;
                                NeuronPtr ptShNeuron ( new Neuron(16) );                                /
/ Neuron Id is set to 16
                                ConPtr ptShCon( new Con(ptShNeuron, 12.4) ); // from poi
nts to ptShNeuron and weight is set to 12.4
                                result.push_back(ptShCon->getWeight());
                                // Test
                                ptShCon->setWeight(2.2);
                                result.push_back(ptShCon->getWeight());

                                // Now, result is a numeric vector that contains the values 12.4 and 2.2
.
```

See also

[getWeight](#) and the unit test files (e.g. runit.Cpp.Con.R)

Definition at line 189 of file Con.cpp.

References [weight](#).

```
{
    weight = w;
}
```

5.2.3.6 bool Con::show ()

Pretty print of the [Con](#) information.

This method outputs in the R terminal the contents of the [Con](#) fields.

Returns

true in case everything works without throwing an exception

See also

[setWeight](#) and the unit test files, e.g., runit.Cpp.Con.R, for usage examples.

Definition at line 200 of file Con.cpp.


References [getId\(\)](#), and [getWeight\(\)](#).


```

{
    int id = getId();
    if (id == NA_INTEGER)
    {
        Rprintf("From: NA\t Invalid Connection \n");
    }
    else
    {
        Rprintf("From:\t %d \t Weight= \t %lf \n", id, getWeight());
    }
    return (true);
}

```

Here is the call graph for this function:



5.2.3.7 bool Con::validate ()

Object validator.

This method checks the object for internal coherence. A try / catch mechanism exits normal execution and returns control to the R terminal in case the contents of the [Con](#) object are identified as corrupted.

Returns

true in case the checks are Ok.

Exceptions

<i>An</i>	std::range error if weight or from are not finite.
-----------	--

Definition at line 221 of file Con.cpp.

References [getId\(\)](#), and [getWeight\(\)](#).


```

{
    BEGIN_RCPP
    if (! R_FINITE(getWeight()) ) throw std::range_error("weight is not finite.");
    if (getId() == NA_INTEGER)

```

```
        throw std::range_error("fromId is not finite.");  
        return (true);  
    END_RCPP};
```

Here is the call graph for this function:



5.2.4 Member Data Documentation

5.2.4.1 `NeuronWeakPtr Con::from` [private]

A smart pointer to the [Neuron](#) used as input during simulation or training.

The `from` field contains the address of the [Neuron](#) whose output will be used as input by the [Neuron](#) containing the [Con](#) object.

Definition at line 22 of file `Con.h`.

Referenced by `getFrom()`, `getId()`, and `setFrom()`.

5.2.4.2 `double Con::weight` [private]

A double variable that contains the weight of the connection.

The `weight` field contains the factor by which the output value of the [Neuron](#) addressed by the `from` field is multiplied during simulation or training.

Definition at line 27 of file `Con.h`.

Referenced by `getWeight()`, and `setWeight()`.


The documentation for this class was generated from the following files:

- `pkg/AMORE/src/Con.h`
- `pkg/AMORE/src/Con.cpp`


5.3 Container< T > Class Template Reference

```
#include <Container.h>
```

Inheritance diagram for Container< T >:



Collaboration diagram for Container< T >:



Public Types

- typedef std::vector< boost::shared_ptr< T > >::iterator iterator
- typedef std::vector< boost::shared_ptr< T > >::const_iterator const_iterator

Public Member Functions

- [Container](#) ()
- [Container](#) (typename std::vector< boost::shared_ptr< T > > [collection](#))
- [iterator begin](#) ()
- [iterator end](#) ()
- std::vector< boost::shared_ptr< T > > [load](#) ()
collection field accessor function
- void [store](#) (typename std::vector< boost::shared_ptr< T > >)
collection field accessor function
- size_type [size](#) ()
Returns the size or length of the vector.
- void [push_back](#) (boost::shared_ptr< T > element)
Append a shared_ptr at the end of collection.
- void [append](#) ([Container](#)< T > v)
Appends a Container<T> object.
- bool [show](#) ()
Pretty print of the Container<T>
- bool [validate](#) ()
Object validator.
- void [reserve](#) (int n)
- void [resize](#) (int n)
- bool [empty](#) ()
- boost::shared_ptr< T > & [operator\[\]](#) (size_type offset)

Protected Attributes

- std::vector< boost::shared_ptr< T > > [collection](#)

5.3.1 Detailed Description

template<typename T>class Container< T >

Definition at line 12 of file Container.h.

5.3.2 Member Typedef Documentation

5.3.2.1 `template<typename T> typedef std::vector<boost::shared_ptr<T>
>::const_iterator Container< T >::const_iterator`

Definition at line 22 of file Container.h.

5.3.2.2 `template<typename T> typedef std::vector<boost::shared_ptr<T> >::iterator
Container< T >::iterator`

Definition at line 19 of file Container.h.

5.3.3 Constructor & Destructor Documentation

5.3.3.1 `template<typename T> Container< T >::Container ()`

Definition at line 9 of file Container.cpp.

```
{
}
```

5.3.3.2 `template<typename T> Container< T >::Container (typename std::vector<
boost::shared_ptr< T > > collection)`

Definition at line 14 of file Container.cpp.

```
collection(collection)
{
}
```

5.3.4 Member Function Documentation

5.3.4.1 `template<typename T> void Container< T >::append (Container< T > v)`

Appends a Container<T> object.

This method inserts the collection field of a second object at the end of the collection field of the calling object.

Parameters

<code>v</code>	The Container<T> object to be added to the current one
----------------	--

See also

The unit test files, e.g., `runit.Cpp.Container.R`, for usage examples.

```

//=====
//Usage example:
//=====
// Data set up

std::vector<int> result;
std::vector<ConPtr> vcA, vcB;
ContainerNeuronPtr ptShvNeuron( new
Container<Neuron>() );
ContainerConPtr ptShvConA( new Container<Con>() )
;
ContainerConPtr ptShvConB( new Container<Con>() )
;
ConPtr ptC;
NeuronPtr ptN;
int ids[] = {1, 2, 3, 4, 5, 6};
double weights[] = {1.13, 2.22, 3.33, 5.6, 4.2, 3
.6 };
for (int i=0; i<=5 ; i++) {
/ Let's create a vector with six neurons
ptN.reset( new Neuron( ids[i] ) );
ptShvNeuron->push_back(ptN);
}
for (int i=0; i<=2 ; i++) {
/ A vector with three connections
ptC.reset( new Con( ptShvNeuron->load().a
t(i), weights[i]) );
ptShvConA->push_back(ptC);
}
for (int i=3; i<=5 ; i++) {
/ Another vector with three connections
ptC.reset( new Con( ptShvNeuron->load().a
t(i), weights[i]) );
ptShvConB->push_back(ptC);
}

// Test
ptShvConA->append(*ptShvConB);
ptShvConA->validate();
ptShvConA->show() ;

// After execution of the code above, the output at the R terminal would
display:
//
// From:      1      Weight=      1.130000
// From:      2      Weight=      2.220000
// From:      3      Weight=      3.330000
// From:      4      Weight=      5.600000
// From:      5      Weight=      4.200000
// From:      6      Weight=      3.600000

```

See also

[Container::store](#) , [Container::push_back](#) and the unit test files, e.g., `runit.Cpp.Container.R`, for usage examples.

Definition at line 207 of file `Container.cpp`.

References `Container< T >::begin()`, `Container< T >::end()`, and `Container< T >::size()`.

```


{
reserve(size() + v.size());
collection.insert(end(), v.begin(), v.end());
}

```



```
}
```

Here is the call graph for this function:




5.3.4.2 `template<typename T> std::vector< boost::shared_ptr< T >>::iterator Container< T >::begin ()`

Definition at line 22 of file Container.cpp.

Referenced by `Container< T >::append()`, and `VecCon::setFrom()`.

```
{  
    return collection.begin();  
}
```

Here is the caller graph for this function:




5.3.4.3 `template<typename T> bool Container< T >::empty ()`

Definition at line 305 of file Container.cpp.

Referenced by `VecCon::buildAndAppend()`, and `VecCon::setFrom()`.

```
{
    return( collection.empty() );
}
```

Here is the caller graph for this function:



5.3.4.4 `template<typename T> std::vector< boost::shared_ptr< T > >::iterator Container< T >::end ()`

Definition at line 29 of file Container.cpp.

Referenced by `Container< T >::append()`.

```
{
    return collection.end();
}
```

Here is the caller graph for this function:



5.3.4.5 `template<typename T> std::vector< boost::shared_ptr< T>> Container< T>::load ()`

collection field accessor function

This method allows access to the data stored in the [collection](#) field.

Returns

The collection vector.

```
//=====
//Usage example:
//=====
// Data set up
std::vector<int> result;
std::vector<ConPtr> vcA, vcB;
ContainerNeuronPtr ptShvNeuron( new
Container<Neuron>() );
ContainerConPtr ptShvCon( new Container<Con>() );

ConPtr ptC;
NeuronPtr ptN;
int ids[] = {10, 20, 30};
double weights[] = {1.13, 2.22, 3.33 };
for (int i=0; i<=2 ; i++) {
/
/ Let's create a vector with three neurons
ptN.reset( new Neuron( ids[i] ) );
ptShvNeuron->push_back(ptN);
}
for (int i=0; i<=2 ; i++) {
/
/ and a vector with three connections
ptC.reset( new Con( ptShvNeuron->load().a
t(i), weights[i] ) );
vcA.push_back(ptC);
}

// Test
ptShvCon->store(vcA);
vcB = ptShvCon->load();
for (int i=0; i<=2 ; i++) {
/
/ get Ids. Container does not have getId defined
result.push_back( vcB.at(i)->getId());
}

// Now, result is an integer vector with values 10, 20, 30.
```

See also

[store](#) and the unit test files, e.g., `runit.Cpp.Container.R`, for usage examples.

Definition at line 254 of file `Container.cpp`.

```
{
return collection;
}
```

5.3.4.6 `template<typename T> boost::shared_ptr< T> & Container< T>::operator[] (size_type offset)`

Definition at line 313 of file Container.cpp.

```
{
    return collection[offset];
}
```

5.3.4.7 `template<typename T> void Container< T>::push_back (boost::shared_ptr< T> TsharedPtr)`

Append a `shared_ptr` at the end of collection.

Implements `push_back` for the [Container](#) class

Parameters

<i>TsharedPtr</i>	A <code>shared_ptr</code> pointer to be inserted at the end of collection
-------------------	---

```
//=====
//Usage example:
//=====
// Data set up
Neuron N1, N2, N3;
Container<Con> MyVecCon;
std::vector<ConPtr> vc;
std::vector<int> result;
N1.setId(10);
N2.setId(20);
N3.setId(30);

// Test
ConPtr ptCon( new Con(&N1, 1.13) ); // Create new Con
and initialize ptCon
MyVecCon.push_back(ptCon);          /
/ push_back
ptCon.reset( new Con(&N2, 2.22) ); // create
new Con and assign to ptCon
MyVecCon.push_back(ptCon);          /
/ push_back
ptCon.reset( new Con(&N3, 3.33) ); // create
new Con and assign to ptCon
MyVecCon.push_back(ptCon);          /
/ push_back

vc = MyVecCon.load();

result.push_back(vc.at(0)->getId());
result.push_back(vc.at(1)->getId());
result.push_back(vc.at(2)->getId());

// After execution of this code, result contains a numeric vector with va
lues 10, 20 and 30.
```

See also


C++ documentation for `std::vector::push_back` and the unit test files, e.g., `runit.Cpp.Container.R`, for usage examples.

Definition at line 71 of file Container.cpp.

Referenced by VecCon::getFrom().

```
{  
    collection.push_back(TsharedPtr);  
}
```

Here is the caller graph for this function:




5.3.4.8 `template<typename T> void Container< T >::reserve (int n)`

Definition at line 297 of file Container.cpp.

Referenced by VecCon::getFrom().

```
{  
    collection.reserve(n);  
}
```

Here is the caller graph for this function:



5.3.4.9 `template<typename T> void Container< T >::resize (int n)`

Definition at line 290 of file Container.cpp.

```
{  
    collection.resize(n);  
}
```

5.3.4.10 `template<typename T> bool Container<T>::show ()`

Pretty print of the `Container<T>`

This method outputs in the R terminal the contents of [Container::collection](#).

Returns

true in case everything works without throwing an exception

*

```
//=====
//Usage example:
//=====
// Data set up
ContainerNeuronPtr ptShvNeuron( new
Container<Neuron>() );
ContainerConPtr ptShvCon( new Container<Con>() );
ConPtr ptC;
NeuronPtr ptN;
int ids[] = {10, 20, 30};
double weights[] = {1.13, 2.22, 3.33 };

for (int i=0; i<=2 ; i++) {
/ Let's create a vector with three neurons
ptN.reset( new Neuron( ids[i] ) );
ptShvNeuron->push_back( ptN );
}

for (int i=0; i<=2 ; i++) {
/ and a vector with three connections
ptC.reset( new Con( ptShvNeuron->load().at(i), weights[i] ) );
ptShvCon->push_back( ptC );
}

// Test
ptShvCon->show() ;

// The output at the R terminal would display:
//
//      # From:  10      Weight=      1.130000
//      # From:  20      Weight=      2.220000
//      # From:  30      Weight=      3.330000
//
```

See also

The unit test files, e.g., `runit.Cpp.Container.R`, for usage examples.

Definition at line 122 of file `Container.cpp`.

Referenced by `Neuron::show()`.

```
{
// This is equivalent to:
// for( auto x : collection) { x.show(); }
// Waiting for C++0x
```

```
foreach (typename boost::shared_ptr<T> itr, *this)
{
    itr->show();
}
return true;
}
```

Here is the caller graph for this function:



5.3.4.11 `template<typename T> size_type Container< T >::size ()`

Returns the size or length of the vector.


This method returns the size of the vector. In the classes derived from `Container<T>` this is aliased as `numOfCons`, `numOfNeurons` and `numOfLayers`. The unit test files, e.g., `runit.Cpp.Container.R`, for usage examples.

Definition at line 282 of file `Container.cpp`.

Referenced by `Container< T >::append()`, `VecCon::buildAndAppend()`, and `VecCon::setFrom()`.

```
{
    return collection.size();
}
```

Here is the caller graph for this function:



5.3.4.12 `template<typename T> void Container< T >::store (typename std::vector< boost::shared_ptr< T > > v)`

collection field accessor function

This method sets the value of the data stored in the [collection](#) field.

Parameters

<code>v</code>	The vector of smart pointers to be stored in the collection field
----------------	---

See also

[load](#) and the unit test files, e.g., `runit.Cpp.Container.R`, for usage examples.

Definition at line 268 of file `Container.cpp`.

```

{
    collection = v;
}

```

5.3.4.13 `template<typename T> bool Container< T >::validate ()`

Object validator.

This method checks the object for internal coherence. This method calls the `validate` method for each element in `collection`,

See also

The unit test files, e.g., `runit.Cpp.Container.R`, for usage examples.

Reimplemented in [VecCon](#).

Definition at line 144 of file Container.cpp.

```
{
    foreach (typename boost::shared_ptr<T> itr, *this)
    {
        itr->validate();
    }
    return true;
}
```

5.3.5 Member Data Documentation

5.3.5.1 `template<typename T> std::vector<boost::shared_ptr<T> > Container< T
>::collection` [protected]

Definition at line 15 of file Container.h.

The documentation for this class was generated from the following files:


- pkg/AMORE/src/[Container.h](#)
- pkg/AMORE/src/[Container.cpp](#)

5.4 Neuron Class Reference

A class to handle the information contained in a general [Neuron](#).

```
#include <Neuron.h>
```

Collaboration diagram for Neuron:



Public Member Functions

- [Neuron](#) ()
- [Neuron](#) (int [Id](#))
- [Neuron](#) (int [Id](#), [VecCon](#) [con](#))
- [~Neuron](#) ()
- int [getId](#) ()
- void [setId](#) (int value)
- [VecNeuron](#) [getFrom](#) ()
- std::vector< int > [getConId](#) ()
- std::vector< double > [getWeight](#) ()
- bool [setFrom](#) ([VecNeuron](#) neuronContainer)
- bool [setWeight](#) (std::vector< double > nWeights)
- int [numOfCons](#) ()
- bool [show](#) ()
- bool [validate](#) ()

Private Attributes

- int [Id](#)
An integer variable with the [Neuron](#) Id.
- [VecCon](#) [con](#)
A vector of input connections.
- double [outputValue](#)

5.4.1 Detailed Description

A class to handle the information contained in a general [Neuron](#).

A general class for neurons. The MLPneuron and RBFneuron classes will specialize this general class

Definition at line 16 of file Neuron.h.

5.4.2 Constructor & Destructor Documentation

5.4.2.1 [Neuron::Neuron](#) ()

Definition at line 10 of file Neuron.cpp.

```

        :
        Id (NA_INTEGER), con ()
    {
    }

```

5.4.2.2 Neuron::Neuron (int *Id*)

Definition at line 15 of file Neuron.cpp.

```

        :
        Id(Id), outputValue(0.0)
    {
    }

```

5.4.2.3 Neuron::Neuron (int *Id*, VecCon *con*)

Definition at line 20 of file Neuron.cpp.

```

        :
        Id(Id), con(con), outputValue(0.0)
    {
    }

```

5.4.2.4 Neuron::~Neuron ()

Definition at line 25 of file Neuron.cpp.

```

{
}

```

5.4.3 Member Function Documentation

5.4.3.1 std::vector< int > Neuron::getConId ()

Definition at line 48 of file Neuron.cpp.

References `con`, and `VecCon::getId()`.

```

{
    return con.getId();
}

```

Here is the call graph for this function:




5.4.3.2 VecNeuron Neuron::getFrom ()

Definition at line 42 of file Neuron.cpp.

References con, and VecCon::getFrom().

```
{
    return con.getFrom();
}
```

Here is the call graph for this function:



5.4.3.3 int Neuron::getId ()


Definition at line 30 of file Neuron.cpp.

References Id.

Referenced by `show()`, and `validate()`.

```
{
    return Id;
}
```

Here is the caller graph for this function:



5.4.3.4 `std::vector< double > Neuron::getWeight ()`

Definition at line 54 of file Neuron.cpp.

References `con`, and `VecCon::getWeight()`.

```
{  
    return con.getWeight();  
}
```

Here is the call graph for this function:



5.4.3.5 `int Neuron::numOfCons ()`


Definition at line 72 of file Neuron.cpp.

References `con`, and `VecCon::numOfCons()`.

Referenced by `show()`.

```
{  
    return con.numOfCons();  
}
```

Here is the call graph for this function:



Here is the caller graph for this function:



5.4.3.6 `bool Neuron::setFrom (VecNeuron neuronContainer)`


Definition at line 60 of file `Neuron.cpp`.

References `con`, and `VecCon::setFrom()`.

```

{
    con.setFrom(neuronContainer);
}
  
```

Here is the call graph for this function:



5.4.3.7 `void Neuron::setId (int value)`

Definition at line 36 of file `Neuron.cpp`.

References `Id`.

```

{
    Id = value;
}
  
```

5.4.3.8 bool Neuron::setWeight (std::vector< double > nWeights)

Definition at line 66 of file Neuron.cpp.

References con, and VecCon::setWeight().

```
{
    con.setWeight (nWeights);
}
```

Here is the call graph for this function:




5.4.3.9 bool Neuron::show ()

Definition at line 78 of file Neuron.cpp.

References con, getId(), numOfCons(), and Container< T >::show().

```
{
    int id = getId();
    Rprintf("\n-----\n");
    if (id == NA_INTEGER)
    {
        Rprintf("\n Id: NA, Invalid neuron Id");
    }
    else
    {
        Rprintf("\n Id: %d", id);
    }
    Rprintf("\n-----\n");
    if (numOfCons() == 0)
    {
        Rprintf("\n No connections defined");
    }
    else
    {
        con.show();
    }
    Rprintf("\n-----\n");
    return true;
}
```


Here is the call graph for this function:



5.4.3.10 bool Neuron::validate ()

Definition at line 105 of file Neuron.cpp.

References con, getId(), and VecCon::validate().

```

{
    BEGIN_RCPP
    if (getId() == NA_INTEGER ) throw std::range_error("[C++ Neuron::validate]: Error, Id is NA.");
    con.validate();
    return (TRUE);
    END_RCPP
}
  
```

Here is the call graph for this function:



5.4.4 Member Data Documentation

5.4.4.1 VecCon Neuron::con [private]

A vector of input connections.

Definition at line 29 of file Neuron.h.

Referenced by getId(), getFrom(), getWeight(), numOfCons(), setFrom(), setWeight(), show(), and validate().

5.4.4.2 `int Neuron::Id` `[private]`

An integer variable with the [Neuron](#) Id.

The [Neuron](#) Id provides a name to the neuron. This value is not expected to be used neither during simulation nor training but it provides an easy reference for human readers.

Definition at line 22 of file [Neuron.h](#).

Referenced by [getId\(\)](#), and [setId\(\)](#).

5.4.4.3 `double Neuron::outputValue` `[private]`

Definition at line 30 of file [Neuron.h](#).

The documentation for this class was generated from the following files:


- [pkg/AMORE/src/Neuron.h](#)
- [pkg/AMORE/src/Neuron.cpp](#)

5.5 VecCon Class Reference


A vector of connections.

```
#include <VecCon.h>
```

Inheritance diagram for VecCon:



Collaboration diagram for VecCon:



Public Member Functions

- [VecCon](#) ()
- [VecCon](#) (std::vector< [ConPtr](#) > collection)
- int [numOfCons](#) ()
Size of the [VecCon](#) object.
- std::vector< int > [getId](#) ()
Getter of the Id values of the vector of Cons.
- bool [buildAndAppend](#) ([VecNeuron](#) neuronContainer, std::vector< double > nWeights)

Builds [Con](#) objects and appends them to collection.
- std::vector< double > [getWeight](#) ()
Getter of the weight field of the [Con](#) objects related to [VecCon](#).
- std::vector< double > [getWeight](#) (std::vector< int > nIds)
Getter of the weights of the specified elements from the [vecCom](#) object.
- [VecNeuron](#) [getFrom](#) ()
Getter of the from field of the [Con](#) objects related to [VecCon](#).
- bool [setWeight](#) (std::vector< double > nWeights)
Setter of the weight field of the [Con](#) objects related to [VecCon](#).
- bool [setWeight](#) (std::vector< double > nWeights, std::vector< int > nIds)
Setter of the weights of the specified elements from the [VecCon](#) object.
- bool [setFrom](#) ([VecNeuron](#) neuronContainer)
Setter of the from fields of the [Con](#) objects related to [VecCon](#).
- void [erase](#) (std::vector< int > nIds)
Erase the specified elements from the [vecCom](#) object.
- [VecConPtr](#) [select](#) (std::vector< int > nIds)
Selects the specified elements from the [vecCom](#) object.
- bool [validate](#) ()
Object validator.

5.5.1 Detailed Description

A vector of connections.

The [VecCon](#) class provides a simple class for a vector of connections. It's named after the R equivalent Reference Class.

Definition at line 16 of file [VecCon.h](#).

5.5.2 Constructor & Destructor Documentation

5.5.2.1 [VecCon::VecCon](#) ()

Definition at line 9 of file [VecCon.cpp](#).

```
{
}
```

5.5.2.2 VecCon::VecCon (std::vector< ConPtr > collection)

Definition at line 14 of file VecCon.cpp.

```

Container<Con> (collection)           :           // Call to Base constructor
{
}

```

5.5.3 Member Function Documentation

5.5.3.1 bool VecCon::buildAndAppend (VecNeuron neuronContainer, std::vector< double > nWeights)

Builds [Con](#) objects and appends them to collection.

This function provides a convenient way of populating a [VecCon](#) object by building and appending [Con](#) objects to collection.

Parameters

<i>FROM</i>	A vector of smart pointers to the neurons to be used in the Con::from fields
<i>WEIGHT</i>	A vector of values to be set in the Con::weight fields

```

//=====
//Usage example:
//=====
// Data set up
std::vector<int> result;
VecCon MyVecCon;
std::vector<NeuronPtr> vNeuron;
std::vector<double> vWeight;

// Test
NeuronPtr ptNeuron( new Neuron(11) );
vNeuron.push_back(ptNeuron);
ptNeuron.reset( new Neuron(22) );
vNeuron.push_back(ptNeuron);
ptNeuron.reset( new Neuron(33) );
vNeuron.push_back(ptNeuron);

vWeight.push_back(12.3);
vWeight.push_back(1.2);
vWeight.push_back(2.1);

MyVecCon.buildAndAppend(vNeuron, vWeight);

result=MyVecCon.getId();

// Now result is a vector that contains the values 11, 22 and 32.

```

See also

[append](#) and the unit test files, e.g. `runit.Cpp.VecCon.R`, for further examples.


Definition at line 146 of file VecCon.cpp.

References `Container< T >::empty()`, `Container< Con >::push_back()`, `Container< Con >::reserve()`, `Container< Con >::size()`, and `Container< T >::size()`.

```
{
  BEGIN_RCPP
  if (neuronContainer.empty())
  { throw std::range_error("[VecCon::BuildAndAppend]: Error, neuronContainer is
    empty"); }
  if (neuronContainer.size() != nWeights.size())
  {
    throw std::range_error(
      "[VecCon::buildAndAppend]: Error, neuronContainer.size() != nWeights.si
        ze()");
  }
  reserve(size() + neuronContainer.size());
  ConPtr ptCon;

  std::vector<double>::iterator itrWeight = nWeights.begin();
  foreach (NeuronPtr itrNeuron, neuronContainer)
  {
    ptCon.reset( new Con( itrNeuron, *itrWeight) );
    push_back(ptCon);
    itrWeight++;
  }
  return true;
END_RCPP}
```

Here is the call graph for this function:



5.5.3.2 void VecCon::erase (std::vector< int > nlds)

Erase the specified elements from the vecCom object.

Provides a convenient way of removing some [Con](#) objects from the collection field of the [VecCon](#) object.

Parameters

<i>vFrom</i>	An <code>std::vector<int></code> with the ids of the connections to remove.
--------------	---

```
//=====
//Usage example:
//=====

// Data set up
std::vector<int> result;
std::vector<NeuronPtr> vNeuron;
VecConPtr ptShvCon( new VecCon() );
VecConPtr vErased;
ConPtr ptC;
NeuronPtr ptN;
int ids[]= {11, 10, 9, 3, 4, 5, 6, 7, 8, 2, 1};
std::vector<double> vWeight;
vWeight.push_back(11.32);
vWeight.push_back(1.26);
vWeight.push_back(2.14);
vWeight.push_back(3.16);
vWeight.push_back(4.14);
vWeight.push_back(5.19);
vWeight.push_back(6.18);
vWeight.push_back(7.16);
vWeight.push_back(8.14);
vWeight.push_back(9.12);
vWeight.push_back(10.31);

for (int i=0; i<vWeight.size() ; i++) {
/ Let's create a vector with three neurons
    ptN.reset( new Neuron( ids[i] ) );
    vNeuron.push_back(ptN);
}
ptShvCon->buildAndAppend(vNeuron, vWeight);

// Test

std::vector<int> toRemove;
toRemove.push_back(1);
toRemove.push_back(3);
toRemove.push_back(5);
toRemove.push_back(7);

ptShvCon->erase(toRemove);
ptShvCon->show();
result=ptShvCon->getId();

// The output at the R terminal would display :
//
// From:      2      Weight=      9.120000
// From:      4      Weight=      4.140000
// From:      6      Weight=      6.180000
// From:      8      Weight=      8.140000
// From:      9      Weight=      2.140000
// From:     10 Weight=      1.260000
// From:     11 Weight=     11.320000
```


See also


[select](#) and the unit test files, e.g. `runit.Cpp.VecCon.R`, for further examples.

Definition at line 493 of file `VecCon.cpp`.

References `Container< Con >::begin()`, `Container< Con >::end()`, and `Container< Con >::resize()`.

```
{
    std::vector<ConPtr>::iterator itr;
    sort(begin(), end(), CompareId());
    sort(nIds.begin(), nIds.end());
    itr = set_difference(begin(), end(), nIds.begin(), nIds.end(), begin(),
        CompareId());
    resize(itr - begin());
}
```

Here is the call graph for this function:

**5.5.3.3 VecNeuron VecCon::getFrom ()**

Getter of the from field of the [Con](#) objects related to [VecCon](#).

This function provides a convenient way of getting the values of the weight field of those [Con](#) object pointed to by the smart pointer stored in the [VecCon](#) object.

Returns

An `std::vector<NeuronPtr>` with the pointer to the incoming neurons.

```
//=====
//Usage example:
//=====
// Data set up
```

```

std::vector<double> result;
int ids[] = {1, 2, 3};
double weights[] = {12.3, 1.2, 2.1 };
VecCon MyVecCon;
std::vector<NeuronPtr> vNeuron;
std::vector<double> vWeight;
NeuronPtr ptNeuron;

    for (int i=0; i<=2; i++) {
        ptNeuron.reset( new Neuron(ids[i]) );
        vNeuron.push_back(ptNeuron);
        vWeight.push_back(weights[i]);
    }
MyVecCon.buildAndAppend(vNeuron, vWeight);
// Test
vNeuron=MyVecCon.getFrom();
for (int i=0; i<=2; i++) {
    result.push_back(vNeuron.at(i)->getId());
}

// Now result is a vector that contains the values 1, 2 and 3 .

```

See also

[getId](#) and the unit test files, e.g. `runit.Cpp.VecCon.R`, for further examples.

Definition at line 321 of file `VecCon.cpp`.

References `numOfCons()`, `Container< T >::push_back()`, and `Container< T >::reserve()`.


Referenced by `Neuron::getFrom()`.

```

{
    VecNeuron result;
    result.reserve(numOfCons());
    foreach(ConPtr itr, *this)
    {
        result.push_back( itr->getFrom() );
    }
    return result;
}

```

Here is the call graph for this function:



Here is the caller graph for this function:



5.5.3.4 `std::vector< int > VecCon::getId ()`

Getter of the Id values of the vector of Cons.

This function returns the Id's of the neurons referred to by the vector of Cons.

Returns

An `std::vector<int>` that contains the Ids

```

//=====
//Usage example:
//=====
// Data set up
Neuron N1, N2, N3;
VecCon MyVecCon;
std::vector<int> result;

N1.setId(10);
N2.setId(20);
N3.setId(30);

ConPtr ptCon( new Con(&N1, 1.13) ); // Create new Con
and initialize ptCon
MyVecCon.push_back(ptCon);          /
/ push_back
ptCon.reset( new Con(&N2, 2.22) ); // create
new Con and assign to ptCon
MyVecCon.push_back(ptCon);          /
/ push_back
ptCon.reset( new Con(&N3, 3.33) ); // create
new Con and assign to ptCon
MyVecCon.push_back(ptCon);          /
/ push_back

// Test
MyVecCon.show() ;
MyVecCon.validate();
result=MyVecCon.getId();

// Now result is a vector that contains the values 10, 20 and 30.
  
```

See also

[getWeight](#) and the unit test files, e.g. `runit.Cpp.VecCon.R`, for further examples.


Definition at line 95 of file VecCon.cpp.

References numOfCons().


Referenced by Neuron::getConId(), and validate().

```
{
    std::vector<int> result;
    result.reserve(numOfCons());
    foreach (ConPtr itr, *this)
    {
        result.push_back(itr->getId());
    }
    return result;
}
```

Here is the call graph for this function:



Here is the caller graph for this function:



5.5.3.5 `std::vector< double > VecCon::getWeight ()`

Getter of the weight field of the [Con](#) objects related to [VecCon](#).

This function provides a convenient way of getting the values of the weight field of those [Con](#) object pointed to by the smart pointer stored in the [VecCon](#) object.

Returns

A numeric (double) vector with the weights

```
//=====
//Usage example:
//=====
// Data set up
std::vector<double> result;
VecCon MyVecCon;
std::vector<NeuronPtr> vNeuron;
std::vector<double> vWeight;

// Test
NeuronPtr ptNeuron( new Neuron(11) );
vNeuron.push_back(ptNeuron);
ptNeuron.reset( new Neuron(22) );
vNeuron.push_back(ptNeuron);
ptNeuron.reset( new Neuron(33) );
vNeuron.push_back(ptNeuron);

vWeight.push_back(12.3);
vWeight.push_back(1.2);
vWeight.push_back(2.1);

MyVecCon.buildAndAppend(vNeuron, vWeight);

result=MyVecCon.getWeight();

// Now result is a vector that contains the values 12.3, 1.2 and 2.1 .
```

See also

[getld](#) and the unit test files, e.g. `runit.Cpp.VecCon.R`, for further examples.

Definition at line 209 of file `VecCon.cpp`.


References `numOfCons()`.

Referenced by `Neuron::getWeight()`.

```
{
    std::vector<double> result;
    result.reserve(numOfCons());
    foreach (ConPtr itr, *this)
    {
        result.push_back( itr->getWeight() );
    }

    return result;
}
```

Here is the call graph for this function:



Here is the caller graph for this function:



5.5.3.6 `std::vector< double > VecCon::getWeight (std::vector< int > nlds)`

Getter of the weights of the specified elements from the vecCom object.

Provides a convenient way of getting the weights of some [Con](#) objects from the collection field of the [VecCon](#) object.

Parameters

<i>vFrom</i>	An <code>std::vector<int></code> with the lds of the connections to select
--------------	--

Returns

An `std::vector<double>` with the weights of the selected connections

```

//=====
//Usage example:
//=====

// Data set up

    std::vector<double> result;
    std::vector<NeuronPtr> vNeuron;
    VecConPtr          ptShvCon( new VecCon() );
    ConPtr  ptC;
    NeuronPtr ptN;
    int ids[]= {11, 10, 9, 3, 4, 5, 6, 7, 8, 2, 1};
    double weights[]={11.32, 1.26, 2.14, 3.16, 4.14, 5.19, 6.18, 7.16
, 8.14, 9.12, 10.31};
    std::vector<double> vWeight;
    for (int i=0; i<11; i++) {
        vWeight.push_back(weights[i]);
    }
    for (int i=0; i<vWeight.size() ; i++) {
/
/ Let's create a vector with three neurons
        ptN.reset( new Neuron( ids[i] ) );
        vNeuron.push_back(ptN);
    }
    ptShvCon->buildAndAppend(vNeuron, vWeight);

// Test
    std::vector<int> toSelect;
    toSelect.push_back(1);
  
```

```

        toSelect.push_back(3);
        toSelect.push_back(5);
        toSelect.push_back(7);

        result=ptShvCon->getWeight(toSelect);

        // Now, result is a numeric vector with the values 10.31, 3.16, 5.19 and
        // 7.16.

```

See also

setWeigh and the unit test files, e.g. runit.Cpp.VecCon.R, for further examples.

Definition at line 609 of file VecCon.cpp.


References `select()`.

```

{
    return select(nIds)->getWeight();
}

```

Here is the call graph for this function:

**5.5.3.7 int VecCon::numOfCons ()**

Size of the [VecCon](#) object.

This function returns the size of the [VecCon](#) object, that is to say, the number of [Con](#) objects it contains.

Returns

The size of the vector

```

//=====
//Usage example:
//=====

```

```

// Data set up
std::vector<int> result;
std::vector<ConPtr> vcA, vcB;
ContainerNeuronPtr ptShvNeuron( new
Container<Neuron>() );
VecConPtr ptShvCon( new VecCon() );
ConPtr ptC;
NeuronPtr ptN;
int ids[] = {10, 20, 30};
double weights[] = {1.13, 2.22, 3.33 };
for (int i=0; i<=2 ; i++) {
/ Let's create a vector with three neurons
ptN.reset( new Neuron( ids[i] ) );
ptShvNeuron->push_back(ptN);
}
// Test
for (int i=0; i<=2 ; i++) {
/ and a vector with three connections
result.push_back(ptShvCon->numOfCons());
/ Append numOfCons to result, create new Con and push_back into MyVecCon
ptC.reset( new Con( ptShvNeuron->load().a
t(i), weights[i]) );
ptShvCon->push_back(ptC);
}

// Now, result contains a numeric vector with values 0, 1, 2, and 3.

```

See also

[Container::size](#) (alias)

Definition at line 54 of file VecCon.cpp.

References `Container< Con >::size()`.

Referenced by `getFrom()`, `getId()`, `getWeight()`, and `Neuron::numOfCons()`.

```


{
    return size();
}

```

Here is the call graph for this function:



Here is the caller graph for this function:



5.5.3.8 VecConPtr VecCon::select (std::vector< int > nlds)

Selects the specified elements from the vecCom object.

Provides a convenient way of selecting some [Con](#) objects from the collection field of the [VecCon](#) object.

Parameters

<i>vFrom</i>	An std::vector<int> with the ids of the connections to select.
--------------	--

```

//=====
//Usage example:
//=====

// Data set up
std::vector<int> result;
std::vector<NeuronPtr> vNeuron;
VecConPtr      ptShvCon( new VecCon() );
ConPtr  ptC;
NeuronPtr ptN;
int ids[]= {11, 10, 9, 3, 4, 5, 6, 7, 8, 2, 1};
double weights[]={11.32, 1.26, 2.14, 3.16, 4.14, 5.19, 6.18, 7.16
, 8.14, 9.12, 10.31};
std::vector<double> vWeight;
for (int i=0; i<11; i++) {
    vWeight.push_back(weights[i]);
}
for (int i=0; i<vWeight.size() ; i++) {
    /
/ Let's create a vector with three neurons
    ptN.reset( new Neuron( ids[i] ) );
    vNeuron.push_back(ptN);
}
ptShvCon->buildAndAppend(vNeuron, vWeight);
// Test
std::vector<int> toSelect;
  
```

```

toSelect.push_back(1);
toSelect.push_back(3);
toSelect.push_back(5);
toSelect.push_back(7);

VecConPtr vSelect ( ptShvCon->select(toSelect) );
result=vSelect->getId();

// Now, result is a numeric vector with the values 1, 3, 5 and 7.

```

See also

[erase](#) and the unit test files, e.g. `runit.Cpp.VecCon.R`, for further examples.

Definition at line 548 of file `VecCon.cpp`.

References `Container< Con >::begin()`, `Container< Con >::end()`, and `Container< Con >::size()`.

Referenced by `getWeight()`, and `setWeight()`.


```

{
  VecConPtr result(new VecCon);
  result->reserve(size());
  sort(begin(), end(), CompareId());
  sort(nIds.begin(), nIds.end());
  set_intersection(begin(), end(), nIds.begin(), nIds.end(),
    back_inserter(result->collection), CompareId());


  return result;
}

```

Here is the call graph for this function:



Here is the caller graph for this function:



5.5.3.9 bool VecCon::setFrom (VecNeuron neuronContainer)

Setter of the from fields of the [Con](#) objects related to [VecCon](#).

This function provides a convenient way of getting the values of the weight field of those [Con](#) object pointed to by the smart pointer stored in the [VecCon](#) object.

Parameters

<i>vFrom</i>	An <code>std::vector<NeuronPtr></code> with the pointers to be set in the from fields of the VecCon object.
--------------	---

Returns

true if not exception is thrown

```

//=====
//Usage example:
//=====

// Data set up
std::vector<int> result;
ContainerNeuronPtr ptShvNeuron( new Container<Neuron>() );
VecConPtr ptShvCon( new VecCon() );
ConPtr ptC;
NeuronPtr ptN;

int ids[] = {10, 20, 30};
double weights[] = {1.13, 2.22, 3.33 };

for (int i=0; i<=2 ; i++) { // Let's
create a vector with three neurons
    ptN.reset( new Neuron( ids[i] ) );
    ptShvNeuron->push_back( ptN );
}
for (int i=0; i<=2 ; i++) { // and a
vector with three connections
    ptC.reset( new Con() );
    ptShvCon->push_back( ptC );
}
  
```

```

    }
    // Test
    ptShvCon->setFrom(ptShvNeuron->load()) ;
    ptShvCon->show();
    result=ptShvCon->getId();

    // Now result is a vector that contains the values 10, 20 and 30.

```

See also

[getFrom](#) and the unit test files, e.g. `runit.Cpp.VecCon.R`, for further examples.

Definition at line 376 of file `VecCon.cpp`.

References `Container< T >::begin()`, `Container< T >::empty()`, `Container< Con >::size()`, and `Container< T >::size()`.


Referenced by `Neuron::setFrom()`.

```

{
    BEGIN_RCPP
    if (neuronContainer.empty())
    { throw std::range_error("[ C++ VecCon::setFrom]: Error, w is empty");}
    if (neuronContainer.size() != size())
    {
        throw std::range_error(
            "[C++ VecCon::setFrom]: Error, neuronContainer.size() != collection.size()");
    }
    std::vector<NeuronPtr>::iterator itrNeuron = neuronContainer.begin();
    foreach(ConPtr itr , *this)
    {
        itr->setFrom( *itrNeuron );
        itrNeuron++;
    }
    return true;
    END_RCPP
}

```

Here is the call graph for this function:



Here is the caller graph for this function:



5.5.3.10 bool VecCon::setWeight (std::vector< double > *nWeights*, std::vector< int > *nIds*)

Setter of the weights of the specified elements from the [VecCon](#) object.

Provides a convenient way of setting the weights of some [Con](#) objects from the collection field of the [VecCon](#) object.

Parameters

<i>vWeight</i>	A numeric (double) vector with the weights to be set in the Con objects contained in the VecCon object.
<i>vFrom</i>	An std::vector<int> with the ids of the connections to select

Returns

true in case no exception is thrown

```

//=====
//Usage example:
//=====

// Data set up
std::vector<double> result;
std::vector<NeuronPtr> vNeuron;
VecConPtr ptShvCon( new VecCon() );
ConPtr ptC;
NeuronPtr ptN;
int ids[]= {11, 10, 9, 3, 4, 5, 6, 7, 8, 2, 1};
double weights[]={11.32, 1.26, 2.14, 3.16, 4.14, 5.19, 6.
18, 7.16, 8.14, 9.12, 10.31};
std::vector<double> vWeight;
for (int i=0; i<11; i++) {
    vWeight.push_back(weights[i]);
}
for (int i=0; i<vWeight.size() ; i++) {
    /
/ Let's create a vector with three neurons
    ptN.reset( new Neuron( ids[i] ) );
    vNeuron.push_back(ptN);
}
ptShvCon->buildAndAppend(vNeuron, vWeight);

std::vector<int> toSelect;
  
```

```

std::vector<double> vNewWeights;
toSelect.push_back(1);
toSelect.push_back(3);
toSelect.push_back(5);
toSelect.push_back(7);
vNewWeights.push_back(1000.1);
vNewWeights.push_back(3000.3);
vNewWeights.push_back(5000.5);
vNewWeights.push_back(7000.7);
ptShvCon->setWeight(vNewWeights, toSelect);

// Test

result = ptShvCon->getWeight();
return wrap(result);

// Now, result is a numeric vector with the values 1000.10, 9.12, 3000.3
0, 4.14, 5000.50, 6.18, 7000.70, 8.14, 2.14, 1.26 and 11.32 .

```

See also

getWeigth and the unit test files, e.g. runit.Cpp.VecCon.R, for further examples.

Definition at line 670 of file VecCon.cpp.


References `select()`.

```

{
BEGIN_RCPP
return select(nIds)->setWeight(nWeights);
END_RCPP
}

```

Here is the call graph for this function:



5.5.3.11 bool VecCon::setWeight (std::vector< double > nWeights)

Setter of the weight field of the [Con](#) objects related to [VecCon](#).

This function provides a convenient way of setting the values of the weight field of those [Con](#) objects pointed to by the smart pointer stored in the [VecCon](#) object.

Parameters

vWeight	A numeric (double) vector with the weights to be set in the Con objects contained in the VecCon object.
----------------	---

Returns

true in case no exception is thrown

```
//=====
//Usage example:
//=====
// Data set up
    std::vector<double> result;
    int ids[] = {1, 2, 3};
    double weights[] = {12.3, 1.2, 2.1 };
    VecCon MyVecCon;
    std::vector<NeuronPtr> vNeuron;
    std::vector<double> vWeight;
    NeuronPtr ptNeuron;

    for (int i=0; i<=2; i++) {
        ptNeuron.reset( new Neuron(ids[i]) );
        vNeuron.push_back(ptNeuron);
        vWeight.push_back(0);
    }
    / weights are set to 0
    MyVecCon.buildAndAppend(vNeuron, vWeight);
    MyVecCon.show();

    for (int i=0; i<=2; i++) {
        vWeight.at(i)=weights[i];
    }

    // Test
    MyVecCon.setWeight(vWeight);
    s are set to 12.3, 1.2 and 2.1
    result=MyVecCon.getWeight();

    // Now result is a vector that contains the values 12.3, 1.2 and 2.1 .
```

See also

[getWeight](#) and the unit test files, e.g. `runit.Cpp.VecCon.R`, for further examples.

Definition at line 264 of file `VecCon.cpp`.

References `Container< Con >::size()`.

Referenced by `Neuron::setWeight()`.

```
{
    BEGIN_RCPP
    if (nWeights.empty())
    { throw std::range_error("[ C++ VecCon::setWeight]: Error, vWeight is empty")
    ;}
    if (nWeights.size() != size())
    {
        throw std::range_error(
            "[C++ VecCon::setWeight]: Error, vWeight.size() != collection.size()");
    }
}
```

```

std::vector<double>::iterator itrWeight = nWeights.begin();
foreach (ConPtr itr, *this)
{
    itr->setWeight( *itrWeight );
    itrWeight++;
}
return true;
END_RCPP}

```

Here is the call graph for this function:



Here is the caller graph for this function:



5.5.3.12 bool VecCon::validate ()

Object validator.

This method checks the object for internal coherence. A try / catch mechanism exits normal execution and returns control to the R terminal in case the contents of the `VecCon` object are identified as corrupted.

Returns

true in case the checks are Ok.

Exceptions

An	std::range error if weight or from are not finite.
----	--

See also

The unit test files, e.g., `runit.Cpp.VecCon.R`, for usage examples.

Reimplemented from [Container< Con >](#).

Definition at line 689 of file `VecCon.cpp`.

References `getId()`.

Referenced by `Neuron::validate()`.

```
{
    BEGIN_RCPP

    std::vector<int>::iterator itr;
    std::vector<int> vIds = getId();
    sort(vIds.begin(), vIds.end());
    itr = adjacent_find(vIds.begin(), vIds.end());
    if (itr != vIds.end())
        throw std::range_error("[C++ VecCon::validate]: Error, duplicated Id.");
    Container<Con>::validate();
    return (true);
END_RCPP};
```

Here is the call graph for this function:



Here is the caller graph for this function:



The documentation for this class was generated from the following files:

- `pkg/AMORE/src/VecCon.h`
- `pkg/AMORE/src/VecCon.cpp`

5.6 vecMLPneuron Class Reference

A vector of connections.

```
#include <VecMLPneuron.h>
```

Public Member Functions

- `std::vector< int > getId ()`
- `bool buildAndAppend (std::vector< int > IDS, std::vector< int > BIAS, VecCon VC)`

5.6.1 Detailed Description

A vector of connections.

The [VecCon](#) class provides a simple class for a vector of connections. It's named after the R equivalent Reference Class.

Definition at line 16 of file `VecMLPneuron.h`.

5.6.2 Member Function Documentation

5.6.2.1 `bool vecMLPneuron::buildAndAppend (std::vector< int > IDS, std::vector< int > BIAS, VecCon VC)`

5.6.2.2 `std::vector<int> vecMLPneuron::getId ()`

The documentation for this class was generated from the following file:


- `pkg/AMORE/src/VecMLPneuron.h`

5.7 VecNeuron Class Reference


A vector of neurons.

```
#include <VecNeuron.h>
```

Inheritance diagram for VecNeuron:



Collaboration diagram for VecNeuron:



Public Member Functions

- [VecNeuron](#) ()
- [VecNeuron](#) (std::vector< [NeuronPtr](#) > vNeuron)
- [~VecNeuron](#) ()
- int [numOfNeurons](#) ()
- std::vector< int > [getId](#) ()

5.7.1 Detailed Description

A vector of neurons.

The vecNeuron class provides a simple class for a vector of neurons. It's named after the R equivalent Reference Class.

Definition at line 17 of file VecNeuron.h.

5.7.2 Constructor & Destructor Documentation

5.7.2.1 VecNeuron::VecNeuron ()

Definition at line 8 of file VecNeuron.cpp.

```
{  
}
```

5.7.2.2 VecNeuron::VecNeuron (std::vector< NeuronPtr > vNeuron)

Definition at line 12 of file VecNeuron.cpp.

```
Container<Neuron>(collection)                                     :  
{  
}
```

5.7.2.3 VecNeuron::~VecNeuron ()

Definition at line 17 of file VecNeuron.cpp.

```
{  
}
```

5.7.3 Member Function Documentation

5.7.3.1 `std::vector< int > VecNeuron::getId ()`

Definition at line 28 of file VecNeuron.cpp.

```
{
    std::vector<int> nIds;
    foreach(NeuronPtr itrNeuron, *this){
        nIds.push_back( itrNeuron->getId() );
    }
    return nIds;
}
```

5.7.3.2 `int VecNeuron::numOfNeurons ()`

Definition at line 22 of file VecNeuron.cpp.

References `Container< Neuron >::size()`.

```
{
    size();
}
```

Here is the call graph for this function:



The documentation for this class was generated from the following files:

- pkg/AMORE/src/[VecNeuron.h](#)
- pkg/AMORE/src/[VecNeuron.cpp](#)


Chapter 6

File Documentation

6.1 pkg/AMORE/src/AMORE.h File Reference

```
#include <iostream>
#include <sstream>
#include <algorithm>
#include <vector>
#include <iterator>
#include <boost/shared_ptr.hpp>
#include <boost/weak_ptr.hpp>
#include <boost/foreach.hpp>
#include <Rcpp.h>
#include "Con.h"
#include "Container.h"
#include "VecCon.h"
#include "Neuron.h"
#include "VecNeuron.h"
#include "Con.cpp"
#include "Container.cpp"
#include "VecCon.cpp"
#include "Neuron.cpp"
#include "VecNeuron.cpp"
```

Include dependency graph for AMORE.h:



Defines

- #define [foreach](#) BOOST_FOREACH
- #define [size_type](#) unsigned int

Typedefs

- typedef boost::shared_ptr< [Con](#) > [ConPtr](#)
- typedef boost::shared_ptr< [Neuron](#) > [NeuronPtr](#)
- typedef boost::weak_ptr< [Neuron](#) > [NeuronWeakPtr](#)
- typedef boost::shared_ptr< [Container](#)< [Con](#) > > [ContainerConPtr](#)
- typedef boost::shared_ptr< [Container](#)< [Neuron](#) > > [ContainerNeuronPtr](#)
- typedef boost::shared_ptr< [VecCon](#) > [VecConPtr](#)
- typedef boost::shared_ptr< [VecNeuron](#) > [VecNeuronPtr](#)

6.1.1 Define Documentation

6.1.1.1 #define foreach BOOST_FOREACH

Definition at line 37 of file AMORE.h.

6.1.1.2 #define size_type unsigned int

Definition at line 40 of file AMORE.h.

6.1.2 Typedef Documentation

6.1.2.1 typedef boost::shared_ptr<Con> ConPtr

Definition at line 43 of file AMORE.h.

6.1.2.2 typedef boost::shared_ptr<Container<Con> > ContainerConPtr

Definition at line 46 of file AMORE.h.

6.1.2.3 `typedef boost::shared_ptr<Container<Neuron> > ContainerNeuronPtr`

Definition at line 47 of file AMORE.h.

6.1.2.4 `typedef boost::shared_ptr<Neuron> NeuronPtr`

Definition at line 44 of file AMORE.h.

6.1.2.5 `typedef boost::weak_ptr<Neuron> NeuronWeakPtr`

Definition at line 45 of file AMORE.h.

6.1.2.6 `typedef boost::shared_ptr<VecCon> VecConPtr`

Definition at line 48 of file AMORE.h.


6.1.2.7 `typedef boost::shared_ptr<VecNeuron> VecNeuronPtr`

Definition at line 49 of file AMORE.h.


6.2 pkg/AMORE/src/Con.cpp File Reference

```
#include "Con.h"
```

Include dependency graph for Con.cpp:




This graph shows which files directly or indirectly include this file:



6.3 pkg/AMORE/src/Con.h File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [Con](#)

A class to handle the information needed to describe an input connection.


6.4 pkg/AMORE/src/Container.cpp File Reference

This graph shows which files directly or indirectly include this file:



6.5 pkg/AMORE/src/Container.h File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class `Container< T >`


6.6 pkg/AMORE/src/Neuron.cpp File Reference

```
#include "Neuron.h"
```

Include dependency graph for Neuron.cpp:




This graph shows which files directly or indirectly include this file:



6.7 pkg/AMORE/src/Neuron.h File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class `Neuron`

A class to handle the information contained in a general `Neuron`.

6.8 pkg/AMORE/src/VecCon.cpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- struct [CompareId](#)

6.9 pkg/AMORE/src/VecCon.h File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [VecCon](#)

A vector of connections.

6.10 pkg/AMORE/src/VecMLPneuron.h File Reference


Classes

- class [vecMLPneuron](#)

A vector of connections.


6.11 pkg/AMORE/src/VecNeuron.cpp File Reference

This graph shows which files directly or indirectly include this file:



6.12 pkg/AMORE/src/VecNeuron.h File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [VecNeuron](#)
A vector of neurons.

Index

- ~Con
 - Con, [12](#)
- ~Neuron
 - Neuron, [36](#)
- ~VecNeuron
 - VecNeuron, [69](#)
- AMORE.h
 - ConPtr, [72](#)
 - ContainerConPtr, [72](#)
 - ContainerNeuronPtr, [72](#)
 - foreach, [72](#)
 - NeuronPtr, [73](#)
 - NeuronWeakPtr, [73](#)
 - size_type, [72](#)
 - VecConPtr, [73](#)
 - VecNeuronPtr, [73](#)
- append
 - Container, [23](#)
- begin
 - Container, [25](#)
- buildAndAppend
 - VecCon, [46](#)
 - vecMLPneuron, [66](#)
- collection
 - Container, [33](#)
- CompareId, [9](#)
 - operator(), [9](#), [10](#)
- Con, [10](#)
 - ~Con, [12](#)
 - Con, [11](#)
 - from, [18](#)
 - getFrom, [12](#)
 - getId, [13](#)
 - getWeight, [14](#)
 - setFrom, [15](#)
 - setWeight, [15](#)
 - show, [16](#)
 - validate, [17](#)
 - weight, [18](#)
- con
 - Neuron, [41](#)
- ConPtr
 - AMORE.h, [72](#)
- const_iterator
 - Container, [23](#)
- Container, [19](#)
 - append, [23](#)
 - begin, [25](#)
 - collection, [33](#)
 - const_iterator, [23](#)
 - Container, [23](#)
 - empty, [25](#)
 - end, [26](#)
 - iterator, [23](#)
 - load, [26](#)
 - push_back, [28](#)
 - reserve, [29](#)
 - resize, [29](#)
 - show, [29](#)
 - size, [31](#)
 - store, [32](#)
 - validate, [32](#)
- ContainerConPtr
 - AMORE.h, [72](#)
- ContainerNeuronPtr
 - AMORE.h, [72](#)
- empty
 - Container, [25](#)
- end
 - Container, [26](#)
- erase
 - VecCon, [47](#)
- foreach
 - AMORE.h, [72](#)
- from
 - Con, [18](#)
- getConId

- Neuron, [36](#)
- getFrom
 - Con, [12](#)
 - Neuron, [36](#)
 - VecCon, [49](#)
- getId
 - Con, [13](#)
 - Neuron, [37](#)
 - VecCon, [51](#)
 - vecMLPNeuron, [66](#)
 - VecNeuron, [70](#)
- getWeight
 - Con, [14](#)
 - Neuron, [37](#)
 - VecCon, [52](#), [54](#)
- Id
 - Neuron, [41](#)
- iterator
 - Container, [23](#)
- load
 - Container, [26](#)
- Neuron, [33](#)
 - ~Neuron, [36](#)
 - con, [41](#)
 - getConId, [36](#)
 - getFrom, [36](#)
 - getId, [37](#)
 - getWeight, [37](#)
 - Id, [41](#)
 - Neuron, [35](#), [36](#)
 - numOfCons, [38](#)
 - outputValue, [42](#)
 - setFrom, [39](#)
 - setId, [39](#)
 - setWeight, [39](#)
 - show, [40](#)
 - validate, [41](#)
- NeuronPtr
 - AMORE.h, [73](#)
- NeuronWeakPtr
 - AMORE.h, [73](#)
- numOfCons
 - Neuron, [38](#)
 - VecCon, [55](#)
- numOfNeurons
 - VecNeuron, [70](#)
- operator()
 - CompareId, [9](#), [10](#)
 - outputValue
 - Neuron, [42](#)
 - pkg/AMORE/src/AMORE.h, [71](#)
 - pkg/AMORE/src/Con.cpp, [73](#)
 - pkg/AMORE/src/Con.h, [74](#)
 - pkg/AMORE/src/Container.cpp, [75](#)
 - pkg/AMORE/src/Container.h, [75](#)
 - pkg/AMORE/src/Neuron.cpp, [75](#)
 - pkg/AMORE/src/Neuron.h, [77](#)
 - pkg/AMORE/src/VecCon.cpp, [77](#)
 - pkg/AMORE/src/VecCon.h, [78](#)
 - pkg/AMORE/src/VecMLPNeuron.h, [78](#)
 - pkg/AMORE/src/VecNeuron.cpp, [79](#)
 - pkg/AMORE/src/VecNeuron.h, [79](#)
 - push_back
 - Container, [28](#)
 - reserve
 - Container, [29](#)
 - resize
 - Container, [29](#)
 - select
 - VecCon, [57](#)
 - setFrom
 - Con, [15](#)
 - Neuron, [39](#)
 - VecCon, [59](#)
 - setId
 - Neuron, [39](#)
 - setWeight
 - Con, [15](#)
 - Neuron, [39](#)
 - VecCon, [61](#), [62](#)
 - show
 - Con, [16](#)
 - Container, [29](#)
 - Neuron, [40](#)
 - size
 - Container, [31](#)
 - size_type
 - AMORE.h, [72](#)
 - store
 - Container, [32](#)
 - validate
 - Con, [17](#)
 - Container, [32](#)

- Neuron, [41](#)
- VecCon, [64](#)
- VecCon, [42](#)
 - buildAndAppend, [46](#)
 - erase, [47](#)
 - getFrom, [49](#)
 - getId, [51](#)
 - getWeight, [52](#), [54](#)
 - numOfCons, [55](#)
 - select, [57](#)
 - setFrom, [59](#)
 - setWeight, [61](#), [62](#)
 - validate, [64](#)
 - VecCon, [45](#)
- VecConPtr
 - AMORE.h, [73](#)
- vecMLPneuron, [66](#)
 - buildAndAppend, [66](#)
 - getId, [66](#)
- VecNeuron, [66](#)
 - ~VecNeuron, [69](#)
 - getId, [70](#)
 - numOfNeurons, [70](#)
 - VecNeuron, [69](#)
- VecNeuronPtr
 - AMORE.h, [73](#)
- weight
 - Con, [18](#)