

# dcConverter

July 23, 2015

---

dcConverter	<i>Function to convert an object between graph classes</i>
-------------	--

---

## Description

dcConverter is supposed to convert an object between classes 'Onto' and 'igraph', or between 'Dnetwork' and 'igraph', or between 'Cnetwork' and 'igraph'.

## Usage

```
dcConverter(obj, from = c("Onto", "igraph", "Dnetwork", "Cnetwork"),  
to = c("igraph", "Onto", "Dnetwork", "Cnetwork"), verbose = TRUE)
```

## Arguments

obj	an object of class "Onto", "igraph", "Dnetwork" or "Cnetwork"
from	a character specifying the class converted from. It can be one of "Onto", "igraph", "Dnetwork" and "Dnetwork"
to	a character specifying the class converted to. It can be one of "Onto", "igraph", "Dnetwork" and "Dnetwork"
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

## Value

an object of class "Onto", "igraph", "Dnetwork" or "Cnetwork"

## Note

Conversion is also supported between classes 'Onto' and 'igraph', or between 'Dnetwork' and 'igraph', or between 'Cnetwork' and 'igraph'

## See Also

[dcRDataLoader](#), [Onto-class](#), [Dnetwork-class](#), [Cnetwork-class](#)

## Examples

```
## Not run:
# 1) conversion between 'Onto' and 'igraph'
# 1a) load onto.GOMF (as 'Onto' object)
on <- dcRDataLoader('onto.GOMF')
on
# 1b) convert the object from 'Onto' to 'igraph' class
ig <- dcConverter(on, from='Onto', to='igraph')
ig
# 1c) convert the object from 'igraph' to 'Onto' class
dcConverter(ig, from='igraph', to='Onto')

# 2) conversion between 'Dnetwork' and 'igraph'
# 2a) computer a domain semantic network (as 'Dnetwork' object)
g <- dcRDataLoader('onto.GOMF')
Anno <- dcRDataLoader('SCOP.sf2GOMF')
dag <- dcDAGannotate(g, annotations=Anno, path.mode="shortest_paths",
verbose=FALSE)
alldomains <- unique(unlist(nInfo(dag)$annotations))
domains <- sample(alldomains,5) # randomly sample 5 domains
dnetwork <- dcDAGdomainSim(g=dag, domains=domains,
method.domain="BM.average", method.term="Resnik", parallel=FALSE,
verbose=FALSE)
dnetwork
# 2b) convert the object from 'Dnetwork' to 'igraph' class
ig <- dcConverter(dnetwork, from='Dnetwork', to='igraph')
ig
# 2c) convert the object from 'igraph' to 'Dnetwork' class
dcConverter(ig, from='igraph', to='Dnetwork')

## End(Not run)
```