

dcBuildInfoDataFrame

December 22, 2014

dcBuildInfoDataFrame	<i>Function to build an object of the S4 class InfoDataframe from an input file</i>
----------------------	---

Description

dcBuildInfoDataFrame is supposed to build an object of the S4 class [InfoDataFrame](#), given an input file. This input file can, for example, contain the domain information.

Usage

```
dcBuildInfoDataFrame(input.file, output.file = "InfoDataFrame.RData")
```

Arguments

input.file	an input file used to build the object. For example, a file containing InterPro domains (InterPro) can be found in http://dcbior.r-forge.r-project.org/data/InterPro/InterPro.txt . As seen in this example, the input file must contain the header (in the first row), and entries in the first column intend to be domain identities (and must be unique). Note: the file should use the tab delimiter as the field separator between columns
output.file	an output file used to save the built object as an RData-formatted file. If NULL, this file will be saved into "InfoDataFrame.RData" in the current working local directory

Value

Any use-specified variable that is given on the right side of the assignment sign '<-', which contains the built dcBuildInfoDataFrame object. Also, an RData file specified in "output.file" is saved in the local directory.

Note

If there are no use-specified variable that is given on the right side of the assignment sign '<-', then no object will be loaded onto the working environment.

See Also

[InfoDataFrame](#)

Examples

```
# build an "InfoDataFrame" object that contains information on InterPro domains (InterPro)
InterPro <-
dcBuildInfoDataFrame(input.file="http://dcgor.r-forge.r-project.org/data/InterPro/InterPro.txt",
output.file="InterPro.RData")
InterPro
```