

AN INTRODUCTION TO THE FLCORE PACKAGE

FLR Core Team

November 30, 2010



OUTLINE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

INTRODUCTION

OUTLINE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

INTRODUCTION

BASIC CLASSES

OUTLINE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

INTRODUCTION

BASIC CLASSES

COMPOSITE CLASSES

OUTLINE

INTRODUCTION
TO FLCore

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

INTRODUCTION

BASIC CLASSES

COMPOSITE CLASSES

LIST CLASSES

OUTLINE

INTRODUCTION
TO FLCore

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

INTRODUCTION

BASIC CLASSES

COMPOSITE CLASSES

LIST CLASSES

MODEL CLASSES

FLCORE STRUCTURE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

Follows S4 paradigm with structured data implemented as classes and several methods to apply on objects of the classes.

FLCORE STRUCTURE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

Follows S4 paradigm with structured data implemented as classes and several methods to apply on objects of the classes.

- ▶ Classes - empty definitions of data

FLCORE STRUCTURE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

Follows S4 paradigm with structured data implemented as classes and several methods to apply on objects of the classes.

- ▶ Classes - empty definitions of data
- ▶ Objects - instances of the classes which have data following the class definition

FLCORE STRUCTURE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

Follows S4 paradigm with structured data implemented as classes and several methods to apply on objects of the classes.

- ▶ Classes - empty definitions of data
- ▶ Objects - instances of the classes which have data following the class definition
- ▶ Methods - implementation of actions to be executed on objects depending on its class

INSIDE FLCORE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

INSIDE FLCORE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Basic classes:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar

INSIDE FLCORE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Basic classes:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar
- ▶ Composite classes:
FLComp, FLBiol, FLCatch, FLFleet, FLIndex, FLMetier,
FLModel, FLStock

INSIDE FLCORE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Basic classes:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar
- ▶ Composite classes:
FLComp, FLBiol, FLCatch, FLFleet, FLIndex, FLMetier, FLModel, FLStock
- ▶ Lists of classes:
FLLst, FLBiols, FLCatches, FLCohorts, FLFleets, FLIndices, FLMetiers, FLQuants, FLStocks

INSIDE FLCORE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Basic classes:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar
- ▶ Composite classes:
FLComp, FLBiol, FLCatch, FLFleet, FLIndex, FLMetier, FLModel, FLStock
- ▶ Lists of classes:
FLLst, FLBiols, FLCatches, FLCohorts, FLFleets, FLIndices, FLMetiers, FLQuants, FLStocks
- ▶ Model class:
FLModel, FLGrowth, FL SR

INSIDE FLCORE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Basic classes:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar
- ▶ Composite classes:
FLComp, FLBiol, FLCatch, FLFleet, FLIndex, FLMetier, FLModel, FLStock
- ▶ Lists of classes:
FLLst, FLBiols, FLCatches, FLCohorts, FLFleets, FLIndices, FLMetiers, FLQuants, FLStocks
- ▶ Model class:
FLModel, FLGrowth, FL SR
- ▶ Methods

BASIC CLASSES

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

	parent	nSlots	virtual	child	distance
FLCohort	FLArray	2	FALSE		
FLQuant	FLArray	2	FALSE	FLQuantPoint	1.00
FLQuantPoint	FLQuant	2	FALSE		

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

1. User defined (age, length etc.)

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

1. User defined (age, length etc.)
2. Year

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

1. User defined (age, length etc.)
2. Year
3. Unit (substocks, male/female)

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

1. User defined (age, length etc.)
2. Year
3. Unit (substocks, male/female)
4. Season

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

1. User defined (age, length etc.)
2. Year
3. Unit (substocks, male/female)
4. Season
5. Area

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

1. User defined (age, length etc.)
2. Year
3. Unit (substocks, male/female)
4. Season
5. Area
6. Iter

FLQUANT EXAMPLE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

```
> data(ple4)
> flq <- window(landings.n(ple4), start = 1995, end = 2001)
> dimnames(flq)
```

```
$age
[1] "1"  "2"  "3"  "4"  "5"  "6"  "7"  "8"  "9"  "10"
```

```
$year
[1] "1995" "1996" "1997" "1998" "1999" "2000" "2001"
```

```
$unit
[1] "unique"
```

```
$season
[1] "all"
```

```
$area
[1] "unique"
```

```
$iter
[1] "1"
```

FLQUANT METHODS

INTRODUCTION TO FLCORE

FLR CORE TEAM

INTRODUCTION

BASIC CLASSES

COMPOSITE CLASSES

LIST CLASSES

MODEL CLASSES

```
> getClassMethods("FLQuant", "package:FLCore")
```

[1] "apply"	"areaMeans"	"areaSums"	"areaVars"
[5] "as.data.frame"	"as.FLQuant"	"barchart"	"<-"
[9] "["	"bubbles"	"bwplot"	"capacity<-"
[13] "catch<-"	"catch.n<-"	"catch.q<-"	"catch.wt<-"
[17] "coerce"	"crewshare<-"	"cv"	"dimMeans"
[21] "dimnames<-"	"dims"	"dimSums"	"dimVars"
[25] "discards<-"	"discards.n<-"	"discards.sel<-"	"discards.wt<-"
[29] "dotplot"	"effort<-"	"effshare<-"	"E"
[33] "fcost<-"	"fec<-"	"FLBiol"	"FLCatch"
[37] "FLCohort"	"FLIndex"	"FLMetier"	"FLQuant"
[41] "FLQuantPoint"	"FLStock"	"harvest<-"	"harvest.spwn<-"
[45] "histogram"	"index<-"	"index.q<-"	"index.var<-"
[49] "iter<-"	"iterMeans"	"iters"	"iterVars"
[53] "jackknife"	"landings<-"	"landings.n<-"	"landings.sel<-"
[57] "landings.wt<-"	"logLAR1"	"mat<-"	"m<-"
[61] "m.spwn<-"	"names"	"n<-"	"plot"
[65] "price<-"	"print"	"propagate"	"pv"
[69] "quant<-"	"quant"	"quantile"	"quantMeans"
[73] "quantSums"	"quantTotals"	"quantVars"	"rec<-"
[77] "r"	"rlnorm"	"rnorm"	"rpois"
[81] "rSq"	"seasonMeans"	"seasonSums"	"seasonVars"
[85] "sel.pattern<-"	"setPlusGroup"	"sp"	"spr0"
[89] "spwn<-"	"ssb<-"	"stock<-"	"stock.n<-"
[93] "stock.wt<-"	"stripplot"	"sweep"	"unitMeans"
[97] "units<-"	"units"	"unitSums"	"unitVars"
[101] "vcost<-"	"window"	"wt<-"	"xyplot"
[105] "yearMeans"	"yearSums"	"yearTotals"	"yearVars"

Six dimensional array used to summarize FLQuant objects.

```
> dimnames(FLQuantPoint(flq))
```

```
$age
```

```
[1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10"
```

```
$year
```

```
[1] "1995" "1996" "1997" "1998" "1999" "2000" "2001"
```

```
$unit
```

```
[1] "unique"
```

```
$season
```

```
[1] "all"
```

```
$area
```

```
[1] "unique"
```

```
$iter
```

```
[1] "mean" "median" "var" "uppq" "lowq"
```

FLQUANTPOINT METHODS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

```
> getClassMethods("FLQuantPoint", "package:FLCore")
```

```
[1] "[<-"      "coerce"    "lowq<-"    "lowq"      "mean"      "mean<-"
[7] "median<-" "median"    "plot"      "quantile"  "rgamma"    "rlnorm"
[13] "rnorm"     "show"      "summary"   "uppq<-"    "uppq"      "var<-"
[19] "var"
```

Six dimensional array used to store cohort data.

```
> dimnames(FLCohort(flq))
```

```
$age
```

```
[1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10"
```

```
$cohort
```

```
[1] "1985" "1986" "1987" "1988" "1989" "1990" "1991" "1992" "1993" "1994"  
[11] "1995" "1996" "1997" "1998" "1999" "2000"
```

```
$unit
```

```
[1] "unique"
```

```
$season
```

```
[1] "all"
```

```
$area
```

```
[1] "unique"
```

```
$iter
```

```
[1] "1"
```

FLCOHORT METHODS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

```
> getClassMethods("FLCohort", "package:FLCore")
```

```
[1] "bubbles"      "ccplot"       "coerce"       "dimnames<-"  "dims"
[6] "flc2flq"      "FLCohort"     "iter<-"       "plot"        "propagate"
[11] "xyplot"
```

A two dimensional array used to store parameter's data.

```
> dimnames(new("FLPar"))
```

```
$param  
[1] ""
```

```
$iter  
[1] "1"
```

FLPAR METHODS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

```
> getClassMethods("FLPar", "package:FLCore")
```

[1]	"ab"	"Arith"	"as.data.frame"	"[<-"
[5]	"["	"coerce"	"convertFLPar"	"densityplot"
[9]	"dims"	"FLPar"	"fmle"	"histogram"
[13]	"iter<-"	"iter"	"mean"	"median"
[17]	"names<-"	"names"	"params<-"	"plot"
[21]	"propagate"	"show"	"splom"	"summary"
[25]	"sv"	"sweep"	"units<-"	"units"
[29]	"var"			

COMPOSITE CLASSES

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

Classes that use FLQuant classes to define their slots.

	parent	nSlots	virtual	child	distance
FLBiol	FLComp	8	FALSE		
FLCatch	FLComp	13	FALSE		
FLFleet	FLComp	8	FALSE		
FLIndex	FLComp	12	FALSE		
FLMetier	FLComp	7	FALSE		
FLModel.1	FLComp	14	FALSE	FLSR	1.00
FLModel.1.1	FLComp	14	FALSE	FLGrowth	1.00
FLStock	FLComp	20	FALSE		

Represents a fish stock and comprises a number of slots.

```
> showClass("FLStock")
```

```
Class "FLStock" [package "FLCore"]
```

Slots:

Name:	catch	catch.n	catch.wt	discards	discards.n
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	discards.wt	landings	landings.n	landings.wt	stock
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	stock.n	stock.wt	m	mat	harvest
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	harvest.spwn	m.spwn	name	desc	range
Class:	FLQuant	FLQuant	character	character	numeric

Extends: "FLComp"

FLStock EXAMPLE

INTRODUCTION TO FLCORE

FLR CORE TEAM

```
> summary(ple4)
```

```
An object of class "FLStock"
```

INTRODUCTION

BASIC CLASSES

```
Name: Plaice in IV
```

```
Description: Imported from a VPA file. ( N:\Projecten\ICES WG\Demersale werkgroep WGNSSK\2009\st
```

Range:	min	max	pgroup	minyear	maxyear	minfbar
1	10	10	1957	2008	2	6

```
Quant: age
```

COMPOSITE CLASSES

catch	:	[1 52 1 1 1 1],	units = tonnes
catch.n	:	[10 52 1 1 1 1],	units = thousands
catch.wt	:	[10 52 1 1 1 1],	units = kg
discards	:	[1 52 1 1 1 1],	units = tonnes
discards.n	:	[10 52 1 1 1 1],	units = thousands
discards.wt	:	[10 52 1 1 1 1],	units = kg
landings	:	[1 52 1 1 1 1],	units = tonnes
landings.n	:	[10 52 1 1 1 1],	units = thousands
landings.wt	:	[10 52 1 1 1 1],	units = kg
stock	:	[1 52 1 1 1 1],	units = tonnes
stock.n	:	[10 52 1 1 1 1],	units = thousands
stock.wt	:	[10 52 1 1 1 1],	units = kg
m	:	[10 52 1 1 1 1],	units = NA
mat	:	[10 52 1 1 1 1],	units = NA
harvest	:	[10 52 1 1 1 1],	units = f
harvest.spwn	:	[10 52 1 1 1 1],	units = NA
m.spwn	:	[10 52 1 1 1 1],	units = NA

LIST CLASSES

MODEL CLASSES

FLStock METHODS

INTRODUCTION TO FLCORE

FLR CORE TEAM

INTRODUCTION

BASIC CLASSES

COMPOSITE CLASSES

LIST CLASSES

MODEL CLASSES

```
> getClassMethods("FLStock", "package:FLCore")
```

[1]	"as.FLBiol"	"as.FLSR"	"[<-"	"["
[5]	"+"	"catch<-"	"catch"	"catch.n<-"
[9]	"catch.n"	"catch.wt<-"	"catch.wt"	"coerce"
[13]	"computeCatch"	"computeDiscards"	"computeLandings"	"computeStock"
[17]	"dimnames<-"	"dims"	"discards<-"	"discards"
[21]	"discards.n<-"	"discards.n"	"discards.wt<-"	"discards.wt"
[25]	"expand"	"fapex"	"fbar"	"harvest<-"
[29]	"harvest"	"harvest.spwn<-"	"harvest.spwn"	"landings<-"
[33]	"landings"	"landings.n<-"	"landings.n"	"landings.wt<-"
[37]	"landings.wt"	"mat<-"	"mat"	"m<-"
[41]	"m"	"m.spwn<-"	"m.spwn"	"name"
[45]	"plot"	"qapply"	"range"	"rec"
[49]	"r"	"setPlusGroup"	"sp"	"spr0"
[53]	"ssb"	"ssbpurec"	"stock<-"	"stock"
[57]	"stock.n<-"	"stock.n"	"stock.wt<-"	"stock.wt"
[61]	"summary"	"survprob"	"trim"	"tsb"

FLStock PLOT

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION


BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

Plaice in IV



Represents a biological population

```
> showClass("FLBiol")
```

```
Class "FLBiol" [package "FLCore"]
```

```
Slots:
```

Name:	n	m	wt	fec	spwn	name	desc
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant	character	character

Name:	range
Class:	numeric

```
Extends: "FLComp"
```

FLBIOL EXAMPLE

INTRODUCTION TO FLCORE

FLR CORE TEAM

INTRODUCTION

BASIC CLASSES

COMPOSITE CLASSES

LIST CLASSES

MODEL CLASSES

```
> summary(flbiol)
```

An object of class "FLBiol"

Name: Plaice in IV

Description: Imported from a VPA file. (N:\Projecten\ICES WG\Demersale werkgroep WGNSSK\2009\st

Range:	min	max	pgroup	minyear	maxyear	minfbar
1	10	10	1957	2008	2	6

Quant: age

n	:	[10 52 1 1 1 1],	units =	thousands
m	:	[10 52 1 1 1 1],	units =	NA
wt	:	[10 52 1 1 1 1],	units =	kg
fec	:	[10 52 1 1 1 1],	units =	NA
spwn	:	[10 52 1 1 1 1],	units =	NA

FLBIOL METHODS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

```
> getClassMethods("FLBiol", "package:FLCore")
```

[1]	"as.FLBiol"	"as.FLSR"	"catch.n"	"coerce"
[5]	"computeStock"	"fbar"	"fec<-"	"fec"
[9]	"harvest"	"leslie"	"mean.lifespan"	"m<-"
[13]	"m"	"n<-"	"n"	"plot"
[17]	"rec"	"r"	"setPlusGroup"	"spwn<-"
[21]	"spwn"	"ssb"	"ssn"	"summary"
[25]	"survprob"	"tsb"	"wt<-"	"wt"

FLBIOL PLOT

INTRODUCTION
TO FLCORE

FLR CORE
TEAM


INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES



FLINDEX

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

Represents a index (e.g. index of abundance from a survey)

```
> showClass("FLIndex")
```

```
Class "FLIndex" [package "FLCore"]
```

Slots:

Name:	type	distribution	index	index.var	catch.n
Class:	character	character	FLQuant	FLQuant	FLQuant

Name:	catch.wt	effort	sel.pattern	index.q	name
Class:	FLQuant	FLQuant	FLQuant	FLQuant	character

Name:	desc	range
Class:	character	numeric

```
Extends: "FLComp"
```

FLINDEX EXAMPLE

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

```
> summary(ple4.index)
```

An object of class "FLIndex"

Name: BTS-Isis

Description: Plaice in IV . Imported from VPA file.

Range:	min	max	pgroup	minyear	maxyear	startf	e
1	8	NA	1985	2008	0.66	0.75	

Type :

Distribution :

Quant: age

```
index      : [ 8 24 1 1 1 1 ], units = NA
index.var  : [ 8 24 1 1 1 1 ], units = NA
catch.n    : [ 8 24 1 1 1 1 ], units = NA
catch.wt   : [ 8 24 1 1 1 1 ], units = NA
effort     : [ 1 24 1 1 1 1 ], units = NA
sel.pattern : [ 8 24 1 1 1 1 ], units = NA
index.q    : [ 8 24 1 1 1 1 ], units = NA
```

FLINDEX METHODS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

```
> getClassMethods("FLIndex", "package:FLCore")
```

[1]	"["	"catch.n<-"	"catch.n"	"catch.wt<-"
[5]	"catch.wt"	"coerce"	"computeCatch"	"dims"
[9]	"effort<-"	"effort"	"index<-"	"index"
[13]	"index.q<-"	"index.q"	"index.var<-"	"index.var"
[17]	"plot"	"sel.pattern<-"	"sel.pattern"	"summary"
[21]	"trim"	"type<-"	"type"	

FLBIOL PLOT

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION


BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

BTS-Isis



FLFLEET

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION


BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

A more complicated class with three levels: Fleet, Metier and Catch



FLFLEET

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

```
> showClass("FLFleet")
```

```
Class "FLFleet" [package "FLCore"]
```

```
Slots:
```

```
Name:      effort      fcost  capacity crewshare  metiers      name      desc
```

```
Class:    FLQuant    FLQuant    FLQuant    FLQuant FLMetiers character character
```

```
Name:      range
```

```
Class:     numeric
```

```
Extends: "FLComp"
```

FLFLEET EXAMPLE

INTRODUCTION TO FLCORE

FLR CORE TEAM

INTRODUCTION

BASIC CLASSES

COMPOSITE CLASSES

LIST CLASSES

MODEL CLASSES

```
> summary(bt4)
```

An object of class "FLFleet"

Name: beam trawl fleet

Description: Example of an FLFleet

Range:	min	max	pgroup	minyear	maxyear
0	0	NA	1957	2001	

Quant: age

effort	:	[1 45 1 1 1 1]	, units = NA
fcost	:	[1 45 1 1 1 1]	, units = NA
capacity	:	[1 45 1 1 1 1]	, units = NA
crewshare	:	[1 45 1 1 1 1]	, units = NA

Metiers:

TBB :

ple	:	[15 45 1 1 1 1]
sol	:	[10 45 1 1 1 1]

FLFLEET METHODS

INTRODUCTION TO FLCORE

FLR CORE TEAM

INTRODUCTION

BASIC CLASSES

COMPOSITE CLASSES

LIST CLASSES

MODEL CLASSES

```
> getClassMethods("FLFleet", "package:FLCore")
```

[1]	"as.data.frame"	"as.FLIndex"	"["	"[["
[5]	"capacity<-"	"capacity"	"catches"	"catch"
[9]	"catchNames"	"catch.n"	"catch.q<-"	"catch.q"
[13]	"catch.sel"	"catch.wt"	"coerce"	"computeCatch"
[17]	"computeDiscards"	"computeLandings"	"crewshare<-"	"crewshare"
[21]	"dims"	"discards<-"	"discards"	"discards.n<-"
[25]	"discards.n"	"discards.sel<-"	"discards.sel"	"discards.wt<-"
[29]	"discards.wt"	"effort<-"	"effort"	"effshare"
[33]	"fcost<-"	"fcost"	"FLFleet"	"iter"
[37]	"landings<-"	"landings"	"landings.n<-"	"landings.n"
[41]	"landings.sel<-"	"landings.sel"	"landings.wt<-"	"landings.wt"
[45]	"metier<-"	"metier"	"metiers<-"	"metiers"
[49]	"price<-"	"price"	"propagate"	"revenue"
[53]	"summary"	"trim"	"vcost"	"window"

LIST CLASSES

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

	parent	nSlots	virtual	child	distance
FLBiols	FLlst	4	FALSE		
FLCatches	FLlst	4	FALSE		
FLCohorts	FLlst	4	FALSE		
FLFleets	FLlst	4	FALSE		
FLIndices	FLlst	4	FALSE		
FLMetiers	FLlst	4	FALSE		
FLQuants	FLlst	4	FALSE		
FLStocks	FLlst	4	FALSE		

MODEL CLASSES

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

	parent	nSlots	virtual	child	distance
FLGrowth	FLModel	15	FALSE		
FLSR	FLModel	18	FALSE		

Class for fitting stock-recruitment relationships. Extends FLModel.

```
> data(nsher)
> summary(nsher)
```

An object of class "FLSR"

Name: Autumn spawning herring in IV, V 3/4/2005 14:46

Description: 'rec' and 'ssb' slots obtained from a 'FLStock' object

Range:

Quant: age

```
rec          : [ 1 45 1 1 1 1 ], units = NA
ssb          : [ 1 45 1 1 1 1 ], units = NA
residuals    : [ 1 45 1 1 1 1 ], units = NA NA
fitted       : [ 1 45 1 1 1 1 ], units = NA
```

Model: rec ~ a * ssb * exp(-b * ssb)

<environment: 0x560f3e0>

Parameters:


```
  params
iter    a      b
1 119.4 0.009027
```

Log-likelihood: 16.352(0)


Variance-covariance:

```
          a          b
a 258.66388793 1.838394e-02
b  0.01838394 2.002586e-06
```


Stock Recruit




Residuals by year




AR(1) Residuals




Residuals by SSB



Residuals by Estimated Recruits



Normal Q-Q Plot



SLOT ACCESSORS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

SLOT ACCESSORS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Try to avoid using @ to access slots

SLOT ACCESSORS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Try to avoid using @ to access slots
- ▶ Use accessors instead

SLOT ACCESSORS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Try to avoid using @ to access slots
- ▶ Use accessors instead
- ▶ e.g. `landings.n(stock)` not `stock@landings.n`

SLOT ACCESSORS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Try to avoid using @ to access slots
- ▶ Use accessors instead
- ▶ e.g. landings.n(stock) not stock@landings.n
- ▶ Protects against internal changes

SLOT ACCESSORS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Try to avoid using @ to access slots
- ▶ Use accessors instead
- ▶ e.g. landings.n(stock) not stock@landings.n
- ▶ Protects against internal changes
- ▶ e.g. catch slots removed from FLCatch

SLOT ACCESSORS

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

- ▶ Try to avoid using @ to access slots
- ▶ Use accessors instead
- ▶ e.g. landings.n(stock) not stock@landings.n
- ▶ Protects against internal changes
- ▶ e.g. catch slots removed from FLCatch
- ▶ But accessor catch() still works