

INTRODUCTION TO THE FLCORE PACKAGE

FLR Core Team

December 2, 2010



① INTRODUCTION

OUTLINE

① INTRODUCTION

② BASIC CLASSES

OUTLINE

① INTRODUCTION

② BASIC CLASSES

③ COMPOSITE CLASSES

OUTLINE

① INTRODUCTION

② BASIC CLASSES

③ COMPOSITE CLASSES

④ LIST CLASSES

OUTLINE

① INTRODUCTION

② BASIC CLASSES

③ COMPOSITE CLASSES

④ LIST CLASSES

⑤ MODEL CLASSES

FLCORE STRUCTURE

Follows S4 paradigm. Objects are instances of a collection of data and methods, where the data structure and the methods to apply are defined by classes.

FLCORE STRUCTURE

Follows S4 paradigm. Objects are instances of a collection of data and methods, where the data structure and the methods to apply are defined by classes.

- ▶ Classes - abstract definition of data structure

FLCORE STRUCTURE

Follows S4 paradigm. Objects are instances of a collection of data and methods, where the data structure and the methods to apply are defined by classes.

- ▶ Classes - abstract definition of data structure
- ▶ Methods - implementation of actions

FLCORE STRUCTURE

Follows S4 paradigm. Objects are instances of a collection of data and methods, where the data structure and the methods to apply are defined by classes.

- ▶ Classes - abstract definition of data structure
- ▶ Methods - implementation of actions
- ▶ Objects - instances of the classes which have data following the class definition and methods depending on its class.

INTRODUCTION
TO FLCORE

FLR CORE
TEAM

INTRODUCTION

BASIC
CLASSES

COMPOSITE
CLASSES

LIST CLASSES

MODEL
CLASSES

INSIDE FLCORE

INSIDE FLCORE

- Basic classes - *single array*:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar

INSIDE FLCORE

- ▶ Basic classes - *single array*:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar
- ▶ Composite classes - *complex class composed of basic classes, both FLCore and R*:
FLComp, FLBiol, FLCatch, FLFleet, FLIndex, FLMetier, FLModel, FLStock

INSIDE FLCORE

- ▶ Basic classes - *single array*:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar
- ▶ Composite classes - *complex class composed of basic classes, both FLCore and R*:
FLComp, FLBiol, FLCatch, FLFleet, FLIndex, FLMetier, FLModel, FLStock
- ▶ List classes - *list of objects of the same class*:
FLlst, FLBiols, FLCatches, FLCohorts, FLFleets, FLIndices, FLMetiers, FLQuants, FLStocks

INSIDE FLCORE

- ▶ Basic classes - *single array*:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar
- ▶ Composite classes - *complex class composed of basic classes, both FLCore and R*:
FLComp, FLBiol, FLCatch, FLFleet, FLIndex, FLMetier, FLModel, FLStock
- ▶ List classes - *list of objects of the same class*:
FLlst, FLBiols, FLCatches, FLCohorts, FLFleets, FLIndices, FLMetiers, FLQuants, FLStocks
- ▶ Model class - *composite classes specific for implementation of models*:
FLModel, FLGrowth, FLRS

INSIDE FLCORE

- ▶ Basic classes - *single array*:
FLArray, FLQuant, FLCohort, FLQuantPoint, FLPar
- ▶ Composite classes - *complex class composed of basic classes, both FLCore and R*:
FLComp, FLBiol, FLCatch, FLFleet, FLIndex, FLMetier, FLModel, FLStock
- ▶ List classes - *list of objects of the same class*:
FLlst, FLBiols, FLCatches, FLCohorts, FLFleets, FLIndices, FLMetiers, FLQuants, FLStocks
- ▶ Model class - *composite classes specific for implementation of models*:
FLModel, FLGrowth, FLRS
- ▶ Methods

BASIC CLASSES

	class	parent	nSlots	virtual	child	distance
1	FLArray	array	2	FALSE	FLQuant	1.00
2	FLArray	array	2	FALSE	FLCohort	1.00
3	FLArray	array	2	FALSE	FLQuantPoint	2.00
4	FLCohort	FLArray	2	FALSE		
5	FLQuant	FLArray	2	FALSE	FLQuantPoint	1.00
6	FLQuantPoint	FLQuant	2	FALSE		

FLQUANT

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

FLQUANT

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

- ① User defined (age, length etc.)

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

- ① User defined (age, length etc.)
- ② Year

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

- ① User defined (age, length etc.)
- ② Year
- ③ Unit (substocks, male/female)

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

- ① User defined (age, length etc.)
- ② Year
- ③ Unit (substocks, male/female)
- ④ Season

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

- ① User defined (age, length etc.)
- ② Year
- ③ Unit (substocks, male/female)
- ④ Season
- ⑤ Area

Six dimensional array used to store data of a particular type (e.g. catch numbers).

Dimensions are:

- ① User defined (age, length etc.)
- ② Year
- ③ Unit (substocks, male/female)
- ④ Season
- ⑤ Area
- ⑥ Iter

FLQUANT EXAMPLE

```
> flq <- window(landings.n(ple4), start = 1995, end = 2001)
> dimnames(flq)
```

```
$age
[1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10"
```

```
$year
[1] "1995" "1996" "1997" "1998" "1999" "2000" "2001"
```

```
$unit
[1] "unique"
```

```
$season
[1] "all"
```

```
$area
[1] "unique"
```

```
$iter
[1] "1"
```

FLQUANT METHODS

```
> getClassMethods("FLQuant", "package:FLCore")
```

```
[1] "areaMeans"      "areaSums"      "areaVars"      "as.FLQuant"
[5] "barchart"       "[<-"           "["             "bubbles"
[9] "bwplot"         "capacity<-"    "catch<-"       "catch.n<-"
[13] "catch.q<-"      "catch.wt<-"    "coerce"         "crewshare<-"
[17] "cv"             "dimMeans"      "dimnames<-"     "dims"
[21] "dimSums"        "dimVars"       "discards<-"     "discards.n<-"
[25] "discards.sel<-" "discards.wt<-" "dotplot"        "effort<-"
[29] "effshare<-"     "E"             "fcost<-"        "fec<-"
[33] "FLBiol"         "FLCatch"       "FLCohort"       "FLIndex"
[37] "FLMetier"       "FLQuant"       "FLQuantPoint"   "FLStock"
[41] "harvest<-"      "harvest.spwn<-" "histogram"       "index<-"
[45] "index.q<-"      "index.var<-"   "iter<-"         "iterMeans"
[49] "iters"          "iterVars"      "jackknife"       "landings<-"
[53] "landings.n<-"   "landings.sel<-" "landings.wt<-"   "logLARI"
[57] "mat<-"          "m<-"           "m.spwn<-"       "names"
[61] "n<-"            "plot"          "price<-"        "print"
[65] "propagate"      "pv"            "quant"          "quantile"
[69] "quantMeans"     "quantSums"     "quantTotals"    "quantVars"
[73] "rec<-"          "r"             "rlnorm"         "rnorm"
[77] "rpois"          "rSq"           "seasonMeans"     "seasonSums"
[81] "seasonVars"     "sel.pattern<-" "setPlusGroup"    "sp"
[85] "spr0"           "spwn<-"        "ssb<-"          "stock<-"
[89] "stock.n<-"      "stock.wt<-"    "striplot"       "sweep"
[93] "unitMeans"      "units"         "unitSums"       "unitVars"
[97] "vcost<-"        "window"        "wt<-"           "xyplot"
[101] "yearMeans"      "yearSums"      "yearTotals"     "yearVars"
```

FLQUANTPOINT

Six dimensional array used to summarize iterations of FLQuant objects.

```
> dimnames(FLQuantPoint(flq))

$age
[1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10"

$year
[1] "1995" "1996" "1997" "1998" "1999" "2000" "2001"

$unit
[1] "unique"

$season
[1] "all"

$area
[1] "unique"

$iter
[1] "mean" "median" "var" "uppq" "lowq"
```

FLQuantPoint EXAMPLE

```
> flq[1:4, 1:5]
```

```
An object of class "FLQuant"  
, , unit = unique, season = all, area = unique
```

```
      year  
age 1995  1996  1997  1998  1999  
  1   7751   1104    892   196   549  
  2  36575  42496  42855 30401  8689  
  3  81398  64382  86948 68920 155971  
  4  78370  46359  43669 56329 39857
```

```
units: thousands
```

```
> FLQuantPoint(flq[1:4, 1:5])
```

```
An object of class "FLQuantPoint":  
-- median:  
, , unit = unique, season = all, area = unique
```

```
      year  
age 1995  1996  1997  1998  1999  
  1   7751  1104    892   196   549  
  2  36575 42496 42855 30401  8689  
  3  81398 64382 86948 68920 155971  
  4  78370 46359 43669 56329 39857
```

```
units: NA
```

FLQUANTPOINT METHODS

```
> getClassMethods("FLQuantPoint", "package:FLCore")
```

```
[1] "[<-"      "["      "coerce"   "FLQuant" "lowq<-"  "lowq"
[7] "mean"     "mean<-"  "median<-" "median"   "plot"    "quantile"
[13] "rgamma"   "rlnorm"  "rnorm"    "show"     "summary" "uppq<-"
[19] "uppq"     "var<-"  "var"
```

FLCohort

Six dimensional array used to store cohort data.

```
> dimnames(FLCohort(flq))
```

```
$age  
[1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10"
```

```
$cohort  
[1] "1985" "1986" "1987" "1988" "1989" "1990" "1991" "1992" "1993" "1994"  
[11] "1995" "1996" "1997" "1998" "1999" "2000"
```

```
$unit  
[1] "unique"
```

```
$season  
[1] "all"
```

```
$area  
[1] "unique"
```

```
$iter  
[1] "1"
```

FLCOHORT EXAMPLE

```
> flq[1:4, 1:5]
```

```
An object of class "FLQuant"
, , unit = unique, season = all, area = unique
```

	year				
age	1995	1996	1997	1998	1999
1	7751	1104	892	196	549
2	36575	42496	42855	30401	8689
3	81398	64382	86948	68920	155971
4	78370	46359	43669	56329	39857

```
units: thousands
```

```
> FLCohort(flq[1:4, 1:5])
```

```
An object of class "FLCohort"
, , unit = unique, season = all, area = unique
```

	cohort							
age	1991	1992	1993	1994	1995	1996	1997	1998
1	NA	NA	NA	7751	1104	892	196	549
2	NA	NA	36575	42496	42855	30401	8689	NA
3	NA	81398	64382	86948	68920	155971	NA	NA
4	78370	46359	43669	56329	39857	NA	NA	NA

```
units: thousands
```

FLCOHORT METHODS

```
> getClassMethods("FLCohort", "package:FLCore")
```

```
[1] "bubbles"      "ccplot"       "coerce"       "dimnames<-"  "dims"  
[6] "flc2flq"      "FLCohort"     "iter<-"      "plot"        "propagate"  
[11] "show"         "xyplot"
```


FLPAR

A two dimensional array used to store parameter's data.

```
> dimnames(new("FLPar"))
```

```
$param  
[1] ""
```

```
$iter  
[1] "1"
```

FLPAR METHODS

```
> getClassMethods("FLPar", "package:FLCore")
```

[1]	"ab"	"Arith"	"as.data.frame"	"[<-"
[5]	"["	"coerce"	"convertFLPar"	"densityplot"
[9]	"dims"	"FLPar"	"fmle"	"histogram"
[13]	"iter<-"	"iter"	"mean"	"median"
[17]	"names<-"	"names"	"params<-"	"plot"
[21]	"propagate"	"show"	"splom"	"summary"
[25]	"sv"	"sweep"	"units<-"	"units"
[29]	"var"			

COMPOSITE CLASSES

Classes that use FLQuant classes to define their slots.

	class	parent	nSlots	virtual	child	distance
1	FLBiol	FLComp	8	FALSE		
2	FLCatch	FLComp	13	FALSE		
3	FLFleet	FLComp	8	FALSE		
4	FLIndex	FLComp	12	FALSE		
5	FLMetier	FLComp	7	FALSE		
6	FLModel	FLComp	14	FALSE	FLSR	1.00
7	FLStock	FLComp	20	FALSE		

FLSTOCK

Represents a fish stock and comprises a number of slots.

```
> showClass("FLStock")
```

```
Class "FLStock" [package "FLCore"]
```

Slots:

Name:	catch	catch.n	catch.wt	discards	discards.n
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	discards.wt	landings	landings.n	landings.wt	stock
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	stock.n	stock.wt	m	mat	harvest
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	harvest.spwn	m.spwn	name	desc	range
Class:	FLQuant	FLQuant	character	character	numeric

Extends: "FLComp"

FLStock EXAMPLE

```
> summary(ple4)
```

An object of class "FLStock"

Name: Plaice in IV

Description: Imported from a VPA file. (N:\Projecten\ICES WG\Demersale werkgroep WGNSSK\2009\st

Range:	min	max	pgroup	minyear	maxyear	minfbar
1	10	10	1957	2008	2	6

Quant: age

```

catch      : [ 1 52 1 1 1 1 ], units = tonnes
catch.n    : [ 10 52 1 1 1 1 ], units = thousands
catch.wt   : [ 10 52 1 1 1 1 ], units = kg
discards   : [ 1 52 1 1 1 1 ], units = tonnes
discards.n : [ 10 52 1 1 1 1 ], units = thousands
discards.wt : [ 10 52 1 1 1 1 ], units = kg
landings   : [ 1 52 1 1 1 1 ], units = tonnes
landings.n : [ 10 52 1 1 1 1 ], units = thousands
landings.wt : [ 10 52 1 1 1 1 ], units = kg
stock      : [ 1 52 1 1 1 1 ], units = tonnes
stock.n    : [ 10 52 1 1 1 1 ], units = thousands
stock.wt   : [ 10 52 1 1 1 1 ], units = kg
m          : [ 10 52 1 1 1 1 ], units = NA
mat        : [ 10 52 1 1 1 1 ], units = NA
harvest    : [ 10 52 1 1 1 1 ], units = f
harvest.spwn : [ 10 52 1 1 1 1 ], units = NA
m.spwn     : [ 10 52 1 1 1 1 ], units = NA

```


FLStock METHODS

```
> getClassMethods("FLStock", "package:FLCore")
```

[1] "as.FLBIol"	"as.FLSR"	"[<-"	"["
[5] "+"	"catch<-"	"catch"	"catch.n<-"
[9] "catch.n"	"catch.wt<-"	"catch.wt"	"coerce"
[13] "computeCatch"	"computeDiscards"	"computeLandings"	"computeStock"
[17] "dimnames<-"	"discards<-"	"discards"	"discards.n<-"
[21] "discards.n"	"discards.wt<-"	"discards.wt"	"expand"
[25] "fapex"	"fbar"	"harvest<-"	"harvest"
[29] "harvest.spwn<-"	"harvest.spwn"	"landings<-"	"landings"
[33] "landings.n<-"	"landings.n"	"landings.wt<-"	"landings.wt"
[37] "mat<-"	"mat"	"m<-"	"m"
[41] "m.spwn<-"	"m.spwn"	"plot"	"rec"
[45] "r"	"setPlusGroup"	"sp"	"spr0"
[49] "ssb"	"ssbpurec"	"stock<-"	"stock"
[53] "stock.n<-"	"stock.n"	"stock.wt<-"	"stock.wt"
[57] "summary"	"survprob"	"trim"	"tsb"

FLSTOCK PLOT

Plaice in IV



Represents a biological population

```
> showClass("FLBiol")
```

```
Class "FLBiol" [package "FLCore"]
```

```
Slots:
```

Name:	n	m	wt	fec	spwn	name	desc
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant	character	character

Name:	range
Class:	numeric

```
Extends: "FLComp"
```


FLBIOL EXAMPLE

```
> summary(flbior)
```

An object of class "FLBior"

Name: Plaice in IV

Description: Imported from a VPA file. (N:\Projecten\ICES WG\Demersale werkgroep WGNSSK\2009\st

Range:	min	max	pgroup	minyear	maxyear	minfbar
1	10	10	1957	2008	2	6

Quant: age


n	:	[10 52 1 1 1 1],	units =	thousands
m	:	[10 52 1 1 1 1],	units =	NA
wt	:	[10 52 1 1 1 1],	units =	kg
fec	:	[10 52 1 1 1 1],	units =	NA
spwn	:	[10 52 1 1 1 1],	units =	NA

FLBIOL METHODS

```
> getClassMethods("FLBiol", "package:FLCore")
```

[1]	"as.FLBiol"	"as.FLSR"	"catch.n"	"coerce"
[5]	"computeStock"	"fbar"	"fec<="	"fec"
[9]	"harvest"	"leslie"	"mean.lifespan"	"m<="
[13]	"m"	"n<="	"n"	"plot"
[17]	"rec"	"r"	"setPlusGroup"	"spwn<="
[21]	"spwn"	"ssb"	"ssn"	"summary"
[25]	"survprob"	"tsb"	"wt<="	"wt"

FLBIOL PLOT



FLINDEX

Represents a index (e.g. index of abundance from a survey)

```
> showClass("FLIndex")
```

```
Class "FLIndex" [package "FLCore"]
```

Slots:

Name:	type	distribution	index	index.var	catch.n
Class:	character	character	FLQuant	FLQuant	FLQuant

Name:	catch.wt	effort	sel.pattern	index.q	name
Class:	FLQuant	FLQuant	FLQuant	FLQuant	character

Name:	desc	range
Class:	character	numeric

```
Extends: "FLComp"
```

FLINDEX EXAMPLE

```
> summary(ple4.index)
```

An object of class "FLIndex"

Name: **BTS-Isis**

Description: Plaice in IV . Imported from VPA file.

Range:	min	max	pgroup	minyear	maxyear	startf	e
1	8	NA	1985	2008	0.66	0.75	

Type :

Distribution :

Quant: age

```

index      : [ 8 24 1 1 1 1 ], units = NA
index.var  : [ 8 24 1 1 1 1 ], units = NA
catch.n    : [ 8 24 1 1 1 1 ], units = NA
catch.wt   : [ 8 24 1 1 1 1 ], units = NA
effort     : [ 1 24 1 1 1 1 ], units = NA
sel.pattern : [ 8 24 1 1 1 1 ], units = NA
index.q    : [ 8 24 1 1 1 1 ], units = NA


```

FLINDEX METHODS

```
> getClassMethods("FLIndex", "package:FLCore")
```

```
[1] "["                "catch.n<-"        "catch.n"           "catch.wt<-"
[5] "catch.wt"         "coerce"            "computeCatch"      "dims"
[9] "effort<-"         "effort"            "index<-"           "index"
[13] "index.q<-"        "index.q"           "index.var<-"       "index.var"
[17] "plot"             "sel.pattern<-"    "sel.pattern"       "summary"
[21] "trim"             "type<-"           "type"
```

FLINDEX PLOT



FLCATCH

Represents the catch of a fleet

```
> showClass("FLCatch")
```

```
Class "FLCatch" [package "FLCore"]
```

```
Slots:
```

Name:	landings	landings.n	landings.wt	landings.sel	discards
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	discards.n	discards.wt	discards.sel	catch.q	price
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	name	desc	range
Class:	character	character	numeric

```
Extends: "FLComp"
```


FLINDEX EXAMPLE

```
> summary(bt4[["TBB"]][["ple"]])
```

An object of class "FLCatch"

Name: ple
Description: North Sea Plaice

Range:	min	max	pgroup	minyear	maxyear
1	15	NA	1957	2001	

Quant: age

landings	:	[1 45 1 1 1 1],	units = tonnes
landings.n	:	[15 45 1 1 1 1],	units = thousands
landings.wt	:	[15 45 1 1 1 1],	units = kg
landings.sel	:	[15 45 1 1 1 1],	units = NA
discards	:	[1 45 1 1 1 1],	units = tonnes
discards.n	:	[15 45 1 1 1 1],	units = thousands
discards.wt	:	[15 45 1 1 1 1],	units = kg
discards.sel	:	[15 45 1 1 1 1],	units = NA
catch.q	:	[15 45 1 1 1 1],	units = thousands
price	:	[15 45 1 1 1 1],	units = NA

FLCATCH METHODS

```
> getClassMethods("FLCatch", "package:FLCore")
```

[1]	"[<-"	"["	"catches<-"	"catch"
[5]	"catchNames"	"catch.n"	"catch.q<-"	"catch.q"
[9]	"catch.sel"	"catch.wt"	"coerce"	"computeCatch"
[13]	"computeDiscards"	"computeLandings"	"discards<-"	"discards"
[17]	"discards.n<-"	"discards.n"	"discards.sel<-"	"discards.sel"
[21]	"discards.wt<-"	"discards.wt"	"FLFleet"	"FLMetier"
[25]	"landings<-"	"landings"	"landings.n<-"	"landings.n"
[29]	"landings.sel<-"	"landings.sel"	"landings.wt<-"	"landings.wt"
[33]	"price<-"	"price"	"revenue"	"setPlusGroup"
[37]	"summary"	"trim"		

FLMETIER

Represents a fleet's metier (classification of activity targeting a species or group of species, in a specific period and area, with a particular gear)

```
> showClass("FLMetier")
```

```
Class "FLMetier" [package "FLCore"]
```

Slots:

Name:	gear	effshare	vcost	catches	name	desc	range
Class:	character	FLQuant	FLQuant	FLCatches	character	character	numeric

Extends: "FLComp"

FLMETIER EXAMPLE

```
> summary(bt4[["TBB"]])
```

An object of class "FLMetier"

Name: TBB
Description:
Range: min max pgroup minyear maxyear
 1 15 NA 1957 2001
Gear : NA
Quant: age

effshare : [1 45 1 1 1 1], units = NA
vcost : [1 45 1 1 1 1], units = NA

Catches:

 ple : [15 45 1 1 1 1]
 sol : [10 45 1 1 1 1]


FLMETIER METHODS

```
> getClassMethods("FLMetier", "package:FLCore")
```

[1]	"["	"["["	"catches<-"	"catches"
[5]	"catch"	"catchNames"	"catch.n"	"catch.q<-"
[9]	"catch.q"	"catch.sel"	"catch.wt"	"coerce"
[13]	"computeCatch"	"computeDiscards"	"computeLandings"	"discards<-"
[17]	"discards"	"discards.n<-"	"discards.n"	"discards.sel<-"
[21]	"discards.sel"	"discards.wt<-"	"discards.wt"	"effshare<-"
[25]	"effshare"	"FLFleet"	"gear<-"	"gear"
[29]	"iter"	"landings<-"	"landings"	"landings.n<-"
[33]	"landings.n"	"landings.sel<-"	"landings.sel"	"landings.wt<-"
[37]	"landings.wt"	"metier<-"	"price<-"	"price"
[41]	"propagate"	"revenue"	"summary"	"trim"
[45]	"vcost<-"	"vcost"		

FLFLEET

A more complicated class with three levels: Fleet, Metier and Catch



FLFLEET

```
> showClass("FLFleet")
```

```
Class "FLFleet" [package "FLCore"]
```

```
Slots:
```

```
Name:      effort      fcost  capacity crewshare  metiers      name      desc
Class:  FLQuant  FLQuant  FLQuant  FLQuant FLMetiers character character
```

```
Name:      range
Class:  numeric
```

```
Extends: "FLComp"
```

FLFLEET EXAMPLE

```
> summary(bt4)
```

An object of class "FLFleet"

Name: beam trawl fleet

Description: Example of an FLFleet

Range:	min	max	pgroup	minyear	maxyear
0	0	NA	1957	2001	

Quant: age

```
effort      : [ 1 45 1 1 1 1 ], units = NA
fcost       : [ 1 45 1 1 1 1 ], units = NA
capacity    : [ 1 45 1 1 1 1 ], units = NA
crewshare   : [ 1 45 1 1 1 1 ], units = NA
```

Metiers:

TBB :

```
ple : [ 15 45 1 1 1 1 ]
sol : [ 10 45 1 1 1 1 ]
```


FLFLEET METHODS

```
> getClassMethods("FLFleet", "package:FLCore")
```

[1]	"as.data.frame"	"as.FLIndex"	"["	"["
[5]	"capacity<-"	"capacity"	"catches"	"catch"
[9]	"catchNames"	"catch.n"	"catch.q<-"	"catch.q"
[13]	"catch.sel"	"catch.wt"	"coerce"	"computeCatch"
[17]	"computeDiscards"	"computeLandings"	"crewshare<-"	"crewshare"
[21]	"dims"	"discards<-"	"discards"	"discards.n<-"
[25]	"discards.n"	"discards.sel<-"	"discards.sel"	"discards.wt<-"
[29]	"discards.wt"	"effort<-"	"effort"	"effshare"
[33]	"fcost<-"	"fcost"	"FLFleet"	"iter"
[37]	"landings<-"	"landings"	"landings.n<-"	"landings.n"
[41]	"landings.sel<-"	"landings.sel"	"landings.wt<-"	"landings.wt"
[45]	"metier<-"	"metier"	"metiers<-"	"metiers"
[49]	"price<-"	"price"	"propagate"	"revenue"
[53]	"summary"	"trim"	"vcost"	"window"

LIST CLASSES

	class	parent	nSlots	virtual	child	distance
1	FLBiols	FLlst	4	FALSE		
2	FLCatches	FLlst	4	FALSE		
3	FLCohorts	FLlst	4	FALSE		
4	FLFleets	FLlst	4	FALSE		
5	FLIndices	FLlst	4	FALSE		
6	FLMetiers	FLlst	4	FALSE		
7	FLQuants	FLlst	4	FALSE		
8	FLStocks	FLlst	4	FALSE		

A list of other classes

```
> showClass("FLlist")
```

```
Class "FLlist" [package "FLCore"]
```

```
Slots:
```

```
Name:      .Data      names      desc      lock
Class:      list character character      logical
```

```
Extends:
```

```
Class "list", from data part
```

```
Class "vector", by class "list", distance 2
```

```
Known Subclasses: "FLStocks", "FLIndices", "FLBiols", "FLCatches", "FLMetiers", "FLFleets",  
"FLQuants", "FLCohorts"
```

FLLST EXAMPLE #1

```
> summary(ple4.indices)
```

An object of class "FLIndices"

Elements: BTS-Isis BTS-Tridens SNS

Name: BTS-Isis

Description: Plaice in IV . Imported from VPA file.

Range:	min	max	pgroup	minyear	maxyear	startf
1	8	NA	1985	2008	0.66	0.75

Quant: age

dim: 8 24 1 1 1 1

Name: BTS-Tridens

Description: Plaice in IV . Imported from VPA file.

Range:	min	max	pgroup	minyear	maxyear	startf
1	9	NA	1996	2008	0.66	0.75

Quant: age

dim: 9 13 1 1 1 1

Name: SNS

Description: Plaice in IV . Imported from VPA file.

Range:	min	max	pgroup	minyear	maxyear	startf
1	3	NA	1982	2008	0.66	0.75

Quant: age

dim: 3 27 1 1 1 1

FLLST EXAMPLE #2

```
> flqs <- FLQuants(f1 = catch(ple4), f2 = landings(ple4))  
> summary(flqs)
```

An object of class "FLQuants"

Elements: f1 f2

Name: f1

```
dim   : 1 52 1 1 1 1  
quant: age  
units: tonnes
```

```
Min      : 78422.95  
1st Qu.: 126077.3  
Mean     : 165127  
Median   : 151975.4  
3rd Qu.: 182754.8  
Max      : 342985.1  
NAs      : 0 %
```

Name: f2

```
dim   : 1 52 1 1 1 1  
quant: age  
units: tonnes
```

```
Min      : 48874  
1st Qu.: 81541.75  
Mean     : 108403.7  
Median   : 110466  
3rd Qu.: 132758.5  
Max      : 169818  
NAs      : 0 %
```

FLIST METHODS

```
> getClassMethods("FLlist", "package:FLCore")
```

```
[1] "[<-"      "["         "[[<-"      "$<-"       "coerce"  
[6] "lapply"   "model.frame" "names"     "range"     "summary"  
[11] "window"
```

MODEL CLASSES

	class	parent	nSlots	virtual	child	distance
1	FLGrowth	FLModel	15	FALSE		
2	FLSR	FLModel	18	FALSE		

FLSR

Represents a stock-recruitment relationship and allows the estimation of its parameters.

```
> showClass("FLSR")
```

```
Class "FLSR" [package "FLCore"]
```

Slots:

Name:	rec	ssb	covar	logerror	model	logl	gr
Class:	FLQuant	FLQuant	FLQuants	logical	formula	function	function

Name:	initial	params	logLik	vcov	hessian	details	residuals
Class:	function	FLPar	logLik	array	array	list	FLArray

Name:	fitted	name	desc	range
Class:	FLArray	character	character	numeric

Extends:

Class "FLModel", directly

Class "FLComp", by class "FLModel", distance 2

FLSR EXAMPLE

```
> summary(nsher)
```

An object of class "FLSR"

Name: Autumn spawning herring in IV, V 3/4/2005 14:46

Description: 'rec' and 'ssb' slots obtained from a 'FLStock' object

Range:

Quant: age

```
rec          : [ 1 45 1 1 1 1 ], units = NA
ssb          : [ 1 45 1 1 1 1 ], units = NA
residuals    : [ 1 45 1 1 1 1 ], units = NA NA
fitted       : [ 1 45 1 1 1 1 ], units = NA
```

Model: rec ~ a * ssb * exp(-b * ssb)

<environment: 0x3558dc0>

Parameters:

```
params
iter   a      b
1 119.4 0.009027
```

Log-likelihood: 16.352(0)

Variance-covariance:

```
      a      b
a 258.66388793 1.838394e-02
b  0.01838394 2.002586e-06
```

FLSR METHODS

```
> getClassMethods("FLSR", "package:FLCore")
```

```
[1] "ab"          "covar<-" "covar"    "fmle"      "lowess"    "plot"      "rec<-"  
[8] "rec"         "spr0"     "ssb<-"    "ssb"       "summary"   "sv"
```

FLSR PLOT

NULL

