

# R-package **FME** : inverse modelling, sensitivity, Monte Carlo - applied to a steady-state model

Karline Soetaert  
NIOO-CEME  
The Netherlands

---

## Abstract

Rpackage **FME** (Soetaert 2009a) contains functions for model calibration, sensitivity, identifiability, and Monte Carlo analysis of nonlinear models.

This vignette, (`vignette("FMEsteady")`), applies **FME** to a partial differential equation, solved with a steady-state solver from package **rootSolve**

A similar vignette (`vignette("FMEdyna")`), applies the functions to a dynamic simulation model, solved with integration routines from package **deSolve**

A third vignette (`vignette("FMEother")`), applies the functions to a simple nonlinear model

`vignette("FMEcmc")` tests the Markov chain Monte Carlo (MCMC) implementation

*Keywords:* steady-state models, differential equations, fitting, sensitivity, Monte Carlo, identifiability, R.

---

## 1. A steady-state model of oxygen in a marine sediment

This is a simple model of oxygen in a marine (submersed) sediment, diffusing along a spatial gradient, with imposed upper boundary concentration oxygen is consumed at maximal fixed rate, and including a monod limitation.

See (Soetaert and Herman 2009) for a description of reaction-transport models.

The constitutive equations are:

$$\begin{aligned}\frac{\partial O_2}{\partial t} &= -\frac{\partial Flux}{\partial x} - cons \cdot \frac{O_2}{O_2 + k_s} \\ Flux &= -D \cdot \frac{\partial O_2}{\partial x} \\ O_2(x=0) &= upO2\end{aligned}$$

```
> par(mfrow=c(2,2))  
> require(FME)
```

First the model parameters are defined...

```
> pars <- c(upO2=360, # concentration at upper boundary, mmolO2/m3  
+          cons=80,   # consumption rate, mmolO2/m3/day
```

```
+          ks=1,          # O2 half-saturation ct, mmolO2/m3
+          D=1)          # diffusion coefficient, cm2/d
```

Next the sediment is vertically subdivided into 100 grid cells, each 0.05 cm thick.

```
> n <- 100                      # nr grid points
> dx <- 0.05    #cm
> dX <- c(dx/2,rep(dx,n-1),dx/2) # dispersion distances; half dx near boundaries
> X <- seq(dx/2,len=n,by=dx)     # distance from upper interface at middle of box
```

The model function takes as input the parameter values and returns the steady-state condition of oxygen. Function `steady.band` from package `rootSolve` ( (Soetaert 2009b)) does this in a very efficient way (see (Soetaert and Herman 2009)).

```
> O2fun <- function(pars)
+ {
+   derivs<-function(t,O2,pars)
+   {
+     with (as.list(pars),{
+       Flux <- -D* diff(c(upO2,O2,O2[n]))/dX
+       dO2 <- -diff(Flux)/dx-cons*O2/(O2+ks)
+       return(list(dO2,UpFlux = Flux[1],LowFlux = Flux[n+1]))
+     })
+   }
+   # Solve the steady-state conditions of the model
+   ox <- steady.band(y=runif(n),func=derivs,parms=pars,nspec=1,positive=TRUE)
+   data.frame(X=X,O2=ox$y)
+ }
```

The model is run

```
> ox<-O2fun(pars)
```

and the results plotted...

```
> plot(ox$O2,ox$X,ylim=rev(range(X)),xlab="mmol/m3",
+      main="Oxygen", ylab="depth, cm",type="l",lwd=2)
```

## 2. Global sensitivity analysis : Sensitivity ranges

The sensitivity of the oxygen profile to parameter `cons`, the consumption rate is estimated. We assume a normally distributed parameter, with mean = 80 (`parMean`), and a variance=100 (`parCovar`). The model is run 100 times (`num`).




Figure 1: The modeled oxygen profile - see text for R-code

```
> print(system.time(
+ Sens2 <- sensRange(parms=pars,func=O2fun,dist="norm",
+                     num=100,parMean=c(cons=80),parCovar=100)
+ ))
```

```
user  system elapsed
1.09   0.00   1.09
```

The results can be plotted in two ways:

```
> par(mfrow=c(1,2))
> plot(Sens2,xyswap=TRUE,xlab= "O2",
+       ylab="depth, cm",main="Sensitivity runs")
> plot(summary(Sens2),xyswap=TRUE,xlab= "O2",
+       ylab="depth, cm",main="Sensitivity ranges")
> par(mfrow=c(1,1))
```

### 3. Local sensitivity analysis : Sensitivity functions

Local sensitivity analysis starts by calculating the sensitivity functions

```
> O2sens <- sensFun(func=O2fun,parms=pars)
```

The summary of these functions gives information about which parameters have the largest effect (univariate sensitivity):

```
> summary(O2sens)
```




Figure 2: Results of the sensitivity run - left: all model runs, right: summary - see text for R-code

	value	scale	L1	L2	Mean	Min	Max	N
upO2	360	360	6.4	0.79	6.4	1.0e+00	11.7466	100
cons	80	80	8.1	1.14	-8.1	-2.2e+01	-0.0084	100
ks	1	1	2.2	0.37	2.2	1.2e-04	9.6137	100
D	1	1	8.1	1.14	8.1	8.4e-03	22.0312	100

In bivariate sensitivity the pair-wise relationship and the correlation is estimated and/or plotted:

```
> pairs(O2sens)
```

```
> cor(O2sens[,-(1:2)])
```


	upO2	cons	ks	D
upO2	1.0000000	-0.9687871	0.8139738	0.9687871
cons	-0.9687871	1.0000000	-0.9317287	-1.0000000
ks	0.8139738	-0.9317287	1.0000000	0.9317287
D	0.9687871	-1.0000000	0.9317287	1.0000000

Multivariate sensitivity is done by estimating the collinearity between parameter sets (Brun, Reichert, and Kunsch 2001).

```
> Coll <- collin(O2sens)
```

```
> Coll
```

	upO2	cons	ks	D	N	collinearity
1	1	1	0	0	2	6.5
2	1	0	1	0	2	2.7



```
> plot(Coll, log="y")
```

Assume both the oxygen flux at the upper interface and a vertical profile of oxygen has been measured.

```
> O2dat <- data.frame(x=seq(0.1,3.5,by=0.1),
+   y = c(279,260,256,220,200,203,189,179,165,140,138,127,116,
+   109,92,87,78,72,62,55,49,43,35,32,27,20,15,15,10,8,5,3,2,1,0))
> O2depth <- cbind(name="O2",O2dat)           # oxygen versus depth
> O2flux <- c(UpFlux=170)                     # measured flux
```

```
> O2fun2 <- function(pars)
+ {
```




Figure 4: collinearity - see text for R-code

```

+ derivs<-function(t,02,pars)
+ {
+   with (as.list(pars),{
+
+     Flux <- -D*diff(c(up02,02,02[n]))/dX
+     d02  <- -diff(Flux)/dx-cons*02/(02+ks)
+
+     return(list(d02,UpFlux = Flux[1],LowFlux = Flux[n+1]))
+   })
+ }
+
+ ox <- steady.band(y=runif(n),func=derivs,parms=pars,nspec=1,
+                   positive=TRUE,rtol=1e-8,atol=1e-10)
+
+ list(data.frame(x=X,02=ox$y),
+       UpFlux=ox$UpFlux)
+ }

```

The function used in the fitting algorithm returns an instance of type `modCost`. This is created by calling function `modCost` twice. First with the modeled oxygen profile, then with the modeled flux.

```

> Objective <- function (P)
+ {
+   Pars <- pars
+   Pars[names(P)]<-P
+   mod02 <- 02fun2(Pars)
+
+   # Model cost: first the oxygen profile
+   Cost  <- modCost(obs=02depth,model=mod02[[1]],x="x",y="y")

```

```

+
+ # then the flux
+ modF1 <- c(UpFlux=mod02$UpFlux)
+ Cost <- modCost(obs=02flux,model=modF1,x=NULL,cost=Cost)
+
+ return(Cost)
+ }

```

We first estimate the identifiability of the parameters, given the data:

```

> print(system.time(
+ sF<-sensFun(Objective,parms=parms)
+ ))

```

```

      user  system elapsed
    0.13    0.00    0.12

```

```

> summary(sF)

```

	value	scale	L1	L2	Mean	Min	Max	N
up02	360	360	4.25	0.97	4.25	0.5069	13.3	36
cons	80	80	3.68	0.99	-3.65	-15.3722	0.5	36
ks	1	1	0.40	0.14	0.40	-0.0069	3.1	36
D	1	1	3.68	0.99	3.68	0.0342	15.4	36

```

> collin(sF)

```

	up02	cons	ks	D	N	collinearity
1	1	1	0	0	2	8.6
2	1	0	1	0	2	3.1
3	1	0	0	1	2	8.7
4	0	1	1	0	2	4.2
5	0	1	0	1	2	50.6
6	0	0	1	1	2	4.2
7	1	1	1	0	3	14.2
8	1	1	0	1	3	50.8
9	1	0	1	1	3	14.7
10	0	1	1	1	3	50.6
11	1	1	1	1	4	51.0

The collinearity of the full set is too high, but as the oxygen diffusion coefficient is well known, it is left out of the fitting. The combination of the three remaining parameters has a low enough collinearity to enable automatic fitting. The parameters are constrained to be >0

```

> collin(sF,parset=c("up02","cons","ks"))

```

	up02	cons	ks	D	N	collinearity
1	1	1	1	0	3	14

```
> print(system.time(
+ Fit<-modFit(p=c(up02=360,cons=80,ks=1),
+             f=Objective,lower=c(0,0,0))
+             ))

      user  system elapsed
      0.85    0.00    0.84

> (SFit<-summary(Fit))

Parameters:
      Estimate Std. Error t value Pr(>|t|)
up02   292.937      2.104 139.241  <2e-16 ***
cons    49.686      2.367  20.991  <2e-16 ***
ks       1.297      1.363   0.951    0.348
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 4.401 on 33 degrees of freedom

Parameter correlation:
      up02   cons    ks
up02 1.0000 0.5791 0.2976
cons 0.5791 1.0000 0.9012
ks   0.2976 0.9012 1.0000
```

We next plot the residuals

```
> plot(Objective(Fit$par),xlab="depth",ylab="",main="residual",legpos="top")
```

and show the best-fit model

```
> Pars <- pars
> Pars[names(Fit$par)]<- Fit$par
> mod02 <- 02fun(Pars)

> plot(02depth$y,02depth$x,ylim=rev(range(02depth$x)),pch=18,
+      main="Oxygen-fitted", xlab="mmol/m3",ylab="depth, cm")
> lines(mod02$02,mod02$X)
```

## 5. Running a Markov chain Monte Carlo

We use the parameter covariances of previous fit to update parameters, while the mean squared residual of the fit is use as prior fo the model variance.

```
> Covar <- SFit$cov.scaled * 2.4^2/3
> s2prior <- SFit$modVariance
```






Figure 5: residuals - see text for R-code




Figure 6: Best fit model - see text for R-code

We run an adaptive Metropolis, making sure that ks does not become negative...

```
> print(system.time(
+ MCMC <- modMCMC(f=Objective,p=Fit$par,jump=Covar,niter=1000,ntrydr=2,
+               var0=s2prior,wvar0=1,updatecov=100,lower=c(NA,NA,0))
+ ))
```

number of accepted runs: 704 out of 1000 (70.4%)

```
user system elapsed
35.45    0.00    35.49
```

```
> MCMC$count
```

```
dr_steps    Alfasteps  num_accepted num_covupdate
      705         2115         704           9
```

Plotting the results is similar to previous cases.

```
> plot(MCMC,Full=TRUE)
```

```
> hist(MCMC,Full=TRUE)
```

```
> pairs(MCMC,Full=TRUE)
```

or summaries can be created:

```
> summary(MCMC)
```

```
          up02      cons          ks  var_model
mean 294.013547 51.960133 2.78151547 123.40841
sd    3.008842  3.412212 2.09147110 702.42953
min  285.712793 44.737945 0.02273058  1.71065
max  309.662747 69.901659 13.90217703 19488.96486
q025 292.277893 49.544951 1.24438890  10.55171
q050 293.714616 51.337096 2.34135552  23.52793
q075 295.388095 53.598523 3.78850131  59.78494
```

```
> cor(MCMC$pars)
```

```
          up02      cons          ks
up02 1.0000000 0.6583082 0.3788591
cons 0.6583082 1.0000000 0.8853622
ks    0.3788591 0.8853622 1.0000000
```

Note: we pass to sensRange the full parameter vector (**parms**) and the parameters sampled during the MCMC (**parInput**).




Figure 7: MCMC plot results - see text for R-code




Figure 8: MCMC histogram results - see text for R-code




Figure 9: MCMC pairs plot - see text for R-code




Figure 10: MCMC range plot - see text for R-code

```
> plot(summary(sensRange(parms=pars,parInput=MCMC$par,f=02fun,num=500)),
+       xyswap=TRUE)
> points(02depth$y,02depth$x)
```

## 6. Finally

This vignette is made with Sweave (Leisch 2002).

## References

- Brun R, Reichert P, Kunsch H (2001). “Practical identifiability analysis of large environmental simulation models.” *WATER RESOURCES RESEARCH*, **37**(4), 1015–1030.
- Leisch F (2002). “Sweave: Dynamic Generation of Statistical Reports Using Literate Data Analysis.” In W Härdle, B Rönz (eds.), “Compstat 2002 - Proceedings in Computational Statistics,” pp. 575–580. Physica Verlag, Heidelberg. ISBN 3-7908-1517-9, URL <http://www.stat.uni-muenchen.de/~leisch/Sweave>.
- Soetaert K (2009a). *FME: A Flexible Modelling Environment for inverse modelling, sensitivity, identifiability, monte carlo analysis*. R package version 1.0.
- Soetaert K (2009b). *rootSolve: Nonlinear root finding, equilibrium and steady-state analysis of ordinary differential equations*. R package version 1.4.
- Soetaert K, Herman PMJ (2009). *A Practical Guide to Ecological Modelling. Using Ras a Simulation Platform*. Springer. ISBN 978-1-4020-8623-6.

### Affiliation:

Karline Soetaert  
 Centre for Estuarine and Marine Ecology (CEME)  
 Netherlands Institute of Ecology (NIOO)  
 4401 NT Yerseke, Netherlands  
 E-mail: [k.soetaert@nioo.knaw.nl](mailto:k.soetaert@nioo.knaw.nl)  
 URL: <http://www.nioo.knaw.nl/users/ksoetaert>