

Package ‘forensim’

June 9, 2012

Type Package

Title Statistical tools for the interpretation of forensic DNA mixtures

Version 3.1

Date 2011-06-09

Author Hinda Haned <h.haned@nfi.minvenj.nl>

Maintainer Hinda Haned <h.haned@nfi.minvenj.nl>

Depends methods, tcltk,tcltk2,tkrplot

Description Statistical methods and simulation tools for the interpretation of forensic DNA mixtures

License GPL (>= 2)

LazyLoad yes

Collate zzz.R classes_definitions.R classes_constructors.R accessors.R
simufreqD.R simupopD.R AuxFunc.R changepop.R PE.R likelihood.R
likeestim.R mincontri.R A2.simu.R A3.simu.R A4.simu.R
mastermix.R N2Exact.R N2error.R simMixSNP.R wrapdataL.R
simPCR2.R simPCR2TK.R PV.R Hbsimu.R LR.R LRmixTK.R

Archs i386

R topics documented:

forensim-package	2
A2.simu	3
A3.simu	4
A4.simu	5
Accessors	6
changepop	7
Cmn	8
comb	9
dataL	10
findfreq	11
findmax	11
Hbsimu	12
lik	13

lik.loc	14
likestim	15
likestim.loc	17
likEvid	18
LR	19
LRmixTK	21
mastermix	21
mincontri	23
N2error	23
N2Exact	24
naomitab	25
nball	26
ngm	26
PE	27
PV	28
sgmNorway	29
simMixSNP	29
simPCR2	30
simPCR2TK	31
simufreqD	32
simugeno	33
simugeno constructor	34
simumix	35
simumix constructor	36
simupopD	37
strusa	39
strveneto	40
tabfreq	40
tabfreq constructor	41
Tu	42
virtualClasses	43
wrapdataL	43
Index	44

forensim-package

The forensim package

Description

forensim is dedicated to the interpretation of forensic DNA mixtures through statistical methods. It relies on three S4 classes that facilitate the manipulation and the storage of genetic data produced in forensic casework: [tabfreq](#), [simugeno](#) and [simumix](#).

[tabfreq](#) objects are used to store allele frequencies, [simugeno](#) objects are used to store genotypes and [simumix](#) objects are used to store DNA mixtures.

For more information about these classes type 'class ?tabfreq', 'class ?simugeno' and 'class ?simumix'.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

A2.simu*A Tcl/Tk graphical user interface for simple DNA mixtures resolution using allele peak heights or areas information when two alleles are observed at a given locus*

Description

The A2.simu function launches a Tcl/Tk graphical interface with functionalities devoted to two-person DNA mixtures resolution, when two alleles are observed at a given locus.

Usage

A2.simu()

Details

When two alleles are observed at a given locus in the DNA stain, seven genotype combinations are possible for the two contributors: (AA,AB), (AB,AB), (AA,BB), (AB,AA), (BB,AA), (AB,BB) and (BB,AB), where A and B are the two observed alleles (in ascending order of molecular weight). Having previously obtained an estimation for the mixture proportion, it is possible to reduce the number of possible genotype combinations by keeping those only supported by the observed data. This is achieved by computing the sum of square differences between the expected allelic ratio and the observed allelic ratio, for all possible mixture combinations. The likelihood of peak heights (or areas), given the combination of genotypes, is high if the residuals are low. Genotype combinations are thus selected according to the peak heights with the highest likelihoods.

The A2.simu() function launches a dialog window with three buttons:

- Plot simulations: plot of the residuals of each possible genotype combination for varying values of the mixture proportion across the interval [0.1, 0.9]. The observed mixture proportion is also reported on the plot.

- Simulation details: a matrix containing the simulation results. Simulation details and genotype combinations with the lowest residuals can be saved as a text file by clicking the "Save" button. It is also possible to choose specific paths and names for the save files.

- Genotypes filter: a matrix giving the mixture proportion conditional on the genotype combination. This conditional mixture proportion helps filter the most plausible genotypes among the seven possible combinations. The matrix can be saved as a text file by clicking the "Save" button. It is also possible to choose a specific path and a name for the save file.

Note

- Linux users may have to download the libtktable package to their system before using the A2.simu function. This is due to the Tktable widget, used in forensim, which is not (always) downloaded with the Tcl/Tk package.

- For the computational details, please see forensim tutorial at <http://forensim.r-forge.r-project.org/misc/forensim-tutorial.pdf>.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Gill P, Sparkes P, Pinchin R, Clayton, Whitaker J, Buckleton J. Interpreting simple STR mixtures using allele peak areas. *Forensic Sci Int* 1998;91:41-53.

See Also

[A3.simu](#): the three-allele model, and [A4.simu](#): the four-allele model

Examples

```
A2.simu()
```

A3.simu	<i>A Tcl/Tk graphical user interface for simple DNA mixtures resolution using allele peak heights or areas when three alleles are observed at a given locus</i>
---------	---

Description

The A3.simu function launches a Tcl/Tk graphical interface with functionalities devoted to two-person DNA mixtures resolution, when three alleles are observed at a given locus.

Usage

```
A3.simu()
```

Details

When three alleles are observed at a given locus in the DNA stain, twelve genotype combinations are possible for the two contributors: (AA,BC), (BB,AC), (CC,AB), (AB,AC), (BC,AC), (AB,BC), (BC,AA), (AC,BB), (AB,CC), (AC,AB), (AC,BC) and (BC,AB) where A, B and C are the three observed alleles (in ascending order of molecular weights). Having previously obtained an estimation for the mixture proportion, it is possible to reduce the number of possible genotype combinations by keeping those only supported by the observed data. This is achieved by computing the sum of square differences between the expected allelic ratio and the observed allelic ratio, for all possible mixture combinations. The likelihood of peak heights (or areas), given the combination of genotypes, is high if the residuals are low. Genotype combinations are thus selected according to the peak heights with the highest likelihoods.

The A3.simu() function launches a dialog window with three buttons:

-Plot simulations: plot of the residuals of each possible genotype combination for varying values of the mixture proportion across the interval [0.1, 0.9]. The observed mixture proportion is also reported on the plot.

-Simulation details: a matrix containing the simulation results. Simulation details and genotype combinations with the lowest residuals can be saved as a text file by clicking the "Save" button. It is also possible to choose specific paths and names for the save files.

-Genotypes filter: a matrix giving the mixture proportion conditional on the genotype combination. This conditional mixture proportion helps filter the most plausible genotypes among the twelve possible combinations. The matrix can be saved as a text file by clicking the "Save" button. It is also possible to choose a specific path and a name for the save file.

Note

-Linux users may have to download the libtktable package to their system before using the A3.simu function. This is due to the Tktable widget, used in forensim, which is not (always) downloaded with the Tcl/Tk package.

-For the computational details, please see forensim tutorial at <http://forensim.r-forge.r-project.org/misc/forensim-tutorial.pdf>.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Gill P, Sparkes P, Pinchin R, Clayton, Whitaker J, Buckleton J. Interpreting simple STR mixtures using allele peak areas. *Forensic Sci Int* 1998;91:41-53.

See Also

[A2.simu](#): the two-allele model, and [A4.simu](#): the four-allele model

Examples

```
A3.simu()
```

A4.simu	<i>A Tcl/Tk graphical user interface for simple DNA mixtures resolution using allele peak heights or areas when four alleles are observed at a given locus</i>
---------	--

Description

The A4.simu function launches a Tcl/Tk graphical interface with functionalities devoted to two-person DNA mixtures resolution, when four alleles are observed at a given locus.

Usage

```
A4.simu()
```

Details

When four alleles are observed at a given locus in the DNA stain, six genotype combinations are possible for the two contributors: (AB,CD),(AC,BD),(AD,BC),(BC,AD),(BD,AC) and (CD,AB) where A, B, C and D are the four observed alleles (in ascending order of molecular weights). Having previously obtained an estimation for the mixture proportion, it is possible to reduce the number of possible genotype combinations by keeping those only supported by the observed data. This is achieved by computing the sum of square differences between the expected allelic ratio and the observed allelic ratio, for all possible mixture combinations. The likelihood of peak heights (or areas), given the combination of genotypes, is high if the residuals are low. Genotype combinations are thus selected according to the peak heights with the highest likelihoods.

The `A4.simu()` function launches a dialog window with three buttons:

- Plot simulations: plot of the residuals of each possible genotype combination for varying values of the mixture proportion across the interval [0.1, 0.9]. The observed mixture proportion is also reported on the plot.
- Simulation details: a matrix containing the simulation results. Simulation details and genotype combinations with the lowest residuals can be saved as a text file by clicking the "Save" button. It is also possible to choose specific paths and names for the save files.
- Genotypes filter: a matrix giving the mixture proportion conditional on the genotype combination. This conditional mixture proportion helps filter the most plausible genotypes among the six possible combinations. The matrix can be saved as a text file by clicking the "Save" button. It is also possible to choose a specific path and a name for the save file.

Note

- Linux users may have to download the `libtktable` package to their system before using the `A4.simu` function. This is due to the `Tktable` widget, used in `forensim`, which is not (always) downloaded with the `Tcl/Tk` package.
- For the computational details, please see `forensim` tutorial at <http://forensim.r-forge.r-project.org/misc/forensim-tutorial.pdf>.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Gill P, Sparkes P, Pinchin R, Clayton, Whitaker J, Buckleton J. Interpreting simple STR mixtures using allele peak areas. *Forensic Sci Int* 1998;91:41-53.

See Also

[A2.simu](#): the two-allele model, and [A3.simu](#): the three-allele model

Examples

```
A4.simu()
```

Accessors

Accessors for forensim objects

Description

Accessors for `forensim` objects: [simugeno](#), [simumix](#) and [tabfreq](#). "`\$`" and "`\$<-`" are used to access the slots of an object, they are equivalent to "`@`" and "`@<-`".

Value

A [simugeno](#), a [simumix](#) or a [tabfreq](#) object.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

Examples

```
data(strusa)
class(strusa)

strusa@pop.names
#equivalent
strusa$pop.names
```

changepop

Function to change population-related information in forensim objects

Description

The changepop function changes population-related information in [tabfreq](#), [simugeno](#) and [simumix](#) objects

Usage

```
changepop(obj, oldpop, newpop)
```

Arguments

obj	a forensim object, either a tabfreq , a simugeno or a simumix object
oldpop	a character vector giving the population names to be changed
newpop	a character vector giving the new population names

Value

a [forensim](#) object where the slots containing population-related information have been modified

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

Examples

```
data(strveneto)
tab1 <- simugeno(strveneto,n=100)
tab2 <- changepop(tab1,"Veneto","VENE")
tab1$pop.names
tab2$pop.names
```

Cmn	<i>The number of all possible combinations of m elements among n with repetitions</i>
-----	---

Description

The number of all possible combinations of m elements among n with repetitions.

Usage

```
Cmn(m, n)
```

Arguments

m	the m elements to combine among n
n	the n elements from which to combine m elements with repetitions

Details

There are $(n+m-1)!/(m!(n-1)!)$ ways to combine m elements among n with repetitions.

Note

Cmn was implemented as an auxiliary function for the [datal](#) function which computes the likelihood of the observed alleles in a mixed DNA stain conditional on the number of contributors.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[comb](#) for all possible combinations of m elements among n with repetitions

Examples

```
Cmn(2, 3)
comb(2, 3)
```

comb	<i>Generate all possible combinations of m elements among n with repetitions</i>
------	--

Description

Generate all possible combinations of m elements among n with repetitions.

Usage

```
comb(m, n)
```

Arguments

m	the number of elements to combine
n	the number of elements from which to combine the m elements

Details

There are $(n+m-1)/(m!(n-1)!)$ ways to combine m elements among n with repetitions, `comb` generates all these possible combinations.

Value

A matrix of $(n+m-1)/(m!(n-1)!)$ rows, and n columns, each row is a possible combination of m elements among n .

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[Cmn](#) for the calculation of the number of all possible combinations of m elements among n with repetitions

Examples

```
#combine 2 objects among 3 with repetitions
Cmn(2,3)
comb(2,3)
```

dataL	<i>Generic formula of the likelihood of the observed alleles in a mixture conditional on the number of contributors for a specific locus</i>
-------	--

Description

The function `dataL` gives the likelihood of a set of alleles observed at a specific locus conditional on the number of contributors that gave these alleles. Calculation is based upon the frequencies of the observed alleles.

Usage

```
dataL(x = 1, p, theta = 0)
```

Arguments

<code>x</code>	an integer giving the number of contributors
<code>p</code>	a numeric vector giving the frequencies of the observed alleles in the mixture
<code>theta</code>	a float in $[0,1[$. <code>theta</code> is equivalent to Wright's F_{st} . In case of population sub-division, it allows a correction of the allele frequencies in the subpopulation of interest

Note

`dataL` function has several similarities with the `Pevd.gen` function of the *forensic* package which computes the probability of the DNA evidence, `dataL` implements a particular case of this probability. Please see <http://cran.r-project.org/web/packages/forensic/>

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Haned H, Pene L, Lobry JR, Dufour AB, Pontier D. Estimating the number of contributors to forensic DNA mixtures: Does maximum likelihood perform better than maximum allele count? *J Forensic Sci*, accepted 2010.

Curran JM, Triggs CM, Buckleton J, Weir BS. Interpreting DNA Mixtures in Structured Populations. *J Forensic Sci* 1999;44(5): 987-995

See Also

[lik.loc](#) and [lik](#) for calculating the likelihood of a given `simumix` object

Examples

```
#likelihood of observing two alleles at frequencies 0.1 and 0.01 when the number of
#contributors is 2, in two cases: theta=0 and theta=0.03
dataL(x=2,p=c(0.1,0.01), theta=0)
dataL(x=2,p=c(0.1,0.01), theta=0.03)
```

findfreq	<i>Finds the allele frequencies of a mixture from a tabfreq object</i>
----------	--

Description

The findfreq function finds the allele frequencies of a mixture stored in a simumix object, from a given tabfreq object. If the tabfreq object contains multiple populations, a reference population from which to extract the frequencies must be specified.

Usage

```
findfreq(mix, freq, refpop = NULL)
```

Arguments

mix	a simumix object
freq	a tabfreq object from which to extract the allele frequencies of the mixture
refpop	a factor giving the reference population in tabfreq from which to extract the allele frequencies

Value

A list giving the allele frequencies for each locus.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[simumix](#)

Examples

```
data(strusa)
s2<-simumix(simugeno(strusa,n=c(0,2000,0)),ncontri=c(0,2,0))
findfreq(s2,strusa,refpop="Cauc")
```

findmax	<i>Function to find the maximum of a vector and its position</i>
---------	--

Description

The findmax function finds the maximum of a vector and its position.

Usage

```
findmax(vec)
```

Arguments

vec a numeric vector

Details

findmax finds the maximum value of a vector and its position.

Value

A matrix of two columns:
max the position of the maximum in vec
maxval the maximum

Note

findmax is an auxiliary function for the [datal](#) function, used to compute the likelihood of the observed alleles in a mixed DNA stain given the number of contributors.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

Examples

```
findmax(1:10)
```

Hbsimu

A Tcl/Tk simulator of the heterozygous balance

Description

Hbsimu is a user-friendly graphical interface simulating the heterozygous balance of heterozygous profiles generated according to the simulation model described in Gill et al. (2005)

Usage

```
Hbsimu()
```

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Gill P, Curran J and Elliot K. A graphical simulation model of the entire DNA process associated with the analysis of short tandem repeat loci. *Nucleic Acids Research* 2005, 33(2): 632-643.

Examples

```
Hbsimu()
```

lik	<i>Likelihood of the observed alleles at different loci in a DNA mixture conditional on the number of contributors to the mixture</i>
-----	---

Description

The `lik` function computes the likelihood of the observed alleles in a forensic DNA mixture, for a set of loci, conditional on the number of contributors to the mixture. The overall likelihood is computed as the product of loci likelihoods.

Usage

```
lik(x = 1, mix, freq, reipop = NULL, theta = NULL, loc=NULL)
```

Arguments

<code>x</code>	the number of contributors to the DNA mixture, default is 1
<code>mix</code>	a <code>simumix</code> object which contains the mixture to be analyzed
<code>freq</code>	a <code>tabfreq</code> object from which to extract the allele frequencies
<code>reipop</code>	a factor giving the reference population in <code>tabfreq</code> from which to extract the allele frequencies. This argument is used only if <code>freq</code> contains allele frequencies for multiple populations, otherwise it is by default set to <code>NULL</code>
<code>theta</code>	a float from $[0,1[$ giving Wright's F_{st} coefficient. <code>theta</code> accounts for population subdivision while computing the likelihood of the data
<code>loc</code>	loci for which the overall likelihood shall be computed. Default (<code>NULL</code>) corresponds to all loci

Details

`lik` computes the likelihood of the alleles observed at all loci conditional on the number of contributors. This function implements the general formula for the interpretation of DNA mixtures in case of population subdivision (Curran et al, 1999), in the particular case where all contributors are unknown and belong to the same subpopulation.

The likelihood for multiple loci is computed as the product of loci likelihoods.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Haned H, Pene L, Lobry JR, Dufour AB, Pontier D. Estimating the number of contributors to forensic DNA mixtures: Does maximum likelihood perform better than maximum allele count? *J Forensic Sci*, accepted 2010.

Curran JM, Triggs CM, Buckleton J, Weir BS. Interpreting DNA Mixtures in Structured Populations. *J Forensic Sci* 1999;44(5): 987-995

See Also

[lik.loc](#) for the likelihood per locus, [likestim](#) and [likestim.loc](#) for the estimation of the number of contributors to a DNA mixture through likelihood maximization

Examples

```
data(strusa)
#simulation of 1000 genotypes from the African American allele frequencies
gen<-simugeno(strusa,n=c(1000,0,0))
#3-person mixture
mix3<-simumix(gen,ncontri=c(3,0,0))
sapply(1:3, function(i) lik(x=i,mix3, strusa, refpop="Afri"))
```

lik.loc	<i>Likelihood per locus of the observed alleles in a DNA mixture conditional on the number of contributors to the mixture</i>
---------	---

Description

The `lik.loc` function computes the likelihood of the observed data in a forensic DNA mixture, for each of the loci involved, conditional on the number of contributors to the mixture.

Usage

```
lik.loc(x = 1, mix, freq, refpop = NULL, theta = NULL, loc=NULL)
```

Arguments

<code>x</code>	the number of contributors to the DNA mixture
<code>mix</code>	a <code>simumix</code> object which contains the mixture to be analyzed
<code>freq</code>	a <code>tabfreq</code> object from which to extract the allele frequencies
<code>refpop</code>	a factor giving the reference population in <code>tabfreq</code> from which to extract the allele frequencies
<code>theta</code>	a float from $[0,1[$ giving Wright's F_{st} coefficient. <code>theta</code> accounts for population subdivision while computing the likelihood of the data.
<code>loc</code>	the loci for which the likelihood shall be computed. Default (set to <code>NULL</code>) corresponds to all loci.

Details

`lik.loc` computes the likelihood per locus of the observed alleles. This function implements the general formula for the interpretation of DNA mixtures in case of subdivided populations (Curran et al, 1999), in the particular case where all contributors are unknown and belong to the same subpopulation.

The F_{st} coefficient given in the `theta` argument allows accounting for population subdivision when all contributors belong to the same subpopulation.

Value

The function `lik.loc` returns a vector, of length the number of loci in `loc`, giving the likelihood of the data for each locus.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Haned H, Pene L, Lobry JR, Dufour AB, Pontier D. Estimating the number of contributors to forensic DNA mixtures: Does maximum likelihood perform better than maximum allele count? *J Forensic Sci*, accepted 2010.

Curran JM, Triggs CM, Buckleton J, Weir BS. Interpreting DNA Mixtures in Structured Populations. *J Forensic Sci* 1999;44(5): 987-995

See Also

[lik](#) for the overall loci likelihood, [likestim](#) and [likestim.loc](#) for the estimation of the number of contributors to a DNA mixture through likelihood maximization

Examples

```
data(strusa)
#simulation of 1000 genotypes from the Caucasian allele frequencies
gen<-simugeno(strusa,n=c(0,100,0))

#4-person mixture
mix4 <- simumix(gen,ncontri=c(0,4,0))
lik.loc(x=2,mix4, strusa, refpop="Cauc")
lik.loc(x=2,mix4, strusa, refpop="Afri")
#You may also want to try:
#likestim(mix4,strusa,refpop="Cauc")
```

likestim	<i>Maximum likelihood estimation of the number of contributors to a forensic DNA mixture for a set of loci</i>
----------	--

Description

The likestim function gives multiloci estimation of the number of contributors to a forensic DNA mixture using likelihood maximization.

Usage

```
likestim(mix, freq, refpop = NULL, theta = NULL, loc=NULL)
```

Arguments

mix	a simumix object
freq	a tabfreq object containing the allele frequencies to use for the calculation
refpop	the reference population from which to extract the allele frequencies used in the likelihood calculation. If tabfreq contains more than one population, refpop must be specified, otherwise, refpop is set to default (NULL).

theta	a float from [0,1[giving Wright's Fst coefficient. theta accounts for population subdivision while computing the likelihood of the data.
loc	loci to be considered in the estimation. Default (set to NULL) corresponds to all loci.

Details

The number of contributors which maximizes the likelihood of the data observed in the mixture is searched in the discrete interval [1,6]. In most cases this interval is a plausible range for the number of contributors.

Value

A matrix of dimension 1 x 2, the first column, max, gives the maximum likelihood estimation of the number of contributors, the second column gives the corresponding likelihood value maxvalue.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Haned H, Pene L, Lobry JR, Dufour AB, Pontier D. Estimating the number of contributors to forensic DNA mixtures: Does maximum likelihood perform better than maximum allele count? *J Forensic Sci*, accepted 2010.

Egeland T, Dalen I, Mostad PF. Estimating the number of contributors to a DNA profile. *Int J Legal Med* 2003, 117: 271-275

Curran JM, Triggs CM, Buckleton J, Weir BS. Interpreting DNA Mixtures in Structured Populations. *J Forensic Sci* 1999, 44(5): 987-995

See Also

[likestim.loc](#) for maximum of likelihood estimations per locus

Examples

```
data(strusa)
#simulation of 1000 genotypes from the Hispanic allele frequencies
gen<-simugeno(strusa,n=c(0,0,100))
#4-person mixture
mix4 <- simumix(gen,ncontri=c(0,0,4))
likestim(mix4,strusa,refpop="Hisp")
```

likestim.loc	<i>Maximum likelihood estimation per locus of the number of contributors to forensic DNA mixtures.</i>
--------------	--

Description

The likestim.loc function returns the estimation of the number of contributors, at each locus, obtained by maximizing the likelihood.

Usage

```
likestim.loc(mix, freq, reffpop = NULL, theta = NULL, loc = NULL)
```

Arguments

mix	a simumix object
freq	a tabfreq object containing the allele frequencies to use for the calculation
reffpop	the reference population from which to extract the allele frequencies used in the likelihood calculation. Default set to NULL, if tabfreq contains more than one population, reffpop must be specified
theta	a float from [0,1[giving Wright's Fst coefficient. theta accounts for population subdivision while computing the likelihood of the data.
loc	loci to be considered in the estimation. Default (set to NULL) corresponds to all loci.

Details

The number of contributors which maximizes the likelihood of the data observed in the mixture is searched in the discrete interval [1,6]. In most cases this interval is a plausible range for the number of contributors.

Value

A matrix of dimension loc x 2. The first column, max, gives the maximum likelihood estimation of the number of contributors for each locus in row. The second column, maxvalue, gives the corresponding likelihood value.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Haned H, Pene L, Lobry JR, Dufour AB, Pontier D. Estimating the number of contributors to forensic DNA mixtures: Does maximum likelihood perform better than maximum allele count? *J Forensic Sci*, accepted 2010.

Egeland T , Dalen I, Mostad PF. Estimating the number of contributors to a DNA profile. *Int J Legal Med* 2003, 117: 271-275

Curran, JM , Triggs CM, Buckleton J , Weir BS. Interpreting DNA Mixtures in Structured Populations. *J Forensic Sci* 1999, 44(5): 987-995

See Also

[likestim](#) for multiloci estimations

Examples

```
data(strusa)
#simulation of 1000 genotypes from the Hispanic allele frequencies
gen<-simugeno(strusa,n=c(0,0,100))
#4-person mixture
mix4 <- simumix(gen,ncontri=c(0,0,4))
likestim.loc(mix4,strusa,refpop="Hisp")
```

likEvid

Likelihood of DNA evidence conditioned on a given hypothesis

Description

likEvid allows the calculation of likelihood for a piece of DNA evidence, for any number of replicates, any number of contributors, and when drop-in and drop-out are possible.

Usage

```
likEvid(Repliste, T, V, x, theta, prDHet, prDHom, prC, freq)
```

Arguments

Repliste	list of the vectors of alleles present at a given locus for any number of replicates. If there are two replicates, showing alleles 12,13, and 14 respectively, then Repliste should be given as list(c(12,13),14). If a replicate is empty, set to NULL. For example, replicates (12,13) and and one empty replicate must be given as: list(c(12,14),NULL).
T	vector of genotypes for the known contributors under Hp. Genotype 12/17 should be given as a vector c(12,17) and genotypes 12/17,14/16, should be given as a unique vector: c(12,17,14,16). If T is empty, set to NULL.
V	vector of genotypes for the known non-contributors (see References section) under Hp. See T for format.)
x	Number of unknown individuals under H. Set to 0 if there are no unknown contributors.
theta	thete correction, value must be taken in [0,1)
prDHet	probability of dropout for heterozygotes. It is possible to assign different values per contributor. In this case, prDHet must be a vector, of length the number of contributors in T + x, and the probabilities must be given in this order. if the probability of dropout for T is d1, and for the unknown is d2, then prDHet=(d1,d2). In case T is not a heterozygote, the given vector must still be of length length(T) +x, but the given value for T does not matter, because it won't be used, the value in prDHom is used instead. This is a bit ad hoc and an improvement is currently under development.

prDHom	probability of dropout for homozygotes. See description of argument PrDHom.
prC	probability of drop-in applied per locus
freq	vector of the corresponding allele frequencies of the analysed locus in the target population

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

- Gill, P.; Kirkham, A. & Curran, J. LoComatioN: A software tool for the analysis of low copy number DNA profiles *Forensic Science International*, 2007, 166(2-3), 128-138
- Curran, J. M.; Gill, P. & Bill, M. R. Interpretation of repeat measurement DNA evidence allowing for multiple contributors and population substructure *Forensic Science International*, 2005, 148, 47-53

See Also

[LRmixTK](#)

Examples

```
#load allele frequencies
library(forensim)
data(ngm)
#create vector of allele frequencies
d10<-ngm$tab$D10
# evaluate the evidence under Hp; contributors are the suspect and one unknown,
# dropout probabilities for the suspect and the unknown are the same: 0.2 for heterozygotes,
# and 0.1 for homozygotes.
likEvid(Repliste=list(c(12,13,14)),T=c(12,13),V=NULL,x=1,theta=0,prDHet=c(0.2,0.2),prDHom=c(0.04,0.04),prC=0,freq=freq)
# evaluate the evidence under Hd; contributors are two unknown people, the dropout
# probabilities for the unknowns is kept the same under Hd
likEvid(Repliste=list(c(12,13,14)),T=0,V=NULL,x=2,theta=0,prDHet=c(0.2,0.2),prDHom=c(0.04,0.04),prC=0,freq=freq)
```

LR	<i>Likelihood ratio for DNA evidence interpretation (2): a sophisticated version of function LR()</i>
----	---

Description

LR Allows the calculation of likelihood ratios for a piece of DNA evidence, for any number of replicates, any number of contributors, and when drop-in and drop-out are possible.

Usage

```
LR(Repliste, Tp, Td, Vp, Vd, xp, xd, theta, prDHet, prDHom, prC, freq)
```

Arguments

Repliste	list of the vectors of alleles present at a given locus for any number of replicates. If there are two replicates, showing alleles 12,13, and 14 respectively, then Repliste should be given as list(c(12,13),14). If a replicate is empty, set to NULL. For example, replicates (12,13) and one empty replicate must be given as: list(c(12,14),NULL).
Tp	vector of genotypes for the known contributors under Hp. Genotype 12/17 should be given as a vector c(12,17) and genotypes 12/17,14/16, should be given as a unique vector: c(12,17,14,16).
Td	vector of genotypes for the known contributors under Hd. Should be in the same format as Tp. If there are no known contributors under Hd, then set Td to NULL.
Vp	vector of genotypes for the known non-contributors (see References section) under Hp. See Tp for format.)
Vd	vector of genotypes for the known non-contributors (see References section) under Hd. Should be in the same format than Vp, if empty, set to NULL.
xp	Number of unknown individuals under Hd. Set to 0 if there are no unknown contributors.
xd	Number of unknown individuals under Hd. Set to 0 if there are no unknown contributors.
theta	thete correction, value must be taken in [0,1)
prDHet	probability of dropout for heterozygotes. It is possible to assign different values per contributor. In this case, prDHet must be a vector, of length the number of contributors in T + x, and the probabilities must be given in this order. if the probability of dropout for T is d1, and for the unknown is d2, then prDHet=(d1,d2). In case T is not a heterozygote, the given vector must still be of length length(T) +x, but the given value for T does not matter, because it won't be used, the value in prDHom is used instead. This is a bit ad hoc and an improvement is currently under development.
prDHom	probability of dropout for homozygotes. See description ofr argument PrDHom.
prC	probability of drop-in applied per locus
freq	vector of the corresponding allele frequencies of the analysed locus in the target population

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

- Gill, P.; Kirkham, A. & Curran, J. LoComatioN: A software tool for the analysis of low copy number DNA profiles *Forensic Science International*, 2007, 166(2-3), 128-138
- Curran, J. M.; Gill, P. & Bill, M. R. Interpretation of repeat measurement DNA evidence allowing for multiple contributors and population substructure *Forensic Science International*, 2005, 148, 47-53

See Also

[LRmixTK](#)

Examples

```
#load allele frequencies
library(forensim)
data(ngm)
#create vector of allele frequencies
d10<-ngm$tab$D10
# heterozygote dropout probability (resp. homozygote) is set to 0.2 for all
# contributors (0.04 for homozygotes)
LR(Repliste=list(c(12,13,14)),Tp=c(12,13),Td=0,Vp=0,Vd=0,xd=2,xp=1,theta=0,prDHet=c(0.2,0.2),
prDHom=c(0.04,0.04),prC=0,freq=d10)
```

LRmixTK

GUI for the LR function

Description

User-friendly graphical user interface for the LR calculator LR.

Usage

```
LRmixTK()
```

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

mastermix

*A Tcl/Tk graphical user interface for simple DNA mixtures resolution
using allele peak heights/ or areas information*

Description

The mastermix function launches a Tcl/Tk graphical user interface dedicated to the resolution of two-person DNA mixtures using allele peak heights/ or areas information. mastermix is the implementation of a method developed by Gill et al (see the references section), and previously programmed into an Excel macro by Dr. Peter Gill.

Usage

```
mastermix()
```

Details

mastermix is a Tcl/Tk graphical user interface implementing a method developed by Gill et al (1998) for simple mixtures resolution, using allele peak heights or areas information.

This method searches through simulation the most likely combination(s) of the contributors' genotypes. Having previously obtained an estimation for the mixture proportion, it is possible to reduce the number of possible genotype combinations by keeping only those supported by the observed data. This is achieved by computing the sum of square differences between the expected allelic ratio and the observed allelic ratio, for all possible mixture combinations. The likelihood of peak heights (or areas), conditional on the combination of genotypes, is high if the residuals are low. Genotype combinations are thus selected according to the peak heights with the highest (conditioned) likelihoods.

mastermix offers a graphical representation of the simulation for three models:

- The two allele model: at a given locus, two alleles are observed in the DNA stain.
- The three allele model: at a given locus, three alleles are observed in the DNA stain.
- The four allele model: at a given locus, four alleles are observed in the DNA stain.

A left-click on each button launches a simulation dialog window for the corresponding model, while a right-click opens the corresponding help page.

Note

- Each implemented model can either be launched using the mastermix interface, or the [A2.simu](#), [A3.simu](#) and [A4.simu](#) functions, depending on the considered model.
- For the computational details, please see forensim tutorial at <http://forensim.r-forge.r-project.org/misc/forensim-tutorial.pdf>.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Gill P, Sparkes P, Pinchin R, Clayton, Whitaker J, Buckleton J. Interpreting simple STR mixtures using allele peak areas. *Forensic Sci Int* 1998;91:41-5.

See Also

[A2.simu](#), [A3.simu](#) and [A4.simu](#)

Examples

```
mastermix()
```

mincontri	<i>Minimum number of contributors required to explain a forensic DNA mixture</i>
-----------	--

Description

mincontri gives the minimum number of contributors required to explain a forensic DNA mixture. This method is also known as the maximum allele count as it relies on the maximum number of alleles showed through all available loci

Usage

```
mincontri(mix, loc = NULL)
```

Arguments

mix	a simumix object
loc	the loci to consider for the calculation of the minimum of contributors, default (NULL) corresponds to all loci

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[likestim](#) for the estimation of the number of contributors through likelihood maximization

Examples

```
data(strusa)
#simulation of 1000 genotypes from the African American allele frequencies
gen<-simugeno(strusa,n=c(1000,0,0))
#5-person mixture
mix5<-simumix(gen,ncontri=c(5,0,0))
#compare
likestim(mix5, strusa, refpop="Afri")
mincontri(mix5)
```

N2error	<i>Calculates exact error for maximum allele count for two markers</i>
---------	--

Description

The maximum allele count principle leads to wrong conclusion for two contributors if only a maximum of one or two alleles is seen. This probability of error is calculated.

Usage

```
N2error(dat)
```

Arguments

dat a data frame, first column gives the alleles size, remaining columns give their frequencies

Value

The probability of error is returned.

Author(s)

Thore Egeland <Thore.Egeland@medisin.uio.no>

Examples

```
#Example based on 15 markers of Tu data
library(forensim)
data(Tu)
N2error(Tu)
```

N2Exact

Calculates exact allele distribution for 2 contributors

Description

The distribution of N, the number of alleles showing is calculated exactly assuming 2 contributors. Theta-correction is not implemented. The function may be used to check accuracy of simulations and indicate required number of simulations for one example.

Usage

N2Exact(p)

Arguments

p vector of allele frequencies. Must sum to 1. Default: for uniformly distributed alleles.

Value

Returns $P(N=i)$ for $i=1,2,3,4$

Author(s)

Thore Egeland <Thore.Egeland@medisin.uio.no>

Examples

```
#Distribution for a marker with 20 alleles of equal frequency
N2Exact(p=rep(0.05,20))
```

naomitab*Handling of missing values in a data frame*

Description

naomitab handles missing values (NA) in a data frame: it returns a list of the columns where NAs have been removed.

Usage

```
naomitab(tab)
```

Arguments

tab a data frame

Value

Returns a list of length the number of columns in tab where each component is a column of tab, and the values are the corresponding rows where NAs have been removed.

Note

This function was designed to handle missing values in data frames in the format of the Journal of Forensic Sciences for population genetic data: allele names are given in the first column, and frequencies for a given allele are read in rows for different loci. When a given allele is not observed, the value is coded NA (originally coded "-" in the journal).

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[tabfreq](#)

Examples

```
data(Tu)
naomitab(Tu)
```

nball	<i>Number of alleles in a mixture</i>
-------	---------------------------------------

Description

nball gives the number of alleles of a simumix object.

Usage

```
nball(mix, byloc = FALSE)
```

Arguments

mix	a simumix object
byloc	a logical indicating whether the number of alleles must be calculated by locus or for all loci (default)

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[simumix](#)

Examples

```
data(strusa)
#simulating 100 genotypes with allele frequencies from the African American population
gaa<-simugeno(strusa,n=c(100,0,0))
#simulating a 4-person mixture
maa4<-simumix(gaa,ncontri=c(4,0,0))
nball(maa4,byloc=TRUE)
```

ngm	<i>Allele frequencies for the new generation markers NGM, for the Caucasian US population</i>
-----	---

Description

Allele frequencies for 15 autosomal short tandem repeats loci in the American Caucasian population.

Usage

```
data(ngm)
```

References

Budowle, B.; Ge, J.; Chakraborty, R.; Eisenberg, A.; Green, R.; Mulero, J.; Lagace, R. & Hennessy, L. Population genetic analyses of the NGM STR loci International Journal of Legal Medicine, 2011, 1-9

Examples

```
library(forensim)
data(ngm)
boxplot(ngm$tab)
```

PE

*The random man exclusion probability***Description**

Computes the random man exclusion probability of a mixture stored in a `simumix` object

Usage

```
PE(mix, freq, refpop = NULL, theta = 0, byloc = FALSE)
```

Arguments

<code>mix</code>	a <code>simumix</code> object
<code>freq</code>	a <code>tabfreq</code> object giving the allele frequencies from which to compute the exclusion probability
<code>refpop</code>	character giving the reference population, used only if <code>freq</code> contains allele frequencies for multiple populations
<code>theta</code>	a float from $[0,1[$ giving Wright's F_{st} coefficient. <code>theta</code> accounts for population subdivision while computing the likelihood of the data.
<code>byloc</code>	logical, if <code>TRUE</code> , than the exclusion probability is computed per locus, if <code>FALSE</code> (default), the calculations are done for all loci simultaneously

Details

PE gives the exclusion probability at a locus, or at several loci when conditions for Hardy Weinberg are met. If this condition is not met in the population, than a value for `theta` must be supplied to take into account dependencies between alleles. The formula of the exclusion probability that allows taking into account departure from Hardy Weinberg proportions due to population subdivision was provided by Bruce Weir, please see the references section.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Clayton T, Buckleton JS. Mixtures. In: Buckleton JS, Triggs CM, Walsh SJ, editors. Forensic DNA Interpretation. CRC Press 2005;217-74

Examples

```
data(strusa)
geno1<-simugeno(strusa,n=c(0,0,100))
mix2 <-simumix(geno1,ncontri=c(0,0,2))
PE(mix2,strusa,"Hispanic",byloc=TRUE)
```

PV	<i>Predictive value of the maximum likelihood estimator of the number of contributors to a DNA mixture</i>
----	--

Description

The PV function implements the predictive value of the maximum likelihood estimator of the number of contributors to a DNA mixture

Usage

```
PV(mat, prior)
```

Arguments

mat	matrix giving the estimates of the conditional probabilities that the maximum likelihood estimator classifies a given stain as a mixture of i contributors given that there are k contributor(s) to the stain. Estimates i must be given in columns for each possible value of the number of contributors given in rows.
prior	numeric vector giving the prior probabilities of encountering a mixture of i contributors. prior must be of length the number of rows in mat.

Value

Vector of the predictive values

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Haned H., Pene L., Sauvage F., Pontier D., The predictive value of the maximum likelihood estimator of the number of contributors to a DNA mixture, submitted, 2010.

See Also

maximum likelihood estimator [likestim](#)

Examples

```
# the following examples reproduce some of the calculations appearing
# in the article cited above, for illustrative purpose, the maximum
# number of contributors is set here to 5
#matcondi: Table 2 in Haned et al. (2010)
matcondi<-matrix(c(1,rep(0,4),0,0.998,0.005,0,0,0,0.002,0.937,0.067,0,0,0,0.058,
0.805,0.131,rep(0,3),0.127,0.662,rep(0,3),0.001,0.207),ncol=6)
#prior defined by a forensic expert (Table 3 in Haned et al., 2010)
prior1<-c(0.45,0.04,0.30,0.15,0.06)
#uniform prior, for each mixture type, the probability of occurrence is 1/5,
#5 being the threshold for the number of contributors
prior2<-c(rep(1/5,5))
#predictive values for prior1
```

```
PV(matcondi,prior1)
#for prior2
PV(matcondi, prior2)
```

sgmNorway

Allele frequencies for the new generation markers sgm, for the Norwegian population

Description

Allele frequencies for 10 autosomal short tandem repeats loci in the Norwegian population.

Usage

```
data(sgmNorway)
```

References

Andreassen, R., S. Jakobsen, and Mevaag, B., Norwegian population data for the 10 autosomal STR loci in the AMPF1STR(R) SGM Plus(TM) system. Forensic Science International, 2007. 170(1): p. 59-61.

simMixSNP

Simulates SNP mixtures

Description

Simulates SNP mixtures and outputs optionally file suitable for wrapdataL function for estimation of number of contributors

Usage

```
simMixSNP(nSNP , p , ncont, writeFile, outfile , id )
```

Arguments

nSNP	Integer number of SNPs>1
p	Minor allele frequency
ncont	Number of contributors >= 1
writeFile	If TRUE, output written to file
outfile	Name of output file
id	Column one of output file identifying run

Value

Returns a data frame with columns Id, marker, allele, frequency and height (=1 for now)

Author(s)

Thore Egeland <Thore.Egeland@medisin.uio.no>

Examples

```
simMixSNP()
```

simPCR2	<i>Polymorphism chain reaction simulation model</i>
---------	---

Description

simPCR2 implements a simulation model for the polymorphism chain reaction (Gill et al., 2005). Giving several input parameters, simPCR2 outputs the number of amplified DNA molecules and their corresponding peak heights (in RFUs).

Usage

```
simPCR2(ncells,probEx,probAlq, probPCR, cyc = 28, Tdrop = 2 * 10^7,
probSperm = 0.5, dip = TRUE,KH=55)
```

Arguments

ncells	initial number of cells
probEx	probability that a DNA molecule is extracted (probability of surviving the extraction process)
probAlq	probability that a DNA molecule is selected for PCR amplification
probPCR	probability that a DNA molecule is amplified during a given round of PCR
cyc	number of PCR cycles, default is 28 cycles
Tdrop	threshold of detection: number of molecules (in the total PCR reaction mixture) that is needed to generate a signal, default is set to 2×10^7 molecules
probSperm	probability of observing alleles of type A in the initial sample of haploid cells (e.g. sperm cells). Probability of observing allele B is given by $1 - \text{probSperm}$
dip	logical indicating the cell ploidy, default is diploid cells (TRUE), FALSE is for haploid cells
KH	positive constant used to scale the peak heights obtained from the number of amplified molecules (see reference section)

Details

A threshold of Tdrop (must be a multiple of 10^7) is needed to generate a signal, then, a log-linear relationship is used to determine the intensity of the signal with respect to the number of successfully amplified DNA molecules. Dropout events occur whenever less than Tdrop molecules are generated.

Value

A matrix with the following components:

HeightA	Peak height of allele A
DropA	Dropout variable for allele A
HeightB	Peak height of allele B
DropB	Dropout variable for allele B

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Jeffreys AJ, Wilson V, Neumann R and Keyte J. Amplification of human minisatellites by the polymerase chain reaction: towards DNA fingerprinting of single cells. *Nucleic Acids Res* 1988;16: 10953_10971.

Gill P, Curran J and Elliot K. A graphical simulation model of the entire DNA process associated with the analysis of short tandem repeat loci. *Nucleic Acids Research* 2005, 33(2): 632-643.

See Also

[simPCR2TK](#)

Examples

```
#simulation of a 28 cycles PCR, with the initial stain containing 5 cells
simPCR2(ncells=5,probEx=0.6,probAlq=0.30,probPCR=0.8,cyc=28, Tdrop=2*10^7,dip=TRUE,KH=55)
```

simPCR2TK

A Tcl/Tk graphical interface for the polymorphism chain reaction simulation model

Description

simPCR2TK is a user-friendly graphical interface for the simPCR2 function that implements a simulation model for the polymorphism chain reaction.

Usage

```
simPCR2TK()
```

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Gill P, Curran J and Elliot K. A graphical simulation model of the entire DNA process associated with the analysis of short tandem repeat loci. *Nucleic Acids Research* 2005, 33(2): 632-643.

See Also

[simPCR2](#)

Examples

```
#launch the graphical interface
simPCR2TK()
```

simufreqD	<i>Function to simulate allele frequencies for independent loci from a Dirichlet model</i>
-----------	--

Description

The simufreqD function simulate single population allele frequencies for independent loci. Allele frequencies are generated as random deviates from a Dirichlet distribution, whose parameters control the mean and the variance of the simulated allele frequencies.

Usage

```
simufreqD(nloc = 1, nal = 2, alpha = 1)
```

Arguments

nloc	the number of loci to simulate
nal	the numbers of alleles per locus. Either an integer, if the loci have the same number of alleles, or an integer vector, if the number of alleles differ between loci
alpha	the parameter used to simulate allele frequencies from the Dirichlet distribution. If the nloc loci have the same allele number, alpha can either be the same for all alleles (default is one: uniform distribution), in this case alpha is an integer, or alpha can be different between alleles at a given locus, in this case, alpha is a matrix of dimension nal x nloc. When the number of alleles differ between loci, alpha can either be the same or differ between alleles at a given locus. In the first case alpha is a vector of length nloc, in the second case, alpha is a matrix of dimensions nal x nloc where NAs are introduced for alleles not seen at a given locus.

Details

Allele frequencies for independent loci are simulated using a Dirichlet distribution with parameter alpha. At a given locus L with n alleles, the allele frequencies are modeled as a vector of random variables $p=(p_1, \dots, p_n)$, following a Dirichlet distribution with parameters: $\alpha = (\alpha_1, \dots, \alpha_n)$ where $p_1 + \dots + p_n = 1$ and $\alpha_1, \dots, \alpha_n > 0$.

Value

A matrix containing the simulated allele frequencies. The data is presented in the format of the Journal of Forensic Sciences for genetic data: allele names are given in the first column, and frequencies for a given allele are read in rows for the different markers in columns. When an allele is not observed for a given locus, the value is coded NA (instead of "-" in the original format).

Note

The code used here for the generation of random Dirichlet deviates was previously implemented in the gtools library.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Johnson NL, Kotz S, Balakrishnan N. Continuous Univariate Distributions, vol 2. John Wiley & Sons, 1995.

Wright S. The genetical structure of populations. Ann Eugen 1951;15:323-354.

See Also

[simupopD](#)

Examples

```
#simulate alleles frequencies for 5 markers with respectively 2, 3, 4, 5, and 6 alleles
simufreqD(nloc=5,na=c(2,3,4,5,6) , alpha=1)
```

simugeno	<i>forensim class for simulated genotypes</i>
----------	---

Description

The S4 simugeno class is used to store existing or simulated genotypes.

Slots

tab.freq: a list giving allele frequencies for each locus. If there are several populations, **tab.freq** gives allele frequencies in each population

nind: integer vector giving the number of individuals. If there are several populations, **nind** gives the numbers of individuals per population

pop.names: factor of populations names

popind: factor giving the population of each individual

which.loc: character vector giving the locus names

tab.geno: matrix giving the genotypes (in rows) for each locus (in columns). The genotype of a homozygous individual carrying the allele "12" is coded "12/12". A heterozygous individual carrying alleles "12" and "13" is coded "12/13" or "13/12".

indID: character vector giving the individuals ID

Methods

names signature(x = "simugeno"): gives the names of the attributes of a simugeno object

show signature(object = "simugeno"): shows a simugeno object

print signature(object = "simugeno"): prints a simugeno object

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[as.simugeno](#) for the simugeno class constructor, [is.simugeno](#), [simumix](#) and [tabfreq](#)

Examples

```
showClass("simugeno")
```

simugeno constructor *simugeno constructor*

Description

Constructor for [simugeno](#) objects.

The function `simugeno` creates a [simugeno](#) object from a [tabfreq](#) object.

The function `as.simugeno` is an alias for `simugeno` function.

`is.simugeno` tests if an object is a valid `simugeno` object.

Note: to get the manpage about [simugeno](#), please type 'class ? simugeno'.

Usage

```
simugeno(tab,which.loc=NULL,n=1)
as.simugeno(tab,which.loc=NULL,n=1)
is.simugeno(x)
```

Arguments

<code>tab</code>	a <code>tabfreq</code> object created with constructor <code>tabfreq</code>
<code>which.loc</code>	a character vector giving the chosen loci for the genotypes simulation. The default is set to <code>NULL</code> , which corresponds to all the loci of the <code>tabfreq</code> object given in argument
<code>n</code>	integer vector giving the number of individuals. If there are several populations, <code>n</code> gives the numbers of individuals to simulate per population. For a single population, default is 1.
<code>x</code>	an object

Details

At a given locus, an individual's genotype is simulated by randomly drawing two alleles (with replacement) at their respective allele frequencies in the target population.

Value

For `simugeno` and `as.simugeno`, a `simugeno` object. For `is.simugeno`, a logical.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

"[simugeno](#)", and [tabfreq](#) for creating a `tabfreq` object from a data file.

Examples

```
data(Tu)
tab<-tabfreq(Tu)
#simulation of 3 individual genotypes for the STR marker FGA
geno1 <- simugeno(tab,which.loc='FGA', n =100)
geno1@tab.geno
```

simumix

forensim class for DNA mixtures

Description

The S4 `simumix` class is used to store DNA mixtures of individual genotypes along with informations about the individuals populations and the loci used to simulate the genotypes.

Slots

ncontri: integer vector giving the number of contributors to the DNA mixture. If there are several populations, `ncontri` gives the number of contributors per population

mix.prof: matrix giving the contributors genotypes (in rows) for each locus (in columns). The genotype of a homozygous individual carrying the allele "12" is coded "12/12". A heterozygous individual carrying alleles "12" and "13" is coded "12/13" or "13/12".

mix.all: list giving the alleles present in the mixture for each locus

which.loc: character vector giving the locus names

popinfo: factor giving the population of each contributor

Methods

names `signature(x = "simumix")`: gives the names of the attributes of a `simumix` object

show `signature(object = "simumix")`: shows a `simumix` object

print `signature(object = "simumix")`: prints a `simumix` object

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[simugeno](#), [as.simumix](#), [is.simumix](#), [simugeno](#) and [tabfreq](#)

Examples

```
showClass("simumix")
data(strusa)
```

simumix constructor	<i>simumix constructor</i>
---------------------	----------------------------

Description

Constructor for [simumix](#) objects.

The function `simumix` creates a [simumix](#) object from a [tabfreq](#) object.

The function `as.simumix` is an alias for `simumix` function.

`is.simumix` tests if an object is a valid `simumix` object.

Note: to get the manpage about [simumix](#), please type `'class ? simumix'`.

Usage

```
simumix(tab,which.loc=NULL,ncontri=1)
as.simumix(tab,which.loc=NULL,ncontri=1)
is.simumix(x)
```

Arguments

<code>tab</code>	a <code>simugeno</code> object created with constructor <code>simugeno</code>
<code>which.loc</code>	a character vector giving the chosen loci for the genotypes simulation. The default is set to <code>NULL</code> , which corresponds to all the loci of the <code>simugeno</code> object given in argument
<code>ncontri</code>	integer vector giving the number of individuals. If there are several populations, <code>ncontri</code> gives the numbers of individuals to simulate per population. Default is one.
<code>x</code>	an object

Details

DNA mixtures are created by randomly drawing individual genotypes with a uniform probability. If there are N individuals in the sample (the `simugeno` object), then each individual has a probability of $1/N$ to be selected.

Value

For `simumix` and `as.simumix`, a `simumix` object. For `is.simumix`, a logical.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

"`simumix`", `simugeno` for creating a `simugeno` object.

Examples

```
data(Tu)
tab<-simugeno(tabfreq(Tu),n=1200)
#simulation of a 3-person mixture characterized with markers FGA, TH01 and TPOX
simumix(tab,which.loc=c('FGA','TH01','TPOX'), n =3)
```

simupopD	<i>Simulate multi-population allele frequencies for independent loci from a reference population, following a Dirichlet model</i>
----------	---

Description

Simulate multi-population allele frequencies for independent loci, from a given reference population, following a Dirichlet model. Allele frequencies in the populations are generated as random deviates from a Dirichlet distribution, whose parameters control the deviation of allele frequencies from the values in the reference population.

Usage

```
simupopD(npop = 1, nloc = 1, na = 2, globalfreq = NULL, which.loc = NULL,
alpha1, alpha2 = 1)
```

Arguments

<code>npop</code>	the number of populations
<code>nloc</code>	the number of loci
<code>na</code>	an integer vector giving the numbers of alleles per locus
<code>globalfreq</code>	matrix of allele frequencies in the reference population. Data must be given in the format of the Journal of Forensic Sciences for genetic data. Default corresponds to allele frequencies generated from a Dirichlet distribution with parameter <code>alpha2</code> for all allele frequencies.
<code>which.loc</code>	which loci to simulate from the <code>globalfreq</code> matrix, default considers all loci
<code>alpha1</code>	a positive float vector of length <code>npop</code> giving the variance parameter of the Dirichlet distribution used to generate allele frequencies in the <code>npop</code> independent populations
<code>alpha2</code>	a positive float giving the parameter to be used to in the Dirichlet distribution to generate allele frequencies for the reference population

Details

In the reference population, allele frequencies for independent loci are simulated using a Dirichlet distribution with parameter α_2 .

At a given locus L with n alleles, the allele frequencies are modeled as a vector of random variables $p=(p_1, \dots, p_n)$ following a Dirichlet distribution with a parameter vector of length n , where each component is equal to α_2 , $p_1+\dots+p_n=1$ and $\alpha_2 > 0$.

Note that a more sophisticated generation of global allele frequencies is possible using the [simufreqD](#) function. Similarly, allele frequencies in the independent populations are simulated using a Dirichlet Distribution. For example, for the first population to simulate, at a given locus L with n alleles, the allele frequencies are modeled as a vector of random variables $p=(p_1, \dots, p_n)$ following a Dirichlet distribution with a parameter vector of length n :

$(p_1(1-\alpha_1)/\alpha_1[1], \dots, p_n(1-\alpha_1[1])/ \alpha_1[1])$, where $p_1+\dots+p_n=1$ and $\alpha_1[1] > 0$.

$\alpha_1[1]$ is the variance parameter for population 1 and is equivalent to Wright's F_{st} . The closer this parameter is to one, the more the population allele frequencies are different from the values of the reference population.

Value

The result is stored in a list with two elements :

<code>globfreq</code>	a <code>tabfreq</code> object giving the allele frequencies of the chosen reference population, with the chosen loci.
<code>popfreq</code>	a <code>tabfreq</code> object giving the allele frequencies of the simulated populations.

Note

The code used here for the generation of random Dirichlet deviates was previously implemented in the `gtools` library.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

References

Nicholson G, Smith AV, Jonsson F, Gustafsson O, Stefansson K, Donnelly P. Assessing population differentiation and isolation from single-nucleotide polymorphism data. *J Roy Stat Soc B* 2002;64:695–715

Marchini J, Cardon LR. Discussion on the meeting on "Statistical modelling and analysis of genetic data" *J Roy Stat Soc B*, 2002;64:740-741

Wright S. The genetical structure of populations. *Ann Eugen* 1951;15:323-354

See Also

[simufreqD](#)

Examples

```
# simulate allele frequencies for two populations
data(Tu)
simupopD(npop=2,globalfreq=Tu, which.loc=c("FGA","TH01","TPOX"),
alpha1=c(0.2,0.3),alpha2=1)
```

strusa	<i>Allele frequencies for 15 autosomal short tandem repeats core loci on U.S. Caucasian, African American, and Hispanic populations.</i>
--------	--

Description

Allele frequencies for 15 autosomal short tandem repeats loci on three American populations : Caucasians, African Americans and Hispanics. Among the 15 loci, 13 belong to the core Combined DNA Index System (CODIS) loci used by the Federal Bureau of Investigation (USA), in forensic DNA analysis, and two supplementary loci are more commonly used in Europe, see details.

Usage

```
data(strusa)
```

Format

strusa is a tabfreq object giving allele frequencies of 15 loci in three American populations.

Details

CSF1PO, FGA, TH01, TPOX, vWA, D3S1358, D5S818, D7S820, D8S1179, D13S317, D16S539, D18S51 and D21S11, belong to the core CODIS loci used in the US, whereas D2S1338 and D19S433 belong to the European core loci.

References

Butler JM, Reeder DJ. <http://www.cstl.nist.gov/strbase/index.htm>, last visited: May 11th 2009

Butler JM, Schoske R, Vallone MP, Redman JW, Kline MC. Allele frequencies for 15 autosomal STR loci on U.S. Caucasian, African American, and Hispanic populations. *J Forensic Sci* 2003;48(8):908-911.

Examples

```
data(strusa)
strusa
#genotypes simulations from each population
geno<- simugeno(strusa,n=c(100,100,100))
geno
#3-person mixture simulation with the contributors from the 3 populations
mix3<- simumix(geno,ncontri=c(1,1,1))
mix3
```

strveneto

Population study of three miniSTR loci in Veneto (Italy)

Description

Allele frequencies for three short tandem repeats loci D10S1248, D2S441 and D22S1045 in a sample of 198 individuals born in Veneto, Italy. These loci are commonly used in forensic DNA characterization.

Usage

```
data(strveneto)
```

Format

strveneto is a tabfreq object

References

Turrina S, Atzei R, De Leo D. Population study of three miniSTR loci in Veneto (Italy). Forensic Sci Int Genetics 2008; 1(1);378-379

Examples

```
data(strveneto)
#allele frequencies
strveneto@tab
```

tabfreq

forensim class for population allele frequencies

Description

The S4 tabfreq class is used to store allele frequencies, from either one or several populations.

Slots

tab: a list giving allele frequencies for each locus. If there are several populations, tab gives allele frequencies in each population

which.loc: character vector giving the names of the loci

pop.names: factor of populations names (optional)

Methods

names signature(x = "tabfreq"): gives the names of the attributes of a tabfreq object

show signature(object = "tabfreq"): shows a tabfreq object

print signature(object="tabfreq"): prints a tabfreq object

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

[as.tabfreq](#), [is.tabfreq](#) and [simugeno](#) for genotypes simulation from allele frequencies stored in a tabfreq object

Examples

```
showClass("tabfreq")
```

tabfreq constructor	<i>tabfreq constructor</i>
---------------------	----------------------------

Description

Constructor for [tabfreq](#) objects.

The function tabfreq creates a [tabfreq](#) object from a data frame or a matrix giving allele frequencies for a single population in the Journal of Forensic Sciences (JFS) format for population genetic data. When multiple populations are considered, data shall be given as a list, where each element is either a matrix or a data frame in the JFS format, and the populations names must be specified.

The function `as.tabfreq` is an alias for the tabfreq function.

`is.tabfreq` tests if an object is a valid tabfreq object.

Note: to get the manpage about [tabfreq](#), please type `'class ? tabfreq'`.

Usage

```
tabfreq(tab, pop.names=NULL)
as.tabfreq(tab, pop.names=NULL)
is.tabfreq(x)
```

Arguments

tab	either a matrix or a data.frame of markers allele frequencies given in the Journal of Forensic Sciences format for population genetic data
pop.names	(optional) a factor giving the populations names. For a single population in tab, default is set to NULL.
x	an object

Value

For tabfreq and `as.tabfreq`, a tabfreq object. For `is.tabfreq`, a logical.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

See Also

"[tabfreq](#)", [simugeno](#) for creating a simugeno object from a tabfreq object.

Examples

```
data(Tu)
tabfreq(Tu, pop.names=factor("Tu"))
```

Tu	<i>Allele frequencies of 15 autosomal short tandem repeats loci on Chinese Tu ethnic minority group</i>
----	---

Description

Population genetic analysis of 15 STR loci of Chinese Tu ethnic minority group.

Usage

```
data(Tu)
```

Format

a data frame presented in the format of the Journal of Forensic Sciences for genetic data: allele names are given in the first column, and frequencies for a given allele are read in rows for the different markers. When a given allele is not observed, value is coded NA (rather than "-" in the original format).

Details

CSF1PO, FGA, TH01, TPOX, vWA, D3S1358, D5S818, D7S820, D8S1179, D13S317, D16S539, D18S51 and D21S11, belong to the core CODIS loci used in the US, whereas D2S1338 and D19S433 belong to the European core loci.

References

Zhu B, Yan J, Shen C, Li T, Li Y, Yu X, Xiong X, Muf H, Huang Y, Deng Y. (2008). Population genetic analysis of 15 STR loci of Chinese Tu ethnic minority group. *Forensic Sci Int*, 174: 255-258.

Examples

```
data(Tu)
tabfreq(Tu)
```

virtualClasses	<i>Virtual classes for forensim</i>
----------------	-------------------------------------

Description

Virtual classes that are only for internal use in forensim

Objects from the Class

A virtual Class: programming tool, not intended for objects creation.

Author(s)

Hinda Haned <h.haned@nfi.minvenj.nl>

wrapdataL	<i>ML estimate of number of contributors for SNPs</i>
-----------	---

Description

Wrap up of dataL in forensim. Given file with columns: "No, Marker, Allele, Frequency and Height" the log likelihood for requested number of contributors is calculated. For now only "Frequency" column is used.

Usage

```
wrapdataL(fil , plotte , nInMixture , tit )
```

Arguments

fil	Input file
plotte	If T, plot
nInMixture	Alternatives for number of contributors, say 1:5
tit	Title to be used in plot

Value

Plot (optional) and log likelihoods

Author(s)

Thore Egeland <Thore.Egeland@medisin.uio.no>

Examples

```
aa<-simMixSNP(nSNP=5,writeFile=TRUE,outfile="sim.txt",ncont=3) #Simulates data
res<-wrapdataL(fil="sim.txt") # Calculates and plots
```

Index

*Topic **classes**

simugeno, 33
 simumix, 35
 tabfreq, 40
 virtualClasses, 43

*Topic **datagen**

forensim-package, 2
 Hbsimu, 12
 simPCR2, 30
 simPCR2TK, 31
 simufreqD, 32
 simugeno, 33
 simugeno constructor, 34
 simumix, 35
 simumix constructor, 36
 simupopD, 37
 tabfreq, 40
 tabfreq constructor, 41

*Topic **datasets**

ngm, 26
 sgmNorway, 29
 strusa, 39
 strveneto, 40
 Tu, 42

*Topic **htest**

A2.simu, 3
 A3.simu, 4
 A4.simu, 5
 dataL, 10
 lik, 13
 lik.loc, 14
 likestim, 15
 likestim.loc, 17
 likEvid, 18
 LR, 19
 LRmixTK, 21
 mastermix, 21
 mincontri, 23
 PE, 27
 PV, 28

*Topic **manip**

Accessors, 6
 changepop, 7

forensim-package, 2
 naomitab, 25
 simugeno, 33
 simugeno constructor, 34
 simumix, 35
 simumix constructor, 36
 tabfreq, 40
 tabfreq constructor, 41

*Topic **misc**

findfreq, 11
 findmax, 11
 nball, 26

*Topic **models**

Cmn, 8
 comb, 9
 \$,simugeno-method (Accessors), 6
 \$,simumix-method (Accessors), 6
 \$,tabfreq-method (Accessors), 6
 \$<-,simugeno-method (Accessors), 6
 \$<-,simumix-method (Accessors), 6
 \$<-,tabfreq-method (Accessors), 6

A2.simu, 3, 5, 6, 22
 A3.simu, 4, 4, 6, 22
 A4.simu, 4, 5, 5, 22
 Accessors, 6
 as.simugeno, 34
 as.simugeno(simugeno constructor), 34
 as.simumix, 36
 as.simumix(simumix constructor), 36
 as.tabfreq, 41
 as.tabfreq(tabfreq constructor), 41
 changepop, 7
 characterOrNULL-class (virtualClasses),
 43
 Cmn, 8, 9
 comb, 8, 9
 dataL, 8, 10, 12
 factorOrNULL-class (virtualClasses), 43
 findfreq, 11
 findmax, 11

- forensim, [7](#)
- forensim (forensim-package), [2](#)
- forensim-package, [2](#)
- Hbsimu, [12](#)
- is.simugeno, [34](#)
- is.simugeno (simugeno constructor), [34](#)
- is.simumix, [36](#)
- is.simumix (simumix constructor), [36](#)
- is.tabfreq, [41](#)
- is.tabfreq (tabfreq constructor), [41](#)
- lik, [10](#), [13](#), [15](#)
- lik.loc, [10](#), [13](#), [14](#)
- likestim, [13](#), [15](#), [15](#), [18](#), [23](#), [28](#)
- likestim.loc, [13](#), [15](#), [16](#), [17](#)
- likEvid, [18](#)
- listOrdadataframe-class (virtualClasses), [43](#)
- LR, [19](#)
- LRmixTK, [19](#), [20](#), [21](#)
- mastermix, [21](#)
- matrixOrdadataframe-class (virtualClasses), [43](#)
- mincontri, [23](#)
- N2error, [23](#)
- N2Exact, [24](#)
- names, simugeno-method (simugeno), [33](#)
- names, simumix-method (simumix), [35](#)
- names, tabfreq-method (tabfreq), [40](#)
- naomitab, [25](#)
- nball, [26](#)
- ngm, [26](#)
- PE, [27](#)
- print, simugeno-method (simugeno), [33](#)
- print, simumix-method (simumix), [35](#)
- print, tabfreq-method (tabfreq), [40](#)
- PV, [28](#)
- sgmNorway, [29](#)
- show, simugeno-method (simugeno), [33](#)
- show, simumix-method (simumix), [35](#)
- show, tabfreq-method (tabfreq), [40](#)
- simMixSNP, [29](#)
- simPCR2, [30](#), [32](#)
- simPCR2TK, [31](#), [31](#)
- simufreqD, [32](#), [38](#)
- simugeno, [2](#), [6](#), [7](#), [33](#), [34–37](#), [41](#), [42](#)
- simugeno (simugeno constructor), [34](#)
- simugeno constructor, [34](#)
- simugeno-class (simugeno), [33](#)
- simugeno-methods (simugeno constructor), [34](#)
- simumix, [2](#), [6](#), [7](#), [11](#), [23](#), [26](#), [27](#), [34](#), [35](#), [36](#), [37](#)
- simumix (simumix constructor), [36](#)
- simumix constructor, [36](#)
- simumix-class (simumix), [35](#)
- simumix-methods (simumix constructor), [36](#)
- simupopD, [33](#), [37](#)
- strusa, [39](#)
- strveneto, [40](#)
- tabfreq, [2](#), [6](#), [7](#), [25](#), [34–36](#), [40](#), [41](#), [42](#)
- tabfreq (tabfreq constructor), [41](#)
- tabfreq constructor, [41](#)
- tabfreq-class (tabfreq), [40](#)
- tabfreq-methods (tabfreq constructor), [41](#)
- Tu, [42](#)
- vectorOrdadataframe-class (virtualClasses), [43](#)
- vectorOrNULL-class (virtualClasses), [43](#)
- virtualClasses, [43](#)
- wrapdataL, [43](#)