

Package ‘fuzzySim’

April 24, 2022

Type Package

Title Fuzzy Similarity in Species Distributions

Version 3.96

Date 2022-04-24

Author Barbosa A.M.

Maintainer A. Marcia Barbosa <ana.marcia.barbosa@gmail.com>

Imports graphics, methods, modEvA, stats, utils

Suggests maptools, parallel, PBSmapping, raster, sp, terra, tools

Description Functions to calculate fuzzy versions of species occurrence patterns based on presence-absence data (including inverse distance interpolation, trend surface analysis and prevalence-independent favourability GLM), and pair-wise fuzzy similarity (based on fuzzy versions of commonly used similarity indices) among those occurrence patterns. Includes also functions for model comparison (overlap and fuzzy similarity, loss or gain), and for data preparation, such as obtaining unique abbreviations of species names, converting species lists (long format) to presence-absence tables (wide format), transposing part of a data frame, assessing the false discovery rate, or analysing and dealing with multicollinearity among variables. Includes also sample datasets for providing practical examples.

License GPL-3

URL fuzzysim.r-forge.r-project.org,

<https://CRAN.R-project.org/package=fuzzySim>

R topics documented:

fuzzySim-package	2
bioThreat	5
corSelect	7
distPres	9
entropy	11
Fav	13
favClass	16
FDR	17
fuzSim	19

fuzzyOverlay	22
fuzzyRangeChange	24
getPreds	26
gridRecords	28
integerCols	30
modelTrim	32
modOverlap	33
multConvert	35
multGLM	36
multicol	40
multTSA	42
pairwiseRangemaps	44
percentTestData	46
rangemapSim	47
rarity	48
rotif.env	50
rotifers	52
sharedFav	52
simFromSetOps	54
simMat	56
spCodes	59
splist2presabs	60
stepByStep	61
timer	63
transpose	64
triMatInd	65
vulnerability	66
Index	68

fuzzySim-package

Fuzzy Similarity in Species Distributions

Description

Functions to calculate fuzzy versions of species occurrence patterns based on presence-absence data (including inverse distance interpolation, trend surface analysis, and prevalence-independent favourability, obtained from probability of presence), as well as pair-wise fuzzy similarity (based on fuzzy logical versions of commonly used similarity indices) among those occurrence patterns. Includes also functions for data preparation, such as obtaining unique abbreviations of species names, gridding point occurrence data onto raster maps, converting species lists (long format) to presence-absence tables (wide format), transposing part of a data frame, selecting relevant variables for models, assessing the false discovery rate, or analysing and dealing with multicollinearity. Includes also sample datasets for providing practical examples. A step-by-step illustrated tutorial is available from the package homepage (<http://fuzzysim.r-forge.r-project.org>).

Details

Package: fuzzySim
Type: Package
Version: 3.96
Date: 2022-04-24
License: GPL-3

Author(s)

A. Marcia Barbosa

Maintainer: A. Marcia Barbosa <ana.marcia.barbosa@gmail.com>

References

Barbosa A.M. (2015) fuzzySim: applying fuzzy logic to binary similarity indices in ecology. *Methods in Ecology and Evolution*, 6: 853-858.

Examples

```
data(rotifers)

head(rotifers)

# add column with species name abbreviations:

rotifers$spcode <- spCodes(rotifers$species, sep.species = "_",
nchar.gen = 1, nchar.sp = 5, nchar.ssp = 0)

head(rotifers)

# convert species list (long format) to presence-absence table
# (wide format):

rotifers.presabs <- splist2presabs(rotifers, sites.col = "TDWG4",
sp.col = "spcode", keep.n = FALSE)

head(rotifers.presabs)

# get 3rd-degree spatial trend surface for some species distributions:

data(rotif.env)

names(rotif.env)

rotifers.tsa <- multTSA(rotif.env, sp.cols = 18:20,
coord.cols = c("Longitude", "Latitude"), id.col = 1)
```

```
head(rotifers.tsa)

# get inverse squared distance to presence for each species:

rotifers.isqd <- distPres(rotif.env, sp.cols = 18:20,
coord.cols = c("Longitude", "Latitude"), id.col = 1, p = 2, inv = TRUE)

head(rotifers.isqd)

# get prevalence-independent environmental favourability models
# for each species:

data(rotif.env)

names(rotif.env)

rotifers.fav <- multGLM(data = rotif.env, sp.cols = 18:20,
var.cols = 5:17, id.col = 1, step = FALSE, trim = TRUE,
Favourability = TRUE)

# get matrix of fuzzy similarity between species distributions:

# either based on inverse squared distance to presence:
rot.fuz.sim.mat <- simMat(rotifers.isqd[ , -1], method = "Jaccard")

# or on environmental favourability for presence:
rot.fuz.sim.mat <- simMat(rotifers.fav$predictions[ , 5:7],
method = "Jaccard")

head(rot.fuz.sim.mat)

# transpose fuzzy rotifer distribution data to compare
# regional species composition rather than species' distributions:

names(rotifers.isqd)

rot.fuz.reg <- transpose(rotifers.fav$predictions, sp.cols = 5:7,
reg.names = 1)

head(rot.fuz.reg)

# get matrix of fuzzy similarity between (some) regions'
# species compositions:

reg.fuz.sim.mat <- simMat(rot.fuz.reg[ , 1:10], method = "Jaccard")

head(reg.fuz.sim.mat)
```

bioThreat	<i>Biotic threat of a stronger over a weaker species based on their favourability values</i>
-----------	----------------------------------------------------------------------------------------------

Description

This function takes two vectors of [Favourability](#) values at different localities for, respectively, a stronger and a weaker species (e.g., a superior vs. an inferior competitor, or an invasive predator vs. an unadapted native prey), and calculates the level of threat that the former may potentially pose to the latter in each locality.

Usage

```
bioThreat(strong_F, weak_F, character = FALSE, ...)
```

Arguments

strong_F	a numeric vector of favourability values (obtained, e.g., with functions Fav or multGLM) for the stronger species.
weak_F	a numeric vector of favourability values for the weaker species. Must be of the same length and in the same order as 'strong_F'.
character	logical value indicating whether the result should be returned in character rather than numeric form. Defaults to FALSE.
...	additional arguments to pass to favClass , namely the breaks for separating favourability values into low, intermediate and high (see Details).

Details

Based on the notion of "favorableness" by Richerson & Lum (1980), according to which competing species may or may not be able to coexist depending on their relative environmental fitnesses, Acevedo et al. (2010, 2012) and some subsequent studies (e.g. Romero et al. 2014, Munoz et al. 2015, Chamorro et al. 2019) proposed possible biotic interaction outcomes of different combinations of favourability values for two species. Favourability has the advantage, in contrast with other types of potential distribution metrics, of being directly comparable among different species, independently of their relative occurrence frequencies (see [Fav](#)). This function builds on those proposals by including additional possible combinations of higher, intermediate or low favourability values (following Munoz & Real 2006), producing the following classification of biotic threat across a set of analysed localities:

0 ('white'): areas where favourability is low for at least one of the species (abiotic exclusion), so biotic threat does not apply.

1 ('green'): areas where favourability is high for both species, so they should both be able to thrive and therefore co-occur (sympatric coexistence), hence biotic threat is low.

2 ('yellow'): areas where favourability is high for the weaker species and intermediate for the stronger species, so the level of threat is moderate.

3 ('orange'): areas where favourability is intermediate for both species, so the stronger one potentially prevails and the level of threat is high.

4 ('red'): areas where favourability is high for the stronger species and intermediate for the weaker species, in which case the level of threat is very high (biotic exclusion).

Value

This function returns either an integer or a character vector (following the 'character' argument, which is set to FALSE by default) of the same length as 'strong_F' and 'weak_F', classifying each locality with the level of biotic threat posed by the former on the latter (see Details).

Author(s)

A. Marcia Barbosa

References

- Acevedo P., Ward A.I., Real R. & Smith G.C. (2010) Assessing biogeographical relationships of ecologically related species using favourability functions: a case study on British deer. *Diversity and Distributions*, 16: 515-528
- Acevedo P., Jimenez-Valverde A., Melo-Ferreira J., Real R. & Alves, P.C. (2012) Parapatric species and the implications for climate change studies: a case study on hares in Europe. *Global Change Biology*, 18: 1509-1519
- Chamorro D., Munoz A.R., Martinez-Freiria F. & Real R. (2019) Using the fuzzy logic in the distribution modelling of competitive interactions. Poster, IBS Malaga 2019 - 9th Biennial Conference of the International Biogeography Society
- Munoz A.R. & Real R. (2006) Assessing the potential range expansion of the exotic monk parakeet in Spain. *Diversity and Distributions*, 12: 656-665
- Munoz A.R., Real R. & Marquez A.L. (2015) Interacciones a escala nacional entre rapaces rupícolas en base a modelos de distribución espacial. Los casos del buitre leonado, alimoche y aguililla perdicera. Informe técnico, Universidad de Malaga & Fundación EDP
- Richerson P.J. & Lum K. (1980) Patterns of plant species diversity in California: relation to weather and topography. *American Naturalist*, 116:504-536
- Romero D., Baez J.C., Ferri-Yanez F., Bellido J. & Real R. (2014) Modelling favourability for invasive species encroachment to identify areas of native species vulnerability. *The Scientific World Journal*, 2014: 519710

See Also

[sharedFav](#), [Fav](#), [favClass](#)

Examples

```
data(rotif.env)
mods <- multGLM(rotif.env, sp.cols = 19:20, var.cols = 5:17)
head(mods$predictions)
favs <- mods$predictions[, 3:4]
threat <- bioThreat(strong_F = favs[,1], weak_F = favs[,2])
```

```
threat_chr <- bioThreat(strong_F = favs[,1], weak_F = favs[,2], char = TRUE)
data.frame(favs, threat = threat, threat_col = threat_chr)
```

corSelect

Select among correlated variables based on a given criterion

Description

This function calculates pairwise correlations among the variables in a dataset and, among each pair of variables correlated above a given threshold, excludes the variable with either the highest variance inflation factor (VIF), or the least significant or least informative bivariate (individual) relationship with the response variable (if supplied), according to a specified criterion.

Usage

```
corSelect(data, sp.cols = NULL, var.cols, cor.thresh = 0.8,
select = "p.value", family = "auto", use = "pairwise.complete.obs", method = "pearson")
```

Arguments

<code>data</code>	a data frame containing the response and predictor variables.
<code>sp.cols</code>	name or index number of the column of 'data' that contains the response (e.g. species) variable. Currently, only one 'sp.cols' can be used at a time, so an error message is returned if <code>length(sp.cols) > 1</code> . If <code>sp.cols = NULL</code> (the default), the function returns only the pairs of variables that are correlated over the given threshold, without selecting those that are more relevant for a target species.
<code>var.cols</code>	names or index numbers of the columns of 'data' that contain the predictor variables.
<code>cor.thresh</code>	threshold value of correlation coefficient above which (or below which, for negative correlations) predictor variables should be excluded. The default is 0.8.
<code>select</code>	character value indicating the criterion for excluding variables among those that are correlated. Can be "p.value" (the default), "AIC", "BIC", or "VIF" (see Details).
<code>family</code>	If 'sp.col' is not NULL, the error distribution and (optionally) the link function to use for assessing significant / informative variables (see glm or family for details). The default "auto" automatically uses "binomial" family for response variables containing only values of 0 and 1; "poisson" for positive integer responses (i.e. count data); "Gamma" for positive non-integer; and "gaussian" (i.e., linear models) otherwise.
<code>use</code>	argument to pass to cor indicating what to do when there are missing values. Can be "pairwise.complete.obs" (the default here), "everything", "all.obs", "complete.obs", "na.or.complete".
<code>method</code>	argument to pass to cor specifying the correlation coefficient to use. Can be "pearson" (the default), "kendall" or "spearman".

Details

Correlations among variables are problematic in multivariate models, as they inflate the variance of coefficients and thus may bias the interpretation of the effects of those variables on the response (Legendre & Legendre 2012). One of the strategies to circumvent this problem is to eliminate one from each pair of correlated variables, but it is not always straightforward to choose the right variable to exclude a priori.

This function selects among correlated variables, based either on their variance inflation factor (VIF: Marquardt 1970; Mansfield & Helms 1982) within the variables dataset (obtained with the `multicol` function and recalculated iteratively after each variable exclusion); or on their relationship with the response, by building a bivariate model of each individual variable against the response and excluding, among each of two correlated variables, the one with the largest (worst) p-value, AIC (Akaike's Information Criterion: Akaike, 1973) or BIC (Bayesian Information Criterion, also known as Schwarz criterion, SBC or SBIC: Schwarz, 1978), which it calculates with the `FDR` function.

If 'sp.cols' is left NULL and the 'select' criterion is other than "VIF", the function returns only the pairs of variables that are correlated above the given threshold. If the 'select' criterion requires assessing bivariate relationships and 'sp.cols' is provided, the function uses only the rows of the dataset where this column (used as the response variable) contains finite values against which the predictor variables can be modelled; rows with NA or NaN in 'sp.cols' are thus excluded from the calculation of correlations among predictor variables.

Value

This function returns a list of 7 elements, unless 'sp.cols = NULL', in which case it returns only the first of these elements:

<code>high.correlations</code>	data frame showing the pairs of input variables that are correlated beyond the given threshold, and their correlation coefficient.
<code>bivariate.significance</code>	data frame with the individual p-value, AIC and BIC (if one of these was the 'select' criterion) of each of the highly correlated variables against the response variable.
<code>excluded.vars</code>	character vector containing the names of the variables to be excluded (i.e., from each highly correlated pair, the variable with the worse 'select' score).
<code>selected.vars</code>	character vector containing the names of the variables to be selected (i.e., the non-correlated variables and, from each correlated pair, the variable with the better 'select' score).
<code>selected.var.cols</code>	integer vector containing the column indices of the selected variables in 'data'.
<code>strongest.remaining.corr</code>	numerical value indicating the strongest correlation coefficient among the selected variables.
<code>remaining.multicollinearity</code>	data frame showing the <code>multicollinearity</code> among the selected variables.

Author(s)

A. Marcia Barbosa

References

- Akaike, H. (1973) Information theory and an extension of the maximum likelihood principle. In: Petrov B.N. & Csaki F., 2nd International Symposium on Information Theory, Tsahkadsor, Armenia, USSR, September 2-8, 1971, Budapest: Akademiai Kiado, p. 267-281.
- Legendre P. & Legendre L. (2012) Numerical ecology (3rd edition). Elsevier, Amsterdam: 990 pp.
- Marquardt D.W. (1970) Generalized inverses, ridge regression, biased linear estimation, and non-linear estimation. *Technometrics* 12: 591-612.
- Mansfield E.R. & Helms B.P. (1982) Detecting multicollinearity. *The American Statistician* 36: 158-160.
- Schwarz, G.E. (1978) Estimating the dimension of a model. *Annals of Statistics*, 6 (2): 461-464.

See Also

[multicol](#), [FDR](#), [cor](#)

Examples

```
data(rotif.env)

corSelect(rotif.env, var.cols = 5:17)

corSelect(rotif.env, sp.cols = 46, var.cols = 5:17)

corSelect(rotif.env, sp.cols = 46, var.cols = 5:17, cor.thresh = 0.7)

corSelect(rotif.env, sp.cols = 46, var.cols = 5:17, method = "spearman")
```

distPres

(Inverse) distance to the nearest presence

Description

This function takes a matrix or data frame containing species presence (1) and absence (0) data and their spatial coordinates (optionally also a pre-calculated distance matrix between all localities), and calculates the (inverse) distance from each locality to the nearest presence locality for each species.

Usage

```
distPres(data, sp.cols, coord.cols = NULL, id.col = NULL,
dist.mat = NULL, method = "euclidian", suffix = "_D", p = 1,
inv = TRUE)
```

Arguments

<code>data</code>	a matrix or data frame containing, at least, two columns with spatial coordinates, and one column per species containing their presence (1) and absence (0) data, with localities in rows.
<code>sp.cols</code>	names or index numbers of the columns containing the species presences and absences in data. It must contain only zeros (0) for absences and ones (1) for presences.
<code>coord.cols</code>	names or index numbers of the columns containing the spatial coordinates in data (in this order, x and y, or longitude and latitude).
<code>id.col</code>	optionally, the name or index number of a column (to be included in the output) containing locality identifiers in data.
<code>dist.mat</code>	optionally, if you do not want distances calculated with any of the methods available in <code>dist</code> , you may provide a distance matrix calculated elsewhere for the localities in data.
<code>method</code>	the method with which to calculate distances between localities. Available options are those of <code>dist</code> . The default is "euclidian".
<code>suffix</code>	character indicating the suffix to add to the distance columns in the resulting data frame. The default is "_D".
<code>p</code>	the power to which distance should be raised. The default is 1; use 2 or higher if you want more conservative distances.
<code>inv</code>	logical value indicating whether distance should be inverted, i.e. standardized to vary between 0 and 1 and then subtracted from 1, so that it varies between 0 and 1 and higher values mean closer to presence. The default is TRUE, which is adequate as a fuzzy version of presence-absence (for using e.g. with <code>fuzSim</code> and <code>simMat</code>). In this case, presences maintain the value 1, and inverse distance to presence is calculated only for absence localities.

Details

This function can be used to calculate a simple spatial interpolation model of a species' distribution (e.g. Barbosa 2015, Areias-Guerreiro et al. 2016).

Value

This function returns a matrix or data frame containing the identifier column (if provided in 'id.col') and one column per species containing the distance (inverse by default) from each locality to the nearest presence of that species.

Author(s)

A. Marcia Barbosa

References

Areias-Guerreiro J., Mira A. & Barbosa A.M. (2016) How well can models predict changes in species distributions? A 13-year-old otter model revisited. *Hystrix - Italian Journal of Mammalogy*, in press. DOI: <http://dx.doi.org/10.4404/hystrix-27.1-11867>

Barbosa A.M. (2015) fuzzySim: applying fuzzy logic to binary similarity indices in ecology. *Methods in Ecology and Evolution*, 6: 853-858

See Also

[dist](#)

Examples

```
data(rotif.env)

head(rotif.env)

names(rotif.env)

# calculate plain distance to presence:

rotifers.dist <- distPres(rotif.env, sp.cols = 18:47,
  coord.cols = c("Longitude", "Latitude"), id.col = 1, p = 1,
  inv = FALSE, suffix = "_D")

head(rotifers.dist)

# calculate inverse squared distance to presence:

rotifers.invd2 <- distPres(rotif.env, sp.cols = 18:47,
  coord.cols = c("Longitude", "Latitude"), id.col = 1, p = 2,
  inv = TRUE, suffix = "_iDsqr")

head(rotifers.invd2)
```

entropy	<i>(Fuzzy) entropy</i>
---------	------------------------

Description

This function computes fuzzy entropy (Kosko 1986, Estrada & Real 2021), or optionally Shannon's (1948) entropy.

Usage

```
entropy(data, sp.cols = 1:ncol(data), method = "fuzzy", base = exp(1), plot = TRUE, na.rm = TRUE, ...)
```

Arguments

<code>data</code>	a vector, matrix or data frame containing the data to analyse.
<code>sp.cols</code>	names or index numbers of the columns of 'data' that contain the values for which to compute entropy (if 'data' is not a vector). The default is to use all columns.
<code>method</code>	character value indicating the method to use. Can be "fuzzy" (the default) or "Shannon". The former requires the input to be a fuzzy system (e.g. Favourability values), while the latter requires probabilities. If <code>method="Shannon"</code> and the values for a vector or column do not sum up to 1, they are divided by their sum so that this additional requirement is met (Estrada & Real 2021).
<code>base</code>	base for computing the logarithm if <code>method="Shannon"</code> . The default is the natural logarithm.
<code>plot</code>	logical value indicating whether to produce a barplot with the results (if 'data' has more than one column). The default is TRUE.
<code>na.rm</code>	logical value indicating whether NA values should be removed before computations. The default is TRUE.
<code>...</code>	additional arguments to be passed to the barplot function.

Details

Fuzzy entropy (Kosko 1986) applies to fuzzy systems (such as [Favourability](#)) and it can take values between zero and one. Fuzzy entropy equals one when the distribution of the values is uniform, i.e. 0.5 in all localities. The smaller the entropy, the more orderly the distribution of the values, i.e. the closer they are to 0 or 1, distinguishing (potential) presences and absences more clearly. Fuzzy entropy can reflect the overall degree of uncertainty in a species' distribution model predictions, and it is directly comparable across species and study areas (Estrada & Real 2021).

Shannon's entropy requires that the input values are probabilities and sum up to 1 (Shannon 1948). This makes sense when analysing the probability that a unique event occurs in a finite universe. However, if a species has more than one presence, the sum of probabilities in all localities equals the number of presences. To satisfy the condition that the inputs sum up to 1, this function divides each value by the sum of values when this is not the case (if `method="Shannon"`). Notice that this has a mathematical justification but not a biogeographical sense, and (unlike fuzzy entropy) the results are comparable only between models based on the same number of presences + absences (Estrada & Real 2021).

Value

This function returns a numeric value of entropy for 'data' (if it is a numeric vector) or for each of 'sp.cols' in 'data' (if it is a matrix or data frame). Optionally (and by default), a barplot is also produced with these values (if there is more than one column) for visual comparison.

Author(s)

A. Marcia Barbosa

References

- Estrada A. & Real R. (2021) A stepwise assessment of parsimony and fuzzy entropy in species distribution modelling. *Entropy*, 23: 1014
- Kosko B. (1986) Fuzzy entropy and conditioning. *Information Sciences*, 40: 165-174
- Shannon C.E. (1948) A mathematical theory of communication. *Bell System Technical Journal*, 27: 379-423

Examples

```
data(rotif.env)

pred <- multGLM(rotif.env, sp.cols = 18:20, var.cols = 5:17)$predictions

head(pred)

entropy(pred, sp.cols = c("Abrigh_F", "Afissa_F", "Apriod_F"))

entropy(pred, sp.cols = c("Abrigh_P", "Afissa_P", "Apriod_P"), method = "Shannon")
```

Fav

Favourability (probability without the effect of sample prevalence)

Description

Computes prevalence-independent favourability for a species' presence, based on a presence/(pseudo)absence model object, or on a vector of predicted probability values plus either the modelled binary response variable, the total number of modelled ones and zeros, or the prevalence (proportion of ones) in the modelled binary response (i.e., in the training data).

Usage

```
Fav(model = NULL, obs = NULL, pred = NULL, n1n0 = NULL, sample.preval = NULL,
method = "RBV", true.preval = NULL, verbosity = 2)
```

Arguments

- | | |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| model | a binary-response, presence/(pseudo)absence probability-producing model object of class "glm", "gam", "gbm", "randomForest" or "bart" (computed with <code>keeptrees=TRUE</code>). |
| obs | alternatively to 'model', a vector of the 1 and 0 values of the binary response variable (e.g. presence-absence of a species) in the model training data. This argument is ignored if 'model' is provided. |
| pred | alternatively to 'model', a numeric vector, RasterLayer or SpatRaster of predicted presence probability values, produced by a presence/(pseudo)absence modelling method yielding presence probability. This argument is ignored if 'model' is provided. |

<code>n1n0</code>	alternatively to 'obs' or 'sample.preval', an integer vector of length 2 providing the total numbers of modelled ones and zeros (in this order) of the binary response variable in the model training data. Ignored if 'obs' or 'model' is provided.
<code>sample.preval</code>	alternatively to 'obs' or 'n1n0', the prevalence (proportion of ones) of the binary response variable in the model training data. Ignored if 'model' is provided.
<code>method</code>	either "RBV" for the original Real, Barbosa & Vargas (2006) procedure, or "AT" if you want to try out the modification proposed by Albert & Thuiller (2008) (but see Details!).
<code>true.preval</code>	the true prevalence (as opposed to sample prevalence), necessary if you want to try the "AT" method (but see Details!).
<code>verbosity</code>	numeric value indicating the amount of messages to display; currently meaningful values are 0, 1, and 2 (the default).

Details

Methods such as Generalized Linear Models, Generalized Additive Models, Random Forests, Boosted Regression Trees / Generalized Boosted Models, Bayesian Additive Regression Trees and several others, are widely used for modelling species' potential distributions using presence/absence data and a set of predictor variables. These models predict presence probability, which incorporates the prevalence (proportion of presences) of the species in the modelled sample. So, predictions for restricted species are always generally low, while predictions for widespread species are always generally higher, regardless of the actual environmental quality. Barbosa (2006) and Real, Barbosa & Vargas (2006) proposed an environmental favourability function which is based on presence probability and cancels out uneven proportions of presences and absences in the modelled data. Favourability thus assesses the extent to which the environmental conditions change the probability of occurrence of a species with respect to its overall prevalence in the study area. Model predictions become, therefore, directly comparable among species with different prevalences. The favourability function is implemented in the **fuzzySim** package and is also in the SAM (Spatial Analysis in Macroecology) software (Rangel et al. 2010).

Using simulated data, Albert & Thuiller (2008) proposed a modification to the favourability function, but it requires knowing the true prevalence of the species (not just the prevalence in the modelled sample), which is rarely possible in real-world modelling. Besides, this suggestion was based on the misunderstanding that the favourability function was a way to obtain the probability of occurrence when prevalence differs from 50%, which is incorrect (see Acevedo & Real 2012).

To get environmental favourability with either the Real, Barbosa & Vargas ("RBV") or the Albert & Thuiller ("AT") method, you just need to get model predictions of presence probability from your data, together with the proportions of presences and absences in the modelled sample, and then use the 'Fav' function. Input data for this function are either a model object resulting from the `glm` function, or the vector of presences-absences (1-0) of your species and the corresponding presence probability values, obtained e.g. with `predict(mymodel, mydata, type = "response")`. Alternatively to the presences-absences, you can provide either the sample prevalence or the numbers of presences and absences in the dataset that was used to generate the presence probabilities. In case you want to use the "AT" method, you also need to provide the true (absolute) prevalence of your species.

Value

If 'model' is provided or if 'pred' is a numeric vector, the function returns a numeric vector of the favourability values. If 'model' is not provided (which would override other arguments) and 'pred' is a RasterLayer or a SpatRaster, the function returns an object of the same class, containing the favourability values.

Author(s)

A. Marcia Barbosa

References

Acevedo P. & Real R. (2012) Favourability: concept, distinctive characteristics and potential usefulness. *Naturwissenschaften* 99: 515-522

Albert C.H. & Thuiller W. (2008) Favourability functions versus probability of presence: advantages and misuses. *Ecography* 31: 417-422.

Barbosa A.M.E. (2006) Modelacion de relaciones biogeograficas entre predadores, presas y parásitos: implicaciones para la conservacion de mamiferos en la Peninsula Iberica. PhD Thesis, University of Malaga (Spain).

Rangel T.F.L.V.B, Diniz-Filho J.A.F & Bini L.M. (2010) SAM: a comprehensive application for Spatial Analysis in Macroecology. *Ecography* 33: 46-50.

Real R., Barbosa A.M. & Vargas J.M. (2006) Obtaining environmental favourability functions from logistic regression. *Environmental and Ecological Statistics* 13: 237-245.

See Also

[multGLM](#)

Examples

```
# obtain a probability model and its predictions:

data(rotif.env)

names(rotif.env)

mod <- with(rotif.env, glm(Abrigh ~ Area + Altitude +
  AltitudeRange + HabitatDiversity + HumanPopulation,
  family = binomial))

prob <- predict(mod, data = rotif.env, type = "response")

# obtain predicted favourability in different ways:

Fav(model = mod)

Fav(obs = rotif.env$Abrigh, pred = prob)
```

```
Fav(pred = mod$fitted.values, n1n0 = c(112, 179))

Fav(pred = mod$fitted.values, sample.preval = 0.38)
```

favClass

Classify favourability into 3 categories (low, intermediate, high)

Description

This function takes a vector of [Favourability](#) values and reclassifies them into 3 increasing categories: low, intermediate or high. By default, the breaks between these classes are 0.2 and 0.8 (see [Details](#)), although these can be changed by the user.

Usage

```
favClass(fav, breaks = c(0.2, 0.8), character = FALSE)
```

Arguments

fav	a numeric vector of favourability values (obtained, e.g., with functions Fav or multGLM).
breaks	a numeric vector of length 2 containing the two values which will divide fav into the 3 classes. Defaults to c(0.2, 0.8) following the literature (see Details).
character	logical value indicating whether the result should be returned in character rather than numeric form. Defaults to FALSE.

Details

Some applications of species distribution models imply setting a threshold to separate areas with high and low probability or favourability for occurrence (see, e.g., [bioThreat](#)). However, it makes little sense to establish as markedly different areas with, for example, 0.49 and 0.51 favourability values (Hosmer & Lemeshow, 1989). It may thus be wiser to open a gap between values considered as clearly favourable and clearly unfavourable. When this option is taken in the literature, commonly used breaks are 0.8 as a threshold to classify highly favourable values, as the odds are more than 4:1 favourable to the species; 0.2 as a threshold below which to consider highly unfavourable values, as odds are less than 1:4; and classifying the remaining values as intermediate favourability (e.g., Munoz & Real 2006, Olivero et al. 2016).

Value

This function returns either an integer or a character vector (following the 'character' argument, which is set to FALSE by default), of the same length as fav, reclassifying it into 3 categories: 1 ('low'), 2 ('intermediate'), or 3 ('high').

Author(s)

A. Marcia Barbosa

References

- Hosmer D.W. Jr & Lemeshow S. (1989) Applied logistic regression. John Wiley & Sons, New York
- Munoz A.R. & Real R. (2006) Assessing the potential range expansion of the exotic monk parakeet in Spain. *Diversity and Distributions*, 12: 656-665
- Olivero J., Fa J.E., Real R., Farfan M.A., Marquez A.L., Vargas J.M., Gonzalez J.P., Cunningham A.A. & Nasi R. (2017) Mammalian biogeography and the Ebola virus in Africa. *Mammal Review*, 47: 24-37

See Also

[Fav](#), [multGLM](#)

Examples

```
data(rotif.env)
mods <- multGLM(rotif.env, sp.cols = 20, var.cols = 5:17)
fav <- mods$predictions[, 2]
data.frame(fav = fav, favcl_num = favClass(fav),
  favcl_chr = favClass(fav, character = TRUE))
```

FDR

False Discovery Rate

Description

Calculate the false discovery rate (type I error) under repeated testing and determine which variables to select and to exclude from multivariate analysis.

Usage

```
FDR(data = NULL, sp.cols = NULL, var.cols = NULL, pvalues = NULL,
  model.type = NULL, family = "auto", correction = "fdr", q = 0.05,
  verbose = TRUE, simplif = FALSE)
```

Arguments

- | | |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data</code> | a data frame containing the response and predictor variables (one in each column). |
| <code>sp.cols</code> | name or index number of the column containing the response variable (currently implemented for only one response variable at a time). |
| <code>var.cols</code> | names or index numbers of the columns containing the predictor variables. |
| <code>pvalues</code> | optionally, instead of 'data', 'sp.cols' and 'var.cols', a data frame with the names of the predictor variables in the first column and their bivariate p-values (obtained elsewhere) in the second column. Example: <code>pvalues <- data.frame(var = letters[1:5], pval = c(0.02, 0.004, 0.07, 0.03, 0.05))</code> . |

<code>model.type</code>	this argument (previously a character value, either "LM" or "GLM") is now deprecated and ignored with a warning if provided. This information is now included in argument 'family' – e.g., if you want linear models (LM), you can set 'family = "gaussian"".
<code>family</code>	The error distribution and (optionally) the link function to use (see glm or family for details). The default "auto" automatically uses "binomial" family for response variables containing only values of 0 and 1; "poisson" for positive integer responses (i.e. count data); "Gamma" for positive non-integer; and "gaussian" (i.e., linear models) otherwise.
<code>correction</code>	the correction procedure to apply to the p-values; see p.adjust.methods for available options and p.adjust for more information. The default is "fdr".
<code>q</code>	the threshold value of FDR-corrected significance above which to reject variables. Defaults to 0.05.
<code>verbose</code>	logical value indicating whether to display messages.
<code>simplif</code>	logical value indicating if simplified results should be provided (see Value).

Details

It is common in ecology to search for statistical relationships between species' occurrence and a set of predictor variables. However, when a large number of variables is analysed (compared to the number of observations), false findings may arise due to repeated testing. Garcia (2003) recommended controlling the false discovery rate (FDR; Benjamini & Hochberg 1995) in ecological studies. The [p.adjust](#) R function performs this and other corrections to the significance (p) values of variables under repeated testing. The 'FDR' function performs repeated regressions (either linear or logistic) or uses already-obtained p values for a set of variables; calculates the FDR with 'p.adjust'; and shows which variables should be retained for or excluded from further multivariate analysis according to their corrected p values (see, for example, Barbosa, Real & Vargas 2009).

The FDR function uses the Benjamini & Hochberg ("BH", alias "fdr") correction by default, but check the [p.adjust](#) documentation for other available methods, namely "BY", which allows for non-independent data. Input data may be the response variable (for example, the presence-absence or abundance of a species) and the predictors (a table with one independent variable in each column, with the same number of rows and in the same order as the response); there should be no missing values in the data. Alternatively, you may already have performed the univariate regressions and have a set of variables and corresponding p values which you want to correct with FDR; in this case, get a table with your variables' names in the first column and their p values in the second column, and supply it as the 'pvalues' argument (no need to provide response or predictors in this case).

Value

If `simplif = TRUE`, this function returns a data frame with the variables' names as row names and 4 columns containing, respectively, their individual (bivariate) coefficients against the response, their individual AIC (Akaike's Information Criterion; Akaike, 1973), BIC (Bayesian Information Criterion, also known as Schwarz criterion, SBC, SBIC; Schwarz, 1978), p-value and adjusted p-value according to the applied 'correction'. If `simplif = FALSE` (the default), the result is a list of two such data frames:

<code>exclude</code>	with the variables to exclude.
<code>select</code>	with the variables to select (under the given 'q' value).

Author(s)

A. Marcia Barbosa

References

Akaike, H. (1973) Information theory and an extension of the maximum likelihood principle. In: Petrov B.N. & Csaki F., 2nd International Symposium on Information Theory, Tsahkadsor, Armenia, USSR, September 2-8, 1971, Budapest: Akademiai Kiado, p. 267-281.

Barbosa A.M., Real R. & Vargas J.M (2009) Transferability of environmental favourability models in geographic space: The case of the Iberian desman (*Galemys pyrenaicus*) in Portugal and Spain. *Ecological Modelling* 220: 747-754

Benjamini Y. & Hochberg Y. (1995) Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society, Series B* 57: 289-300

Garcia L.V. (2003) Controlling the false discovery rate in ecological research. *Trends in Ecology and Evolution* 18: 553-554

Schwarz, G.E. (1978) Estimating the dimension of a model. *Annals of Statistics*, 6 (2): 461-464.

See Also

[p.adjust](#)

Examples

```
data(rotif.env)

names(rotif.env)

FDR(data = rotif.env, sp.cols = 18, var.cols = 5:17)

FDR(data = rotif.env, sp.cols = 18, var.cols = 5:17, simplif = TRUE)

my_pvalues <- data.frame(var = letters[1:5], pval = c(0.02, 0.004, 0.07, 0.03, 0.05))
FDR(pvalues = my_pvalues)
```

fuzSim

Fuzzy similarity

Description

This function calculates fuzzy similarity, based on a fuzzy version of the binary similarity index specified in method, between two binary (0 or 1) or fuzzy (between 0 and 1) variables.

Usage

```
fuzSim(x, y, method, na.rm = TRUE)
```

Arguments

<code>x</code>	a vector of (optionally fuzzy) presence-absence data, with 1 meaning presence, 0 meaning absence, and values in between meaning fuzzy presence (or the degree to which each locality belongs to the set of species presences, or to which each species belongs to the locality; Zadeh, 1965). Fuzzy presence-absence can be obtained, for example, with functions <code>multGLM</code> , <code>multTSA</code> or <code>distPres</code> in this package.
<code>y</code>	a vector similar to 'x', of the same length and in the same order.
<code>method</code>	the similarity index to use. Currently available options are "Jaccard", "Sorensen", "Simpson" and "Baroni" (see Details).
<code>na.rm</code>	logical value indicating whether NA values should be ignored. The default is TRUE.

Details

Similarity between ecological communities, beta diversity patterns, biotic regions, and distributional relationships among species are commonly determined based on pair-wise (dis)similarities in species' occurrence patterns. Some of the most commonly employed similarity indices are those of Jaccard (1901), Sorensen (1948), Simpson (1960) and Baroni-Urbani & Buser (1976), which are here implemented in their fuzzy versions (Barbosa, 2015), able to deal with both binary and fuzzy data. Jaccard's and Baroni's indices have associated tables of significant values (Baroni-Urbani & Buser 1976, Real & Vargas 1996, Real 1999).

Value

The function returns a value between 0 and 1 representing the fuzzy similarity between the provided 'x' and 'y' vectors. Note, for example, that Jaccard similarity can be converted to dissimilarity (or Jaccard distance) if subtracted from 1, while 1-Sorensen is not a proper distance metric as it lacks the property of triangle inequality (see https://en.wikipedia.org/wiki/S%C3%B8rensen%E2%80%9380%93Dice_coefficient).

Note

The formulas used in this function may look slightly different from some of their published versions (e.g. Baroni-Urbani & Buser 1976), not only because the letters are switched, but because here the A and B are the numbers of attributes present in each element, whether or not they are also present in the other one. Thus, our 'A+B' is equivalent to 'A+B+C' in formulas where A and B are the numbers of attributes present in one but not the other element, and our A+B-C is equivalent to their A+B+C. The formulas used here (adapted from Olivero et al. 1998) are faster to calculate, visibly for large datasets.

Author(s)

A. Marcia Barbosa

References

- Barbosa A.M. (2015) fuzzySim: applying fuzzy logic to binary similarity indices in ecology. *Methods in Ecology and Evolution*, 6: 853-858.
- Baroni-Urbani C. & Buser M.W. (1976) Similarity of Binary Data. *Systematic Zoology*, 25: 251-259
- Jaccard P. (1901) Etude comparative de la distribution florale dans une portion des Alpes et des Jura. *Memoires de la Societe Vaudoise des Sciences Naturelles*, 37: 547-579
- Olivero J., Real R. & Vargas J.M. (1998) Distribution of breeding, wintering and resident waterbirds in Europe: biotic regions and the macroclimate. *Ornis Fennica*, 75: 153-175
- Real R. (1999) Tables of significant values of Jaccard's index of similarity. *Miscellanea Zoologica* 22: 29:40
- Real R. & Vargas J.M (1996) The probabilistic basis of Jaccard's index of similarity. *Systematic Biology* 45: 380-385
- Simpson, G.G. (1960) Notes on the measurement of faunal resemblance. *Amer. J. Sci.* 258A, 300-311
- Sorensen T. (1948) A method of establishing groups of equal amplitude in plant sociology based on similarity of species and its application to analyses of the vegetation on Danish commons. *Kongelige Danske Videnskabernes Selskab*, 5(4): 1-34
- Zadeh L.A. (1965) Fuzzy sets. *Information and Control*, 8: 338-353

See Also

[simMat](#); [modOverlap](#)

Examples

```
data(rotif.env)

names(rotif.env)

# you can calculate similarity between binary species occurrence patterns:

fuzSim(rotif.env[, "Abrigh"], rotif.env[, "Afissa"], method = "Jaccard")
fuzSim(rotif.env[, "Abrigh"], rotif.env[, "Afissa"], method = "Sorensen")
fuzSim(rotif.env[, "Abrigh"], rotif.env[, "Afissa"], method = "Simpson")
fuzSim(rotif.env[, "Abrigh"], rotif.env[, "Afissa"], method = "Baroni")

# or you can model environmental favourability for these species
# and calculate fuzzy similarity between their environmental predictions
# which goes beyond the strict coincidence of their occurrence records:

fav <- multGLM(rotif.env, sp.cols = 18:19, var.cols = 5:17, step = TRUE,
FDR = TRUE, trim = TRUE, P = FALSE, Fav = TRUE) $ predictions

fuzSim(fav[, "Abrigh_F"], fav[, "Afissa_F"], method = "Jaccard")
fuzSim(fav[, "Abrigh_F"], fav[, "Afissa_F"], method = "Sorensen")
```

```
fuzSim(fav[, "Abrigh_F"], fav[, "Afissa_F"], method = "Simpson")
fuzSim(fav[, "Abrigh_F"], fav[, "Afissa_F"], method = "Baroni")
```

fuzzyOverlay

Row-wise overlay operations based on fuzzy logic

Description

Logical and set operations are useful for comparative distribution modelling, to assess consensus or mismatches between the predictions of different models, and to quantify differences between models obtained for different time periods. Fuzzy set theory (Zadeh 1965, Barbosa & Real 2012) allows performing such operations without converting model predictions from continuous to binary, thus avoiding the application of arbitrary thresholds and the distortion or over-simplification of those predictions. The result is a continuous numerical value quantifying the intersection, union, sum, or other operation among model predictions, whether binary or continuous.

Usage

```
fuzzyOverlay(data, overlay.cols = 1:ncol(data), op = "intersection",
na.rm = FALSE, round.digits = 2)
```

Arguments

data	matrix or data frame containing the model predictions to compare.
overlay.cols	vector of the names or index numbers of the columns to compare. The default is all columns in data.
op	character value indicating the operation to perform between the prediction columns in 'data'. Can be "consensus" for the arithmetic mean of predictions (or the fuzzy equivalent of the proportion of models that agree that the species occurs at each site), "fuzzy_and" or "intersection" for fuzzy intersection; "fuzzy_or" or "union" for fuzzy union; "prob_and" or "prob_or" for probabilistic and/or, respectively (see Details); "maintenance" for the values where all predictions for the same row (rounded to the number of digits specified in the next argument) are the same. If 'data' has only two columns to compare, you can also calculate "xor" for exclusive 'or', "AnotB" for the occurrence of the species in column 1 in detriment of that in column 2, "expansion" for the prediction increase in rows where column 2 has higher values than column 1, "contraction" for the prediction decrease in rows where column 2 has lower values than column 1, or "change" for a mix of the latter two, with positive values where there has been an increase and negative values where there was decrease in favourability from columns 1 to 2. For expansion, contraction and maintenance, rows where the values do not satisfy the condition (i.e. second column larger, smaller, or roughly equal to the first column) get a value of zero.
na.rm	logical value indicating if NA values should be ignored. The default is FALSE, so rows with NA in any of the prediction columns get NA as a result.
round.digits	integer value indicating the number of decimal places to be used if op = "maintenance". The default is 2.

Details

If your predictions are probabilities, "prob_and" (probabilistic 'and') gives the probability of all species in 'data' occurring simultaneously by multiplying all probabilities; and "prob_or" (probabilistic 'or') gives the probability of any of them occurring at each site. These can be quite restrictive, though; probabilistic "and" can give particularly unrealistically small values.

If you have (or convert your probabilities to) favourability predictions, which can be used directly with fuzzy logic (Real et al. 2006; see [Fav](#) function), you can use "fuzzy_and" or "intersection" to get the favourability for all species co-occurring at each site, and "fuzzy_or" or "union" to get favourability for any of them to occur at each site (Barbosa & Real 2012).

Value

This function returns a vector, with length equal to the number of rows in data, containing the row-wise result of the operation performed.

Author(s)

A. Marcia Barbosa

References

- Barbosa A.M. & Real R. (2012) Applying fuzzy logic to comparative distribution modelling: a case study with two sympatric amphibians. *The Scientific World Journal*, 2012, Article ID 428206
- Real R., Barbosa A.M. & Vargas J.M. (2006) Obtaining environmental favourability functions from logistic regression. *Environmental and Ecological Statistics* 13: 237-245.
- Zadeh, L.A. (1965) Fuzzy sets. *Information and Control*, 8: 338-353

See Also

[fuzSim](#), [modOverlap](#) and [fuzzyRangeChange](#) for overall (not row-wise) comparisons among model predictions.

Examples

```
data(rotif.env)

names(rotif.env)

# get model predictions for 3 of the species in rotif.env:

mods <- multGLM(rotif.env, sp.cols = 18:20, var.cols = 5:17, id.col = 1,
  step = TRUE, FDR = TRUE, trim = TRUE)

preds <- mods$predictions[ , c("Abrigh_F", "Afissa_F", "Apriod_F")]

# calculate intersection and union among those predictions:
```

```

preds$intersect <- fuzzyOverlay(preds, op = "intersection")

preds$union <- fuzzyOverlay(preds, op = "union")

head(preds)

# imagine you have a model prediction for species 'Abrigh' in a future time
# (here we will create one by randomly jittering the current predictions)

preds$Abrigh_imag <- jitter(preds[, "Abrigh_F"], amount = 0.2)
preds$Abrigh_imag[preds$Abrigh_imag < 0] <- 0
preds$Abrigh_imag[preds$Abrigh_imag > 1] <- 1

# you can calculate row-wise prediction changes from Abrigh to Abrigh_imag:

preds$Abrigh_exp <- fuzzyOverlay(preds, overlay.cols = c("Abrigh_F",
"Abrigh_imag"), op = "expansion")

preds$Abrigh_contr <- fuzzyOverlay(preds, overlay.cols = c("Abrigh_F",
"Abrigh_imag"), op = "contraction")

preds$Abrigh_chg <- fuzzyOverlay(preds, overlay.cols = c("Abrigh_F",
"Abrigh_imag"), op = "change")

preds$Abrigh_maint <- fuzzyOverlay(preds, overlay.cols = c("Abrigh_F",
"Abrigh_imag"), op = "maintenance")

head(preds)

```

fuzzyRangeChange

Range change based on continuous (fuzzy) values

Description

This function quantifies overall range change (expansion, contraction, maintenance and balance) based on either presence-absence data or the continuous predictions of two models.

Usage

```

fuzzyRangeChange(pred1, pred2, number = TRUE, prop = TRUE,
na.rm = TRUE, round.digits = 2, measures = c("Gain", "Loss",
"Stable presence", "Stable absence", "Balance"), plot = TRUE, ...)

```

Arguments

pred1	numeric vector containing the predictions (between 0 and 1) of the model that will serve as reference.
-------	--------------------------------------------------------------------------------------------------------

pred2	numeric vector containing the predictions (between 0 and 1) of the model whose change will be calculated. Must be of the same length and in the same order as 'pred1'.
number	logical value indicating if results should include the fuzzy number of cases. The default is TRUE.
prop	logical value indicating if results should include the proportion of the total number of cases. The default is TRUE.
na.rm	logical value indicating whether NA values should be ignored. The default is TRUE.
round.digits	argument to pass to fuzzyOverlay , indicating the number of decimal places to which to round 'pred' for calculating 'maintenance' or 'stability'. The default is 2.
measures	character vector listing the range change measures to calculate. The default is all available measures.
plot	logical value indicating whether to make a barplot with the results. The default is TRUE.
...	additional arguments to be passed to the barplot function (if plot = TRUE).

Value

This function returns a data frame with the following values in different rows (among those that are included in 'measures'):

Gain	sum of the predicted values that have increased from 'pred1' to 'pred2' (fuzzy equivalent of the number of gained presences)
Loss	sum of the predicted values that have decreased from 'pred1' to 'pred2' (fuzzy equivalent of the number of lost presences)
Stable_presence	fuzzy equivalent of the number of predicted presences that have remained as such (when rounded to 'round.digits') between 'pred1' and 'pred2'
Stable_absence	fuzzy equivalent of the number of predicted absences that have remained as such (when rounded to 'round.digits') between 'pred1' and 'pred2')
Balance	sum of the change in predicted values from 'pred1' to 'pred2' (fuzzy equivalent of the balance of gained and lost presences)

If prop = TRUE (the default), there is an additional column named "Proportion" in which these values are divided by the total number of reference values (i.e., the fuzzy range or non-range size). If plot = TRUE (the default), a barplot is also produced representing the last column of the result data frame.

Author(s)

A. Marcia Barbosa

See Also

[fuzSim](#), [modOverlap](#) for other ways to compare models; [fuzzyOverlay](#) for row-wise model comparisons

Examples

```
# get an environmental favourability model for a rotifer species:

data(rotif.env)

names(rotif.env)

fav_current <- multGLM(rotif.env, sp.cols = 18, var.cols = 5:17,
step = TRUE, FDR = TRUE, trim = TRUE, P = FALSE, Fav = TRUE) $
predictions

# imagine you have a model prediction for this species in a future time
# (here we will create one by randomly jittering the current predictions)

fav_imag <- jitter(fav_current, amount = 0.2)
fav_imag[fav_imag < 0] <- 0
fav_imag[fav_imag > 1] <- 1

# calculate range change given by current and imaginary future predictions:

fuzzyRangeChange(fav_current, fav_imag)

fuzzyRangeChange(fav_current, fav_imag, number = FALSE)

fuzzyRangeChange(fav_current, fav_imag, ylim = c(-1, 1),
ylab = "Proportional change")
```

getPreds

Get model predictions

Description

This function allows getting the predictions of multiple models when applied to a given dataset. It can be useful if you have a list of model objects (e.g. resulting from [multGLM](#)) and want to apply them to a new data set containing the same variables for another region or time period. There are options to include the logit link ('Y') and/or 'Favourability' (see [Fav](#)).

Usage

```
getPreds(data, models, id.col = NULL, Y = FALSE, P = TRUE,
Favourability = TRUE, incl.input = FALSE, verbosity = 2)
```

Arguments

data	an object of class either 'data.frame' or 'RasterStack' to which to apply the 'models' (below) to get their predictions; must contain all variables (with the same names, case-sensitive) included in any of the 'models'.
------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<code>models</code>	an object of class 'list' containing one or more model objects, obtained e.g. with function <code>glm</code> or <code>multGLM</code> .
<code>id.col</code>	optionally, the index number of a column of 'data' containing row identifiers, to be included in the result. Ignored if <code>incl.input = TRUE</code> , or if 'data' is a RasterStack rather than a data frame.
<code>Y</code>	logical, whether to include the logit link (y) value in the predictions.
<code>P</code>	logical, whether to include the probability value in the predictions.
<code>Favourability</code>	logical, whether to include Favourability in the predictions (see Fav).
<code>incl.input</code>	logical, whether to include input columns in the output data frame (if the 'data' input is a data frame too). The default is <code>FALSE</code> .
<code>verbosity</code>	numeric value indicating the amount of messages to display; currently meaningful values are 0, 1, and 2 (the default).

Value

This function returns the model predictions in an object of the same class as the input 'data', i.e. either a data frame or a RasterStack.

Author(s)

A. Marcia Barbosa

See Also

[multGLM](#), [predict](#)

Examples

```
data(rotif.env)

names(rotif.env)

# identify rotifer data in the Eastern and Western hemispheres:

unique(rotif.env$CONTINENT)

rotif.env$HEMISPHERE <- "Eastern"

rotif.env$HEMISPHERE[rotif.env$CONTINENT %in%
c("NORTHERN_AMERICA", "SOUTHERN_AMERICA")] <- "Western"

head(rotif.env)

# separate the rotifer data into hemispheres

east.hem <- rotif.env[rotif.env$HEMISPHERE == "Eastern", ]
west.hem <- rotif.env[rotif.env$HEMISPHERE == "Western", ]
```

```
# make models for 3 of the species in rotif.env based on their distribution
# in the Eastern hemisphere:

mods <- multGLM(east.hem, sp.cols = 18:20, var.cols = 5:17,
  id.col = 1, step = FALSE, FDR = FALSE, trim = FALSE)

# get the models' predictions for the Western hemisphere dataset:

preds <- getPreds(west.hem, models = mods$models, P = TRUE,
  Favourability = TRUE)

head(preds)
```

gridRecords	<i>Grid (or thin) point occurrence records to the resolution of a raster map</i>
-------------	----------------------------------------------------------------------------------

Description

This function takes a Raster* or SpatRaster object and a set of spatial coordinates of a species' presence (and optionally absence) records, and returns a data frame with the presences and absences as well as the corresponding values of the rasters in the grid of pixels (cells). This is analogous to removing duplicates and thinning points (both presences and absences) with a distance equal to the pixel size of the raster map(s) on which analysis will be based.

Usage

```
gridRecords(rst, pres.coords, abs.coords = NULL, absences = TRUE,
  species = NULL, na.rm = TRUE)
```

Arguments

rst	a Raster* or SpatRaster object (the latter is processed faster) with the desired spatial resolution and extent for the species presence-(pseudo)absence data, and the layer(s) whose values to extract for those data.
pres.coords	a matrix or data frame with two columns containing, respectively, the x and y, or longitude and latitude coordinates (in this order, and in the same coordinate reference system as 'rst') of the points where species presence was detected.
abs.coords	(optional) same as 'pres.coords' but for points where the species was not detected. If NULL and if absences=TRUE (the default), all pixels that are not intersected by 'pres.coords' will be returned as absence cells.
absences	logical value indicating whether pixels without presence records should be returned as absences. The default is TRUE.

species	(optional) character vector, of the same length as 'nrow(pres.coords)', indicating the species to which each pair of coordinates corresponds. Useful for gridding records of more than one species at a time. If specified, 'abs.coords' cannot be used.
na.rm	Logical value indicating whether pixels without values in any of the 'rst' layers should be removed from the resulting data frame. The default is TRUE.

Details

See e.g. Baez et al. (2020), where this function was used to get unique presences and absences from point occurrence data at the spatial resolution of marine raster variables.

Value

This function returns a data frame with the following columns:

'presence'	integer, 1 for the cells (pixels) with at least one presence point, and 0 for the cells without any presence point (if absences = TRUE) or with at least one absence point (if 'abs.coords' are provided) AND with no presence points. If the 'species' argument is provided, instead of 'presence' you get one column named as each species.
'x', 'y'	centroid coordinates of each cell (pixel).
'cell'	the pixel identifier in 'rst'.
one column for each layer in 'rst'	value of each pixel for each layer.

Note

This function requires either the **raster** or the **terra** package, depending on the class of 'rst'.

Author(s)

A. Marcia Barbosa

References

Baez J.C., Barbosa A.M., Pascual P., Ramos M.L. & Abascal F. (2020) Ensemble modelling of the potential distribution of the whale shark in the Atlantic Ocean. *Ecology and Evolution*, 10: 175-184

See Also

'extract' in package **raster** or in package **terra**

Examples

```
## Not run:

# you can run these examples if you have the 'terra' package installed
require(terra)
```

```

# import a raster map and aggregate it to a coarser resolution:
r <- rast(system.file("ex/elev.tif", package = "terra"))
r <- aggregate(r, 6)
plot(r)

# generate some random presence and absence points:
set.seed(123)
presences <- terra::spatSample(as.polygons(r), 100)
set.seed(456)
absences <- terra::spatSample(as.polygons(r), 70)
points(presences, pch = 20, cex = 0.3, col = "black")
points(absences, pch = 20, cex = 0.3, col = "white")

# use 'gridRecords' on these random points:
gridded_pts <- gridRecords(rst = r, pres.coords = terra::crds(presences), abs.coords = terra::crds(absences))
head(gridded_pts)

# map the gridded points (presences black, absences white):
points(gridded_pts[, c("x", "y")], col = gridded_pts$presence)

# you can also do it with only presence (no absence) records
# in this case, by default (with 'absences = TRUE'),
# all pixels without presence points are returned as absences:

gridded_pres <- gridRecords(rst = r, pres.coords = terra::crds(presences))
head(gridded_pres)
plot(r)
points(presences, pch = 20, cex = 0.2, col = "black")
points(gridded_pres[, c("x", "y")], col = gridded_pres$presence)

# with only presence (no absence) records, as in this latter case,
# you can grid records for multiple species at a time
# by adding a 'species' argument

presences$species <- rep(c("species1", "species2", "species3"), each = 33)
data.frame(presences)
plot(r)
plot(presences, col = as.factor(presences$species), add = TRUE)
gridded_pres_mult <- gridRecords(rst = r, pres.coords = terra::crds(presences), species = presences$species)
head(gridded_pres_mult)

## End(Not run)

```

Description

This function detects which numeric columns in a data frame contain only whole numbers, and converts those columns to integer class, so that they take up less space.

Usage

```
integerCols(data)
```

Arguments

`data` a data frame containing possibly integer columns classified as "numeric".

Value

The function returns a data frame with the same columns as 'data', but with those that are numeric and contain only whole numbers (possibly including NA) now classified as "integer".

Author(s)

A. Marcia Barbosa

See Also

[is.integer](#), [as.integer](#), [multConvert](#)

Examples

```
dat <- data.frame(
  var1 = 1:10,
  var2 = as.numeric(1:10),
  var3 = as.numeric(c(1:4, NA, 6:10)),
  var4 = as.numeric(c(1:3, NaN, 5, Inf, 7, -Inf, 9:10)),
  var5 = as.character(1:10),
  var6 = seq(0.1, 1, by = 0.1),
  var7 = letters[1:10]
) # creates a sample data frame

dat

str(dat)
# var2 classified as "numeric" but contains only whole numbers
# var3 same as var2 but containing also NA values
# var4 same as var2 but containing also NaN and infinite values
# var5 contains only whole numbers but initially classified as factor

dat <- integerCols(dat)

str(dat)
# var2 and var3 now classified as "integer"
# var4 remains as numeric because contains infinite and NaN
# (not integer) values
# var5 remains as factor
```

modelTrim

Trim off non-significant variables from a model

Description

This function performs a stepwise removal of non-significant variables from a model.

Usage

```
modelTrim(model, method = "summary", alpha = 0.05)
```

Arguments

model	a model object.
method	the method for getting the individual p-values. Can be either "summary" for the p-values of the coefficient estimates, or "anova" for the p-values of the variables themselves (see Details).
alpha	the p-value above which a variable is removed.

Details

Stepwise variable selection is a common procedure for simplifying models. It maximizes predictive efficiency in an objective and reproducible way, and is useful when the individual importance of the predictors is not known a priori (Hosmer & Lemeshow, 2000). The [step](#) R function performs such procedure using an information criterion (AIC) to select the variables, but it often leaves variables that are not significant in the model. Such variables can be subsequently removed with a manual stepwise procedure (e.g. Crawley 2007, p. 442; Barbosa & Real 2010, 2012; Estrada & Arroyo 2012). The 'modelTrim' function performs such removal automatically until all remaining variables are significant. It can also be applied to a full model (i.e., without previous use of the step function), as it serves as a backward stepwise selection procedure based on the significance of the coefficients (if method = "summary", the default) or on the significance of the variables themselves (if method = "anova", better when there are categorical variables in the model).

Value

The input model object after removal of non-significant variables.

Author(s)

A. Marcia Barbosa

References

Barbosa A.M. & Real R. (2010) Favourable areas for expansion and reintroduction of Iberian lynx accounting for distribution trends and genetic diversity of the European rabbit. *Wildlife Biology in Practice* 6: 34-47

Barbosa A.M. & Real R. (2012) Applying fuzzy logic to comparative distribution modelling: a case study with two sympatric amphibians. The Scientific World Journal, Article ID 428206

Crawley M.J. (2007) The R Book. John Wiley & Sons, Chichester (UK)

Estrada A. & Arroyo B. (2012) Occurrence vs abundance models: Differences between species with varying aggregation patterns. Biological Conservation, 152: 37-45

Hosmer D. W. & Lemeshow S. (2000) Applied Logistic Regression (2nd ed). John Wiley and Sons, New York

See Also

[step](#)

Examples

```
# load sample data:

data(rotif.env)

names(rotif.env)

# build a stepwise model of a species' occurrence based on
# some of the variables:

mod <- with(rotif.env, step(glm(Abrigh ~ Area + Altitude + AltitudeRange +
HabitatDiversity + HumanPopulation, family = binomial)))

# examine the model:

summary(mod) # contains non-significant variables

# use modelTrim to get rid of non-significan effects:

mod <- modelTrim(mod)

summary(mod) # only significant variables now
```

modOverlap

Overall overlap between model predictions

Description

This function calculates the degree of overlap between the predictions of two models, using niche comparison metrics such as Schoener's D, Hellinger distance and Warren's I.

Usage

```
modOverlap(pred1, pred2, na.rm = TRUE)
```

Arguments

pred1	numeric vector of the predictions of a generalized linear model (values between 0 and 1).
pred2	numeric vector of the predictions of another generalized linear model; must be of the same length and in the same order as 'pred1'.
na.rm	logical value indicating whether NA values should be removed prior to calculation. The default is TRUE.

Details

See Warren et al. (2008).

Value

This function returns a list of 3 metrics:

SchoenerD	Schoener's (1968) D statistic for niche overlap, varying between 0 (no overlap) and 1 (identical niches).
WarrenI	the I index of Warren et al. (2008), based on Hellinger distance (below) but re-formulated to also vary between 0 (no overlap) and 1 (identical niches).
HellingerDist	Hellinger distance (as in van der Vaart 1998, p. 211) between probability distributions, varying between 0 and 2.

Note

Thanks to Heidi K. Mod for reporting a typo in a previous version of the function. Another function providing similar measures, `niche.overlap`, is available in package **phyloclim**, but it requires complex and software-specific input data formats.

Author(s)

A. Marcia Barbosa

References

- Schoener T.W. (1968) Anolis lizards of Bimini: resource partitioning in a complex fauna. *Ecology* 49: 704-726
- van der Vaart A.W. (1998) *Asymptotic statistics*. Cambridge Univ. Press, Cambridge (UK)
- Warren D.L., Glor R.E. & Turelli M. (2008) Environmental niche equivalency versus conservatism: quantitative approaches to niche evolution. *Evolution*, 62: 2868-83 (and further ERRATUM)

See Also

[fuzSim](#); `niche.overlap` in package **phyloclim**

Examples

```
# get an environmental favourability model for a rotifer species:

data(rotif.env)

names(rotif.env)

fav_current <- multGLM(rotif.env, sp.cols = 18, var.cols = 5:17,
  step = TRUE, FDR = TRUE, trim = TRUE, P = FALSE, Fav = TRUE) $
  predictions

# imagine you have a model prediction for this species in a future time
# (here we will create one by randomly jittering the current predictions)

fav_imag <- jitter(fav_current, amount = 0.2)
fav_imag[fav_imag < 0] <- 0
fav_imag[fav_imag > 1] <- 1

# calculate niche overlap between current and imaginary future predictions:

modOverlap(fav_current, fav_imag)
```

multConvert

Multiple conversion

Description

This function can simultaneously convert multiple columns of a matrix or data frame.

Usage

```
multConvert(data, conversion, cols = 1:ncol(data))
```

Arguments

data	A matrix or data frame containing columns that need to be converted
conversion	the conversion to apply, e.g. as.factor or a custom-made function
cols	the columns of 'data' to convert

Details

Sometimes we need to change the data type (class, mode) of a variable in R. There are various possible conversions, performed by functions like [as.integer](#), [as.factor](#) or [as.character](#). If we need to perform the same conversion on a number of variables (columns) in a data frame, we can convert them all simultaneously using this function. By default it converts all columns in 'data', but you can specify just some of those. 'multConvert' can also be used to apply other kinds of transformations – for example, if you need to divide some of your columns by 100, just write a function to do this and then use 'multConvert' to apply this function to any group of columns.

Value

The input data with the specified columns converted as specified in 'conversion'.

Author(s)

A. Marcia Barbosa

Examples

```
data(rotif.env)

str(rotif.env)

# convert the first 4 columns to character:
converted.rotif.env <- multConvert(data = rotif.env,
  conversion = as.character, cols = 1:4)

str(converted.rotif.env)

names(rotif.env)

# divide some columns by 100:

div100 <- function(x) x / 100

rotif.env.cent <- multConvert(data = rotif.env,
  conversion = div100, cols = c(6:10, 12:17))

head(rotif.env.cent)
```

multGLM

GLMs with variable selection for multiple species

Description

This function performs selection of variables and calculates generalized linear models for a set of (species) presence/absence records in a data frame, with a range of options for data partition, variable selection, and output form.

Usage

```
multGLM(data, sp.cols, var.cols, id.col = NULL, family = "binomial",
  test.sample = 0, FDR = FALSE, correction = "fdr", corSelect = FALSE,
  cor.thresh = 0.8, step = TRUE, trace = 0, start = "null.model",
  direction = "both", select = "AIC", trim = TRUE, Y.prediction = FALSE,
  P.prediction = TRUE, Favourability = TRUE, group.preds = TRUE,
  TSA = FALSE, coord.cols = NULL, degree = 3, verbosity = 2, ...)
```

Arguments

<code>data</code>	a data frame in wide format (see splist2presabs) containing, in separate columns, your species' binary (0/1) occurrence data and the predictor variables.
<code>sp.cols</code>	names or index numbers of the columns containing the species data to be modelled.
<code>var.cols</code>	names or index numbers of the columns containing the predictor variables to be used for modelling.
<code>id.col</code>	(optional) name or index number of column containing the row identifiers (if defined, it will be included in the output 'predictions' data frame).
<code>family</code>	argument to be passed to the glm function; currently, only 'binomial' is implemented here.
<code>test.sample</code>	a subset of data to set aside for subsequent model testing. Can be a value between 0 and 1 for a proportion of the data to choose randomly (e.g. 0.2 for 20%); or an integer number for a particular number of cases to choose randomly among the records in 'data'; or a vector of integers for the index numbers of the particular rows to set aside; or "Huberty" for his rule of thumb based on the number of variables (Huberty 1994, Fielding & Bell 1997).
<code>FDR</code>	logical value indicating whether to do a preliminary exclusion of variables based on the false discovery rate (see FDR). The default is FALSE.
<code>correction</code>	argument to pass to the FDR function if FDR = TRUE. The default is "fdr", but see p.adjust for other options.
<code>corSelect</code>	logical value indicating whether to do a preliminary exclusion of highly correlated variables (see corSelect). The default is FALSE.
<code>cor.thresh</code>	numerical value indicating the correlation threshold to pass to corSelect (used only if <code>corSelect</code> = TRUE).
<code>step</code>	logical, whether to use the step function to perform a stepwise variable selection (based on AIC or BIC).
<code>trace</code>	if positive, information is printed during the running of step . Larger values may give more detailed information.
<code>start</code>	character string specifying whether to start with the 'null.model' (so that variable selection starts forward) or with the 'full.model' (so selection starts backward). Used only if <code>step</code> = TRUE.
<code>direction</code>	argument to be passed to step specifying the direction of variable selection ('forward', 'backward' or 'both'). Used only if <code>step</code> = TRUE.
<code>select</code>	character string specifying the criterion for stepwise selection of variables. Options are "AIC" (Akaike's Information Criterion; Akaike, 1973), the default; or BIC (Bayesian Information Criterion, also known as Schwarz criterion, SBC or SBIC; Schwarz, 1978). Used only if <code>step</code> = TRUE.
<code>trim</code>	logical indicating whether to trim off non-significant variables from the models using modelTrim function. Can be used whether or not <code>step</code> = TRUE. Works as a backward variable elimination procedure based on statistical significance.
<code>Y.prediction</code>	logical, whether to include output predictions in the scale of the predictor variables (type = "link" in predict.glm).

P.prediction	logical, whether to include output predictions in the scale of the response variable, i.e. probability (type = "response" in <code>predict.glm</code>).
Favourability	logical, whether to apply the <code>Favourability</code> function to remove the effect of prevalence on predicted probability (Real et al. 2006) and include its results in the output.
group.preds	logical, whether to group together predictions of similar type ('Y', 'P' or 'F') in the output 'predictions' table (e.g. if FALSE: sp1_Y, sp1_P, sp1_F, sp2_Y, sp2_P, sp2_F; if TRUE: sp1_Y, sp2_Y, sp1_P, sp2_P, sp1_F, sp2_F).
TSA	logical, whether to add a trend surface analysis (calculated individually for each species) as a spatial variable in each model. See <code>multTSA</code> for more details. The default is FALSE.
coord.cols	argument to pass to <code>multTSA</code> (if TSA = TRUE).
degree	argument to pass to <code>multTSA</code> (if TSA = TRUE).
verbosity	numeric value indicating the amount of messages to display; currently meaningful values are 0, 1, and 2 (the default).
...	additional arguments to be passed to <code>modelTrim</code> .

Details

This function automatically calculates binomial GLMs for one or more species (or other binary variables) in a data frame. The function can optionally perform `stepwise` variable selection (and it does so by default) instead of forcing all variables into the models, starting from either the null model (the default, so selection starts forward) or from the full model (so selection starts backward) and using Akaike's information criterion (AIC) as a variable selection criterion. Instead or subsequently, it can also perform stepwise removal of non-significant variables from the models using the `modelTrim` function.

There is also an optional preliminary selection of non-correlated variables, and/or of variables with a significant bivariate relationship with the response, based on the false discovery rate (FDR). Note, however, that some variables can be significant in a multivariate model even if they would not have been selected by FDR.

`Favourability` is also calculated, removing the effect of species prevalence from occurrence probability and thus allowing direct comparisons between models (Real et al. 2006).

By default, all data are used in model training, but you can define an optional 'test.sample' to be reserved for model testing afterwards. You may also want to do a previous check for multicollinearity among variables, e.g. the variance inflation factor (VIF), using `multicol`.

The 'multGLM' function will create a list of the resulting models (each with the name of the corresponding species column) and a data frame with their predictions ('Y', 'P' and/or 'F', all of which are optional). If you plan on representing these predictions in a GIS based on .dbf tables, remember that dbf only allows up to 10 characters in column names; 'multGLM' predictions will add 2 characters (_Y, _P and/or _F) to each of your species column names, so use species names/codes with up to 8 characters in the data set that you are modelling. You can create (sub)species name abbreviations with the `spCodes` function.

Value

This function returns a list with the following components:

predictions	a data frame with the model predictions (if either of Y.prediction, P.prediction or Favourability are TRUE).
models	a list of the resulting model objects.
variables	a list of character vectors naming the variables finally included in each model according to the specified selection criteria.

Author(s)

A. Marcia Barbosa

References

Akaike, H. (1973) Information theory and an extension of the maximum likelihood principle. In: Petrov B.N. & Csaki F., 2nd International Symposium on Information Theory, Tsahkadsor, Armenia, USSR, September 2-8, 1971, Budapest: Akademiai Kiado, p. 267-281.

Fielding A.H. & Bell J.F. (1997) A review of methods for the assessment of prediction errors in conservation presence/absence models. *Environmental Conservation* 24: 38-49

Huberty C.J. (1994) *Applied Discriminant Analysis*. Wiley, New York, 466 pp. Schaafsma W. & van Vark G.N. (1979) Classification and discrimination problems with applications. Part IIa. *Statistica Neerlandica* 33: 91-126

Real R., Barbosa A.M. & Vargas J.M. (2006) Obtaining environmental favourability functions from logistic regression. *Environmental and Ecological Statistics* 13: 237-245.

Schwarz, G.E. (1978) Estimating the dimension of a model. *Annals of Statistics*, 6 (2): 461-464.

See Also

[glm](#), [Fav](#), [step](#), [modelTrim](#), [multicol](#), [corSelect](#)

Examples

```
data(rotif.env)

names(rotif.env)

# make models for 2 of the species in rotif.env:

mods <- multGLM(rotif.env, sp.cols = 46:47, var.cols = 5:17, id.col = 1,
  step = TRUE, FDR = TRUE, trim = TRUE)

names(mods)
head(mods$predictions)
names(mods$models)
mods$models[[1]]
mods$models[["Ttetra"]]

# include each species' spatial trend in the models:
```

```

mods <- multGLM(rotif.env, sp.cols = 46:47, var.cols = 5:17, id.col = 1,
step = TRUE, FDR = TRUE, trim = TRUE, TSA = TRUE, coord.cols = c(11, 10))

mods$models[[1]]
mods$models[["Ttetra"]]

mods$variables
# you can then use these selected variables elsewhere

```

multicol

Analyse multicollinearity in a dataset, including VIF

Description

This function analyses multicollinearity in a set of variables or in a model, including the R-squared, tolerance and variance inflation factor (VIF).

Usage

```
multicol(vars = NULL, model = NULL, reorder = TRUE)
```

Arguments

vars	A matrix or data frame containing the numeric variables for which to calculate multicollinearity. Only the 'independent' (predictor, explanatory, right hand side) variables should be entered, as the result obtained for each variable depends on all the other variables present in the analysed data set.
model	Alternatively to 'vars', a model object of class "glm" to calculate 'multicol' among the included variables.
reorder	logical, whether variables should be output in decreasing order or VIF value rather than in their input order. The default is TRUE.

Details

Testing collinearity among covariates is a recommended step of data exploration before applying a statistical model (Zuur et al. 2010). However, you can also calculate multicollinearity among the variables already included in a model.

The multicol function calculates the degree of multicollinearity in a set of numeric variables, using three closely related measures: R squared (the coefficient of determination of a linear regression of each predictor variable on all other predictor variables, i.e., the amount of variation in each variable that is accounted for by other variables in the dataset); tolerance (1 - R squared), i.e. the amount of variation in each variable that is not included in the remaining variables; and the variance inflation factor: $VIF = 1 / (1 - R \text{ squared})$, which, in a linear model with these variables as predictors, reflects the degree to which the variance of an estimated regression coefficient is increased due only to the correlations among covariates (Marquardt 1970; Mansfield & Helms 1982).

Value

The function returns a matrix with one row per analysed variable, the names of the variables as row names, and 3 columns: R-squared, Tolerance and VIF.

Author(s)

A. Marcia Barbosa

References

- Marquardt D.W. (1970) Generalized inverses, ridge regression, biased linear estimation, and non-linear estimation. *Technometrics* 12: 591-612.
- Mansfield E.R. & Helms B.P. (1982) Detecting multicollinearity. *The American Statistician* 36: 158-160.
- Zuur A.F., Ieno E.N. & Elphick C.S. (2010) A protocol for data exploration to avoid common statistical problems. *Methods in Ecology and Evolution* 1: 3-14.

See Also

vif in package **HH**, vif in package **usdm**

Examples

```
data(rotif.env)
names(rotif.env)

# calculate multicollinearity among the predictor variables:
multicol(rotif.env[ , 5:17], reorder = FALSE)
multicol(rotif.env[ , 5:17])

# you can also calculate multicol among the variables included in a model:
mod <- step(glm(Abrigh ~ Area + Altitude + AltitudeRange +
HabitatDiversity + HumanPopulation + Latitude + Longitude +
Precipitation + PrecipitationSeasonality + TemperatureAnnualRange
+ Temperature + TemperatureSeasonality + UrbanArea,
data = rotif.env))
multicol(model = mod)

# more examples using R datasets:
multicol(trees)

# you'll get a warning and some NA results if any of the variables
# is not numeric:
multicol(OrchardSprays)

# so define the subset of numeric 'vars' to calculate 'multicol' for:
multicol(OrchardSprays[ , 1:3])
```

multTSA

*Trend Surface Analysis for multiple species***Description**

This function performs trend surface analysis for one or more species at a time. It converts categorical presence-absence (1-0) data into continuous surfaces denoting the spatial trend in species' occurrence patterns.

Usage

```
multTSA(data, sp.cols, coord.cols, id.col = NULL, degree = 3,
step = TRUE, criterion = "AIC", type = "P", Favourability = FALSE,
suffix = "_TS", save.models = FALSE, verbosity = 2, ...)
```

Arguments

data	a matrix or data frame containing, at least, two columns with spatial coordinates, and one column per species containing their presence (1) and absence (0) data, with localities in rows.
sp.cols	names or index numbers of the columns containing the species presences and absences in data. Must contain only zeros (0) for absences and ones (1) for presences.
coord.cols	names or index numbers of the columns containing the spatial coordinates in data (x and y, or longitude and latitude, in this order!).
id.col	optionally, the name or index number of a column (to be included in the output) containing locality identifiers in data.
degree	the degree of the spatial polynomial to use (see Details). The default is 3.
step	logical value indicating whether the regression of presence-absence on the spatial polynomial should do a stepwise inclusion of the polynomial terms (using the step function with default settings, namely backward AIC selection), rather than forcing all terms into the equation. The default is TRUE.
criterion	character value indicating whether the backward stepwise selection of variables (if step = TRUE) should be made according to "AIC" (the default, using the step function) or to "significance" (using the modelTrim function).
type	the type of trend surface to obtain. Can be either "Y" for the raw polynomial equation (i.e. in the scale of the predictors, e.g. if you want to use the spatial trend as a predictor variable in a model), "P" for the logit-transformed probability (e.g. if you want to use the output as a prediction of presence probability based on spatial trend alone), or "F" for spatial favourability, i.e., prevalence-independent probability (see Fav).
Favourability	deprecated argument; linktype should now be used instead, although (at least for the timebeing) this argument will still be accepted (with Favourability = TRUE internally resulting in type = "F") for back-compatibility.

<code>suffix</code>	character indicating the suffix to add to the trend surface columns in the resulting data frame. The default is "_TS".
<code>save.models</code>	logical value indicating whether the models obtained from the regressions should be saved and included in the output. The default is FALSE.
<code>verbosity</code>	integer value indicating the amount of messages to display; currently meaningful values are 0, 1, and 2 (the default).
<code>...</code>	additional arguments to be passed to <code>modelTrim</code> (if <code>step = TRUE</code> and <code>criterion = "significance"</code>).

Details

Trend Surface Analysis is a way to model the spatial structure in species' distributions by regressing occurrence data on the spatial coordinates x and y , for a linear trend, or on polynomial terms of these coordinates (x^2 , y^2 , $x*y$, etc.), for curvilinear trends (Legendre & Legendre, 1998; Borcard et al., 2011). Second- and third-degree polynomials are often used. 'multTSA' allows specifying the degree of the spatial polynomial to use. By default, it uses a 3rd-degree polynomial and performs stepwise AIC selection of the polynomial terms to include.

Value

This function returns a matrix or data frame containing the identifier column (if provided in 'id.col') and one column per species containing the value predicted by the trend surface analysis. If `save.models = TRUE`, the output is a list containing this dataframe plus a list of the model objects.

Author(s)

A. Marcia Barbosa

References

Borcard D., Gillet F. & Legendre P. (2011) Numerical Ecology with R. Springer, New York.
 Legendre P. & Legendre L. (1998) Numerical Ecology. Elsevier, Amsterdam.

See Also

`distPres`, `poly`, `multGLM`

Examples

```
data(rotif.env)

head(rotif.env)

names(rotif.env)

tsa <- multTSA(rotif.env, sp.cols = 18:20,
coord.cols = c("Longitude", "Latitude"), id.col = 1)

head(tsa)
```

pairwiseRangemaps	<i>Pairwise intersection (and union) of range maps</i>
-------------------	--------------------------------------------------------

Description

This function takes a set of rangemaps and returns a matrix containing the areas of their pairwise intersections; optionally, also their individual areas and/or their areas of pairwise unions.

Usage

```
pairwiseRangemaps(rangemaps, projection, diag = TRUE, unions = TRUE,
  verbosity = 2, Ncpu = 1, nchunks = 1, subchunks = NULL,
  filename = "rangemap_matrix.csv")
```

Arguments

rangemaps	a character vector of rangemap filenames, including folder paths if not in the working directory. ESRI shapefile (.shp) is currently the only accepted format. Specifying the extension is optional.
projection	argument to be passed to function 'importShapefile' of package PBSmapping
diag	logical, whether to fill the diagonal of the resulting matrix with the area of each rangemap. The default is TRUE, and it is also automatically set to TRUE (as it is necessary) if unions = TRUE.
unions	logical, whether to fill the upper triangle of the resulting matrix with the area of union of each pair of rangemaps. The default is TRUE. It is not as computationally intensive as the intersection, as it is calculated not with spatial but with algebraic operations within the matrix (union = area1 + area2 - intersection).
verbosity	integer number indicating the amount of progress messages to display.
Ncpu	integer indicating the number of CPUs (central processing units) to employ if parallel computing is to be used. The default is 1 CPU, which implies no parallel computing, but you may want to increase this if you have many and/or large rangemaps and your machine has more cores that can be used simultaneously. You can find out the total number of cores in your machine with the detectCores function of the parallel package; a usually wise option is to use all cores except one (i.e., Ncpu = parallel::detectCores()-1).
nchunks	either an integer indicating the number of chunks of rows in which to divide the results matrix for calculations, or character "decreasing" to indicate that the matrix should be divided into chunks of decreasing number of rows (as intersections are calculated in the lower triangle, rows further down the matrix have an increasing number of intersections to compute). Note, however, that rangemap size, not rangemap number, is the main determinant of computation time. The default is 1 (no division of the matrix) but, if you have many rangemaps, the process can get clogged. With chunks, each set of rows of the matrix is calculated and saved to disk, and the memory is cleaned before the next chunk begins.

subchunks	optional integer vector specifying which chunks to actually calculate. This is useful if a previous, time-consuming run of pairwiseRangemaps was interrupted (e.g. by a power outage) and you want to calculate only the remaining chunks.
filename	optional character vector indicating the name of the file to save the resulting matrix to.

Details

This calculation can be very intensive and slow, especially if you have many and/or large rangemaps, due to the time needed for spatial operations between maps. You can set `nchunks = "decreasing"` for the matrix to be calculated in parts and the memory cleaned between one part and the next; and, if your computer has more than one core that you can use, you can increase `Ncpu` to get parallel computing.

Value

This function returns a square matrix containing, in the lower triangle, the area of the pair-wise intersections among the input 'rangemaps'; in the diagonal (if `diag = TRUE` or `union = TRUE`), the area of each rangemap; and in the upper triangle (if `union = TRUE`), the area of the pair-wise unions among the rangemaps.

Note

This function uses the **PBSmapping** package to import and intersect the polygon rangemaps and to calculate areas. Remember to use projected rangemaps, preferably with an equal-area reference system, so that calculations are correct.

Author(s)

A. Marcia Barbosa

References

Barbosa A.M. & Estrada A. (2016) Calcular corotipos sin dividir el territorio en OGUs: una adaptacion de los indices de similitud para su utilizacion directa sobre areas de distribucion. In: Gomez Zotano J., Arias Garcia J., Olmedo Cobo J.A. & Serrano Montes J.L. (eds.), Avances en Biogeografia. Areas de Distribucion: Entre Puentes y Barreras, pp. 157-163. Editorial Universidad de Granada & Tundra Ediciones, Granada (Spain)

See Also

[rangemapSim](#)

percentTestData	<i>Percent test data</i>
-----------------	--------------------------

Description

Based on the work of Schaafsma & van Vark (1979), Huberty (1994) provided a heuristic ("rule of thumb") for determining an adequate proportion of data to set aside for testing species presence/absence models, based on the number of predictor variables that are used (Fielding & Bell 1997). The 'percentTestData' function calculates this proportion as a percentage.

Usage

```
percentTestData(nvar)
```

Arguments

nvar	the number of variables in the model.
------	---------------------------------------

Value

A numeric value of the percentage of data to leave out of the model for further model testing.

Author(s)

A. Marcia Barbosa

References

Huberty C.J. (1994) Applied Discriminant Analysis. Wiley, New York, 466 pp.

Schaafsma W. & van Vark G.N. (1979) Classification and discrimination problems with applications. Part IIa. Statistica Neerlandica 33: 91-126

Fielding A.H. & Bell J.F. (1997) A review of methods for the assessment of prediction errors in conservation presence/absence models. Environmental Conservation 24: 38-49

See Also

[multGLM](#)

Examples

```
# say you're building a model with 15 variables:

percentTestData(15)

# the result tells you that 21% is an appropriate percentage of data
# to set aside for testing your model, so train it with 79% of the data
```

rangemapSim *Pairwise similarity between rangemaps*

Description

Calculate pairwise similarity among rangemaps from a matrix of their areas of intersection and union

Usage

```
rangemapSim(rangemap.matrix, total.area,
method = c("Jaccard", "Sorensen", "Simpson", "Baroni"),
diag = FALSE, upper = FALSE, verbosity = 2)
```

Arguments

<code>rangemap.matrix</code>	a matrix like the one produced by function pairwiseRangemaps , containing the areas of pairwise intersection among rangemaps in the lower triangle, individual rangemap areas in the diagonal, and pairwise union areas in the upper diagonal.
<code>total.area</code>	numeric value indicating the total size of the study area, in the same units as the areas in the <code>rangemap.matrix</code> . Used only if 'method' uses shared absences (as is the case of "Baroni")
<code>method</code>	character value indicating the similarity index to use. Currently implemented indices are "Jaccard", "Sorensen", "Simpson" and "Baroni". The default is the first one.
<code>diag</code>	logical value indicating if the diagonal of the resulting matrix should be filled
<code>upper</code>	logical value indicating if the upper triangle of the resulting matrix should be filled (symmetrical to the lower triangle)
<code>verbosity</code>	integer number indicating the amount of messages to display.

Details

Distributional relationships among species are commonly determined based on pair-wise (dis)similarities in species' occurrence patterns. Some of the most commonly employed similarity indices are those of Jaccard (1901), Sorensen (1948), Simpson (1960) and Baroni-Urbani & Buser (1976), which are here implemented for comparing rangemaps based on their areas of intersection and union (Barbosa & Estrada, in press).

Value

This function returns a square matrix of pairwise similarities between the rangemaps in 'rangemap.matrix', calculated with the (first) similarity index specified in 'method'.

Author(s)

A. Marcia Barbosa

References

- Barbosa A.M. & Estrada A. (in press) Calcular corotipos sin dividir el territorio en OGUs: una adaptacion de los indices de similitud para su utilizacion directa sobre areas de distribucion. In: Areas de distribucion: entre puentes y barreras. Universidad de Granada, Spain.
- Baroni-Urbani C. & Buser M.W. (1976) Similarity of Binary Data. *Systematic Zoology*, 25: 251-259
- Jaccard P. (1901) Etude comparative de la distribution florale dans une portion des Alpes et des Jura. *Memoires de la Societe Vaudoise des Sciences Naturelles*, 37: 547-579
- Simpson G.G. (1960) Notes on the measurement of faunal resemblance. *Amer. J. Sci.* 258A, 300-311
- Sorensen T. (1948) A method of establishing groups of equal amplitude in plant sociology based on similarity of species and its application to analyses of the vegetation on Danish commons. *Kongelige Danske Videnskabernes Selskab*, 5(4): 1-34

See Also

[pairwiseRangemaps](#); [simFromSetOps](#); [simMat](#)

rarity

(Fuzzy) rarity

Description

This function computes the index of species rarity of Real et al. (2006), using either crisp (presence/absence, i.e. ones and zeros) or fuzzy values (e.g. [Favourability](#), between zero and one), for a single species or for several species across a study area. Rarity is like a (potential) richness index in which rarer species have higher weight.

Usage

```
rarity(data, sp.cols = 1:ncol(data), na.rm = TRUE)
```

Arguments

data	a numeric vector, matrix or data frame containing the presence/absence or the Favourability (fuzzy presence) values for the target species.
sp.cols	names or index numbers of the columns of 'data' that contain the species values for which to compute rarity.
na.rm	logical value indicating whether NA values should be removed before the computation.

Details

If the input data include only one species (i.e. a numeric vector or a one-column table, with one value for each locality), rarity is 1 divided by the sum of its values. If the input includes more than one species or column, rarity is the sum of the product of each (fuzzy) presence value by the rarity of the corresponding species, so that rarer species have higher weight in the resulting sum (Real et al. 2006). See also Estrada et al. (2011) for a more complex version of fuzzy rarity.

Value

If 'data' is a vector or a one-column table, or if 'sp.cols' is of length 1, this function returns a single value of rarity for the underlying species, which is simply 1 divided by the sum of its values. If 'data' and 'sp.cols' refer to more than 1 column, the function returns the total combined rarity value of all corresponding species for each row in 'data' (see Examples).

Author(s)

A. Marcia Barbosa

References

Real R., Estrada A., Barbosa A.M. & Vargas J.M. (2006) Aplicacion de la logica difusa al concepto de rareza para su uso en Gap Analysis: el caso de los mamíferos terrestres en Andalucía. Serie Geografica 13: 99-116

Estrada A., Real R. & Vargas J.M. (2011) Assessing coincidence between priority conservation areas for vertebrate groups in a Mediterranean hotspot. Biological Conservation, 144: 1120-1129

See Also

[vulnerability](#)

Examples

```
data(rotif.env)

head(rotif.env)

rarity(rotif.env[, 18])

rarity(rotif.env, sp.cols = "Abrigh")

rarity(rotif.env, sp.cols = 18:47) # yields one value of combined rarity for each row in 'data'

# fuzzy rarity (from favourability values):

pred <- multGLM(rotif.env, sp.cols = 18:20, var.cols = 5:17)$predictions

head(pred)

rarity(pred, sp.cols = "Abrigh_F")
```

```
rarity(pred, sp.cols = c("Abrigh_F", "Afissa_F", "Apriod_F")) # yields one value of combined rarity for each row in
```

rotif.env	<i>Rotifers and environmental variables on TDWG level 4 regions of the world</i>
-----------	----------------------------------------------------------------------------------

Description

These data were extracted from a database of monogonont rotifer species presence records on the geographical units used by the Biodiversity Information Standards (formerly Taxonomic Database Working Group, TDWG: <https://www.tdwg.org>) and a few environmental (including human and spatial) variables on the same spatial units. The original data were compiled and published by Fontaneto et al. (2012) in long (narrow, stacked) format. Here they are presented in wide or unstacked format (presence-absence table, obtained with the `splist2presabs` function), reduced to the species recorded in at least 100 (roughly one third) different TDWG level 4 units, and with abbreviations of the species' names (obtained with the `spCodes` function). Mind that this is not a complete picture of these species' distributions, due to insufficient sampling in many regions.

Usage

```
data(rotif.env)
```

Format

A data frame with 291 observations on the following 47 variables.

TDWG4 a factor with 291 levels indicating the abbreviation code of each TDWG4 region

LEVEL_NAME a factor with 291 levels indicating the name of each TDWG4 region

REGION_NAME a factor with 47 levels indicating the name of the main geographical region to which each TDWG4 level belongs

CONTINENT a factor with 9 levels indicating the continent to which each TDWG4 level belongs

Area a numeric vector

Altitude a numeric vector

AltitudeRange a numeric vector

HabitatDiversity a numeric vector

HumanPopulation a numeric vector

Latitude a numeric vector

Longitude a numeric vector

Precipitation a numeric vector

PrecipitationSeasonality a numeric vector

TemperatureAnnualRange a numeric vector

Temperature a numeric vector

TemperatureSeasonality a numeric vector
UrbanArea a numeric vector
Abrigh a numeric vector
Afissa a numeric vector
Apriod a numeric vector
Bangul a numeric vector
Bcalyc a numeric vector
Bplica a numeric vector
Bquadr a numeric vector
Burceo a numeric vector
Cgibba a numeric vector
Edilat a numeric vector
Flongi a numeric vector
Kcochl a numeric vector
Kquadr a numeric vector
Ktropi a numeric vector
Lbulla a numeric vector
Lclost a numeric vector
Lhamat a numeric vector
Lluna a numeric vector
Llunar a numeric vector
Lovali a numeric vector
Lpatel a numeric vector
Lquadr a numeric vector
Mventr a numeric vector
Ppatul a numeric vector
Pquadr a numeric vector
Pvulga a numeric vector
Specti a numeric vector
Tpatin a numeric vector
Tsimil a numeric vector
Ttetra a numeric vector

Source

Fontaneto D., Barbosa A.M., Segers H. & Pautasso M. (2012) The 'rotiferologist' effect and other global correlates of species richness in monogonont rotifers. *Ecography*, 35: 174-182.

Examples

```
data(rotif.env)
```

```
head(rotif.env)
```

rotifers

Rotifer species on TDWG level 4 regions of the world

Description

These data were extracted from a database of monogonont rotifer species records on the geographical units used by the Biodiversity Information Standards (formerly Taxonomic Database Working Group, TDWG: <https://www.tdwg.org>). The original data were compiled and published by Fontaneto et al. (2012) for all TDWG levels. Here they are reduced to the TDWG - level 4 units and to the species recorded in at least 100 (roughly one third) of these units. Mind that this is not a complete picture of these species' distributions, due to insufficient sampling in many regions.

Usage

```
data("rotifers")
```

Format

A data frame with 3865 observations on the following 2 variables.

TDWG4 a factor with 274 levels corresponding to the code names of the TDWG level 4 regions in which the records were taken

species a factor with 30 levels corresponding to the names of the (sub)species recorded in at least 100 different TDWG level 4 regions

Source

Fontaneto D., Barbosa A.M., Segers H. & Pautasso M. (2012) The 'rotiferologist' effect and other global correlates of species richness in monogonont rotifers. *Ecography*, 35: 174-182.

Examples

```
data(rotifers)
```

```
head(rotifers, 10)
```

sharedFav

Shared favourability for two competing species

Description

This function implements the graphical analyses of Acevedo et al. (2010, 2012) on biogeographical interactions. It takes two vectors of favourability values at different localities for, respectively, a stronger and a weaker competing species (or two equally strong competitors), and plots their favourableness or shared favourability to assess potential competitive interactions.

Usage

```
sharedFav(strong_F, weak_F, conf = 0.95, bin_interval = "0.1", ...)
```

Arguments

<code>strong_F</code>	a numeric vector of favourability values (obtained, e.g., with functions Fav or multGLM) for the stronger species.
<code>weak_F</code>	a numeric vector of favourability values for the weaker species. Must be of the same length and in the same order as <code>strong_F</code> .
<code>conf</code>	confidence level for the confidence intervals in the plot. The default is 0.95. Set it to NA for no confidence intervals (see "Note" below).
<code>bin_interval</code>	character value specifying the method for grouping the favourability values into bins, to plot and compare mean favourability for each species. Currently implemented options are "0.1" (the default, dividing the values at 0.1 intervals as per Acevedo et al. 2010, 2012) and "quantiles" (as the former method may generate an error if there are overly small bins to calculate confidence intervals). See "Note" below.
<code>...</code>	some additional arguments can be passed to barplot , such as "main" (for the plot title) or "las" (for the orientation of the axis labels).

Details

This function implements the biogeographic analyses of Acevedo et al. (2010, 2012), assessing the trends of environmental favourability across a range of favourability intersection values between two interacting species. It first calculates the fuzzy intersection (minimum value) between the two species' favourability values at each locality (i.e., favourability for the occurrence of both species simultaneously); it groups these values into 10 bins; and calculates the mean favourability (and its confidence interval) for each of the two species within each interval.

According to the notion of "favorableness" by Richerson & Lum (1980), competing species may or may not be able to coexist depending on their relative environmental fitnesses; competition between species increases and competitive exclusion decreases as their favourability intersection increases (Acevedo et al. 2010, 2012). The shaded area in the shared favourability plot, where at least one of the species is at intermediate favourability, is the area where competitive interactions may limit species occurrence. Outside this shaded area, where favourability is either very low for at least one of the species (left) or very high for both species (right side of the plot), competition is not limiting (see also [bioThreat](#) for details).

Value

This function returns the numeric value of the fuzzy overlap index (Dubois & Prade 1980; Acevedo et al. 2010, 2012) and the shared favourability plot, with circles and a continuous line representing favourability for the stronger species, and squares and a dashed line representing favourability for the weaker species. The height of the bars at the bottom represents the proportional sample size of each bin.

Note

This function may generate an error if one or more bins don't have enough values for the confidence interval to be computed. If this occurs, you can try a different 'bin_interval' (e.g. "quantiles") or set the 'conf' argument to NA (in which case confidence intervals will not be computed). Either will affect only the plot, not the overall fuzzy overlap value.

Author(s)

A. Marcia Barbosa

References

Acevedo P., Ward A.I., Real R. & Smith G.C. (2010) Assessing biogeographical relationships of ecologically related species using favourability functions: a case study on British deer. *Diversity and Distributions*, 16: 515-528

Acevedo P., Jimenez-Valverde A., Melo-Ferreira J., Real R. & Alves, P.C. (2012) Parapatric species and the implications for climate change studies: a case study on hares in Europe. *Global Change Biology*, 18: 1509-1519

Dubois D. & Prade H. (1980) *Fuzzy sets and systems: theory and applications*. Academic Press, New York

Richerson P.J. & Lum K. (1980) Patterns of plant species and diversity in California: relation to weather and topography. *American Naturalist*, 116: 504-536

See Also

[bioThreat](#), [Fav](#)

Examples

```
# get favourability model predictions for two species:
data(rotif.env)
mods <- multGLM(rotif.env, sp.cols = 19:20, var.cols = 5:17)
head(mods$predictions)
favs <- mods$predictions[ , 3:4]

# get shared favourability:
sharedFav(strong_F = favs[,1], weak_F = favs[,2], main = "Shared favourability")

sharedFav(strong_F = favs[,1], weak_F = favs[,2], bin_interval = "quantiles", main = "Shared favourability", las =
```

simFromSetOps

Calculate similarity from set operations

Description

This function calculates pair-wise similarity based on the results of set operations (intersection, union) among the subjects.

Usage

```
simFromSetOps(size1, size2, intersection, union, total.size = NULL,
method = c("Jaccard", "Sorensen", "Simpson", "Baroni"),
verbosity = 1)
```

Arguments

size1	size of subject 1 (e.g., area of the distribution range of a species, or its number of presences within a grid). Not needed if method = "Jaccard".
size2	the same for subject 2.
intersection	size of the intersection among subjects 1 and 2 (area of the intersection among their distribution ranges, or number of grid cells in which they co-occur).
union	size of the union of subjects 1 and 2.
total.size	total size of the study area. Needed only when calculating a similarity index that takes shared absences into account (i.e., method = "Baroni").
method	the similarity index to use. Currently implemented options are "Jaccard", "Sorensen", "Simpson" or "Baroni".
verbosity	integer indicating whether to display messages.

Details

Similarities among ecological communities, beta diversity patterns, biotic regions, and distributional relationships among species are commonly determined based on pair-wise (dis)similarities in species' occurrence patterns. This function implements some of the most commonly employed similarity indices, namely those of Jaccard (1901), Sorensen (1948), Simpson (1960) and Baroni-Urbani & Buser (1976), based on the amount of occupied and overlap area between two species.

Value

The numeric value of similarity among subjects 1 and 2.

Author(s)

A. Marcia Barbosa

References

- Baroni-Urbani C. & Buser M.W. (1976) Similarity of Binary Data. *Systematic Zoology*, 25: 251-259
- Jaccard P. (1901) Etude comparative de la distribution florale dans une portion des Alpes et des Jura. *Memoires de la Societe Vaudoise des Sciences Naturelles*, 37: 547-579
- Simpson, G.G. (1960) Notes on the measurement of faunal resemblance. *Amer. J. Sci.* 258A, 300-311
- Sorensen T. (1948) A method of establishing groups of equal amplitude in plant sociology based on similarity of species and its application to analyses of the vegetation on Danish commons. *Kongelige Danske Videnskabernes Selskab*, 5(4): 1-34

See Also

[fuzSim](#), [simMat](#)

Examples

```
# take two species which occur in 22 and 35 area units, respectively
# and which overlap in 8 of those units:

sp1 <- 22
sp2 <- 35
int <- 8
uni <- sp1 + sp2 - int

# calculate similarity between their distributions based on
# different indices:

simFromSetOps(intersection = int, union = uni, method = "Jaccard")

simFromSetOps(sp1, sp2, int, uni, method = "Sorensen")

simFromSetOps(sp1, sp2, int, uni, method = "Simpson")

# if you want Baroni-Urbani & Buser's index
# you need to provide also the total size of your study area:

simFromSetOps(sp1, sp2, int, uni, total = 100, method = "Baroni")
```

simMat

Pair-wise (fuzzy) similarity matrix

Description

`simMat` takes a matrix or data frame containing species occurrence data or regional species composition, either categorical (0 or 1) or fuzzy (between 0 and 1), and uses the [fuzSim](#) function to calculate a square matrix of pair-wise similarities between them, using a fuzzy logic version (Barbosa, 2015) of the specified similarity index.

Usage

```
simMat(data, method, diag = TRUE, upper = TRUE, verbosity = 2)
```

Arguments

data	a matrix or data frame containing (optionally fuzzy) species presence-absence data (in wide format, i.e. one column per species), with 1 meaning presence, 0 meaning absence, and values in between for fuzzy presence (or the degree to which each locality belongs to the set of species presences; see Zadeh, 1965).
------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	Fuzzy presence-absence can be obtained, for example, with multGLM , distPres or multTSA . These data can also be transposed for comparing regional species compositions.
method	the similarity index whose fuzzy version to use. See fuzSim for available options.
diag	logical value indicating whether the diagonal of the matrix should be filled (with ones). Defaults to TRUE.
upper	logical value indicating whether the upper triangle of the matrix (symmetric to the lower triangle) should be filled. Defaults to TRUE.
verbosity	integer value indicating the amount of messages to display; currently meaningful values are 0, 1, and 2 (the default).

Details

The fuzzy versions of species occurrence data and of binary similarity indices introduce tolerance for small spatial differences in species' occurrence localities, allow for uncertainty about species occurrence, and may compensate for under-sampling and geo-referencing errors (Barbosa, 2015).

Value

This function returns a square matrix of pair-wise similarities among the species distributions (columns) in data. Similarity is calculated with the fuzzy version of the index specified in `method`, which yields traditional binary similarity if the data are binary (0 or 1), or fuzzy similarity if the data are fuzzy (between 0 and 1) (Barbosa, 2015).

Author(s)

A. Marcia Barbosa

References

Barbosa A.M. (2015) fuzzySim: applying fuzzy logic to binary similarity indices in ecology. *Methods in Ecology and Evolution*, 6: 853-858.

See Also

[fuzSim](#)

Examples

```
# load and look at the rotif.env presence-absence data:

data(rotif.env)

head(rotif.env)

names(rotif.env)
```

```

# build a matrix of similarity among these binary data
# using e.g. Jaccard's index:

bin.sim.mat <- simMat(rotif.env[ , 18:47], method = "Jaccard")

head(bin.sim.mat)

# calculate a fuzzy version of the presence-absence data
# based on inverse distance to presences:

rotifers.invd <- distPres(rotif.env, sp.cols = 18:47,
coord.cols = c("Longitude", "Latitude"), id.col = 1, suffix = ".d",
p = 1, inv = TRUE)

head(rotifers.invd)

# build a matrix of fuzzy similarity among these fuzzy
# distribution data, using the fuzzy version of Jaccard's index:

fuz.sim.mat <- simMat(rotifers.invd[ , -1], method = "Jaccard")

head(fuz.sim.mat)

# plot the similarity matrices as colours:

image(x = 1:ncol(bin.sim.mat), y = 1:nrow(bin.sim.mat),
z = bin.sim.mat, col = rev(heat.colors(256)), xlab = "", ylab = "",
axes = FALSE, main = "Binary similarity")
axis(side = 1, at = 1:ncol(bin.sim.mat), tick = FALSE,
labels = colnames(bin.sim.mat), las = 2)
axis(side = 2, at = 1:nrow(bin.sim.mat), tick = FALSE,
labels = rownames(bin.sim.mat), las = 2)

image(x = 1:ncol(fuz.sim.mat), y = 1:nrow(fuz.sim.mat),
z = fuz.sim.mat, col = rev(heat.colors(256)), xlab = "", ylab = "",
axes = FALSE, main = "Fuzzy similarity")
axis(side = 1, at = 1:ncol(fuz.sim.mat), tick = FALSE,
labels = colnames(fuz.sim.mat), las = 2, cex = 0.5)
axis(side = 2, at = 1:nrow(fuz.sim.mat), tick = FALSE,
labels = rownames(fuz.sim.mat), las = 2)

# plot a UPGMA dendrogram from each similarity matrix:

plot(hclust(as.dist(1 - bin.sim.mat), method = "average"),
main = "Binary cluster dendrogram")

plot(hclust(as.dist(1 - fuz.sim.mat), method = "average"),
main = "Fuzzy cluster dendrogram")

```

```
# you can get fuzzy chorotypes from these similarity matrices
# (or fuzzy biotic regions if you transpose 'data'),
# so that localities are in columns and species in rows)
# using the RMACOQUI package (Olivero et al. 2011)
```

spCodes

Obtain unique abbreviations of species names

Description

This function takes a vector of species names and converts them to abbreviated species codes containing the specified numbers of characters from the genus, the specific and optionally also the subspecific name. Separators can be specified by the user. The function checks that the resulting codes are unique.

Usage

```
spCodes(species, nchar.gen = 3, nchar.sp = 3, nchar.ssp = 0,
sep.species = " ", sep.spcode = "", verbosity = 2)
```

Arguments

species	a character vector containig the species names to be abbreviated.
nchar.gen	the number of characters from the genus name to be included in the resulting species code.
nchar.sp	the number of characters from the specific name to be included in the resulting species code.
nchar.ssp	optionally, the number of characters from the subspecific name to be included in the resulting species code. Set it to 0 if you have subspecific names in 'species' but do not want them included in the resulting species codes.
sep.species	the character that separates genus, specific and subspecific names in 'species'. The default is a white space.
sep.spcode	the character you want separating genus and species abbreviations in the resulting species codes. The default is an empty character (no separator).
verbosity	integer value indicating the amount of messages to display. Defaults to 2, for showing all messages.

Value

This function returns a character vector containing the species codes resulting from the abbreviation. If the numbers of characters specified do not make for unique codes, an error message is displayed showing which 'species' names caused it, so that you can try again with different 'nchar.gen', 'nchar.sp' and/or 'nchar.ssp'.

Author(s)

A. Marcia Barbosa

See Also[substr](#), [strsplit](#)**Examples**

```

data(rotifers)

head(rotifers)

## add a column to 'rotifers' with shorter versions of the species names:

## Not run:
rotifers$spcode <- spCodes(rotifers$species, sep.species = "_",
  nchar.gen = 1, nchar.sp = 4, nchar.ssp = 0, sep.spcode = ".")

# this produces an error due to resulting species codes not being unique

## End(Not run)

rotifers$spcode <- spCodes(rotifers$species, sep.species = "_",
  nchar.gen = 1, nchar.sp = 5, nchar.ssp = 0, sep.spcode = ".")

# with a larger number of characters from the specific name,
# resulting codes are now unique

## check out the result:
head(rotifers)

```

splist2presabs

*Convert a species list to a presence-absence table***Description**

This function takes a locality+species dataset in long (stacked) format, i.e., a matrix or data frame containing localities in one column and their recorded species in another column, and converts them to a presence-absence table (wide format) suitable for mapping and for computing distributional similarities (see e.g. [simMat](#)). Try out the Examples below for an illustration).

Usage

```
splist2presabs(data, sites.col, sp.col, keep.n = FALSE)
```

Arguments

<code>data</code>	a matrix or data frame with localities in one column and species in another column. Type or paste <code>'data(rotifers); head(rotifers)'</code> (without the quote marks) in the R console for an example.
<code>sites.col</code>	the name or index number of the column containing the localities in <code>'data'</code> .
<code>sp.col</code>	the name or index number of the column containing the species names or codes in <code>'data'</code> .
<code>keep.n</code>	logical value indicating whether to get in the resulting table the number of times each species appears in each locality; if FALSE (the default), only presence (1) or absence (0) is recorded.

Value

A data frame containing the localities in the first column and then one column per species indicating their presence or absence (or their number of records if `keep.n = TRUE`). Type `'data(rotif.env); head(rotif.env[,18:47])'` (without the quote marks) in the R console for an example.

Author(s)

A. Marcia Barbosa

See Also

[table](#)

Examples

```
data(rotifers)

head(rotifers)

rotifers.presabs <- splist2presabs(rotifers, sites.col = "TDWG4",
  sp.col = "species", keep.n = FALSE)

head(rotifers.presabs)
```

Description

This function builds a generalized linear model with forward stepwise inclusion of variables, using AIC as the selection criterion, and provides the values predicted at each step, as well as their correlation with the final model predictions.

Usage

```
stepByStep(data, sp.col, var.cols, family = binomial(link = "logit"),
  Favourability = FALSE, trace = 0, cor.method = "pearson")
```

Arguments

<code>data</code>	a data frame containing your target and predictor variables.
<code>sp.col</code>	index number of the column of 'data' that contains the target variable.
<code>var.cols</code>	index numbers of the columns of 'data' that contain the predictor variables.
<code>family</code>	argument to be passed to the glm function indicating the family (and error distribution) to use in modelling. The default is binomial distribution with logit link (for binary target variables).
<code>Favourability</code>	logical, whether to apply the Favourability function to remove the effect of prevalence from predicted probability (Real et al. 2006). Applicable only to binomial GLMs. Defaults to FALSE.
<code>trace</code>	argument to pass to the step function. If positive, information is printed during the stepwise procedure. Larger values may give more detailed information. The default is 0 (silent).
<code>cor.method</code>	character string to pass to function cor indicating which coefficient should be used for correlating predictions at each step with those of the final model. Can be "pearson" (the default), "kendall", or "spearman".

Details

Stepwise variable selection often includes more variables than would a model selected after examining all possible combinations of the variables (e.g. with packages **MuMIn** and **glmulti**). The 'stepByStep' function can be useful to assess if a stepwise model with just the first few variables could already provide predictions very close to the final ones (see e.g. Fig. 3 in Munoz et al., 2005). It can also be useful to see which variables determine the more general trends in the model predictions, and which just add (local) additional nuances.

Value

This function returns a list of the following components:

<code>predictions</code>	a data frame with the model's fitted values at each step of the variable selection.
<code>correlations</code>	a numeric vector of the correlation between the predictions at each step and those of the final model.
<code>variables</code>	a character vector of the variables in the final model, named with the step at which each was included.
<code>model</code>	the resulting model object.

Author(s)

A. Marcia Barbosa

References

Munoz, A.R., Real R., BARBOSA A.M. & Vargas J.M. (2005) Modelling the distribution of Bonelli's Eagle in Spain: Implications for conservation planning. *Diversity and Distributions* 11: 477-486

Real R., Barbosa A.M. & Vargas J.M. (2006) Obtaining environmental favourability functions from logistic regression. *Environmental and Ecological Statistics* 13: 237-245.

See Also

[step](#), [glm](#), [modelTrim](#)

Examples

```
data(rotif.env)

stepByStep(data = rotif.env, sp.col = 18, var.cols = 5:17,
cor.method = "spearman")

stepByStep(data = rotif.env, sp.col = 18, var.cols = 5:17,
cor.method = "spearman", Favourability = TRUE)

stepByStep(data = rotif.env, sp.col = 9, var.cols = c(5:8, 10:17),
family = poisson)
```

timer

Timer

Description

Reporting of time elapsed since a given start time. This function is used internally by other functions in the package.

Usage

```
timer(start.time)
```

Arguments

`start.time` A date-time object of class [POSIXct](#), e.g. as given by [Sys.time](#).

Value

The function returns a message informing of the time elapsed since the input 'start.time'.

Author(s)

A. Marcia Barbosa

See Also

[Sys.time](#), [proc.time](#), [difftime](#)

Examples

```
# get starting time:
start <- Sys.time()

# do some random analysis:
sapply(rnorm(50000), function(x) x*5)

# see how long it took:
timer(start)
```

transpose	<i>Transpose (part of) a matrix or dataframe</i>
-----------	--------------------------------------------------

Description

This function transposes (a specified part of) a matrix or data frame, optionally using one of its columns as column names for the transposed result. It can be useful for turning a species presence-absence table into a regional species composition table.

Usage

```
transpose(data, sp.cols = 1:ncol(data), reg.names = NULL)
```

Arguments

- data a matrix or data frame containing the species occurrence data to transpose.
- sp.cols names or index numbers of the columns containing the species occurrences in 'data' which are meant to be transposed.
- reg.names name or index number of the column in 'data' containing the region names, to be used as column names in the transposed result.

Value

This function returns the transposed 'sp.cols' of 'data', with the column specified in 'reg.names' as column names.

Author(s)

A. Marcia Barbosa

See Also

[t](#)

Examples

```
data(rotif.env)

head(rotif.env)

names(rotif.env)

rotif.reg <- transpose(rotif.env, sp.cols = 18:47, reg.names = 1)

head(rotif.reg)
```

triMatInd	<i>Triangular matrix indices</i>
-----------	----------------------------------

Description

This function outputs the indices of one triangle (the lower one by default) of an input square matrix. It is used by `simMat` and, for large matrices, makes it faster than e.g. with `lower.tri` or `upper.tri`.

Usage

```
triMatInd(mat, lower = TRUE, list = FALSE)
```

Arguments

<code>mat</code>	a square matrix.
<code>lower</code>	logical indicating whether the indices should correspond to the lower triangle. The default is TRUE; FALSE produces the upper triangle indices.
<code>list</code>	logical indicating whether the results should be output as a list instead of a matrix. The default is FALSE.

Value

The indices (row, column) of the elements of the matrix that belong to the requested triangle.

Author(s)

A. Marcia Barbosa

References

<http://stackoverflow.com/questions/20898684/how-to-efficiently-generate-lower-triangle-indices-of-a-symmetric-matrix>

See Also

`lower.tri`, `upper.tri`

Examples

```
mat <- matrix(nrow = 4, ncol = 4)
mat
triMatInd(mat)
triMatInd(mat, list = TRUE)
```

vulnerability	(Fuzzy) vulnerability
---------------	-----------------------

Description

This function computes the index of species vulnerability of Estrada et al. (2011), using either crisp (presence/absence, i.e. ones and zeros) or fuzzy (Favourability, between zero and one) values, taking into account the conervation status of each species. Vulnerability is like a (potential) richness index in which more vulnerable species (i.e., those with a more threatened conservation status) have higher weight.

Usage

```
vulnerability(data, sp.cols = 1:ncol(data), categories, na.rm = TRUE)
```

Arguments

data	a numeric vector, matrix or data frame containing the presence/absence (ones and zeros) or the Favourability (fuzzy presence, between zero and one) values for the target species.
sp.cols	names or index numbers of the columns of 'data' that contain the species values for which to compute vulnerability.
categories	numeric vector of the same length as 'sp.cols' (or of length 1 if 'data' is a vector) indicating the IUCN Red List category of each species. This vector should be provided in the same order as the columns in data[, sp.cols]. See Details.
na.rm	logical value indicating whether NA values should be removed before the computation.

Details

The numeric values for the 'categories' argument are suggested by Estrada et al. (2011) to be as follows for each species, according to its IUCN Red List category (available at <https://www.iucnredlist.org>):

- Critically endangered (CR): 16
- Endangered (EN): 8
- Vulnerable (VU): 4
- Near Threatened (NT): 2
- Least Concern (LC): 1
- Data Deficient (DD): 1

Not evaluated (NE): 0

These values follow an exponential scale, because a critically endangered species is generally considered more important than two endangered species, an endangered species more important than two vulnerable species, and so on (Estrada et al. 2011).

Value

This function returns a numeric vulnerability value for each value or each row in 'data'.

Author(s)

A. Marcia Barbosa

References

Estrada A., Real R. & Vargas J.M. (2011) Assessing coincidence between priority conservation areas for vertebrate groups in a Mediterranean hotspot. *Biological Conservation*, 144: 1120-1129

See Also

[rarity](#)

Examples

```
data(rotif.env)

# note the 'categories' below are made up, as rotifers are not on yet redlisted
# see Details above for how to get actual values for your species

vulnerability(rotif.env[, 18], categories = 8)

vulnerability(rotif.env, sp.cols = "Abrigh", categories = 8)

vulnerability(rotif.env, sp.cols = c("Apriod", "Burceo", "Kcochl"), categories = c(8, 16, 2))

# fuzzy vulnerability (from favourability values):

pred <- multGLM(rotif.env, sp.cols = c("Apriod", "Burceo", "Kcochl"), var.cols = 5:17)$predictions

head(pred)

vulnerability(pred, sp.cols = "Apriod_F", categories = 8)

vulnerability(pred, sp.cols = c("Apriod_F", "Burceo_F", "Kcochl_F"), categories = c(8, 16, 2))
```

Index

- * **character**
 - spCodes, 59
- * **classes**
 - integerCols, 30
 - multConvert, 35
- * **datasets**
 - rotif.env, 50
 - rotifers, 52
- * **manip**
 - integerCols, 30
 - multConvert, 35
 - splist2presabs, 60
 - transpose, 64
- * **models**
 - distPres, 9
 - Fav, 13
 - modelTrim, 32
 - multGLM, 36
 - multTSA, 42
 - percentTestData, 46
 - stepByStep, 61
- * **model**
 - getPreds, 26
- * **multivariate**
 - corSelect, 7
 - FDR, 17
 - multGLM, 36
 - multicol, 40
 - multTSA, 42
 - stepByStep, 61
- * **package**
 - fuzzySim-package, 2
- * **prediction**
 - getPreds, 26
- * **regression**
 - multGLM, 36
 - multTSA, 42
 - stepByStep, 61
- * **spatial**
 - distPres, 9
 - multTSA, 42
- as.character, 35
- as.factor, 35
- as.integer, 31, 35
- barplot, 12, 25, 53
- bioThreat, 5, 16, 53, 54
- cor, 7, 9, 62
- corSelect, 7, 37, 39
- detectCores, 44
- difftime, 64
- dist, 10, 11
- distPres, 9, 20, 43, 57
- entropy, 11
- family, 7, 18
- Fav, 5, 6, 12, 13, 16, 17, 23, 26, 27, 38, 39, 42, 48, 53, 54, 62, 66
- favClass, 5, 6, 16
- FDR, 8, 9, 17, 37, 38
- fuzSim, 10, 19, 23, 25, 34, 56, 57
- fuzzyOverlay, 22, 25
- fuzzyRangeChange, 23, 24
- fuzzySim (fuzzySim-package), 2
- fuzzySim-package, 2
- getPreds, 26
- glm, 7, 14, 18, 27, 37, 39, 62, 63
- gridRecords, 28
- integerCols, 30
- is.integer, 31
- lower.tri, 65
- modelTrim, 32, 37–39, 42, 43, 63

modOverlap, [21](#), [23](#), [25](#), [33](#)
multConvert, [31](#), [35](#)
multGLM, [5](#), [15–17](#), [20](#), [26](#), [27](#), [36](#), [43](#), [46](#), [53](#),
[57](#)
multicol, [8](#), [9](#), [38](#), [39](#), [40](#)
multTSA, [20](#), [38](#), [42](#), [57](#)

p.adjust, [18](#), [19](#), [37](#)
p.adjust.methods, [18](#)
pairwiseRangemaps, [44](#), [47](#), [48](#)
parallel, [44](#)
percentTestData, [46](#)
poly, [43](#)
POSIXct, [63](#)
predict, [27](#)
predict.glm, [37](#), [38](#)
proc.time, [64](#)

rangemapSim, [45](#), [47](#)
rarity, [48](#), [67](#)
rotif.env, [50](#)
rotifers, [52](#)

sharedFav, [6](#), [52](#)
simFromSetOps, [48](#), [54](#)
simMat, [10](#), [21](#), [48](#), [56](#), [56](#), [60](#), [65](#)
spCodes, [38](#), [50](#), [59](#)
splist2presabs, [37](#), [50](#), [60](#)
step, [32](#), [33](#), [37–39](#), [42](#), [62](#), [63](#)
stepByStep, [61](#)
strsplit, [60](#)
substr, [60](#)
Sys.time, [63](#), [64](#)

t, [64](#)
table, [61](#)
timer, [63](#)
transpose, [57](#), [64](#)
triMatInd, [65](#)

upper.tri, [65](#)

vulnerability, [49](#), [66](#)