

$\mu Toss$ Quick Start Guide

$\mu Toss$ Team

September 13, 2010

1 Introduction

The $\mu Toss$ packages allow the user to discover, apply and compare multiple testing procedure and multiple interval estimation procedures.

The $\mu Toss$ packages include a corpus of functions implementing and integrating these procedures and a GUI. These are found in the `mutoss` and `mutossGUI` packages respectively.

2 $\mu Toss$ Rationale

The rationale behind the $\mu Toss$ packages is two-fold.

It is aimed at allowing statisticians to discover, apply and compare standard and custom multiplicity controlling procedures. This is achieved by the `mutoss` package.

It is also aimed at the researcher wishing to Analyse new data or reproduce published results. This is accomplished by the `mutossGUI` package.

| |
|---|
| At the time of release, the package has only undergone basic testing. This being the case, we recommend new data to be analyzed with standard software alongside $\mu Toss$. This is planned to change in future releases. |
|---|

3 System Requirements

3.1 `mutoss` Package

The package will run on any machine running R with recommended version 2.8 and above.

3.2 `mutossGUI` package

On top of the `mutoss` package requirements, Java Run time Environment ver 5 and above is needed.

4 GUI Work flow

Download and install the *mutossGUI* package. The GUI should start automatically. Others wise load it with

```
>mutossGUI()
```

4.1 Testing of Hypotheses

If you have already a vector of p-values start at step (5).

1. Load the raw data (assumed to be a *data.frame* object) using the **Data** button.
2. Specify the model type and explanatory variables using the **Model** button. For linear contrasts choose **Single endpoint in k groups**. For applying the same model to many response variables choose **Multiple (linear) regression**.
3. Define model by choosing response and explanatory variables.
4. Define the hypotheses of interest by specifying the contrasts using the **Hypotheses** button.
5. Insert p-values using the **p-Value** button or calculate them following the previous steps.
6. Choose the error type to control using the **Error Rate** button.
7. Use the **Adjusted p-Values** to calculate the procedure specific adjusted p-values (you will be prompted for additional options when necessary) or choose **Rejected** to apply the procedure and reject hypotheses.
8. Visualize results by choosing the **Info** option in the **Adjusted p-Values** or **Rejected** buttons.
9. Save the output as an R object using the **File->Export MuToss Object to R** option.

Further analysis is now possible using the `compareMutoss` functions or other R functionality.

4.2 Interval Estimations

Steps 1-4 are identical to the hypothesis testing work flow.

1. Load the raw data (assumed to be a *data.frame* object) using the **Data** button.
2. Specify the model type and explanatory variables using the **Model** button. For linear contrasts choose **Single endpoint in k groups**. For applying the same model to many response variables choose **Multiple (linear) regression**.

3. Define model by choosing response and explanatory variables.
4. Define the contrasts of interest by specifying the contrasts using the **Hypotheses** button.
5. Choose the error type to control using the **Error Rate** button.
6. Use the **Confidence Intervals** to compute confidence intervals on parameters of interest.
7. Visualize results by choosing the **Info** option in the **Confidence Intervals** button.
8. Save the output as an R object using the **File->Export MuToss Object to R** option.

Further analysis is now possible using R functionality.

5 Command Line Work Flow

Download and install the *mutoss* package to access the different procedures in the package (note *mutossGUI* is not needed for this purpose). A list can be presented using

```
>help(package='mutoss')
```

To work with these elementary functions, just use them as any other R function. See inline help for further details.

To use these functions to read and write into Mutoss S4 class objects use the *mutoss.apply()* function. See the inline help of the function for further details.

6 Glossary

Hypotheses-Testing-Procedures The corpus of procedures for testing multiple statistical hypotheses.

Interval-Estimating-Procedures The corpus of procedures for constructing interval estimates for multiple parameters.

p-Value-Procedures The corpus of (multiple) hypotheses testing procedures which rely on the marginal p-values of each hypothesis (and do not require the original data and model). These procedures might possibly require additional information such as logical relations between procedures, a qualitative description of the probabilistic relation between test statistics etc.

Data-Procedures The corpus of (multiple) testing procedures which require the original response variables, the explanatory variables (model) and the parameters of interest (contrasts).

These procedures can be seen as p-value-procedures with a specific relation between test-statistics which is derived from the model and the contrasts.

Error-Type The type of error a procedure aims to control. This can be a hypothesis testing error rate (FWER, FDR,...) or an interval estimation error rate (simultaneous coverage, false coverage rate,...).

Error-Rate The allowed rate of the *Error Type*.