

Lesson 3

Jan Verbesselt, Frank Davenport, Ben De Vries

November 7, 2013

Abstract

Today we will explore the potential of R and the relevant libraries which enable reading, writing, analysis, and visualisation of spatial data. The objective of today is to show what sort of spatial analysis can be done using a script and give you a better idea of what is possible. Today is more a tutorial style of lesson as a preparation for next weeks lessons on vector and raster data analysis.

1 Today's learning objectives

- Read, write, and visualize spatial data (vector/raster) using a script
- Find libraries which offer spatial data handling functions
- Learn to include functions from a library in your script
- Spatially join points and polygon's

2 Set your working directory and load your libraries

2.1 Set the working directory

Let's do some basic set up first.

- Create a folder which will be your working directory e.g. *lesson3*
- Create an R script within that folder
- Set your working directory to the *lesson3* folder
- Create a *data* folder within your working directory

In the code block below type in the file path to where your data is being held and then (if you want) use the `setwd()` (set working directory) command to give R a default location to look for data files.

```
>setwd("lesson3")
>getwd()

>datdir <- file.path("data")
>datdir <- "data"
```

2.2 Load libraries

By loading the *rasta* package, a series of R packages are automatically loaded that will provide the functions we need to complete this exercise. For this exercise all of the packages should (hopefully) be already installed on your machine. We will load them below using the `library()` command.

```
>library(rasta)
```

Below the packages are listed that are automatically loaded (see Packages tab in Rstudio). We included some comments describing how we use each of the packages in the exercises.

```
>## Packages for Reading/Writing/Manipulating Spatial Data
>library(rgdal) # reading shapefiles and raster data
>library(rgeos) # vector manipulations
>library(maptools) # mapping
>library(spdep)  # useful spatial stat functions
>library(spatstat) # functions for generating random points
>library(raster) # raster data analysis
>## Packages for Data Visualization and Manipulation
>library(ggplot2) # plotting
>library(reshape2) # preparing your data
>library(scales)
```

What does the scales package do?

3 Read, plot, and explore spatial data

3.1 Read in a shapefile

The most flexible way to read in a shapefile is by using the `readOGR` command. This is the only option that will also read in the `.prj` file associated with the shapefile. NCEAS has a useful summary of the [various ways to read in a shapefile](#). We recommend always using `readOGR()`. Read OGR can be used for almost any vector data format. To read in a shapefile, you enter two arguments:

- `dsn`: the directory containing the shapefile (even if this is already your working directory)
- `layer`: the name of the shapefile, without the file extension

```
>?readOGR
```

Let's download the file, unzip, and read it in into R:

```
>download.file("http://rasta.r-forge.r-project.org/kenyashape.zip",
+             file.path(datdir, "kenyashape.zip"))
>unzip(file.path(datdir, "kenyashape.zip"), exdir = datdir)
>kenya <- readOGR(dsn = datdir, layer = "kenya")
```

What is the projection of this shape file?

3.2 Plotting the data

Plotting is easy, use the `plot()` command:

```
>plot(kenya)
```




Figure 1: Adminstrative boundaries of Kenya

Obviously there are more options to dress up your plot and make a proper map/graphic. A common method is to use `spplot()` from the `sp` package. However, functions available in the **ggplot2** package are very intuitive and produce excellent maps. We will address maps and graphics later in the class. For now, let us move onto reading in some tabular data and merging that data to our shapefile (similar to the join operation in ArcGIS).

3.3 Exploring the data within the vector file

We can explore some basic aspects of the data using `summary()` and `str()`. Summary works on almost all R objects but returns different results depending on the type of object. For example if the object is the result of a linear regression then summary will give you the coefficient estimates, standard errors, t-stats, R^2 , et cetera.

```
>summary(kenya)
>str(kenya,2)
```

As mentioned above, the `summary()` command works on virtually all R objects. In this case it gives some basic information about the projection, coordinates, and data contained in our shapefile

The `str()` or structure command tells us how R is actually storing and organizing our shapefile. This is a useful way to explore complex objects in R. When we use `str()` on a spatial polygon object, it tells us the object has five “slots”:

1. *data*: This holds the data.frame
2. *polygons*: This holds the coordinates of the polygons
3. *plotOrder*: The order that the coordinates should be drawn
4. *bbox*: The coordinates of the bounding box (edges of the shape file)
5. *proj4string*: A character string describing the projection system

The only one we want to worry about is data, because this is where the data.frame() associated with our spatial object is stored. We access slots using the @ sign.

```
>## ACCESS THE SHAPEFILE DATA
>dmdat <- as(kenya, "data.frame")
># extract the data into a regular data.frame
>head(dmdat)

  ip89DId ip89DName
0    1010   Nairobi
1    2010    Kiambu
2    2020 Kirinyaga
3    2030   Muranga
4    2040 Nyandaura
5    2050    Nyeri

>kenya$new <- 1:nrow(dmdat)
># add a new column, just like adding data to a data.frame
>head(kenya@data)

  ip89DId ip89DName new
0    1010   Nairobi   1
1    2010    Kiambu   2
2    2020 Kirinyaga   3
3    2030   Muranga   4
4    2040 Nyandaura   5
5    2050    Nyeri    6
```

4 Read in a .csv file and join it to the shapefile

4.1 Read in a .csv file

First lets read in a *.csv* file using `read.csv()`

```
>## READ AND EXPLORE A CSV
>filepath <- system.file("extdata/kenpop89to99.csv", package = "rasta")
>d <- read.csv(filepath)
```

The data is also available from <http://rasta.r-forge.r-project.org/>. How can we download the data from the website and read in it into R?

Before we merge the csv file to our shapefile, let's do some basic cleaning. The csv file has some excess columns and rows. Let's get rid of them. We access rows and columns by using square brackets `[,]`.

Here are some examples using are data.frame *d*:

- `d[1,]` first row, all columns
- `d[,1]` first column all rows
- `d[1,1]` item in the first row and first column
- `d[,1:5]` columns 1 through 5 (also works with rows)
- `d[,c(1,4,5)]` columns 1,4 and 5 (also works with rows)
- `d$variable` same as above, but returns the column as a vector
- `d[d$variable>10,]` rows from all columns that correspond where the values in 'variable' are greater than 10

Hopefully you get the idea. See the R cheat sheet: <http://cran.r-project.org/doc/contrib/Short-refcard.pdf> for more information. Now we extract only the columns we want and then use the `unique()` command to get rid of duplicate rows.

Let's practice:

```
>## EXTRACT COLUMNS FROM CSV
>names(d)
>d <- d[,c("ip89DIId", "PopChg", "BrateChg", "Y89Pop", "Y99Pop")]
>#Grab only the columns we want
>names(d)
>str(d)
>nrow(d)
>d <- unique(d) #get rid of duplicate rows
>nrow(d) #note we now have less rows
```

4.2 Join the csv file to our shapefile

In R there a variety of options available for joining data sets. The most simple and intuitive is the `merge()` command (see `?merge` for details). Merge takes two data.frames and matches them based on common attributes in columns. If the user does not specify the name(s) of the columns then merge will just look for common column names and perform the join on those.

However with spatial objects the process is a little more tricky.

Unfortunately merge automatically re-orders the new merged data.frame based on the common columns. This will not work for a spatial object as the associated shapes (points, lines, or polygons) would have to be reordered as well. There are a variety of ways around this and we will show a simple one below.

First we demonstrate the basic `merge()` function. Then we will show one method for merging tabular to spatial data.

```
>## EXPLORE MERGE AND DO A TABLE JOIN
>#First a basic Merge Just to Demonstrate
>d2 <- kenya@data
>names(d)

[1] "ip89DId" "PopChg" "BrateChg" "Y89Pop" "Y99Pop"

>names(d2)

[1] "ip89DId" "ip89DName" "new"

>d3 <- merge(d,d2)
>#They have common column names so we don't have to specify what to join on
>head(d3)
```

	ip89DId	PopChg	BrateChg	Y89Pop	Y99Pop	ip89DName	new
1	1010	57	-12	1325620	2085820	Nairobi	1
2	2010	52	-14	908120	1383300	Kiambu	2
3	2020	16	-15	389440	452180	Kirinyaga	3
4	2030	-14	-31	862540	737520	Muranga	4
5	2040	34	-21	348520	468300	Nyandaura	5
6	2050	6	-23	607980	644380	Nyeri	6

```
>d4 <- merge(d,kenya) #This will produce the same result.
>head(d4)
```

	ip89DId	PopChg	BrateChg	Y89Pop	Y99Pop	ip89DName	new
1	1010	57	-12	1325620	2085820	Nairobi	1
2	2010	52	-14	908120	1383300	Kiambu	2
3	2020	16	-15	389440	452180	Kirinyaga	3
4	2030	-14	-31	862540	737520	Muranga	4
5	2040	34	-21	348520	468300	Nyandaura	5
6	2050	6	-23	607980	644380	Nyeri	6

Now lets do the Table Join: Join csv data to our Shapefile We can do the join in one line by using the match() function.

```
>?match
```

```
>ds1 <- kenya ## take a copy as backup
```

```
>str(as(kenya,"data.frame"))
```

```
'data.frame':      41 obs. of  3 variables:
```

```
$ ip89DId  : int  1010 2010 2020 2030 2040 2050 3010 3020 3030 3040 ...
```

```
$ ip89DName: Factor w/ 41 levels "Baringo","Bugoma",...: 26 11 13 25 30 31 12 17 19 24 ...
```

```
$ new      : int   1 2 3 4 5 6 7 8 9 10 ...
```

```
>str(d)
```

```
'data.frame':      41 obs. of  5 variables:
```

```
$ ip89DId : int  1010 2010 2020 2030 2040 2050 3010 3020 3030 3040 ...
```

```
$ PopChg  : int   57 52 16 -14 34 6 37 31 25 40 ...
```

```
$ BrateChg: int  -12 -14 -15 -31 -21 -23 -11 -1 -16 -18 ...
```

```
$ Y89Pop  : int  1325620 908120 389440 862540 348520 607980 593260 375320 57960 459740 ..
```

```
$ Y99Pop  : int  2085820 1383300 452180 737520 468300 644380 813060 490400 72380 643240 .
```

Let's do the matching:

```
>kenya@data <- data.frame(as(kenya,"data.frame"),
```

```
+      d[match(kenya@data[, "ip89DId"], d[, "ip89DId"]),])
```

```
>match(kenya@data[, "ip89DId"], d[, "ip89DId"])
```

```
[1]  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25
```

```
[26] 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41
```

```
>## kenya@data[, "ip89DId"]%in%d[, "ip89DId"]
```

```
>names(ds1)
```

```
[1] "ip89DId" "ip89DName" "new"
```

```
>names(kenya)
```

```
[1] "ip89DId" "ip89DName" "new" "ip89DId.1" "PopChg" "BrateChg"
```

```
[7] "Y89Pop" "Y99Pop"
```

```
>head(kenya)
```

	ip89DId	ip89DName	new	ip89DId.1	PopChg	BrateChg	Y89Pop	Y99Pop
0	1010	Nairobi	1	1010	57	-12	1325620	2085820
1	2010	Kiambu	2	2010	52	-14	908120	1383300
2	2020	Kirinyaga	3	2020	16	-15	389440	452180
3	2030	Muranga	4	2030	-14	-31	862540	737520
4	2040	Nyandaura	5	2040	34	-21	348520	468300
5	2050	Nyeri	6	2050	6	-23	607980	644380

Note also that we have duplicated the join field 'ip89DId'. We can delete it afterwards but it's a nice way to double check and make sure our join worked correctly. More information can be found [here](#).

5 Create random points and extract as a text file

We are going to do a point in polygon spatial join. However before we do that we are going to generate some random points. We will use the function `runifpoint()` from the `spatstat` package. This function creates N points drawn from a spatial uniform distribution (complete spatial randomness) within a given bounding box. The bounding box can be in a variety of forms but the most straightforward is simply a four element vector with $xmin$ (the minimum x coordinate), $xmax$, $ymin$, and $ymax$. In the code below we will extract this box from our Kenya data set, convert it to a vector, generate the points, and then plot the points on top of the Kenya map.

```
>## GENERATE RANDOM POINTS
>win <- bbox(kenya)
>#the bounding box around the Kenya dataset
>win
>win <- t(win)
>#transpose the bounding box matrix
>win
>win <- as.vector(win)
>#convert to a vector for input into runifpoint()
>win
>dran1 <- runifpoint(100, win = as.vector(t(bbox(kenya))))
>#create 100 random points

>win <- extent(kenya)
>dran2 <- runifpoint(n = 100, win = as.vector(win))
```

```
>plot(kenya)
>plot(dran1, add = TRUE, col = "red")
>plot(dran2, add = TRUE, col = "blue", pch = 19, cex = 0.5)
```




Figure 2: Random points within the Kenya shape file

Now that we have created some random points, we will extract the x coordinates (longitude), y coordinates (latitude), and then simulate some values to go with them.

```
>##CONVERT RANDOM POINTS TO DATA.FRAME
```

```
>dp <- as.data.frame(dran1)
```

```
>#This creates a simple data frame with 2 columns, x and y
```

```
>head(dp)
```

	x	y
1	36.99775	-1.3536290
2	35.71125	0.8575079
3	35.67045	-1.9205217
4	38.43750	-1.7491008
5	37.30662	0.4651358
6	38.87545	-3.1675016

```
>#Now we will add some values that will be aggregated in the next exercise
```

```
>dp$values<-rnorm(100,5,10)
```

```
>#generates 100 values from a Normal distribution with mean 5, and sd=10
```

```
>head(dp)
```

	x	y	values
1	36.99775	-1.3536290	-1.607262
2	35.71125	0.8575079	14.463026
3	35.67045	-1.9205217	9.712926
4	38.43750	-1.7491008	-5.672025
5	37.30662	0.4651358	-6.303184
6	38.87545	-3.1675016	-3.747729

6 Do a point in polygon spatial join

Now we will convert the *data.frame* to a *SpatialPointsDataFrame* object and then do a point in polygon spatial join. The command for converting coordinates to spatial points is *SpatialPointsDataFrame()*

```
>## CONVERT RANDOM POINTS TO SPATIAL POINTS DATAFRAME
>dsp <- SpatialPointsDataFrame(coords = dp[, c("x","y")],
+                             data = data.frame("values" = dp$values))
>summary(dsp)
```

Object of class SpatialPointsDataFrame

Coordinates:

	min	max
x	33.939787	41.769554
y	-4.632792	4.505862

Is projected: NA

proj4string : [NA]

Number of points: 100

Data attributes:

	Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
	-18.250	-1.841	5.186	5.521	13.910	28.910

Since the Data was Generated from a source with same projection as the Kenya data, we will go ahead and define the projection:

```
>dsp@proj4string <- kenya@proj4string
```


Now that we have created some points and defined their projection, we are ready to do a point in polygon spatial join. We will use the `over()` command (short for `overlay()`).

In the `over()` command we feed it a spatial polygon object (`ds`), a spatial points object (`dsp`), and tell it what function we want to use to aggregate the spatial point up. In this case we will use the *mean* (but we could use any function or write our own). The result will give us a `data.frame`, and we will then put the resulting aggregated values back into the `data.frame()` associated with `ds` (`ds@data`).

See `?over()` for more information.

```
>## POINT IN POLY JOIN
>#The data frame tells us for each point the index of the polygon it falls into
>dmdat <- over(kenya, dsp, fn = mean)
>head(dmdat)

      values
0         NA
1         NA
2 10.243740
3         NA
4         NA
5  -7.524508

>inds <- row.names(dmdat)
>#get the row names of dmdat so that we can put the data back into the shape file
>head(inds)

[1] "0" "1" "2" "3" "4" "5"
```

Use the row names from `dmdat` to add the aggregated point values to the data of the Kenya shape file:

```
>names(kenya@data)

[1] "ip89DId" "ip89DName" "new" "ip89DId.1" "PopChg" "BrateChg"
[7] "Y89Pop" "Y99Pop"

>kenya@data[inds, "pntvals"] <- dmdat
>head(kenya@data)

  ip89DId ip89DName new ip89DId.1 PopChg BrateChg Y89Pop Y99Pop pntvals
0    1010   Nairobi  1     1010     57      -12 1325620 2085820      NA
1     2010    Kiambu  2     2010     52      -14  908120 1383300      NA
2     2020 Kirinyaga  3     2020     16      -15  389440  452180 10.243740
3     2030   Muranga  4     2030    -14      -31  862540  737520      NA
4     2040 Nyandaura  5     2040     34      -21  348520  468300      NA
5     2050    Nyeri  6     2050      6      -23  607980  644380 -7.524508
```

7 Cropping a raster using a shape file

```
>library(rasta)
>filepath <- system.file("extdata", "anom.2000.03.tiff", package = "rasta")
>g <- raster(filepath)
>plot(g)
>plot(kenya, add = TRUE) # plot kenya on top to get some sense of the extent

>## Crop the Raster Dataset to the Extent of the Kenya Shapefile
>gc <- crop(g, kenya) #clip the raster to the extent of the shapefile
>#Then test again to make sure they line up
>plot(gc)
>plot(kenya, add = TRUE)
```




Figure 3: Temperature anomaly for Africa (for March 2003)




Figure 4: Kenian temperature anomaly for March 2003

8 Make maps with ggplot2()

If you have not already done so, load ggplot2 and some related packages. For more info on the ggplot2 and the grammar of graphics see the resources at <http://had.co.nz/ggplot2/>. The ‘gg’ in the ggplot2 is short for *The Grammar of Graphics* which references a famous book by the same name. The idea behind the book and the software is to try and decompose any graphic into a set of fundamental elements. We can then use these elements to construct any type of graphic we want (the elements are the grammar), rather than having a different command for every type of graphic out there. We do not have time to do a full overview of ggplot2 but if you click on the link above and scroll down there is a good visual overview of how ggplot2 works. If you have time take a minute to visit the website.

8.1 Setting up the data with fortify()

The ggplot2() package separates spatial data into 2 elements: (1) the data.frame and 2) the spatial coordinates. If you want to make a map from a shapefile you first have to use the fortify() command which converts the shapefile to a format readable by ggplot2:

```
>## PREP SPATIAL DATA FOR GGLOT WITH FORTIFY()
>pds <- fortify(kenya, region="ip89DId")
>#convert to form readable by ggplot2
>pds$ip89DId <- as.integer(pds$id)
>head(pds)
```

	long	lat	order	hole	piece	group	id	ip89DId
1	36.90520	-1.164938	1	FALSE	1	1010.1	1010	1010
2	36.91353	-1.165222	2	FALSE	1	1010.1	1010	1010
3	36.91662	-1.165453	3	FALSE	1	1010.1	1010	1010
4	36.93624	-1.175885	4	FALSE	1	1010.1	1010	1010
5	36.93929	-1.178597	5	FALSE	1	1010.1	1010	1010
6	36.93855	-1.180768	6	FALSE	1	1010.1	1010	1010

Now, we will build the map step by step using ggplot2. We could do it all in one line, but it's easier to do it one step at a time so you can see how the different elements combine to make the final graphic. In the code below we will first create the basic layer using the ggplot command, and then we customize to it.

```
>#MAKE A BASIC MAP
>p1 <- ggplot(d)
>p1 <- p1 + geom_map(aes(fill = PopChg, map_id = ip89DId), map = pds)
>p1 <- p1 + expand_limits(x = pds$long, y = pds$lat)
>p1 <- p1 + coord_equal() #this keeps the map from having that 'squished' look
>p1
```




Figure 5: Basic Map with Default Elements

Now we have a basic map, let's make some tweaks to it.

```
>#CHANGE THE COLOR SCHEME, TWEAK THE LEGEND
>#Change the Colour Scheme
>p1 <- p1 + scale_fill_gradient(name="Population \nChange",
+                               low ="wheat", high = "steelblue")
>#to set break points, enter in breaks=c(...,...)
>#The \n in Population \nChange' indicates a carriage return
>p1
```




Figure 6: We Changed the Color Scale and Gave the Legend a Proper Name

Now we will get rid of all the unnecessary information in the background.

```
>#EDIT THE BACKGROUND  
>#Get Rid of the Background  
>#Blank Grid, Background,Axis,and Tic Marks  
>bGrid <- theme(panel.grid = element_blank())  
>bBack <- theme(panel.background = element_blank())  
>bAxis <- theme(axis.title.y = element_blank())  
>bTics <- theme(axis.text = element_blank(), axis.text.y = element_blank(),  
+             axis.ticks = element_blank())  
>p1 <- p1 + bAxis + bTics + bGrid + bBack + xlab("")  
>p1
```




Figure 7: We got rid of all the unnecessary background material

Now let's label the polygon names and data values.

```
>#ADD SOME LABELS
>#Add Some Polygon labels
>#Polygon Labels
>cens <- as.data.frame(coordinates(kenya))
>#extract the coordinates for centroid of each polygon
>cens$Region <- kenya$ip89DName
>cens$ip89DId <- kenya$ip89DId
>head(cens) #we will use this file to label the polygons
```

	V1	V2	Region	ip89DId
0	36.85894	-1.2985245	Nairobi	1010
1	36.82240	-1.0743964	Kiambu	2010
2	37.31793	-0.5266225	Kirinyaga	2020
3	37.03273	-0.8108003	Muranga	2030
4	36.48166	-0.3224750	Nyandaura	2040
5	36.95420	-0.3395780	Nyeri	2050

```
>p1 <- p1 + geom_text(data = cens, aes(V1,V2,label = Region), size = 2.5, vjust=1) +
+ labs(title="Population Change in Kenya \n (1989-1999)")
>p1
```




Figure 8: We added text labels and a title

```
>#Add Some value Labels
>pdlab <- merge(cens,d) #Merge the centroids without data
>head(pdlab) #We will use this to label the polygons with their data values
```


	ip89DId	V1	V2	Region	PopChg	BrateChg	Y89Pop	Y99Pop
1	1010	36.85894	-1.2985245	Nairobi	57	-12	1325620	2085820
2	2010	36.82240	-1.0743964	Kiambu	52	-14	908120	1383300
3	2020	37.31793	-0.5266225	Kirinyaga	16	-15	389440	452180
4	2030	37.03273	-0.8108003	Muranga	-14	-31	862540	737520
5	2040	36.48166	-0.3224750	Nyandaura	34	-21	348520	468300
6	2050	36.95420	-0.3395780	Nyeri	6	-23	607980	644380

```
>p1 <- p1 + geom_text(data = pdlab,
+   aes(V1, V2, label = paste("(",PopChg,")",sep="")),
+   colour = "black" ,size = 2,vjust = 3.7)
>p1
```




Figure 9: Now we added the actual value labels for the data

8.2 Plotting Panel Maps

So now we have made a basic map with a legend, location labels, and value labels. One of the advantages of ggplot is the ease with which you can create panel graphics, or to use the ggplot terminology ‘faceting’. Imagine for example that you have a spatial panel data set—multiple observations of the same spatial feature over several years. Ggplot gives you several options for displaying this data using either the `facet_wrap()` or `facet_grid()` commands. In the example below we will make panel maps for the population data in the Kenya data set.

```
>#-----RESHAPE THE DATA AND MAKE A PANEL MAP-----
>pd <- d[,c("ip89DId","Y89Pop","Y99Pop")] #select out certain columns
>pd <- melt(pd, id.vars="ip89DId") # convert the data to 'long' form
>head(pd) # take a look at the data
```

	ip89DId	variable	value
1	1010	Y89Pop	1325620
2	2010	Y89Pop	908120
3	2020	Y89Pop	389440
4	2030	Y89Pop	862540
5	2040	Y89Pop	348520
6	2050	Y89Pop	607980

```

>pmap <- ggplot(pd)
>p2 <- pmap + geom_map(aes(fill = value, map_id = ip89DId), map=pds) +
+               facet_wrap(~variable)
>p2 <- p2 + expand_limits(x = pds$lon, y = pds$lat) + coord_equal()
>p2 + labs(title="Basic panel map")

```




Figure 10: Basic panel map

We can use the ``ncols'` (number of columns) argument in `facet_wrap()` to make the panels stack vertically instead of horizontally.

```

>#-----TWEAK THE PANEL MAP-----
>#If we want to stack the panels vertically we change the options in facet_wrap()
>p2 <- p2 + facet_wrap(~variable, ncol=1) #have only 1 column of panels

```

Finally we can use the same options we used above to make our final map.

```

>##MORE PANEL MAP TWEAKS
># We can add all the other tweaks as before
>p2 <- p2 + scale_fill_gradient(name="Population", low = "wheat", high = "steelblue")
>#to set break points, enter in
>p2 <- p2 + bAxis + bGrid + bTics + bBack
>p2 <- p2 + theme(panel.border=element_rect(fill=NA))
># this removes the background but keeps aborder around the panels
># We can also adjust the format, theme, et cetera of the panel lables
># with "strip.text.x"
>p2 <- p2 + theme(strip.background=element_blank(), strip.text.x = element_text(size=12))
>p2
>

```




Figure 11: Basic panel map

9 Exercise lesson 3

Provide a clear, reproducible, and documented script where:

- the raster (temperature anomaly) is sampled (in a random sample of 30 pixels),
- the random points are then visualised on top of the raster
- derive the median or standard deviation of all the temperature values of the sampled points (hint: see *?extract* within the *raster* package)
- add the derived e.g. median to the plot as a text label
- upload the code (reproducible!) to your github account
- Add your name, date, and description of what the script does

10 Special thanks and more info

Special acknowledgments go to **Frank Davenport** (**Spatial R class**) for excellent R spatial introduction on which this lesson is based.