

jss: A Document Class for Publications in the Journal of Statistical Software

Achim Zeileis

July 2, 2007

1 Introduction

The L^AT_EX 2_ε document class **jss** is an extension of the standard L^AT_EX 2_ε **article** class for publications in the Journal of Statistical Software (JSS, <http://www.jstatsoft.org/>). It provides infrastructure for all four kinds of publications in JSS: regular articles, code snippets, book reviews and software reviews. Each document requires several declarations to be made in the header (before `\begin{document}`) which are described in Section 2 separately for articles/code snippets and book/software reviews along with some general commands which can be used in all documents.

The final version of JSS papers should be prepared using this JSS style file; the submission of the final version needs to include the full sources (`.tex`, `.bib`, and all graphics). A quick check for the most important aspects of the JSS style is given in Section 2.1; authors should make sure that all of them are addressed in the final version.

All documents need to be processed by pdf_TE_X, some useful information on this is provided in Section 3, which also contains some information on using B_IB_TE_X. B_IB_TE_X together with the style file `jss.bst` produces references and citations in the required format.

The actual code for the batch file (`jss.ins`), the driver (`jss.drv`) and the class (`jss.cls`) are briefly described in Section 4. Note, that usually you do not have to read that section when you want to prepare a submission for JSS.

2 Instructions for authors

To use the JSS styles, you have to include the class file `jss.cls`, the logo `jsslogo.jpg` and the B_IB_TE_X style `jss.bst` in your search path. This can either be your local working directory or in your `texmf` or `localtexmf` tree.

The L^AT_EX documents have to include the `jss.cls` first by

```
\documentclass[type]{jss}
```

where *type* can be **article** (which is the default), **codesnippet**, **bookreview** or **softwarereview**. Templates with brief instructions are provided in `article.tex`, `codesnippet.tex`, `bookreview.tex` and `softwarereview.tex` respectively. The corresponding commands used for the header declarations are described in more detail in the following.

By using `jss.cls`, the packages **graphicx**, **a4wide**, **color**, **hyperref**, **ae**, **fancyverb** and **natbib** are loaded automatically. Authors may, of course, include further packages but should not change the page layout or change the font or font encoding. If the package **thumbpdf** is available, its inclusion is encouraged

The titles of JSS publications are capitalized, i.e., in title style, but the section headers are not and should be in sentence-style.

Hint. If you want to use markup in section headers you will usually have to escape it for the PDF bookmarks by giving the text for the bookmark explicitly without markup, e.g.,

```
\section[Calling C++ from R]{Calling \proglang{C++} from \proglang{R}}
```

Hint. Sometimes L^AT_EX places a page break immediately after a (sub)section header. If this occurs in the *final* document please include a `\clearpage` before the header.

Hint. If compilation with pdfT_EX fails with an error at `\begin{document}` the reason is almost surely that some of the declarations in the header have not been made properly. For example, `\Plainauthor`, `\Plaintitle` or `\Plainkeywords` might be missing or still containing markup.

Acknowledgments should be included at the end of the paper before the references in a separate section set up via `\section*{Acknowledgments}`.

2.1 Style checklist

A quick check for the most important aspects of the JSS style is given below. Authors should make sure that all of them are addressed in the final version. More details can be found in the remainder of this manual.

- The manuscript can be compiled by pdfT_EX.
- `\proglang`, `\pkg` and `\code` has been used for highlighting throughout the paper (including references).
- References are provided in a `.bib` BIBT_EX database and included in the text by `\cite`, `\citep`, `\citet`, etc.
- Titles and headers are formatted properly:
 - `\title` in title style,
 - `\section` etc. in sentence style,
 - all titles in the BIBT_EX file in title style.
- Figures, tables and equations are marked with a `\label` and referred to by `\ref`, e.g., “Figure~\ref{...}”.
- Software packages are `\cite{}d` properly.

2.2 Articles and code snippets

For JSS articles and code snippets respectively, the following declarations have to be made in the header of the T_EX sources (before `\begin{document}`). See also the template `article.tex` or `codesnippet.tex` respectively.

`\author` The command `\author` specifies the list of authors. The name of each author should be followed by a linebreak and his affiliation (only the university, in a single line). The authors should be separated by `\And` (instead of `\and`), e.g.,

```
\author{Achim Zeileis\\Wirtschaftsuniversit\"at Wien \And
        Second Author\\Plus Affiliation}
```

If not all authors fit into a single line, `\AND` (instead of `\And`) should be used in front of authors that should go into the next line.

`\Plainauthor` The list of authors without affiliations. It needs to be comma-separated and must not contain

any markup (bold fonts etc.), e.g.,

```
\Plainauthor{Achim Zeileis, Second Author}
```

\title The title of the paper. It should be capitalized and may contain further markup (line breaks, bold fonts, etc.), e.g.,

```
\title{A Capitalized Title:\\ With a Package \pkg{foo} in the Subtitle}
```

\Plaintitle The full title without any markup (line breaks, bold fonts etc.). The default is to use **\title**, therefore it needs to be specified only if it is different from **\title**, e.g.,

```
\Plaintitle{A Capitalized Title: With a Package foo in the Subtitle}
```

\Shorttitle A shorter version of the title to be used for page headings. The default is to use **\title**, therefore it needs to be specified only if it is different from **\title**, e.g.,

```
\Shorttitle{A Capitalized Title}
```

\Abstract Enter the abstract for your article here, e.g.,

```
\Abstract{
  The abstract of the article.
}
```

\Keywords A comma-separated list of (at least one) keyword(s) which should not be capitalized, e.g., **\Keywords{keywords, comma-separated, not capitalized}**.

\Plainkeywords The list of keywords without any markup. The default is to use **\Keywords**, therefore it needs to be specified only if it is different from **\Keywords**.

\Volume The JSS volume number in which the article is published, e.g., **\Volume{11}**. Note: you will be provided with this information upon acceptance of your paper. If it was not accepted (yet), do not use this command.

\Issue The JSS issue number in which the article is published, e.g., **\Issue{9}**. Note: you will be provided with this information upon acceptance of your paper. If it was not accepted (yet), do not use this command.

\Month The month in which the article is published, e.g., **\Month{September}**. Note: you will be provided with this information upon acceptance of your paper. If it was not accepted (yet), do not use this command.

\Year The year in which the article is published, e.g., **\Year{2004}**. Note: you will be provided with this information upon acceptance of your paper. If it was not accepted (yet), do not use this command.

\Submitdate The date of submission for the article, e.g., **\Submitdate{2004-09-29}**. Note: you will be provided with this information upon acceptance of your paper. If it was not accepted (yet), do not use this command.

\Acceptdate The date of acceptance for the article, e.g., **\Acceptdate{2004-09-29}**. Note: you will be provided with this information upon acceptance of your paper. If it was not accepted (yet), do not use this command.

\Address The address of (at least) one author should be given in the following format

```
\Address{
  Achim Zeileis\\
```

```

Department of Statistics and Mathematics\\
Wirtschaftsuniversit\\at Wien\\
1090 Wien, Austria\\
E-mail: \email{Achim.Zeileis@wu-wien.ac.at}\\
URL: \url{http://statmath.wu-wien.ac.at/~zeileis/}
}

```

It is also possible to include your telephone and fax number, by adding them in the format

```

Telephone: +43/1/31336-5053
Fax: +43/1/31336-734

```

before the e-mail address.

Furthermore, if the document is prepared using the **Sweave** functions in R, something like the following line

```
%% need no \usepackage{Sweave.sty}
```

(with ‘%%’) needs to be included in the header.

2.3 Book and software reviews

For JSS book and software reviews respectively, the following declarations have to be made in the header of the T_EX sources (before `\begin{document}`). See also the template `bookreview.tex` or `softwarereview.tex` respectively. Note that some commands might differ between book and software reviews, this is always stated explicitly below.

\Reviewer The command `\Reviewer` specifies the name of the reviewer followed by a linebreak and his affiliation (only the university, in a single line), e.g.,

```
\Reviewer{Frederic Udina\\Pompeu Fabra University}
```

\Plainreviewer The name of the reviewer without affiliation. It must not contain any markup (bold fonts etc.), e.g.,

```
\Plainauthor{Frederic Udina}
```

The following five commands are just required for book reviews.

\Booktitle The title of the book. It should be capitalized and may contain further markup (line breaks, bold fonts, etc.), e.g.,

```
\Booktitle{Visualizing Categorical Data}
```

\Bookauthor Author(s) of the book, e.g.,

```
\Bookauthor{Michael Friendly}
```

If there are several authors they should be comma-separated, and the last author separated by **and**, e.g., `\Bookauthor{A and B}` or `\Bookauthor{A, B and C}`.

\Pubyear Year of publication, e.g., `\Pubyear{2000}`.

\ISBN ISBN number, e.g., `\ISBN{1-58025-660-0}`.

`\Pages` Number of pages, both arabic and roman (if available), e.g., `\Pages{456}` or `\Pages{xvi + 145}`.
The following command is just required for software reviews.

`\Softwaretitle` The title of the software. It should be capitalized and may contain further markup (line breaks, bold fonts, etc.), e.g.,
`\Softwaretitle{Aabel 1.5.7}`

The remaining commands are again required for both book and software reviews.

`\Publisher` Publisher of the book/software, e.g., `\Publisher{SAS Institute Inc.}` or `\Publisher{Gigawiz Ltd. Co.}`.

`\Pubaddress` Address of the publisher of the book/software, e.g., `\Pubaddress{Carey, NC}`.

`\Price` Price of the book/software. For books this might simply be `\Price{USD 69.95}` or `\Price{USD 69.95 (P)}`, but could also distinguish between hardcover and paperback versions `\Price{USD 69.95 (P), USD 89.95 (H)}`. Analogously, for a software it could be `\Price{USD 349 (standard), USD 249 (academic)}`.

`\URL` A URL for the book or software, e.g.,
`\URL{http://www.math.yorku.ca/SCS/vcd/}`

If no URL is available, use `\URL{}`.

`\Plaintitle` The full book or software title without any markup (line breaks, bold fonts etc.). The default is to use `\Booktitle` or `\Softwaretitle` respectively, therefore it needs to be specified only if it is different from `\Booktitle` or `\Softwaretitle`, e.g.,
`\Plaintitle{Visualizing Categorical Data}`

`\Shorttitle` A shorter version of the book or software title to be used for page headings. The default is to use `\Booktitle` or `\Softwaretitle` respectively, therefore it needs to be specified only if it is different from `\Booktitle` or `\Softwaretitle`, e.g.,
`\Shorttitle{Visualizing Categorical Data}`

`\Volume` The JSS volume number in which the review is published, e.g., `\Volume{11}`. Note: you will be provided with this information upon acceptance of your paper.

`\Issue` The JSS issue number in which the review is published, e.g., `\Issue{9}`. Note: you will be provided with this information upon acceptance of your paper.

`\Month` The month in which the review is published, e.g., `\Month{September}`. Note: you will be provided with this information upon acceptance of your paper.

`\Year` The year in which the review is published, e.g., `\Year{2004}`. Note: you will be provided with this information upon acceptance of your paper.

`\Submitdate` The date of publication for the review, e.g., `\Submitdate{2004-09-29}`. Note: you will be provided with this information upon acceptance of your paper.

`\Address` The address of (at least) one author should be given in the following format

```

\Address{
  Achim Zeileis\\
  Department f"ur Statistik & Mathematik\\
  Wirtschaftsuniversit"at Wien\\
  1090 Wien, Austria\\
  E-mail: \email{Achim.Zeileis@wu-wien.ac.at}\\
  URL: \url{http://statmath.wu-wien.ac.at/~zeileis/}
}

```

It is also possible to include your telephone and fax number, by adding them in the format

Telephone: +43/1/31336-5053
Fax: +43/1/31336-734

before the e-mail address.

2.4 Further commands

The **jss** package provides several commands for typesetting names related to software (programming languages, packages, code) and mathematical formulae.

Writing about software

- \proglang** This should be used for typesetting the names of programming languages, e.g., `\proglang{JAVA}`, `\proglang{C++}` or `\proglang{R}`. This applies also to programmable environments which also have a GUI like `\proglang{SAS}`, `\proglang{Stata}` or `\proglang{S-PLUS}`.
- \pkg** This should be used for typesetting the names of packages, e.g., `\pkg{CMregr}`, `\pkg{MATCH}` or `\pkg{strucchange}`.
- \code** This should be used for typesetting code chunks within the text, e.g., `\code{plot(1:10)}`. Currently, this simply uses a typewriter font and might give problems with special characters. In such cases the code can also be set using `\verb`, e.g., `\verb/print("hello world")/`.

Layout of code

`jss.cls` only provides very simple means of including code which are mostly borrowed from **Sweave**. There are three verbatim environments for code: `Code`, `CodeInput` and `CodeOutput`. Furthermore, there is an environment `CodeChunk` which can be put around sequences of `CodeInputs` and `CodeOutputs` to (hopefully) keep L^AT_EX from page-breaking in the middle of a code chunk. In short, there are two options: a) if no distinction between input and output is necessary, the code is placed between `\begin{Code}` and `\end{Code}`. b) If input and output should be distinguished, this can be done like in the following example.

```
\begin{CodeChunk}
\begin{CodeInput}
first input first line
first input second line
\end{CodeInput}
\begin{CodeOutput}
output of first input
\end{CodeOutput}
\begin{CodeInput}
second input
\end{CodeInput}
\begin{CodeOutput}
second output
\end{CodeOutput}
\end{CodeChunk}
```

An example what this could look like, is the following R code. The first three lines are the input, the rest is output.

```
\begin{CodeChunk}
\begin{CodeInput}
```

```

R> data(cars)
R> fm <- lm(dist ~ speed, data = log(cars))
R> summary(fm)
\end{CodeInput}
\begin{CodeOutput}
Call:
lm(formula = dist ~ speed, data = log(cars))

Residuals:
    Min       1Q   Median       3Q      Max
-1.00215 -0.24578 -0.02898  0.20717  0.88289

Coefficients:
            Estimate Std. Error t value Pr(>|t|)
(Intercept)  -0.7297     0.3758  -1.941   0.0581 .
speed         1.6024     0.1395   11.484 2.26e-15 ***
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.4053 on 48 degrees of freedom
Multiple R-Squared:  0.7331,    Adjusted R-squared:  0.7276
F-statistic: 131.9 on 1 and 48 DF,  p-value: 2.259e-15
\end{CodeOutput}
\end{CodeChunk}

```

If you prepare your paper using **Sweave** (which is recommended if you describe an R package) do *not* include **Sweave.sty** into your document, the necessary commands are already available within **jss.cls**. To prevent **Sweave** from including **Sweave.sty** automatically you need to include a line like

```
%% need no \usepackage{Sweave.sty}
```

(with ‘%%’) into the header of your document.

If this basic infrastructure for typesetting your code is not sufficient, you can also use other \LaTeX packages like the **listings** package.

Mathematical formulae

Commonly used operators like E , VAR , COV , and P should be set using the commands $\backslash E$, $\backslash \text{VAR}$, $\backslash \text{COV}$ and $\backslash \text{Prob}$. Beyond this, **jss** does not provide (or enforce) a certain mathematical notation. However, using the **statex** package (e.g., available from CTAN and in \TeX Live) could be useful.

3 Using pdf \TeX and Bib \TeX

Using pdf \TeX

A \LaTeX document (**foo.tex**, say) using **jss.cls** needs to be compiled using pdf \TeX , typically this will be done using either of the following commands:

```
pdflatex foo.tex
```

```
texi2dvi --pdf foo.tex
```

```
texi2pdf foo.tex
```

If you are not using command line tools but some integrated GUI editor for L^AT_EX documents you will have to press the ‘pdfL^AT_EX’ button (as opposed to the ‘L^AT_EX’ button).

All graphics included into the document have to be in a format pdfT_EX can deal with, i.e., PDF for vector graphics or JPG/PNG/etc. for bitmaps/raster graphics. If you cannot produce PDF graphics directly but only PS/EPS, these can be converted using `ps2pdf` or `epstopdf` (usually preferred).

Hint. If you are used to compiling your documents with standard L^AT_EX and then getting automatic reloads of the resulting DVI document in your DVI viewer, which is not possible with PDF documents in many PDF viewers: you might want to look at `xpdf` (Linux) or `gsview` (Windows, see <http://www.cs.wisc.edu/~ghost/gsview/>) which have a reload function.

Hint. If you want to use markup in section headers you will usually have to escape it for the PDF bookmarks by giving the text for the bookmark explicitly without markup, e.g.,

```
\section[Calling C++ from R]{Calling \proglang{C++} from \proglang{R}}
```

Hint. If you know how to produce L^AT_EX documents that can be processed with both L^AT_EX and pdfT_EX, you can do so if you provide an EPS substitute for `jsslogo.jpg` (e.g. an empty or converted `jsslogo.eps`). Note, however, that the final document needs to be processed with pdfT_EX. Neither this manual nor the JSS encourage or support compilation of JSS documents with standard L^AT_EX.

References with B^IB_T_EX

The format for references (e.g., articles, books, software, proceedings) should look like this

Brown RL, Durbin J, Evans JM (1975). “Techniques for Testing the Constancy of Regression Relationships over Time.” *Journal of the Royal Statistical Society B*, **37**, 149–163.

Friendly M (2000). *Visualizing Categorical Data*. SAS Insitute, Carey, NC.

R Development Core Team (2004). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria. ISBN 3-900051-00-3, URL <http://www.R-project.org/>.

Urbanek S, Theus M (2003). “iPlots – High Interaction Graphics for R.” In K Hornik, F Leisch, A Zeileis (eds.), “Proceedings of the 3rd International Workshop on Distributed Statistical Computing, Vienna, Austria,” ISSN 1609-395X, URL <http://www.ci.tuwien.ac.at/Conferences/DSC-2003/Proceedings/>.

Important. Note, that also the titles of papers are in title style (as opposed to sentence style), i.e., they are capitalized. The first word after a colon ‘:’ is always capitalized. Furthermore, commands like `\proglang` and `\pkg` should also be used for the references. The names of journals or proceeding volumes should not be abbreviated.

The easiest way to achieve this is to use B^IB_T_EX together with the style file `jss.bst`. To do so, the references just have to be included in a B^IB_T_EX file, `foo.bib` say, which has to be included at the end of the L^AT_EX document by `\bibliography{foo}`. Note, that to obtain references in the format above, the `title` field in your `bib` file, needs to be capitalized (contrary to the folklore, there are B^IB_T_EX styles that rely on this even for `@Article` entries), i.e. the entry `title = {Visualizing Categorical Data}` is correct, while entries like `title = {Visualizing categorical data}` or (even worse) `title = {{Visualizing categorical data}}` are not.

The default in `jss.cls` is to use the `natbib` package with options `authoryear`, `round` and `longnamesfirst`. If you cite any article with six or more authors the latter option should

be turned off. This can be done by using the option `shortnames` when loading the `jss.cls` class

```
\documentclass[article,shortnames]{jss}
```

4 The code

4.1 The batch file

First comes the code for creating the batch file `jss.ins` which in turn can be used for producing the package and driver files.

```
1 <*install>
2 \begin{filecontents}{\filename.ins}
3 % Simply TeX or LaTeX this file to extract various files from the source
4 % file 'jss.dtx'.
5 \def\filedate{2004/09/29}
6 \def\batchfile{jss.ins}
7 \input docstrip.tex
8 \generateFile{jss.drv}{t}{\from{jss.dtx}{driver}}
9 \generateFile{jss.cls}{t}{\from{jss.dtx}{class}}
10 \Msg{*****}
11 \Msg{* For documentation, run LaTeX on jss.dtx or jss.drv. *}
12 \Msg{*****}
13 \end{filecontents}
14 </install>
```

4.2 The driver

Next comes the documentation driver file for T_EX, i.e., the file that will produce the documentation you are currently reading. It will be extracted from this file by the `docstrip` program. Since it is the first code in the file one can alternatively process this file directly with L^AT_EX 2_ε to obtain the documentation.

```
15 <*driver>
16 \documentclass{ltxdoc}
17 \providecommand{\file}[1]{\texttt{#1}}
18 \providecommand{\pkg}[1]{\normalfont\fontseries{b}\selectfont #1}}
19 \usepackage{color,hyperref,a4wide}
20 \oddsidemargin1.2cm
21 \textwidth14.2cm
22 \textheight23.3cm
23 \topmargin-.7cm
24 \setlength{\parskip}{0.7ex plus0.1ex minus0.1ex}
25 \setlength{\parindent}{0em}
26 \begin{document}
27   \OnlyDescription
28   \DocInput{jss.dtx}
29 \end{document}
30 </driver>
```

4.3 The class

Next is the main part, the code for the class file.

It requires L^AT_EX 2_ε

```
31 <*class>
32 \NeedsTeXFormat{LaTeX2e}
33 \ProvidesClass{jss}[\filedate\space\fileversion\space jss class by Achim Zeileis]
34 </class>
```

and is based on the `article` class. But before we load the class we declare and process some options. These reflects whether we want to write an article, code snippet, a book re-

view or software review. The `shortnames` option is for loading `natbib` *without* the option `longnamesfirst`.

```

35 <*class>
36 %% options
37 \newif\if@article
38 \newif\if@codesnippet
39 \newif\if@bookreview
40 \newif\if@softwarereview
41 \newif\if@review
42 \newif\if@shortnames
43
44 \@articletrue
45 \@codesnippetfalse
46 \@bookreviewfalse
47 \@softwarereviewfalse
48 \@reviewfalse
49 \@shortnamesfalse
50
51 \DeclareOption{article}{\@articletrue%
52   \@codesnippetfalse \@bookreviewfalse \@softwarereviewfalse}
53 \DeclareOption{codesnippet}{\@articlefalse%
54   \@codesnippettrue \@bookreviewfalse \@softwarereviewfalse}
55 \DeclareOption{bookreview}{\@articlefalse%
56   \@codesnippetfalse \@bookreviewtrue \@softwarereviewfalse}
57 \DeclareOption{softwarereview}{\@articlefalse%
58   \@codesnippetfalse \@bookreviewfalse \@softwarereviewtrue}
59 \DeclareOption{shortnames}{\@shortnamestrue}
60
61 \ProcessOptions
62 \LoadClass[11pt,a4paper,twoside]{article}
63 </class>

```

A few packages are required and the font encoding is specified.

```

64 <*class>
65 %% required packages
66 \RequirePackage{graphicx,a4wide,color,hyperref,ae,fancyvrb}
67 \RequirePackage[T1]{fontenc}
68 </class>

```

The bibliography is generated using `natbib` and the `BIBTEX` style `jss.bst`.

```

69 <*class>
70 %% bibliography
71 \if@shortnames
72   \usepackage[authoryear,round]{natbib}
73 \else
74   \usepackage[authoryear,round,longnamesfirst]{natbib}
75 \fi
76 \bibpunct{{}{}}{;}{a}{}{,}
77 \bibliographystyle{jss}
78 </class>

```

Paragraphs are not indented, instead `\parskip` is increased.

```

79 <*class>
80 %% paragraphs
81 \setlength{\parskip}{0.7ex plus0.1ex minus0.1ex}
82 \setlength{\parindent}{0em}
83 </class>

```

To process the meta information we need some new commands: for all publications,

```

84 <*class>
85 %% for all publications
86 \newcommand{\Address}[1]{\def\@Address{#1}}
87 \newcommand{\Plaintitle}[1]{\def\@Plaintitle{#1}}
88 \newcommand{\Shorttitle}[1]{\def\@Shorttitle{#1}}
89 \newcommand{\Plainauthor}[1]{\def\@Plainauthor{#1}}
90 \newcommand{\Volume}[1]{\def\@Volume{#1}}
91 \newcommand{\Year}[1]{\def\@Year{#1}}
92 \newcommand{\Month}[1]{\def\@Month{#1}}
93 \newcommand{\Issue}[1]{\def\@Issue{#1}}
94 \newcommand{\Submitdate}[1]{\def\@Submitdate{#1}}
95 </class>

for articles and code snippets,

96 <*class>
97 %% for articles and code snippets
98 \newcommand{\Acceptdate}[1]{\def\@Acceptdate{#1}}
99 \newcommand{\Abstract}[1]{\def\@Abstract{#1}}
100 \newcommand{\Keywords}[1]{\def\@Keywords{#1}}
101 \newcommand{\Plainkeywords}[1]{\def\@Plainkeywords{#1}}
102 </class>

for book and software reviews,

103 <*class>
104 %% for book and software reviews
105 \newcommand{\Reviewer}[1]{\def\@Reviewer{#1}}
106 \newcommand{\Booktitle}[1]{\def\@Booktitle{#1}}
107 \newcommand{\Bookauthor}[1]{\def\@Bookauthor{#1}}
108 \newcommand{\Publisher}[1]{\def\@Publisher{#1}}
109 \newcommand{\Pubaddress}[1]{\def\@Pubaddress{#1}}
110 \newcommand{\Pubyear}[1]{\def\@Pubyear{#1}}
111 \newcommand{\ISBN}[1]{\def\@ISBN{#1}}
112 \newcommand{\Pages}[1]{\def\@Pages{#1}}
113 \newcommand{\Price}[1]{\def\@Price{#1}}
114 \newcommand{\Plainreviewer}[1]{\def\@Plainreviewer{#1}}
115 \newcommand{\Softwaretitle}[1]{\def\@Softwaretitle{#1}}
116 \newcommand{\URL}[1]{\def\@URL{#1}}
117 </class>

and for internal use only.

118 <*class>
119 %% for internal use
120 \newcommand{\Seriesname}[1]{\def\@Seriesname{#1}}
121 \newcommand{\Hypersubject}[1]{\def\@Hypersubject{#1}}
122 \newcommand{\Hyperauthor}[1]{\def\@Hyperauthor{#1}}
123 \newcommand{\Footername}[1]{\def\@Footername{#1}}
124 \newcommand{\Firstdate}[1]{\def\@Firstdate{#1}}
125 \newcommand{\Seconddate}[1]{\def\@Seconddate{#1}}
126 \newcommand{\Reviewauthor}[1]{\def\@Reviewauthor{#1}}
127 </class>

```

Some defaults for theses commands are specified, which are (hopefully) a useful guidance when using the `jss.cls`.

```

128 <*class>
129 %% defaults
130 \author{Firstname Lastname\Affiliation}
131 \title{Title}
132 \Abstract{---!!!---an abstract is required---!!!---}
133 \Plainauthor{\@author}
134 \Volume{VV}

```

```

135 \Year{YYYY}
136 \Month{MMMMM}
137 \Issue{II}
138 \Submitdate{yyyy-mm-dd}
139 \Acceptdate{yyyy-mm-dd}
140 \Address{
141   Firstname Lastname\\
142   Affiliation\\
143   Address, Country\\
144   E-mail: \email{name@address}\\
145   URL: \url{http://link/to/webpage/}
146 }
147
148 \Reviewer{Firstname Lastname\\Affiliation}
149 \Plainreviewer{Firstname Lastname}
150 \Booktitle{Book Title}
151 \Bookauthor{Book Author}
152 \Publisher{Publisher}
153 \Pubaddress{Publisher's Address}
154 \Pubyear{YYY}
155 \ISBN{x-xxxxx-xxx-x}
156 \Pages{xv + 123}
157 \Price{USD 69.95 (P)}
158 \URL{http://link/to/webpage/}
159 </class>

```

Conditional on the type of document several other defaults and some meta information is stored.

```

160 <*class>
161 \if@article
162   \Seriesname{Issue}
163   \Hypersubject{Journal of Statistical Software}
164   \Plaintitle{\@title}
165   \Shorttttitle{\@title}
166   \Plainkeywords{\@Keywords}
167 \fi
168
169 \if@codesnippet
170   \Seriesname{Code Snippet}
171   \Hypersubject{Journal of Statistical Software -- Code Snippets}
172   \Plaintitle{\@title}
173   \Shorttttitle{\@title}
174   \Plainkeywords{\@Keywords}
175 \fi
176
177 \if@bookreview
178   \Seriesname{Book Review}
179   \Hypersubject{Journal of Statistical Software -- Book Reviews}
180   \Plaintitle{\@Booktitle}
181   \Shorttttitle{\@Booktitle}
182   \Reviewauthor{\@Bookauthor\\
183                 \@Publisher, \@Pubaddress, \@Pubyear.\\
184                 ISBN~\@ISBN. \@Pages~pp. \@Price.\\
185                 \url{\@URL}}
186   \Plainkeywords{}
187   \@reviewtrue
188 \fi
189
190 \if@softwarereview
191   \Seriesname{Software Review}

```

```

192 \Hypersubject{Journal of Statistical Software -- Software Reviews}
193 \Plaintitle{\@Softwaretitle}
194 \Shorttitle{\@Softwaretitle}
195 \Booktitle{\@Softwaretitle}
196 \Reviewauthor{\@Publisher, \@Pubaddress. \@Price.\@
197             \url{\@URL}}
198 \Plainkeywords{}
199 \@reviewtrue
200 \fi
201
202 \if@review
203 \Hyperauthor{\@Plainreviewer}
204 \Keywords{}
205 \Footername{Reviewer}
206 \Firstdate{\textit{Published:} \@Submitdate}
207 \Seconddate{}
208 \else
209 \Hyperauthor{\@Plainauthor}
210 \Keywords{---!!!---at least one keyword is required---!!!---}
211 \Footername{Affiliation}
212 \Firstdate{\textit{Submitted:} \@Submitdate}
213 \Seconddate{\textit{Accepted:} \@Acceptdate}
214 \fi
215 \end{class}

```

For typesetting of code some basic infrastructure along the lines of Sweave is provided. First, the Sweave commands are provided explicitly,

```

216 \begin{class}
217 %% Sweave(-like)
218 \DefineVerbatimEnvironment{Sinput}{Verbatim}{fontshape=s1}
219 \DefineVerbatimEnvironment{Soutput}{Verbatim}{}
220 \DefineVerbatimEnvironment{Scode}{Verbatim}{fontshape=s1}
221 \newenvironment{Schunk}{}{}
222 \end{class}

```

and analogous commands with more neutral names for general pieces of code.

```

223 \begin{class}
224 \DefineVerbatimEnvironment{Code}{Verbatim}{}
225 \DefineVerbatimEnvironment{CodeInput}{Verbatim}{fontshape=s1}
226 \DefineVerbatimEnvironment{CodeOutput}{Verbatim}{}
227 \newenvironment{CodeChunk}{}{}
228 \setkeys{Gin}{width=0.8\textwidth}
229 \end{class}

```

The header for all JSS publications has the logo `jsslogo.jpg` along with the publication information.

```

230 \begin{class}
231 %% new \maketitle
232 \def\@myoddhead{
233   {\color{white} JSS}\@[-1.42cm]
234   \hspace{-2em} \includegraphics[height=23mm,keepaspectratio]{jsslogo} \hfill
235   \parbox[b]{23mm}{118mm}{\hrule height 3pt
236     \center{
237       {\fontfamily{pzc} \fontsize{28}{32} \selectfont Journal of Statistical Software}
238     }
239     \vfill
240     {\it \small \@Month{ } \@Year, Volume~\@Volume, \@Seriesname~\@Issue.%
241       \hfill \href{http://www.jstatsoft.org/}{http://www.jstatsoft.org/}}\@[-0.1cm]
241     \hrule height 3pt}}
242 \end{class}

```

This header is then used in the re-defined `\maketitle`:

```

243 < *class>
244 \if@review
245   \renewcommand{\maketitle}{\@oddhead{\@myoddhead}\[3\baselineskip]
246     {\large
247       \noindent
248       Reviewer: \@Reviewer
249       \vspace{\baselineskip}
250       \hrule
251       \vspace{\baselineskip}
252       \textbf{\@Booktitle}
253       \begin{quotation} \noindent
254       \@Reviewauthor
255       \end{quotation}
256       \vspace{0.7\baselineskip}
257       \hrule
258       \vspace{1.3\baselineskip}
259     }
260
261     \thispagestyle{empty}
262     \markboth{\centerline{\@Shorttitle}}{\centerline{\@Hypersubject}}
263     \pagestyle{myheadings}
264   }
265 \else
266   \def\maketitle{\@oddhead{\@myoddhead} \par
267     \begin{group}
268       \def\thefootnote{\fnsymbol{footnote}}
269       \def\@makefnmark{\hbox to 0pt{$^{\@thefnmark}$}\hss}
270       \long\def\@makefntext##1{\parindent 1em\noindent
271         \hbox to 1.8em{\hss $\m@th ^{\@thefnmark}$}\##1}
272       \@maketitle \@thanks
273     \end{group}
274     \setcounter{footnote}{0}
275     \thispagestyle{empty}
276     \markboth{\centerline{\@Shorttitle}}{\centerline{\@Hypersubject}}
277     \pagestyle{myheadings}
278
279     \let\maketitle\relax \let\@maketitle\relax
280     \gdef\@thanks{}\gdef\@author{}\gdef\@title{}\let\thanks\relax
281   }
282
283   \def\@maketitle{\vbox{\hsize\textwidth \linewidth\hsize \vskip 1in
284     {\centering
285       {\LARGE\bf \@title\par}
286       \vskip 0.2in plus 1fil minus 0.1in
287       {
288         \def\and{\unskip\enspace{\rm and}\enspace}%
289         \def\And{\end{tabular}\hss \egroup \hskip 1in plus 2fil
290           \hbox to 0pt\bgroup\hss \begin{tabular}[t]{c}\large\bf\rule{\z@}{24pt}\ignorespaces}%
291         \def\AND{\end{tabular}\hss\egroup \hfil\hfil\egroup
292           \vskip 0.1in plus 1fil minus 0.05in
293           \hbox to \linewidth\bgroup\rule{\z@}{10pt} \hfil\hfil
294           \hbox to 0pt\bgroup\hss \begin{tabular}[t]{c}\large\bf\rule{\z@}{24pt}\ignorespaces}
295         \hbox to \linewidth\bgroup\rule{\z@}{10pt} \hfil\hfil
296         \hbox to 0pt\bgroup\hss \begin{tabular}[t]{c}\large\bf\rule{\z@}{24pt}\@author
297         \end{tabular}\hss\egroup
298       \hfil\hfil\egroup}
299       \vskip 0.3in minus 0.1in
300       \hrule

```

```

301 \begin{abstract}
302 \@Abstract
303 \end{abstract}}
304 \textit{Keywords}:~\@Keywords.
305 \vskip 0.1in minus 0.05in
306 \hrule
307 \vskip 0.2in minus 0.1in
308 }}
309 \fi
310 </class>

```

The appearance of sections, subsections and subsubsections is controlled by

```

311 <*class>
312 %% sections, subsections, and subsubsections
313 \newlength{\preXLskip}
314 \newlength{\preLskip}
315 \newlength{\preMskip}
316 \newlength{\preSskip}
317 \newlength{\postMskip}
318 \newlength{\postSskip}
319 \setlength{\preXLskip}{1.8\baselineskip plus 0.5ex minus 0ex}
320 \setlength{\preLskip}{1.5\baselineskip plus 0.3ex minus 0ex}
321 \setlength{\preMskip}{1\baselineskip plus 0.2ex minus 0ex}
322 \setlength{\preSskip}{.8\baselineskip plus 0.2ex minus 0ex}
323 \setlength{\postMskip}{.5\baselineskip plus 0ex minus 0.1ex}
324 \setlength{\postSskip}{.3\baselineskip plus 0ex minus 0.1ex}
325
326
327 \newcommand{\jsssec}[2][default]{\vskip \preXLskip%
328 \pdfbookmark[1]{#1}{Section.\thesection.#1}%
329 \refstepcounter{section}%
330 \centerline{\textbf{\Large \thesection. #2}} \nopagebreak
331 \vskip \postMskip \nopagebreak}
332 \newcommand{\jsssecnn}[1]{\vskip \preXLskip%
333 \centerline{\textbf{\Large #1}} \nopagebreak
334 \vskip \postMskip \nopagebreak}
335
336 \newcommand{\jsssubsec}[2][default]{\vskip \preMskip%
337 \pdfbookmark[2]{#1}{Subsection.\thesubsection.#1}%
338 \refstepcounter{subsection}%
339 \textbf{\large \thesubsection. #2} \nopagebreak
340 \vskip \postSskip \nopagebreak}
341 \newcommand{\jsssubsecnn}[1]{\vskip \preMskip%
342 \textbf{\large #1} \nopagebreak
343 \vskip \postSskip \nopagebreak}
344
345 \newcommand{\jsssubsubsec}[2][default]{\vskip \preSskip%
346 \pdfbookmark[3]{#1}{Subsubsection.\thesubsubsection.#1}%
347 \refstepcounter{subsubsection}%
348 {\large \textit{#2}} \nopagebreak
349 \vskip \postSskip \nopagebreak}
350 \newcommand{\jsssubsubsecnn}[1]{\vskip \preSskip%
351 {\textit{\large #1}} \nopagebreak
352 \vskip \postSskip \nopagebreak}
353
354 \newcommand{\jsssimplesec}[2][default]{\vskip \preLskip%
355 %% \pdfbookmark[1]{#1}{Section.\thesection.#1}%
356 \refstepcounter{section}%
357 \textbf{\large #1} \nopagebreak
358 \vskip \postSskip \nopagebreak}

```



```

359 \newcommand{\jsssimplesecnn}[1]{\vskip \preLskip%
360 \textbf{\large #1} \nopagebreak
361 \vskip \postSskip \nopagebreak}
362
363 \if@review
364 \renewcommand{\section}{\secdef \jsssimplesec \jsssimplesecnn}
365 \renewcommand{\subsection}{\secdef \jsssimplesec \jsssimplesecnn}
366 \renewcommand{\subsubsection}{\secdef \jsssimplesec \jsssimplesecnn}
367 \else
368 \renewcommand{\section}{\secdef \jsssec \jsssecnn}
369 \renewcommand{\subsection}{\secdef \jsssubsec \jsssubsecnn}
370 \renewcommand{\subsubsection}{\secdef \jsssubsubsec \jsssubsubsecnn}
371 \fi
372 \end{class}

```

All JSS publications also have a footer with a somewhat extended publication information preceded by the address of the author/reviewer.

```

373 \begin{class}
374 %% footer
375 \newlength{\footerskip}
376 \setlength{\footerskip}{2.5\baselineskip plus 2ex minus 0.5ex}
377
378 \newcommand{\makefooter}{%
379 \vspace{\footerskip}
380
381 \begin{samepage}
382 \textbf{\large \@Footname: \nopagebreak}\hspace{.3\baselineskip} \nopagebreak
383 \@Address \nopagebreak
384 \vfill
385 \hrule \nopagebreak
386 \vspace{.1\baselineskip}
387 {\fontfamily{pzc} \fontsize{13}{15} \selectfont Journal of Statistical Software}
388 \hfill
389 \url{http://www.jstatsoft.org/}\hspace{.3\baselineskip} \nopagebreak
390 published by the American Statistical Association
391 \hfill
392 \url{http://www.amstat.org/}\hspace{.3\baselineskip} \nopagebreak
393 {Volume~\@Volume, \@Seriesname~\@Issue}
394 \hfill
395 \@Firstdate\hspace{.3\baselineskip} \nopagebreak
396 {\@Month{}} \@Year}
397 \hfill
398 \@Seconddate \nopagebreak
399 \vspace{.3\baselineskip}
400 \hrule
401 \end{samepage}
402 }
403 \end{class}

```

The hypersetup uses some modified colors

```

404 \begin{class}
405 %% colors
406 \definecolor{Red}{rgb}{0.7,0,0}
407 \definecolor{Blue}{rgb}{0,0,0.8}
408 \end{class}

```

and is then defined by

```

409 \begin{class}
410 \if@review
411 \hypersetup{%

```

```

412     hyperindex = {true},
413     colorlinks = {true},
414     linktocpage = {true},
415     plainpages = {false},
416     linkcolor = {Blue},
417     citecolor = {Blue},
418     urlcolor = {Red},
419     pdfstartview = {Fit},
420     pdfpagemode = {None},
421     pdfview = {XYZ null null null}
422 }
423 \else
424 \hypersetup{%
425     hyperindex = {true},
426     colorlinks = {true},
427     linktocpage = {true},
428     plainpages = {false},
429     linkcolor = {Blue},
430     citecolor = {Blue},
431     urlcolor = {Red},
432     pdfstartview = {Fit},
433     pdfpagemode = {UseOutlines},
434     pdfview = {XYZ null null null}
435 }
436 \fi
437 \</class>

```

The information for the hyper summary requires some information which has not been processed before the beginning of the document. Therefore, we need a second `\hypersetup`.

```

438 \<class>
439 \AtBeginDocument{
440     \hypersetup{%
441         pdfauthor = {\@Hyperauthor},
442         pdftitle = {\@Plaintitle},
443         pdfsubject = {\@Hypersubject},
444         pdfkeywords = {\@Plainkeywords}
445     }
446 }
447 \</class>

```

We put the header at the beginning of the document and the footer at the end of it.

```

448 \<class>
449 \AtBeginDocument{\maketitle}
450 \AtEndDocument{\makefooter}
451 \</class>

```

Finally, some additional commands are provided for writing about software (code, programming languages, packages),

```

452 \<class>
453 %% commands
454 \makeatletter
455 \newcommand\code{\bgroup\@makeother\_ \@makeother\~ \@makeother\$\@codex}
456 \def\@codex#1{\fontfamily\hyphenchar\font=-1 #1\egroup}
457 \makeatother
458 %%\let\code=\texttt
459 \let\proglang=\textsf
460 \newcommand{\pkg}[1]{\fontseries{b}\selectfont #1}
461 \</class>

```

for specifying e-mail addresses,

```

462 <*class>
463 \newcommand{\email}[1]{\href{mailto:#1}{\normalfont\texttt{#1}}}
464 </class>

digital object identifiers (DOIs),

465 <*class>
466 \newcommand{\doi}[1]{\href{http://dx.doi.org/#1}{\normalfont\texttt{doi:#1}}}
467 </class>

and for mathematical notation.

468 <*class>
469 \newcommand{\E}{\mathsf{E}}
470 \newcommand{\VAR}{\mathsf{VAR}}
471 \newcommand{\COV}{\mathsf{COV}}
472 \newcommand{\Prob}{\mathsf{P}}
473 </class>

```