

1 - run **grep gnulinux /boot/grub/grub.cfg**

```
root@lab1:~# grep gnulinux /boot/grub/grub.cfg
menuentry 'Ubuntu' --class ubuntu --class gnu-linux --class gnu --class os $menuentry_id_option 'gnulinux-simple-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
  submenu 'Advanced options for Ubuntu' $menuentry_id_option 'gnulinux-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
    menuentry 'Ubuntu, with Linux 4.15.0-47-generic' --class ubuntu --class gnu-linux --class gnu --class os
$menuentry_id_option 'gnulinux-4.15.0-47-generic-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
    menuentry 'Ubuntu, with Linux 4.15.0-47-generic (recovery mode)' --class ubuntu --class gnu-linux --class gnu --
class os $menuentry_id_option 'gnulinux-4.15.0-47-generic-recovery-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
    menuentry 'Ubuntu, with Linux 4.15.0-46-generic' --class ubuntu --class gnu-linux --class gnu --class os
$menuentry_id_option 'gnulinux-4.15.0-46-generic-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
    menuentry 'Ubuntu, with Linux 4.15.0-46-generic (recovery mode)' --class ubuntu --class gnu-linux --class gnu --
class os $menuentry_id_option 'gnulinux-4.15.0-46-generic-recovery-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
    menuentry 'Ubuntu, with Linux 4.15.0-42-generic' --class ubuntu --class gnu-linux --class gnu --class os
$menuentry_id_option 'gnulinux-4.15.0-42-generic-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
    menuentry 'Ubuntu, with Linux 4.15.0-42-generic (recovery mode)' --class ubuntu --class gnu-linux --class gnu --
class os $menuentry_id_option 'gnulinux-4.15.0-42-generic-recovery-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
    menuentry 'Ubuntu, with Linux 4.15.0-30-generic' --class ubuntu --class gnu-linux --class gnu --class os
$menuentry_id_option 'gnulinux-4.15.0-30-generic-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
    menuentry 'Ubuntu, with Linux 4.15.0-30-generic (recovery mode)' --class ubuntu --class gnu-linux --class gnu --
class os $menuentry_id_option 'gnulinux-4.15.0-30-generic-recovery-ef5d1337-ed70-436c-a4b2-31580b42e4b8' {
```

Combining both of them (bold, red) into "**gnulinux-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8>gnulinux-4.15.0-30-generic-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8**"

(note the ">" between them !!)

2 - add this to **/etc/default/grub** . We only changing one line, in my example to look like that :

```
GRUB_DEFAULT="gnulinux-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8>gnulinux-4.15.0-30-generic-advanced-ef5d1337-ed70-436c-a4b2-31580b42e4b8"
```

(whole entry must be between "" quotes!)

3 - Next we need to run **update-grub** to recreate config file