Chapter 6

Neighbour embeddings

R. Heller · Date: 2026-07-29 · Last changed: 2026-09-07

Why do t-SNE and UMAP disagree about the same data?

6.1 What this chapter answers

The four methods in this chapter — LLE, Laplacian eigenmaps, t-SNE and UMAP — do not try to recover the unfolding. That sentence has to come before any number, because the rest of the chapter scores them against the unfolding and a reader who meets the scores first will read them as a verdict on the methods rather than on the pairing.

What each of them minimises is a discrepancy between **neighbourhoods**: which points are near which, in the ambient cloud and in the picture. None of them carries a term that asks for a distance to be reproduced. The registry records this as a field rather than as a remark — `consumes = "neighbourhood"` — so a later chapter cannot forget it. `reconstruction_error()` is a Procrustes distance to the chart, and asking these four to be small on it is asking them for something they were never built to deliver.

Then this chapter judges them by it anyway, for two reasons. The reader will: every one of these methods is used in practice as though its output were a map, and a map is a claim about distance. And the benchmark can, which is the rarer thing — the answer key exists in closed form, so the question "how much of the geometry survived?" has an exact answer rather than an argument. What comes out is not that the methods are bad. It is that the setting on which they are most often tuned, and the picture that tuning produces, move in the *opposite* direction to accuracy.

6.2 Setup

```
grid   <- read_run("data/processed/benchmark-grid.rds",
 ↪  "2483a468d82d4d64")
```

Table 6.1: The four registry entries this chapter describes.

label	consumes	stochastic
LLE	neighbourhood	FALSE
Laplacian eigenmaps	neighbourhood	FALSE
t-SNE	neighbourhood	TRUE
UMAP	neighbourhood	TRUE

```
sweeps <- read_run("data/processed/part2-sweeps.rds",
 ↪  "16d43ff4992c0e58")
budget <- read_run("data/processed/seed-budget.rds",
 ↪  "e5f73dce72d53066")

NBR  <- c("lle", "laplacian", "tsne", "umap")
pat  <- miura_ori(nx = 6L, ny = 6L)
cell <- sample_manifold(pat, theta = 0.5, n = N_DEFAULT, seed =
 ↪  BENCH_SEEDS[1])
```

Three committed artefacts. `benchmark-grid.rds` sweeps θ at fixed neighbourhood size; `part2-sweeps.rds` sweeps the neighbourhood size at three fixed θ; `seed-budget.rds` is the measurement standing rule 1's seed floor is checked against. `cell` is one sample, drawn once, used for every figure that shows an embedding rather than a curve.

6.3 Background

```
knitr::kable(
  method_table()[method_table()$chapter == 6L,
                 c("label", "consumes", "stochastic")],
  row.names = FALSE,
  caption = "The four registry entries this chapter describes.")
```

LLE (Roweis and Saul, 2000) writes each point as a weighted combination of its k nearest neighbours and then finds the low-dimensional configuration that keeps those weights. **Laplacian eigenmaps** (Belkin and Niyogi, 2003) takes the bottom eigenvectors of the graph Laplacian of a heat-kernel-weighted neighbourhood graph. Both are spectral, deterministic, and solve a single eigenproblem.

t-SNE (van der Maaten and Hinton, 2008) converts ambient distances into a neighbour-probability distribution, converts embedding distances into a second one with a heavy-tailed kernel, and minimises the Kullback–Leibler divergence between them by gradient descent from a random initialisation. **UMAP** (McInnes et al., 2018) builds a fuzzy simplicial set on the neighbourhood graph and minimises a cross-entropy, also from a random start. Both are stochastic, and the registry refuses to run them unseeded:

```
unseeded <- tryCatch(embed("tsne", cell), error =
 ↪  conditionMessage)
cat(strwrap(unseeded, width = 72), sep = "\n")
```

```
#> tsne is stochastic and was called without a seed. Standing rule 1:
#> every stochastic result in this book is reported across BENCH_SEEDS,
#> and an unseeded fit cannot be one of them.
```

That error is deliberate. Standing rule 1 says every stochastic result in this book is reported across `BENCH_SEEDS`, and an unseeded fit cannot be one of them — it is an anecdote with no way of being labelled as one afterwards. The cheapest place to enforce a reporting rule is at the call that would break it.

> Two neighbourhood parameters, two names, one quantity. t-SNE's is *perplexity*, a smooth measure of the effective number of neighbours; UMAP's is `n_neighbors`. `R/methods.R` maps the registry's `k` onto both, so a sweep over `k` is a sweep over perplexity for one and over `n_neighbors` for the other, and the curves are comparable. A previous version of `embed_tsne()` declared `k` and passed a fixed perplexity — every `k` returned the same embedding, and a flat curve would have been read as insensitivity to neighbourhood size.

6.4 What the methods produce, and what it costs

```
fit <- lapply(NBR, function(m)
  embed(m, cell, k = K_DEFAULT,
        seed = if (isTRUE(METHOD_REGISTRY[[m]]$stochastic))
         ↪  BENCH_SEEDS[1]))
names(fit) <- NBR

Dchart   <- reference_dist(cell, "chart")
cell_err <- vapply(fit, reconstruction_error, numeric(1), truth
 ↪  = cell$truth)
cell_qnx <- vapply(fit, qnx, numeric(1), reference = Dchart, K =
 ↪  K_QNX)
```

Figure 6.1 is one cell of the grid — a Miura at $\theta = 0.5$, 800 points, no noise — seen four ways. LLE returns the chart to within 0.092; UMAP to 0.18; Laplacian eigenmaps to 0.22; t-SNE, at this neighbourhood size, to 0.63, which is most of the way to the score a random configuration earns.

The Q_{NX} column tells a different story about the same four pictures. Scored at $K = 20$ **against the chart**, they run 0.911, 0.757, 0.767 and 0.755. t-SNE, last by Procrustes distance by a factor of 3.5, is *ahead* of UMAP on rank preservation. That is not a contradiction and not a defect in either metric: one reads distances and the other reads rank order, and an embedding that shatters the sheet into islands can keep every local rank while destroying every distance between islands.




Figure 6.1: One folded sample, embedded four ways. Colour is the first chart coordinate and the black paths are level sets of the second, so a faithful embedding shows a smooth colour ramp crossed by non-intersecting paths. The Procrustes error against the chart is printed under each panel. The axes carry no numbers because an embedding is defined only up to a similarity and its units mean nothing.

6.4.1 The deception

The parameter these methods are tuned on is the neighbourhood size, and tuning is done by looking. That is the part exact truth is able to expose.

```
KS       <- c(5L, 12L, 30L, 70L)
tperp    <- lapply(KS, function(kk) embed("tsne", cell, k = kk,
                                          seed = BENCH_SEEDS[1]))
perp_err <- vapply(tperp, reconstruction_error, numeric(1), truth
 ↪  = cell$truth)
perp_qnx <- vapply(tperp, qnx, numeric(1), reference = Dchart, K
 ↪  = K_QNX)
```




Figure 6.2: t-SNE on one sample at four perplexities. Left to right the picture loses every visible feature and gains an order of magnitude in accuracy. Colour is the first chart coordinate; the black paths are level sets of the second, and the axes are unnumbered for the same reason as in the previous figure.

The left-hand panel of Figure 6.2 is the picture practitioners recognise and reward: crisp, well-separated islands, obvious structure, something to point at. It scores 0.88. The right-hand panel is a featureless filled quadrilateral with no structure to point at whatsoever. It scores 0.089, a factor of 9.9 better, and it is featureless because **the answer is a flat rectangular patch**. The truth

here has no clusters in it. Every island in the left-hand panel is an artefact of the setting.

Q_{NX} against the chart moves the same way — 0.727 to 0.875 — so this is not one metric's idiosyncrasy. What disagrees with both is the eye. The tuning advice that circulates for these methods is largely advice about how the picture looks (Wattenberg et al., 2016; Kobak and Berens, 2019), and on this benchmark that advice points away from the truth, monotonically, across the whole swept range.

6.5 Results

```
cl <- grid[grid$noise == "none" & grid$status == "ok" &
           grid$method %in% c(NBR, "isomap"), ]
sp <- do.call(data.frame,
              aggregate(rmse ~ method + theta, cl,
                        function(x) c(lo = min(x), med =
                         ↪  median(x),
                                      hi = max(x))))
names(sp) <- sub("^rmse\\.", "", names(sp))

th_max <- max(THETA_GRID)
degrade <- vapply(c(NBR, "isomap"), function(m) {
  a <- sp[sp$method == m, ]
  a$med[a$theta == th_max] / a$med[a$theta == 0]
}, numeric(1))

widths <- transform(sp, w = hi - lo)
worst  <- widths[widths$method == "tsne", ]
worst  <- worst[which.max(worst$w), ]

out_hi <- aggregate(rmse ~ method,
                    grid[grid$noise == "outlier" & grid$status ==
 ↪  "ok" &
                         grid$theta == th_max, ], median)
out_hi <- setNames(out_hi$rmse, out_hi$method)

out_hi_mid <- aggregate(rmse ~ method,
                        grid[grid$noise == "outlier" &
 ↪  grid$status == "ok" &
                             grid$theta >= 0.5, ], median)
out_hi_mid <- setNames(out_hi_mid$rmse, out_hi_mid$method)

tsn  <- sp[sp$method == "tsne", ]; tsn <- tsn[order(tsn$theta), ]
ump  <- sp[sp$method == "umap", ]; ump <- ump[order(ump$theta), ]
gap  <- abs(tsn$med - ump$med)
over <- pmin(tsn$hi, ump$hi) > pmax(tsn$lo, ump$lo)

jump <- function(noise) {
  a <- aggregate(qnx ~ theta,
```

```
                grid[grid$method == "lle" & grid$noise == noise
↪  &
                     grid$status == "ok", ], median)
  max(diff(a$qnx[order(a$theta)]))
}
lle_jump <- c(none = jump("none"), outlier = jump("outlier"))
```

The prediction, stated before the figure because a flat curve otherwise reads as nothing happening: **these curves should be nearly flat.** Fold angle is a difficulty parameter for a method that consumes distance, because folding contracts ambient distance and leaves the chart alone (Chapter 2). It is a much weaker difficulty parameter for a method that consumes rank order, because within a facet the fold changes no distance at all and across a crease it changes ranks only where two facets pass close. A method that never trusted global structure has less to lose as the global structure degrades.




Figure 6.3: Procrustes error against the chart across the fold sweep, no noise. The band is the full spread across the twenty benchmark seeds and is the result; the solid line is its median, drawn to locate the band rather than to summarise it. The dashed grey line in each panel is Isomap's median, for scale.

Figure 6.3 is the prediction met. From flat sheet to $\theta = 0.95$, Isomap's median error grows by a factor of 7.9; Laplacian eigenmaps' by 1.1, UMAP's by 1.3, t-SNE's by 1.7. Only LLE behaves like a distance method, at 5.3, which is what one would expect of a method whose weights are least-squares reconstructions in the ambient space.

Flatness is not a compliment here. Isomap is better than all four at *every* θ in this regime, including the last one, and it gets there by consuming a geometry the crease pattern supplies exactly. A flat curve at a mediocre level says the error is dominated by something the fold does not touch — the objective mismatch itself — not that the method is robust.

Where the flatness does buy something is off the clean diagonal. Under the outlier noise model at $\theta = 0.95$, the ordering inverts: t-SNE lands at 0.402 and UMAP at 0.407, against 0.608 for Isomap, 0.626 for PCA and 0.888 for LLE. A handful of displaced points lengthens a shortest path through the neighbourhood graph and moves an ambient distance; it changes few ranks. The methods that were never reading distances are the ones that do not notice.

6.5.1 Neighbourhood size, and where Isomap breaks

```
sw <- sweeps[sweeps$status == "ok" & sweeps$method %in% c(NBR,
 ↪  "isomap"), ]
ks <- aggregate(rmse ~ method + k_tck + theta, sw, median)
k_max <- max(ks$k_tck)

best_k <- do.call(rbind, lapply(split(ks, list(ks$method,
 ↪  ks$theta)),
  function(a) data.frame(method = a$method[1], theta =
   ↪  a$theta[1],
                         k_star  = a$k_tck[which.min(a$rmse)],
                         penalty = a$rmse[a$k_tck == k_max] /
                          ↪  min(a$rmse))))
iso_k <- best_k[best_k$method == "isomap", ]
iso_k <- iso_k[order(iso_k$theta), ]
nbr_k <- best_k[best_k$method %in% NBR, ]
```




Figure 6.4: Procrustes error against neighbourhood size, at three fold angles. Each panel has its own vertical scale, because the levels differ by more than an order of magnitude and the shape of each curve is the point. Isomap has an interior optimum that moves to smaller neighbourhoods as the sheet folds; every neighbour method is still improving at the largest size swept.

Figure 6.4 is the sharpest thing in the chapter. Isomap's best neighbourhood size falls from 45 at $\theta = 0.2$, to 20 at 0.5, to 8 at 0.8. That is the short-circuit onset of Chapter 5 seen from the other side: as the sheet closes, the neighbourhood size at which the graph starts bridging between facets comes down, and past it Isomap's error rises. Choosing 70 — an unremarkable choice — costs it a factor of 1.68 over its own optimum at the tightest fold.

Not one of the four neighbour methods has an interior optimum anywhere in this sweep. Their worst penalty for taking the largest neighbourhood swept is 1.02, across all twelve method–angle combinations; for most of them it is exactly one, because the largest neighbourhood *is* the best. They cannot be short-circuited by a neighbourhood that is too large, because they never built a global object out of local ones. This is the genuine win, and it is narrow: it is robustness to a tuning mistake and to contamination, not accuracy.

6.5.2 Do they actually disagree?

The chapter's title asks why t-SNE and UMAP disagree about the same data. On this benchmark the honest answer is that mostly they do not, and what looks like disagreement is one draw from each of two wide distributions.

Their median errors differ by 0.048 across the sweep, against a t-SNE seed band whose median width is 0.72. The two bands overlap at 20 of the 20 fold angles in the grid — all of them. Two practitioners running one t-SNE and one UMAP on the same sample will get pictures that differ, and will usually be looking at within-method seed variation rather than at a difference between the methods. Where the two do separate is not in the median but in the spread: UMAP's band is 4.9 times narrower than t-SNE's, so a UMAP run is a much better estimate of what UMAP does than a t-SNE run is of what t-SNE does.

6.6 Diagnostics

6.6.1 Two conventions, and which claim needs which

Every claim above about recovery is made against the **chart** — the answer key — using either the Procrustes error or Q_{NX} at $K = 20$. The grid also carries trustworthiness, continuity and k-NN preservation, and those are scored at $k = 10$ against **ambient** distance, which is a different question: whether the embedding preserved the neighbourhoods a method could actually see. Both are defensible and they are not interchangeable. In `part2-sweeps.rds` the ambient-referenced trio is scored at the *swept* k, so its rows are not comparable with each other; Q_{NX} stays pinned at 20 against the chart and is. Every number in this chapter's figures is one of the two chart-referenced ones.

```
Kgrid <- unique(round(exp(seq(log(2), log(400), length.out =
 ↪  18L))))
ref   <- c(fit, list(pca    = embed("pca", cell),
                     isomap = embed("isomap", cell, k =
                      ↪  K_DEFAULT)))
rx <- do.call(rbind, lapply(names(ref), function(m)
  data.frame(method = m, K = Kgrid, rnx = rnx(ref[[m]], Dchart, K
   ↪  = Kgrid))))

margin <- min(vapply(Kgrid, function(kk) {
  a <- rx[rx$K == kk, ]
  a$rnx[a$method == "pca"] - max(a$rnx[a$method %in% NBR])
}, numeric(1)))
ts <- rx[rx$method == "tsne", ]
```

Figure 6.5 puts the global loss on one axis. $R_{NX}(K)$ is Q_{NX} corrected for the K/n baseline, so it is comparable across neighbourhood sizes (Lee and Verleysen, 2009); small K is local structure and large K is global. PCA — a shadow, and the weakest thing in Part II by construction — sits above all four neighbour methods at **every** K from 2 to 400, by at least 0.032. There is no neighbourhood size at which any of these four is the better description of the chart's rank order.




Figure 6.5: Rank preservation against the chart across every neighbourhood size, on one sample. The two methods that consume distance or geodesics are drawn dashed. No neighbour method reaches PCA at any neighbourhood size, and t-SNE is the only curve that falls as the neighbourhood grows.

Isomap is the exception to note rather than to bury: at the smallest neighbourhood it sits below LLE, at 0.858 against 0.883, and only overtakes it a few neighbours later. A geodesic method has no special claim on the very local rank order, which is exactly the part LLE is built out of.

t-SNE is the only curve that falls: 0.848 at $K = 2$, 0.685 at $K = 400$. It buys the local structure it is best at by spending the global structure, which is the trade its critics describe and its defenders accept (Chari and Pachter, 2023; Lause et al., 2024). Here the trade is priced exactly, because the thing being spent is known.

6.6.2 What twenty seeds is, and what it is not

```
bud <- budget$budget[budget$budget$method %in% NBR, ]
bud <- bud[order(-bud$seeds_needed), c("method", "stochastic",
 ↪  "sd",
                                       "seeds_needed")]
knitr::kable(bud, row.names = FALSE, digits = 4,
             col.names = c("method", "stochastic", "worst-cell
              ↪  sd",
                           "seeds needed"),
             caption = "Seeds required to resolve a reportable
              ↪  difference, from
              ↪  data/processed/seed-budget.rds.")
```

```
declined  <- grid[grid$method == "laplacian" & grid$status ==
 ↪  "declined", ]
dec       <- table(declined$noise)
dec_share <- nrow(declined) / sum(grid$method == "laplacian")
```

Table 6.2: Seeds required to resolve a reportable difference, from data/processed/seed-budget.rds.

method	stochastic	worst-cell sd	seeds needed
tsne	TRUE	0.2873	3241
lle	FALSE	0.2034	1624
laplacian	FALSE	0.0446	79
umap	TRUE	0.0438	76

Standing rule 1's floor is twenty seeds. `seed-budget.rds` measures what that floor is worth: for each method it draws 40 samples per cell at three fold angles and two noise models, takes the within-cell standard deviation of excess error over the floor, and inverts the two-sample expression for the seeds needed to resolve a difference of 0.02 at 80% power and the 5% level.

None of the four passes. t-SNE would need 3241 seeds, LLE 1624, Laplacian eigenmaps 79 and UMAP 76. The floor is between one and two orders of magnitude short for the first two. That is why the bands in Figure 6.3 are the result and no mean line is drawn anywhere in this chapter: at $\theta = 0.4$ t-SNE's twenty seeds span 0.098 to 0.875, a range of 0.777 on a metric bounded by one. A mean of that is a number with no cell in it.

Note which methods are on that list. LLE and Laplacian eigenmaps are deterministic: the same input gives the same output every time. What varies across seeds for them is the *sample*, redrawn from the same surface, and LLE's sensitivity to it is larger than either stochastic method's sensitivity to its own initialisation. "Seed variance" is two different quantities wearing one name, and only for t-SNE and UMAP does it mean what the phrase suggests.

6.7 Where it fails

6.7.1 `preserve.seed`, and a correction to the correction

```
small <- sample_manifold(pat, theta = 0.5, n = 200L, seed =
 ↪  BENCH_SEEDS[1])
runs  <- function(preserve) {
  set.seed(1L)
  vapply(BENCH_SEEDS, function(s)
    umap::umap(small$X, n_neighbors = K_DEFAULT, n_epochs = 60L,
               preserve.seed = preserve)$layout[1L, 1L],
                ↪  numeric(1))
}
has_arg  <- "preserve.seed" %in% names(formals(umap::umap))
default  <- formals(umap::umap)$preserve.seed
distinct <- c(kept = length(unique(runs(TRUE))),
              released = length(unique(runs(FALSE))))
```

The natural idiom for standing rule 1 is to seed once and loop. With `umap::umap()` that idiom silently collapses the whole loop into one run. The

pinned version takes a `preserve.seed` argument — present: TRUE, default: TRUE — and that default is the mechanism. Twenty calls with the argument at its default return 1 distinct answer; the same twenty with it switched off return 20. The function restores R's random state on exit, so consecutive calls all start from the same place, and the reported seed-to-seed spread of every UMAP result in this book would have been exactly zero — a violation of standing rule 1 that produces no warning, no error and numbers that look fine.

> The provenance of this finding needs stating, because the repository twice recorded it wrongly and in opposite directions. `PLAN.md` S1-6 predicted the defect and named `preserve.seed` as its cause. `R/methods.R` and `tests/testthat/test-methods.R` then recorded that the prediction had named the wrong mechanism, on the ground that the pinned version has no such argument, and asserted the behaviour instead. The prediction was right: the argument is present, it defaults to `TRUE`, and switching it off restores the variation — all three checked in the chunk above rather than asserted here. The test is still a good test, because it pins the behaviour rather than an explanation of it; its comment is wrong and the registry's is too.

The registry uses `uwot::umap()` instead, which consumes R's random stream, so a caller who forgets to seed gets visibly different answers rather than twenty identical ones. The choice of implementation moves the answer, and it moves it by changing what a seed means rather than by changing an algorithm.

6.7.2 Laplacian eigenmaps declines a whole noise model

`embed_laplacian()` returned nothing on 400 of the 1200 cells it was offered, which is 33% of them, and every one of those cells carries the outlier noise model: outlier and nothing else. The heat kernel underflows on a spread sample, rows of the weight matrix go to zero, the graph disconnects at working precision, and the second eigenvector is then read out of a degenerate space where every direction is equally valid. The helper detects that and refuses. A refusal is a result and the grid records it as one; what it is not is a score, and Chapter 10 must not average over the cells that are missing.

6.7.3 LLE under outliers stops being a curve

LLE never declines a cell, and that is worse than declining one. Under the outlier model its median error over the upper half of the fold sweep is 0.832, second only to the diffusion map, and its Q_{NX} against the chart stops behaving like a function of θ: between adjacent grid points it steps *upward* by as much as 0.18, against 0.003 on the clean sweep. Standing rule 2 asks for a curve; what this cell array produces is a scatter that happens to be indexed by θ. The reconstruction weights are least-squares fits in the ambient space, so one displaced neighbour rewrites a row of the weight matrix, and the whole embedding is a null space of that matrix. Nothing in the method notices.

6.7.4 What this chapter does not establish

One pattern family, one tessellation size, one ambient dimension, and 800 points. The neighbourhood sweep runs to 70, which is 9% of the sample — the curves are still falling there and this chapter cannot say where they stop. Nothing here measures whether these methods are good at the task they were built for, which is a question about cluster recovery that a folded sheet with no clusters cannot ask (Espadoto et al., 2021).

6.8 Reproduce this

- `scripts/run-benchmark-grid.R` → `data/processed/benchmark-grid.rds`, the θ sweep at fixed k.
- `scripts/run-part2-sweeps.R` → `data/processed/part2-sweeps.rds`, the k sweep at three fixed θ.
- `scripts/measure-seed-budget.R` → `data/processed/seed-budget.rds`.
- `tests/testthat/test-methods.R` asserts the unseeded refusal, the seed-to-seed variation of `Rtsne` and `uwot`, and the `umap::umap` behaviour above.

Each script's header declares the artefact it writes, and `scripts/check-artefact-producers.R` maps every artefact the book reads back to one.

6.9 Further reading

Roweis and Saul (Roweis and Saul, 2000) and Belkin and Niyogi (Belkin and Niyogi, 2003) are the primary sources for the two spectral methods, and both are usually read beside Isomap (Tenenbaum et al., 2000), which Chapter 5 covers and which is the one method here that consumes a geometry a crease pattern supplies exactly. Van der Maaten and Hinton (van der Maaten and Hinton, 2008) and McInnes, Healy and Melville (McInnes et al., 2018) are the primary sources for the other two.

On what the pictures are worth, Wattenberg, Viégas and Johnson (Wattenberg et al., 2016) is the clearest demonstration that the perplexity setting manufactures structure; Kobak and Berens (Kobak and Berens, 2019) is the practical counterpart. Kobak and Linderman (Kobak and Linderman, 2021) show that the global structure both methods are accused of losing is substantially a matter of initialisation rather than of the objective. Chari and Pachter (Chari and Pachter, 2023) press the case against reading these embeddings as maps and Lause, Berens and Kobak (Lause et al., 2024) answer it. For the rank-based criteria used here, Lee and Verleysen (Lee and Verleysen, 2009) is the reference, and Machado, Behrisch and Telea (Machado et al., 2025) make the point this chapter's two-metric disagreement illustrates: a projection quality metric is necessary and not sufficient.