

Batch Correction with ComBat

2026-04-17

Introduction

Batch effects — systematic technical variation introduced by different sequencing dates, instruments, library-prep operators, or reagent lots — bias gene-expression measurements in ways that can swamp biological signal if not addressed. ComBat is the most widely used batch-correction method, applying an empirical-Bayes adjustment to centre and scale each gene's distribution per batch. It is appropriate when batches are known and condition is not confounded with batch; the alternative — including batch as a covariate in differential-expression models — preserves more information when downstream analysis explicitly models batch.

Prerequisites

A working understanding of normalisation, the distinction between technical and biological variation, and basic empirical-Bayes shrinkage.

Theory

ComBat models each gene's expression as

$$Y_{ij} = \alpha_j + X\beta_j + \gamma_{bj} + \delta_{bj}\varepsilon_{ij},$$

with sample i , gene j , batch b , additive batch effect γ_{bj} , and multiplicative batch effect δ_{bj} . The empirical-Bayes step shrinks per-gene batch-effect estimates toward a common distribution across genes, stabilising estimation when batches contain few samples. The output is an expression matrix with batch effects removed but biological condition (specified via `mod`) preserved.

ComBat-Seq (in `sva`) is the count-data analogue, designed for raw RNA-seq counts before normalisation; standard ComBat assumes log-normalised input.

Assumptions

Batches are known; biological condition is not perfectly confounded with batch (otherwise correction is impossible); sufficient samples per batch for stable empirical-Bayes shrinkage.

R Implementation

```
library(sva)

set.seed(2026)
# Simulated: 10 genes x 20 samples, 2 batches, 2 conditions
expr <- matrix(rnorm(10 * 20), 10, 20)
batch <- c(rep(1, 10), rep(2, 10))
condition <- rep(c("A", "B"), 10)

# Add batch effect
```

```

expr[, batch == 2] <- expr[, batch == 2] + 2

mod <- model.matrix(~ condition)
expr_corrected <- ComBat(dat = expr, batch = batch, mod = mod)

# PCA before/after
# prcomp(t(expr))$x[, 1:2]; prcomp(t(expr_corrected))$x[, 1:2]

```

Output & Results

`ComBat()` returns the batch-corrected expression matrix; `ComBat_seq()` returns batch-corrected counts. PCA before and after correction is the standard QC check: condition-driven clustering should remain or strengthen, while batch-driven separation should diminish substantially.

Interpretation

A reporting sentence: “ComBat correction with condition included as a covariate (`mod = model.matrix(~ condition)`) reduced batch variance from 35 % of PC1 to under 5 %, while preserving the condition-driven separation that explains 28 % of the remaining variance. The corrected matrix was used for downstream visualisation and clustering.” Always report which covariates were preserved during correction.

Practical Tips

- Do *not* run `ComBat` when condition is fully confounded with batch — the correction will remove the biological signal along with the batch effect.
- Use `ComBat_seq()` for raw RNA-seq counts; standard `ComBat` is for log-normalised data.
- For differential-expression analysis, consider including batch as a covariate in the DE design (`design = ~ batch + condition` in `DESeq2`/`edgeR`/`limma`) rather than running `ComBat` first; the model-based approach is generally preferred.
- Always report batch-correction methods explicitly in publications; reviewers expect clarity about how batch was handled.
- Alternative methods include `RUVSeq` (latent factor extraction), `svaseq` (surrogate variable analysis), and `limma::removeBatchEffect()` (simple linear adjustment); the choice depends on whether batches are known.
- Pair correction with PCA before and after as a routine QC step; visible improvement is the validation for whether the correction worked.

R Packages Used

`sva::ComBat()` and `ComBat_seq()` for the canonical empirical-Bayes batch correction; `RUVSeq` for unsupervised factor-based correction; `limma::removeBatchEffect()` for simple linear batch removal; `harmony` for batch correction in single-cell RNA-seq workflows.

For Reviewers

What to look for in a paper using this method.

- **Common misapplications.**
- **Diagnostics that should be reported but often aren’t.**
- **Red flags in tables and figures.**
- **What to verify.**
- **What an adequate Methods paragraph must contain.**

See also — labs in this chapter

- RNA-seq with DESeq2 / edgeR
- Enrichment analysis (GSEA / ORA)
- scRNA-seq with Seurat