

Chapter 20

CONSORT — randomised trials

CONSORT — *Consolidated Standards of Reporting Trials* — covers randomised controlled trials. The 25-item checklist and flow diagram are at <https://www.consort-statement.org/>. The templates below cover the analytic methods most often used for primary and secondary endpoints in a trial.

This page contains **141 method-specific templates**. Each is a skeleton with placeholders in italics; the prose is written so you can paste it into a manuscript and replace only the bracketed values.

20.0.1 2^k Factorial Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **2^k Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

2^k Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → factorial-2k — For Reviewers

20.0.2 3^k Factorial Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **3^k Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

3^k Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → factorial-3k — For Reviewers

20.0.3 Adaptive Trial Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Adaptive Trial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Adaptive Trial Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → adaptive-design — For Reviewers

20.0.4 Alpha-Spending Functions

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Alpha-Spending Functions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Alpha-Spending Functions yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → alpha-spending — For Reviewers

20.0.5 Anderson-Darling Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Anderson-Darling Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Anderson-Darling Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → anderson-darling-test — For Reviewers

20.0.6 Balanced Incomplete Block Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Balanced Incomplete Block Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Balanced Incomplete Block Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → balanced-incomplete-block — For Reviewers

20.0.7 Bartlett's Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Bartlett's Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Bartlett's Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `bartlett-test` — For Reviewers

20.0.8 Baseline Adjustment with ANCOVA

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Baseline Adjustment with ANCOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Baseline Adjustment with ANCOVA yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `baseline-adjustment-ancova` — For Reviewers

20.0.9 Benjamini-Hochberg FDR

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Benjamini-Hochberg FDR** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Benjamini-Hochberg FDR yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `benjamini-hochberg-fdr` — For Reviewers

20.0.10 Benjamini-Yekutieli FDR

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Benjamini-Yekutieli FDR** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Benjamini-Yekutieli FDR yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → benjamini-yekutieli — For Reviewers

20.0.11 Bland-Altman Limits of Agreement

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Bland-Altman Limits of Agreement** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Bland-Altman Limits of Agreement yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → bland-altman-analysis — For Reviewers

20.0.12 Blinding Procedures

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Blinding Procedures** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Blinding Procedures yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → blinding-procedures — For Reviewers

20.0.13 Block Randomisation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Block Randomisation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Block Randomisation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → block-randomization — For Reviewers

20.0.14 Bonferroni Correction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Bonferroni Correction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Bonferroni Correction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → bonferroni-correction — For Reviewers

20.0.15 Bootstrap Confidence Intervals

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Bootstrap Confidence Intervals** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*.

Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Bootstrap Confidence Intervals yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → bootstrap-confidence-intervals
— For Reviewers

20.0.16 Box-Behnken Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Box-Behnken Designs** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Box-Behnken Designs yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → box-behnken-design — For Reviewers

20.0.17 Central Composite Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Central Composite Designs** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Central Composite Designs yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → central-composite-design —
For Reviewers

20.0.18 Chi-Squared Goodness-of-Fit Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Chi-Squared Goodness-of-Fit Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Chi-Squared Goodness-of-Fit Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → chi-squared-goodness-of-fit
— For Reviewers

20.0.19 Chi-Squared Test of Independence

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Chi-Squared Test of Independence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Chi-Squared Test of Independence yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → chi-squared-independence —
For Reviewers

20.0.20 Clinical Equivalence Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Clinical Equivalence Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Clinical Equivalence Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → equivalence-clinical — For Reviewers

20.0.21 Cluster-Randomised Trials**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Cluster-Randomised Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cluster-Randomised Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cluster-rct — For Reviewers

20.0.22 Cochran-Mantel-Haenszel Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Cochran-Mantel-Haenszel Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cochran-Mantel-Haenszel Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cochrane-mantel-haenszel — For Reviewers

20.0.23 Cohen's Kappa**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Cohen’s Kappa** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cohen’s Kappa yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cohens-kappa — For Reviewers

20.0.24 Completely Randomised Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Completely Randomised Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Completely Randomised Design yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → completely-randomized-design — For Reviewers

20.0.25 Conditional Power

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Conditional Power** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Conditional Power yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → conditional-power — For Reviewers

20.0.26 Constrained Mixture Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Constrained Mixture Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Constrained Mixture Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → constrained-mixture — For Reviewers

20.0.27 Crossover Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Crossover Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Crossover Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → crossover-designs — For Reviewers

20.0.28 Crossover RCT Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Crossover RCT Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Crossover RCT Design yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → rct-design-crossover — For Reviewers

20.0.29 Cutpoint Selection**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Cutpoint Selection** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cutpoint Selection yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cutpoint-selection — For Reviewers

20.0.30 Desirability Functions**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Desirability Functions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Desirability Functions yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → desirability-function — For Reviewers

20.0.31 Diagnostic Test Accuracy**Methods paragraph (copy-paste, fill in italics):**

[*N*=] participants/observations were analysed using **Diagnostic Test Accuracy** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Diagnostic Test Accuracy yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → diagnostic-accuracy — For Reviewers

20.0.32 Effect Size: Cohen's d

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Effect Size: Cohen's d** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Effect Size: Cohen's d yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → effect-size-cohens-d — For Reviewers

20.0.33 Effect Size: Cohen's h

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Effect Size: Cohen's h** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Effect Size: Cohen's h yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → effect-size-cohens-h — For Reviewers

20.0.34 Effect Size: Eta-Squared

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Effect Size: Eta-Squared** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Effect Size: Eta-Squared yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → effect-size-eta-squared — For Reviewers

20.0.35 Effect Sizes: Overview

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Effect Sizes: Overview** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Effect Sizes: Overview yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → effect-sizes-overview — For Reviewers

20.0.36 Equivalence Testing with TOST

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Equivalence Testing with TOST** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Equivalence Testing with TOST yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → equivalence-tost — For Reviewers

20.0.37 Factorial Trials**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Factorial Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Factorial Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → factorial-trial — For Reviewers

20.0.38 Fisher's Exact Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Fisher's Exact Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Fisher's Exact Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → fisher-exact-test — For Reviewers

20.0.39 Fractional Factorial Designs**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Fractional Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Fractional Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → fractional-factorial-design
— For Reviewers

20.0.40 Friedman Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Friedman Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Friedman Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → friedman-test — For Reviewers

20.0.41 Graeco-Latin Square Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Graeco-Latin Square Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Graeco-Latin Square Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `graeco-latin-square` — For Reviewers

20.0.42 Holm’s Step-Down Correction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Holm’s Step-Down Correction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Holm’s Step-Down Correction yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `holm-correction` — For Reviewers

20.0.43 Interim Analyses and Group Sequential Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Interim Analyses and Group Sequential Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Interim Analyses and Group Sequential Designs yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `interim-analysis-group-sequential` — For Reviewers

20.0.44 Intraclass Correlation Coefficient (ICC)

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Intraclass Correlation Coefficient (ICC)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Intraclass Correlation Coefficient (ICC) yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `icc-continuous-agreement` — For Reviewers

20.0.45 ITT vs Per-Protocol Analysis**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **ITT vs Per-Protocol Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

ITT vs Per-Protocol Analysis yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `itt-vs-pp-analysis` — For Reviewers

20.0.46 Kendall's Tau**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Kendall's Tau** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Kendall's Tau yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `kendall-tau` — For Reviewers

20.0.47 Kolmogorov-Smirnov Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Kolmogorov-Smirnov Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with*

95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Kolmogorov-Smirnov Test yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → kolmogorov-smirnov-test — For Reviewers

20.0.48 Kruskal-Wallis Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Kruskal-Wallis Test** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Kruskal-Wallis Test yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → kruskal-wallis — For Reviewers

20.0.49 Latin Square Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Latin Square Designs** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Latin Square Designs yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → latin-square — For Reviewers

20.0.50 Levene's Test of Variances

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Levene’s Test of Variances** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Levene’s Test of Variances yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `levене-test` — For Reviewers

20.0.51 Likelihood Ratios

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Likelihood Ratios** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Likelihood Ratios yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `likelihood-ratios` — For Reviewers

20.0.52 Mann-Whitney U Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Mann-Whitney U Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Mann-Whitney U Test yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `mann-whitney-u` — For Reviewers

20.0.53 McNemar's Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **McNemar's Test** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

McNemar's Test yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → mcnemar-test — For Reviewers

20.0.54 Method of Steepest Ascent

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Method of Steepest Ascent** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Method of Steepest Ascent yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → steepest-ascent — For Reviewers

20.0.55 Minimisation Algorithm

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Minimisation Algorithm** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Minimisation Algorithm yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → minimization-algorithm — For Reviewers

20.0.56 Minimum Detectable Effect

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Minimum Detectable Effect** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Minimum Detectable Effect yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → minimum-detectable-effect — For Reviewers

20.0.57 Missing Data in RCTs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Missing Data in RCTs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Missing Data in RCTs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → missing-data-rct — For Reviewers

20.0.58 Mixed ANOVA

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Mixed ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Mixed ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → mixed-anova — For Reviewers

20.0.59 Multiple Comparisons: Overview**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Multiple Comparisons: Overview** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multiple Comparisons: Overview yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multiple-comparisons-overview — For Reviewers

20.0.60 Multiple Imputation**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Multiple Imputation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multiple Imputation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multiple-imputation — For Reviewers

20.0.61 Non-Inferiority Margin Selection**Methods paragraph (copy-paste, fill in italics):**

[*N*=] participants/observations were analysed using **Non-Inferiority Margin Selection** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Non-Inferiority Margin Selection yielded [*estimate*] (95% CI [*lower*, *upper*], $p = [\textit{value}]$). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → non-inferiority-margin — For Reviewers

20.0.62 Null and Alternative Hypotheses

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Null and Alternative Hypotheses** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Null and Alternative Hypotheses yielded [*estimate*] (95% CI [*lower*, *upper*], $p = [\textit{value}]$). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → null-alternative-hypotheses — For Reviewers

20.0.63 O’Brien-Fleming Boundary

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **O’Brien-Fleming Boundary** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

O'Brien-Fleming Boundary yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → obrien-fleming-boundary — For Reviewers

20.0.64 One-Proportion Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **One-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

One-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → one-proportion-test — For Reviewers

20.0.65 One-Sample t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **One-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

One-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → one-sample-t-test — For Reviewers

20.0.66 One-Sample z-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **One-Sample z-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

One-Sample z-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → one-sample-z-test — For Reviewers

20.0.67 One-Way ANOVA

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **One-Way ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

One-Way ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → one-way-anova — For Reviewers

20.0.68 Optimal Designs: D, A, I

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Optimal Designs: D, A, I** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Optimal Designs: D, A, I yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → optimal-design-d-a-i — For Reviewers

20.0.69 Orthogonal Arrays

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Orthogonal Arrays** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Orthogonal Arrays yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → orthogonal-arrays — For Reviewers

20.0.70 P-Values Explained

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **P-Values Explained** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

P-Values Explained yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → p-values-explained — For Reviewers

20.0.71 Paired t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Paired t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Paired t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `paired-t-test` — For Reviewers

20.0.72 Parallel-Group RCT Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Parallel-Group RCT Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Parallel-Group RCT Design yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `rct-design-parallel` — For Reviewers

20.0.73 Pearson Correlation Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Pearson Correlation Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Pearson Correlation Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `pearson-correlation-test` — For Reviewers

20.0.74 Permutation Tests

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Permutation Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Permutation Tests yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → permutation-tests — For Reviewers

20.0.75 Plackett-Burman Designs**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Plackett-Burman Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Plackett-Burman Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → plackett-burman — For Reviewers

20.0.76 Pocock Boundary**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Pocock Boundary** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Pocock Boundary yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → pocock-boundary — For Reviewers

20.0.77 Post-Hoc Power: A Controversy**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Post-Hoc Power: A Controversy** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Post-Hoc Power: A Controversy yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → post-hoc-power-controversy — For Reviewers

20.0.78 Post-Hoc Tests with Tukey HSD

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Post-Hoc Tests with Tukey HSD** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Post-Hoc Tests with Tukey HSD yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → post-hoc-tests-tukey — For Reviewers

20.0.79 Power Analysis for DOE

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power Analysis for DOE** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power Analysis for DOE yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-in-doe — For Reviewers

20.0.80 Power Analysis: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power Analysis: Introduction** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power Analysis: Introduction yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-analysis-introduction — For Reviewers

20.0.81 Power for Agreement (Kappa)

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Agreement (Kappa)** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power for Agreement (Kappa) yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-agreement-kappa — For Reviewers

20.0.82 Power for Bland-Altman Studies

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Bland-Altman Studies** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power for Bland-Altman Studies yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-bland-altman — For Reviewers

20.0.83 Power for Chi-Squared Tests**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Power for Chi-Squared Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Chi-Squared Tests yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-chi-squared — For Reviewers

20.0.84 Power for Cluster-RCT**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Power for Cluster-RCT** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Cluster-RCT yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-cluster-rct — For Reviewers

20.0.85 Power for Correlation Tests

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Correlation Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Correlation Tests yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-correlation — For Reviewers

20.0.86 Power for Cox Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Cox Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Cox Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-cox-regression — For Reviewers

20.0.87 Power for Crossover Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Crossover Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Crossover Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-crossover — For Reviewers

20.0.88 Power for Diagnostic Accuracy

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Diagnostic Accuracy** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Diagnostic Accuracy yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-diagnostic-accuracy — For Reviewers

20.0.89 Power for Equivalence (TOST)

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Equivalence (TOST)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Equivalence (TOST) yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-equivalence-tost — For Reviewers

20.0.90 Power for ICC

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for ICC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were

checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for ICC yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-icc — For Reviewers

20.0.91 Power for Linear Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-linear-regression — For Reviewers

20.0.92 Power for Logistic Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-logistic-regression — For Reviewers

20.0.93 Power for McNemar's Test

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Power for McNemar’s Test** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Power for McNemar’s Test yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → power-mcnemar — For Reviewers

20.0.94 Power for Non-Inferiority Trials

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Power for Non-Inferiority Trials** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Power for Non-Inferiority Trials yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → power-non-inferiority — For Reviewers

20.0.95 Power for One-Proportion Test

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Power for One-Proportion Test** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Power for One-Proportion Test yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → power-one-proportion — For Reviewers

20.0.96 Power for One-Sample t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for One-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for One-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-one-sample-t — For Reviewers

20.0.97 Power for One-Way ANOVA

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for One-Way ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for One-Way ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-anova — For Reviewers

20.0.98 Power for Paired t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Paired t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*.

Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Paired t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-paired-t — For Reviewers

20.0.99 Power for Repeated-Measures ANOVA

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Repeated-Measures ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Repeated-Measures ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-repeated-measures — For Reviewers

20.0.100 Power for Stepped-Wedge Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Stepped-Wedge Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Stepped-Wedge Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-stepped-wedge — For Reviewers

20.0.101 Power for the Log-Rank Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for the Log-Rank Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for the Log-Rank Test yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-logrank-test — For Reviewers

20.0.102 Power for Two-Proportion Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Two-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Two-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-two-proportions — For Reviewers

20.0.103 Predictive Values and Prevalence

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Predictive Values and Prevalence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Predictive Values and Prevalence yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → predictive-values-prevalence
— For Reviewers

20.0.104 Principles of Blocking

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Principles of Blocking** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Principles of Blocking yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → blocking-principles — For Reviewers

20.0.105 Randomisation in Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Randomisation in Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Randomisation in Design yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → randomization-in-design — For Reviewers

20.0.106 Randomisation Methods

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Randomisation Methods** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Randomisation Methods yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → randomization-methods — For Reviewers

20.0.107 Randomised Complete Block Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Randomised Complete Block Design** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Randomised Complete Block Design yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → randomised-complete-block — For Reviewers

20.0.108 Reliability and Cronbach's Alpha

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Reliability and Cronbach's Alpha** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Reliability and Cronbach's Alpha yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → reliability-cronbach-alpha — For Reviewers

20.0.109 Repeated-Measures ANOVA

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Repeated-Measures ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Repeated-Measures ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → repeated-measures-anova — For Reviewers

20.0.110 Repeated-Measures Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Repeated-Measures Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Repeated-Measures Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → repeated-measures-design — For Reviewers

20.0.111 Resolution and Aliasing

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Resolution and Aliasing** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size*

with 95% confidence interval reported as the primary outcome].
Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Resolution and Aliasing yielded [estimate] (95% CI [lower, upper],
p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → resolution-aliasing — For Reviewers

20.0.112 Response Surface Methodology

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Response Surface Methodology** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Response Surface Methodology yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → response-surface-methodology — For Reviewers

20.0.113 Robust Parameter Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Robust Parameter Design** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Robust Parameter Design yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → robust-parameter-design — For Reviewers

20.0.114 ROC Analysis

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **ROC Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

ROC Analysis yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → roc-analysis — For Reviewers

20.0.115 Sample Size for a Two-Sample t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Sample Size for a Two-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Sample Size for a Two-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-two-sample-t — For Reviewers

20.0.116 Sample Size Re-Estimation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Sample Size Re-Estimation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Sample Size Re-Estimation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → sample-size-reestimation —
For Reviewers

20.0.117 Sample Size Sensitivity Analysis

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Sample Size Sensitivity Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Sample Size Sensitivity Analysis yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → sensitivity-analysis-sample-size —
For Reviewers

20.0.118 Sensitivity Analyses in Clinical Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Sensitivity Analyses in Clinical Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Sensitivity Analyses in Clinical Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → sensitivity-analysis-clinical —
For Reviewers

20.0.119 Shapiro-Wilk Normality Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Shapiro-Wilk Normality Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with*

95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Shapiro-Wilk Normality Test yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → shapiro-wilk-test — For Reviewers

20.0.120 Signal-to-Noise Ratios

Methods paragraph (copy-paste, fill in italics):

[$N=$] participants/observations were analysed using **Signal-to-Noise Ratios** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Signal-to-Noise Ratios yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → signal-to-noise-ratio — For Reviewers

20.0.121 Simplex Centroid Designs

Methods paragraph (copy-paste, fill in italics):

[$N=$] participants/observations were analysed using **Simplex Centroid Designs** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Simplex Centroid Designs yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → mixture-centroid — For Reviewers

20.0.122 Simplex Lattice Mixture Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Simplex Lattice Mixture Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Simplex Lattice Mixture Designs yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → mixture-designs-simplex — For Reviewers

20.0.123 Spearman Rank Correlation Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Spearman Rank Correlation Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Spearman Rank Correlation Test yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → spearman-correlation-test — For Reviewers

20.0.124 Split-Plot Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Split-Plot Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Split-Plot Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `split-plot-design` — For Reviewers

20.0.125 Stepped-Wedge Trial

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stepped-Wedge Trial** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stepped-Wedge Trial yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `stepped-wedge-trial` — For Reviewers

20.0.126 Stratified Randomisation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stratified Randomisation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stratified Randomisation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `stratified-randomization` — For Reviewers

20.0.127 Strip-Plot Designs

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Strip-Plot Designs** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Strip-Plot Designs yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → strip-plot-design — For Reviewers

20.0.128 Subgroup Analyses

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Subgroup Analyses** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Subgroup Analyses yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → subgroup-analysis — For Reviewers

20.0.129 Subgroup Forest Plots

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Subgroup Forest Plots** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Subgroup Forest Plots yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → forest-plot-subgroup — For Reviewers

20.0.130 Taguchi Methods

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Taguchi Methods** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Taguchi Methods yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → taguchi-methods — For Reviewers

20.0.131 The Bootstrap: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Bootstrap: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Bootstrap: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → bootstrap-introduction — For Reviewers

20.0.132 The Jackknife

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Jackknife** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Jackknife yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$).
[Diagnostic / assumption summary]. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → jackknife — For Reviewers

20.0.133 The Runs Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **The Runs Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Runs Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$).
[Diagnostic / assumption summary]. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → runs-test — For Reviewers

20.0.134 The Sign Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **The Sign Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Sign Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$).
[Diagnostic / assumption summary]. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → sign-test — For Reviewers

20.0.135 Two-Proportion Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Two-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Two-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → two-proportion-test — For Reviewers

20.0.136 Two-Sample t-Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Two-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Two-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → two-sample-t-test — For Reviewers

20.0.137 Two-Way ANOVA**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Two-Way ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Two-Way ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → two-way-anova — For Reviewers

20.0.138 Type I and Type II Errors**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Type I and Type II Errors** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Type I and Type II Errors yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → type-i-type-ii-errors — For Reviewers

20.0.139 Weighted Kappa

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Weighted Kappa** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Weighted Kappa yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → weighted-kappa — For Reviewers

20.0.140 Welch's t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Welch's t-Test** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Welch's t-Test yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → welch-t-test — For Reviewers

20.0.141 Wilcoxon Signed-Rank Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Wilcoxon Signed-Rank Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Wilcoxon Signed-Rank Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → wilcoxon-signed-rank — For Reviewers