

Chapter 19

STROBE — observational studies

STROBE — *Strengthening the Reporting of Observational Studies in Epidemiology* — covers cohort, case-control, and cross-sectional studies. The 22-item checklist is at <https://www.strobe-statement.org/>. The templates below cover the analytic methods you are most likely to use in a STROBE-aligned paper.

This page contains **186 method-specific templates**. Each is a skeleton with placeholders in *italics*; the prose is written so you can paste it into a manuscript and replace only the bracketed values.

19.0.1 2^k Factorial Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **2^k Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

2^k Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → factorial-2k — For Reviewers

19.0.2 3^k Factorial Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **3^k Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

3^k Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → factorial-3k — For Reviewers

19.0.3 Accelerated Failure Time Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Accelerated Failure Time Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Accelerated Failure Time Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → accelerated-failure-time — For Reviewers

19.0.4 Added-Variable Plots

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Added-Variable Plots** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Added-Variable Plots yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → added-variable-plots — For Reviewers

19.0.5 Anderson-Darling Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Anderson-Darling Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Anderson-Darling Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → anderson-darling-test — For Reviewers

19.0.6 Balanced Incomplete Block Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Balanced Incomplete Block Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Balanced Incomplete Block Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → balanced-incomplete-block — For Reviewers

19.0.7 Bartlett's Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Bartlett's Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions

were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Bartlett's Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `bartlett-test` — For Reviewers

19.0.8 Benjamini-Hochberg FDR

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Benjamini-Hochberg FDR** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Benjamini-Hochberg FDR yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `benjamini-hochberg-fdr` — For Reviewers

19.0.9 Benjamini-Yekutieli FDR

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Benjamini-Yekutieli FDR** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Benjamini-Yekutieli FDR yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `benjamini-yekutieli` — For Reviewers

19.0.10 Best Subset Selection

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Best Subset Selection** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Best Subset Selection yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → best-subset-selection — For Reviewers

19.0.11 Beta Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Beta Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Beta Regression yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → beta-regression — For Reviewers

19.0.12 Bonferroni Correction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Bonferroni Correction** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Bonferroni Correction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → bonferroni-correction — For Reviewers

19.0.13 Bootstrap Confidence Intervals

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Bootstrap Confidence Intervals** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Bootstrap Confidence Intervals yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → bootstrap-confidence-intervals — For Reviewers

19.0.14 Box-Behnken Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Box-Behnken Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Box-Behnken Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → box-behnken-design — For Reviewers

19.0.15 Censoring Types

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Censoring Types** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Censoring Types yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → censoring-types — For Reviewers

19.0.16 Central Composite Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Central Composite Designs** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Central Composite Designs yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → central-composite-design — For Reviewers

19.0.17 Centring and Scaling Predictors

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Centring and Scaling Predictors** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Centring and Scaling Predictors yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → centered-scaled-predictors — For Reviewers

19.0.18 Checking Cox Assumptions

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Checking Cox Assumptions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Checking Cox Assumptions yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cox-assumptions-check — For Reviewers

19.0.19 Chi-Squared Goodness-of-Fit Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Chi-Squared Goodness-of-Fit Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Chi-Squared Goodness-of-Fit Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → chi-squared-goodness-of-fit — For Reviewers

19.0.20 Chi-Squared Test of Independence

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Chi-Squared Test of Independence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Chi-Squared Test of Independence yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → chi-squared-independence — For Reviewers

19.0.21 Cochran-Mantel-Haenszel Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cochran-Mantel-Haenszel Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cochran-Mantel-Haenszel Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cochrane-mantel-haenszel — For Reviewers

19.0.22 Competing Risks: Cumulative Incidence

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Competing Risks: Cumulative Incidence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Competing Risks: Cumulative Incidence yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → competing-risks-cif — For Reviewers

19.0.23 Completely Randomised Design

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Completely Randomised Design** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Completely Randomised Design yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → completely-randomized-design
— For Reviewers

19.0.24 Concordance and the C-Index

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Concordance and the C-Index** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Concordance and the C-Index yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → concordance-c-index — For Reviewers

19.0.25 Conditional Survival

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Conditional Survival** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Conditional Survival yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → conditional-survival — For Reviewers

19.0.26 Constrained Mixture Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Constrained Mixture Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Constrained Mixture Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → constrained-mixture — For Reviewers

19.0.27 Contrasts in R

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Contrasts in R** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Contrasts in R yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → contrasts-in-r — For Reviewers

19.0.28 Cook's Distance

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cook's Distance** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cook's Distance yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cooks-distance — For Reviewers

19.0.29 Cox Proportional Hazards Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cox Proportional Hazards Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cox Proportional Hazards Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cox-proportional-hazards — For Reviewers

19.0.30 Cox Regression as Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cox Regression as Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cox Regression as Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → survival-regression-cox — For Reviewers

19.0.31 Crossover Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Crossover Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions

were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Crossover Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → crossover-designs — For Reviewers

19.0.32 Desirability Functions

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Desirability Functions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Desirability Functions yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → desirability-function — For Reviewers

19.0.33 Dirichlet Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Dirichlet Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Dirichlet Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → dirichlet-regression — For Reviewers

19.0.34 Dummy Coding

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Dummy Coding** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Dummy Coding yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → dummy-coding — For Reviewers

19.0.35 Effect (Deviation) Coding

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Effect (Deviation) Coding** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Effect (Deviation) Coding yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → effect-coding — For Reviewers

19.0.36 Effect Size: Cohen's d

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Effect Size: Cohen's d** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Effect Size: Cohen's d yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → effect-size-cohens-d — For Reviewers

19.0.37 Effect Size: Cohen's h

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Effect Size: Cohen's h** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Effect Size: Cohen's h yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → effect-size-cohens-h — For Reviewers

19.0.38 Effect Size: Eta-Squared

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Effect Size: Eta-Squared** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Effect Size: Eta-Squared yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → effect-size-eta-squared — For Reviewers

19.0.39 Effect Sizes: Overview

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Effect Sizes: Overview** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Effect Sizes: Overview yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `effect-sizes-overview` — For Reviewers

19.0.40 Elastic Net**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Elastic Net** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Elastic Net yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `elastic-net` — For Reviewers

19.0.41 Equivalence Testing with TOST**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Equivalence Testing with TOST** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Equivalence Testing with TOST yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `equivalence-tost` — For Reviewers

19.0.42 Fine-Gray Subdistribution Hazards**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Fine-Gray Subdistribution Hazards** as implemented in *[package vX.Y]* in R

[vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Fine-Gray Subdistribution Hazards yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

Reviewer checklist for this method. → fine-gray-regression — For Reviewers

19.0.43 Fisher's Exact Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Fisher's Exact Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use = 0.05; *[multiple-comparison adjustment if any].*

Results paragraph (copy-paste):

Fisher's Exact Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

Reviewer checklist for this method. → fisher-exact-test — For Reviewers

19.0.44 Fractional Factorial Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Fractional Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use = 0.05; *[multiple-comparison adjustment if any].*

Results paragraph (copy-paste):

Fractional Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

Reviewer checklist for this method. → fractional-factorial-design
— For Reviewers

19.0.45 Frailty Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Frailty Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Frailty Models yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → frailty-models — For Reviewers

19.0.46 Friedman Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Friedman Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Friedman Test yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → friedman-test — For Reviewers

19.0.47 GAMMs: Additive Mixed Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **GAMMs: Additive Mixed Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

GAMMs: Additive Mixed Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `gamm-additive-mixed` — For Reviewers

19.0.48 GAMs: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **GAMs: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

GAMs: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `gam-introduction` — For Reviewers

19.0.49 Generalised Estimating Equations

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Generalised Estimating Equations** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Generalised Estimating Equations yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `generalized-estimating-equations` — For Reviewers

19.0.50 glmer: Generalised Mixed Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **glmer: Generalised Mixed Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

glmer: Generalised Mixed Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → glmer-generalized-mixed — For Reviewers

19.0.51 Graeco-Latin Square Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Graeco-Latin Square Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Graeco-Latin Square Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → graeco-latin-square — For Reviewers

19.0.52 Hazard, Survival, and Cumulative Hazard

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Hazard, Survival, and Cumulative Hazard** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Hazard, Survival, and Cumulative Hazard yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → hazard-survival-cumulative —
For Reviewers

19.0.53 Holm's Step-Down Correction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Holm's Step-Down Correction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Holm's Step-Down Correction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → holm-correction — For Reviewers

19.0.54 Hurdle Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Hurdle Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Hurdle Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → hurdle-models — For Reviewers

19.0.55 Interactions in Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Interactions in Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Interactions in Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → interactions-in-regression — For Reviewers

19.0.56 Interval-Censored Data

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Interval-Censored Data** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Interval-Censored Data yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → interval-censored-data — For Reviewers

19.0.57 Joint Longitudinal-Survival Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Joint Longitudinal-Survival Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Joint Longitudinal-Survival Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → joint-longitudinal-survival — For Reviewers

19.0.58 Kaplan-Meier Estimation

Methods paragraph (copy-paste, fill in italics):

[*N=*] participants/observations were analysed using **Kaplan-Meier Estimation** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Kaplan-Meier Estimation yielded [*estimate*] (95% CI [*lower, upper*], $p = [value]$). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → kaplan-meier — For Reviewers

19.0.59 Kendall's Tau

Methods paragraph (copy-paste, fill in italics):

[*N=*] participants/observations were analysed using **Kendall's Tau** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Kendall's Tau yielded [*estimate*] (95% CI [*lower, upper*], $p = [value]$). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → kendall-tau — For Reviewers

19.0.60 Kolmogorov-Smirnov Test

Methods paragraph (copy-paste, fill in italics):

[*N=*] participants/observations were analysed using **Kolmogorov-Smirnov Test** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Kolmogorov-Smirnov Test yielded [*estimate*] (95% CI [*lower, upper*], $p = [value]$). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → kolmogorov-smirnov-test — For Reviewers

19.0.61 Kruskal-Wallis Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Kruskal-Wallis Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Kruskal-Wallis Test yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `kruskal-wallis` — For Reviewers

19.0.62 Landmark Analysis

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Landmark Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Landmark Analysis yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `landmark-analysis` — For Reviewers

19.0.63 Lasso Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Lasso Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Lasso Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → lasso-regression — For Reviewers

19.0.64 Latin Square Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Latin Square Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Latin Square Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → latin-square — For Reviewers

19.0.65 Left Truncation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Left Truncation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Left Truncation yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → left-truncation — For Reviewers

19.0.66 Levene's Test of Variances

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Levene's Test of Variances** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with*

95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Levene's Test of Variances yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → `levене-test` — For Reviewers

19.0.67 Leverage and Influence

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Leverage and Influence** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Leverage and Influence yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → `leverage-influence` — For Reviewers

19.0.68 Linear Regression Assumptions

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Linear Regression Assumptions** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Linear Regression Assumptions yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → `regression-assumptions` — For Reviewers

19.0.69 Log-Rank Test: Details

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Log-Rank Test: Details** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Log-Rank Test: Details yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → log-rank-test-details — For Reviewers

19.0.70 Logistic Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → logistic-regression — For Reviewers

19.0.71 Logistic Regression Diagnostics

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Logistic Regression Diagnostics** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Logistic Regression Diagnostics yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `logistic-regression-diagnostics`
— For Reviewers

19.0.72 Mann-Whitney U Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Mann-Whitney U Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Mann-Whitney U Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `mann-whitney-u` — For Reviewers

19.0.73 McNemar’s Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **McNemar’s Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

McNemar’s Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `mcnemar-test` — For Reviewers

19.0.74 Method of Steepest Ascent

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Method of Steepest Ascent** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size*

with 95% confidence interval reported as the primary outcome].
Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Method of Steepest Ascent yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → steepest-ascent — For Reviewers

19.0.75 Minimum Detectable Effect

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Minimum Detectable Effect** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Minimum Detectable Effect yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → minimum-detectable-effect — For Reviewers

19.0.76 Mixed ANOVA

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Mixed ANOVA** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Mixed ANOVA yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → mixed-anova — For Reviewers

19.0.77 Mixed-Effects Models: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Mixed-Effects Models: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Mixed-Effects Models: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `mixed-models-intro` — For Reviewers

19.0.78 Model Selection with AIC and BIC

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Model Selection with AIC and BIC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Model Selection with AIC and BIC yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `model-selection-aic-bic` — For Reviewers

19.0.79 Multi-State Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multi-State Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multi-State Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multi-state-models — For Reviewers

19.0.80 Multicollinearity and VIF

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multi-collinearity and VIF** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multicollinearity and VIF yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multicollinearity-vif — For Reviewers

19.0.81 Multinomial Logistic Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multinomial Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multinomial Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multinomial-logistic — For Reviewers

19.0.82 Multiple Comparisons: Overview

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multiple Comparisons: Overview** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*.

Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multiple Comparisons: Overview yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → [multiple-comparisons-overview](#)
— For Reviewers

19.0.83 Multiple Linear Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multiple Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multiple Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → [multiple-linear-regression](#) —
For Reviewers

19.0.84 Negative Binomial Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Negative Binomial Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Negative Binomial Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → [negative-binomial-regression](#)
— For Reviewers

19.0.85 Nested vs Crossed Random Effects

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Nested vs Crossed Random Effects** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Nested vs Crossed Random Effects yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → nested-crossed-random-effects
— For Reviewers

19.0.86 Null and Alternative Hypotheses

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Null and Alternative Hypotheses** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Null and Alternative Hypotheses yielded *[estimate]* (95% CI *[lower, upper]*), $p = [value]$. *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → null-alternative-hypotheses
— For Reviewers

19.0.87 Offsets in Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Offsets in Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Offsets in Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `offsets-in-regression` — For Reviewers

19.0.88 One-Proportion Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **One-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

One-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `one-proportion-test` — For Reviewers

19.0.89 One-Sample t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **One-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

One-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `one-sample-t-test` — For Reviewers

19.0.90 One-Sample z-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **One-Sample z-Test** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

One-Sample z-Test yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → one-sample-z-test — For Reviewers

19.0.91 One-Way ANOVA

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **One-Way ANOVA** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

One-Way ANOVA yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → one-way-anova — For Reviewers

19.0.92 Optimal Designs: D, A, I

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Optimal Designs: D, A, I** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Optimal Designs: D, A, I yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → optimal-design-d-a-i — For Reviewers

19.0.93 Ordinal Logistic Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Ordinal Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Ordinal Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → ordinal-logistic — For Reviewers

19.0.94 Orthogonal Arrays

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Orthogonal Arrays** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Orthogonal Arrays yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → orthogonal-arrays — For Reviewers

19.0.95 P-Values Explained

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **P-Values Explained** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

P-Values Explained yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → p-values-explained — For Reviewers

19.0.96 Paired t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Paired t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Paired t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → paired-t-test — For Reviewers

19.0.97 Parametric Survival: Log-Normal

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Parametric Survival: Log-Normal** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Parametric Survival: Log-Normal yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → parametric-survival-lognormal — For Reviewers

19.0.98 Parametric Survival: Weibull

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Parametric Survival: Weibull** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with*

95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Parametric Survival: Weibull yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → parametric-survival-weibull
— For Reviewers

19.0.99 Partial Correlation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Partial Correlation** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Partial Correlation yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → partial-correlation — For Reviewers

19.0.100 Pearson Correlation Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Pearson Correlation Test** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Pearson Correlation Test yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → pearson-correlation-test —
For Reviewers

19.0.101 Permutation Tests

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Permutation Tests** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Permutation Tests yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → permutation-tests — For Reviewers

19.0.102 Plackett-Burman Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Plackett-Burman Designs** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Plackett-Burman Designs yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → plackett-burman — For Reviewers

19.0.103 Poisson Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Poisson Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Poisson Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → poisson-regression — For Reviewers

19.0.104 Polynomial Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Polynomial Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Polynomial Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → polynomial-regression — For Reviewers

19.0.105 Post-Hoc Power: A Controversy

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Post-Hoc Power: A Controversy** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Post-Hoc Power: A Controversy yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → post-hoc-power-controversy — For Reviewers

19.0.106 Post-Hoc Tests with Tukey HSD

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Post-Hoc Tests with Tukey HSD** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Post-Hoc Tests with Tukey HSD yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → post-hoc-tests-tukey — For Reviewers

19.0.107 Power Analysis for DOE

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power Analysis for DOE** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power Analysis for DOE yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-in-doe — For Reviewers

19.0.108 Power Analysis: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power Analysis: Introduction** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power Analysis: Introduction yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-analysis-introduction
— For Reviewers

19.0.109 Power for Agreement (Kappa)

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Agreement (Kappa)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Agreement (Kappa) yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-agreement-kappa — For Reviewers

19.0.110 Power for Bland-Altman Studies

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Bland-Altman Studies** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Bland-Altman Studies yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-bland-altman — For Reviewers

19.0.111 Power for Chi-Squared Tests

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Chi-Squared Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size]*

with 95% confidence interval reported as the primary outcome].
Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power for Chi-Squared Tests yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-chi-squared — For Reviewers

19.0.112 Power for Cluster-RCT

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Cluster-RCT** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power for Cluster-RCT yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-cluster-rct — For Reviewers

19.0.113 Power for Correlation Tests

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Correlation Tests** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power for Correlation Tests yielded [estimate] (95% CI [lower, upper], $p = [value]$). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-correlation — For Reviewers

19.0.114 Power for Cox Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Cox Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Cox Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-cox-regression — For Reviewers

19.0.115 Power for Crossover Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Crossover Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Crossover Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-crossover — For Reviewers

19.0.116 Power for Diagnostic Accuracy

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Diagnostic Accuracy** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Diagnostic Accuracy yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-diagnostic-accuracy — For Reviewers

19.0.117 Power for Equivalence (TOST)**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Power for Equivalence (TOST)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Equivalence (TOST) yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-equivalence-tost — For Reviewers

19.0.118 Power for ICC**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Power for ICC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for ICC yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-icc — For Reviewers

19.0.119 Power for Linear Regression**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Power for Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-linear-regression — For Reviewers

19.0.120 Power for Logistic Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-logistic-regression — For Reviewers

19.0.121 Power for McNemar's Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for McNemar's Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for McNemar's Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-mcnemar — For Reviewers

19.0.122 Power for Non-Inferiority Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Non-Inferiority Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Non-Inferiority Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-non-inferiority — For Reviewers

19.0.123 Power for One-Proportion Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for One-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for One-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-one-proportion — For Reviewers

19.0.124 Power for One-Sample t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for One-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for One-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-one-sample-t — For Reviewers

19.0.125 Power for One-Way ANOVA**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Power for One-Way ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for One-Way ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-anova — For Reviewers

19.0.126 Power for Paired t-Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Power for Paired t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Paired t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-paired-t — For Reviewers

19.0.127 Power for Repeated-Measures ANOVA**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Power for Repeated-Measures ANOVA** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power for Repeated-Measures ANOVA yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-repeated-measures — For Reviewers

19.0.128 Power for Stepped-Wedge Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Stepped-Wedge Trials** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power for Stepped-Wedge Trials yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-stepped-wedge — For Reviewers

19.0.129 Power for the Log-Rank Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for the Log-Rank Test** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Power for the Log-Rank Test yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → power-logrank-test — For Reviewers

19.0.130 Power for Two-Proportion Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Power for Two-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Power for Two-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-two-proportions — For Reviewers

19.0.131 Principles of Blocking

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Principles of Blocking** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Principles of Blocking yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → blocking-principles — For Reviewers

19.0.132 Probit Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Probit Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Probit Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → probit-regression — For Reviewers

19.0.133 Quantile Regression**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Quantile Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Quantile Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → quantile-regression — For Reviewers

19.0.134 Quasi-Poisson Regression**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Quasi-Poisson Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Quasi-Poisson Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → quasi-poisson — For Reviewers

19.0.135 R-Squared and Adjusted R-Squared**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **R-Squared and Adjusted R-Squared** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

R-Squared and Adjusted R-Squared yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → **r-squared-adjusted** — For Reviewers

19.0.136 Random-Intercept Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Random-Intercept Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Random-Intercept Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → **random-intercepts** — For Reviewers

19.0.137 Random-Slope Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Random-Slope Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Random-Slope Models yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → random-slopes — For Reviewers

19.0.138 Randomisation in Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Randomisation in Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Randomisation in Design yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → randomization-in-design — For Reviewers

19.0.139 Randomised Complete Block Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Randomised Complete Block Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Randomised Complete Block Design yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → randomised-complete-block — For Reviewers

19.0.140 Recurrent Events

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Recurrent Events** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Recurrent Events yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → recurrent-events — For Reviewers

19.0.141 Repeated-Measures ANOVA

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Repeated-Measures ANOVA** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Repeated-Measures ANOVA yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → repeated-measures-anova — For Reviewers

19.0.142 Repeated-Measures Designs

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Repeated-Measures Designs** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Repeated-Measures Designs yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → repeated-measures-design —
For Reviewers

19.0.143 Residual Diagnostics

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Residual Diagnostics** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Residual Diagnostics yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → residual-diagnostics — For Reviewers

19.0.144 Resolution and Aliasing

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Resolution and Aliasing** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Resolution and Aliasing yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → resolution-aliasing — For Reviewers

19.0.145 Response Surface Methodology

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Response Surface Methodology** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Response Surface Methodology yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → response-surface-methodology
— For Reviewers

19.0.146 Restricted Mean Survival Time (RMST)**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Restricted Mean Survival Time (RMST)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Restricted Mean Survival Time (RMST) yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → restricted-mean-survival-time
— For Reviewers

19.0.147 Ridge Regression**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Ridge Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Ridge Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → ridge-regression — For Reviewers

19.0.148 Robust Parameter Design**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Robust Parameter Design** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Robust Parameter Design yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → robust-parameter-design — For Reviewers

19.0.149 Robust Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Robust Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Robust Regression yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → robust-regression — For Reviewers

19.0.150 ROC and AUC for Logistic Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **ROC and AUC for Logistic Models** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

ROC and AUC for Logistic Models yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → roc-auc-for-logistic — For Reviewers

19.0.151 Royston-Parmar Flexible Parametric Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Royston-Parmar Flexible Parametric Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Royston-Parmar Flexible Parametric Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → flexible-parametric-royston-parmar — For Reviewers

19.0.152 Sample Size for a Two-Sample t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Sample Size for a Two-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Sample Size for a Two-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → power-two-sample-t — For Reviewers

19.0.153 Sample Size Sensitivity Analysis

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Sample Size Sensitivity Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect*

size with 95% confidence interval reported as the primary outcome].
Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Sample Size Sensitivity Analysis yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → sensitivity-analysis-sample-size
— For Reviewers

19.0.154 Schoenfeld Residuals

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Schoenfeld Residuals** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Schoenfeld Residuals yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → schoenfeld-residuals — For Reviewers

19.0.155 Shapiro-Wilk Normality Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Shapiro-Wilk Normality Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Shapiro-Wilk Normality Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → shapiro-wilk-test — For Reviewers

19.0.156 Signal-to-Noise Ratios

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Signal-to-Noise Ratios** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Signal-to-Noise Ratios yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → signal-to-noise-ratio — For Reviewers

19.0.157 Simple Linear Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Simple Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Simple Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → simple-linear-regression — For Reviewers

19.0.158 Simplex Centroid Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Simplex Centroid Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Simplex Centroid Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → mixture-centroid — For Reviewers

19.0.159 Simplex Lattice Mixture Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Simplex Lattice Mixture Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Simplex Lattice Mixture Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → mixture-designs-simplex — For Reviewers

19.0.160 Simulating Survival Data

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Simulating Survival Data** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Simulating Survival Data yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → survival-simulation — For Reviewers

19.0.161 Spearman Rank Correlation Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Spearman Rank Correlation Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Spearman Rank Correlation Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → spearman-correlation-test — For Reviewers

19.0.162 Spline Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Spline Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Spline Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → spline-regression — For Reviewers

19.0.163 Split-Plot Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Split-Plot Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Split-Plot Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → split-plot-design — For Reviewers

19.0.164 Stepwise Regression: Pitfalls

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stepwise Regression: Pitfalls** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stepwise Regression: Pitfalls yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → stepwise-regression-pitfalls — For Reviewers

19.0.165 Stratified Cox Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stratified Cox Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stratified Cox Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → stratified-cox — For Reviewers

19.0.166 Strip-Plot Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Strip-Plot Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Strip-Plot Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `strip-plot-design` — For Reviewers

19.0.167 Taguchi Methods

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Taguchi Methods** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Taguchi Methods yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `taguchi-methods` — For Reviewers

19.0.168 The Bootstrap: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Bootstrap: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Bootstrap: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `bootstrap-introduction` — For Reviewers

19.0.169 The Brier Score for Survival

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Brier Score for Survival** as implemented in *[package vX.Y]* in R *[vX.Y]*.

Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Brier Score for Survival yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `brier-score-survival` — For Reviewers

19.0.170 The Jackknife

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Jackknife** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Jackknife yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `jackknife` — For Reviewers

19.0.171 The Nelson-Aalen Estimator

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Nelson-Aalen Estimator** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Nelson-Aalen Estimator yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `nelson-aalen-estimator` — For Reviewers

19.0.172 The Runs Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Runs Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Runs Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → runs-test — For Reviewers

19.0.173 The Sign Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Sign Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Sign Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → sign-test — For Reviewers

19.0.174 Time-Dependent ROC

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Time-Dependent ROC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Time-Dependent ROC yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → time-dependent-roc — For Reviewers

19.0.175 Time-Varying Covariates

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Time-Varying Covariates** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Time-Varying Covariates yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → time-varying-covariates — For Reviewers

19.0.176 Tobit Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Tobit Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Tobit Regression yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → tobit-regression — For Reviewers

19.0.177 Truncated Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Truncated Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Truncated Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → truncated-regression — For Reviewers

19.0.178 Two-Proportion Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Two-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Two-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → two-proportion-test — For Reviewers

19.0.179 Two-Sample t-Test**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Two-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Two-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → two-sample-t-test — For Reviewers

19.0.180 Two-Way ANOVA**Methods paragraph (copy-paste, fill in italics):**

[*N*=] participants/observations were analysed using **Two-Way ANOVA** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Two-Way ANOVA yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → two-way-anova — For Reviewers

19.0.181 Type I and Type II Errors

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Type I and Type II Errors** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Type I and Type II Errors yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → type-i-type-ii-errors — For Reviewers

19.0.182 Weighted Log-Rank Tests

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Weighted Log-Rank Tests** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Weighted Log-Rank Tests yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → `weighted-log-rank` — For Reviewers

19.0.183 Welch’s t-Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Welch’s t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Welch’s t-Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `welch-t-test` — For Reviewers

19.0.184 Wilcoxon Signed-Rank Test

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Wilcoxon Signed-Rank Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Wilcoxon Signed-Rank Test yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `wilcoxon-signed-rank` — For Reviewers

19.0.185 Worked lme4::lmer Examples

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Worked lme4::lmer Examples** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Worked lme4::lmer Examples yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → lme4-lmer-examples — For Reviewers

19.0.186 Zero-Inflated Models**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Zero-Inflated Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Zero-Inflated Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → zero-inflated-models — For Reviewers

