

Chapter 21

TRIPOD-AI — prediction models

TRIPOD-AI — *Transparent Reporting of a multivariable prediction model for Individual Prognosis Or Diagnosis, AI extension* — covers prediction models, including those built with machine learning. The checklist is at <https://www.tripod-statement.org/>. The templates below cover model development, validation, calibration, and fairness reporting.

This page contains **163 method-specific templates**. Each is a skeleton with placeholders in italics; the prose is written so you can paste it into a manuscript and replace only the bracketed values.

21.0.1 A Complete mlr3 Workflow

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **A Complete mlr3 Workflow** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

A Complete mlr3 Workflow yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → mlr3-workflow — For Reviewers

21.0.2 A Complete tidymodels Workflow

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **A Complete tidymodels Workflow** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

A Complete tidymodels Workflow yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → tidymodels-workflow — For Reviewers

21.0.3 Accelerated Failure Time Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Accelerated Failure Time Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Accelerated Failure Time Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → accelerated-failure-time — For Reviewers

21.0.4 Adaptive Trial Designs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Adaptive Trial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Adaptive Trial Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → adaptive-design — For Reviewers

21.0.5 Added-Variable Plots**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Added-Variable Plots** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Added-Variable Plots yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → added-variable-plots — For Reviewers

21.0.6 Alpha-Spending Functions**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Alpha-Spending Functions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Alpha-Spending Functions yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → alpha-spending — For Reviewers

21.0.7 Anomaly Detection**Methods paragraph (copy-paste, fill in italics):**

[*N*=] participants/observations were analysed using **Anomaly Detection** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Anomaly Detection yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → anomaly-detection — For Reviewers

21.0.8 Bagging

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Bagging** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Bagging yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → bagging — For Reviewers

21.0.9 Baseline Adjustment with ANCOVA

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Baseline Adjustment with ANCOVA** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Baseline Adjustment with ANCOVA yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → baseline-adjustment-ancova — For Reviewers

21.0.10 Best Subset Selection

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Best Subset Selection** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Best Subset Selection yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → best-subset-selection — For Reviewers

21.0.11 Beta Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Beta Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Beta Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → beta-regression — For Reviewers

21.0.12 Bland-Altman Limits of Agreement

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Bland-Altman Limits of Agreement** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Bland-Altman Limits of Agreement yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → bland-altman-analysis — For Reviewers

21.0.13 Blinding Procedures

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Blinding Procedures** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Blinding Procedures yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → blinding-procedures — For Reviewers

21.0.14 Block Randomisation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Block Randomisation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Block Randomisation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → block-randomization — For Reviewers

21.0.15 Calibration Plots

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Calibration Plots** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions

were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Calibration Plots yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → calibration-plots — For Reviewers

21.0.16 CatBoost

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **CatBoost** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

CatBoost yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → catboost — For Reviewers

21.0.17 Censoring Types

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Censoring Types** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Censoring Types yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → censoring-types — For Reviewers

21.0.18 Centring and Scaling Predictors

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Centring and Scaling Predictors** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Centring and Scaling Predictors yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → centered-scaled-predictors — For Reviewers

21.0.19 Checking Cox Assumptions

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Checking Cox Assumptions** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Checking Cox Assumptions yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → cox-assumptions-check — For Reviewers

21.0.20 Class Weights for Imbalanced Data

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Class Weights for Imbalanced Data** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Class Weights for Imbalanced Data yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → class-weights-imbalanced —
For Reviewers

21.0.21 Clinical Equivalence Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Clinical Equivalence Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Clinical Equivalence Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → equivalence-clinical — For Reviewers

21.0.22 Cluster-Randomised Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cluster-Randomised Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cluster-Randomised Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cluster-rct — For Reviewers

21.0.23 Cohen's Kappa

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cohen's Kappa** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cohen's Kappa yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → cohens-kappa — For Reviewers

21.0.24 Competing Risks: Cumulative Incidence**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Competing Risks: Cumulative Incidence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Competing Risks: Cumulative Incidence yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → competing-risks-cif — For Reviewers

21.0.25 Concordance and the C-Index**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Concordance and the C-Index** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Concordance and the C-Index yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → concordance-c-index — For Reviewers

21.0.26 Conditional Power**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Conditional Power** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Conditional Power yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → conditional-power — For Reviewers

21.0.27 Conditional Survival

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Conditional Survival** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Conditional Survival yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → conditional-survival — For Reviewers

21.0.28 Contrasts in R

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Contrasts in R** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Contrasts in R yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → contrasts-in-r — For Reviewers

21.0.29 Convolutional Neural Networks: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Convolutional Neural Networks: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Convolutional Neural Networks: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `cnm-introduction` — For Reviewers

21.0.30 Cook's Distance

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cook's Distance** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cook's Distance yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `cooks-distance` — For Reviewers

21.0.31 Cox Proportional Hazards Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cox Proportional Hazards Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cox Proportional Hazards Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `cox-proportional-hazards` — For Reviewers

21.0.32 Cox Regression as Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cox Regression as Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cox Regression as Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `survival-regression-cox` — For Reviewers

21.0.33 Cross-Validation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Cross-Validation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Cross-Validation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `cross-validation` — For Reviewers

21.0.34 Crossover RCT Design

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Crossover RCT Design** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Crossover RCT Design yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → rct-design-crossover — For Reviewers

21.0.35 Cutpoint Selection

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Cutpoint Selection** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Cutpoint Selection yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → cutpoint-selection — For Reviewers

21.0.36 DBSCAN as an ML Tool

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **DBSCAN as an ML Tool** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

DBSCAN as an ML Tool yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → clustering-dbscan-ml — For Reviewers

21.0.37 Decision Trees (CART)

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Decision Trees (CART)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Decision Trees (CART) yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → decision-trees-cart — For Reviewers

21.0.38 Diagnostic Test Accuracy

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Diagnostic Test Accuracy** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Diagnostic Test Accuracy yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → diagnostic-accuracy — For Reviewers

21.0.39 Dirichlet Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Dirichlet Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95%*

confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Dirichlet Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `dirichlet-regression` — For Reviewers

21.0.40 Dropout and Early Stopping

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Dropout and Early Stopping** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Dropout and Early Stopping yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `dropout-early-stopping` — For Reviewers

21.0.41 Dummy Coding

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Dummy Coding** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Dummy Coding yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `dummy-coding` — For Reviewers

21.0.42 Effect (Deviation) Coding

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Effect (Deviation) Coding** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Effect (Deviation) Coding yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → effect-coding — For Reviewers

21.0.43 Elastic Net

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Elastic Net** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Elastic Net yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → elastic-net — For Reviewers

21.0.44 Extremely Randomised Trees

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Extremely Randomised Trees** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Extremely Randomised Trees yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → extremely-randomized-trees — For Reviewers

21.0.45 Factorial Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Factorial Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Factorial Trials yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → factorial-trial — For Reviewers

21.0.46 Feature Engineering

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Feature Engineering** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Feature Engineering yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → feature-engineering — For Reviewers

21.0.47 Feature Selection

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Feature Selection** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Feature Selection yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → feature-selection — For Reviewers

21.0.48 Feedforward Networks in torch

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Feedforward Networks in torch** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Feedforward Networks in torch yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → feedforward-networks-torch — For Reviewers

21.0.49 Fine-Gray Subdistribution Hazards

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Fine-Gray Subdistribution Hazards** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Fine-Gray Subdistribution Hazards yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → fine-gray-regression — For Reviewers

21.0.50 Frailty Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Frailty Models** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Frailty Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → frailty-models — For Reviewers

21.0.51 GAMMs: Additive Mixed Models**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **GAMMs: Additive Mixed Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

GAMMs: Additive Mixed Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → gamm-additive-mixed — For Reviewers

21.0.52 GAMs: Introduction**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **GAMs: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

GAMs: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → gam-introduction — For Reviewers

21.0.53 Generalised Estimating Equations**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Generalised Estimating Equations** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Generalised Estimating Equations yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → generalized-estimating-equations
— For Reviewers

21.0.54 glmer: Generalised Mixed Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **glmer: Generalised Mixed Models** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

glmer: Generalised Mixed Models yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → glmer-generalized-mixed — For Reviewers

21.0.55 Gradient Boosting

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Gradient Boosting** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Gradient Boosting yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → gradient-boosting — For Reviewers

21.0.56 Hazard, Survival, and Cumulative Hazard

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Hazard, Survival, and Cumulative Hazard** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Hazard, Survival, and Cumulative Hazard yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → hazard-survival-cumulative — For Reviewers

21.0.57 Hurdle Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Hurdle Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Hurdle Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → hurdle-models — For Reviewers

21.0.58 Interactions in Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Interactions in Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Interactions in Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → interactions-in-regression —
For Reviewers

21.0.59 Interim Analyses and Group Sequential Designs**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Interim Analyses and Group Sequential Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Interim Analyses and Group Sequential Designs yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → interim-analysis-group-sequential —
For Reviewers

21.0.60 Interval-Censored Data**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Interval-Censored Data** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Interval-Censored Data yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → interval-censored-data — For Reviewers

21.0.61 Intraclass Correlation Coefficient (ICC)

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Intraclass Correlation Coefficient (ICC)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Intraclass Correlation Coefficient (ICC) yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `icc-continuous-agreement` —
For Reviewers

21.0.62 Isolation Forest

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Isolation Forest** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Isolation Forest yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `isolation-forest` — For Reviewers

21.0.63 Isotonic Regression Calibration

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Isotonic Regression Calibration** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Isotonic Regression Calibration yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → isotonic-regression — For Reviewers

21.0.64 ITT vs Per-Protocol Analysis

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **ITT vs Per-Protocol Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

ITT vs Per-Protocol Analysis yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → itt-vs-pp-analysis — For Reviewers

21.0.65 Joint Longitudinal-Survival Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Joint Longitudinal-Survival Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Joint Longitudinal-Survival Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → joint-longitudinal-survival — For Reviewers

21.0.66 k-Means as an ML Tool

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **k-Means as an ML Tool** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

k-Means as an ML Tool yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → clustering-kmeans-ml — For Reviewers

21.0.67 k-Nearest Neighbours Classification

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **k-Nearest Neighbours Classification** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

k-Nearest Neighbours Classification yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → knn-classification — For Reviewers

21.0.68 k-Nearest Neighbours Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **k-Nearest Neighbours Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

k-Nearest Neighbours Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → knn-regression — For Reviewers

21.0.69 Kaplan-Meier Estimation

Methods paragraph (copy-paste, fill in italics):

[*N=*] participants/observations were analysed using **Kaplan-Meier Estimation** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Kaplan-Meier Estimation yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → kaplan-meier — For Reviewers

21.0.70 Kernel SVMs

Methods paragraph (copy-paste, fill in italics):

[*N=*] participants/observations were analysed using **Kernel SVMs** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Kernel SVMs yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → svm-kernel — For Reviewers

21.0.71 Landmark Analysis

Methods paragraph (copy-paste, fill in italics):

[*N=*] participants/observations were analysed using **Landmark Analysis** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Landmark Analysis yielded [*estimate*] (95% CI [*lower, upper*], p = [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → landmark-analysis — For Reviewers

21.0.72 Lasso Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Lasso Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Lasso Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → lasso-regression — For Reviewers

21.0.73 Left Truncation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Left Truncation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Left Truncation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → left-truncation — For Reviewers

21.0.74 Leverage and Influence

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Leverage and Influence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Leverage and Influence yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → leverage-influence — For Reviewers

21.0.75 LightGBM

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **LightGBM** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

LightGBM yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → lightgbm — For Reviewers

21.0.76 Likelihood Ratios

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Likelihood Ratios** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Likelihood Ratios yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → likelihood-ratios — For Reviewers

21.0.77 LIME Explanations

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **LIME Explanations** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95%*

confidence interval reported as the primary outcome]. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

LIME Explanations yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → lime-explanations — For Reviewers

21.0.78 Linear Discriminant as ML

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Linear Discriminant as ML** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Linear Discriminant as ML yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → linear-discriminant-ml — For Reviewers

21.0.79 Linear Regression Assumptions

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Linear Regression Assumptions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Linear Regression Assumptions yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → regression-assumptions — For Reviewers

21.0.80 Linear Support Vector Machines

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Linear Support Vector Machines** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Linear Support Vector Machines yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → svm-linear — For Reviewers

21.0.81 Log-Rank Test: Details

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Log-Rank Test: Details** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Log-Rank Test: Details yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → log-rank-test-details — For Reviewers

21.0.82 Logistic Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Logistic Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `logistic-regression` — For Reviewers

21.0.83 Logistic Regression as ML

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Logistic Regression as ML** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Logistic Regression as ML yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `logistic-regression-ml` — For Reviewers

21.0.84 Logistic Regression Diagnostics

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Logistic Regression Diagnostics** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Logistic Regression Diagnostics yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `logistic-regression-diagnostics` — For Reviewers

21.0.85 Minimisation Algorithm

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Minimisation Algorithm** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Minimisation Algorithm yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → minimization-algorithm — For Reviewers

21.0.86 Missing Data in RCTs

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Missing Data in RCTs** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Missing Data in RCTs yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → missing-data-rct — For Reviewers

21.0.87 Mixed-Effects Models: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Mixed-Effects Models: Introduction** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Mixed-Effects Models: Introduction yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → mixed-models-intro — For Reviewers

21.0.88 Model Selection with AIC and BIC

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Model Selection with AIC and BIC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Model Selection with AIC and BIC yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → model-selection-aic-bic — For Reviewers

21.0.89 Multi-State Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multi-State Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multi-State Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multi-state-models — For Reviewers

21.0.90 Multicollinearity and VIF

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multicollinearity and VIF** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*.

Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multicollinearity and VIF yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multicollinearity-vif — For Reviewers

21.0.91 Multinomial Logistic Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multinomial Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multinomial Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multinomial-logistic — For Reviewers

21.0.92 Multiple Imputation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multiple Imputation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multiple Imputation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multiple-imputation — For Reviewers

21.0.93 Multiple Linear Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Multiple Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Multiple Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → multiple-linear-regression — For Reviewers

21.0.94 Naive Bayes

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Naive Bayes** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Naive Bayes yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → naive-bayes — For Reviewers

21.0.95 Negative Binomial Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Negative Binomial Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Negative Binomial Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → negative-binomial-regression
— For Reviewers

21.0.96 Nested Cross-Validation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Nested Cross-Validation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Nested Cross-Validation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → nested-cv — For Reviewers

21.0.97 Nested vs Crossed Random Effects

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Nested vs Crossed Random Effects** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Nested vs Crossed Random Effects yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → nested-crossed-random-effects
— For Reviewers

21.0.98 Neural Networks: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Neural Networks: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Neural Networks: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → neural-networks-intro — For Reviewers

21.0.99 Non-Inferiority Margin Selection**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Non-Inferiority Margin Selection** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Non-Inferiority Margin Selection yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → non-inferiority-margin — For Reviewers

21.0.100 O’Brien-Fleming Boundary**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **O’Brien-Fleming Boundary** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

O’Brien-Fleming Boundary yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → obrien-fleming-boundary — For Reviewers

21.0.101 Offsets in Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Offsets in Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Offsets in Regression yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → `offsets-in-regression` — For Reviewers

21.0.102 Ordinal Logistic Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Ordinal Logistic Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Ordinal Logistic Regression yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → `ordinal-logistic` — For Reviewers

21.0.103 Parallel-Group RCT Design

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Parallel-Group RCT Design** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Parallel-Group RCT Design yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `rct-design-parallel` — For Reviewers

21.0.104 Parametric Survival: Log-Normal

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Parametric Survival: Log-Normal** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Parametric Survival: Log-Normal yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `parametric-survival-lognormal` — For Reviewers

21.0.105 Parametric Survival: Weibull

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Parametric Survival: Weibull** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Parametric Survival: Weibull yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `parametric-survival-weibull` — For Reviewers

21.0.106 Partial Correlation

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Partial Correlation** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Partial Correlation yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → partial-correlation — For Reviewers

21.0.107 Partial Dependence Plots

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Partial Dependence Plots** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Partial Dependence Plots yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → partial-dependence-plots — For Reviewers

21.0.108 Platt Scaling

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Platt Scaling** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Platt Scaling yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → platt-scaling — For Reviewers

21.0.109 Pocock Boundary

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Pocock Boundary** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Pocock Boundary yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → pocock-boundary — For Reviewers

21.0.110 Poisson Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Poisson Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Poisson Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → poisson-regression — For Reviewers

21.0.111 Polynomial Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Polynomial Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Polynomial Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → polynomial-regression — For Reviewers

21.0.112 Predictive Values and Prevalence

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Predictive Values and Prevalence** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Predictive Values and Prevalence yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → predictive-values-prevalence — For Reviewers

21.0.113 Preprocessing with recipes

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Preprocessing with recipes** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Preprocessing with recipes yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → recipes-preprocessing — For Reviewers

21.0.114 Probit Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Probit Regression** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Probit Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → probit-regression — For Reviewers

21.0.115 Quantile Regression**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Quantile Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Quantile Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → quantile-regression — For Reviewers

21.0.116 Quasi-Poisson Regression**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Quasi-Poisson Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Quasi-Poisson Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → quasi-poisson — For Reviewers

21.0.117 R-Squared and Adjusted R-Squared**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **R-Squared and Adjusted R-Squared** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

R-Squared and Adjusted R-Squared yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → r-squared-adjusted — For Reviewers

21.0.118 Random Forests

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Random Forests** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Random Forests yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → random-forest — For Reviewers

21.0.119 Random-Intercept Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Random-Intercept Models** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Random-Intercept Models yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → random-intercepts — For Reviewers

21.0.120 Random-Slope Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Random-Slope Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Random-Slope Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → random-slopes — For Reviewers

21.0.121 Randomisation Methods

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Randomisation Methods** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Randomisation Methods yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → randomization-methods — For Reviewers

21.0.122 Recurrent Events

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Recurrent Events** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Recurrent Events yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → recurrent-events — For Reviewers

21.0.123 Regularisation in ML**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Regularisation in ML** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Regularisation in ML yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → regularization-ridge-lasso-ml — For Reviewers

21.0.124 Reliability and Cronbach's Alpha**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Reliability and Cronbach's Alpha** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Reliability and Cronbach's Alpha yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → reliability-cronbach-alpha — For Reviewers

21.0.125 Residual Diagnostics**Methods paragraph (copy-paste, fill in italics):**

[*N*=] participants/observations were analysed using **Residual Diagnostics** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Residual Diagnostics yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → residual-diagnostics — For Reviewers

21.0.126 Restricted Mean Survival Time (RMST)

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Restricted Mean Survival Time (RMST)** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Restricted Mean Survival Time (RMST) yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → restricted-mean-survival-time — For Reviewers

21.0.127 Ridge Regression

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Ridge Regression** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use $\alpha = 0.05$; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Ridge Regression yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → ridge-regression — For Reviewers

21.0.128 RNNs and LSTMs: Introduction

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **RNNs and LSTMs: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

RNNs and LSTMs: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → rnn-lstm-intro — For Reviewers

21.0.129 Robust Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Robust Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Robust Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → robust-regression — For Reviewers

21.0.130 ROC Analysis

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **ROC Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

ROC Analysis yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$).
[Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → roc-analysis — For Reviewers

21.0.131 ROC and AUC for Logistic Models**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **ROC and AUC for Logistic Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

ROC and AUC for Logistic Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

Reviewer checklist for this method. → roc-auc-for-logistic — For Reviewers

21.0.132 Royston-Parmar Flexible Parametric Models**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Royston-Parmar Flexible Parametric Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Royston-Parmar Flexible Parametric Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

Reviewer checklist for this method. → flexible-parametric-royston-parmar — For Reviewers

21.0.133 Sample Size Re-Estimation**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Sample Size Re-Estimation** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Sample Size Re-Estimation yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → sample-size-reestimation — For Reviewers

21.0.134 Schoenfeld Residuals

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Schoenfeld Residuals** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Schoenfeld Residuals yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → schoenfeld-residuals — For Reviewers

21.0.135 Sensitivity Analyses in Clinical Trials

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Sensitivity Analyses in Clinical Trials** as implemented in [package vX.Y] in R [vX.Y]. Assumptions were checked: [list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome]. Two-sided p-values use = 0.05; [multiple-comparison adjustment if any].

Results paragraph (copy-paste):

Sensitivity Analyses in Clinical Trials yielded [estimate] (95% CI [lower, upper], p = [value]). [Diagnostic / assumption summary]. [Sensitivity analysis result].

Reviewer checklist for this method. → sensitivity-analysis-clinical
— For Reviewers

21.0.136 SHAP Values

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **SHAP Values** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

SHAP Values yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → shap-values — For Reviewers

21.0.137 Simple Linear Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Simple Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Simple Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → simple-linear-regression —
For Reviewers

21.0.138 Simulating Survival Data

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Simulating Survival Data** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Simulating Survival Data yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → survival-simulation — For Reviewers

21.0.139 SMOTE for Imbalanced Classes

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **SMOTE for Imbalanced Classes** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

SMOTE for Imbalanced Classes yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → smote-imbalanced — For Reviewers

21.0.140 Spline Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Spline Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Spline Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → spline-regression — For Reviewers

21.0.141 Stacking Ensembles

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stacking Ensembles** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stacking Ensembles yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → **stacking-ensembles** — For Reviewers

21.0.142 Stepped-Wedge Trial

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stepped-Wedge Trial** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stepped-Wedge Trial yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → **stepped-wedge-trial** — For Reviewers

21.0.143 Stepwise Regression: Pitfalls

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stepwise Regression: Pitfalls** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stepwise Regression: Pitfalls yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `stepwise-regression-pitfalls`
— For Reviewers

21.0.144 Stratified Cox Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stratified Cox Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stratified Cox Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `stratified-cox` — For Reviewers

21.0.145 Stratified Randomisation

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Stratified Randomisation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Stratified Randomisation yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `stratified-randomization` — For Reviewers

21.0.146 Subgroup Analyses

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Subgroup Analyses** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Subgroup Analyses yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → subgroup-analysis — For Reviewers

21.0.147 Subgroup Forest Plots**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Subgroup Forest Plots** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Subgroup Forest Plots yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → forest-plot-subgroup — For Reviewers

21.0.148 Supervised Learning: Overview**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Supervised Learning: Overview** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p -values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Supervised Learning: Overview yielded *[estimate]* (95% CI *[lower, upper]*, $p =$ *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → supervised-learning-overview — For Reviewers

21.0.149 The Bias-Variance Tradeoff

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Bias-Variance Tradeoff** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Bias-Variance Tradeoff yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → bias-variance-tradeoff — For Reviewers

21.0.150 The Brier Score for Survival

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Brier Score for Survival** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Brier Score for Survival yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → brier-score-survival — For Reviewers

21.0.151 The Nelson-Aalen Estimator

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **The Nelson-Aalen Estimator** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

The Nelson-Aalen Estimator yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `nelson-aalen-estimator` — For Reviewers

21.0.152 Time-Dependent ROC

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Time-Dependent ROC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Time-Dependent ROC yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `time-dependent-roc` — For Reviewers

21.0.153 Time-Varying Covariates

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Time-Varying Covariates** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Time-Varying Covariates yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `time-varying-covariates` — For Reviewers

21.0.154 Tobit Regression

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Tobit Regression** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Tobit Regression yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → tobit-regression — For Reviewers

21.0.155 Train-Test Splits

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Train-Test Splits** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Train-Test Splits yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → train-test-split — For Reviewers

21.0.156 Transformers: Overview

Methods paragraph (copy-paste, fill in italics):

[*N*=] participants/observations were analysed using **Transformers: Overview** as implemented in [*package vX.Y*] in R [*vX.Y*]. Assumptions were checked: [*list checks performed*]. [*Effect size with 95% confidence interval reported as the primary outcome*]. Two-sided p-values use = 0.05; [*multiple-comparison adjustment if any*].

Results paragraph (copy-paste):

Transformers: Overview yielded [*estimate*] (95% CI [*lower, upper*], $p =$ [*value*]). [*Diagnostic / assumption summary*]. [*Sensitivity analysis result*].

Reviewer checklist for this method. → transformer-overview — For Reviewers

21.0.157 Truncated Regression

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Truncated Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Truncated Regression yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → truncated-regression — For Reviewers

21.0.158 Variable Importance

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Variable Importance** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Variable Importance yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → variable-importance — For Reviewers

21.0.159 Weighted Kappa

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Weighted Kappa** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Weighted Kappa yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → weighted-kappa — For Reviewers

21.0.160 Weighted Log-Rank Tests**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Weighted Log-Rank Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Weighted Log-Rank Tests yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → weighted-log-rank — For Reviewers

21.0.161 Worked lme4::lmer Examples**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **Worked lme4::lmer Examples** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Worked lme4::lmer Examples yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → lme4-lmer-examples — For Reviewers

21.0.162 XGBoost**Methods paragraph (copy-paste, fill in italics):**

[N=] participants/observations were analysed using **XGBoost** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

XGBoost yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `xgboost` — For Reviewers

21.0.163 Zero-Inflated Models

Methods paragraph (copy-paste, fill in italics):

[N=] participants/observations were analysed using **Zero-Inflated Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $= 0.05$; *[multiple-comparison adjustment if any]*.

Results paragraph (copy-paste):

Zero-Inflated Models yielded *[estimate]* (95% CI *[lower, upper]*, $p = [value]$). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

Reviewer checklist for this method. → `zero-inflated-models` — For Reviewers