

Facets and Panels

2026-04-17

Introduction

Small multiples — a grid of identical plots, one per subgroup — are one of the most powerful visualisation idioms in modern data analysis. They let the reader compare a relationship across many conditions without overlaying everything on a single set of axes, which becomes unreadable beyond three or four series. `ggplot2` calls this faceting and provides two complementary functions: `facet_wrap()` for a one-dimensional set of panels arranged into rows and columns, and `facet_grid()` for a strict row-by-column matrix indexed by two grouping variables.

Prerequisites

A working knowledge of `ggplot2`'s grammar of graphics, layered geoms, and the distinction between aesthetic mappings and faceting variables.

Theory

`facet_wrap(~ var)` partitions the data by `var`, creates one panel per level, and arranges them into a single block whose dimensions can be specified with `nrow` or `ncol`. `facet_grid(rows ~ cols)` produces a matrix of panels indexed by two variables, leaving an empty cell for combinations that have no data. Both functions share a `scales` argument controlling axis behaviour:

- "fixed" (default): all panels share x and y axes — the right choice when the comparative question is the headline.
- "free_x", "free_y", "free": each panel sets its own axis range — useful when scales differ enough that fixed axes hide structure within panels but at the cost of cross-panel comparability.

Strip labels (the panel headers) are themed via `labeller`; `label_both` combines variable name and level, `label_parsed` interprets the level as a math expression.

Assumptions

No statistical assumptions; faceting is a display convention. The only practical constraint is that the number of panels remains small enough to be readable at the final print size — usually no more than 9–12 panels per page.

R Implementation

```
library(ggplot2); library(palmerpenguins)
data(penguins)

# facet_wrap: one factor
ggplot(penguins, aes(flipper_length_mm, body_mass_g)) +
  geom_point(aes(colour = species), alpha = 0.7) +
  facet_wrap(~ sex) +
  theme_minimal()
```

```

# facet_grid: two factors (rows = island, cols = sex)
ggplot(penguins, aes(flipper_length_mm, body_mass_g)) +
  geom_point(aes(colour = species), alpha = 0.7) +
  facet_grid(island ~ sex) +
  theme_minimal()

# Free scales
ggplot(penguins, aes(flipper_length_mm, body_mass_g)) +
  geom_point(aes(colour = species), alpha = 0.7) +
  facet_wrap(~ species, scales = "free") +
  theme_minimal()

```

Output & Results

Three faceted views: a two-panel split by sex, a 3-by-3 grid by island and sex, and a three-panel split by species with free axes per panel. Each version answers a different question — “how does the relationship differ between sexes”, “across both island and sex”, or “what does it look like inside each species ignoring scale”.

Interpretation

A reporting sentence (figure caption): “Body mass against flipper length faceted by sex (`facet_wrap(~sex)`); colour distinguishes the three penguin species.” Always describe the faceting variable in the caption — readers should not have to infer the grid axis from strip labels alone.

Practical Tips

- Reach for `facet_wrap()` when there is one grouping variable; use `facet_grid()` only when the row/column structure is meaningful and balanced.
- Keep `scales = "fixed"` whenever the cross-panel comparison is the inferential focus; switch to free scales only when within-panel magnitudes differ enough to obscure shape.
- Limit the panel count: 9–12 is the practical upper bound on a journal-sized figure; beyond that, faceting fragments rather than illuminates.
- Use `labeller = labeller(var = c("M" = "Male", "F" = "Female"))` to spell out short factor levels for the reader.
- For aligned axes across `facet_wrap()` panels with very different ranges, fix one axis (`scales = "free_y"`) rather than freeing both — this preserves comparability where it matters.
- `coord_cartesian(xlim = ..., ylim = ...)` zooms while leaving the underlying data unfiltered; combine with `facet_grid()` when you want fixed-scale comparisons but with a tighter view than the natural data range.

R Packages Used

`ggplot2` for `facet_wrap()` and `facet_grid()`; `ggh4x` for nested facets and per-panel scale control; `palmerpenguins` as a small dataset rich in faceting structure for examples.

For Reviewers

What to look for in a paper using this method.

- Common misapplications.
- Diagnostics that should be reported but often aren’t.
- Red flags in tables and figures.
- What to verify.
- What an adequate Methods paragraph must contain.

See also — labs in this chapter

- `ggplot2` grammar and multi-panel layouts