

Deep Generative Models

Lecture 4

Roman Isachenko

Moscow Institute of Physics and Technology
Yandex School of Data Analysis

2024, Autumn

Recap of previous lecture

Forward KL for flow model

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \log p(\mathbf{f}_{\boldsymbol{\theta}}(\mathbf{x})) + \log |\det(\mathbf{J}_{\mathbf{f}})|$$

Reverse KL for flow model

$$KL(p||\pi) = \mathbb{E}_{p(\mathbf{z})} [\log p(\mathbf{z}) - \log |\det(\mathbf{J}_{\mathbf{g}})| - \log \pi(\mathbf{g}_{\boldsymbol{\theta}}(\mathbf{z}))]$$

Flow KL duality

$$\arg \min_{\boldsymbol{\theta}} KL(\pi(\mathbf{x})||p(\mathbf{x}|\boldsymbol{\theta})) = \arg \min_{\boldsymbol{\theta}} KL(p(\mathbf{z}|\boldsymbol{\theta})||p(\mathbf{z}))$$

- ▶ $p(\mathbf{z})$ is a base distribution; $\pi(\mathbf{x})$ is a data distribution;
- ▶ $\mathbf{z} \sim p(\mathbf{z})$, $\mathbf{x} = \mathbf{g}_{\boldsymbol{\theta}}(\mathbf{z})$, $\mathbf{x} \sim p(\mathbf{x}|\boldsymbol{\theta})$;
- ▶ $\mathbf{x} \sim \pi(\mathbf{x})$, $\mathbf{z} = \mathbf{f}_{\boldsymbol{\theta}}(\mathbf{x})$, $\mathbf{z} \sim p(\mathbf{z}|\boldsymbol{\theta})$.

Recap of previous lecture

Bayes theorem

$$p(\mathbf{t}|\mathbf{x}) = \frac{p(\mathbf{x}|\mathbf{t})p(\mathbf{t})}{p(\mathbf{x})} = \frac{p(\mathbf{x}|\mathbf{t})p(\mathbf{t})}{\int p(\mathbf{x}|\mathbf{t})p(\mathbf{t})d\mathbf{t}}$$

- ▶ \mathbf{x} – observed variables, \mathbf{t} – unobserved variables (latent variables/parameters);
- ▶ $p(\mathbf{x}|\mathbf{t})$ – likelihood;
- ▶ $p(\mathbf{x}) = \int p(\mathbf{x}|\mathbf{t})p(\mathbf{t})d\mathbf{t}$ – evidence;
- ▶ $p(\mathbf{t})$ – prior distribution, $p(\mathbf{t}|\mathbf{x})$ – posterior distribution.

Posterior distribution

$$p(\theta|\mathbf{X}) = \frac{p(\mathbf{X}|\theta)p(\theta)}{p(\mathbf{X})} = \frac{p(\mathbf{X}|\theta)p(\theta)}{\int p(\mathbf{X}|\theta)p(\theta)d\theta}$$

Recap of previous lecture

Latent variable models (LVM)

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta})d\mathbf{z} = \int p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})p(\mathbf{z})d\mathbf{z}.$$

MLE problem for LVM

$$\begin{aligned}\boldsymbol{\theta}^* &= \arg \max_{\boldsymbol{\theta}} \log p(\mathbf{X}|\boldsymbol{\theta}) = \arg \max_{\boldsymbol{\theta}} \sum_{i=1}^n \log p(\mathbf{x}_i|\boldsymbol{\theta}) = \\ &= \arg \max_{\boldsymbol{\theta}} \sum_{i=1}^n \log \int p(\mathbf{x}_i|\mathbf{z}_i, \boldsymbol{\theta})p(\mathbf{z}_i)d\mathbf{z}_i.\end{aligned}$$

Naive Monte-Carlo estimation

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})p(\mathbf{z})d\mathbf{z} = \mathbb{E}_{p(\mathbf{z})}p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) \approx \frac{1}{K} \sum_{k=1}^K p(\mathbf{x}|\mathbf{z}_k, \boldsymbol{\theta}),$$

where $\mathbf{z}_k \sim p(\mathbf{z})$.

Recap of previous lecture

ELBO derivation 1 (inequality)

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \log \int p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta}) d\mathbf{z} \geq \mathbb{E}_q \log \frac{p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta})}{q(\mathbf{z})} = \mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x})$$

ELBO derivation 2 (equality)

$$\begin{aligned}\mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x}) &= \int q(\mathbf{z}) \log \frac{p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta})}{q(\mathbf{z})} d\mathbf{z} = \int q(\mathbf{z}) \log \frac{p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta}) p(\mathbf{x}|\boldsymbol{\theta})}{q(\mathbf{z})} d\mathbf{z} = \\ &= \log p(\mathbf{x}|\boldsymbol{\theta}) - KL(q(\mathbf{z})||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta}))\end{aligned}$$

Variational decomposition

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x}) + KL(q(\mathbf{z})||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})) \geq \mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x}).$$

Recap of previous lecture

Variational lower Bound (ELBO)

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x}) + KL(q(\mathbf{z})||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})) \geq \mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x}).$$

$$\mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x}) = \int q(\mathbf{z}) \log \frac{p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta})}{q(\mathbf{z})} d\mathbf{z} = \mathbb{E}_q \log p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) - KL(q(\mathbf{z})||p(\mathbf{z}))$$

Log-likelihood decomposition

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \mathbb{E}_q \log p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) - KL(q(\mathbf{z})||p(\mathbf{z})) + KL(q(\mathbf{z})||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})).$$

- Instead of maximizing incomplete likelihood, maximize ELBO

$$\max_{\boldsymbol{\theta}} p(\mathbf{x}|\boldsymbol{\theta}) \rightarrow \max_{q,\boldsymbol{\theta}} \mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x})$$

- Maximization of ELBO by variational distribution q is equivalent to minimization of KL

$$\arg \max_q \mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x}) \equiv \arg \min_q KL(q(\mathbf{z})||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})).$$

Outline

1. EM-algorithm

Amortized inference

ELBO gradients, reparametrization trick

2. Variational autoencoder (VAE)

3. Normalizing flows as VAE model

4. Discrete VAE latent representations

Outline

1. EM-algorithm

Amortized inference

ELBO gradients, reparametrization trick

2. Variational autoencoder (VAE)

3. Normalizing flows as VAE model

4. Discrete VAE latent representations

Outline

1. EM-algorithm

Amortized inference

ELBO gradients, reparametrization trick

2. Variational autoencoder (VAE)

3. Normalizing flows as VAE model

4. Discrete VAE latent representations

Amortized variational inference

E-step

$$q(\mathbf{z}) = \arg \max_q \mathcal{L}_{q, \theta^*}(\mathbf{x}) = \arg \min_q KL(q || p) = p(\mathbf{z} | \mathbf{x}, \theta^*).$$

$q(\mathbf{z})$ approximates true posterior distribution $p(\mathbf{z} | \mathbf{x}, \theta^*)$, that is why it is called **variational posterior**.

- ▶ $p(\mathbf{z} | \mathbf{x}, \theta^*)$ could be **intractable**;
- ▶ $q(\mathbf{z})$ is different for each object \mathbf{x} .

Variational Bayes

Restrict a family of all possible distributions $q(\mathbf{z})$ to a parametric class $q(\mathbf{z} | \mathbf{x}, \phi)$ **conditioned on samples \mathbf{x} with parameters ϕ** .

- ▶ E-step

$$\phi_k = \phi_{k-1} + \eta \cdot \nabla_{\phi} \mathcal{L}_{\phi, \theta_{k-1}}(\mathbf{x}) \big|_{\phi=\phi_{k-1}}$$

- ▶ M-step

$$\theta_k = \theta_{k-1} + \eta \cdot \nabla_{\theta} \mathcal{L}_{\phi_k, \theta}(\mathbf{x}) \big|_{\theta=\theta_{k-1}}$$


Variational EM illustration

► E-step

$$\phi_k = \phi_{k-1} + \eta \nabla_{\phi} \mathcal{L}_{\phi, \theta_{k-1}}(\mathbf{x}) \Big|_{\phi=\phi_{k-1}}$$

► M-step

$$\theta_k = \theta_{k-1} + \eta \nabla_{\theta} \mathcal{L}_{\phi_k, \theta}(\mathbf{x}) \Big|_{\theta=\theta_{k-1}}$$



Variational EM-algorithm

ELBO

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \mathcal{L}_{\phi,\boldsymbol{\theta}}(\mathbf{x}) + KL(q(\mathbf{z}|\mathbf{x}, \phi)||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})) \geq \mathcal{L}_{\phi,\boldsymbol{\theta}}(\mathbf{x}).$$

$$\mathcal{L}_{q,\boldsymbol{\theta}}(\mathbf{x}) = \mathbb{E}_q \log p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) - KL(q(\mathbf{z}|\mathbf{x}, \phi)||p(\mathbf{z}))$$

► E-step

$$\phi_k = \phi_{k-1} + \eta \cdot \nabla_{\phi} \mathcal{L}_{\phi,\boldsymbol{\theta}_{k-1}}(\mathbf{x})|_{\phi=\phi_{k-1}},$$

where ϕ – parameters of the variational posterior distribution $q(\mathbf{z}|\mathbf{x}, \phi)$.

► M-step

$$\boldsymbol{\theta}_k = \boldsymbol{\theta}_{k-1} + \eta \cdot \nabla_{\boldsymbol{\theta}} \mathcal{L}_{\phi_k,\boldsymbol{\theta}}(\mathbf{x})|_{\boldsymbol{\theta}=\boldsymbol{\theta}_{k-1}},$$

where $\boldsymbol{\theta}$ – parameters of the generative distribution $p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})$.

Now all that is left is to obtain **unbiased** Monte Carlo estimates of the gradients: $\nabla_{\phi} \mathcal{L}_{\phi,\boldsymbol{\theta}}(\mathbf{x})$, $\nabla_{\boldsymbol{\theta}} \mathcal{L}_{\phi,\boldsymbol{\theta}}(\mathbf{x})$.

Outline

1. EM-algorithm

Amortized inference

ELBO gradients, reparametrization trick

2. Variational autoencoder (VAE)

3. Normalizing flows as VAE model

4. Discrete VAE latent representations

ELBO gradients, (M-step, $\nabla_{\theta} \mathcal{L}_{\phi, \theta}(\mathbf{x})$)

$$\mathcal{L}_{q, \theta}(\mathbf{x}) = \mathbb{E}_q \log p(\mathbf{x}|\mathbf{z}, \theta) - KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}))$$

M-step: $\nabla_{\theta} \mathcal{L}_{\phi, \theta}(\mathbf{x})$

$$\begin{aligned} \nabla_{\theta} \mathcal{L}_{\phi, \theta}(\mathbf{x}) &= \nabla_{\theta} \int q(\mathbf{z}|\mathbf{x}, \phi) \log p(\mathbf{x}|\mathbf{z}, \theta) d\mathbf{z} = \\ &= \int q(\mathbf{z}|\mathbf{x}, \phi) \nabla_{\theta} \log p(\mathbf{x}|\mathbf{z}, \theta) d\mathbf{z} \approx \\ &\approx \nabla_{\theta} \log p(\mathbf{x}|\mathbf{z}^*, \theta), \quad \mathbf{z}^* \sim q(\mathbf{z}|\mathbf{x}, \phi). \end{aligned}$$

Naive Monte-Carlo estimation

$$p(\mathbf{x}|\theta) = \int p(\mathbf{x}|\mathbf{z}, \theta) p(\mathbf{z}) d\mathbf{z} \approx \frac{1}{K} \sum_{k=1}^K p(\mathbf{x}|\mathbf{z}_k, \theta), \quad \mathbf{z}_k \sim p(\mathbf{z}).$$

The variational posterior $q(\mathbf{z}|\mathbf{x}, \phi)$ assigns typically more probability mass in a smaller region than the prior $p(\mathbf{z})$.

ELBO gradients, (E-step, $\nabla_{\phi} \mathcal{L}_{\phi, \theta}(\mathbf{x})$)

E-step: $\nabla_{\phi} \mathcal{L}_{\phi, \theta}(\mathbf{x})$

Difference from M-step: density function $q(\mathbf{z}|\mathbf{x}, \phi)$ depends on the parameters ϕ , it is impossible to use the Monte-Carlo estimation:

$$\begin{aligned}\nabla_{\phi} \mathcal{L}_{\phi, \theta}(\mathbf{x}) &= \nabla_{\phi} \int q(\mathbf{z}|\mathbf{x}, \phi) \log p(\mathbf{x}|\mathbf{z}, \theta) d\mathbf{z} - \nabla_{\phi} KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z})) \\ &\neq \int q(\mathbf{z}|\mathbf{x}, \phi) \nabla_{\phi} \log p(\mathbf{x}|\mathbf{z}, \theta) d\mathbf{z} - \nabla_{\phi} KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}))\end{aligned}$$

Reparametrization trick (LOTUS trick)

Suppose that $\mathbf{z} \sim q(\mathbf{z}|\mathbf{x}, \phi)$ is a random variable that is induced by the random variable $\epsilon \sim p(\epsilon)$ using the deterministic transform $\mathbf{z} = \mathbf{g}_{\phi}(\mathbf{x}, \epsilon)$. Then

$$\mathbb{E}_{\mathbf{z} \sim q(\mathbf{z}|\mathbf{x}, \phi)} \mathbf{f}(\mathbf{z}) = \mathbb{E}_{\epsilon \sim p(\epsilon)} \mathbf{f}(\mathbf{g}_{\phi}(\mathbf{x}, \epsilon))$$

Note that LHS takes the expectation by the parametric distribution $q(\mathbf{z}|\mathbf{x}, \phi)$ and the RHS uses non-parametric distribution $p(\epsilon)$.

ELBO gradients, (E-step, $\nabla_{\phi} \mathcal{L}_{\phi, \theta}(\mathbf{x})$)

Reparametrization trick (LOTUS trick)

$$\begin{aligned}\nabla_{\phi} \int q(\mathbf{z}|\mathbf{x}, \phi) \mathbf{f}(\mathbf{z}) d\mathbf{z} &= \nabla_{\phi} \int p(\epsilon) \mathbf{f}(\mathbf{g}_{\phi}(\mathbf{x}, \epsilon)) d\epsilon \\ &= \int p(\epsilon) \nabla_{\phi} \mathbf{f}(\mathbf{g}_{\phi}(\mathbf{x}, \epsilon)) d\epsilon \approx \nabla_{\phi} \mathbf{f}(\mathbf{g}_{\phi}(\mathbf{x}, \epsilon^*)),\end{aligned}$$

where $\epsilon^* \sim p(\epsilon)$.

Variational assumption

$$p(\epsilon) = \mathcal{N}(0, \mathbf{I}); \quad \mathbf{z} = \mathbf{g}_{\phi}(\mathbf{x}, \epsilon) = \sigma_{\phi}(\mathbf{x}) \odot \epsilon + \mu_{\phi}(\mathbf{x});$$

$$q(\mathbf{z}|\mathbf{x}, \phi) = \mathcal{N}(\mu_{\phi}(\mathbf{x}), \sigma_{\phi}^2(\mathbf{x})).$$

Here $\mu_{\phi}(\cdot)$, $\sigma_{\phi}(\cdot)$ are parameterized functions (outputs of neural network).

We will say that $q(\mathbf{z}|\mathbf{x}, \phi) = \text{NN}_e(\mathbf{x}, \phi)$ is the **encoder**.

ELBO gradient (E-step, $\nabla_{\phi} \mathcal{L}_{\phi, \theta}(\mathbf{x})$)

$$\nabla_{\phi} \mathcal{L}_{\phi, \theta}(\mathbf{x}) = \nabla_{\phi} \int q(\mathbf{z}|\mathbf{x}, \phi) \log p(\mathbf{x}|\mathbf{z}, \theta) d\mathbf{z} - \nabla_{\phi} KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}))$$

Reconstruction term

$$\begin{aligned} \nabla_{\phi} \int q(\mathbf{z}|\mathbf{x}, \phi) \log p(\mathbf{x}|\mathbf{z}, \theta) d\mathbf{z} &= \int p(\epsilon) \nabla_{\phi} \log p(\mathbf{x}|\mathbf{g}_{\phi}(\mathbf{x}, \epsilon), \theta) d\epsilon \approx \\ &\approx \nabla_{\phi} \log p(\mathbf{x}|\sigma_{\phi}(\mathbf{x}) \odot \epsilon^* + \mu_{\phi}(\mathbf{x}), \theta), \quad \text{where } \epsilon^* \sim \mathcal{N}(0, \mathbf{I}) \end{aligned}$$

Let the generative distribution $p(\mathbf{x}|\mathbf{z}, \theta)$ be the neural network.

We will say that $p(\mathbf{x}|\mathbf{z}, \theta) = \text{NN}_d(\mathbf{z}, \theta)$ is the **decoder**.

KL term

$p(\mathbf{z})$ is the prior distribution on the latent variables \mathbf{z} . Let assume $p(\mathbf{z}) = \mathcal{N}(0, \mathbf{I})$.

$$\nabla_{\phi} KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z})) = \nabla_{\phi} KL(\mathcal{N}(\mu_{\phi}(\mathbf{x}), \sigma_{\phi}^2(\mathbf{x})) || \mathcal{N}(0, \mathbf{I}))$$

This expression has analytical formula.

Outline

1. EM-algorithm

Amortized inference


ELBO gradients, reparametrization trick

2. Variational autoencoder (VAE)

3. Normalizing flows as VAE model

4. Discrete VAE latent representations

Generative models zoo



Variational autoencoder (VAE)

Final EM-algorithm

- ▶ pick random sample $\mathbf{x}_i, i \sim U[1, n]$.
- ▶ compute the objective:

$$\epsilon^* \sim r(\epsilon); \quad \mathbf{z}^* = \mathbf{g}_\phi(\mathbf{x}, \epsilon^*);$$

$$\mathcal{L}_{\phi, \theta}(\mathbf{x}) \approx \log p(\mathbf{x}|\mathbf{z}^*, \theta) - KL(q(\mathbf{z}^*|\mathbf{x}, \phi) || p(\mathbf{z}^*)).$$

- ▶ compute a stochastic gradients w.r.t. ϕ and θ

$$\nabla_\phi \mathcal{L}_{\phi, \theta}(\mathbf{x}) \approx \nabla_\phi \log p(\mathbf{x}|\mathbf{g}_\phi(\mathbf{x}, \epsilon^*), \theta) - \nabla_\phi KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}));$$

$$\nabla_\theta \mathcal{L}_{\phi, \theta}(\mathbf{x}) \approx \nabla_\theta \log p(\mathbf{x}|\mathbf{z}^*, \theta).$$


- ▶ update θ, ϕ according to the selected optimization method (SGD, Adam, etc):

$$\phi := \phi + \eta \cdot \nabla_\phi \mathcal{L}_{\phi, \theta}(\mathbf{x}),$$

$$\theta := \theta + \eta \cdot \nabla_\theta \mathcal{L}_{\phi, \theta}(\mathbf{x}).$$


Variational Autoencoder

$$\mathcal{L}_{\phi, \theta}(\mathbf{x}) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \left[\log p(\mathbf{x}|\mathbf{z}, \theta) - \log \frac{q(\mathbf{z}|\mathbf{x}, \phi)}{p(\mathbf{z})} \right] \rightarrow \max_{\phi, \theta}.$$




Variational autoencoder (VAE)

- ▶ Encoder $q(\mathbf{z}|\mathbf{x}, \phi) = \text{NN}_e(\mathbf{x}, \phi)$ outputs $\mu_\phi(\mathbf{x})$ and $\sigma_\phi(\mathbf{x})$.
- ▶ Decoder $p(\mathbf{x}|\mathbf{z}, \theta) = \text{NN}_d(\mathbf{z}, \theta)$ outputs parameters of the sample distribution.



Variational autoencoder (VAE)

- ▶ VAE learns stochastic mapping between \mathbf{x} -space, from complicated distribution $\pi(\mathbf{x})$, and a latent \mathbf{z} -space, with simple distribution.
- ▶ The generative model learns a joint distribution $p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta}) = p(\mathbf{z})p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})$, with a prior distribution $p(\mathbf{z})$, and a stochastic decoder $p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})$.
- ▶ The stochastic encoder $q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi})$ (inference model), approximates the true but intractable posterior $p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})$ of the generative model.



Outline

1. EM-algorithm

Amortized inference

ELBO gradients, reparametrization trick

2. Variational autoencoder (VAE)

3. Normalizing flows as VAE model

4. Discrete VAE latent representations

VAE vs Normalizing flows

	VAE	NF
Objective	ELBO \mathcal{L}	Forward KL/MLE
Encoder	stochastic $\mathbf{z} \sim q(\mathbf{z} \mathbf{x}, \phi)$	deterministic $\mathbf{z} = \mathbf{f}_{\theta}(\mathbf{x})$ $q(\mathbf{z} \mathbf{x}, \theta) = \delta(\mathbf{z} - \mathbf{f}_{\theta}(\mathbf{x}))$
Decoder	stochastic $\mathbf{x} \sim p(\mathbf{x} \mathbf{z}, \theta)$	deterministic $\mathbf{x} = \mathbf{g}_{\theta}(\mathbf{z})$ $p(\mathbf{x} \mathbf{z}, \theta) = \delta(\mathbf{x} - \mathbf{g}_{\theta}(\mathbf{z}))$
Parameters	ϕ, θ	$\theta \equiv \phi$

Theorem

MLE for normalizing flow is equivalent to maximization of ELBO for VAE model with deterministic encoder and decoder:

$$p(\mathbf{x}|\mathbf{z}, \theta) = \delta(\mathbf{x} - \mathbf{f}_{\theta}^{-1}(\mathbf{z})) = \delta(\mathbf{x} - \mathbf{g}_{\theta}(\mathbf{z}));$$

$$q(\mathbf{z}|\mathbf{x}, \theta) = p(\mathbf{z}|\mathbf{x}, \theta) = \delta(\mathbf{z} - \mathbf{f}_{\theta}(\mathbf{x})).$$

Normalizing flow as VAE

Proof

1. Dirac delta function property

$$\mathbb{E}_{\delta(\mathbf{x}-\mathbf{y})} \mathbf{f}(\mathbf{x}) = \int \delta(\mathbf{x}-\mathbf{y}) \mathbf{f}(\mathbf{x}) d\mathbf{x} = \mathbf{f}(\mathbf{y}).$$

2. CoV theorem and Bayes theorem:

$$p(\mathbf{x}|\boldsymbol{\theta}) = p(\mathbf{z}) |\det(\mathbf{J}_{\mathbf{f}})|;$$

$$p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta}) = \frac{p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) p(\mathbf{z})}{p(\mathbf{x}|\boldsymbol{\theta})}; \quad \Rightarrow \quad p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) = p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta}) |\det(\mathbf{J}_{\mathbf{f}})|.$$

3. Log-likelihood decomposition

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \mathcal{L}_{\boldsymbol{\theta}}(\mathbf{x}) + KL(q(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta}) || p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})) = \mathcal{L}_{\boldsymbol{\theta}}(\mathbf{x}).$$

Normalizing flow as VAE

Proof

ELBO objective:

$$\begin{aligned}\mathcal{L} &= \mathbb{E}_{q(\mathbf{z}|\mathbf{x},\theta)} \left[\log p(\mathbf{x}|\mathbf{z},\theta) - \log \frac{q(\mathbf{z}|\mathbf{x},\theta)}{p(\mathbf{z})} \right] \\ &= \mathbb{E}_{q(\mathbf{z}|\mathbf{x},\theta)} \left[\log \frac{p(\mathbf{x}|\mathbf{z},\theta)}{q(\mathbf{z}|\mathbf{x},\theta)} + \log p(\mathbf{z}) \right].\end{aligned}$$

1. Dirac delta function property:

$$\mathbb{E}_{q(\mathbf{z}|\mathbf{x},\theta)} \log p(\mathbf{z}) = \int \delta(\mathbf{z} - \mathbf{f}_\theta(\mathbf{x})) \log p(\mathbf{z}) d\mathbf{z} = \log p(\mathbf{f}_\theta(\mathbf{x})).$$

2. CoV theorem and Bayes theorem:

$$\mathbb{E}_{q(\mathbf{z}|\mathbf{x},\theta)} \log \frac{p(\mathbf{x}|\mathbf{z},\theta)}{q(\mathbf{z}|\mathbf{x},\theta)} = \mathbb{E}_{q(\mathbf{z}|\mathbf{x},\theta)} \log \frac{p(\mathbf{z}|\mathbf{x},\theta) |\det(\mathbf{J}_\mathbf{f})|}{q(\mathbf{z}|\mathbf{x},\theta)} = \log |\det \mathbf{J}_\mathbf{f}|.$$

3. Log-likelihood decomposition

$$\log p(\mathbf{x}|\theta) = \mathcal{L}_\theta(\mathbf{x}) = \log p(\mathbf{f}_\theta(\mathbf{x})) + \log |\det \mathbf{J}_\mathbf{f}|.$$

Outline

1. EM-algorithm

Amortized inference

ELBO gradients, reparametrization trick

2. Variational autoencoder (VAE)

3. Normalizing flows as VAE model

4. Discrete VAE latent representations

Discrete VAE latents

Motivation

- ▶ Previous VAE models had **continuous** latent variables \mathbf{z} .
- ▶ **Discrete** representations \mathbf{z} are potentially a more natural fit for many of the modalities.
- ▶ Powerful autoregressive models (like PixelCNN) have been developed for modelling distributions over discrete variables.
- ▶ All cool transformer-like models work with discrete tokens.

ELBO

$$\mathcal{L}_{\phi, \theta}(\mathbf{x}) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \log p(\mathbf{x}|\mathbf{z}, \theta) - KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z})) \rightarrow \max_{\phi, \theta}.$$

- ▶ Reparametrization trick to get unbiased gradients.
- ▶ Normal assumptions for $q(\mathbf{z}|\mathbf{x}, \phi)$ and $p(\mathbf{z})$ to compute KL analytically.

Discrete VAE latents

Assumptions

- ▶ Let $c \sim \text{Categorical}(\boldsymbol{\pi})$, where

$$\boldsymbol{\pi} = (\pi_1, \dots, \pi_K), \quad \pi_k = P(c = k), \quad \sum_{k=1}^K \pi_k = 1.$$

- ▶ Let VAE model has discrete latent representation c with prior $p(c) = \text{Uniform}\{1, \dots, K\}$.

ELBO


$$\mathcal{L}_{\phi, \theta}(\mathbf{x}) = \mathbb{E}_{q(c|\mathbf{x}, \phi)} \log p(\mathbf{x}|c, \theta) - \textcolor{brown}{KL}(q(c|\mathbf{x}, \phi) || p(c)) \rightarrow \max_{\phi, \theta}.$$

$$\begin{aligned} \textcolor{brown}{KL}(q(c|\mathbf{x}, \phi) || p(c)) &= \sum_{k=1}^K q(k|\mathbf{x}, \phi) \log \frac{q(k|\mathbf{x}, \phi)}{p(k)} = \\ &= \sum_{k=1}^K q(k|\mathbf{x}, \phi) \log q(k|\mathbf{x}, \phi) - \sum_{k=1}^K q(k|\mathbf{x}, \phi) \log p(k) = \\ &= -H(q(c|\mathbf{x}, \phi)) + \log K. \end{aligned}$$

Discrete VAE latents

$$\mathcal{L}_{\phi, \theta}(\mathbf{x}) = \mathbb{E}_{q(c|\mathbf{x}, \phi)} \log p(\mathbf{x}|c, \theta) + H(q(c|\mathbf{x}, \phi)) - \log K \rightarrow \max_{\phi, \theta}.$$

- ▶ Our encoder should output discrete distribution $q(c|\mathbf{x}, \phi)$.
- ▶ We need the analogue of the reparametrization trick for the discrete distribution $q(c|\mathbf{x}, \phi)$.
- ▶ Our decoder $p(\mathbf{x}|c, \theta)$ should input discrete random variable c .



Summary

- ▶ Amortized variational inference allows to efficiently compute the stochastic gradients for ELBO using Monte-Carlo estimation.
- ▶ The reparametrization trick gets unbiased gradients w.r.t to the variational posterior distribution $q(\mathbf{z}|\mathbf{x}, \phi)$.
- ▶ The VAE model is an LVM with two neural network: stochastic encoder $q(\mathbf{z}|\mathbf{x}, \phi)$ and stochastic decoder $p(\mathbf{x}|\mathbf{z}, \theta)$.
- ▶ NF models could be treated as VAE model with deterministic encoder and decoder.
- ▶ Discrete VAE representations is a natural form of latent variables.