

# Deep Generative Models

## Lecture 12

Roman Isachenko



AI Masters

2025, Spring

## Recap of previous lecture

$$\frac{d\mathbf{x}(t)}{dt} = \mathbf{f}_\theta(\mathbf{x}(t), t); \quad \text{with initial condition } \mathbf{x}(t_0) = \mathbf{x}_0$$

### Theorem (continuity equation)

If  $\mathbf{f}$  is uniformly Lipschitz continuous in  $\mathbf{x}$  and continuous in  $t$ , then

$$\frac{d \log p_t(\mathbf{x}(t))}{dt} = -\text{tr} \left( \frac{\partial \mathbf{f}(\mathbf{x}(t), t)}{\partial \mathbf{x}(t)} \right)$$

### Solution of continuity equation

$$\log p_1(\mathbf{x}(1)) = \log p_0(\mathbf{x}(0)) - \int_0^1 \text{tr} \left( \frac{\partial \mathbf{f}(\mathbf{x}(t), t)}{\partial \mathbf{x}(t)} \right) dt.$$

- ▶ This solution will give us the density along the trajectory (not the total probability path).
- ▶ But it is difficult to estimate **the last term** efficiently.

# Recap of previous lecture

## SDE basics

Let define stochastic process  $\mathbf{x}(t)$  with initial condition  $\mathbf{x}(0) \sim p_0(\mathbf{x})$ :

$$d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt + g(t)d\mathbf{w},$$

where  $\mathbf{w}(t)$  is the standard Wiener process (Brownian motion)

$\mathbf{w}(t) - \mathbf{w}(s) \sim \mathcal{N}(0, (t - s)\mathbf{I})$ ,  $d\mathbf{w} = \epsilon \cdot \sqrt{dt}$ , where  $\epsilon \sim \mathcal{N}(0, \mathbf{I})$ .

## Discretization of SDE (Euler method) - SDEsolve

$$\mathbf{x}(t + dt) = \mathbf{x}(t) + \mathbf{f}(\mathbf{x}(t), t) \cdot dt + g(t) \cdot \epsilon \cdot \sqrt{dt}$$

- ▶ At each moment  $t$  we have the density  $p_t(\mathbf{x}) = p(\mathbf{x}, t)$ .
- ▶  $p : \mathbb{R}^m \times [0, 1] \rightarrow \mathbb{R}_+$  is a **probability path** between  $p_0(\mathbf{x})$  and  $p_1(\mathbf{x})$ .

## Recap of previous lecture

### Theorem (Kolmogorov-Fokker-Planck)

Evolution of the distribution  $p_t(\mathbf{x})$  is given by the following equation:

$$\frac{\partial p_t(\mathbf{x})}{\partial t} = -\operatorname{div}(\mathbf{f}(\mathbf{x}, t)p_t(\mathbf{x})) + \frac{1}{2}g^2(t)\Delta_{\mathbf{x}}p_t(\mathbf{x})$$

### Langevin SDE (special case)

$$d\mathbf{x} = \frac{1}{2} \frac{\partial}{\partial \mathbf{x}} \log p_t(\mathbf{x}) dt + \mathbf{1} \cdot d\mathbf{w}$$

The density  $p(\mathbf{x}|\boldsymbol{\theta})$  is a **stationary** distribution for the SDE.

### Langevin dynamics

Samples from the following dynamics will come from  $p(\mathbf{x}|\boldsymbol{\theta})$  under mild regularity conditions for small enough  $\eta$ .

$$\mathbf{x}_{t+1} = \mathbf{x}_t + \frac{\eta}{2} \nabla_{\mathbf{x}_t} \log p(\mathbf{x}_t|\boldsymbol{\theta}) + \sqrt{\eta} \cdot \boldsymbol{\epsilon}, \quad \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}).$$


## Recap of previous lecture

$d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt + g(t)d\mathbf{w}$  – SDE with the probability path  $p_t(\mathbf{x})$

### Probability flow ODE

There exists ODE with identical the probability path  $p_t(\mathbf{x})$  of the form

$$d\mathbf{x} = \left( \mathbf{f}(\mathbf{x}, t) - \frac{1}{2}g^2(t)\frac{\partial}{\partial \mathbf{x}} \log p_t(\mathbf{x}) \right) dt$$



Song Y., et al. *Score-Based Generative Modeling through Stochastic Differential Equations*, 2020

## Recap of previous lecture

$$d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt, \quad \mathbf{x}(t + dt) = \mathbf{x}(t) + \mathbf{f}(\mathbf{x}, t)dt$$

### Reverse ODE

Let  $\tau = 1 - t$  ( $d\tau = -dt$ ).

$$d\mathbf{x} = -\mathbf{f}(\mathbf{x}, 1 - \tau)d\tau$$

### Reverse SDE

There exists the reverse SDE for the SDE  $d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt + g(t)d\mathbf{w}$  that has the following form

$$d\mathbf{x} = \left( \mathbf{f}(\mathbf{x}, t) - g^2(t) \frac{\partial}{\partial \mathbf{x}} \log p_t(\mathbf{x}) \right) dt + g(t)d\mathbf{w}, \quad dt < 0$$

### Sketch of the proof


- ▶ Convert initial SDE to probability flow ODE.
- ▶ Revert probability flow ODE.
- ▶ Convert reverse probability flow ODE to reverse SDE.

# Recap of previous lecture

$$d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt + g(t)d\mathbf{w} - \text{SDE}$$

$$d\mathbf{x} = \left( \mathbf{f}(\mathbf{x}, t) - \frac{1}{2}g^2(t)\frac{\partial}{\partial \mathbf{x}} \log p_t(\mathbf{x}) \right) dt - \text{probability flow ODE}$$

$$d\mathbf{x} = \left( \mathbf{f}(\mathbf{x}, t) - g^2(t)\frac{\partial}{\partial \mathbf{x}} \log p_t(\mathbf{x}) \right) dt + g(t)d\mathbf{w} - \text{reverse SDE}$$



# Outline

1. Diffusion and Score matching SDEs
2. Score-based generative models through SDEs
3. Flow Matching
4. Conditional Flow Matching



# Outline

1. Diffusion and Score matching SDEs
2. Score-based generative models through SDEs
3. Flow Matching
4. Conditional Flow Matching

# Score matching SDE

## Denoising score matching

$$\mathbf{x}_t = \mathbf{x} + \sigma_t \cdot \epsilon_t, \quad q(\mathbf{x}_t | \mathbf{x}) = \mathcal{N}(\mathbf{x}, \sigma_t^2 \cdot \mathbf{I})$$

$$\mathbf{x}_{t-1} = \mathbf{x} + \sigma_{t-1} \cdot \epsilon_{t-1}, \quad q(\mathbf{x}_{t-1} | \mathbf{x}) = \mathcal{N}(\mathbf{x}, \sigma_{t-1}^2 \cdot \mathbf{I})$$

$$\mathbf{x}_t = \mathbf{x}_{t-1} + \sqrt{\sigma_t^2 - \sigma_{t-1}^2} \cdot \epsilon, \quad q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \mathcal{N}(\mathbf{x}_{t-1}, (\sigma_t^2 - \sigma_{t-1}^2) \cdot \mathbf{I})$$

Let turn this Markov chain to the continuous stochastic process  $\mathbf{x}(t)$  taking  $T \rightarrow \infty$ :

$$\begin{aligned} \mathbf{x}(t) &= \mathbf{x}(t - dt) + \sqrt{\sigma^2(t) - \sigma^2(t - dt)} \cdot \epsilon \\ &= \mathbf{x}(t - dt) + \sqrt{\frac{\sigma^2(t) - \sigma^2(t - dt)}{dt}} dt \cdot \epsilon \\ &= \mathbf{x}(t - dt) + \sqrt{\frac{d[\sigma^2(t)]}{dt}} \cdot d\mathbf{w} \end{aligned}$$

# Score matching SDE

$$\mathbf{x}(t) = \mathbf{x}(t - dt) + \sqrt{\frac{d[\sigma^2(t)]}{dt}} \cdot d\mathbf{w}$$

## Variance Exploding SDE

$$d\mathbf{x} = \sqrt{\frac{d[\sigma^2(t)]}{dt}} \cdot d\mathbf{w}$$

$\sigma(t)$  is a monotonically increasing function.

$$d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt + g(t)d\mathbf{w}, \quad \mathbf{f}(\mathbf{x}, t) = 0, \quad g(t) = \sqrt{\frac{d[\sigma^2(t)]}{dt}}$$

$$d\mathbf{x} = \left( -\frac{1}{2} \frac{d[\sigma^2(t)]}{dt} \frac{\partial}{\partial \mathbf{x}} \log p_t(\mathbf{x}) \right) dt - \text{probability flow ODE}$$

$$d\mathbf{x} = \left( -\frac{d[\sigma^2(t)]}{dt} \frac{\partial}{\partial \mathbf{x}} \log p_t(\mathbf{x}) \right) dt + \sqrt{\frac{d[\sigma^2(t)]}{dt}} d\mathbf{w} - \text{reverse SDE}$$

# Diffusion SDE

## Denoising Diffusion

$$\mathbf{x}_t = \sqrt{1 - \beta_t} \cdot \mathbf{x}_{t-1} + \sqrt{\beta_t} \cdot \epsilon, \quad q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \mathcal{N}(\sqrt{1 - \beta_t} \cdot \mathbf{x}_{t-1}, \beta_t \cdot \mathbf{I})$$

Let turn this Markov chain to the continuous stochastic process taking  $T \rightarrow \infty$  and taking  $\beta_t = \beta(\frac{t}{T}) \cdot \frac{1}{T}$  (with  $dt = \frac{1}{T}$ )

$$\begin{aligned} \mathbf{x}(t) &= \sqrt{1 - \beta(t)dt} \cdot \mathbf{x}(t - dt) + \sqrt{\beta(t)dt} \cdot \epsilon \approx \\ &\approx (1 - \frac{1}{2}\beta(t)dt) \cdot \mathbf{x}(t - dt) + \sqrt{\beta(t)dt} \cdot \epsilon = \\ &= \mathbf{x}(t - dt) - \frac{1}{2}\beta(t)\mathbf{x}(t - dt)dt + \sqrt{\beta(t)} \cdot d\mathbf{w} \end{aligned}$$

## Variance Preserving SDE

$$d\mathbf{x} = -\frac{1}{2}\beta(t)\mathbf{x}(t)dt + \sqrt{\beta(t)} \cdot d\mathbf{w}$$

# Diffusion SDE

## Variance Preserving SDE

$$d\mathbf{x} = -\frac{1}{2}\beta(t)\mathbf{x}(t)dt + \sqrt{\beta(t)} \cdot d\mathbf{w}$$

$$\mathbf{f}(\mathbf{x}, t) = -\frac{1}{2}\beta(t)\mathbf{x}(t), \quad g(t) = \sqrt{\beta(t)}$$

Variance is preserved if  $\mathbf{x}(0)$  has a unit variance.

$$d\mathbf{x} = \left( -\frac{1}{2}\beta(t)\mathbf{x}(t) - \frac{1}{2}\beta(t)\frac{\partial}{\partial\mathbf{x}} \log p_t(\mathbf{x}) \right) dt - \text{probability flow ODE}$$

$$d\mathbf{x} = \left( -\frac{1}{2}\beta(t)\mathbf{x}(t) - \beta(t)\frac{\partial}{\partial\mathbf{x}} \log p_t(\mathbf{x}) \right) dt + \sqrt{\beta(t)}d\mathbf{w} - \text{reverse SDE}$$

# Diffusion SDE

$$d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt + g(t)d\mathbf{w}$$

## Variance Exploding SDE (NCSN)

$$d\mathbf{x} = \sqrt{\frac{d[\sigma^2(t)]}{dt}} \cdot d\mathbf{w}$$

## Variance Preserving SDE (DDPM)

$$d\mathbf{x} = -\frac{1}{2}\beta(t)\mathbf{x}(t)dt + \sqrt{\beta(t)} \cdot d\mathbf{w}$$

## Efficient Solvers

- ▶ Converting SDEs to PF-ODEs gives us the more efficient inference.
- ▶ We can apply any ODESolve procedure to reduce the number of inference steps.
- ▶ In practice it reduces from 100-1000 steps to 20-50 steps.

---

Lu C. et al. *Dpm-solver: A fast ode solver for diffusion probabilistic model sampling in around 10 steps*, 2022

# Outline

1. Diffusion and Score matching SDEs
2. Score-based generative models through SDEs
3. Flow Matching
4. Conditional Flow Matching

# Score-based generative models through SDEs


## Discrete-in-time objective

$$\mathbb{E}_{\pi(\mathbf{x}_0)} \mathbb{E}_{t \sim U\{1, T\}} \mathbb{E}_{q(\mathbf{x}_t | \mathbf{x}_0)} \left\| \mathbf{s}_{\theta, t}(\mathbf{x}_t) - \nabla_{\mathbf{x}_t} \log q(\mathbf{x}_t | \mathbf{x}_0) \right\|_2^2$$

Is it possible to train score-based diffusion in continuous time?

## Continuous-in-time objective

$$\mathbb{E}_{\pi(\mathbf{x}(0))} \mathbb{E}_{t \sim U[0, 1]} \mathbb{E}_{q(\mathbf{x}(t) | \mathbf{x}(0))} \left\| \mathbf{s}_{\theta}(\mathbf{x}(t), t) - \nabla_{\mathbf{x}(t)} \log q(\mathbf{x}(t) | \mathbf{x}(0)) \right\|_2^2$$





# Score-based generative models through SDEs

## Continuous-in-time objective

$$\mathbb{E}_{\pi(\mathbf{x}(0))} \mathbb{E}_{t \sim U[0,1]} \mathbb{E}_{q(\mathbf{x}(t)|\mathbf{x}(0))} \left\| \mathbf{s}_{\theta}(\mathbf{x}(t), t) - \nabla_{\mathbf{x}(t)} \log q(\mathbf{x}(t)|\mathbf{x}(0)) \right\|_2^2$$

$$q(\mathbf{x}(t)|\mathbf{x}(0)) = \mathcal{N}\left(\boldsymbol{\mu}(\mathbf{x}(t), \mathbf{x}(0)), \boldsymbol{\sigma}^2(\mathbf{x}(t), \mathbf{x}(0)) \cdot \mathbf{I}\right)$$

$$\nabla_{\mathbf{x}(t)} \log q(\mathbf{x}(t)|\mathbf{x}(0)) = -\frac{1}{\boldsymbol{\sigma}} \odot (\mathbf{x}(t) - \boldsymbol{\mu})$$

$$d\mathbf{x} = \sqrt{\frac{d[\sigma^2(t)]}{dt}} \cdot d\mathbf{w} - \text{Variance Exploding SDE}$$

$$d\mathbf{x} = -\frac{1}{2}\beta(t)\mathbf{x}(t)dt + \sqrt{\beta(t)} \cdot d\mathbf{w} - \text{Variance Preserving SDE}$$

Is it possible to derive the expressions for  $\boldsymbol{\mu}(\mathbf{x}(t), \mathbf{x}(0))$  and  $\boldsymbol{\Sigma}(\mathbf{x}(t), \mathbf{x}(0))$  for VE-SDE and VP-SDE?

# Score-based generative models through SDEs

$$q(\mathbf{x}(t)|\mathbf{x}(0)) = \mathcal{N}\left(\boldsymbol{\mu}(\mathbf{x}(t), \mathbf{x}(0)), \boldsymbol{\Sigma}(\mathbf{x}(t), \mathbf{x}(0))\right)$$

## Theorem

Moments of the SDE  $d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt + g(t)d\mathbf{w}$  satisfies the equations

$$\frac{d\boldsymbol{\mu}(\mathbf{x}(t), \mathbf{x}(0))}{dt} = \mathbb{E}[\mathbf{f}(\mathbf{x}(t), t)|\mathbf{x}(0)]$$

$$\frac{d\boldsymbol{\Sigma}(\mathbf{x}(t), \mathbf{x}(0))}{dt} = \mathbb{E}\left[\mathbf{f} \cdot (\mathbf{x}(t) - \boldsymbol{\mu})^T + (\mathbf{x}(t) - \boldsymbol{\mu}) \cdot \mathbf{f}^T | \mathbf{x}(0)\right] + g^2(t) \cdot \mathbf{I}$$

## Proof

$$\begin{aligned}\mathbb{E}[d\mathbf{x}|\mathbf{x}(0)] &= \mathbb{E}[\mathbf{f}(\mathbf{x}, t)dt|\mathbf{x}(0)] + \mathbb{E}[g(t)d\mathbf{w}|\mathbf{x}(0)] \\ &= \mathbb{E}[\mathbf{f}(\mathbf{x}, t)|\mathbf{x}(0)] dt + g(t)\mathbb{E}[d\mathbf{w}|\mathbf{x}(0)] \\ &= \mathbb{E}[\mathbf{f}(\mathbf{x}, t)|\mathbf{x}(0)] dt\end{aligned}$$

# Score-based generative models through SDEs

## Theorem

$$\frac{d\mu(\mathbf{x}(t), \mathbf{x}(0))}{dt} = \mathbb{E} [\mathbf{f}(\mathbf{x}(t), t) | \mathbf{x}(0)]$$

## Proof (continued)

$$\begin{aligned}\mathbb{E} [d\mathbf{x} | \mathbf{x}(0)] &= \mathbb{E} [\mathbf{f}(\mathbf{x}, t) | \mathbf{x}(0)] dt \\ \frac{d\mathbb{E} [\mathbf{x}(t) | \mathbf{x}(0)]}{dt} &= \frac{d\mu(\mathbf{x}(t), \mathbf{x}(0))}{dt} = \mathbb{E} [\mathbf{f}(\mathbf{x}, t) | \mathbf{x}(0)]\end{aligned}$$

## Examples

$$\text{NCSN: } \mathbf{f}(\mathbf{x}, t) = 0 \quad \Rightarrow \quad \mu = \mathbf{x}(0)$$

$$\text{DDPM: } \mathbf{f}(\mathbf{x}, t) = -\frac{1}{2}\beta(t)\mathbf{x}(t) \quad \Rightarrow \quad \frac{d\mu}{dt} = -\frac{1}{2}\beta(t)\mu$$

$$\mu = \mathbf{x}(0) \exp \left( -\frac{1}{2} \int_0^t \beta(s) ds \right)$$

# Score-based generative models through SDEs

## Training

$$\mathbb{E}_{\pi(\mathbf{x}(0))} \mathbb{E}_{t \sim U[0,1]} \mathbb{E}_{q(\mathbf{x}(t)|\mathbf{x}(0))} \left\| \mathbf{s}_{\theta}(\mathbf{x}(t), t) - \nabla_{\mathbf{x}(t)} \log q(\mathbf{x}(t)|\mathbf{x}(0)) \right\|_2^2$$

$$q(\mathbf{x}(t)|\mathbf{x}(0)) = \mathcal{N}\left(\boldsymbol{\mu}(\mathbf{x}(t), \mathbf{x}(0)), \boldsymbol{\Sigma}(\mathbf{x}(t), \mathbf{x}(0))\right)$$

## NCSN

$$q(\mathbf{x}(t)|\mathbf{x}(0)) = \mathcal{N}\left(\mathbf{x}(0), [\sigma^2(t) - \sigma^2(0)] \cdot \mathbf{I}\right)$$

## DDPM


$$q(\mathbf{x}(t)|\mathbf{x}(0)) = \mathcal{N}\left(\mathbf{x}(0)e^{-\frac{1}{2} \int_0^t \beta(s) ds}, \left(1 - e^{-\int_0^t \beta(s) ds}\right) \cdot \mathbf{I}\right)$$

Here we omit the derivations of the variance.

# Score-based generative models through SDEs

## Sampling

Solve reverse SDE using numerical solvers (SDEsolve).



- ▶ Discretization of the reverse SDE gives us the ancestral sampling.
- ▶ Discretization of the probability flow ODE gives us deterministic sampling.

# Outline

1. Diffusion and Score matching SDEs
2. Score-based generative models through SDEs
3. Flow Matching
4. Conditional Flow Matching

## Continuous-in-time NF

Let return to the ODE dynamic  $\mathbf{x}(t)$  in time interval  $t \in [0, 1]$

- ▶  $\mathbf{x}_0 \sim p_0(\mathbf{x}) = p(\mathbf{x})$ ,  $\mathbf{x}_1 \sim p_1(\mathbf{x}) = \pi(\mathbf{x})$ ;
- ▶  $p(\mathbf{x})$  is a base distribution ( $\mathcal{N}(0, \mathbf{I})$ ) and  $\pi(\mathbf{x})$  is a true data distribution.

$$\frac{d\mathbf{x}}{dt} = \mathbf{f}(\mathbf{x}, t), \quad \text{with initial condition } \mathbf{x}(0) = \mathbf{x}_0.$$

### KFP theorem (continuity equation)

$$\frac{\partial p_t(\mathbf{x})}{\partial t} = -\text{div}(\mathbf{f}(\mathbf{x}, t)p_t(\mathbf{x})) \Leftrightarrow \frac{d \log p_t(\mathbf{x}(t))}{dt} = -\text{tr} \left( \frac{\partial \mathbf{f}(\mathbf{x}(t), t)}{\partial \mathbf{x}(t)} \right)$$

- ▶ It is hard to solve continuity equation directly because of the trace part.
- ▶ There is a method (called adjoint method) that solves this equation directly, but it is unstable and not scalable.

# Continuous-in-time NF

## KFP theorem (continuity equation)

$$\frac{\partial p_t(\mathbf{x})}{\partial t} = -\operatorname{div}(\mathbf{f}(\mathbf{x}, t)p_t(\mathbf{x})) \Leftrightarrow \frac{d \log p_t(\mathbf{x}(t))}{dt} = -\operatorname{tr}\left(\frac{\partial \mathbf{f}(\mathbf{x}(t), t)}{\partial \mathbf{x}(t)}\right)$$

- ▶ If we know the vector field  $\mathbf{f}(\mathbf{x}, t)$ , then KFP (or continuity) equation gives us the way to compute the density  $p_t(\mathbf{x})$ .
- ▶ Flow matching gives the alternative way to solve the NeuralODE.

## Flow Matching

$$\mathbb{E}_{t \sim U[0,1]} \mathbb{E}_{\mathbf{x} \sim p_t(\mathbf{x})} \|\mathbf{f}(\mathbf{x}, t) - \mathbf{f}_\theta(\mathbf{x}, t)\|^2 \rightarrow \min_{\theta}$$


- ▶ Approximate the true vector field  $\mathbf{f}(\mathbf{x}, t)$  via  $\mathbf{f}_\theta(\mathbf{x}, t)$ .
- ▶ Use  $\mathbf{f}_\theta(\mathbf{x}, t)$  for deterministic sampling from the ODE.



# Flow Matching

$$\mathbb{E}_{t \sim U[0,1]} \mathbb{E}_{\mathbf{x} \sim p_t(\mathbf{x})} \|\mathbf{f}(\mathbf{x}, t) - \mathbf{f}_\theta(\mathbf{x}, t)\|^2 \rightarrow \min_{\theta}$$

- ▶ There exists infinite number of possible  $\mathbf{f}(\mathbf{x}, t)$  between  $\pi(\mathbf{x})$  and  $p(\mathbf{x})$ .
- ▶ The true vector field  $\mathbf{f}(\mathbf{x}, t)$  is **unknown**.
- ▶ We need to select the "best"  $\mathbf{f}(\mathbf{x}, t)$  and makes the objective tractable.



# Outline

1. Diffusion and Score matching SDEs
2. Score-based generative models through SDEs
3. Flow Matching
4. Conditional Flow Matching

# Flow Matching

## Latent variable model

Let introduce the latent variable  $\mathbf{z}$ :

$$p_t(\mathbf{x}) = \int p_t(\mathbf{x}|\mathbf{z})p(\mathbf{z})d\mathbf{z}$$

Here  $p_t(\mathbf{x}|\mathbf{z})$  is a **conditional probability path**.

The conditional probability path  $p_t(\mathbf{x}|\mathbf{z})$  satisfies KFP theorem

$$\frac{\partial p_t(\mathbf{x}|\mathbf{z})}{\partial t} = -\text{div}(\mathbf{f}(\mathbf{x}, \mathbf{z}, t)p_t(\mathbf{x}|\mathbf{z})),$$

where  $\mathbf{f}(\mathbf{x}, \mathbf{z}, t)$  is a **conditional vector field**.

$$\frac{d\mathbf{x}}{dt} = \mathbf{f}(\mathbf{x}, t) \quad \Rightarrow \quad \frac{d\mathbf{x}}{dt} = \mathbf{f}(\mathbf{x}, \mathbf{z}, t)$$

What is the relationship between  $\mathbf{f}(\mathbf{x}, t)$  and  $\mathbf{f}(\mathbf{x}, \mathbf{z}, t)$ ?

---

*Tong A., et al. Improving and Generalizing Flow-Based Generative Models with Minibatch Optimal Transport, 2023*

# Flow Matching

$$\frac{\partial p_t(\mathbf{x}|\mathbf{z})}{\partial t} = -\text{div}(\mathbf{f}(\mathbf{x}, \mathbf{z}, t)p_t(\mathbf{x}|\mathbf{z})),$$

## Theorem

The following vector field generates the probability path  $p_t(\mathbf{x})$ .

$$\mathbf{f}(\mathbf{x}, t) = \mathbb{E}_{p_t(\mathbf{z}|\mathbf{x})} \mathbf{f}(\mathbf{x}, \mathbf{z}, t) = \int \mathbf{f}(\mathbf{x}, \mathbf{z}, t) \frac{p_t(\mathbf{x}|\mathbf{z})p(\mathbf{z})}{p_t(\mathbf{x})} d\mathbf{z}$$

## Proof

$$\begin{aligned} \frac{\partial p_t(\mathbf{x})}{\partial t} &= \frac{\partial}{\partial t} \int p_t(\mathbf{x}|\mathbf{z})p(\mathbf{z})d\mathbf{z} = \int \left( \frac{\partial p_t(\mathbf{x}|\mathbf{z})}{\partial t} \right) p(\mathbf{z})d\mathbf{z} = \\ &= \int (-\text{div}(\mathbf{f}(\mathbf{x}, \mathbf{z}, t)p_t(\mathbf{x}|\mathbf{z}))) p(\mathbf{z})d\mathbf{z} = \\ &= -\text{div} \left( \int \mathbf{f}(\mathbf{x}, \mathbf{z}, t)p_t(\mathbf{x}|\mathbf{z})p(\mathbf{z})d\mathbf{z} \right) = -\text{div}(\mathbf{f}(\mathbf{x}, t)p_t(\mathbf{x})) \end{aligned}$$

# Flow Matching

## Flow Matching (FM)

$$\mathbb{E}_{t \sim U[0,1]} \mathbb{E}_{\mathbf{x} \sim p_t(\mathbf{x})} \|\mathbf{f}(\mathbf{x}, t) - \mathbf{f}_\theta(\mathbf{x}, t)\|^2 \rightarrow \min_{\theta}$$

## Conditional Flow Matching (CFM)

$$\mathbb{E}_{t \sim U[0,1]} \mathbb{E}_{\mathbf{z} \sim p(\mathbf{z})} \mathbb{E}_{\mathbf{x} \sim p_t(\mathbf{x}|\mathbf{z})} \|\mathbf{f}(\mathbf{x}, \mathbf{z}, t) - \mathbf{f}_\theta(\mathbf{x}, t)\|^2 \rightarrow \min_{\theta}$$


## Theorem

If  $\text{supp}(p_t(\mathbf{x})) = \mathbb{R}^m$ , then the optimal value of FM objective is equal to the optimal value of CFM objective.

## Proof

It is proved similarly with the denoising score matching theorem.

# Conditional Flow Matching



- ▶ We do not want to model  $p_t(\mathbf{x})$  because it is complex.
- ▶ We showed that it is possible to solve CFM task instead of FM task.
- ▶ Let choose the convenient conditioning latent variable  $\mathbf{z}$ .
- ▶ Let parametrize  $p_t(\mathbf{x}|\mathbf{z})$  instead of  $p_t(\mathbf{x})$ . It must satisfy the following constraints

$$p(\mathbf{x}) = \mathcal{N}(0, \mathbf{I}) = \mathbb{E}_{p(\mathbf{z})} p_0(\mathbf{x}|\mathbf{z}); \quad \pi(\mathbf{x}) = \mathbb{E}_{p(\mathbf{z})} p_1(\mathbf{x}|\mathbf{z}).$$

# Summary

- ▶ Score matching (NCSN) and diffusion models (DDPM) are the discretizations of the SDEs (variance exploding and variance preserving).
- ▶ It is possible to train the continuous-in-time score-based generative models through forward and reverse SDEs.
- ▶ Discretization of the reverse SDE gives the ancestral sampling of the DDPM.
- ▶ Flow matching suggests to fit the vector field directly.
- ▶ Conditional flow matching introduces the latent variable  $\mathbf{z}$  to reformulate the initial task in terms of conditional dynamics.