

Assignment 1, COMP4702

Roy Portas

March 27, 2017

Question 1.2

The first column of the data is the date, the second column appears to be a unique ID for each entry.

The third column contains numbers between 25 and 30, this is possibly a temperature in degrees. The values also change gradually which seems correct for the given time intervals

The fourth column contains numbers between 26 and around 50000. If this is plotted against the ID field, it produces a line.

The fifth column contains numbers between 7.3 and 8.3, with a mean of 7.846 and a standard StdDev of 0.142. This suggests that the value doesn't change much.

It could possibly be weather data, containing temperature, humidity, etc.

Question 1.6

```
1 % in is the input array
2 % n is the group size
3 function out = q6(in, n)
4
5     out = [];
6
7     chunks = length(in)/n;
8
9     for i = 1:chunks
10         end_ind = length(in) - i * n + n;
11
12         start_ind = end_ind - n + 1;
13         start_ind = max([1, start_ind]);
14
15         temp = in(start_ind:end_ind);
16
17         out = [out, temp];
18     end
19
20 end
```

Question 2.1




Figure 1: Lines of best fit




Figure 2: Error vs Polynomial Degree

The above figure shows that as more polynomial degrees are introduced the error on the testing data decreases, which is expected as this was the data the model was trained on.

However the error on the validation data increases after the 7th polynomial, thus we are overfitting the data.

Question 2.4

```
1 function q4(data, class)
2     class_names = unique(class);
3     x_values = 1:length(class);
4
5     class1 = zeros(1, length(class));
6     class2 = zeros(1, length(class));
7
8     for i = x_values
9         if strcmp(class{i}, class_names{1})
10             class1(i) = 1;
11         else
12             class2(i) = 1;
13         end
14     end
15
16     % Verify the classes are correct
17     % figure;
18     % hold on;
19     % scatter(1:length(class1), class1);
20     % scatter(1:length(class2), class2);
21     % hold off;
22
23     estimate_range = 1:0.1:8;
24
25     class1_data = data;
26     class1_data(class2 == 1) = NaN;
27
28     class1_mle = mle(class1_data);
29     class1_pdf = normpdf(estimate_range, class1_mle(1), class1_mle
30         (2));
31
32     class2_data = data;
33     class2_data(class1 == 1) = NaN;
34
35     class2_mle = mle(class2_data);
36     class2_pdf = normpdf(estimate_range, class2_mle(1), class2_mle
37         (2));
```

```

38 % figure;
39
40 % scatter(x_values , data);
41
42 % Verify the classes are divided
43 figure;
44
45 hold on;
46
47 yyaxis left;
48 scatter(class1_data , x_values , 'r');
49 scatter(class2_data , x_values , 'b');
50
51 yyaxis right;
52 plot(estimate_range , class1_pdf , 'r');
53 plot(estimate_range , class2_pdf , 'b');
54 legend('Iris Setosa', 'Iris Versicolor');
55 hold off;
56
57 % Plot the likelihood
58 figure;
59 hold on;
60 plot(estimate_range , class1_pdf);
61 plot(estimate_range , class2_pdf);
62 xlim([1 , 10]);
63
64 title('Likelihoods');
65 xlabel('x');
66 ylabel('P(x|C_i)');
67
68 p_class1 = class1_pdf ./ (class1_pdf + class2_pdf);
69 p_class2 = class2_pdf ./ (class1_pdf + class2_pdf);
70
71 figure;
72 hold on
73
74 plot(estimate_range , p_class1);
75 plot(estimate_range , p_class2);
76
77 title('Posteriors');
78 xlabel('x');
79 ylabel('P(x|C_i)');
80
81 hold off;
82

```




Figure 3: Likelihoods




Figure 4: Posteriors

Question 3.1

With the given dataset, we want to find a way to classify the two classes, this can be given by the posterior $P(C_i|x)$. To do so we first need to estimate the prior $P(C_i)$ and $p(x|C)$.

This will allow us to estimate the proportion of data points for a given class i .
 $p(x|c)$ can easily be found by using the matlab function `mvnpdf`.
 Finding the posteriors for each class yields the below histogram.




Figure 5: Posteriors

Question 3.2

Question 3.5

The computed KL values are listed in the table below

M and H1	2.6898
M and K1	0.2741
M and K2	0.28186

There was an issue encountered while finding these variables, it was caused by the 0 values in some of the bins of the histogram estimator, this caused the division to produce Infinity values. This was fixed by replacing the infinity values with 0.




Figure 6: Q5

Below is the code used to calculate the KL function, see the function called KL at the bottom of the script.

```

1  % Q5
2
3  x = [randn(30, 1); 5 + randn(30, 1)];
4
5  subplot(2, 2, 1);
6  hold on;
7  hist(x, 20);
8  title('Histogram with 20 bins');
9  xlabel('X values');
10 ylabel('Probability');
11 hold off;
12
13 % Demo the results
14 subplot(2, 2, 2);
15 yyaxis left;
16 hist(x, 20);
17 yyaxis right;
18
19 % Generate 100 random datapoints between that covers the range of
    data in x
20 x_points = min(x):((max(x)-min(x))/99):max(x);
21

```



```

22 % Generate the histogram bin counts
23 [dist, edges] = histcounts(x, 20);
24 N = sum(dist);
25 x0 = edges(1);
26 h = edges(2) - edges(1);
27
28 data = zeros(1, 100);
29
30 % Histogram estimator
31 for i = 1:100
32     bin = ceil((x_points(i) - x0) / h);
33     x_in_bin = dist(bin);
34
35     data(i) = x_in_bin / (N * h);
36 end
37
38
39 % Create the kernel density estimators
40
41 % Default kernel width
42 [K1, k1x, bw1] = ksdensity(x, x_points);
43
44 % Half of the default kernel width
45 [K2, k2x, bw2] = ksdensity(x, x_points, 'width', bw1/2);
46
47 hold on;
48 plot(k1x, K1, 'r');
49 plot(k2x, K2, 'g');
50
51 title('K1 and K2 kernel densities');
52 legend('Data', 'K1', 'K2');
53 hold off;
54
55 % Calculate the Guassian mixed model
56 mixed = K1/2 + K2/2;
57
58 subplot(2, 2, 3);
59 hold on;
60 yyaxis left;
61 hist(x, 20);
62 yyaxis right;
63 plot(k1x, mixed, 'b');
64
65 title('Mixed Model');
66 legend('Data', 'Mixed model');

```

```

67 hold off;
68
69 subplot(2, 2, 4);
70 hold on;
71 hist(x, 20);
72 scatter(x_points, zeros(1, 100), 'r');
73
74 title('Test points');
75 legend('Data', 'Test points');
76 hold off;
77
78 % Do the calculations
79 KL(mixed, data)
80 KL(mixed, K1)
81 KL(mixed, K2)
82
83 %
84 % Calculate the KL Divergence
85 %
86 function result = KL(p, q)
87     result = zeros(size(p));
88
89     valid = p > 0 & q > 0;
90
91     result1 = sum(p(valid) .* log(p(valid) ./ q(valid)));
92     result2 = sum(q(valid) .* log(q(valid) ./ p(valid)));
93
94     result(valid) = result1 + result2;
95
96     result = mode(result);
97 end

```