

Data Base System Implementation

COP-6726

Submitted by:
Naman Arora
UFID: 3979-0439
Nikunj Sarda
UFID: 9360-6581

Introduction:

This document is intended to present the outcomes and the process of the completed work for the Project 3. The relational operations for DB file implementation have been successfully materialized and tested. The repository for all the work is present [here](#).

Source File Hierarchy:

The directories are arranged in a flat manner with exception of a tpch-dbgen project directory. The tpch-dbgen is the git repository for the TPCB sub program. Please make sure the *.tbl files are present BEFORE test is run.

Note that we need flex version to higher than 2.6 to run the above implementation to not get below error:

```
"lexer_func.l:67:1: error: 'yyfunclineneno' undeclared (first use in this function); did you mean 'yyfuncleng'?"
```

while running the make to generate test.out file. If such an error arises, however, please uncomment line 16 in 'lexer_func.l'.

The compilation process:

The compilation process is accomplished by a recursive call to Makefiles in each subdirectory by the Makefile in the src/ directory.

The provided NamanArora_NikunjSarda_p3.zip has one sub-directory, src/.

```
$> unzip NamanArora_NikunjSarda_p3.zip
```

```
$> cd proj3
```

Now to build:

```
$> make
```

The above command will create all the binaries, test.out, gtest.out, test_heap.out and test_bigq.out along with tpch-dbgen/dbgen.

To generate tpch-dbgen files (tpch-dbgen/ sub-dir is always compiled with all of the above targets)

```
$> cd tpch-dbgen/
```

```
$> ./dbgen <options> -s <size>
```

```
$> cp *.tbl ..
```

```
$> sync
```

To generate heap database files required for running the test driver,

```
$> make heap_gen.out
```

```
$> ./create_heap_file.sh # All the heap database files will be available
```

To generate binary for creating sorted database files:

```
$> make sorted_test_file.out # This creates the binary driver for project 2 milestone 2
```

To run the associated Gtests for the current submission:

```
$> make gtest.out
```

```
$> ./gtest.out
```

To clean the repository, excluding *.bin and *.tbl files,

```
$> make clean
```

To clean the repository, including *.bin and *.tbl files

```
$> make distclean
```

Change log:

- ➔ Added group_by.h and group_by.cc as the implementation of the GroupBy operation
- ➔ Added join.h and join.cc as the implementation of the Join operation
- ➔ Added rem_dup.h and rem_dup.cc as the implementation of the remove Duplicate operation
- ➔ Added sum.h and sum.cc as the implementation of the sum operation
- ➔ Added sel_file.h and sel_file.cc as the implementation to select file
- ➔ Added sel_pipe.h and sel_pipe.cc as the implementation to select pipe
- ➔ Added write_out.h and write_out.cc as the implementation of the writing a file
- ➔ Added project.h and project.cc as the implementation to select project
- ➔ Added an overloaded constructor for class OrderMaker which generates instances that help in sorting based on a single attribute.
- ➔ Added a destructor for BigQ that waits for the worker thread to join back.
- ➔ Added a Record :: deserialize function which returns the record in form of a character array.

group_by.cc:

- ➔ void mk_grps(struct grp_args *arg, vector<Record *> &grps, vector<struct grp_args *> &args): This functions receives vectors in form of pointers pointing to constant memory location so that vectors are not copied across functions
- ➔ void push_results(struct grp_args *arg, vector<struct grp_args *> &args): Put the results in the out pipe
- ➔ void *grp_thr(void *a): Function to create a thread for the group
- ➔ GroupBy :: GroupBy(): Constructor of the class to initialize initial argument
- ➔ GroupBy :: ~GroupBy(): Destructor of the class to destroy class variable
- ➔ void GroupBy :: Run(Pipe *in_pipe, Pipe *out_pipe, OrderMaker *order, Function *func): Public function called from outside the class to start the GroupBy operation
- ➔ void GroupBy :: WaitUntilDone(): Function to pause future threads till current thread is completed
- ➔ void GroupBy :: Use_n_Pages(int n): Function to decide number of pages to be used

join.cc:

- ➔ void sort_merge(struct join_args *arg): Function to merge 2 given records in sorted manner
- ➔ void nested_loop(struct join_args *arg): Function to do record join using nested loop

- ➔ void *join_thr(void *a): Function to create a thread for the Join
- ➔ Join :: Join(): Constructor of the class to initialize initial argument
- ➔ Join :: ~Join(): Destructor of the class to destroy class variable
- ➔ void Join :: Run(Pipe *in_pipeL, Pipe *in_pipeR, Pipe *out_pipe, CNF *cnf, Record *literal, Schema *schL, Schema *schR): Public function called from outside the class to start the Join operation
- ➔ void Join :: WaitUntilDone(): Function to pause future threads till current thread is completed
- ➔ void Join :: Use_n_Pages(int n): Function to decide number of pages to be used

project.cc:

- ➔ void *project_thr(void *a): Function to create a thread for the Project
- ➔ Project :: Project(): Constructor of the class to initialize initial argument
- ➔ Project :: ~Project(): Destructor of the class to destroy class variable
- ➔ void Project :: Run(Pipe *in_pipe, Pipe *out_pipe, int *keep, int atts_in, int atts_out): Public function called from outside the class to start the Project selection
- ➔ void Project :: WaitUntilDone(): Function to pause future threads till current thread is completed
- ➔ void Project :: Use_n_Pages(int n): Function to decide number of pages to be used

rem_dup.cc:

- ➔ void *dup_thr(void *a): Function to create a thread for duplicate removal
- ➔ DuplicateRemoval :: DuplicateRemoval(): Constructor of the class to initialize initial argument
- ➔ DuplicateRemoval :: ~DuplicateRemoval(): Destructor of the class to destroy class variable
- ➔ void DuplicateRemoval :: Run(Pipe *in_pipe, Pipe *out_pipe, Schema *sch): Public function called from outside the class to start the duplicate removal operation
- ➔ void DuplicateRemoval :: WaitUntilDone(): Function to pause future threads till current thread is completed
- ➔ void DuplicateRemoval :: Use_n_Pages(int n): Function to decide number of pages to be used

sel_file.cc:

- ➔ void *file_thr(void *input): Function to create a thread for file selection
- ➔ SelectFile :: SelectFile(): Constructor of the class to initialize initial argument
- ➔ SelectFile :: ~SelectFile(): Destructor of the class to destroy class variable
- ➔ void SelectFile :: Run(DBFile *dbf, Pipe *out_pipe, CNF *cnf, Record *literal): Public function called from outside the class to start the File selection
- ➔ void SelectFile :: WaitUntilDone(): Function to pause future threads till current thread is completed
- ➔ void SelectFile :: Use_n_Pages(int n): Function to decide number of pages to be used

sel_pipe.cc:

- ➔ void *pipe_thr(void *a): Function to create a thread for pipe selection
- ➔ SelectPipe :: SelectPipe(): Constructor of the class to initialize initial argument

- ➔ SelectPipe :: ~SelectPipe(): Destructor of the class to destroy class variable
- ➔ void SelectPipe :: Run(Pipe *in_pipe, Pipe *out_pipe, CNF *cnf, Record *literal): Public function called from outside the class to start the Pipe selection
- ➔ void SelectPipe :: WaitUntilDone(): Function to pause future threads till current thread is completed
- ➔ void SelectPipe :: Use_n_Pages(int n): Function to decide number of pages to be used

sum.cc:

- ➔ void get_sum_rec(struct sum_args *arg, int *int_res, double *double_res): Function to sum the given records
- ➔ void *sum_thr(void *a): Function to create a thread for sum
- ➔ Sum :: Sum(): Constructor of the class to initialize initial argument
- ➔ Sum :: ~Sum(): Destructor of the class to destroy class variable
- ➔ void Sum :: Run(Pipe *in_pipe, Pipe *out_pipe, Function *func): Public function called from outside the class to start the Sum operation
- ➔ void Sum :: WaitUntilDone(): Function to pause future threads till current thread is completed
- ➔ void Sum :: Use_n_Pages(int n): Function to decide number of pages to be used

write_out.cc:

- ➔ void *write_thr(void *a): Function to create a thread for writing file
- ➔ WriteOut :: WriteOut(): Constructor of the class to initialize initial argument
- ➔ WriteOut :: ~WriteOut(): Destructor of the class to destroy class variable
- ➔ void WriteOut :: Run(Pipe *in_pipe, FILE *f, Schema *sch): Public function called from outside the class to start the writing file
- ➔ void WriteOut :: WaitUntilDone(): Function to pause future threads till current thread is completed
- ➔ void WriteOut :: Use_n_Pages(int n): Function to decide number of pages to be used

Outputs:

output1.txt

1 of 3

```
1
2 ** IMPORTANT: MAKE SURE THE INFORMATION BELOW IS CORRECT **
3 catalog location:      catalog
4 tpch files dir:       ./
5 heap files dir:       ./
6
7
8 ps_partkey: [6333], ps_suppkey: [6334], ps_availqty: [3711], ps_supplycost: [1.010000], ps_comment: [s use slyly. fluffily express requests wake carefully ironic packages]
9 ps_partkey: [9097], ps_suppkey: [4098], ps_availqty: [3012], ps_supplycost: [1.010000], ps_comment: [s the bold pinto beans cajole carefully after the slyly unusual instructions. slyly special packages above t
10 ps_partkey: [20468], ps_suppkey: [469], ps_availqty: [6884], ps_supplycost: [1.000000], ps_comment: [furiously among the slyly ironic instructions. final, unusual packages wake slyly. final accounts cajole. de
11 ps_partkey: [27115], ps_suppkey: [9618], ps_availqty: [7966], ps_supplycost: [1.020000], ps_comment: [e regular, ironic dugouts. slyly special requests cajole quickly across the blithely express requests. depo
12 ps_partkey: [34494], ps_suppkey: [9501], ps_availqty: [7438], ps_supplycost: [1.020000], ps_comment: [egular excuses. final, regular deposits wake. pinto beans according to th]
13 ps_partkey: [43172], ps_suppkey: [685], ps_availqty: [6600], ps_supplycost: [1.010000], ps_comment: [ites integrate blithely above the slyly regular instructions. asymptotes besides the regular, even accounts
14 ps_partkey: [43764], ps_suppkey: [1277], ps_availqty: [2344], ps_supplycost: [1.020000], ps_comment: [; furious, ironic requests nag furiously against the silent packages-- furiously pending pinto beans use bl
15 ps_partkey: [51671], ps_suppkey: [4177], ps_availqty: [3399], ps_supplycost: [1.020000], ps_comment: [iously. blithely bold requests haggle furiously. slyly final requests sleep. final, final theodolites cajol
16 ps_partkey: [60953], ps_suppkey: [954], ps_availqty: [8611], ps_supplycost: [1.010000], ps_comment: [ully even dolphins wake carefully about the slyly final pinto beans]
17 ps_partkey: [61707], ps_suppkey: [1708], ps_availqty: [3178], ps_supplycost: [1.020000], ps_comment: [ide of the unusual, regular excuses. unusual, special packages are carefully across the even theodolites: f
18 ps_partkey: [71984], ps_suppkey: [6999], ps_availqty: [6016], ps_supplycost: [1.010000], ps_comment: [eodolites are blithely across the special requests. quickly regular excuses are furiously against the slyly
19 ps_partkey: [74375], ps_suppkey: [6883], ps_availqty: [864], ps_supplycost: [1.020000], ps_comment: [lithely express asymptotes nag regular packages. special, ruthless instructions against the furiously ruthle
20 ps_partkey: [76994], ps_suppkey: [9502], ps_availqty: [9712], ps_supplycost: [1.000000], ps_comment: [l. carefully ironic platelets cajole furiously among the furiously regular asymptotes. furiously express asy
21 ps_partkey: [93653], ps_suppkey: [3654], ps_availqty: [4473], ps_supplycost: [1.020000], ps_comment: [ of the carefully final requests. bold deposits are slyly. instructions nod furiously instructions. careful
22 ps_partkey: [102497], ps_suppkey: [2498], ps_availqty: [6491], ps_supplycost: [1.000000], ps_comment: [fully final accounts. even accounts after the carefully final accounts haggle according to the blithely sp
23 ps_partkey: [122543], ps_suppkey: [5056], ps_availqty: [5753], ps_supplycost: [1.000000], ps_comment: [e the quickly ironic dependencies. slyly ironic accounts]
24 ps_partkey: [139711], ps_suppkey: [9712], ps_availqty: [4286], ps_supplycost: [1.010000], ps_comment: [ully unusual escapades sleep along the special instructions. final, bold ideas across the slyly ironic ide
25 ps_partkey: [155112], ps_suppkey: [5113], ps_availqty: [7635], ps_supplycost: [1.000000], ps_comment: [refully bold packages. special somas cajole according to the foxes. furiously even accou]
26 ps_partkey: [158093], ps_suppkey: [5639], ps_availqty: [3751], ps_supplycost: [1.000000], ps_comment: [iously unusual gifts maintain quickly according to the slyly pending deposits. quickly ]
27 ps_partkey: [193659], ps_suppkey: [6179], ps_availqty: [6606], ps_supplycost: [1.010000], ps_comment: [can haggle. quickly express packages are blithely. even requests against the silent accounts sleep special
28 ps_partkey: [193981], ps_suppkey: [3982], ps_availqty: [619], ps_supplycost: [1.010000], ps_comment: [ic accounts after the unusual, regular instructions grow carefully around the blithely unusual dependencies
29 . pending accounts along the bl]
30
31 query1 returned 21 records and took 165.078 milliseconds!
32 Calling cleanup!
33
34
35 *****
36
37 ** IMPORTANT: MAKE SURE THE INFORMATION BELOW IS CORRECT **
38 catalog location:      catalog
39 tpch files dir:       ./
40 heap files dir:       ./
41
42
43 int: [31], string: [slate seashell steel medium moccasin], double: [931.030000]
44 int: [1030], string: [orange floral olive ivory lace], double: [931.030000]
45 int: [2029], string: [midnight brown dim violet almond], double: [931.020000]
NORMAL output1.txt
text utf-8[unix] 939 words 0% 1/139 : 1 [6]trailing
[submit] 0:Makefile 1:zsh- 2:vim*
CPU:0.7%
```


output1.txt

2 of 3

```
43 int: [31], string: [slate seashell steel medium moccasin], double: [931.030000]
44 int: [1030], string: [orange floral olive ivory lace], double: [931.030000]
45 int: [2029], string: [midnight brown dim violet almond], double: [931.020000]
46 int: [3028], string: [puff slate tomato moccasin azure], double: [931.020000]
47 int: [4027], string: [white ivory moccasin coral puff], double: [931.020000]
48 int: [5026], string: [blanched blush pink light wheat], double: [931.020000]
49 int: [6025], string: [purple medium light aquamarine dark], double: [931.020000]
50 int: [7024], string: [forest rosy peach antique midnight], double: [931.020000]
51 int: [8023], string: [mint salmon moccasin blanched beige], double: [931.020000]
52 int: [9022], string: [peru misty sandy dark drab], double: [931.020000]
53 int: [10021], string: [blush steel green sienna snow], double: [931.020000]
54 int: [11020], string: [plum khaki powder beige peru], double: [931.020000]
55
56
57 query2 returned 12 records and took 46.382 milliseconds!
58 Calling cleanup!
59
60
61 *****
62
63 ** IMPORTANT: MAKE SURE THE INFORMATION BELOW IS CORRECT **
64 catalog location: catalog
65 tpch files dir: ./
66 heap files dir: ./
67
68
69 double: [92462275.000000]
70
71
72 query3 returned 1 records and took 5.967 milliseconds!
73 Calling cleanup!
74
75
76 *****
77
78 ** IMPORTANT: MAKE SURE THE INFORMATION BELOW IS CORRECT **
79 catalog location: catalog
80 tpch files dir: ./
81 heap files dir: ./
82
83
84 query4
85 double: [400420639.000000]
86 query4 returned 1 recs and took 459.078 milliseconds!
87 Calling cleanup!
88
89
90 *****
91
92 ** IMPORTANT: MAKE SURE THE INFORMATION BELOW IS CORRECT **
93 catalog location: catalog
94 tpch files dir: ./
95 heap files dir: ./
96
97
98 query5 finished..output written to file ps.w.tmp. Query took 431.503 milliseconds!
99 Calling cleanup!
100
101
102 *****
NORMAL output1.txt
```

text utf-8[unix] 939 words 73% 102/139 : 1 [6]trailing

output1.txt

3 of 3

```
80 tpch files dir: ./
81 heap files dir: ./
82
83
84 query4
85 double: [400420639.000000]
86 query4 returned 1 recs and took 459.078 milliseconds!
87 Calling cleanup!
88
89
90 *****
91
92 ** IMPORTANT: MAKE SURE THE INFORMATION BELOW IS CORRECT **
93 catalog location: catalog
94 tpch files dir: ./
95 heap files dir: ./
96
97
98 query5 finished..output written to file ps.w.tmp. Query took 431.503 milliseconds!
99 Calling cleanup!
100
101
102 *****
103
104 ** IMPORTANT: MAKE SURE THE INFORMATION BELOW IS CORRECT **
105 catalog location: catalog
106 tpch files dir: ./
107 heap files dir: ./
108
109
110 query6
111 double: [16823584.000000]
112 double: [15219447.000000]
113 double: [16536255.000000]
114 double: [14906042.000000]
115 double: [17565478.000000]
116 double: [15059477.000000]
117 double: [15561551.000000]
118 double: [15696449.000000]
119 double: [15761338.000000]
120 double: [16300618.000000]
121 double: [16597283.000000]
122 double: [16502039.000000]
123 double: [16095418.000000]
124 double: [15956879.000000]
125 double: [16284216.000000]
126 double: [15926341.000000]
127 double: [16578888.000000]
128 double: [16234868.000000]
129 double: [16836317.000000]
130 double: [15951412.000000]
131 double: [15778636.000000]
132 double: [14505101.000000]
133 double: [15140802.000000]
134 double: [16117877.000000]
135 double: [16484326.000000]
136 query6 returned sum for 25 groups (expected 25 groups) and took 995.348 milliseconds!
137 Calling cleanup!
138
139
```

NORMAL output1.txt

text utf-8[unix] 939 words 100% 139/139 : 1 [6]trailing

[submit] 0:Makefile 1:zsh- 2:vim*

CPU:1.1%

GTest

```
[naman@0xb1ad3] - (~/.git/database-from-scratch/src/submit) - [git://proj3 x] -  
> ./gtest.out  
  
** IMPORTANT: MAKE SURE THE INFORMATION BELOW IS CORRECT **  
catalog location:      catalog  
tpch files dir:        ./  
heap files dir:        ./  
  
[=====] Running 4 tests from 4 test cases.  
[-----] Global test environment set-up.  
[-----] 1 test from DUPLICATE  
[ RUN      ] DUPLICATE.duplicate  
[          OK ] DUPLICATE.duplicate (197 ms)  
[-----] 1 test from DUPLICATE (197 ms total)  
  
[-----] 1 test from SUMTEST  
[ RUN      ] SUMTEST.sum  
double: [-7021.000000]  
[          OK ] SUMTEST.sum (5 ms)  
[-----] 1 test from SUMTEST (5 ms total)  
  
[-----] 1 test from JOINTEST  
[ RUN      ] JOINTEST.join  
[          OK ] JOINTEST.join (5796 ms)  
[-----] 1 test from JOINTEST (5796 ms total)  
  
[-----] 1 test from SELECTFILETEST  
[ RUN      ] SELECTFILETEST.selectfile  
[          OK ] SELECTFILETEST.selectfile (8 ms)  
[-----] 1 test from SELECTFILETEST (8 ms total)  
  
[-----] Global test environment tear-down  
[=====] 4 tests from 4 test cases ran. (6006 ms total)  
[ PASSED   ] 4 tests.  
Calling cleanup!
```